

**FCC
Electromagnetic Compatibility
Test Report**

For

**3M™ Model 701
Digital Library Assistant**

**Safety and Security Systems Division
Library Systems
St. Paul, MN 55144-1000**

4 October, 2000

Report Number F0800002

Prepared By:

CR-SEMS Product Safety
Building 76-1-01
410 East Fillmore Avenue
St. Paul, Minnesota 55144-1000

3M Product Safety 3M Center Building 76-1-01 St. Paul MN 55144-1000	Phone: 651 778 6279 Fax: 651 778 6252 E-mail: rdkuhn1@mmm.com	3 EMC Laboratory
--	--	-------------------------------

CERTIFICATE OF COMPLIANCE

USA STANDARD 47 CODE OF FEDERAL REGULATIONS

Radiated Emissions (FCC Part 15, Subpart B, Class A)
Radiated Emissions (FCC Part 15, Subpart C)

MANUFACTURER'S NAME:	3M Company Safety and Security Systems Division Library Systems St. Paul, MN 55144-1000
NAME OF EQUIPMENT:	Digital Library Assistant
MODEL NUMBER:	701
SERIAL NUMBER	Prototype - Sample 2
TEST REPORT NUMBER:	F0800002
DATE:	4 October, 2000

As the responsible EMC Project Engineer, I hereby declare that the equipment tested, as specified in the test report, at the 3M Product Safety EMC Laboratory is in compliance with 47 CFR, Part 15, Subpart B and Subpart C. It is the manufacturer's responsibility to assure that additional production units of this model are manufactured with identical electrical and mechanical characteristics.

Roger D. Kuhn
EMC Test Engineer

3	Model 701 Digital Library Assistant	Report: F0800002	3
EMC Laboratory	Product Safety	4 October, 2000	Page 3 of 31

TABLE OF CONTENTS

Title Page

Certificate of Compliance

Table of Contents

1.0 Test Summary

2.0 Introduction

2.1 Scope

2.2 EUT Description and Operation

2.3 Block Diagram

2.4 Part List

2.5 Modifications to EUT

2.6 Measurement Uncertainty

3.0 Applicable Document

4.0 Radiated Emissions

4.1 Frequency Stability

4.1.1 Test Procedure

4.1.2 Test Criteria

4.1.3 Test Results

4.2 Emissions Bandwidth

4.2.1 Test Procedure

4.2.2 Test Criteria

4.2.3 Test Results

4.3 Spurious Emissions (12.5 to 30 MHz.)

4.3.1 Test Procedure

4.3.2 Test Criteria

4.3.3 Test Results

4.4 Radiated Emissions (30 to 40000 MHz.)

4.4.1 Test Procedure

4.4.2 Test Criteria

4.4.3 Test Results

5.0 List of Test Equipment

6.0 Labeling Information

Appendix A Emissions Bandwidth Test Data

Appendix B Spurious Emissions Test Data

Appendix C Radiated Emissions Test Data

Appendix D Test Photographs

3	Model 701 Digital Library Assistant	Report: F0800002	3
EMC Laboratory	Product Safety	4 October, 2000	Page 4 of 31

1.0 TEST SUMMARY

Test Report Number: F0800002

Requester: John E. Nelson

Company: 3M
Safety and Security Systems Division
Library Systems
Building 209
St. Paul, MN 55144

Telephone Number: 651 - 736-5160

Test Dates: 28 September, 2000 through 4 October, 2000

Equipment Under Test: Model 701 Digital Library Assistant

Date Of Receipt: 27 September, 2000

Test Environment: Temperature: 20 to 30 degrees C
Relative Humidity: 30 to 70 % RH

Test Results: Passed the following tests:
Radiated Emissions: FCC Part 15 Subpart B Class A;
Radiated Emissions: FCC Part 15 Subpart C;

Modifications: Modifications were required (See Paragraph 2.5)

Test Location: 3M Product Safety EMC Laboratory
Building 76
410 Fillmore Ave.
St. Paul, MN 55144-1000

3	Model 701 Digital Library Assistant	Report: F0800002	3
EMC Laboratory	Product Safety	4 October, 2000	Page 5 of 31

2.0 INTRODUCTION

2.1 Scope

This report contains results describing the conformance of the Equipment Under Test (EUT) to FCC Part 15, Subpart B, "Class A" rules for unintentional radiators and FCC Part 15, Subpart C rules for intentional radiators.

This report is the confidential property of the client and applies only to the specific item tested under the stated test conditions. It is the manufacturer's responsibility to assure that additional production units of this model are manufactured with identical electrical and mechanical characteristics. This report shall not be reproduced without the written approval of the testing laboratory. When approval has been granted, the report shall be reproduced in its entirety.

The appropriate testing standards and references that were used are contained in Section 3.0. Worst case test data, test configuration, and photographs (worst case configuration) are provided in the Appendices. Equipment and documentation labeling information is contained in Section 7.0.

Subsequent tests are necessary from time to time on equipment taken at random from production. Re-testing of the EUT is also required when the EMC profile has been changed or is suspected of being changed.

The 3M Product Safety EMC Laboratory is recognized under the United States Department of Commerce National Institute of Standards and Technology's National Voluntary Laboratory Program (NVLAP) for satisfactory compliance with criteria established in Title 15, Part 285 Code of Federal Regulations. These criteria encompass the requirements of ISO/IEC Guide 25 and the relevant requirements of ISO 9002 (ANSI/ASQ Q92-1987) as suppliers of test results. Accreditation by the National Voluntary Laboratory Accreditation Program is awarded for specific services, listed on the Scope of Accreditation for: Electromagnetic Compatibility and Telecommunications, FCC, under Lab Code 200033. A complete copy of the Scope of Accreditation is available upon request. The FCC Site Registration Number is 93334.

The NVLAP accreditation or this test report does not in any way constitute or imply product certification, approval, or endorsement by NVLAP, NIST, or any agency of the U.S. Government.

3	Model 701 Digital Library Assistant	Report: F0800002	3
EMC Laboratory	Product Safety	4 October, 2000	Page 6 of 31

2.2 EUT Description and Operation

The Equipment Under Test (EUT) is the 3M™ Model 701 Digital Library Assistant, Serial Number Prototype - Sample 2.

The 3M™ Model 701 Digital Library Assistant (DLA) is designed and tested for use in processing 3M™ Brand Digital Identification D1Tags. These tags are used to identify library items, like books and videotapes, for the library users. The DLA:

1. Reads 3M Brand Digital Identification D1 Tags placed in items that are arranged on a shelf or on a desk, and
2. Processes identification codes that can, for example, be compared with customer-generated lists to determine shelf order, aid in reshelving items, and identify items the library is interested in locating.

The product has not been tested or proven safe for other uses.


The reader has a transmit frequency of 13.561 MHz. And a power output level of 1.000 watts (30 dBm).

The EUT has an integral antenna with an area of 22.69 square inches (0.015 square meters). The antenna located in the front portion of the handheld unit of the EUT and is connected to the reader via a coax cable employing SMC connectors.

All tests were made using a battery input of 7.2 volts DC.

3	Model 701 Digital Library Assistant	Report: F0800002	3
EMC Laboratory	Product Safety	4 October, 2000	Page 7 of 31

2.3 Block Diagram



3	Model 701 Digital Library Assistant	Report: F0800002	3
EMC Laboratory	Product Safety	4 October, 2000	Page 8 of 31

2.4 Parts List

<u>Description</u>	<u>Manufacturer</u>	<u>Model / Type</u>	<u>Remark</u>
Handheld Computer (Palm)	TRG Products	TRGPro	
PWR PCD	3M	78-8123-1743-2	
PIC PCB	3M	78-8123-1613-7	
RFID Reader	Texas Instruments	Commander 320	FCC ID A92COM320
Antenna	3M	78-8123-1660-8	

3	Model 701 Digital Library Assistant	Report: F0800002	3
EMC Laboratory	Product Safety	4 October, 2000	Page 9 of 31

2.5 Modifications to the EUT

The following modifications of the EUT were necessary to meet the test standards:

<u>Equipment</u>	<u>Modifications</u>	<u>Where</u>	<u>Material</u>	<u>Turns</u>
Reader Data Cable (RS232)	Common Mode Choke	In Handheld Handle	Steward 28B2025-0A0 (or equivalent)	1 Turns
Coax	Common Mode Choke	In Handheld Handle	Steward 28B0392-0A0 (or Equivalent)	1 Turns
TI Reader	Grounded RS-232 Connector	Grounded RS 232 connector screw to Board Stand-off	Shortest path using ground pad	

3	Model 701 Digital Library Assistant	Report: F0800002	3
EMC Laboratory	Product Safety	4 October, 2000	Page 10 of 31

2.6 Measurement Uncertainty

The data and test results referenced in this report are true and accurate. However, there may be deviations within the calibration limits of the test equipment and facilities that can account for a nominal measurement deviation of ± 2 dB. Furthermore, EUT component and manufacturing process variables may result in additional deviation. The calculated confidence level is 95 %.

3.0 APPLICABLE DOCUMENTS

The following documents were used as reference for the limits and test procedures specified herein.

CFR 47	Part 15 Radio Frequency Devices	1999
ANSI C63.4	American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 KHz to 40 GHz.	1992
CISPR 16-1	Specification for radio disturbance and immunity measuring apparatus and methods Part 1: Radio disturbance and immunity measuring apparatus	1993
CISPR 16-2	Specification for radio disturbance and immunity measuring apparatus and methods Part 2: Methods of measurements of disturbances and immunity	1996

3	Model 701 Digital Library Assistant	Report: F0800002	3
EMC Laboratory	Product Safety	4 October, 2000	Page 11 of 31

4.0 RADIATED EMISSIONS

Radiated emissions testing was performed in accordance with ANSI C63.4. The limits are prescribed in FCC Part 15, Subpart B and in FCC Part 15, Subpart C.

4.1 Frequency Stability

The Frequency Stability testing was performed in accordance with ANSI C63.4 and FCC Part 15 to insure that the intentional radiator frequency stability was within the allowable limits for input power and temperature variations.

4.1.1 Test Procedure

The Frequency Stability was measured using the radiated signals from the EUT so that the measurement equipment would not load the radio frequency circuits. An EMI receiver was used for the frequency stability measurements. The Reader was put into a continuous output mode through instructions from the host computer (test mode of operation). 1) The frequency was measured while the input AC power to the External Power Supply was varied over the required input voltage range. 2) The frequency was also measured while the ambient air temperature was varied over the required ambient temperature range (at startup, 2 minutes, 5 minutes, and 10 minutes).

4.1.2 Test Criteria

The FCC Part 15, Subpart C for Frequency Stability Limits versus Supply Voltage is given below.

<u>Carrier Frequency</u>	<u>Voltage Range</u>	<u>Max.Frequency Change</u>
<u>(MHz)</u>	<u>(% of Nominal Supply)</u>	<u>(%)</u>
13.56	85 % to 115 %, (102 to 138 V RMS)	+/- 0.01 %

The FCC Part 15, Subpart C for Frequency Stability Limits versus Temperature is given below.

<u>Carrier Frequency</u>	<u>Temperature Range</u>	<u>Max. Frequency Change</u>
<u>(MHz)</u>	<u>(degrees C)</u>	<u>(%)</u>
13.56	-20 to +50	+/- 0.01 %

3	Model 701 Digital Library Assistant	Report: F0800002	3
EMC Laboratory	Product Safety	4 October, 2000	Page 12 of 31

5.1.3 Test Results

The EUT met the FCC Part 15, Subpart C Frequency Stability requirement.

Carrier Frequency Stability versus Supply Voltage

<u>Carrier Frequency</u> <u>(MHz)</u>	<u>Lowest Frequency</u> <u>(MHz)</u>	<u>Highest Frequency</u> <u>(MHz)</u>	<u>Frequency Change</u> <u>(%)</u>
13.56036	13.56009	13.56050	+/- 0.003 %

Carrier Frequency Stability versus Temperature

<u>Carrier Frequency</u> <u>(MHz)</u>	<u>Lowest Frequency</u> <u>(MHz)</u>	<u>Highest Frequency</u> <u>(MHz)</u>	<u>Frequency Change</u> <u>(%)</u>
13.56036	13.56014	13.56036	+/- 0.0016 %

3	Model 701 Digital Library Assistant	Report: F0800002	3
EMC Laboratory	Product Safety	4 October, 2000	Page 13 of 31

4.2 Emission Bandwidth

The EUT was placed in an anechoic chamber and the Emission Bandwidth testing was preformed in accordance with ANSI C63.4 and FCC Part 15, Paragraph 15.225. The Emission Bandwidth measurements were made to determine the intentional radiator frequency and determine the level of electromagnetic energy radiated at that frequency and at the band edges from the EUT.

4.2.1 Test Procedure

A measurement antenna (loop) was positioned at a distance of 5 meters (to insure far field measurements) from the center of the EUT. An EMI receiver was used for the emissions measurements. Initial sweep measurements were taken with the receiver in continuous frequency overview mode utilizing peak level signal detection. The intentional radiator frequency and band edge frequencies utilizing quasi-peak detection were then maximized. Maximizing a frequency involves finding the angle of the highest emission levels by rotating the EUT 360 degrees (sampling at least every 4 degrees). Then the antenna, which was fixed at 1-meter height, was rotated until the highest emissions levels found. Measurement results were automatically calculated via software running the EMI receiver. The final quasi-peak measurements recorded were determined by the following formula:

Result (dB μ V/m) = receiver level (μ V) + antenna factor (dB/m) + cable loss (dB) - preamp gain (dB) + lineal conversion (dB).

4.2.2 Test Criteria

The FCC Part 15 Subpart C, Paragraph 15.225 Carrier Frequency Limits are given below.

Lower Band Edge	Upper Band Edge
<u>(MHz)</u>	<u>(MHz)</u>
13.553	13.567

The FCC Part 15, Subpart C radiated limits are given below.

Frequency	Distance	Field Strength
<u>(MHz)</u>	<u>(m)</u>	<u>(dB μV/m)</u>
1.705 to 30.00	10	48.62
13.553 to 13.567	10	99.08

Note: A 40 dB/decade extrapolation factor was use per 15.31.

3	Model 701 Digital Library Assistant	Report: F0800002	3
EMC Laboratory	Product Safety	4 October, 2000	Page 14 of 31

4.2.3 Test Results

The EUT met the FCC Part 15, Subpart C Emission Bandwidth requirements. The intentional radiator frequency was within the allowed band and all maximized quasi-peak measurements for the EUT were below the quasi-peak limits. The test scan is shown in Appendix B.

Frequency (MHz)	Level (dBµV/m)	Limit (dBµV/m)	Passing Margin (dB)	Turntable (degrees)	Antenna Orientation/Angle (Polarity/degrees)
13.561 ¹	66.7	99.08	32.38	80	V / X+35
13.553 ²	36.8	48.62	11.82	80	V / X+35
13.567 ²	35.3	48.62	13.32	80	V / X+35

1 - Intentional Radiator Frequency

2 - Band edges measured with a receiver bandwidth setting of 1 KHz. Per ANSI C63.4 Paragraph 13.1.7.

3	Model 701 Digital Library Assistant	Report: F0800002	3
EMC Laboratory	Product Safety	4 October, 2000	Page 15 of 31

4.3 Spurious Emissions (12.5 to 30 MHz.)

The EUT was placed in an anechoic chamber and the Spurious Emissions testing was performed in accordance with ANSI C63.4 and FCC Part 15, Subpart C. The Spurious Emission measurements were made to determine the level of electromagnetic energy radiated from the EUT.

4.3.1 Test Procedure

A measurement antenna (loop) was positioned at a distance of 5 meters (to insure far field measurements) from the center of the EUT. An EMI receiver was used for the emissions measurements. Initial sweep measurements were taken with the receiver in continuous frequency overview mode utilizing peak level signal detection. Acceptance analysis of these sweeps was used to determine which discrete frequencies, other than the intentional radiator frequency and band edge frequencies, were to be maximized. Maximizing a frequency involves finding the angle of the highest emission levels by rotating the EUT 360 degrees (sampling at least every 4 degrees). Then the antenna, which was fixed at 1-meter height, was rotated until the highest emissions levels found. Final measurements were taken utilizing quasi-peak detection. Measurement results were automatically calculated via software running the EMI receiver. The final measurements recorded were determined by the following formula:

Result (dBμV/m) = receiver level (μV) + antenna factor (dB/m) + cable loss (dB) - preamp gain (dB) + lineal conversion (dB).

4.2.2 Test Criteria

The FCC Part 15, Subpart C radiated limits are given below.

Frequency (MHz)	Distance (m)	Field Strength (dB μV/m)
1.705 to 30.00	10	48.62
13.553 to 13.567	10	99.08

Note: A 40 dB/decade extrapolation factor was use per 15.31.

3	Model 701 Digital Library Assistant	Report: F0800002	3
EMC Laboratory	Product Safety	4 October, 2000	Page 16 of 31

4.3.3 Test Results

The EUT met the FCC Part 15, Subpart C Spurious Emissions (12.5 to 30 MHz.) requirements. All maximized quasi-peak measurements for the EUT were below the quasi-peak limits. Test data is shown in Appendix C. The worst-case quasi-peak emission was as follows:

Frequency (MHz)	Level (dBμV/m)	Limit (dBμV/m)	Passing Margin (dB)	Turntable (degrees)	Antenna Orientation/Angle (Polarity/degrees)
13.5715	48.3	48.62	0.32	80	V / X+35

3	Model 701 Digital Library Assistant	Report: F0800002	3
EMC Laboratory	Product Safety	4 October, 2000	Page 17 of 31

4.4 Radiated Emissions (30 to 40000 MHz)

The EUT was placed in an anechoic chamber and the Spurious Emissions testing was preformed in accordance with ANSI C63.4, FCC Part 15, Subpart B "Class A", and FCC Part 15, Subpart C. The Radiated Emission measurements were made to determine the level of electromagnetic energy radiated from the EUT.

4.4.1 Test Procedure

A measurement antenna was positioned at a distance of 3 meters from the center of the EUT. An EMI receiver was used for the emissions measurements in the range of 30 MHz to 2000 MHz (the upper limit of measurement is determined by Paragraph 15.33). Initial sweep measurements were taken with the receiver in continuous frequency overview mode utilizing peak level signal detection. Acceptance analysis of these sweeps was made to determine which discrete frequencies were to be maximized. Maximizing a frequency involves finding the angle of the highest emission levels by rotating the EUT 360 degrees (sampling at least every 4 degrees) and varying antenna height between 1 and 4 meters at the angle of highest emissions levels found. Final measurements were taken utilizing quasi-peak detection (peak and average detectors were used above 1000 MHz). Measurement results were automatically calculated via software running the EMI receiver. The final measurements recorded were determined by the following formula:

Result (dB μ V/m) = receiver level (μ V) + antenna factor (dB/m) + cable loss (dB) - preamp gain (dB) + lineal conversion (dB).

4.4.2 Test Criteria

The FCC Part 15, Subpart C radiated limits are given below.

Frequency (MHz)	Distance (m)	Field Strength (dB μ V/m)
30 to 88	10	29.54
88 to 216	10	33.06
216 to 960	10	35.56
960 to 40000	10	43.52

3	Model 701 Digital Library Assistant	Report: F0800002	3
EMC Laboratory	Product Safety	4 October, 2000	Page 18 of 31

The FCC Part 15, Subpart B, "Class A" radiated limits are given below. The lower limit shall apply at the transition frequency.

Frequency (MHz)	Distance (m)	Field Strength (dB μ V/m)
30 to 88	10	39.08
88 to 216	10	43.52
216 to 960	10	46.44
960 to 1000	10	49.54
1000 to 40000	3	59.5 and 79.5*

* Per 15.35(B)

4.4.3 Test Results

The EUT met the FCC Part 15, Subpart C and the FCC Part 15, Subpart B, "Class A" Radiated Emissions (30 to 40000MHz.) requirements. All maximized quasi-peak measurements for the EUT were below the quasi-peak limits. Test data is shown in Appendix D. The worst-case quasi-peak emission was as follows:

Frequency (MHz)	Level (dB μ V/m)	Limit (dB μ V/m)	Passing Margin (dB)	Turntable (degrees)	Antenna (Meters/Polarity)
338.98	34.3	35.56 ¹	1.26	285	1.0/H
87.03	26.6	39.08	12.46	355	1.0/V

1 - This is a harmonic of the intentional radiator, therefore the lower limit level (FCC Part 15 Subpart C) is shown.

3	Model 701 Digital Library Assistant	Report: F0800002	3
EMC Laboratory	Product Safety	4 October, 2000	Page 19 of 31

5.0 LIST OF TEST EQUIPMENT

The following test equipment was used to perform the indicated tests. All of the test equipment was calibrated by an accredited calibration laboratory or by the manufacturer. All calibration intervals are one year. All equipment calibrations, test procedures, and the test facility are traceable to the standards of the National Institute of Standards and Technology (NIST). The test facility site attenuation verification results fall within the normalized site attenuation (NSA) criteria for open area test sites using volumetric measurements.

CONDUCTED EMISSIONS

EMCO LISN, Model 3825-2, Serial No. 1039 (cal due date: 08 May 01)
Solar High Pass Filter, Model 8131 - 5.0 (cal due date: 12 Mar 01)
HP RF Limiter, Model 11867A, Serial No. 01211 (cal due date: 12 Mar 01)
Rohde & Schwarz EMI Receiver, Model ESBI 52, S/N 835387/003 (cal due date: 04 May 01)
Rohde & Schwarz EMI Receiver Display, Serial No. 835518/001 (cal due date: 04 May 01)
Rohde & Schwarz ES-K1, ES-K2, & ES-K12 EMI Software, Version 1.50

Frequency Stability

Advantest Spectrum Analyzer, Model R3272A, Serial No. J00233 (cal due date: 28 July 00)
Thermotron Environmental Chamber, Model SM-3SS, Serial No. 19972-S (cal due date: 17 June 00)

RADIATED EMISSIONS

ElectroMetrics Large Loop Antenna. Model ALR25M, Serial No. 603 (cal due date: 08 May 01)
EMCO Biconilog Antenna, Model 3143, Serial No. 1111 (cal due date: 08 May 01)
HP Pre-Amplifier, Model 8447D, Serial No. 2944A08064 (cal due date: 09 May 01)
HP RF Limiter, Model 11867A, Serial No. 01211 (cal due date: 12 Mar 01)
Rohde & Schwarz EMI Receiver, Model ESBI 52, S/N 835387/003 (cal due date: 04 May 01)
Rohde & Schwarz EMI Receiver Display, Serial No. 835518/001 (cal due date: 04 May 01)
Rohde & Schwarz ES-K1, ES-K2, & ES-K12 EMI Software, Version 1.50

3	Model 701 Digital Library Assistant	Report: F0800002	3
EMC Laboratory	Product Safety	4 October, 2000	Page 20 of 31

TEST FACILITY

Lindgren Semi-Anechoic Chamber, Model 11867A, serial No. 01211 (verification due date: 28 Apr 01)

The radiated and conducted emission measurements were performed in our Anechoic Chamber located at 3M Building 76, 410 Fillmore Street, St. Paul, MN. Details concerning the site are on file with the FCC laboratory Division in Columbia Maryland.

The Facility Registration Number is 93334, 31-March - 2000.

3	Model 701 Digital Library Assistant	Report: F0800002	3
EMC Laboratory	Product Safety	4 October, 2000	Page 21 of 31

6.0 LABELING INFORMATION

The FCC (Federal Communications Commission) requires the following labeling information. Since the equipment has intentional and unintentional radiators, it must be labeled as a digital device and as an intentional radiator.

Labels on the Product

The following statement shall be placed in a conspicuous location on the device:

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

FCC ID: _____

Labels in the Manuals

The following statement shall be placed in a prominent location in the text of the user manual:

NOTE: This equipment has been tested and found to comply with the limits for a Class A digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide a reasonable protection against harmful interference when the equipment is operated in a commercial environment. This equipment generates, uses, and can radiate radio frequency energy and, if not installed and used in accordance with the instruction manual, may cause harmful interference to radio communications. Operation of this equipment in a residential area is likely to cause harmful interference in which case the user will be required to correct the interference at his own expense.

FCC ID: _____


NO MODIFICATIONS. Modifications to this device shall not be made without the written consent of 3M, Incorporated. Unauthorized modifications may void the authority granted under Federal Communications Commission Rules permitting the operation of this device.

3	Model 701 Digital Library Assistant	Report: F0800002	3
EMC Laboratory	Product Safety	4 October, 2000	Page 22 of 31

Appendix A

Emission Bandwidth

[dB μ V/m]



MES	701	10/3	sc1	x	Bandwidth Sweep - Hold MaxPeak
MES	701	10/3	sc2	x	Bandwidth Scan - QP 9 KHz RBW
MES	701	10/3	sc3	x	Bandwidth Scan - QP 1 KHz RBW
LIM	FCC	12.5-30	MHz		

3	Model 701 Digital Library Assistant	Report: F0800002	3
EMC Laboratory	Product Safety	4 October, 2000	Page 24 of 31


Appendix B

Spurious Emissions (12.5 to 30 MHz.)

3
EMC Lab

Date: _____

Level [dB μ V/m]



MES 701 10/3 sc4 x Spur. Emissions - Hold MaxPeak
LIM FCC 12.5-30 MHz

3	Model 701 Digital Library Assistant	Report: F0800002	3
EMC Laboratory	Product Safety	4 October, 2000	Page 27 of 31

Appendix C

Radiated Emissions

RADIATED EMISSIONS

SHEET 1 OF 1

TEST REPORT # F0800002

EUT MODEL # 701

EUT SERIAL # Prototype - Sample 2

DESCRIPTION Digital Library Assistant

FREQ. (MHz)	MAXIMIZED QP SIGNAL		LIMIT LINE (dBμV/m)	PASSING MARGIN (dB)	MAXIMIZED POSITION		REMARKS
	H/V	(dBμV/m)*			TURNTABLE (°)	ANTENNA (M)	
40.658	V	24.8	29.54	4.74	10	1.0	Transmitter Harmonic
87.030	V	26.6	39.08	12.46	355	1.0	
87.030	H	21.4	39.08	17.68	90	2.0	
108.458	V	21.7	33.06	11.36	0	1.0	Transmitter Harmonic
149.199	V	22.2	43.52	21.32	20	1.0	
203.384	V	23.2	33.06	9.86	200	1.0	Transmitter Harmonic
203.384	H	24.7	33.06	8.36	260	1.0	Transmitter Harmonic
207.206	V	20.6	43.52	22.92	200	1.0	
207.206	H	21.3	43.52	22.22	255	1.0	
216.945	H	22.3	35.56	13.26	250	1.1	Transmitter Harmonic
230.502	H	28.8	35.56	6.76	280	1.0	Transmitter Harmonic
244.064	H	25.4	35.56	10.16	270	1.0	Transmitter Harmonic
257.623	H	29.6	35.56	5.96	100	1.3	Transmitter Harmonic
284.744	V	26.7	35.56	8.86	220	2.0	Transmitter Harmonic
284.744	H	31.7	35.56	3.86	270	1.0	Transmitter Harmonic
311.863	H	31.4	35.56	4.16	120/285	1.0	Transmitter Harmonic
338.981	H	34.3	35.56	1.26	285	1.0	Transmitter Harmonic
366.102	V	27.7	35.56	7.86	245	1.3	Transmitter Harmonic
366.102	H	34.2	35.56	1.36	290	1.0	Transmitter Harmonic
372.990	V	26.1	46.44	20.34	0	1.6	
393.223	H	30.7	35.56	4.86	125/290	1.0	Transmitter Harmonic
414.491	V	25.5	46.44	20.94	10	1.2	
420.349	V	27.9	35.56	7.66	280	1.2	Transmitter Harmonic
422.806	V	24.9	46.44	21.54	10	1.2	


Test Engineer: _____

Date: _____

Reviewed by: _____


Date: _____

Level [dB μ V/m]



MES 701 10/4 sc2 v Vertical Sweep - Hold MaxPeak
LIM FCC CLASS-A F QP 10M
LIM FCC Subpart C F QP

Level [dB μ V/m]




MES 701 10/4 sc2 h Horizontal Sweep -Hold MaxPeak
LIM FCC CLASS-A F QP 10M
LIM FCC Subpart C F QP

3	Model 701 Digital Library Assistant	Report: F0800002	3
EMC Laboratory	Product Safety	4 October, 2000	Page 30 of 31

Appendix D

Photographs



Emissions Bandwidth/Spurious Emissions

Radiated Emissions (30 to 1000MHz)

