



深圳市沃莱特电子有限公司

Shenzhen World Elite Electronic CO.,LTD.

Room 101-1, Building 4, Xiangyu'er Industrial Park, No. 8 Longsheng Road, Longgang Community, Longgang Street, Longgang District, Shenzhen, China

D135 Antenna test report V1

DATE

2025/1/5

Main objectives of
this report:


Optimal matching

Main conclusions of
this report:

Antenna	band	material	Performance requirement
BT	2400-2480MHz	onboard	

All information contained in this report is copyrighted by Volight and should not be distributed to any third party!


Antenna end matching circuit:



BT	
Element	
E1(0402)	
E2(0402)	1nH
E3(0402)	1.2P

Antenna passive S11 parameter test:

BT





Freq (MHz)	2400	2440	2480
SWR	1.35	1.13	1.48
Log Mag	-16.36	-24.22	-14.25

Antenna passive efficiency and gain test:

BT		
Frequency (MHz)	Gain (dBi)	Efficiency (%)
2400	0.15	49.35
2410	0.23	49.71
2420	0.34	49.94
2430	0.27	50.13
2440	0.30	50.00
2450	0.33	50.06
2460	0.32	49.05
2470	0.24	48.21
2480	0.33	47.41
2490	0.21	46.74
2500	0.05	46.13

Antenna passive radiation pattern:





Antenna OTA test:

Antenna optimization and matching		
Channels	TRP	TIS
0	-0.6	-89.82
39	0.08	-90.1
78	-0.47	-90.26

Antenna position and matching picture:

