

# **FCC Test Report**

Report No.: AGC08218221101FE04

FCC ID : 2ASFYKS13NMUSBL0001

**APPLICATION PURPOSE**: Original Equipment

**PRODUCT DESIGNATION**: WIRELESS KEYBOARD DONGLE

**BRAND NAME** : MAD CATZ

**MODEL NAME** : S.T.R.I.K.E. 11 DONGLE

**APPLICANT**: MAD CATZ GLOBAL LIMITED

**DATE OF ISSUE** : Nov. 23, 2022

**STANDARD(S)** : FCC Part 15.247

**REPORT VERSION**: V1.0

Attestation of Global Compliance (Shenzhen) Co., Ltd



Page 2 of 45

# **REPORT REVISE RECORD**

Report Version	Revise Time	Issued Date	Valid Version	Notes
V1.0	/	Nov. 23, 2022	Valid	Initial Release



Page 3 of 45

# **TABLE OF CONTENTS**

1. VERIFICATION OF COMPLIANCE	5
2. GENERAL INFORMATION	ε
2.1. PRODUCT DESCRIPTION	6
2.2. TABLE OF CARRIER FREQUENCYS	6
2.3. RELATED SUBMITTAL(S)/GRANT(S)	8
2.4. TEST METHODOLOGY	8
2.5. SPECIAL ACCESSORIES	8
2.6. EQUIPMENT MODIFICATIONS	
2.7. ANTENNA REQUIREMENT	8
3. MEASUREMENT UNCERTAINTY	9
4. DESCRIPTION OF TEST MODES	10
5. SYSTEM TEST CONFIGURATION	11
5.1. CONFIGURATION OF TESTED SYSTEM	11
5.2. EQUIPMENT USED IN TESTED SYSTEM	
5.3. SUMMARY OF TEST RESULTS	11
6. TEST FACILITY	12
7. PEAK OUTPUT POWER	13
7.1. MEASUREMENT PROCEDURE	13
7.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	13
7.3. LIMITS AND MEASUREMENT RESULT	14
8. BANDWIDTH	16
8.1. MEASUREMENT PROCEDURE	16
8.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	16
8.3. LIMITS AND MEASUREMENT RESULTS	16
9. CONDUCTED SPURIOUS EMISSION	20
9.1. MEASUREMENT PROCEDURE	20
9.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	
9.3. MEASUREMENT EQUIPMENT USED	
9.4. LIMITS AND MEASUREMENT RESULT	20
10. MAXIMUM CONDUCTED OUTPUT POWER SPECTRAL DENSITY	Testing/Inspection



Page 4 of 45

10.1. MEASUREMENT PROCEDURE	27
10.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	27
10.3. MEASUREMENT EQUIPMENT USED	27
10.4. LIMITS AND MEASUREMENT RESULT	27
11. RADIATED EMISSION	29
11.1. MEASUREMENT PROCEDURE	29
11.2. TEST SETUP	30
11.3. LIMITS AND MEASUREMENT RESULT	31
11.4. TEST RESULT	31
12. LINE CONDUCTED EMISSION TEST	41
12.1. LIMITS OF LINE CONDUCTED EMISSION TEST	41
12.2. BLOCK DIAGRAM OF LINE CONDUCTED EMISSION TEST	41
12.3. PRELIMINARY PROCEDURE OF LINE CONDUCTED EMISSION TEST	42
12.4. FINAL PROCEDURE OF LINE CONDUCTED EMISSION TEST	
12.5. TEST RESULT OF LINE CONDUCTED EMISSION TEST	43
APPENDIX A: PHOTOGRAPHS OF TEST SETUP	45
APPENDIX B: PHOTOGRAPHS OF EUT	45



Page 5 of 45

# 1. VERIFICATION OF COMPLIANCE

Applicant	MAD CATZ GLOBAL LIMITED
Address	FLAT/RM 507 5/F NEW TREASURE CENTRE 10 NG FONG STREET SAN POKONG KL HONGKONG China
Manufacturer	MAD CATZ GLOBAL LIMITED
Address	FLAT/RM 507 5/F NEW TREASURE CENTRE 10 NG FONG STREET SAN POKONG KL HONGKONG China
Factory	MAD CATZ GLOBAL LIMITED
Address	FLAT/RM 507 5/F NEW TREASURE CENTRE 10 NG FONG STREET SAN PO KONG KL HONGKONG China
Product Designation	WIRELESS KEYBOARD DONGLE
Brand Name	MAD CATZ
Test Model	S.T.R.I.K.E. 11 DONGLE
Date of receipt of test item	Nov. 03, 2022
Date of test	Nov. 03, 2022 to Nov. 22, 2022
Deviation	No any deviation from the test method
Condition of Test Sample	Normal
Test Result	Pass
Report Template	AGCRT-US-BLE/RF

# We hereby certify that:

The above equipment was tested by Attestation of Global Compliance (Shenzhen) Co., Ltd. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.10 (2013) and the energy emitted by the sample EUT tested as described in this report is in compliance with radiated emission limits of FCC part 15.247.

Prepared By	Bibo zhay		
	Bibo Zhang (Project Engineer)	Nov. 23, 2022	
Reviewed By	Calin Lin		
	Calvin Liu (Reviewer)	Nov. 23, 2022	
Approved By	Max Zhang		
	Max Zhang (Authorized Officer)	Nov. 23, 2022	



Page 6 of 45

#### 2. GENERAL INFORMATION

# 2.1. PRODUCT DESCRIPTION

The EUT is designed as a "WIRELESS KEYBOARD DONGLE". It is designed by way of utilizing the GFSK technology to achieve the system operation.

A major technical description of EUT is described as following

<u> </u>	3
Operation Frequency	2.402GHz to 2.479GHz
RF Output Power	-4.642dBm (Max)
Modulation	GFSK
Number of channels	78 Channels
Antenna Designation	PCB Antenna (Comply with requirements of the FCC part 15.203)
Antenna Gain	-20.55dBi
Hardware Version	V0.01
Software Version	V0.01
Power Supply	DC 5V by PC

#### 2.2. TABLE OF CARRIER FREQUENCYS

Channels	Frequency (GHz)	Channels	Frequency (GHz)
00	2.402	39	2.441
01	2.403	40	2.442
02	2.404	41	2.443
03	2.405	42	2.444
04	2.406	43	2.445
05	2.407	44	2.446
06	2.408	45	2.447
07	2.409	46	2.448
08	2.410	47	2.449
09	2.411	48	2.450
10	2.412	49	2.451
11	2.413	50	2.452
12	2.414	51	2.453
13	2.415	52	2.454
14	2.416	53	2.455
15	2.417	54	2.456
16	2.418	55	2.457
17	2.419	56	2.458
18	2.420	57	2.459
19	2.421	58	2.460
20	2.422	59	2.461
21	2.423	60	2.462

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: http://www.agccert.com/



Page 7 of 45

22	2.424	61	2.463
23	2.425	62	2.464
24	2.426	63	2.465
25	2.427	64	2.466
26	2.428	65	2.467
27	2.429	66	2.468
28	2.430	67	2.469
29	2.431	68	2.470
30	2.432	69	2.471
31	2.433	70	2.472
32	2.434	71	2.473
33	2.435	72	2.474
34	2.436	73	2.475
35	2.437	74	2.476
36	2.438	75	2.477
37	2.439	76	2.478
38	2.440	77	2.479



Page 8 of 45

# 2.3. RELATED SUBMITTAL(S)/GRANT(S)

This submittal(s) (test report) is intended for **FCC ID: 2ASFYKS13NMUSBL0001** filing to comply with the FCC Part 15.247 requirements.

#### 2.4. TEST METHODOLOGY

Both conducted and radiated testing was performed according to the procedures in ANSI C63.10 (2013). Radiated testing was performed at an antenna to EUT distance 3 meters.

#### 2.5. SPECIAL ACCESSORIES

Refer to section 5.2.

#### 2.6. EQUIPMENT MODIFICATIONS

Not available for this EUT intended for grant.

#### 2.7. ANTENNA REQUIREMENT

This intentional radiator is designed with a permanently attached antenna of an antenna to ensure that no antenna other than that furnished by the responsible party shall be used with the device. For more information of the antenna, please refer to the APPENDIX B: PHOTOGRAPHS OF EUT.



Page 9 of 45

# 3. MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement y ±U, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of k=2, providing a level of confidence of approximately 95%.

Item	Measurement Uncertainty	
Uncertainty of Conducted Emission for AC Port	$U_c = \pm 2.9 \text{ dB}$	
Uncertainty of Radiated Emission below 1GHz	$U_c = \pm 3.8 \text{ dB}$	
Uncertainty of Radiated Emission above 1GHz	$U_c = \pm 4.9 \text{ dB}$	
Uncertainty of total RF power, conducted	$U_c = \pm 0.8 \text{ dB}$	
Uncertainty of RF power density, conducted	$U_c = \pm 2.6 \text{ dB}$	
Uncertainty of spurious emissions, conducted	$U_c = \pm 2.7 \%$	
Uncertainty of Occupied Channel Bandwidth	$U_c = \pm 2 \%$	




Page 10 of 45

# 4. DESCRIPTION OF TEST MODES

NO.	TEST MODE DESCRIPTION		
1	Low channel TX_2402MHz_GFSK_1Mbps		
2	Middle channel TX_2446MHz_GFSK_1Mbps		
3	High channel TX_2479MHz_GFSK_1Mbps		

Note: 1. Only the result of the worst case was recorded in the report, if no other cases.

- 2. For Radiated Emission, 3axis were chosen for testing for each applicable mode.
- 3. For Conducted Test method, a temporary antenna connector is provided by the manufacture.






Page 11 of 45

# 5. SYSTEM TEST CONFIGURATION

# **5.1. CONFIGURATION OF TESTED SYSTEM**

Radiated Emission Configure:



# Conducted Emission Configure:

EUT	AE

# **5.2. EQUIPMENT USED IN TESTED SYSTEM**

Item	Equipment	Model No.	ID or Specification	Remark
1	WIRELESS KEYBOARD DONGLE	S.T.R.I.K.E. 11 DONGLE	2ASFYKS13NMUSBL0001	EUT
2	PC	D15	N/A	AE
3	PC adapter	HW-050200C01	DC 5V	AE

#### 5.3. SUMMARY OF TEST RESULTS

FCC RULES	DESCRIPTION OF TEST	RESULT
15.247 (b)(3)	Peak Output Power	Compliant
15.247 (a)(2)	6 dB Bandwidth	Compliant
15.247 (d)	Conducted Spurious Emission	Compliant
15.247 (e)	Maximum Conducted Output Power Density	Compliant
15.209	Radiated Emission	Compliant
15.207	Conducted Emission	Compliant



Page 12 of 45

# **6. TEST FACILITY**

Test Site	Attestation of Global Compliance (Shenzhen) Co., Ltd
Location	1-2/F, Building 19, Junfeng Industrial Park, Chongqing Road, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China
Designation Number	CN1259
FCC Test Firm Registration Number	975832
A2LA Cert. No.	5054.02
Description	Attestation of Global Compliance (Shenzhen) Co., Ltd is accredited by A2LA

# TEST EQUIPMENT OF CONDUCTED EMISSION TEST

Equipment	Manufacturer	Model	S/N	Cal. Date	Cal. Due
Test Receiver	R&S	ESPI	101206	Mar. 28, 2022	Mar. 27, 2023
Artificial power network	R&S	ESH2-Z5	100086	Jun. 08, 2022	Jun. 07, 2023
Test Software	FARA	EZ-EMC	Ver. AGC-CON03A1	N/A	N/A

# TEST EQUIPMENT OF RADIATED EMISSION TEST

Equipment	Manufacturer	Model	S/N	Cal. Date	Cal. Due
Test Receiver	R&S	ESCI	10096	Mar. 28, 2022	Mar. 27, 2023
EXA Signal Analyzer	Agilent	N9010A	MY53470504	Aug. 04, 2022	Aug. 03, 2023
Signal Analyzer	Aglient	N9020A	MY52090123	Aug. 04, 2022	Aug. 03, 2023
2.4GHz Filter	EM Electronics	N/A	N/A	Mar. 18, 2022	Mar. 19, 2024
Attenuator	ZHINAN	E-002	N/A	Aug. 04, 2022	Aug. 03, 2024
Horn Antenna	SCHWARZBEC	BBHA9170	768	Oct. 31, 2021	Oct. 30, 2023
Active Loop Antenna (9K-30Mhz)	ZHINAN	ZN30900C	18051	Mar. 12, 2022	Mar. 11, 2024
Double-Ridged Waveguide Horn	ETS	3117	00034609	Apr. 23, 2021	Apr. 22, 2023
Double-Ridged Waveguide Horn	ETS	3117	00154520	Sep. 06, 2021	Sep. 05, 2023
Preamplifier Assembly	ETS	3117PA	00225134	Sep. 01, 2022	Sep. 02, 2024
Wideband Antenna	SCHWARZBECK	VULB9168	VULB9168-494	Jan. 08, 2021	Jan. 07, 2023
Test Software	Tonscend	JS32-RE	Ver.2.5	N/A	N/A



Page 13 of 45

# 7. PEAK OUTPUT POWER


#### 7.1. MEASUREMENT PROCEDURE

For peak power test:

- 1. Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
- 2. RBW ≥ DTS bandwidth.
- 3. VBW≥3\*RBW.
- 4. SPAN≥VBW.
- 5. Sweep: Auto.
- 6. Detector function: Peak.
- 7. Trace: Max hold.

Allow trace to stabilize. Use the marker-to-peak function to set the marker to the peak of the emission. The indicated level is the peak output power, after any corrections for external attenuators and cables.

# 7.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) PEAK POWER TEST SETUP






Page 14 of 45

#### 7.3. LIMITS AND MEASUREMENT RESULT

7.0. Elimito Atto meadottement redoct							
	Test Data of Conducted Output Power						
Test Mode Test Channel (MHz) Peak Power Limits (dBm) Pass or Fail							
	2402	-4.642	≤30	Pass			
GFSK	2446	-5.735	≤30	Pass			
	2479	-6.685	≤30	Pass			


**Test Graphs of Conducted Output Power** 













Page 16 of 45

#### 8. BANDWIDTH

#### 8.1. MEASUREMENT PROCEDURE

#### 6dB bandwidth:

- 1. Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
- 2. Set the EUT Work on the top, the middle and the bottom operation frequency individually.
- 3. Set SPA Centre Frequency = Operation Frequency, RBW= 100 kHz, VBW ≥ 3×RBW.
- 4. Set SPA Trace 1 Max hold, then View.

#### Occupied bandwidth:

- 1. Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
- 2, Set the EUT Work on the top, the middle and the bottom operation frequency individually.
- 3. Set Span = approximately 2 to 5 times the 20 dB bandwidth, centered on a hoping channel The nominal IF filter bandwidth (3 dB RBW) shall be in the range of 1% to 5% of the OBW and video bandwidth (VBW) shall be approximately three times RBW; Sweep = auto; Detector function = peak
- 4. Set SPA Trace 1 Max hold, then View.


Note: The EUT was tested according to ANSI C63.10 for compliance to FCC PART 15.247 requirements.

# 8.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)

The same as described in section 7.2.

#### 8.3. LIMITS AND MEASUREMENT RESULTS

Test Data of Occupied Bandwidth and DTS Bandwidth						
Test Mode	Test Channel (MHz)	99% Occupied Bandwidth (MHz)	-6dB Bandwidth (MHz)	Limits (MHz)	Pass or Fail	
	2402	1.800	1.010	≥0.5	Pass	
GFSK	2446	1.847	1.034	≥0.5	Pass	
	2479	1.902	1.053	≥0.5	Pass	







Test Graphs of Occupied Bandwidth 04:24:09 PM Nov 09, 2022 Radio Std: None SENSE:INT Center Freq: 2.402000000 GHz
Trig: Free Run Avg|Hole
#Atten: 30 dB Frequency Avg|Hold: 10/10 Radio Device: BTS #IFGain:Low Ref 30.00 dBm Center Freq 2.402000000 GHz Center 2.402 GHz #Res BW 30 kHz Span 3 MHz Sweep 4.133 ms CF Step 300.000 kHz Man #VBW 100 kHz **Auto Total Power** 2.03 dBm **Occupied Bandwidth** 1.7998 MHz Freq Offset 0 Hz 70.495 kHz 99.00 % **Transmit Freq Error OBW Power** -26.00 dB x dB Bandwidth 2.058 MHz x dB Test\_Graph\_2.4G\_ANT1\_2402\_OBW 04:28:13 PM Nov 09, 2022 Radio Std: None SENSE:INT Center Freq: 2.446000000 GHz
Trig: Free Run Avg|Hole
#Atten: 30 dB Frequency Freq 2.446000000 GHz Avg|Hold: 10/10 Radio Device: BTS #IFGain:Low Ref 30.00 dBm Center Freq 2 446000000 GHz Center 2.446 GHz #Res BW 30 kHz Span 3 MHz Sweep 4.133 ms **CF Step #VBW 100 kHz** 300,000 kHz <u>Auto</u> **Total Power** 0.54 dBm **Occupied Bandwidth** 1.8467 MHz Freq Offset **Transmit Freq Error** 16.694 kHz **OBW Power** 99.00 % x dB Bandwidth -26.00 dB 2.132 MHz x dB


Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.


Test\_Graph\_2.4G\_ANT1\_2446\_OBW














Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: http://www.agccert.com/









Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: http://www.agccert.com/



Page 20 of 45

# 9. CONDUCTED SPURIOUS EMISSION

#### 9.1. MEASUREMENT PROCEDURE

- 1. Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
- 2, Set the EUT Work on the top, the middle and the bottom operation frequency individually.
- 3. Set SPA Trace 1 Max hold, then View.

Note: The EUT was tested according to ANSI C63.10 for compliance to FCC PART 15.247 requirements.

# 9.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)


The same as described in section 7.2.

#### 9.3. MEASUREMENT EQUIPMENT USED

The same as described in section 6.

#### 9.4. LIMITS AND MEASUREMENT RESULT

5.4. EIIII TO AND MEAGONEMENT NEGGET						
LIMITS AND MEA	LIMITS AND MEASUREMENT RESULT					
Applicable Limite	Measurement Re	sult				
Applicable Limits	Test Data	Criteria				
In any 100 kHz Bandwidth Outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produce by the intentional radiator shall be at least 20 dB below that in 100KHz bandwidth within the band that contains the highest level of the desired power.	At least -20dBc than the reference level	PASS				






Test Graphs of Spurious Emissions in Non-Restricted Frequency Bands



Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.


Test\_Graph\_2.4G\_ANT1\_2402\_Lower Band Emissions










































Test Graphs of Band Edge Emissions in Non-Restricted Frequency Bands Frequency Avg Type: Log-Pwr Avg|Hold: 100/100 RACE 1 2
TYPE MW
DET P N Center Freq 2.398500000 GHz Trig: Free Run #Atten: 30 dB PNO: Fast \*
IFGain:Low **Auto Tune** Mkr2 2.400 000 0 GHz -36.792 dBm Ref 20.00 dBm Center Freq 2.398500000 GHz Start Freq 2.390000000 GHz Stop Freq 2.407000000 GHz Start 2.390000 GHz #Res BW 100 kHz Stop 2.407000 GHz Sweep 2.000 ms (30000 pts) **CF Step** 1.700000 MHz **#VBW** 300 kHz <u>Auto</u> FUNCTION Freq Offset 0 Hz Test\_Graph\_2.4G\_ANT1\_2402\_Lower Band Edge Emissions Frequency Center Freq 2.487000000 GHz Avg Type: Log-Pwr Avg|Hold: 100/100 Trig: Free Run #Atten: 30 dB PNO: Fast ↔ IFGain:Low **Auto Tune** Mkr2 2.483 500 0 GHz -51.816 dBm Ref 20.00 dBm Center Freq 2.487000000 GHz Start Freq 2.474000000 GHz Stop Freq 2.500000000 GHz Start 2.47400 GHz #Res BW 100 kHz Stop 2.50000 GHz Sweep 4.000 ms (30000 pts) **CF Step** 2.600000 MHz **#VBW** 300 kHz <u>Auto</u> FUNCTION Freq Offset 0 Hz

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Test\_Graph\_2.4G\_ANT1\_2479\_Higher Band Edge Emissions



Page 27 of 45

# 10. MAXIMUM CONDUCTED OUTPUT POWER SPECTRAL DENSITY

#### 10.1. MEASUREMENT PROCEDURE

- (1). Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
- (2). Set the EUT Work on the top, the middle and the bottom operation frequency individually.
- (3). Set the SPA Trace 1 Max hold, then View.

Note: The method of PKPSD in the KDB 558074 item 8.4 was used in this testing.

# 10.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)

Refer to Section 7.2.

#### 10.3. MEASUREMENT EQUIPMENT USED


Refer to Section 6.

#### 10.4. LIMITS AND MEASUREMENT RESULT


Test Data of Conducted Output Power Spectral Density					
Test Mode	Test Channel (MHz)	Power density (dBm/3kHz)	Limit (dBm/3kHz)	Pass or Fail	
	2402	-12.578	<b>≤8</b>	Pass	
GFSK	2446	-13.712	≤8	Pass	
	2479	-15.225	≪8	Pass	

Test Graphs of Conducted Output Power Spectral Density












Page 29 of 45

#### 11. RADIATED EMISSION

#### 11.1. MEASUREMENT PROCEDURE


- 1. The EUT was placed on the top of the turntable 0.8 or 1.5 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
- 2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
- 3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
- 4. For each suspected emission, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
- 5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
- 6. For emissions above 1GHz, use 1MHz RBW and 3MHz VBW for peak reading. Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
- 7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum values.
- 8.If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
- 9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
- 10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High Low scan is not required in this case.






#### 11.2. TEST SETUP


# Radiated Emission Test-Setup Frequency Below 30MHz



#### RADIATED EMISSION TEST SETUP 30MHz-1000MHz



# RADIATED EMISSION TEST SETUP ABOVE 1000MHz





Page 31 of 45

# 11.3. LIMITS AND MEASUREMENT RESULT

15.209 Limit in the below table has to be followed

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(kHz)	300
0.490~1.705	24000/F(kHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

Note: All modes were tested for restricted band radiated emission, the test records reported below are the worst result compared to other modes.

# 11.4. TEST RESULT

#### Radiated emission below 30MHz


The amplitude of spurious emissions from 9kHz to 30MHz which are attenuated more than 20 dB below the permissible value need not be reported.



Page 32 of 45

# Radiated emission from 30MHz to 1000MHz

EUT	WIRELESS KEYBOARD DONGLE	Model Name	S.T.R.I.K.E. 11 DONGLE
Temperature	22°C	Relative Humidity	56%
Pressure	985hPa	Test Voltage	Normal Voltage
Test Mode	Mode 1	Antenna	Horizontal




NO.	Freq. [MHz]	Level [dBµV/m]	Factor [dB]	Limit [dBµV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	56.19	23.41	12.35	40.00	16.59	100	280	Horizontal
2	101.78	28.10	21.67	43.50	15.40	100	130	Horizontal
3	241.46	27.10	22.98	46.00	18.90	100	210	Horizontal
4	455.83	30.43	26.00	46.00	15.57	100	70	Horizontal
5	791.45	33.21	27.94	46.00	12.79	100	60	Horizontal
6	871.96	36.15	30.19	46.00	9.85	100	110	Horizontal

**RESULT: PASS** 



Page 33 of 45

EUT	WIRELESS KEYBOARD DONGLE	Model Name	S.T.R.I.K.E. 11 DONGLE
Temperature	22°C	Relative Humidity	56%
Pressure	985hPa	Test Voltage	Normal Voltage
Test Mode	Mode 1	Antenna	Vertical



NO.	Freq. [MHz]	Level [dBµV/m]	Factor [dB]	Limit [dBµV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	56.19	29.43	14.92	40.00	10.57	100	140	Vertical
2	109.54	24.66	14.28	43.50	18.84	100	0	Vertical
3	156.1	25.12	21.54	43.50	18.38	100	240	Vertical
4	636.25	29.35	26.33	46.00	16.65	100	260	Vertical
5	759.44	34.25	30.40	46.00	11.75	100	200	Vertical
6	853.53	35.43	32.26	46.00	10.57	100	340	Vertical

# **RESULT: PASS**

**Note:** 1. Factor=Antenna Factor + Cable loss, Margin=Limit-Level.

2. All test modes had been tested. The mode 1 is the worst case and recorded in the report.



Page 34 of 45

# Radiated emission above 1GHz

EUT	WIRELESS KEYBOARD DONGLE	Model Name	S.T.R.I.K.E. 11 DONGLE
Temperature	22°C	Relative Humidity	56%
Pressure	985hPa	Test Voltage	Normal Voltage
Test Mode	Mode 1	Antenna	Horizontal

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	Value Type
4804.000	46.37	0.08	46.45	74	-27.55	peak
4804.000	36.98	0.08	37.06	54	-16.94	AVG
7206.000	42.17	2.21	44.38	74	-29.62	peak
7206.000	32.57	2.21	34.78	54	-19.22	AVG
Remark:						
-actor = Anter	na Factor + Cabl	e Loss – Pre-	amplifier.			·

EUT	WIRELESS KEYBOARD DONGLE	Model Name	S.T.R.I.K.E. 11 DONGLE
Temperature	22°C	Relative Humidity	56%
Pressure	985hPa	Test Voltage	Normal Voltage
Test Mode	Mode 1	Antenna	Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	\/alva Tree
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	Value Type
4804.000	44.89	0.08	44.97	74	-29.03	peak
4804.000	35.27	0.08	35.35	54	-18.65	AVG
7206.000	40.16	2.21	42.37	74	-31.63	peak
7206.000	31.78	2.21	33.99	54	-20.01	AVG
emark:						



Page 35 of 45

EUT	WIRELESS KEYBOARD DONGLE	Model Name	S.T.R.I.K.E. 11 DONGLE
Temperature	22°C	Relative Humidity	56%
Pressure	985hPa	Test Voltage	Normal Voltage
Test Mode	Mode 2	Antenna	Horizontal

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	Value Type
4880.000	47.65	0.14	47.79	74	-26.21	peak
4880.000	36.58	0.14	36.72	54	-17.28	AVG
7320.000	43.57	2.36	45.93	74	-28.07	peak
7320.000	32.47	2.36	34.83	54	-19.17	AVG
Remark:					•	•
- actor = Anter	nna Factor + Cab	e Loss – Pre-a	amplifier.			

EUT	WIRELESS KEYBOARD DONGLE	Model Name	S.T.R.I.K.E. 11 DONGLE
Temperature	22°C	Relative Humidity	56%
Pressure	985hPa	Test Voltage	Normal Voltage
Test Mode	Mode 2	Antenna	Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type		
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	value Type		
4880.000	45.79	0.14	45.93	74	-28.07	peak		
4880.000	35.21	0.14	35.35	54	-18.65	AVG		
7320.000	41.37	2.36	43.73	74	-30.27	peak		
7320.000	30.45	2.36	32.81	54	-21.19	AVG		
Remark:								
Factor = Anter	Factor = Antenna Factor + Cable Loss - Pre-amplifier.							



Page 36 of 45

EUT	WIRELESS KEYBOARD DONGLE	Model Name	S.T.R.I.K.E. 11 DONGLE
Temperature	22°C	Relative Humidity	56%
Pressure	985hPa	Test Voltage	Normal Voltage
Test Mode	Mode 3	Antenna	Horizontal

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	Value Type
4960.000	47.94	0.22	48.16	74	-25.84	peak
4960.000	37.62	0.22	37.84	54	-16.16	AVG
7440.000	43.47	2.64	46.11	74	-27.89	peak
7440.000	33.21	2.64	35.85	54	-18.15	AVG
						1
Remark:					•	•
actor = Anter	na Factor + Cabl	e Loss – Pre-	amplifier.		_	-

EUT	WIRELESS KEYBOARD DONGLE	Model Name	S.T.R.I.K.E. 11 DONGLE
Temperature	22°C	Relative Humidity	56%
Pressure	985hPa	Test Voltage	Normal Voltage
Test Mode	Mode 3	Antenna	Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type	
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	value Type	
4960.000	46.37	0.22	46.59	74	-27.41	peak	
4960.000	36.49	0.22	36.71	54	-17.29	AVG	
7440.000	42.51	2.64	45.15	74	-28.85	peak	
7440.000	32.07	2.64	34.71	54	-19.29	AVG	
Remark:						•	
Factor = Anter	nna Factor + Cable	e Loss – Pre-	-amplifier.	_		_	


# **RESULT: PASS**

#### Note:

The amplitude of other spurious emissions from 1G to 25 GHz which are attenuated more than 20 dB below the permissible value need not be reported.

Factor = Antenna Factor + Cable loss - Amplifier gain, Margin=Emission Level-Limit.


The "Factor" value can be calculated automatically by software of measurement system.







Test result for band edge emission at restricted bands

EUT	WIRELESS KEYBOARD DONGLE	Model Name	S.T.R.I.K.E. 11 DONGLE
Temperature	25°C	Relative Humidity	56%
Pressure	985hPa	Test Voltage	Normal Voltage
Test Mode	Mode 1	Antenna	Horizontal






**RESULT: PASS** 






**WIRELESS KEYBOARD EUT Model Name** S.T.R.I.K.E. 11 DONGLE **DONGLE Temperature** 25°C **Relative Humidity** 56% **Pressure** 985hPa **Test Voltage** Normal Voltage **Test Mode** Vertical Mode 1 **Antenna** 



**RESULT: PASS** 






**WIRELESS KEYBOARD EUT Model Name** S.T.R.I.K.E. 11 DONGLE **DONGLE Temperature** 25°C **Relative Humidity** 56% **Pressure** 985hPa **Test Voltage** Normal Voltage **Test Mode** Horizontal Mode 3 **Antenna** 











**RESULT: PASS** 





**WIRELESS KEYBOARD EUT Model Name** S.T.R.I.K.E. 11 DONGLE **DONGLE Temperature** 25°C **Relative Humidity** 56% **Pressure** 985hPa **Test Voltage** Normal Voltage Vertical **Test Mode** Mode 3 **Antenna** 



**RESULT: PASS** 

Note: The factor had been edited in the "Input Correction" of the Spectrum Analyzer.



Page 41 of 45

# 12. LINE CONDUCTED EMISSION TEST


#### 12.1. LIMITS OF LINE CONDUCTED EMISSION TEST

Francis	Maximum RF Line Voltage							
Frequency	Q.P.( dBuV)	Average( dBuV)						
150kHz~500kHz	66-56	56-46						
500kHz~5MHz	56	46						
5MHz~30MHz	60	50						

Note: 1. The lower limit shall apply at the transition frequency.

2. The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz.

# 12.2. BLOCK DIAGRAM OF LINE CONDUCTED EMISSION TEST





Page 42 of 45

#### 12.3. PRELIMINARY PROCEDURE OF LINE CONDUCTED EMISSION TEST

- 1. The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. When the EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.10 (see Test Facility for the dimensions of the ground plane used). When the EUT is a floor-standing equipment, it is placed on the ground plane which has a 3-12 mm non-conductive covering to insulate the EUT from the ground plane.
- 2. Support equipment, if needed, was placed as per ANSI C63.10.
- 3. All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10.
- 4. All support equipment received AC120V/60Hz power from a LISN, if any.
- 5. The EUT received DC 5V power from adapter which received AC120V/60Hz power from a LISN.
- 6. The test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
- 7. Analyzer / Receiver scanned from 150 kHz to 30MHz for emissions in each of the test modes.
- 8. During the above scans, the emissions were maximized by cable manipulation.
- 9. The test mode(s) were scanned during the preliminary test.

Then, the EUT configuration and cable configuration of the above highest emission level were recorded for reference of final testing.

#### 12.4. FINAL PROCEDURE OF LINE CONDUCTED EMISSION TEST


- 1. EUT and support equipment was set up on the test bench as per step 2 of the preliminary test.
- 2. A scan was taken on both power lines, Line 1 and Line 2, recording at least the six highest emissions. Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit. If EUT emission level was less – 2dB to the A.V. limit in Peak mode, then the emission signal was re-checked using Q.P and Average detector.
- 3. The test data of the worst case condition(s) was reported on the Summary Data page.



Page 43 of 45

# 12.5. TEST RESULT OF LINE CONDUCTED EMISSION TEST

#### LINE CONDUCTED EMISSION TEST-L1



x x x MES agc\_fin

# MEASUREMENT RESULT: "agc fin"

20	022/11/8 21: Frequency MHz	03 Level dBμV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
	0.154000	57.20	6.9	66	8.6	QP	L1	GND
	0.230000	50.70	6.4	62	11.7	QP	L1	GND
	0.522000	43.40	5.4	56	12.6	QP	L1	GND
	0.530000	42.60	5.4	56	13.4	QP	L1	GND
	0.538000	43.90	5.4	56	12.1	QP	L1	GND
	0.770000	40.70	5.4	56	15.3	OP	L1	GND

#### MEASUREMENT RESULT: "agc fin2"

2	022/11/8 21:	04						
	Frequency	Level	Transd	Limit	Margin	Detector	Line	PE
	MHz	dΒμV	dB	dΒμV	dB			
	0.154000	40.40	6.9	56	15.4	AV	L1	GND
	0.230000	31.80	6.4	52	20.6	AV	L1	GND
	0.518000	28.40	5.4	46	17.6	AV	L1	GND
	0.690000	25.90	5.4	46	20.1	AV	L1	GND
	0.770000	22.80	5.4	46	23.2	AV	L1	GND
	1.298000	22.40	5.8	46	23.6	AV	L1	GND


**RESULT: PASS** 

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: http://www.agccert.com/



# LINE CONDUCTED EMISSION TEST-N



# MEASUREMENT RESULT: "agc\_fin"

2022/11/8	21:09						
Frequenc	y Level	Transd	Limit	Margin	Detector	Line	PE
MH	z dBµV	dB	dΒμV	dB			
0.15400	0 47.20	6.9	66	18.6	QP	N	GND
0.16600	0 45.70	6.8	65	19.5	QP	N	GND
0.21800	0 42.40	6.4	63	20.5	QP	N	GND
0.30600	0 38.60	6.0	60	21.5	QP	N	GND
0.33000	0 40.40	5.9	60	19.1	QP	N	GND
0.52200	0 39.60	5.4	56	16.4	QP	N	GND

# MEASUREMENT RESULT: "agc\_fin2"

2022/11/8	21:07						
Frequenc	y Level	Transd	Limit	Margin	Detector	Line	PE
MH	z dBµV	dB	dΒμV	dB			
0.19000	0 23.00	6.6	54	31.0	AV	N	GND
0.51400	0 29.90	5.4	46	16.1	AV	N	GND
1.24600	0 17.20	5.8	46	28.8	AV	N	GND
2.20200	0 15.00	6.5	46	31.0	AV	N	GND
2.66600	0 14.20	6.5	46	31.8	AV	N	GND
3.15400	0 13.90	6.5	46	32.1	AV	N	GND

# **RESULT: PASS**

Note: All the test modes had been tested, the Mode 1 was the worst case. Only the data of the worst case would be record in this test report.



Page 45 of 45

# APPENDIX A: PHOTOGRAPHS OF TEST SETUP

Refer to the Report No.: AGC08218221101AP01

**APPENDIX B: PHOTOGRAPHS OF EUT** 

Refer to the Report No.: AGC08218221101AP02

----END OF REPORT----



# Conditions of Issuance of Test Reports

- 1. All samples and goods are accepted by the Attestation of Global Compliance (Shenzhen) Co., Ltd (the "Company") solely for testing and reporting in accordance with the following terms and conditions. The company provides its services on the basis that such terms and conditions constitute express agreement between the company and any person, firm or company requesting its services (the "Clients").
- 2. Any report issued by Company as a result of this application for testing services (the "Report") shall be issued in confidence to the Clients and the Report will be strictly treated as such by the Company. It may not be reproduced either in its entirety or in part and it may not be used for advertising or other unauthorized purposes without the written consent of the Company. The Clients to whom the Report is issued may, however, show or send it, or a certified copy thereof prepared by the Company to its customer, supplier or other persons directly concerned. The Company will not, without the consent of the Clients, enter into any discussion or correspondence with any third party concerning the contents of the Report, unless required by the relevant governmental authorities, laws or court orders.
- 3. The Company shall not be called or be liable to be called to give evidence or testimony on the Report in a court of law without its prior written consent, unless required by the relevant governmental authorities, laws or court orders.
- 4. In the event of the improper use of the report as determined by the Company, the Company reserves the right to withdraw it, and to adopt any other additional remedies which may be appropriate.
- 5. Samples submitted for testing are accepted on the understanding that the Report issued cannot form the basis of, or be the instrument for, any legal action against the Company.
- 6. The Company will not be liable for or accept responsibility for any loss or damage however arising from the use of information contained in any of its Reports or in any communication whatsoever about its said tests or investigations.
- 7.Clients wishing to use the Report in court proceedings or arbitration shall inform the Company to that effect prior to submitting the sample for testing.
- 8. The Company is not responsible for recalling the electronic version of the original report when any revision is made to them. The Client assumes the responsibility to providing the revised version to any interested party who uses them.
- 9. Subject to the variable length of retention time for test data and report stored hereinto as otherwise specifically required by individual accreditation authorities, the Company will only keep the supporting test data and information of the test report for a period of six years. The data and information will be disposed of after the aforementioned retention period has elapsed. Under no circumstances shall we provide any data and information which has been disposed of after retention period. Under no circumstances shall we be liable for damage of any kind, including (but not limited to) compensatory damages, lost profits, lost data, or any form of special, incidental, indirect, consequential or punitive damages of any kind, whether based on breach of contract of warranty, tort (including negligence), product liability or otherwise, even if we are informed in advance of the possibility of such damages.