

Contention Based Protocol NVNT be160 6985MHz Interfere 6985 MHz_2




Contention Based Protocol NVNT be160 6985MHz Interfere 6985 MHz_3



Contention Based Protocol NVNT be160 6985MHz Interfere 6985 MHz_4



Contention Based Protocol NVNT be160 6985MHz Interfere 6985 MHz_5



Contention Based Protocol NVNT be160 6985MHz Interfere 6985 MHz_6




Contention Based Protocol NVNT be160 6985MHz Interfere 6985 MHz_7




Contention Based Protocol NVNT be160 6985MHz Interfere 6985 MHz _8




Contention Based Protocol NVNT be160 6985MHz Interfere 6985 MHz _9



Contention Based Protocol NVNT be160 6985MHz Interfere 6985 MHz _10




Contention Based Protocol NVNT be160 6985MHz Interfere 7060 MHz_1



Contention Based Protocol NVNT be160 6985MHz Interfere 7060 MHz_2



Contention Based Protocol NVNT be160 6985MHz Interfere 7060 MHz_3



Contention Based Protocol NVNT be160 6985MHz Interfere 7060 MHz_4



Contention Based Protocol NVNT be160 6985MHz Interfere 7060 MHz_5



Contention Based Protocol NVNT be160 6985MHz Interfere 7060 MHz_6



Contention Based Protocol NVNT be160 6985MHz Interfere 7060 MHz_7




Contention Based Protocol NVNT be160 6985MHz Interfere 7060 MHz_8



Contention Based Protocol NVNT be160 6985MHz Interfere 7060 MHz_9





11.8. APPENDIX H: FREQUENCY STABILITY

11.8.1. Test Result

Frequency Error vs. Voltage									
802.11a:5975MHz									
Temp.	Volt.	0 Minute		2 Minute		5 Minute		10 Minute	
		Freq.Error (MHz)	Tolerance (ppm)	Freq.Error (MHz)	Tolerance (ppm)	Freq.Error (MHz)	Tolerance (ppm)	Freq.Error (MHz)	Tolerance (ppm)
TN	VL	5975.0143	2.39	5975.0202	3.37	5975.0215	3.60	5975.0095	1.60
TN	VN	5975.0016	0.27	5974.9996	-0.07	5974.9983	-0.29	5975.0073	1.22
TN	VH	5974.9845	-2.59	5975.0004	0.06	5975.0190	3.18	5975.0032	0.53
Frequency Error vs. Temperature									
802.11a:5975MHz									
Temp.	Volt.	0 Minute		2 Minute		5 Minute		10 Minute	
		Freq.Error (MHz)	Tolerance (ppm)	Freq.Error (MHz)	Tolerance (ppm)	Freq.Error (MHz)	Tolerance (ppm)	Freq.Error (MHz)	Tolerance (ppm)
50	VN	5975.0054	0.91	5975.0077	1.29	5974.9872	-2.15	5974.9795	-3.43
40	VN	5975.0172	2.88	5974.9990	-0.17	5974.9924	-1.27	5975.0228	3.81
30	VN	5974.9990	-0.17	5975.0225	3.77	5974.9892	-1.80	5974.9819	-3.03
20	VN	5975.0064	1.07	5975.0224	3.74	5974.9845	-2.60	5975.0131	2.20
10	VN	5975.0166	2.78	5975.0242	4.05	5974.9842	-2.64	5975.0193	3.23
0	VN	5974.9997	-0.06	5974.9756	-4.09	5975.0026	0.44	5975.0170	2.85
-10	VN	5974.9984	-0.27	5975.0085	1.42	5974.9971	-0.49	5975.0200	3.34

Note:

1. All antennas, test modes and test channels have been tested, only the worst data record in the report.
2. For the detail Test Conditions, please refer to section 7.5 TEST ENVIRONMENT.

END OF REPORT