

# **FCC Test Report**

Report No.: AGC00275180602FE03

FCC ID : JFZSP60BT

**APPLICATION PURPOSE**: Original Equipment

**PRODUCT DESIGNATION**: BLUETOOTH SPEAKER

BRAND NAME : audio-technica

MODEL NAME : AT-SP60BT

**CLIENT**: Audio-Technica Corporation

**DATE OF ISSUE** : Jun. 20, 2018

STANDARD(S)

TEST PROCEDURE(S)

: FCC Part 15 Subpart C Section 15.249

REPORT VERSION 'V1.0

Attestation of Global Compliance (Shenzhen) Co., Ltd

#### **CAUTION:**

This report shall not be reproduced except in full without the written permission of the test laboratory and shall not be quoted out of context.



The results spower this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at a true and the authenticity of the authenticity of

Attestation of Global Compliance

Tel: +86-755 2908 1955 Fax: +86-755 2600 8484 E-mail: agc@agc-cert.com @ 400 089 2118 Add: 2/F., Building 2, No.1-4,Chaxi Sanwei Technical Industrial Park,Gushu, Xixiang, Baoan District, Shenzhen, Guangdong China



Page 2 of 65

## **Report Revise Record**

Report Version	Revise Time	Issued Date	Valid Version	Notes
V1.0	plience / © Mile	Jun. 20, 2018	Valid	Initial release

The results shown this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by KGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at http://www.agc.gett.com.



## TABLE OF CONTENTS

1. VERIFICATION OF CONFORMITY	
2. GENERAL INFORMATION	5
2.1. PRODUCT DESCRIPTION	
3. MEASUREMENT UNCERTAINTY	
4. DESCRIPTION OF TEST MODES	
5. SYSTEM TEST CONFIGURATION	8
5.1. CONFIGURATION OF EUT SYSTEM 5.2. EQUIPMENT USED IN EUT SYSTEM 5.3. SUMMARY OF TEST RESULTS	8 8 9
6. TEST FACILITY	10
7.TEST METHOD	11
8. TEST EQUIPMENT LIST	11
9. RADIATED EMISSION	12
9.1TEST LIMIT 9.2. MEASUREMENT PROCEDURE 9.3. TEST SETUP 9.4. TEST RESULT	12 13
10. BAND EDGE EMISSION	39
10.1. MEASUREMENT PROCEDURE 10.2 TEST SETUP 10.3 RADIATED TEST RESULT	39
11. 20DB BANDWIDTH	44
11.1. MEASUREMENT PROCEDURE	44 44
12. FCC LINE CONDUCTED EMISSION TEST	
12.1. LIMITS OF LINE CONDUCTED EMISSION TEST	52 52
APPENDIX A: PHOTOGRAPHS OF TEST SETUP	55
APPENDIX B. PHOTOGRAPHS OF FUT	58



Page 4 of 0

## 1. VERIFICATION OF CONFORMITY

Applicant	Audio-Technica Corporation
Address	2-46-1 Nishi-naruse, Machida, Tokyo 194-8666, Japan
Manufacturer	Shenzhen Jonter Digital Co., Ltd.
Address	Building 4, Jinfo Industrial Park, Hezhou Village, Xixiang Town, Baoan District, Shenzhen, China
Product Designation	BLUETOOTH SPEAKER
Brand Name	audio-technica
Test Model	AT-SP60BT
Date of test	Jun. 06, 2018 to Jun. 16, 2018
Deviation	None
Condition of Test Sample	Normal Normal State of the Stat
Report Template	AGCRT-US-BR/RF

We hereby certify that:

The above equipment was tested by Attestation of Global Compliance (Shenzhen) Co., Ltd. The test data, the energy emitted by the sample tested as described in this report is in compliance with the requirements of FCC Rules Part 15.249. The test results of this report relate only to the tested sample identified in this report.

Tested By		Henry	Zhang		
© Mestalion of Com	Henry Zhang(Z	hang Zh	nuorui)	Jun. 16, 2	018
Reviewed By_	The table to table	cuo	cheng	© Mestallari of Global	Compliance
CC in	Cool Cheng(Che	eng Men	igguo)	Jun. 20, 2	018
Approved By		Fowe	站空		
® Allesation of C	Forrest Lei(Le Authorize		•	Jun. 20, 2	018

The results spowford this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by XOC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.ago.go.tt.com.



Page 5 of 65

## 2. GENERAL INFORMATION

## 2.1. PRODUCT DESCRIPTION

A major technical description of EUT is described as following

2 N 2 N 2 N 2 N 2 N 2 N 2 N 2 N 2 N 2 N	
Operation Frequency	2.402 GHz to 2.480GHz
RF Output Power	2.97dBm(Max EIRP Power=Max radiation field-95.2)
Bluetooth Version	V4.2
Modulation	BR ⊠GFSK, EDR ⊠π /4-DQPSK, ⊠8DPSK BLE □GFSK
Number of channels	79 for BR/EDR
Hardware Version	6.0
Software Version	V12
Antenna Designation	PCB Antenna
Antenna Gain	1.2dBi
Power Supply	DC 3.7V by battery
Note: The USB port only	used for charging and can't be used to transfer data with PC.

## 2.2. TABLE OF CARRIER FREQUENCYS

BR/EDR channel List

Frequency Band	Channel Number	Frequency
100	0	2402MHz
The Mill and the second	A State of the sta	2403MHz
8 Figure of Clothat Co.	GC: CO	
CC CC	38	2440 MHz
2400~2483.5MHz	39	2441 MHz
The templates @ Manufacture and the second s	40	2442 MHz
of Globald C. G. Allege	CO DO	
	77	2479 MHz
	78	2480 MHz



## 3. MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement y ±U, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of k=2, providing a level of confidence of approximately 95%.

- Uncertainty of Conducted Emission, Uc = ±3.2 dB
- Uncertainty of Radiated Emission below 1GHz, Uc = ±3.9 dB
- Uncertainty of Radiated Emission above 1GHz, Uc = ±4.8 dB

## 4. DESCRIPTION OF TEST MODES

NO.	TEST MODE DESCRIPTION
® Martin Tool cools	Low channel GFSK
2 2	Middle channel GFSK
3	High channel GFSK
· 4 不是那	Low channel π /4-DQPSK
S 5 to d Clobs	Middle channel π /4-DQPSK
G 6	High channel π /4-DQPSK
7	Low channel 8DPSK
Filter Some 8 SE THE	Middle channel 8DPSK
9 Paris	High channel 8DPSK
10	BT Link with charging
11th Complete	BT Link

#### Note:

- 1. All the test modes can be supply by battery, only the result of the worst case was recorded in the report, if no other cases.
- 2. For Radiated Emission, 3axis were chosen for testing for each applicable mode.
- 3. The EUT used fully-charged battery when tested.





The results spound this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by XCC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at a true www.ago.gent.com.




Page 8 of 65

## 5. SYSTEM TEST CONFIGURATION


## 5.1. CONFIGURATION OF EUT SYSTEM

Configure 1: (Normal hopping)



Note: Owing to the EUT has own battery, testing may be performed while PC or adapter removed.

Configure 2: (Control continuous TX)



## **5.2. EQUIPMENT USED IN EUT SYSTEM**

Item	Equipment	Mfr/Brand	Model/Type No.	Remark
1 ,	BLUETOOTH	audio-technica	AT-SP60BT	EUT
2	Battery	HKD	HKD-22	Accessory
3	PC	APPLE	A1465	A.E
4	Control box	SERIAL	N/A	A.E
5	Adapter	IPRO	NTR-S01	A.E
6	USB Cable	N/A	1m unshielded	A.E
7	USB Cable	N/A	0.6m unshielded	Accessory
8	AUX in Cable	N/A	0.6m unshielded	Accessory
9	IPOD	APPLE	A1367	A.E
10	TF Card	Kingston	SDA10/16GB	A.E
11	Mobile Phone	Huawei	V9	aggation of Civia



#### 5.3. SUMMARY OF TEST RESULTS

FCC RULES	DESCRIPTION OF TEST	RESULT
§15.249(a) §15.209	Radiated Emission	Compliant
§15.249(d)	Band Edges	Compliant
§15.207	Conduction Emission	Compliant
§15.215	Bandwidth	Compliant



Page 10 of 65

## 6. TEST FACILITY

Test Site	Attestation of Global Compliance (Shenzhen) Co., Ltd
Location	1-2F., Bldg.2, No.1-4, Chaxi Sanwei Technical Industrial Park, Gushu, Xixiang, Bao'an District B112-B113, Bldg.12, Baoan Bldg Materials Center, No.1 of Xixiang Inner Ring Road, Baoan District, Shenzhen 518012
NVLAP Lab Code	600153-0
Designation Number	CN5028
Test Firm Registration Number	682566
Description	Attestation of Global Compliance(Shenzhen) Co., Ltd is accredited by National Voluntary Laboratory Accreditation program, NVLAP Code 600153-0



age 11 of 65

## 7. TEST METHOD

All measurements contained in this report were conducted with ANSI C63.10-2013

## 8. TEST EQUIPMENT LIST

#### **TEST EQUIPMENT OF CONDUCTED EMISSION TEST**

Equipment	Manufacturer	Model	S/N	Cal. Date	Cal. Due
Test Receiver	R&S	ESPI	101206	Jun.20, 2017	Jun.19, 2018
LISN	R&S	ESH2-Z5	100086	Aug.21, 2017	Aug.20, 2018

## **TEST EQUIPMENT OF RADIATED EMISSION TEST**

Equipment	Manufacturer	Model	S/N	Cal. Date	Cal. Due
Test Receiver	R&S	ESCI	10096	Jun.20, 2017	Jun.19, 2018
EXA Signal Analyzer	Aglient	N9010A	MY53470504	Dec.08, 2017	Dec.07, 2018
Horn antenna	SCHWARZBECK	BBHA 9170	#768	Sep.20, 2017	Sep.19, 2018
preamplifier	ChengYi	EMC184045SE	980508	Sep.15, 2017	Sep.14, 2018
Double-Ridged Waveguide Horn	ETS LINDGREN	3117	00034609	May 18, 2017	May 17, 2019
Broadband Preamplifier	SCHWARZBECK	BBV 9718	9718-205	Jun.20, 2017	Jun.19, 2018
Antenna	SCHWARZBECK	VULB9168	D69250	Sep.28, 2017	Sep.27, 2018
Loop Antenna	A.H.Systems,Inc	SAS-562B	C AMO	Mar. 01, 2018	Feb. 28, 2019
Radiation Cable 1	MXT	RS1	R005	June 6, 2018	June 5, 2019
Radiation Cable 2	MXT	RS1	R006	June 6, 2018	June 5, 2019
Filter (2.4-2.483GHz)	Micro-tronics	087	<b>-C</b>	Jun.20, 2017	Jun.19, 2018



Page 12 of 65

## 9. RADIATED EMISSION

## 9.1TEST LIMIT

## Standard FCC15.249

Fundamental	Field Strength of Fundamental	Field Strength of Harmonics
Frequency	(millivolts/meter)	(microvolts/meter)
900-928MHz	50	500
2400-2483.5MHz	50	500
5725-5875MHz	50	500
24.0-24.25GHz	250	2500

#### Standard FCC 15.209

Frequency	Distance	Field Str	engths Limit
(MHz)	Meters	μ V/m	dB(μV)/m
0.009 ~ 0.490	300	2400/F(kHz)	2
0.490 ~ 1.705	30	24000/F(kHz)	吃那
1.705 ~ 30	30	30 (1)	E Sandador of Globa
30 ~ 88	3	100	40.0
88 ~ 216	3 - 6	150	43.5
216 ~ 960	3	200	46.0
960 ~ 1000	3	500	54.0
Above 1000	3 The factor of the second	Other:74.0 dB(μV)/m (Average)	(Peak) 54.0 dB(μV)/m

Remark:

- (1) Emission level dB $\mu$  V = 20 log Emission level  $\mu$  V/m
- (2) The smaller limit shall apply at the cross point between two frequency bands.
- (3) Distance is the distance in meters between the measuring instrument, antenna and the closest point of any part of the device or system.




Report No.: AGC00275180602FE03 Page 13 of 65

#### 9.2. MEASUREMENT PROCEDURE

- 1. The measuring distance of 3m shall be used for measurements. The EUT was placed on the top of a rotating table 0.8 meter above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation(Below 1GHz)
- 2. The measuring distance of 3m shall used for measurements. The EUT was placed on the top of a rotating table 1.5 meter above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation(Above 1GHz)
- The height of the test antenna shall vary between 1m to 4m.Both horizontal and vertical polarization Of the antenna are set to make the measurement.
- 4. The initial step in collecting radiated emission data is a receive peak detector mode. Pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- 5. All readings are peak unless otherwise stated QP in column of Note. Peak denoted that the Peak reading compliance with the QP limits and then QP Mode measurement didn't perform(Below 1GHz)
- 6. All readings are Peak mode value unless otherwise stated AVG in column of Note. If the Peak mode measured value compliance with the Peak limits and lower than AVG Limits, the EUT shall be deemed to meet Peak & AVG limits and then only Peak mode was measured, but AVG mode didn't perform.(Above 1GHz)

The results spound this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by XCC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.ago.go.tt.com.





The following table is the setting of spectrum analyzer and receiver.


Spectrum Parameter	Setting
Start ~Stop Frequency	9KHz~150KHz/RB 200Hz for QP
Start ~Stop Frequency	150KHz~30MHz/RB 9KHz for QP
Start ~Stop Frequency	30MHz~1000MHz/RB 120KHz for QP
Start ~Stop Frequency	Fundamental: 2.4~2.483GHz RBW 2MHz/ VBW 6MHz for Peak, RBW 2MHz/ VBW 10Hz for Average Harmonics: 1GHz~25GHz RBW 1MHz/ VBW 3MHz for Peak, RBW 1MHz/ VBW 10Hz for Average
Receiver Parameter	Setting
Start ~Stop Frequency	9KHz~150KHz/RB 200Hz for QP
Start ~Stop Frequency	150KHz~30MHz/RB 9KHz for QP
Start ~Stop Frequency	30MHz~1000MHz/RB 120KHz for QP

The results shown this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at http://www.agc.cett.com.




## 9.3. TEST SETUP

## Radiated Emission Test-Setup Frequency Below 30MHz




## RADIATED EMISSION TEST SETUP 30MHz-1000MHz



The results spoured this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by XOC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.ago.go.tt.com.



## RADIATED EMISSION TEST SETUP ABOVE 1000MHz



The results shown this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by 40°C, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.ago.gent.com.



Page 17 of 65

## 9.4. TEST RESULT

FOR BR/EDR

(Worst modulation: 8DPSK)

## **RADIATED EMISSION BELOW 30MHz**


No emission found between lowest internal used/generated frequencies to 30MHz.

The results spoured this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by KGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at a true www.agc. gent.com.



## **RADIATED EMISSION BELOW 1GHz**

## RADIATED EMISSION TEST- (30MHz-1GHz)-LOW CHANNEL-HORIZONTAL




#### A. Suspected List:

Frequency MHz	Polarization	Reading dB(uV)	Factor dB (1/m)	Level dB(u∀/m) PK	Limit dB(u∀/m) QP	Margin dB	Pass/Fail	Height cm	Angle deg
42.125	H	5.5	17.4	22.9	40.0	17.1	Pass	150.0	252.9
61.040	Н	6.5	16.1	22.6	40.0	17.4	Pass	100.0	93.7
114.390	Н	12.0	14.9	26.9	43.5	16.6	Pass	200.0	41.2
147.855	H	5.5	16.6	22.1	43.5	21.4	Pass	150.0	288.4
733.250	H	5.8	27.1	32.9	46.0	13.1	Pass	200.0	289.5
981.570	Н	6.0	30.9	36.9	54.0	17.1	Pass	200.0	289.5

**RESULT: PASS** 



## RADIATED EMISSION TEST- (30MHz-1GHz)-LOW CHANNEL -VERTICAL



#### A. Suspected List:

Frequency MHz	Polarization	Reading dB(uV)	Factor dB (1/m)	Level dB(uV/m) PK	Limit dB(uV/m) QP	Margin dB	Pass/Fail	Height cm	Angle deg
43.095	V	6.1	17.4	23.5	40.0	16.5	Pass	100.0	106.9
68.800	V	7.0	14.8	21.8	40.0	18.2	Pass	100.0	287.2
103.720	V	12.4	13.9	26.3	43.5	17.2	Pass	100.0	287.2
113.420	V	10.9	14.8	25.7	43.5	17.8	Pass	150.0	323.2
384.050	v	12.9	20.2	33.1	46.0	12.9	Pass	100.0	70.3
922.400	V	7.1	30.4	37.5	46.0	8.5	Pass	150.0	249.9


#### **RESULT: PASS**

Note: 1. Factor=Antenna Factor + Cable loss, Margin=Measurement-Limit.

2. The "Factor" value can be calculated automatically by software of measurement system.



## RADIATED EMISSION TEST- (30MHz-1GHz)-MIDDLE CHANNEL-HORIZONTAL




#### A. Suspected List:

Frequency MHz	Polarization	Reading dB(uV)	Factor dB (1/m)	Level dB(u√/m) PK	Limit dB(uV/m) QP	Margin dB	Pass/Fail	Height cm	Angle deg
40.185	H	5.4	17.4	22.8	40.0	17.2	Pass	200.0	92.1
102.265	Н	9.2	13.7	22.9	43.5	20.6	Pass	150.0	251.2
114.875	H	11.2	15.0	26.2	43.5	17.3	Pass	200.0	92.1
154.160	Н	5.7	16.6	22.3	43.5	21.2	Pass	100.0	1.4
816.185	Н	5.6	29.0	34.6	46.0	11.4	Pass	100.0	109.6
996.605	Н	6.5	31.1	37.6	54.0	16.4	Pass	200.0	92.1

**RESULT: PASS** 



## RADIATED EMISSION TEST- (30MHz-1GHz)- MIDDLE CHANNEL -VERTICAL



#### A. Suspected List:

Frequency MHz	Polarization	Reading dB(uV)	Factor dB (1/m)	Level dB(uV/m) PK	Limit dB(uV/m) QP	Margin dB	Pass/Fail	Height cm	Angle deg
41.155	V	5.1	17.4	22.5	40.0	17.5	Pass	150.0	178.5
101.295	V	12.3	13.6	25.9	43.5	17.6	Pass	200.0	93.7
104.690	v	12.3	14.0	26.3	43.5	17.2	Pass	200.0	93.7
113.905	V	10.7	14.9	25.6	43.5	17.9	Pass	150.0	287.9
384.050	V	8.9	20.2	29.1	46.0	16.9	Pass	150.0	251.8
927.250	v	5.5	30.4	35.9	46.0	10.1	Pass	150.0	214.6


## **RESULT: PASS**

Note: 1. Factor=Antenna Factor + Cable loss, Margin=Measurement-Limit.

2. The "Factor" value can be calculated automatically by software of measurement system.



## RADIATED EMISSION TEST- (30MHz-1GHz)-HIGH CHANNEL-HORIZONTAL




#### A. Suspected List:

Frequency MHz	Polarization	Reading dB(uV)	Factor dB (1/m)	Level dB(uV/m) PK	Limit dB(uV/m) QP	Margin dB	Pass/Fail	Height cm	Angle deg
46.490	Н	5.8	17.2	23.0	40.0	17.0	Pass	200.0	120.6
104.205	Н	7.1	13.9	21.0	43.5	22.5	Pass	100.0	92.6
114.390	Н	9.1	14.9	24.0	43.5	19.5	Pass	100.0	56.5
159.495	Н	5.6	16.6	22.2	43.5	21.3	Pass	150.0	288.4
384.050	H	12.2	20.2	32.4	46.0	13.6	Pass	150.0	161.1
970.415	Н	5.7	30.8	36.5	54.0	17.5	Pass	100.0	92.6

**RESULT: PASS** 



## RADIATED EMISSION TEST- (30MHz-1GHz)-HIGH CHANNEL -VERTICAL



#### A. Suspected List:

Frequency MHz			- 1 48 1 48/11		Limit dB(u∨/m) QP	Margin dB	Pass/Fail	Height cm	Angle deg
43.580	V	4.9	17.4	22.3	40.0	17.7	Pass	150.0	143.7
67.830	V	7.7	15.0	22.7	40.0	17.3	Pass	100.0	93.5
104.690	v	13.7	14.0	27.7	43.5	15.8	Pass	150.0	251.3
114.875	V	12.5	15.0	27.5	43.5	16.0	Pass	100.0	93.5
384.050	V	17.2	20.2	37.4	46.0	8.6	Pass	150.0	33.8
963.140	V	6.1	30.8	36.9	54.0	17.1	Pass	150.0	287.9

## **RESULT: PASS**

Note: 1. Factor=Antenna Factor + Cable loss, Margin=Measurement-Limit.

2. The "Factor" value can be calculated automatically by software of measurement system.




Page 24 of 65

## RADIATED EMISSION ABOVE 1GHz FOR BR/EDR

(Worst modulation: 8DPSK)


#### For Fundamental

## RADIATED EMISSION TEST- (ABOVE 1GHz)-LOW CHANNEL-HORIZONTAL




No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
	-	MHz	dBu∀	dB/m	dBu∀/m	dBu∀/m	dB		cm	degree	
1		2402.000	85.91	10.32	96.23	114.00	-17.77	peak			
2	*	2402.000	77.97	10.32	88.29	94.00	-5.71	AVG	100	325	

RESULT: PASS





## RADIATED EMISSION TEST- (ABOVE 1GHz)-LOW CHANNEL- VERTICAL




No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
	-	MHz	dBu∀	dB/m	dBu∀/m	dBu∀/m	dB		cm	degree	
1		2402.000	85.46	10.32	95.78	114.00	-18.22	peak			
2	*	2402.000	77.47	10.32	87.79	94.00	-6.21	AVG	100	110	

RESULT: PASS

The results showed this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by KGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.ago-gett.com.




## RADIATED EMISSION TEST- (ABOVE 1GHz)-MIDDLE CHANNEL-HORIZONTAL



No	. Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
	-	MHz	dBu∀	dB/m	dBu∀/m	dBu∀/m	dB		cm	degree	
1		2441.000	86.95	10.36	97.31	114.00	-16.69	peak			
2	*	2441.000	79.01	10.36	89.37	94.00	-4.63	AVG	100	321	


**RESULT: PASS** 

The results showed this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.agc.gett.com.






## RADIATED EMISSION TEST- (ABOVE 1GHz)-MIDDLE CHANNEL- VERTICAL



No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
	-	MHz	dBu∀	dB/m	dBu∀/m	dBu∀/m	dB		cm	degree	
1		2441.000	86.48	10.36	96.84	114.00	-17.16	peak			
2	*	2441.000	78.47	10.36	88.83	94.00	-5.17	AVG	100	117	


**RESULT: PASS** 

The results shown in this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by 40°C, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.agc.gent.com.






## RADIATED EMISSION TEST- (ABOVE 1GHz)-HIGH CHANNEL-HORIZONTAL



No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
	-	MHz	dBu∀	dB/m	dBuV/m	dBu∀/m	dB		cm	degree	
1		2480.000	87.76	10.41	98.17	114.00	-15.83	peak			
2	*	2480.000	79.82	10.41	90.23	94.00	-3.77	AVG	100	324	


**RESULT: PASS** 

The results showing this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at a step www.agc.goalt.com.





## RADIATED EMISSION TEST- (ABOVE 1GHz)-HIGH CHANNEL- VERTICAL



N	lo.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		-	MHz	dBu∀	dB/m	dBu\//m	dBu∀/m	dB		cm	degree	
	1		2480.000	87.29	10.41	97.70	114.00	-16.30	peak			
	2	*	2480.000	79.30	10.41	89.71	94.00	-4.29	AVG	100	112	

## **RESULT: PASS**

Note: Factor=Antenna Factor + Cable loss - Amplifier gain, Margin=Measurement-Limit.

The "Factor" value can be calculated automatically by software of measurement system.



Page 30 of 65

## Field strength of the fundamental signal

## 3Mbps Result:

## Peak value

Frequency	Reading Level	Factor	Measurement	Limit	Over	Antenna	
(MHz)	(dBuv)	(dB/m)	(dBuv/m)	(dBuv/m)	(dB)	Polarization	
2402	85.91	10.32	96.23	114	-17.77	Horizontal	
2402	85.46	10.32	95.78	114	-18.22	Vertical	
2441	86.95	10.36	97.31	114	-16.69	Horizontal	
2441	86.48	10.36	96.84	114	-17.16	Vertical	
2480	87.76	10.41	98.17	114	-15.83	Horizontal	
2480	87.29	10.41	97.70	114	-16.30	Vertical	

## Average value

Frequency	Reading Level	Factor	Measurement	Limit	Over	Antenna	
(MHz)	(dBuv)	(dB/m)	(dBuv/m)	(dBuv/m)	(dB)	Polarization	
2402	77.97	10.32	88.29	94	-5.71	Horizontal	
2402	77.47	10.32	87.79	94	-6.21	Vertical	
2441	79.01	10.36	89.37	94	-4.63	Horizontal	
2441	78.47	10.36	88.83	94	-5.17	Vertical	
2480	79.82	10.41	90.23	94	-3.77	Horizontal	
2480	79.30	10.41	89.71	94	-4.29	Vertical	



Page 31 of 65

## 2Mbps Result:

#### Peak value

Frequency	Reading Level	Factor	Measurement	Limit	Over	Antenna	
(MHz)	(dBuv)	(dB/m)	(dBuv/m)	(dBuv/m)	(dB)	Polarization	
2402	85.49	10.32	95.81	114	-18.19	Horizontal	
2402	84.97	10.32	95.29	114	-18.71	Vertical	
2441	86.50	10.36	96.86	114	-17.14	Horizontal	
2441	86.05	10.36	96.41	114	-17.59	Vertical	
2480	87.28	10.41	97.69	114	-16.31	Horizontal	
2480	86.81	10.41	97.22	114	-16.78	Vertical	

## Average value

Frequency	Reading Level	Factor	Measurement	Limit	Over	Antenna
(MHz)	(dBuv)	(dB/m)	(dBuv/m)	(dBuv/m)	(dB)	Polarization
2402	77.53	10.32	87.85	94	-6.15	Horizontal
2402	77.07	10.32	87.39	94	-6.61	Vertical
2441	78.58	10.36	88.94	94	-5.06	Horizontal
2441	78.03	10.36	88.39	94	-5.61	Vertical
2480	79.33	10.41	89.74	94	-4.26	Horizontal
2480	78.84	10.41	89.25	94	-4.75	Vertical



Page 32 of 65

## 1Mbps Result:

#### Peak value

Frequency	Reading Level	Factor	Measurement	Limit	Over	Antenna
(MHz)	(dBuv)	(dB/m)	(dBuv/m)	(dBuv/m)	(dB)	Polarization
2402	85.08	10.32	95.40	114	-18.60	Horizontal
2402	84.57	10.32	94.89	114	-19.11	Vertical
2441	86.09	10.36	96.45	114	-17.55	Horizontal
2441	85.56	10.36	95.92	114	-18.08	Vertical
2480	86.79	10.41	97.20	114	-16.80	Horizontal
2480	86.40	10.41	96.81	114	-17.19	Vertical

## Average value

Frequency	Reading Level	Factor	Measurement	Limit	Over	Antenna
(MHz)	(dBuv)	(dB/m)	(dBuv/m)	(dBuv/m)	(dB)	Polarization
2402	77.04	10.32	87.36	94	-6.64	Horizontal
2402	76.66	10.32	86.98	94	-7.02	Vertical
2441	78.12	10.36	88.48	94	-5.52	Horizontal
2441	77.57	10.36	87.93	94	-6.07	Vertical
2480	78.91	10.41	89.32	94	-4.68	Horizontal
2480	78.38	10.41	88.79	94	-5.21	Vertical




age 33 of 65

## FOR BR/EDR

(Worst modulation: 8DPSK)


#### **For Harmonics**

## RADIATED EMISSION TEST- (ABOVE 1GHz)-LOW CHANNEL-HORIZONTAL




No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
	-	MHz	dBu∀	dB/m	dBu∀/m	dBu√/m	dB		cm	degree	
1		2200.000	33.65	10.10	43.75	74.00	-30.25	peak			
2		3808.333	30.94	14.01	44.95	74.00	-29.05	peak			
3	*	4804.000	42.21	7.69	49.90	74.00	-24.10	peak			

RESILIT. PASS





## RADIATED EMISSION TEST- (ABOVE 1GHz)-LOW CHANNEL- VERTICAL




No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
d	-	MHz	dBu∀	dB/m	dBu∀/m	dBu∀/m	dB		cm	degree	
1		2233.333	32.55	10.14	42.69	74.00	-31.31	peak			
2		3758.333	31.21	13.70	44.91	74.00	-29.09	peak			
3	*	4804.000	41.05	7.69	48.74	74.00	-25.26	peak			

**RESULT: PASS** 

The results showed the sample (s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.agc.gett.com.



## RADIATED EMISSION TEST- (ABOVE 1GHz)-MIDDLE CHANNEL-HORIZONTAL




No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
d	-	MHz	dBu∀	dB/m	dBuV/m	dBu∀/m	dB		cm	degree	
1		2158.333	33.08	10.05	43.13	74.00	-30.87	peak			
2		3850.000	31.03	14.27	45.30	74.00	-28.70	peak			
3	*	4882.000	42.66	7.89	50.55	74.00	-23.45	peak			

**RESULT: PASS** 

The results showed this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by 100°C, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at although the confirmed at although the confirmed at all the confirmed at



## RADIATED EMISSION TEST- (ABOVE 1GHz)-MIDDLE CHANNEL- VERTICAL




No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height		Comment
	-	MHz	dBu∀	dB/m	dBu∀/m	dBu∀/m	dB		cm	degree	
1		2125.000	33.23	10.02	43.25	74.00	-30.75	peak			
2		3741.667	30.93	13.60	44.53	74.00	-29.47	peak			
3	*	4882.000	39.89	7.89	47.78	74.00	-26.22	peak			

**RESULT: PASS** 

The results showed this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by 100°C, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at although the confirmed at although the confirmed at all the confirmed at



# RADIATED EMISSION TEST- (ABOVE 1GHz)-HIGH CHANNEL-HORIZONTAL




No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector _	Antenna Height	Table Degree	Comment
	-	MHz	dBu∀	dB/m	dBuV/m	dBu∀/m	dB		cm	degree	
1		2191.667	33.11	10.09	43.20	74.00	-30.80	peak			
2		3775.000	31.57	13.80	45.37	74.00	-28.63	peak			
3	*	4960.000	43.10	8.09	51.19	74.00	-22.81	peak			-

DECILIT: DACC

The results showed this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by 100°C, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at although the confirmed at although the confirmed at all the confirmed at



# RADIATED EMISSION TEST- (ABOVE 1GHz)-HIGH CHANNEL- VERTICAL



No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
	-	MHz	dBu∀	dB/m	dBu∀/m	dBu∀/m	dB		cm	degree	
1		2191.667	32.67	10.09	42.76	74.00	-31.24	peak			
2		3783.333	30.63	13.86	44.49	74.00	-29.51	peak			
3	*	4960.000	41.91	8.09	50.00	74.00	-24.00	peak			

## **RESULT: PASS**

Note: 6~25GHz at least have 20dB margin. No recording in the test report.

Factor=Antenna Factor + Cable loss - Amplifier gain, Margin=Measurement-Limit.

The "Factor" value can be calculated automatically by software of measurement system.

The results spowford this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by XOC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.ago.go.tt.com.



### 10. BAND EDGE EMISSION


### 10.1. MEASUREMENT PROCEDURE

- The EUT operates at hopping-off test mode. The lowest or highest channels are tested to verify the largest transmission and spurious emissions power at the continuous transmission mode.
- 2. Max hold the trace of the setup 1, and the EUT operates at hopping-on test mode to verify the largest spurious emissions power.
- 3. Set the spectrum analyzer in the following setting in order to capture the lower and upper band-edges of the emission.

	Start frequenc	y(MHz)		Stop frequency(MHz)				
	2200	Kingliance	The Compilers	© A station	2405	100°		
8 F.	2478	Global Co	attestation of Glob	-,0 "	2500			

#### **10.2 TEST SETUP**

## RADIATED EMISSION TEST SETUP



The results spowford this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by XOC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.ago.go.tt.com.





Page 40 of 65



# **10.3 RADIATED TEST RESULT**

## FOR BR/EDR

(Worst modulation: 8DPSK)

### TEST PLOT OF BAND EDGE FOR LOW CHANNEL-Horizontal



No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
	-	MHz	dBu∀	dB/m	dBu∀/m	dBu∀/m	dB		cm	degree	
1		2350.675	32.69	10.27	42.96	74.00	-31.04	peak			
2		2390.000	33.00	10.31	43.31	74.00	-30.69	peak			
3		2400.000	41.97	10.32	52.29	74.00	-21.71	peak			
4	*	2402.000	85.94	10.32	96.26	74.00	22.26	peak			
5	Х	2402.000	78.00	10.32	88.32	74.00	14.32	AVG	100	151	

The results spowth this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.agc.gott.com.




## TEST PLOT OF BAND EDGE FOR LOW CHANNEL -Vertical




No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
	-	MHz	dBu∀	dB/m	dBu∀/m	dBu√/m	dB		cm	degree	
1		2353.750	31.83	10.27	42.10	74.00	-31.90	peak			
2		2390.000	31.21	10.31	41.52	74.00	-32.48	peak			
3		2400.000	41.06	10.32	51.38	74.00	-22.62	peak			
4	*	2402.000	85.48	10.32	95.80	74.00	21.80	peak			
5	Х	2402.000	77.43	10.32	87.75	74.00	13.75	AVG	100	323	

The results showed this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGE, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.agc.gett.com.






# TEST PLOT OF BAND EDGE FOR HIGH CHANNEL -Horizontal




No.	). N	Иk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		. [	MHz	dBu∀	dB/m	dBu\//m	dBu∀/m	dB		cm	degree	
1		*	2480.000	87.79	10.41	98.20	74.00	24.20	peak			
2	: 2	Х	2480.000	79.79	10.41	90.20	74.00	16.20	AVG	100	153	
3			2483.500	34.19	10.41	44.60	74.00	-29.40	peak			
4			2487.973	34.13	10.42	44.55	74.00	-29.45	peak			

The results spowth this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.agc.gott.com.





# TEST PLOT OF BAND EDGE FOR HIGH CHANNEL-Vertical



No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height		Comment
	-	MHz	dBu∀	dB/m	dBu∀/m	dBu∀/m	dB		cm	degree	
1	*	2480.000	87.32	10.41	97.73	74.00	23.73	peak			
2	Х	2480.000	79.27	10.41	89.68	74.00	15.68	AVG	100	326	
3		2483.500	33.76	10.41	44.17	74.00	-29.83	peak			
4		2488.377	33.71	10.42	44.13	74.00	-29.87	peak			

### **RESULT: PASS**

Note: Factor=Antenna Factor + Cable loss - Amplifier gain, Over=Measure-Limit.

The "Factor" value can be calculated automatically by software of measurement system.

Hopping on mode and Hopping off mode have been tested, but only worst case reported.

The results spowford this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by XOC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.ago.go.tt.com.




## 11. 20DB BANDWIDTH

### 11.1. MEASUREMENT PROCEDURE

- 1. Set the EUT Work on the top, the middle and the bottom operation frequency individually.
- 2. Set Span = approximately 2 to 3 times the 20 dB bandwidth, centered on a hoping channel RBW ≥ 1% of the 20 dB bandwidth, VBW ≥ 3RBW; Sweep = auto; Detector function = peak
- 3. Set SPA Trace 1 Max hold, then View.

### 11.2. TEST SET-UP




# 11.3. LIMITS AND MEASUREMENT RESULTS

#### FOR BR/EDR


BLUETO	OOTH 1MBPS LIN	MITS AND MEASU	REMENT RESULT						
	Measurement Result								
Applicable Limits		Result							
		99%OBW (MHz)	-20dB BW(MHz)	Result					
Stoke Company	Low Channel	0.944	1.083	PASS					
N/A	Middle Channel	0.940	1.078	PASS					
1111	High Channel	0.956	1.087	PASS					

The results spowford this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.agc.gent.com.






#### TEST PLOT OF BANDWIDTH FOR LOW CHANNEL




#### TEST PLOT OF BANDWIDTH FOR MIDDLE CHANNEL



The results spowford this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.agc.gent.com.



#### TEST PLOT OF BANDWIDTH FOR HIGH CHANNEL




The results spoured this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by XOC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.ago.go.tt.com.



BLUETO	OOTH 2MBPS LIN	MITS AND MEASU	REMENT RESULT		
		Measure	ement Result		
Applicable Limits		Dogult			
		99%OBW (MHz)	-20dB BW(MHz)	Result	
The plane of the plane	Low Channel	1.229	1.382	PASS	
N/A	Middle Channel	1.231	1.393	PASS	
	High Channel	1.234	1.377	PASS	


### TEST PLOT OF BANDWIDTH FOR LOW CHANNEL




The results spound this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by XCC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at a true www.ago.gent.com.



#### TEST PLOT OF BANDWIDTH FOR MIDDLE CHANNEL



#### TEST PLOT OF BANDWIDTH FOR HIGH CHANNEL




The results spowford this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by XOC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.ago.go.tt.com.



BLUETO	OOTH 3MBPS LIN	MITS AND MEASU	REMENT RESULT	30N (09Y)	
			ement Result		
Applicable Limits					
		99%OBW (MHz)	-20dB BW(MHz)	Result	
玉 拉	Low Channel	1.232	1.395	PASS	
N/A	Middle Channel	1.232	1.400	PASS	
	High Channel	1.236	1.386	PASS	


### TEST PLOT OF BANDWIDTH FOR LOW CHANNEL




The results spound this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by XCC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.ago.go.tt.com.



#### TEST PLOT OF BANDWIDTH FOR MIDDLE CHANNEL



#### TEST PLOT OF BANDWIDTH FOR HIGH CHANNEL



The results spowford this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by XOC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.ago.go.tt.com.



# 12. FCC LINE CONDUCTED EMISSION TEST


## 12.1. LIMITS OF LINE CONDUCTED EMISSION TEST

F	Maximum RF	Maximum RF Line Voltage							
Frequency	Q.P.( dBuV)	Average( dBuV)							
150kHz~500kHz	66-56	56-46							
500kHz~5MHz	56	46							
5MHz~30MHz	60	50							

#### Note:

- 1. The lower limit shall apply at the transition frequency.
- 2. The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz

### 12.2. BLOCK DIAGRAM OF LINE CONDUCTED EMISSION TEST



The results spound this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by XCC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.ago.go.tt.com.



Report No.: AGC00275180602FE03

Page 52 of 65

#### 12.3. PRELIMINARY PROCEDURE OF LINE CONDUCTED EMISSION TEST

- 1. The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. When the EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.10 (see Test Facility for the dimensions of the ground plane used). When the EUT is a floor-standing equipment, it is placed on the ground plane which has a 3-12 mm non-conductive covering to insulate the EUT from the ground plane.
- 2. Support equipment, if needed, was placed as per ANSI C63.10.
- 3. All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10.
- 4. All support equipments received AC120V/60Hz power from a LISN, if any.
- 5. The EUT received DC charging voltage by adapter or PC which received 120V/60Hzpower by a LISN.
- 6. The test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
- 7. Analyzer / Receiver scanned from 150 kHz to 30MHz for emissions in each of the test modes.
- 8. During the above scans, the emissions were maximized by cable manipulation.
- 9. The test mode(s) were scanned during the preliminary test.

Then, the EUT configuration and cable configuration of the above highest emission level were recorded for reference of final testing.

### 12.4. FINAL PROCEDURE OF LINE CONDUCTED EMISSION TEST

- EUT and support equipment was set up on the test bench as per step 2 of the preliminary test.
- 2. A scan was taken on both power lines, Line 1 and Line 2, recording at least the six highest emissions. Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit. If EUT emission level was less –2dB to the A.V. limit in Peak mode, then the emission signal was re-checked using Q.P and Average detector.
- 3. The test data of the worst case condition(s) was reported on the Summary Data page.

The results spound this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by XCC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at a trp://www.ago.go.tt.com.




## 12.5. TEST RESULT OF LINE CONDUCTED EMISSION TEST

## By adapter(worst case)

### FOR BR/EDR

### Line Conducted Emission Test Line 1-L



#### MEASUREMENT RESULT:

Frequency MHz	Level dBuV	Transd dB	Limit dBuV	Margin dB	Detector	Line	PE
0.422000	33.10	10.1	57	24.3	QP	L1	FLO
1.974000	33.50	10.2	56	22.5	QP	L1	FLO
2.922000	39.00	9.9	56	17.0	QP	L1	FLO
3.890000	39.60	10.1	56	16.4	QP	L1	FLO
4.410000	35.40	10.2	56	20.6	QP	L1	FLO
5.374000	42.20	10.3	60	17.8	QP	L1	FLO


#### MEASUREMENT RESULT:

Frequency MHz	Level dBuV	Transd dB	Limit dBuV	Margin dB	Detector	Line	PE
0.418000	20.60	10.1	48	26.9	AV	L1	FLO
1.966000	28.30	10.2	46	17.7	AV	L1	FLO
2.922000	31.30	9.9	46	14.7	AV	L1	FLO
3.890000	26.00	10.1	46	20.0	AV	L1	FLO
4.398000	22.40	10.2	46	23.6	AV	L1	FLO
5.370000	23.70	10.3	50	26.3	AV	L1	FLO

The results spowth this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.agc.gott.com.



### Line Conducted Emission Test Line 2-N



#### MEASUREMENT RESULT:

Frequency MHz	Level dBuV	Transd dB	Limit dBuV	Margin dB	Detector	Line	PE
0.286000 0.422000 0.694000 1.002000 1.958000 5.374000	35.40 36.50 33.70 33.50 37.50 43.30	10.1 10.1 10.1 10.2 10.2 10.3	61 57 56 56 56	25.2 20.9 22.3 22.5 18.5 16.7	QP QP QP	N N N N N	FLO FLO FLO FLO FLO

#### MEASUREMENT RESULT:

Frequency MHz	Level dBuV	Transd dB	Limit dBuV	Margin dB	Detector	Line	PE
0.286000 0.426000 0.634000 0.974000 1.946000 5.390000	22.50 18.50 18.10 24.40 27.00 26.20	10.1 10.1 10.2 10.2 10.2	51 47 46 46 46 50	28.1 28.8 27.9 21.6 19.0 23.8	AV AV AV AV AV	N N N N N	FLO FLO FLO FLO FLO

The results showed this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.agc-gett.com.



# APPENDIX A: PHOTOGRAPHS OF TEST SETUP

FCC LINE CONDUCTED EMISSION TEST SETUP




FCC RADIATED EMISSION TEST SETUP




The results showed this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.agc.go.tt.com.


Attestation of Global Compliance







The results shown this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at a type AGC.








The results shown this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by (60°, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at http://www.agc.gett.com.

Attestation of Global Compliance




## **APPENDIX B: PHOTOGRAPHS OF EUT**

TOTAL VIEW OF EUT



TOP VIEW OF EUT



The results spowfor this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attr://www.agc.gett.com.


Attestation of Global Compliance



## **BOTTOM VIEW OF EUT**



FRONT VIEW OF EUT



The results showed this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.agc.gett.com.


Attestation of Global Compliance



# **BACK VIEW OF EUT**



**LEFT VIEW OF EUT** 



The results showed this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.agc.gett.com.

Attestation of Global Compliance



# RIGHT VIEW OF EUT



**VIEW OF EUT (PORT)** 



The results shown this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.agc.gett.com.

Attestation of Global Compliance



# **OPEN VIEW OF EUT**



VIEW OF BATTERY




The results spowd this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attr://www.agc-gent.com.


Attestation of Global Compliance



# **INTERNAL VIEW OF EUT-1**



#### **INTERNAL VIEW OF EUT-2**




The results spound this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by (GC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at a titp://www.agc.gatt.com.


Attestation of Global Compliance



# **INTERNAL VIEW OF EUT-3**



**INTERNAL VIEW OF EUT-4** 




The results showing this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at a true; //www.agc.gott.com.

Attestation of Global Compliance



# **INTERNAL VIEW OF EUT-5**



VIEW OF ADAPTER(AE)



The adapter was supplied by AGC

## ----END OF REPORT----

The results showed this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attr://www.agc.cett.com.

Attestation of Global Compliance