

FCC§1.1307 (b) (1) & §2.1091& RSS-102 - MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Applicable Standard

According to subpart 1.1307 (b)(1), 2.1091 systems operating under the provisions of this section shall be operated in a manner that ensures the public is not exposed to RF energy level in excess of the communication guidelines.

FCC Limits for Maximum Permissible Exposure (MPE)

(A) Limits for Occupational/Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842/f	4.89/f	(900/f ²)*	6
30-300	61.4	0.163	1.0	6
300-1500	--	--	f/300	6
1500-100,000	--	--	5	6

(B) Limits for General Population/Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f ²)*	30
30-300	27.5	0.073	0.2	30
300-1500	--	--	f/1500	30
1500-100,000	--	--	1.0	30

f = frequency in MHz *Plane-wave equivalent power density

According to RSS-102:

4.2 RF Field Strength Limits for Devices Used by the General Public (Uncontrolled Environment)

Frequency Range (MHz)	Electric Field (V/m rms)	Magnetic Field (A/m rms)	Power Density (W/m ²)	Averaging Time (minutes)
0.003-1	280	2.19	-	6
1-10	280/ f	2.19/ f	-	6
10-30	28	2.19/ f	-	6
30-300	28	0.073	2*	6
300-1500	1.585 $f^{0.5}$	0.0042 $f^{0.5}$	$f/150$	6
1500-15000	61.4	0.163	10	6
15000-150000	61.4	0.163	10	616000/ $f^{1.2}$
150000-300000	0.158 $f^{0.5}$	4.21 x 10 ⁻⁴ $f^{0.5}$	6.67 x 10 ⁻⁵ f	616000/ $f^{1.2}$

Note: f is frequency in MHz.

* Power density limit is applicable at frequencies greater than 100 MHz.

4.4 RF Field Strength Limits for Controlled Use Devices (Controlled Environment)

Frequency Range (MHz)	Electric Field (V/m rms)	Magnetic Field (A/m rms)	Power Density (W/m ²)	Averaging Time (minutes)
0.003-1	600	4.9	-	6
1-10	600/ f	4.9/ f	-	6
10-30	60	4.9/ f	-	6
30-300	60	0.163	10*	6
300-1500	3.54 $f^{0.5}$	0.0094 $f^{0.5}$	$f/30$	6
1500-15000	137	0.364	50	6
15000-150000	137	0.364	50	616000/ $f^{1.2}$
150000-300000	0.354 $f^{0.5}$	9.4 x 10 ⁻⁴ $f^{0.5}$	3.33 x 10 ⁻⁴ f	616000/ $f^{1.2}$

Note: f is frequency in MHz.

*Power density limit is applicable at frequencies greater than 100 MHz.

Result**Calculated Formulary:**

Predication of MPE limit at a given distance

$$S = \frac{PG}{4\pi R^2}$$

S = power density (in appropriate units, e.g. mW/cm² for FCC, and W/m² for IC)

P = power input to the antenna (in appropriate units, e.g., mW for FCC, and W for IC).

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain.

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm for FCC, and m for IC)

For FCC calculation:

Frequency (MHz)	Antenna Gain		Conducted Power (W)	The minimum Distance (m)	Calculated RF Exposure (mW/cm ²)	MPE Limit (mW/cm ²)	Note
	(dBi)	(numeric)					
156.8	3	2	25	1.5	0.1769	1.0	Controlled Environment
156.8	3	2	25	1.5	0.1769	0.2	UnControlled Environment

For IC calculation:

Frequency (MHz)	Antenna Gain		Conducted Power (W)	The minimum Distance (m)	Calculated RF Exposure (W/m ²)	MPE Limit (W/m ²)	Note
	(dBi)	(numeric)					
156.8	3	2	25	1.5	1.769	10	Controlled Environment
156.8	3	2	25	1.5	1.769	2.0	UnControlled Environment

Note: The Maximum power is 25 W which declared by manufacture

Radiation Exposure Statement:

To comply with RF exposure requirements, the minimum permissible distance is 1.5 m required between the antenna and the body of the user or nearby persons.

Result: Compliance