

FCC EMC Test Report

Applicant: TECNO MOBILE LIMITED

Address of Applicant: FLAT N 16/F BLOCK B UNIVERSAL INDUSTRIAL CENTRE
19-25 SHAN MEI STREET FOTAN NT HONGKONG

Equipment Under Test (EUT)

Product Name: Mobile Phone

Model No.: AD10

Trade Mark: TECNO

FCC ID: 2ADYY-AD10

Applicable Standards: FCC CFR Title 47 Part 15B

Date of Sample Receipt: 29 Oct., 2022

Date of Test: 30 Oct., to 05 Dec., 2022

Date of report Issued: 06 Dec., 2022


Test Result: PASS

Tested by:
Test Engineer**Date:**

06 Dec., 2022

Reviewed by:
Project Engineer**Date:**

06 Dec., 2022

Approved by:
Manager**Date:**

06 Dec., 2022

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in above the application standard version. Test results reported herein relate only to the item(s) tested.

This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

1 Version

Version No.	Date	Description
00	06 Dec., 2022	Original

2 Contents

	Page
Cover Page	1
1 Version	2
2 Contents.....	3
3 General Information.....	4
3.1 Client Information	4
3.2 General Description of E.U.T.	4
3.3 Test Mode	4
3.4 Description of Test Auxiliary Equipment	5
3.5 Description of Cable Used.....	5
3.6 Measurement Uncertainty	5
3.7 Additions to, Deviations, or Exclusions from the Method	5
3.8 Laboratory Facility	5
3.9 Laboratory Location.....	5
3.10 Test Instruments List.....	6
4 Measurement Setup and Procedure	7
4.1 Test Setup	7
4.2 Test Procedure	9
5 Test Results.....	10
5.1 Summary	10
5.1.1 Clause and data summary	10
5.1.2 Test Limit.....	10
5.2 Conducted Emission	11
5.3 Radiated Emission	15

3 General Information

3.1 Client Information

Applicant:	TECNO MOBILE LIMITED
Address:	FLAT N 16/F BLOCK B UNIVERSAL INDUSTRIAL CENTRE 19-25 SHAN MEI STREET FOTAN NT HONGKONG
Manufacturer:	TECNO MOBILE LIMITED
Address:	FLAT N 16/F BLOCK B UNIVERSAL INDUSTRIAL CENTRE 19-25 SHAN MEI STREET FOTAN NT HONGKONG
Factory:	SHENZHEN TECNO TECHNOLOGY CO., LTD.
Address:	101, Building 24, Waijing Industrial Park, Fumin Community, Fucheng Street, Longhua District, Shenzhen City, P.R.China

3.2 General Description of E.U.T.

Product Name:	Mobile Phone
Model No.:	AD10
Power Supply:	Rechargeable Li-ion Polymer Battery DC3.89V, 2550mAh & Rechargeable Li-ion Polymer Battery DC3.89V, 2310mAh
AC Adapter:	Model: U450TSA Input: AC100-240V, 50/60Hz, 1.8A Output: DC 5.0V, 2.0A or DC 11.0V, 4.1A MAX
Test Sample Condition:	The test samples were provided in good working order with no visible defects.

3.3 Test Mode

Operating Mode	Detail Description
PC mode	Keep the EUT in Downloading mode(Worst case)
Charging+Recording mode	Keep the EUT in Charging+Recording mode
Charging+Playing mode	Keep the EUT in Charging+Playing mode
FM mode	Keep the EUT in FM receiver mode
GPS mode	Keep the EUT in GPS receiver mode

The sample was placed 0.8m above the ground plane of 3m chamber. Measurements in both horizontal and vertical polarities were performed. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, rotating the turntable, varying antenna height from 1m to 4m in both horizontal and vertical polarizations. The emissions worst-case are shown in Test Results of the following pages.

3.4 Description of Test Auxiliary Equipment

Manufacturer	Description	Model	S/N	FCC ID/DoC
Lenovo	Laptop	ThinkPad T14 Gen 1	SL10Z47277	DoC
HP	Printer	HP LaserJet P1007	VNFP409729	DoC

3.5 Description of Cable Used

Cable Type	Description	Length	From	To
Detached USB Cable	Shielding	1.0m	EUT	PC/Adapter
Detached headset cable	Unshielded	1.2m	EUT	Headset

3.6 Measurement Uncertainty

Parameter	Expanded Uncertainty (Confidence of 95%(U = 2Uc(y)))
Conducted Emission for LISN (9kHz ~ 10MHz)	1.9 dB
Conducted Emission for LISN (10MHz ~ 30MHz)	2.6 dB
Radiated Emission (30MHz ~ 1GHz) (3m SAC)	3.8 dB
Radiated Emission (1GHz ~ 18GHz) (3m SAC)	3.6 dB

Note: All the measurement uncertainty value were shown with a coverage $k=2$ to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

3.7 Additions to, Deviations, or Exclusions from the Method

No

3.8 Laboratory Facility

The test facility is recognized, certified, or accredited by the following organizations:

● **FCC - Designation No.: CN1211**

JianYan Testing Group Shenzhen Co., Ltd. has been accredited as a testing laboratory by FCC(Federal Communications Commission). The test firm Registration No. is 727551.

● **ISED – CAB identifier.: CN0021**

The 3m Semi-anechoic chamber and 10m Semi-anechoic chamber of JianYan Testing Group Shenzhen Co., Ltd. has been Registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 10106A-1.

● **CNAS - Registration No.: CNAS L15527**

JianYan Testing Group Shenzhen Co., Ltd. is accredited to ISO/IEC 17025:2017 General Requirements for the Competence of Testing and Calibration laboratories for the competence of testing. The Registration No. is CNAS L15527.

● **A2LA - Registration No.: 4346.01**

This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2017 General requirements for the competence of testing and calibration laboratories. The test scope can be found as below link: <https://portal.a2la.org/scopepdf/4346-01.pdf>

3.9 Laboratory Location

JianYan Testing Group Shenzhen Co., Ltd.

Address: No.101, Building 8, Innovation Wisdom Port, No.155 Hongtian Road, Huangpu Community, Xinqiao Street, Bao'an District, Shenzhen, Guangdong, People's Republic of China.

Tel: +86-755-23118282, Fax: +86-755-23116366

Email: info-JYTee@lets.com, Website: <http://jyt.lets.com>

3.10 Test Instruments List


Radiated Emission(3m SAC):					
Test Equipment	Manufacturer	Model No.	Manage No.	Cal. Date (mm-dd-yy)	Cal. Due date (mm-dd-yy)
3m SAC	ETS	9m*6m*6m	WXJ001-1	04-14-2021	04-13-2024
BiConiLog Antenna	Schwarzbeck	VULB9163	WXJ002	03-08-2022	03-07-2023
Horn Antenna	Schwarzbeck	BBHA9120D	WXJ002-2	03-08-2022	03-07-2023
Pre-amplifier (30MHz ~ 1GHz)	Schwarzbeck	BBV9743B	WXJ001-2	01-20-2022	01-19-2023
Pre-amplifier (1GHz ~ 18GHz)	SKET	LNPA_0118G-50	WXJ001-3	01-20-2022	01-19-2023
EMI Test Receiver	Rohde & Schwarz	ESRP7	WXJ003-1	03-05-2022	03-04-2023
Spectrum Analyzer	Rohde & Schwarz	FSP 30	WXJ004	01-20-2022	01-19-2023
Coaxial Cable (30MHz ~ 1GHz)	JYTSZ	JYT3M-1G-NN-8M	WXG001-4	01-20-2022	01-19-2023
Coaxial Cable (1GHz ~ 18GHz)	JYTSZ	JYT3M-18G-NN-8M	WXG001-5	01-20-2022	01-19-2023
Band Reject Filter Group	Tonscend	JS0806-F	WXJ089	N/A	
Test Software	Tonscend	TS+	Version: 3.0.0.1		

Conducted Emission:					
Test Equipment	Manufacturer	Model No.	Manage No.	Cal. Date (mm-dd-yy)	Cal. Due date (mm-dd-yy)
EMI Test Receiver	Rohde & Schwarz	ESR3	WXJ003-2	07-12-2022	07-11-2023
LISN	Schwarzbeck	NSLK 8127	QCJ001-13	02-24-2022	02-23-2023
LISN	Rohde & Schwarz	ESH3-Z5	WXJ005-1	03-30-2022	03-29-2023
LISN Coaxial Cable (9kHz ~ 30MHz)	JYTSZ	JYTCE-1G-NN-2M	WXG003-1	02-24-2022	02-23-2023
RF Switch	TOP PRECISION	RSU0301	WXG003	N/A	
Test Software	AUDIX	E3	Version: 6.110919b		

4 Measurement Setup and Procedure

4.1 Test Setup


1) Conducted emission measurement:




Note: The detailed descriptions please refer to Figure 8 of ANSI C63.4:2014.

2) Radiated emission measurement:

Below 1GHz (3m SAC)





4.2 Test Procedure

Test method	Test step
Conducted emission	1. The E.U.T and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm/50uH coupling impedance for the measuring equipment. 2. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refer to the block diagram of the test setup and photographs). 3. Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.4 on conducted measurement.
Radiated emission	For below 1GHz: 1. The EUT was placed on the tabletop of a rotating table 0.8 m the ground at a 3 m semi anechoic chamber. The measurement distance from the EUT to the receiving antenna is 3 m. 2. EUT works in each mode of operation that needs to be tested, and having the EUT continuously working, respectively on 3 axis (X, Y & Z) and considered typical configuration to obtain worst position. The highest signal levels relative to the limit shall be determined by rotating the EUT from 0° to 360° and with varying the measurement antenna height between 1 m and 4 m in vertical and horizontal polarizations. 3. Open the test software to control the test antenna and test turntable. Perform the test, save the test results, and export the test data. For above 1GHz: 1. The EUT was placed on the tabletop of a rotating table 0.8 m the ground at a 3 m fully anechoic room. The measurement distance from the EUT to the receiving antenna is 3 m. 2. EUT works in each mode of operation that needs to be tested, and having the EUT continuously working, respectively on 3 axis (X, Y & Z) and considered typical configuration to obtain worst position. The highest signal levels relative to the limit shall be determined by rotating the EUT from 0° to 360° and with varying the measurement antenna height between 1 m and 4 m in vertical and horizontal polarizations. 3. Open the test software to control the test antenna and test turntable. Perform the test, save the test results, and export the test data.

5 Test Results

5.1 Summary

5.1.1 Clause and data summary

Test items	Standard clause	Test data	Result
Conducted Emission	Part 15.107	See Section 5.2	Pass
Radiated Emission	Part 15.109	See Section 5.3	Pass
Remark: 1. The EUT is a Class B digital device. 2. Pass: The EUT complies with the essential requirements in the standard.			
Test Method:	ANSI C63.4:2014		


5.1.2 Test Limit

Test items	Limit																													
Conducted Emission	<table><tr><th rowspan="2">Frequency (MHz)</th><th colspan="2">Class A Limit (dBμV)</th><th colspan="2">Class B Limit (dBμV)</th></tr><tr><th>Quasi-Peak</th><th>Average</th><th>Quasi-Peak</th><th>Average</th></tr><tr><td>0.15 – 0.5</td><td>79</td><td>66</td><td>66 to 56 Note 1</td><td>56 to 46 Note 1</td></tr><tr><td>0.5 – 5</td><td>73</td><td>60</td><td>56</td><td>46</td></tr><tr><td>5 – 30</td><td>73</td><td>60</td><td>60</td><td>50</td></tr></table>	Frequency (MHz)	Class A Limit (dBμV)		Class B Limit (dBμV)		Quasi-Peak	Average	Quasi-Peak	Average	0.15 – 0.5	79	66	66 to 56 Note 1	56 to 46 Note 1	0.5 – 5	73	60	56	46	5 – 30	73	60	60	50					
	Frequency (MHz)		Class A Limit (dBμV)		Class B Limit (dBμV)																									
		Quasi-Peak	Average	Quasi-Peak	Average																									
	0.15 – 0.5	79	66	66 to 56 Note 1	56 to 46 Note 1																									
	0.5 – 5	73	60	56	46																									
	5 – 30	73	60	60	50																									
Note 1: The limit level in dBμV decreases linearly with the logarithm of frequency.																														
Note 2: The more stringent limit applies at transition frequencies.																														
Radiated Emission	<table><tr><th rowspan="2">Frequency (MHz)</th><th colspan="2">Class A Limit (dBμV/m)</th><th colspan="2">Class B Limit (dBμV/m)</th></tr><tr><th>Quasi-Peak @ 3m</th><th>Quasi-Peak @ 10m</th><th>Quasi-Peak @ 3m</th><th>Quasi-Peak @ 10m</th></tr><tr><td>30 – 88</td><td>49.0</td><td>39.0</td><td>40.0</td><td>30.0</td></tr><tr><td>88 – 216</td><td>53.5</td><td>43.5</td><td>43.5</td><td>33.5</td></tr><tr><td>216 – 960</td><td>56.0</td><td>46.0</td><td>46.0</td><td>36.0</td></tr><tr><td>960 – 1000</td><td>60.0</td><td>50.0</td><td>54.0</td><td>44.0</td></tr></table>	Frequency (MHz)	Class A Limit (dBμV/m)		Class B Limit (dBμV/m)		Quasi-Peak @ 3m	Quasi-Peak @ 10m	Quasi-Peak @ 3m	Quasi-Peak @ 10m	30 – 88	49.0	39.0	40.0	30.0	88 – 216	53.5	43.5	43.5	33.5	216 – 960	56.0	46.0	46.0	36.0	960 – 1000	60.0	50.0	54.0	44.0
	Frequency (MHz)		Class A Limit (dBμV/m)		Class B Limit (dBμV/m)																									
		Quasi-Peak @ 3m	Quasi-Peak @ 10m	Quasi-Peak @ 3m	Quasi-Peak @ 10m																									
	30 – 88	49.0	39.0	40.0	30.0																									
	88 – 216	53.5	43.5	43.5	33.5																									
	216 – 960	56.0	46.0	46.0	36.0																									
	960 – 1000	60.0	50.0	54.0	44.0																									
	Note: The more stringent limit applies at transition frequencies.																													
	<table><tr><th rowspan="2">Frequency</th><th colspan="2">Class A Limit (dBμV/m) @ 3m</th><th colspan="2">Class B Limit (dBμV/m) @ 3m</th></tr><tr><th>Average</th><th>Peake</th><th>Average</th><th>Peake</th></tr><tr><td>Above 1 GHz</td><td>60.0</td><td>80.0</td><td>54.0</td><td>74.0</td></tr></table>	Frequency	Class A Limit (dBμV/m) @ 3m		Class B Limit (dBμV/m) @ 3m		Average	Peake	Average	Peake	Above 1 GHz	60.0	80.0	54.0	74.0															
	Frequency		Class A Limit (dBμV/m) @ 3m		Class B Limit (dBμV/m) @ 3m																									
Average		Peake	Average	Peake																										
Above 1 GHz	60.0	80.0	54.0	74.0																										
Note: The measurement bandwidth shall be 1 MHz or greater.																														

5.2 Conducted Emission

Unfold:

Product name:	Mobile Phone	Product model:	AD10
Test by:	Mike	Test mode:	PC mode
Test frequency:	150 kHz ~ 30 MHz	Phase:	Line
Test voltage:	AC 120 V/60 Hz		




	Freq	Read Level	LISN Factor	Cable Loss	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dB	dBuV	dBuV	dB	
1	0.158	23.33	0.04	0.01	33.88	55.56	-21.68	Average
2	0.158	44.02	0.04	0.01	54.57	65.56	-10.99	QP
3	0.206	22.03	0.05	0.04	32.62	53.36	-20.74	Average
4	0.238	33.93	0.05	0.02	44.50	62.17	-17.67	QP
5	0.494	12.64	0.05	0.03	23.22	46.10	-22.88	Average
6	3.985	11.49	0.11	0.08	22.18	46.00	-23.82	Average
7	4.049	23.33	0.11	0.08	34.02	56.00	-21.98	QP
8	10.963	26.08	0.24	0.11	36.93	60.00	-23.07	QP
9	11.021	17.65	0.24	0.11	28.50	50.00	-21.50	Average
10	15.066	14.50	0.29	0.14	25.43	50.00	-24.57	Average
11	15.066	23.55	0.29	0.14	34.48	60.00	-25.52	QP
12	22.063	21.03	0.36	0.16	32.05	60.00	-27.95	QP

Remark:

1. Level = Read level + LISN Factor + Cable Loss.

Product name:	Mobile Phone	Product model:	AD10
Test by:	Mike	Test mode:	PC mode
Test frequency:	150 kHz ~ 30 MHz	Phase:	Neutral
Test voltage:	AC 120 V/60 Hz		




	Freq	Read Level	LISN Factor	Cable Loss	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dB	dBuV	dBuV	dB	
1	0.158	43.26	0.06	0.01	53.83	65.56	-11.73	QP
2	0.194	37.52	0.05	0.03	48.10	63.84	-15.74	QP
3	0.198	26.36	0.05	0.04	36.95	53.71	-16.76	Average
4	0.274	23.67	0.05	0.02	34.24	50.98	-16.74	Average
5	0.410	20.12	0.04	0.04	30.70	47.64	-16.94	Average
6	1.480	14.50	0.07	0.14	25.21	46.00	-20.79	Average
7	4.384	25.25	0.10	0.08	35.93	56.00	-20.07	QP
8	5.993	26.18	0.14	0.09	36.91	60.00	-23.09	QP
9	6.024	14.45	0.14	0.09	25.18	50.00	-24.82	Average
10	15.226	12.44	0.27	0.14	23.35	50.00	-26.65	Average
11	15.226	21.24	0.27	0.14	32.15	60.00	-27.85	QP
12	22.535	19.53	0.37	0.16	30.56	60.00	-29.44	QP

Remark:

1. Level = Read level + LISN Factor + Cable Loss.

Fold:

Product name:	Mobile Phone	Product model:	AD10
Test by:	Mike	Test mode:	PC mode
Test frequency:	150 kHz ~ 30 MHz	Phase:	Line
Test voltage:	AC 120 V/60 Hz		




Trace: 43

	Freq	Read Level	LISN Factor	Cable Loss	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dB	dBuV	dBuV	dB	
1	0.162	28.43	0.04	0.01	38.98	55.34	-16.36	Average
2	0.162	41.06	0.04	0.01	51.61	65.34	-13.73	QP
3	0.198	36.06	0.05	0.04	46.65	63.71	-17.06	QP
4	0.219	21.89	0.05	0.03	32.47	52.88	-20.41	Average
5	0.494	16.62	0.05	0.03	27.20	46.10	-18.90	Average
6	1.725	16.30	0.08	0.18	27.06	56.00	-28.94	QP
7	3.922	22.74	0.11	0.08	33.43	56.00	-22.57	QP
8	4.224	10.60	0.11	0.08	21.29	46.00	-24.71	Average
9	10.847	15.77	0.23	0.12	26.62	50.00	-23.38	Average
10	11.198	25.64	0.24	0.11	36.49	60.00	-23.51	QP
11	14.907	23.07	0.29	0.14	34.00	60.00	-26.00	QP
12	14.986	13.94	0.29	0.14	24.87	50.00	-25.13	Average

Remark:

1. Level = Read level + LISN Factor + Cable Loss.

Product name:	Mobile Phone	Product model:	AD10
Test by:	Mike	Test mode:	PC mode
Test frequency:	150 kHz ~ 30 MHz	Phase:	Neutral
Test voltage:	AC 120 V/60 Hz		



	Freq	Read Level	LISN Factor	Cable Loss	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dB	dBuV	dBuV	dB	
1	0.162	42.56	0.06	0.01	53.13	65.34	-12.21	QP
2	0.166	29.19	0.06	0.01	39.76	55.16	-15.40	Average
3	0.246	24.60	0.05	0.01	35.16	51.91	-16.75	Average
4	0.270	31.89	0.05	0.02	42.46	61.12	-18.66	QP
5	0.393	27.71	0.04	0.04	38.29	57.99	-19.70	QP
6	0.494	20.39	0.04	0.03	30.96	46.10	-15.14	Average
7	1.602	13.38	0.07	0.16	24.11	46.00	-21.89	Average
8	4.006	24.06	0.10	0.08	34.74	56.00	-21.26	QP
9	5.993	25.46	0.14	0.09	36.19	60.00	-23.81	QP
10	6.523	14.00	0.15	0.10	24.75	50.00	-25.25	Average
11	15.146	21.48	0.27	0.14	32.39	60.00	-27.61	QP
12	15.226	12.40	0.27	0.14	23.31	50.00	-26.69	Average

Remark:


1. Level = Read level + LISN Factor + Cable Loss.

5.3 Radiated Emission

Unfold:

Below 1GHz:

Product Name:	Mobile Phone	Product Model:	AD10
Test By:	Mike	Test mode:	PC mode
Test Frequency:	30 MHz ~ 1 GHz	Polarization:	Vertical
Test Voltage:	AC 120V/60Hz		




Suspected Data List

NO.	Freq. [MHz]	Reading[dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Trace	Polarity
1	62.0100	40.05	25.52	-14.53	40.00	14.48	PK	Vertical
2	152.559	39.34	21.14	-18.20	43.50	22.36	PK	Vertical
3	240.005	50.41	36.20	-14.21	46.00	9.80	PK	Vertical
4	480.031	43.38	34.04	-9.34	46.00	11.96	PK	Vertical
5	720.009	43.06	38.00	-5.06	46.00	8.00	PK	Vertical
6	995.392	40.14	38.34	-1.80	54.00	15.66	PK	Vertical

Remark:

1. Level = Reading + Factor(Antenna Factor + Cable Loss – Preamplifier Factor).

Product Name:	Mobile Phone	Product Model:	AD10
Test By:	Mike	Test mode:	PC mode
Test Frequency:	30 MHz ~ 1 GHz	Polarization:	Horizontal
Test Voltage:	AC 120V/60Hz		



Suspected Data List


NO.	Freq. [MHz]	Reading[dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Trace	Polarity
1	94.6020	36.68	21.29	-15.39	43.50	22.21	PK	Horizontal
2	120.549	37.64	21.03	-16.61	43.50	22.47	PK	Horizontal
3	213.087	48.70	33.81	-14.89	43.50	9.69	PK	Horizontal
4	240.005	56.10	41.89	-14.21	46.00	4.11	PK	Horizontal
5	479.983	45.61	36.27	-9.34	46.00	9.73	PK	Horizontal
6	837.622	42.24	38.64	-3.60	46.00	7.36	PK	Horizontal

Remark:

1. Level = Reading + Factor(Antenna Factor + Cable Loss – Preamplifier Factor).

Above 1GHz:

Product Name:	Mobile Phone	Product Model:	AD10
Test By:	Mike	Test mode:	PC mode
Test Frequency:	1000 MHz ~ 6000 MHz	Polarization:	Vertical
Test Voltage:	AC 120V/60Hz		




Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Trace	Polarity
1	1655.62	68.67	-22.29	46.38	74.00	27.62	PK	Vertical
2	1655.62	57.83	-22.29	35.54	54.00	18.46	AV	Vertical
3	4774.37	47.66	-8.81	38.85	54.00	15.15	AV	Vertical
4	4774.37	57.08	-8.81	48.27	74.00	25.73	PK	Vertical
5	5908.12	56.47	-4.26	52.21	74.00	21.79	PK	Vertical
6	5908.12	46.72	-4.26	42.46	54.00	11.54	AV	Vertical

Remark:

1. Level = Reading + Factor(Antenna Factor + Cable Loss – Preamplifier Factor).

Product Name:	Mobile Phone	Product Model:	AD10
Test By:	Mike	Test mode:	PC mode
Test Frequency:	1000 MHz ~ 6000 MHz	Polarization:	Horizontal
Test Voltage:	AC 120V/60Hz		



Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Trace	Polarity
1	1132.50	66.50	-22.86	43.64	74.00	30.36	PK	Horizontal
2	1132.50	57.50	-22.86	34.64	54.00	19.36	AV	Horizontal
3	4726.87	46.86	-9.02	37.84	54.00	16.16	AV	Horizontal
4	4726.87	57.14	-9.02	48.12	74.00	25.88	PK	Horizontal
5	5674.37	56.97	-5.27	51.70	74.00	22.30	PK	Horizontal
6	5674.37	46.30	-5.27	41.03	54.00	12.97	AV	Horizontal


Remark:

1. Level = Reading + Factor(Antenna Factor + Cable Loss – Preamplifier Factor).

Fold:

Below 1GHz:

Product Name:	Mobile Phone	Product Model:	AD10
Test By:	Mike	Test mode:	PC mode
Test Frequency:	30 MHz ~ 1 GHz	Polarization:	Vertical
Test Voltage:	AC 120V/60Hz		




Suspected Data List

NO.	Freq. [MHz]	Reading[dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Trace	Polarity
1	55.4140	37.02	23.73	-13.29	40.00	16.27	PK	Vertical
2	189.856	41.53	25.58	-15.95	43.50	17.92	PK	Vertical
3	240.005	45.52	31.31	-14.21	46.00	14.69	PK	Vertical
4	480.031	42.76	33.42	-9.34	46.00	12.58	PK	Vertical
5	720.009	41.18	36.12	-5.06	46.00	9.88	PK	Vertical
6	998.787	39.03	37.28	-1.75	54.00	16.72	PK	Vertical

Remark:

1. Level = Reading + Factor(Antenna Factor + Cable Loss – Preamplifier Factor).

Product Name:	Mobile Phone	Product Model:	AD10
Test By:	Mike	Test mode:	PC mode
Test Frequency:	30 MHz ~ 1 GHz	Polarization:	Horizontal
Test Voltage:	AC 120V/60Hz		



Suspected Data List


NO.	Freq. [MHz]	Reading[dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Trace	Polarity
1	48.6240	37.59	24.81	-12.78	40.00	15.19	PK	Horizontal
2	120.937	38.93	22.23	-16.70	43.50	21.27	PK	Horizontal
3	212.263	47.52	32.61	-14.91	43.50	10.89	PK	Horizontal
4	240.005	52.07	37.86	-14.21	46.00	8.14	PK	Horizontal
5	479.983	44.47	35.13	-9.34	46.00	10.87	PK	Horizontal
6	796.542	44.55	40.45	-4.10	46.00	5.55	PK	Horizontal

Remark:

1. Level = Reading + Factor(Antenna Factor + Cable Loss – Preamplifier Factor).

Above 1GHz:

Product Name:	Mobile Phone	Product Model:	AD10
Test By:	Mike	Test mode:	PC mode
Test Frequency:	1000 MHz ~ 6000 MHz	Polarization:	Vertical
Test Voltage:	AC 120V/60Hz		




Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Trace	Polarity
1	1603.75	72.00	-22.44	49.56	74.00	24.44	PK	Vertical
2	1603.75	62.84	-22.44	40.40	54.00	13.60	AV	Vertical
3	4285.62	47.64	-11.11	36.53	54.00	17.47	AV	Vertical
4	4285.62	57.60	-11.11	46.49	74.00	27.51	PK	Vertical
5	5436.25	56.74	-6.02	50.72	74.00	23.28	PK	Vertical
6	5436.25	47.62	-6.02	41.60	54.00	12.40	AV	Vertical

Remark:

1. Level = Reading + Factor(Antenna Factor + Cable Loss – Preamplifier Factor).

Product Name:	Mobile Phone	Product Model:	AD10
Test By:	Mike	Test mode:	PC mode
Test Frequency:	1000 MHz ~ 6000 MHz	Polarization:	Horizontal
Test Voltage:	AC 120V/60Hz		



Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Trace	Polarity
1	1163.75	65.22	-22.95	42.27	74.00	31.73	PK	Horizontal
2	1163.75	54.74	-22.95	31.79	54.00	22.21	AV	Horizontal
3	4941.25	46.54	-8.13	38.41	54.00	15.59	AV	Horizontal
4	4941.25	57.23	-8.13	49.10	74.00	24.90	PK	Horizontal
5	5933.75	56.32	-4.28	52.04	74.00	21.96	PK	Horizontal
6	5933.75	45.86	-4.28	41.58	54.00	12.42	AV	Horizontal

Remark:

1. Level = Reading + Factor(Antenna Factor + Cable Loss – Preamplifier Factor).

-----End of report-----