



EMC Technologies Pty Ltd

ABN 82 057 105 549

57 Assembly Drive

Tullamarine Victoria Australia 3043

Ph: + 613 9335 3333

Fax: + 613 9338 9260

email: melb@emctech.com.au

**EMI TEST REPORT FOR CERTIFICATION
to
FCC PART 15 Subpart C (Section 15.247) & RSS-210**

FCC ID: EJE-WB0019

Industry Canada ID: 337J-WB0019

Test Sample: LifeBook "S" Series

Model: S7020

Radio Modules: Mini-PCI WLAN (Calexico2 11a+b/g), Model:
WM3B2915ABG & Bluetooth, Model UGXZ5-102A

Report Number M050322_Cert_WM3B2915ABG_11abg_DTS_BT

Tested for: Fujitsu Australia Ltd.

Issue Date: 4th April 2005

EMC Technologies Pty Ltd reports apply only to the specific samples tested under stated test conditions. It is the manufacturer's responsibility to assure that additional production units of this model are manufactured with identical electrical and mechanical components. EMC Technologies Pty Ltd shall have no liability for any deductions, inferences or generalisations drawn by the client or others from EMC Technologies Pty Ltd issued reports. This report shall not be used to claim, constitute or imply product endorsement by EMC Technologies Pty Ltd.



The tests, calibrations or measurements covered by this document have been performed in accordance with NATA requirements which include the requirements of ISO/IEC 17025 and are traceable to national standards of measurement. This document shall not be reproduced, except in full.

**NATA Accredited Laboratory
Number: 5292**

EMI TEST REPORT FOR CERTIFICATION
to
FCC PART 15 Subpart C (Section 15.247) & RSS-210
EMC Technologies Report No. M050322_Cert_WM3B2915ABG_11abg_DTS_BT
Issue Date: 4th April 2005

CONTENTS

- 1.0 INTRODUCTION**
- 2.0 GENERAL INFORMATION**

RESULTS – WLAN, WM3B2915ABG (802.11b, 802.11g and *802.11a)

- 3.0 CONDUCTED EMI MEASUREMENTS**
- 4.0 SPURIOUS EMI MEASUREMENTS**
- 5.0 PEAK OUTPUT POWER**
- 6.0 CHANNEL BANDWIDTH**
- 7.0 RADIO FREQUENCY EXPOSURE**
- 8.0 PEAK POWER SPECTRAL DENSITY**
- 9.0 ANTENNA REQUIREMENT**
- 10.0 COMPLIANCE STATEMENT**

***RESULTS of 802.11a (5.15 – 5.35 GHz Band)**

Refer to Report No: M050322_Cert_WM3B2915ABG_11abg_NII_BT

RESULTS – Bluetooth, UGXZ5-102A

Refer to Report No: M050322_Cert_BT_WM3B2915ABG_11abg

- APPENDIX A: MEASUREMENT INSTRUMENT DETAILS**
- APPENDIX B: REPORT PHOTOGRAPHS**
- APPENDIX C: FUNCTIONAL DESCRIPTION**
- APPENDIX D: BLOCK DIAGRAM**
- APPENDIX E: SCHEMATICS**
- APPENDIX F: ANTENNA INFORMATION**
- APPENDIX G: FCC LABELLING DETAILS**
- APPENDIX H: USER MANUAL**
- APPENDIX I: CHANNEL BANDWIDTH PLOTS**
- APPENDIX J: HARMONICS PLOTS**
- APPENDIX K: BANDEDGE PLOTS**
- APPENDIX L: PEAK POWER SPECTRAL DENSITY PLOTS**

Attachment 1: RF Exposure Information

Attachment 2: FCC DOC for LifeBook “S” Series

Attachment 3: FCC Part 15B Test Report (Report: FG05-034EAL)



This Laboratory is accredited by the National Association of Testing Authorities, Australia. The tests reported herein have been performed in accordance with its terms of accreditation for FCC Part 15. This document shall not be reproduced, except in full.

EMI TEST REPORT FOR CERTIFICATION
to
FCC PART 15 Subpart C (Section 15.247) & RSS-210

Report Number: M050322_Cert_WM3B2915ABG_11abg_DTS_BT

Test Sample: LifeBook "S" Series
Model: S7020
Radio Modules: Mini-PCI WLAN, Model: WM3B2915ABG (Intel Corp.)
Bluetooth, Model: UGXZ5-102A (Fujitsu Ltd)

FCC ID: EJE-WB0019
Industry Canada ID: 337J-WB0019
Equipment Type: Intentional Radiator (Transceiver)

Manufacturer (LifeBook): Fujitsu Ltd
Address: 1405, Ohamaru, Inagi-shi, Tokyo 206-8503, Japan
Contact: Mr. Tsuyoshi Uchihara

Tested for: Fujitsu Australia Ltd

Test Standards: FCC Part 15, Subpart C – Intentional Radiators
FCC Part 15.247: 2400 – 2483.5 MHz & 5725 – 5850 MHz Operation Band
ANSI C63.4 – 2003
OET Bulletin No. 65


RSS-210 Issue 5 Low Power Licence-Exempt RadioCommunication Devices:
6.2.2 (o) 2400 – 2483.5 MHz & 5725 – 5850 MHz Spread Spectrum

RSS-102 Issue 1 (Provisional), Evaluation Procedure for Mobile and Portable
Radio Transmitters with respect to Health Canada's Safety Code 6 for
Exposure of Humans to Radio Frequency Fields

Test Dates: 18th to 30th March 2005

Test Officer: 
Chieu Huynh
B.Eng (Hons) Electronics

Attestation: *I hereby certify that the device(s) described herein were tested as described in this report and that the data included is that which was obtained during such testing.*

Authorised Signatory: 
Chris Zombolas
Technical Director
EMC Technologies Pty Ltd



This Laboratory is accredited by the National Association of Testing Authorities, Australia. The tests reported herein have been performed in accordance with its terms of accreditation for FCC Part 15. This document shall not be reproduced, except in full.

EMI TEST REPORT FOR CERTIFICATION
to
FCC PART 15 Subpart C (Section 15.247) & RSS-210

1.0 INTRODUCTION

EMI testing was performed on test sample LifeBook "S" Series, Model: S7020 with Mini-PCI Wireless LAN Module (Calexico2 11a+b/g), Model WM3B2915ABG & Bluetooth, Model UGXZ5-102A.

The Calexico2 WLAN supports IEEE 802.11b, IEEE 802.11g and IEEE802.11a (DTS & U-NII) configurations. Tests were performed in all three configurations and also on the Bluetooth.

The results for configurations IEEE 802.11b, IEEE 802.11g and IEEE802.11a (DTS: 5725 – 5850 MHz) are reported in this test report.

The results for IEEE 802.11a (U-NII) and Bluetooth are reported separately.
Refer to EMC Technologies' test report: M050322_Cert_WM3B2915ABG_11abg_NII_BT (U-NII) and M050322_Cert_BT_WM3B2915ABG_11abg (Bluetooth).

Test results and procedures were performed in accordance with the following Federal Communications Commission (FCC) standards/regulations:

47 CFR, Part 15, Subpart C:	Rules for intentional radiators (particularly section 15.247)
Section 15.203:	Antenna requirements
Section 15.205:	Restricted bands of operation
Section 15.207:	Conducted Emission Limits
Section 15.209:	Radiated Emission Limits (General requirements)
Section 15.247:	Operation in the bands 902-928 MHz, 2400-2483.5 MHz, 5725-5850 MHz

The test sample **complied** with the requirements of 47 CFR, Part 15 Subpart C - Section 15.247.

The test sample also complied with the Industry Canada RSS-210 issue 5 (Low Power Licence-Exempt Radiocommunication Devices (All Frequency Bands)) clause 6.2.2(o) and the RF exposure requirements of RSS-102.



This Laboratory is accredited by the National Association of Testing Authorities, Australia. The tests reported herein have been performed in accordance with its terms of accreditation for FCC Part 15. This document shall not be reproduced, except in full.

1.1 Summary of Results

1.1.1 WLAN, Calexico2 802.11b, 802.11g and 802.11a (DTS) - FCC Subpart C, Section 15.247

FCC Part 15, Subpart C Clauses	Industry Canada RSS-210 Clauses	Test Performed	Result
15.203	5.5	Antenna Requirement	Not Applicable
15.205	6.3	Operation in Restricted Band	Complies
15.207	6.6	Conducted Emissions	Complies
15.209	6.3	Radiated Emissions	Complies
15.247 (a)(2)	6.2.2(o)(iv)	Channel Bandwidth	Complies
15.247 (b)(3)	6.2.2(o)(b)	Peak Output Power	Complies
15.247 (b)(5)		Radio Frequency Hazard	Complies
15.247 (c)	6.2.2(o)(e1)	Out of Band Emissions	Complies
15.247 (d)	6.2.2(o)(iv)	Peak Power Spectral Density	Complies

1.1.2 WLAN, Calexico2 802.11a (U-NII) - FCC Subpart E, Section 15.407

FCC Part 15, Subpart E Clauses	Industry Canada RSS-210 Clauses	Test Performed	Result
15.203	5.5	Antenna Requirement	Not Applicable
15.205	6.3	Operation in Restricted Band	Complies
15.207	6.6	Conducted Emissions	Complies
15.209	6.3	Radiated Emissions	Complies
15.407 (a)(4)	6.2.2(q1)	Peak Transmit Power	Complies
15.407 (a)(5)	6.2.2(q1)	Peak Power Spectral Density	Complies
15.407 (a)(6)		Peak Excursion	Complies
15.407 (b)	6.2.2(q1)	Undesirable Emission	Complies
15.407 (f)		Radio Frequency Hazard	Complies
15.407 (g)	6.4	Frequency Stability	Complies

Refer to EMC Technologies Report No: M050322_Cert_WM3B2915ABG_11abg_NII_BT

1.1.3 Bluetooth - FCC Subpart C, Section 15.247

FCC Part 15, Subpart C Clauses	Industry Canada RSS-210 Clauses	Test Performed	Result
15.203	5.5	Antenna Requirement	Not Applicable
15.205	6.3	Operation in Restricted Band	Complies
15.207	6.6	Conducted Emissions	Complies
15.209	6.3	Radiated Emissions	Complies
15.247 (a)(1)&(3)	6.2.2(o)(ii)	Channel Occupancy/Bandwidth	Complies
15.247 (b)(1)	6.2.2(o)(b)	Peak Output Power	Complies
15.247 (b)(5)		Radio Frequency Hazard	Complies
15.247 (c)	6.2.2(o)(e1)	Out of Band Emissions	Complies

Refer to EMC Technologies Report No: M050322_Cert_BT_WM3B2915ABG_11abg

The measurement procedure used was in accordance with ANSI C63.4-2003 and OET Bulletin No. 65. The instrumentation conformed to the requirements of ANSI C63.2-1996.

1.2 Modifications by EMC Technologies

No modifications were required.



This Laboratory is accredited by the National Association of Testing Authorities, Australia. The tests reported herein have been performed in accordance with its terms of accreditation for FCC Part 15. This document shall not be reproduced, except in full.

2.0 GENERAL INFORMATION

(Information supplied by the Client)

2.1 Product Details

Test Sample (Host PC):	LifeBook "S" Series
Model Number:	S7020
Serial Number:	Pre-production Sample
Manufacturer:	Fujitsu Ltd
CPU Type and Speed:	Dothan 2.13 GHz Banias 1.7 GHz Celeron-M 1.7 GHz
Wired LAN:	Broadcom BCM5751M 10 Base-T/100 Base-TX/1000 Base-T)
Modem:	Agere MDC 1.5, Model: AM2
Port Replicator Model:	FPCPR48 / FPCPR48AP
AC Adapter Model:	SEC80P2-19.0
Voltage:	19 V
Current Specs:	3.16 A
Watts:	60 W
Radio Modules:	WLAN (Calexico2 11a+b/g) and Bluetooth
WLAN Model Number:	WM3B2915ABG
WLAN Manufacturer:	Intel Corporation
Interface Type:	Mini-PCI Wireless LAN Module
Bluetooth Model Number:	UGXZ5-102A
Bluetooth Manufacturer:	Fujitsu Ltd
FCC ID:	EJE-WB0019
Industry Canada ID:	337J-WB0019
Equipment Type:	Intentional Radiator (Transceiver)



This Laboratory is accredited by the National Association of Testing Authorities, Australia. The tests reported herein have been performed in accordance with its terms of accreditation for FCC Part 15. This document shall not be reproduced, except in full.

2.2 Technical Specifications

2.2.1 WLAN Transmitter Specifications

Transmitter:	Mini-PCI Wireless LAN Module
Wireless Module:	Calexico2 (11a+b/g)
Model Number:	WM3B2915ABG
Manufacturer:	Intel Corporation
Modulation Type:	Direct Sequence Spread Spectrum (DSSS for 802.11b) Orthogonal Frequency Division Multiplexing (OFDM for 802.11g) Orthogonal Frequency Division Multiplexing (OFDM for 802.11a)
802.11a	BPSK – 6Mbps, 9Mbps QPSK – 12Mbps, 18Mbps 16QAM – 24Mbps, 36Mbps 64QAM – 48Mbps, 54Mbps
802.11g	BPSK – 6Mbps, 9Mbps QPSK – 12Mbps, 18Mbps 16QAM – 24Mbps, 36Mbps 64QAM – 48Mbps, 54Mbps
802.11b	DBPSK – 1Mbps DQPSK – 2Mbps CCK – 5.5Mbps, 11Mbps
Maximum Data Rate:	802.11b = 11Mbps, 802.11g and 802.11a = 54Mbps
Frequency Range:	2.4 – 2483.5 GHz for 11b/g 5.15 - 5.35 GHz and 5.725 - 5.850 GHz for 11a
Number of Channels:	11 channels for 11b or 11g 13 channels for 11a
Antenna Types:	2 x Yokowo Monopole Ceramic – Model: YCE-5008 Located on top edge of LCD screen
Antenna gain:	802.11b/g = 2.08 dBi 802.11a (5.15 – 5.35 GHz) = 1.66 dBi 802.11a (5.725 – 5.825 GHz) = 1.79 dBi
Max. Output Power:	802.11b = 15 dBm 802.11g = 14 dBm 802.11a = 10-14 dBm
Power Supply:	3.3 VDC from PCI bus
Chipset Used:	82533MDE and 82533RGE

Frequency allocation and maximum output power setting for 802.11b/g:

Channel Number	Frequency (MHz)	EUT Power level setting dBm	
		802.11b	802.11g
1	2412*	15	14
2	2417	15	14
3	2422	15	14
4	2427	15	14
5	2432	15	14
6	2437*	15	14
7	2442	15	14
8	2447	15	14
9	2452	15	14
10	2457	15	14
11	2462*	15	14

*Channels tested and reported in this report



This Laboratory is accredited by the National Association of Testing Authorities, Australia. The tests reported herein have been performed in accordance with its terms of accreditation for FCC Part 15. This document shall not be reproduced, except in full.

Frequency allocation and maximum output power setting for 802.11a:

Channel Number	Frequency (MHz)	Power level setting dBm
*Channels tested and reported in this report (DTS)		
149	5745*	14
153	5765	14
157	5785*	14
161	5805	14
165	5825*	14
*Channels tested and reported in the U-NII submission (M050322_Cert_WM3B2915ABG_11abg_NII_BT)		
36	5180*	10
40	5200	10
44	5220	10
48	5240	10
52	5260*	14
56	5280	14
60	5300	14
64	5320*	14

2.2.2 Bluetooth Transmitter Specifications

Transmitter: Bluetooth
Model Number: UGXZ5-102A
Manufacturer: Fujitsu Ltd
Network Standard: Bluetooth™ RF Test Specification
Modulation Type: Frequency Hopping Spread Spectrum (FHSS)
Frequency Range: 2402 MHz to 2480 MHz
Number of Channels: 79
Carrier Spacing: 1.0 MHz
Antenna Types: Yokowo Monopole Ceramic Antenna, Model: YCE-5250
 Located on left side of keyboard near the TAB key
Antenna gain: 2.78 dBi
Max. Output Power: 12 dBm
Reference Oscillator: 16 MHz (Built-in)
Power Supply: 3.3 VDC from host.

Frequency allocation:

Channel Number	Frequency (MHz)	Bluetooth Utility power setting
1*	2402	Power (Ext, Int) = 180, 46
2	2403	
3	2404	
.	.	
.	.	
.	.	
39	2440	
40*	2441	
41	2442	
.	.	
.	.	
.	.	
77	2478	
78	2479	
79*	2480	

*Channels tested and reported in the Bluetooth submission (M050322_Cert_BT_WM3B2915ABG_11abg)



This Laboratory is accredited by the National Association of Testing Authorities, Australia. The tests reported herein have been performed in accordance with its terms of accreditation for FCC Part 15. This document shall not be reproduced, except in full.

2.3 Operational Description

The EUT is a LifeBook "S" Series, Model: S7020 installed with a Mini-PCI Wireless LAN (WLAN) Module (Calexico2 11a+b/g, Model WM3B2915ABG) & Bluetooth, Model UGXZ5-102A.

The same WLAN radio module and Bluetooth combination has been previously certified by Fujitsu under FCC ID: EJE-WB0016 and IC: 337J-WB0016 in a different host.

The intention of this application is to re-certify this WLAN and Bluetooth with a different antenna combination in host – LifeBook "S" Series, Model: S7020.

2.4 Test Configuration

The Intel WLAN software and the BlueSuiteCasira software were used to set-up the WLAN module and Bluetooth devices respectively to continuously transmit during the tests. The LCD screen was observed for the transmitter status shown for the respective software.

Antenna

The Calexico2 (11a+b/g) WLAN, Model WM3B2915ABG is configured with Yokowo Monopole Ceramic Antenna – Model: YCE-5008 and ALPS Bluetooth device, Model UGXZ5-102A is configured with Yokowo Monopole Ceramic Antenna - Model: YCE-5250. The installation of the OEM WLAN module, Bluetooth Device and the Antenna in Fujitsu LifeBook "S" Series, Model: S7020 is in a controlled environment. The installation is performed during the production/assembly process at the Fujitsu factory.

Refer to Appendix F – Antenna Information.

There are three antennas: WLAN antennas (x2) are located on the right hand side and left hand side on the top edge of the LCD screen. Bluetooth antenna is located on left side of keyboard near the TAB key.

Refer to photos in Appendix B3 for WLAN Antenna locations.

AC Adapter

The AC adapter SEC80P2-19.0 was used for all the tests. Details of the AC adapter are supplied in section 2.1 of this report.

2.5 Block Diagram

Refer to Appendix D - Block Diagram



2.6 Support Equipment

External Monitor:	Hewlett Packard 15" Color monitor, Model D2827A, FCC ID: C5F7NFCMC1515X
Printer:	Diconix, Model: 150, FCC ID: E759WG-RBCN150
USB Floppy Drive/s:	Fujitsu Model: FPCFDD11, P/N CP032173-01 Fujitsu Model: FPCFDD12, P/N CP078720-01 USB OMNI Floppy Drive Model # USB F3501 SN W316000096
PS2 Mouse	A4 Tech M/N: SWW-25
LAN Hub:	Kingston SOHO Hub Model: KNE8TP/H (FCC ID: JICKNE8TP-HO)
Headphones:	Verbatim Multimedia Stereo headset
PCMCIA Slot:	6 MB Compact flash card with Adapter, Apacer P/N 88.10200030
Memory Card:	Secure Digital- 32 MB

2.7 Test Procedure

Emissions measurements were performed in accordance with the procedures of ANSI C63.4-2003. Radiated emissions tests were performed at a distance of 3 and 10 metres from the EUT. OET Bulletin 65 dated June 2001 was used for reference.

2.8 Test Facility

2.8.1 General

Radiated Emission measurements were performed at EMC Technologies open area test site (OATS) situated at Lerderderg Gorge, near the township of Bacchus Marsh in Victoria, Australia. Conducted emission measurements were performed at EMC Technologies' laboratory in Tullamarine, Victoria Australia.

The above sites have been fully described in a report submitted to the FCC office, and accepted in a letter dated June 14, 2002, **FCC Registration Number 90560**.

EMC Technologies open area test site (OATS) has also been accepted by Industry Canada for the performance of radiated measurements in accordance with RSS 212, Issue 1 (Provisional). **Industry Canada File Number, IC 4161**, (Registration Date - November 5th 2001).

2.8.2 NATA Accreditation

EMC Technologies is accredited in Australia to test to the following standards by the National Association of Testing Authorities (NATA).

"FCC Part 15 unintentional and intentional emitters in the frequency range 9kHz to 18 GHz excluding TV receivers (15.117 and 15.119), TV interface devices (15.115), cable ready consumer electronic equipment (15.118), cable locating equipment (15.213) and unlicensed national information infrastructure devices (Sub part E)."

The current full scope of accreditation can be found on the NATA website: www.nata.asn.au
It also includes a large number of emission, immunity, SAR, EMR and Safety standards.

NATA is the Australian national laboratory accreditation body and has accredited EMC Technologies to operate to the IEC/ISO17025 requirements. A major requirement for accreditation is the assessment of the company and its personnel as being technically competent in testing to the standards. This requires fully documented test procedures, continued calibration of all equipment to the National Standard at the National Measurements Laboratory (NML) and an internal quality system to ISO 9002. NATA has mutual recognition agreements with the National Voluntary Laboratory Accreditation Program (NVLAP) and the American Association for Laboratory Accreditation (A²LA).



This Laboratory is accredited by the National Association of Testing Authorities, Australia. The tests reported herein have been performed in accordance with its terms of accreditation for FCC Part 15. This document shall not be reproduced, except in full.

2.9 Units of Measurements

2.9.1 Conducted Emissions

Measurements are reported in units of dB relative to one microvolt. (dB μ V).

2.9.2 Radiated Emissions

Measurements are reported in units of dB relative to one microvolt per metre (dB μ V/m).

2.10 Test Equipment Calibration

All measurement instrumentation and transducers were calibrated in accordance with the applicable standards by an independent NATA registered laboratory such as Agilent Technologies (Australia) Pty Ltd or the National Measurement Laboratory (NML). All equipment calibration is traceable to Australia national standards at the National Measurements Laboratory. The reference antenna calibration was performed by NML and the working antennas (biconical and log-periodic) calibrated by the NATA approved procedures. The complete list of test equipment used for the measurements, including calibration dates and traceability is contained in Appendix A

2.11 Ambients at OATS

The Open Area Test Site (OATS) is an area of low background ambient signals. No significant broadband ambients are present however commercial radio and TV signals exceed the limit in the FM radio, VHF and UHF television bands. Radiated prescan measurements were performed in the shielded enclosure to check for possible radiated emissions at the frequencies where the OATS ambient signals exceeded the test limit.



RESULTS

WLAN Module – WM3B2915ABG (802.11b, 802.11g and 802.11a (DTS))

3.0 CONDUCTED EMISSION MEASUREMENTS

Testing was performed in accordance with the requirements of FCC Part 15.207
Refer to Attachment 3 – FCC Part 15B Test Report (Report: FG05-034EAL)

4.0 SPURIOUS EMISSION MEASUREMENTS

4.1 Test Procedure

Testing was performed in accordance with the requirements of FCC Part 15.247(c).

Radiated emission measurements were performed to the limits as per section 15.209. The measurements were made at the open area test site.

The EUT was set up on the table top (placed on turntable) of total height 80 cm above the ground plane, and operated as described in section 2 of this report. The EMI Receiver was operated under software control via the PC Controller through the IEEE.488 Interface Bus Card Adaptor. The test frequency range was sub-divided into smaller bands with sufficient frequency resolution to permit reliable display and identification of possible EMI peaks while also permitting fast frequency scan times. Calibrated EMCO 3115 and EMCO 3116 Horn antennas were used for measurements between 1 to 40 GHz.

The measurement of emissions between 30 - 1000 MHz, refer to Attachment 3 – FCC Part 15B Test Report (Report: FG05-034EAL).

The measurement of emissions above 1000 MHz, appearing in the restricted bands, was made using an average detector with a bandwidth of 1.0 MHz.

The EUT was slowly rotated with the Peak Detector set to Max-Hold. This was performed for two antenna heights. When an emission was located, it was positively identified and its maximum level found by rotating the automated turntable, and by varying the antenna height. Each significant peak was investigated with the Quasi-Peak/Average Detectors. The software for cable losses automatically corrected the measurement data for each frequency range, antenna factors and preamplifier gain and all data was then stored on disk in sequential data files. This process was performed for both horizontal and vertical antenna polarisations.

4.2 Calculation of field strength

The field strength was calculated automatically by the software using all the pre-stored calibration data. The method of calculation is shown below:

E = V + AF - G + L Where:

- E** = Radiated Field Strength in dBμV/m.
- V** = EMI Receiver Voltage in dBμV. (measured value)
- AF** = Antenna Factor in dB(m⁻¹). (stored as a data array)
- G** = Preamplifier Gain in dB. (stored as a data array)
- L** = Cable insertion loss in dB. (stored as a data array of Insertion Loss versus frequency)

• Example Field Strength Calculation

Assuming a receiver reading of 34.0 dBμV is obtained at 90 MHz, the Antenna Factor at that frequency is 9.2 dB. The cable loss is 1.9 dB while the preamplifier gain is 20 dB. The resulting Field Strength is therefore as follows:

$$34.0 + 9.2 + 1.9 - 20 = 25.1 \text{ dB}\mu\text{V/m}$$

Measurement uncertainty with a confidence interval of 95% is:

- Free radiation tests (1000 MHz – 18,000 MHz) ± 4.1 dB



This Laboratory is accredited by the National Association of Testing Authorities, Australia. The tests reported herein have been performed in accordance with its terms of accreditation for FCC Part 15. This document shall not be reproduced, except in full.

4.3 Radiated Emissions (Spurious and Harmonics)

4.3.1 Frequency Band: 1 – 40 GHz

All measurements above 1 GHz were initially made over a distance of 3 metres. This was decreased to 1.0 metre as the emission levels from the device were very low.

The 54 dB μ V/m limit at 3 metres has been converted to 64 dB μ V/m at 1 metre using a factor of 20 dB per decade where emissions were located in the restricted bands.

Testing was performed while both the WLAN transmitter and Bluetooth transmitter continuously operated. Harmonics related to the WLAN transmitter are reported below. For harmonics related to the Bluetooth transmitter, refer to M050322_Cert_BT_WM3B2915ABG_11abg.

Measurements for the WLAN were performed on the following frequency channels:

802.11b/g (DTS):

Low (channel 1, 2412 MHz), middle (channel 6, 2437 MHz) and high (Channel 11, 2462 MHz) frequency channel.

802.11a (DTS):

Low (channel 149, 5745 MHz), middle (channel 157, 5785 MHz) and high (Channel 165, 5825 MHz) frequency channel.

4.3.1.1 Configuration 802.11b

Initial investigations were performed with three modulation types: (DBPSK, DQPSK and CCK). No significant differences in emissions were observed. Final testing was performed while the transmitter continuously operated with the modulation rate of 11 Mbps (CCK).

The field strength at 2483.5 MHz when the EUT was operating at its highest channel (2462 MHz), was 51.6 dB μ V/m peak & 37.8 dB μ V/m average and was > 20 dB below the maximum field strength of the in-band carrier.

The field strength at 2400 MHz when the EUT was operating at its lowest channel (2412 MHz), was 61.8 dB μ V/m peak & 45.5 dB μ V/m average and was > 20 dB below the maximum field strength of the in-band carrier.

Channel 1 - 2412 MHz

Frequency MHz	Level dB μ V/m		Antenna Polarization	Peak Limit dB μ V/m	Average Limit dB μ V/m	Result
	Peak Detector	Average Detector				
2412	Transmitter	Fundamental				
4824	53.3	41.0	Vert/Hort	74.0	54.0	Pass
7236	53.4	41.1	Vert/Hort	-	-	Pass
9648	55.9	42.4	Vert/Hort	-	-	Pass
12060	57.0	43.8	Vert/Hort	74.0	54.0	Pass
14472	60.3	46.7	Vert/Hort	74.0	54.0	Pass
16884	63.9	49.3	Vert/Hort	-	-	Pass
19296	65.0	51.5	Vert/Hort	84.0* (1m)	64.0* (1m)	Pass
21708	66.4	53.2	Vert/Hort	-	-	Pass
24120	67.8	54.7	Vert/Hort	-	-	Pass

*Measurement was performed at 1 metre distance and the limits were corrected accordingly.



Channel 6 - 2437 MHz

Frequency MHz	Level dBuV/m		Antenna Polarization	Peak Limit dBuV/m	Average Limit dBuV/m	Result
	Peak Detector	Average Detector				
2437	Transmitter	Fundamental				
4874	54.0	41.3	Vert/Hort	74.0	54.0	Pass
7311	53.4	41.1	Vert/Hort	74.0	54.0	Pass
9748	55.9	42.4	Vert/Hort	-	-	Pass
12185	57.0	43.8	Vert/Hort	74.0	54.0	Pass
14622	60.3	46.7	Vert/Hort	-	-	Pass
17059	63.9	49.3	Vert/Hort	-	-	Pass
19496	65.0	51.5	Vert/Hort	84.0* (1m)	64.0* (1m)	Pass
21933	66.4	53.2	Vert/Hort	-	-	Pass
24370	67.8	54.7	Vert/Hort	-	-	Pass

*Measurement was performed at 1 metre distance and the limits were corrected accordingly.

Channel 11 - 2462 MHz

Frequency MHz	Level dBuV/m		Antenna Polarization	Peak Limit dBuV/m	Average Limit dBuV/m	Result
	Peak Detector	Average Detector				
2462	Transmitter	Fundamental				
4924	54.1	42.0	Vert/Hort	74.0	54.0	Pass
7386	53.4	41.1	Vert/Hort	74.0	54.0	Pass
9848	55.9	42.4	Vert/Hort	-	-	Pass
12310	57.0	43.8	Vert/Hort	74.0	54.0	Pass
14772	60.3	46.7	Vert/Hort	-	-	Pass
17234	63.9	49.3	Vert/Hort	-	-	Pass
19696	65.0	51.5	Vert/Hort	84.0* (1m)	64.0* (1m)	Pass
22158	66.4	53.2	Vert/Hort	84.0* (1m)	64.0* (1m)	Pass
24620	67.8	54.7	Vert/Hort	-	-	Pass

*Measurement was performed at 1 metre distance and the limits were corrected accordingly.

Result: 2nd harmonic was recorded within the restricted bands of up to 25 GHz. Other harmonics were confirmed low with both RBW and VBW reduced (the peak and average levels listed in the above tables were noise floor readings). Harmonics were complied with the FCC limits in sections 15.209 and 15.247 by a margin of 12.0 dB. The measurement uncertainty for radiated emissions in this band was ± 4.1 dB.



This Laboratory is accredited by the National Association of Testing Authorities, Australia. The tests reported herein have been performed in accordance with its terms of accreditation for FCC Part 15. This document shall not be reproduced, except in full.

4.3.1.2 Configuration 802.11g

Initial investigations were performed with four modulation types: (BPSK, QPSK, 16QAM and 64QAM). No significant differences in emissions were observed. Final testing was performed while the transmitter continuously operated with the modulation rate of 6 Mbps (BPSK).

The field strength at 2483.5 MHz when the EUT was operating at its highest channel (2462 MHz), was 54.4 dB μ V/m peak & 41.4 dB μ V/m average and was > 20 dB below the maximum field strength of the in-band carrier.

The field strength at 2400 MHz when the EUT was operating at its lowest channel (2412 MHz), was 69.1 dB μ V/m peak & 55.5 dB μ V/m average and was > 20 dB below the maximum field strength of the in-band carrier.

Channel 1 - 2412 MHz

Frequency MHz	Level dBuV/m		Antenna Polarization	Peak Limit dBuV/m	Average Limit dBuV/m	Result
	Peak Detector	Average Detector				
2412	Transmitter	Fundamental				
4824	53.7	40.8	Vert/Hort	74.0	54.0	Pass
7236	53.4	41.1	Vert/Hort	-	-	Pass
9648	55.9	42.4	Vert/Hort	-	-	Pass
12060	57.0	43.8	Vert/Hort	74.0	54.0	Pass
14472	60.3	46.7	Vert/Hort	74.0	54.0	Pass
16884	63.9	49.3	Vert/Hort	-	-	Pass
19296	65.0	51.5	Vert/Hort	84.0* (1m)	64.0* (1m)	Pass
21708	66.4	53.2	Vert/Hort	-	-	Pass
24120	67.8	54.7	Vert/Hort	-	-	Pass

*Measurement was performed at 1 metre distance and the limits were corrected accordingly.

Channel 6 - 2437 MHz

Frequency MHz	Level dBuV/m		Antenna Polarization	Peak Limit dBuV/m	Average Limit dBuV/m	Result
	Peak Detector	Average Detector				
2437	Transmitter	Fundamental				
4874	53.7	40.8	Vert/Hort	74.0	54.0	Pass
7311	53.4	41.1	Vert/Hort	74.0	54.0	Pass
9748	55.9	42.4	Vert/Hort	-	-	Pass
12185	57.0	43.8	Vert/Hort	74.0	54.0	Pass
14622	60.3	46.7	Vert/Hort	-	-	Pass
17059	63.9	49.3	Vert/Hort	-	-	Pass
19496	65.0	51.5	Vert/Hort	84.0* (1m)	64.0* (1m)	Pass
21933	66.4	53.2	Vert/Hort	-	-	Pass
24370	67.8	54.7	Vert/Hort	-	-	Pass

*Measurement was performed at 1 metre distance and the limits were corrected accordingly.



Channel 11 - 2462 MHz

Frequency MHz	Level dBuV/m		Antenna Polarization	Peak Limit dBuV/m	Average Limit dBuV/m	Result
	Peak Detector	Average Detector				
2462	Transmitter	Fundamental				
4924	53.7	40.8	Vert/Hort	74.0	54.0	Pass
7386	53.4	41.1	Vert/Hort	74.0	54.0	Pass
9848	55.9	42.4	Vert/Hort	-	-	Pass
12310	57.0	43.8	Vert/Hort	74.0	54.0	Pass
14772	60.3	46.7	Vert/Hort	-	-	Pass
17234	63.9	49.3	Vert/Hort	-	-	Pass
19696	65.0	51.5	Vert/Hort	84.0* (1m)	64.0* (1m)	Pass
22158	66.4	53.2	Vert/Hort	84.0* (1m)	64.0* (1m)	Pass
24620	67.8	54.7	Vert/Hort	-	-	Pass

*Measurement was performed at 1 metre distance and the limits were corrected accordingly.

Result: No harmonics were recorded within the restricted bands of up to 25 GHz. Harmonics were confirmed low with both RBW and VBW reduced (the peak and average levels listed in the above tables were noise floor readings). Harmonics were complied with the FCC limits in sections 15.209 and 15.247. The measurement uncertainty for radiated emissions in this band was ± 4.1 dB.

4.3.1.3 Configuration 802.11a (5.725 – 5.850 MHz)

Initial investigations were performed with four modulation types: (BPSK, QPSK, 16QAM and 64QAM). No significant differences in emissions were observed. Final testing was performed while the transmitter continuously operated with the modulation rate of 54 Mbps (64QAM).

The field strength at 5850 MHz when the EUT was operating at its highest channel (5825 MHz), was 65.2 dB μ V/m peak & 51.8 dB μ V/m average and was > 20 dB below the maximum field strength of the in-band carrier.

The field strength at 5725 MHz when the EUT was operating at its lowest channel (5745 MHz), was 69.8 dB μ V/m peak & 53.9 dB μ V/m average and was > 20 dB below the maximum field strength of the in-band carrier.

Channel 149 – 5745 MHz

Frequency MHz	Level dBuV/m		Antenna Polarization	Peak Limit dBuV/m	Average Limit dBuV/m	Result
	Peak Detector	Average Detector				
5745	Transmitter	Fundamental				
11490	57.7	44.3	Vert/Hort	74.0	54.0	Pass
17235	64.1	49.6	Vert/Hort	-	-	Pass
22980	65.5	50.5	Vert/Hort	84.0* (1m)	64.0* (1m)	Pass
28725	69.3	55.2	Vert/Hort	-	-	Pass
34470	78.7	65.0	Vert/Hort	-	-	Pass

*Measurement was performed at 1 metre distance and the limits were corrected accordingly.



Channel 157 – 5785 MHz

Frequency MHz	Level dBuV/m		Antenna Polarization	Peak Limit dBuV/m	Average Limit dBuV/m	Result
	Peak Detector	Average Detector				
5785	Transmitter	Fundamental				
11570	57.7	44.3	Vert/Hort	74.0	54.0	Pass
17355	64.1	49.6	Vert/Hort	-	-	Pass
23140	65.5	50.5	Vert/Hort	-	-	Pass
28925	69.3	55.2	Vert/Hort	-	-	Pass
34710	78.7	65.0	Vert/Hort	-	-	Pass

*Measurement was performed at 1 metre distance and the limits were corrected accordingly.

Channel 161 – 5825 MHz

Frequency MHz	Level dBuV/m		Antenna Polarization	Peak Limit dBuV/m	Average Limit dBuV/m	Result
	Peak Detector	Average Detector				
5825	Transmitter	Fundamental				
11650	57.7	44.3	Vert/Hort	74.0	54.0	Pass
17475	64.1	49.6	Vert/Hort	-	-	Pass
23300	65.5	50.5	Vert/Hort	-	-	Pass
29125	69.3	55.2	Vert/Hort	-	-	Pass
34950	78.7	65.0	Vert/Hort	-	-	Pass

*Measurement was performed at 1 metre distance and the limits were corrected accordingly.

Result: No harmonics were recorded within the restricted bands of up to 40 GHz. Harmonics were confirmed low with both RBW and VBW reduced (the peak and average levels listed in the above tables were noise floor readings). Harmonics were complied with the FCC limits in section 15.209 and 15.247. The measurement uncertainty for radiated emissions in this band was ± 4.1 dB.

4.3.1.4 Spurious Emissions Generated When Both (WLAN and BT) Transmitters Transmitting

Result: No spurious emissions were recorded within the restricted bands of up to 40 GHz. Spurious emissions were confirmed low with both RBW and VBW reduced. Emissions were complied with the FCC limits in sections 15.209 and 15.247. The measurement uncertainty for radiated emissions in this band was ± 4.1 dB.

4.3.2 Frequency Band: 30 - 1000 MHz

Refer to Attachment 3 – FCC Part 15B Test Report (Report: FG05-034EAL).



4.3.3 RF Conducted Measurements at the Antenna Terminal

In the 100 kHz bandwidth within the operating band, the highest emissions (spurious/harmonics) level that is produced by the intentional radiator shall be at least 20 dB below.

Measurements for the WLAN were performed on the following frequency channels:

802.11b/g (DTS):

Low (channel 1, 2412 MHz), middle (channel 6, 2437 MHz) and high (Channel 11, 2462 MHz) frequency channel.

802.11a (DTS):

Low (channel 149, 5745 MHz), middle (channel 157, 5785 MHz) and high (Channel 165, 5825 MHz) frequency channel.

The transmitter output was connected to the spectrum analyser in peak hold mode.

The resolution bandwidth of 100 kHz and the video bandwidth of 300 kHz were utilised.

4.3.3.1 Calexico2 - WM3B2915ABG - Configuration 802.11a (5.725 – 5.850 GHz)

Refer to Appendix J1 for Harmonics plots

Result: Complies.

4.3.3.2 Calexico2 - WM3B2915ABG - Configuration 802.11b

Refer to Appendix J2 for Harmonics plots

4.3.3.3 Calexico2 - WM3B2915ABG - Configuration 802.11g

Refer to Appendix J3 for Harmonics plots

Result: Complies.



4.3.4 Band Edge Measurements

In the 100 kHz bandwidth within the operating band, the highest emissions (spurious/harmonics) level that is produced by the intentional radiator shall be at least 20 dB below.

Measurements for the WLAN were performed on the following frequency channels:

802.11b/g (DTS):

Low (channel 1, 2412 MHz), middle (channel 6, 2437 MHz) and high (Channel 11, 2462 MHz) frequency channel.

802.11a (DTS):

Low (channel 149, 5745 MHz), middle (channel 157, 5785 MHz) and high (Channel 165, 5825 MHz) frequency channel.

The transmitter output was connected to the spectrum analyser in peak hold mode.

The resolution bandwidth of 100 kHz and the video bandwidth of 300 kHz were utilised.

4.3.4.1 Calexico2 - WM3B2915ABG - Configuration 802.11a (5.725 – 5.850 GHz)

Refer to Appendix K1 for Band Edge plots

NB: D1 line indicates the 20 dB limit below the highest level of the transmitter

Result: Complies.

4.3.4.2 Calexico2 - WM3B2915ABG - Configuration 802.11b

Refer to Appendix K2 for Band Edge plots

NB: D1 line indicates the 20 dB limit below the highest level of the transmitter

Result: Complies.

4.3.4.3 Calexico2 - WM3B2915ABG - Configuration 802.11g

Refer to Appendix K3 for Band Edge plots

NB: D1 line indicates the 20 dB limit below the highest level of the transmitter

Result: Complies.



5.0 PEAK OUTPUT POWER - Section 15.247 (b)(1) & (3)

Testing was performed in accordance with the requirements of FCC Part 15.247(b)(3).

Measurements were performed while the WLAN transmitter continuously transmitted.

The transmitter output was connected to the spectrum analyser in peak hold mode.

The peak output power measurement was performed using the integration method as per test method # 3 of DA 02-2138. The resolution bandwidth of 1 MHz was used. The video bandwidth of 100 kHz was used ($VBW \geq 1/T$, where T (worst case) = 170 μ S).

Variation by +/- 15% of the supply voltage, in accordance with Section 15.31(e), to the computer power supply did not vary the output power observed.

5.1 Configuration 802.11a

Initial investigations were performed with four modulation types: (BPSK, QPSK, 16QAM and 64QAM). No significant differences in peak output power were observed. Final testing was performed while the transmitter continuously operated with the modulation rate of 54 Mbps (64QAM).

Frequency MHz	P dBm	Limit dBm	P mW	Limit mW	Result
5745	14.1	30	25.7	1000	Pass
5785	14.5	30	28.2	1000	Pass
5825	13.3	30	21.4	1000	Pass

Result: Complies.

5.2 Configuration 802.11b

Initial investigations were performed with three modulation types: (DBPSK, DQPSK and CCK). Power with CCK modulation (rate = 11 Mbps) was observed to be slightly worst. Final testing was performed while the transmitter continuously operating with the modulation rate of 11 Mbps (CCK).

Frequency MHz	P dBm	Limit dBm	P mW	Limit mW	Result
2412	15.1	30	32.4	1000	Pass
2437	14.7	30	29.5	1000	Pass
2462	14.8	30	30.2	1000	Pass

Result: Complies

5.3 Configuration 802.11g

Initial investigations were performed with four modulation types: (BPSK, QPSK, 16QAM and 64QAM). Power with 64QAM modulation (rate = 54 Mbps) was observed to be slightly worst. Final testing was performed while the transmitter continuously operated with the modulation rate of 54 Mbps (64QAM).

Frequency MHz	P dBm	Limit dBm	P mW	Limit mW	Result
2412	15.2	30	33.1	1000	Pass
2437	13.6	30	22.9	1000	Pass
2462	14.1	30	25.7	1000	Pass

Result: Complies



This Laboratory is accredited by the National Association of Testing Authorities, Australia. The tests reported herein have been performed in accordance with its terms of accreditation for FCC Part 15. This document shall not be reproduced, except in full.

6.0 CHANNEL BANDWIDTH

Testing was performed in accordance with the requirements of FCC Part 15.247(a)(2)

In the bands 2400 - 2483.5 MHz and 5725 – 5850 MHz, the minimum 6 dB bandwidth was at least 500 kHz. The 6 dB bandwidth was measured while the transmitter continuously transmitted on a low, middle and high frequency channel.

The transmitter output (antenna port) was connected to the spectrum analyser in peak hold mode.

The resolution bandwidth of 100 kHz and the video bandwidth of 300 kHz were utilised

Measurements for the WLAN were performed on the following frequency channels:

802.11b/g (DTS):

Low (channel 1, 2412 MHz), middle (channel 6, 2437 MHz) and high (Channel 11, 2462 MHz) frequency channel.

802.11a (DTS):

Low (channel 149, 5745 MHz), middle (channel 157, 5785 MHz) and high (Channel 165, 5825 MHz) frequency channel.

6.1 Configuration 802.11a

Initial investigations were performed with four modulation types: (BPSK, QPSK, 16QAM and 64QAM). No significant differences in bandwidth were observed. Final testing was performed while the transmitter continuously operated with the modulation rate of 6 Mbps (BPSK).

Frequency MHz	Bandwidth MHz	Result	6 dB Bandwidth Plots
5745	16.4	Complies	Appendix I1
5785	16.4	Complies	Appendix I1
5825	16.4	Complies	Appendix I1

The minimum 6 dB bandwidth is at least 500 kHz

Result: Complies

6.2 Configuration 802.11b

Initial investigations were performed with three modulation types: (DBPSK, DQPSK and CCK). No significant differences in bandwidth were observed. Final testing was performed while the transmitter continuously operating with the modulation rate of 11 Mbps (CCK).

Frequency MHz	Bandwidth MHz	Result	6 dB Bandwidth Plots
2412.0	9.3	Complies	Appendix I2
2437.0	9.3	Complies	Appendix I2
2462.0	9.2	Complies	Appendix I2

The minimum 6 dB bandwidth is at least 500 kHz

Result: Complies



6.3 Configuration 802.11g

Initial investigations were performed with four modulation types: (BPSK, QPSK, 16QAM and 64QAM). No significant differences in bandwidth were observed. Final testing was performed while the transmitter continuously operated with the modulation rate of 54 Mbps (64QAM).

Frequency MHz	Bandwidth MHz	Result	6 dB Bandwidth Plots
2412.0	16.5	Complies	Appendix I3
2437.0	16.5	Complies	Appendix I3
2462.0	16.1	Complies	Appendix I3

The minimum 6 dB bandwidth is at least 500 kHz

Result: Complies



This Laboratory is accredited by the National Association of Testing Authorities, Australia. The tests reported herein have been performed in accordance with its terms of accreditation for FCC Part 15. This document shall not be reproduced, except in full.

7.0 RADIO FREQUENCY EXPOSURE (HAZARD) INFORMATION

Testing was performed in accordance with the requirements of FCC Part 15.247(b)(5)

Spread spectrum transmitters operating in the 2400 - 2483.5 MHz and 5725 – 5850 MHz bands are required to be operated in a manner that ensures that the public is not exposed to RF energy levels in accordance with CFR 47, Section 1.1307(b)(1).

The WLAN is a mobile device. The antennas are located on the top edge of LCD screen (2 antennas left and right) projected distance of greater than 20cm from user.

The Bluetooth is a portable device. The antenna is located on left side of keyboard near the TAB key projected distance of greater than 1.5cm from the bottom of the laptop.

The separation distance between the WLAN and BT antennas is greater than 20cm. Therefore, they are not co-located transmitters.

MPE calculation for Bluetooth is not applicable and SAR is not required as the power for BT is below the low threshold.

The MPE calculation shown below is for the WLAN mobile device for a separation distance of greater than 20cm.

In accordance with Section 1.1310, the Maximum Permissible Exposure (MPE) limit for the General Population/Uncontrolled Exposure of 1.0 has been applied, i.e 1mW/cm².

Friis transmission formula: $P_d = (P \cdot G) / (4 \cdot \pi \cdot r^2)$

where: P_d = power density (mW/cm²)

P = power input to the antenna (mW)

G = antenna gain (numeric)

r = distance to the center of radiation of the antenna (cm)

The result was extracted from section 5.0 of this report (WLAN Module):

Maximum peak output power = 15.2 dBm = 33.1 mW

Antenna (Inverted F) gain (typical) = 2.08 dBi = 1.61 numeric

Prediction distance = 20 cm

Prediction frequency = 2412 MHz

MPE limit for uncontrolled exposure at prediction frequency = 1 mW/cm²

The power density calculated = 0.011 mW/cm²

Results: Calculations show that the Radio devices with described antennas complied with Maximum Permissible Exposure (MPE) limit for the General Population/Uncontrolled Exposure



8.0 PEAK POWER SPECTRAL DENSITY - Section 15.247(d)

Testing was performed accordance with the requirements of FCC Part 15.247(d)

The transmitter output (antenna port) was connected to the spectrum analyser in peak hold mode.

The resolution bandwidth of 3 kHz and the video bandwidth of 30 kHz were utilised

Measurements for the WLAN were performed on the following frequency channels:

802.11b/g (DTS):

Low (channel 1, 2412 MHz), middle (channel 6, 2437 MHz) and high (Channel 11, 2462 MHz) frequency channel.

802.11a (DTS):

Low (channel 149, 5745 MHz), middle (channel 157, 5785 MHz) and high (Channel 165, 5825 MHz) frequency channel.

8.1 Configuration 802.11a

Initial investigations were performed with four modulation types: (BPSK, QPSK, 16QAM and 64QAM). No significant differences in peak power spectral density were observed. Final testing was performed while the transmitter continuously operated with the modulation rate of 54 Mbps (64QAM).

Frequency MHz	Level dBm	Limit dBm	Result	Spectral Density plots
5745	-23.3	8.0	Complies	Appendix L1
5785	-26.1	8.0	Complies	Appendix L1
5825	-29.1	8.0	Complies	Appendix L1

The specification limit is 8 dBm in any 3 kHz band during a continuous transmission.

Result: Complies

8.2 Configuration 802.11b

Initial investigations were performed with three modulation types: (DBPSK, DQPSK and CCK). Peak power spectral density with CCK modulation (rate = 11 Mbps) was observed to be slightly worst. Final testing was performed while the transmitter continuously operating with the modulation rate of 11 Mbps (CCK).

Frequency MHz	Level dBm	Limit dBm	Result	Spectral Density plots
2412.0	-11.8	8.0	Complies	Appendix L2
2437.0	-11.9	8.0	Complies	Appendix L2
2462.0	-11.8	8.0	Complies	Appendix L2

The specification limit is 8 dBm in any 3 kHz band during a continuous transmission.

Result: Complies



8.3 Configuration 802.11g

Initial investigations were performed with four modulation types: (BPSK, QPSK, 16QAM and 64QAM). No significant differences in peak power spectral density were observed. Final testing was performed while the transmitter continuously operated with the modulation rate of 54 Mbps (64QAM).

Frequency MHz	Level dBm	Limit dBm	Result	Spectral Density plots
2412.0	-20.5	8.0	Complies	Appendix L3
2437.0	-21.0	8.0	Complies	Appendix L3
2462.0	-20.0	8.0	Complies	Appendix L3

The specification limit is 8 dBm in any 3 kHz band during a continuous transmission.

Result: Complies

9.0 ANTENNA REQUIREMENT

Testing to the requirements of FCC Part 15.203 was not applicable as this intentional radiator was designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

10.0 COMPLIANCE STATEMENT

The LifeBook "S" Series, Model: S7020 with Mini-PCI Wireless LAN Module (Calexico2 11a+b/g, Model WM3B2915ABG) & Bluetooth, Model UGXZ5-102A, tested on behalf of Fujitsu Australia Ltd, **comply** with the requirements of 47 CFR, Part 15 Subpart C - Rules for Radio Frequency Devices (intentional radiators), Section 15.247 - Operation in the frequency band 2400 - 2483.5 MHz and 5725 - 5850 MHz.

The test sample also complies with the Industry Canada RSS-210 issue 5 (Low Power Licence-Exempt Radiocommunication Devices (All Frequency Bands)) clause 6.2.2(o) 2400 - 2483.5 MHz Spread Spectrum requirements and the RF exposure requirements of RSS-102.

Results were as follows:

WLAN, Calexico2 802.11b, 802.11g and 802.11a (DTS) - FCC Subpart C, Section 15.247

FCC Part 15, Subpart C Clauses	Industry Canada RSS-210 Clauses	Test Performed	Result
15.203	5.5	Antenna Requirement	Not Applicable
15.205	6.3	Operation in Restricted Band	Complies
15.207	6.6	Conducted Emissions	Complies
15.209	6.3	Radiated Emissions	Complies
15.247 (a)(2)	6.2.2(o)(iv)	Channel Bandwidth	Complies
15.247 (b)(3)	6.2.2(o)(b)	Peak Output Power	Complies
15.247 (b)(5)		Radio Frequency Hazard	Complies
15.247 (c)	6.2.2(o)(e1)	Out of Band Emissions	Complies
15.247 (d)	6.2.2(o)(iv)	Peak Power Spectral Density	Complies

The results for IEEE 802.11a (U-NII) and Bluetooth are reported separately.

Refer to EMC Technologies' test report: M050322_Cert_WM3B2915ABG_11abg_NII_BT (U-NII) and M050322_Cert_BT_WM3B2915ABG_11abg (Bluetooth).



This Laboratory is accredited by the National Association of Testing Authorities, Australia. The tests reported herein have been performed in accordance with its terms of accreditation for FCC Part 15. This document shall not be reproduced, except in full.

TEST REPORT APPENDICES

APPENDIX A: MEASUREMENT INSTRUMENT DETAILS
APPENDIX B: REPORT PHOTOGRAPHS
APPENDIX C: FUNCTIONAL DESCRIPTION
APPENDIX D: BLOCK DIAGRAM
APPENDIX E: SCHEMATICS
APPENDIX F: ANTENNA INFORMATION
APPENDIX G: FCC LABELLING DETAILS
APPENDIX H: USER MANUAL
APPENDIX I: CHANNEL BANDWIDTH PLOTS
APPENDIX J: HARMONICS PLOTS
APPENDIX K: BANDEDGE PLOTS
APPENDIX L: PEAK POWER SPECTRAL DENSITY PLOTS

Attachment 1: RF Exposure Information
Attachment 2: FCC DOC for LifeBook “S” Series
Attachment 3: FCC Part 15B Test Report (Report: FG05-034EAL)



This Laboratory is accredited by the National Association of Testing Authorities, Australia. The tests reported herein have been performed in accordance with its terms of accreditation for FCC Part 15. This document shall not be reproduced, except in full.