

1. RF Exposure Requirements

1.1 General Information

Client Information

Applicant:	HCS (Suzhou) Limited
Address of applicant:	19F-20F, Building B-3rd, No.209 Zhuyuan Road, New District, Suzhou, P.R.China
Manufacturer:	HCS (Suzhou) Limited
Address of manufacturer:	19F-20F, Building B-3rd, No.209 Zhuyuan Road, New District, Suzhou, P.R.China
Factory:	Himit (Yueyang) Technology Ltd.
Address of factory	Building 4, Lingang High-tech Industrial Park, Yueyang Area, China (Hunan) Free Trade Pilot Zone

General Description of EUT:

Product Name:	Remote Control
Trade Name:	Vispera, Veltech
Model No.:	RC4213802/01BR
	RC4213404/01BR, RC4213405/01BR, RC4213406/01BR, Babylon
Adding Model(s):	RCU, RC421XXXX/XXR, RC421XXXX/XXBR, ("X"=0-9."B"means packed with battery)
Rated Voltage:	DC3V
Battery Capacity:	/
FCC ID:	2AGOFRC421B
Equipment Type:	Mobile device

Technical Characteristics of EUT:

Bluetooth

Bluetooth Version:	BLE5.0
Frequency Range:	2402-2480MHz
RF Output Power:	1Mbps:1.85dBm (Conducted) 2Mbps:1.90dBm (Conducted)
Data Rate:	1Mbps; 2Mbps
Modulation:	GFSK
Quantity of Channels:	40
Channel Separation:	2MHz
Type of Antenna:	PCB Antenna
Antenna Gain:	-1.1dBi

SRD

Support Standards:	IEEE802.15.4
Frequency Range:	2405-2480MHz

RF Output Power: -2.10dBm (Conducted)
 Type of Modulation: MSK
 Type of Antenna: PCB Antenna
 Antenna Gain: -1.1dBi

1.2 RF Exposure Exemption

According to §1.1307(b)(3) and 447498 D04 Interim General RF Exposure Guidance v01, system operating under the provisions of this section shall be operating in a manner that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure.

Option A: FCC Rule Part 1.1307 (b)(3)(i)(A): The available maximum time-averaged power is no more than 1mW, regardless of separation distance.

Option B: FCC Rule Part 1.1307 (b)(3)(i)(B): The available maximum time-averaged power or effective radiated power (ERP), whichever is greater, is less than or equal to the threshold P_{th} (mW) described in the following formula. P_{th} is given by:

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases}$$

Where

$$x = -\log_{10} \left(\frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right) \text{ and } f \text{ is in GHz;}$$

and

$$ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases}$$

d = the separation distance (cm);

Option C: FCC Rule Part 1.1307 (b)(3)(i)(C): The minimum separation distance (R in meters) from the body of a nearby person for the frequency (f in MHz) at which the source operates, the ERP (watts) is no more than the calculated value prescribed for that frequency. R must be at least $\lambda/2\pi$, where λ is the free-space operating wavelength in meters.

Single RF Sources Subject to Routine Environmental Evaluation	
RF Source frequency (MHz)	Threshold ERP (watts)
0.3-1.34	$1,920 R^2$
1.34-30	$3,450 R^2/f^2$
30-300	$3.83 R^2$

300-1,500	0.0128 R ² f
1,500-100,000	19.2R ²

For Multiple RF sources: FCC Rule Part 1.1307(b)(3)(ii):

- (A) The available maximum time-averaged power of each source is no more than 1 mW and there is a separation distance of two centimeters between any portion of a radiating structure operating and the nearest portion of any other radiating structure in the same device, except if the sum of multiple sources is less than 1 mW during the time-averaging period, in which case they may be treated as a single source (separation is not required).
- (B) In the case of fixed RF sources operating in the same time-averaging period, or of multiple mobile or portable RF sources within a device operating in the same time averaging period, if the sum of the fractional contributions to the applicable thresholds is less than or equal to 1 as indicated in the following equation.

$$\sum_{i=1}^a \frac{P_i}{P_{th,i}} + \sum_{j=1}^b \frac{ERP_j}{ERP_{th,j}} + \sum_{k=1}^c \frac{Evaluated_k}{Exposure Limit_k} \leq 1$$

1.3 Calculated Result

Radio Access Technology	Min. Frequency	Max. Output Power	Max. Tune-Up Output Power	Antenna Gain	Duty Cycle	Tune-Up EIRP
	(MHz)	(dBm)	(dBm)	(dBi)	(%)	(dBm)
Bluetooth	2402	1.90	2.00	-1.1	100	0.90
SRD	2405	-2.10	-2.00	-1.1	100	-3.10

Frequency (MHz)	Option	Min. Distance	Tune-Up ERP		Exposure Limit	Ratio	Result
		(cm)	(dBm)	(mW)	(mW)		Pass/Fail
2402	B	0.5	-1.25	0.75	2.786195349	0.27	Pass
2405	B	0.5	-5.25	0.30	2.786195349	0.11	Pass

Note: 1. $ERP = EIRP - 2.15 \text{ dB}$; $EIRP = \text{Output Power} + \text{Antenna gain}$

2. Option A, B and C refers as clause 1.2.

3. For option B, $P_{th}(\text{mW})$ convert to $Exposure Limit(\text{mW})$; For option C, $ERP(\text{W})$ convert to $Exposure Limit(\text{mW})$.

4. $Ratio = \text{Tune-Up ERP}(\text{mW}) / \text{Exposure Limit}(\text{mW})$

Mode for Simultaneous Multi-band Transmission:

Radio Access Technology	Ratio 1	Ratio 2	Simultaneous Ratio	Limit	Result
					Pass/Fail
--	--	--	--	--	--

Note: BT and SRD can't transmit at the same time.

Result: Pass