

FCC Test Report

FCC ID : SUFIFT21544A

Equipment : InfoTag 1.54 G2 COLOUR

Model No. : InfoTag 1.54

Brand Name : DIGI

Applicant : DIGI SINGAPORE PTE. LTD.

Address : 4 Leng Kee Rd, #05-03/04/05&11, SIS Building,

Singapore 159088

Standard : 47 CFR FCC Part 15.249

Received Date : May 03, 2019 Tested Date : May 09, 2019

We, International Certification Corp., would like to declare that the tested sample has been evaluated and in compliance with the requirement of the above standards. The test results contained in this report refer exclusively to the product. It may be duplicated completely for legal use with the approval of the applicant. It shall not be reproduced except in full without the written approval of our laboratory.

Reviewed by: Approved by:

Along Chen / Assistant Manager Gary Chang / Manager

Testing Laboratory 2732

Report No.: FR921907-01 Page: 1 of 24



Table of Contents

1	GENERAL DESCRIPTION	5
1.1	Information	5
1.2	Local Support Equipment List	7
1.3	Test Setup Chart	7
1.4	The Equipment List	8
1.5	Test Standards	
1.6	Deviation from Test Standard and Measurement Procedure	g
1.7	Measurement Uncertainty	
2	TEST CONFIGURATION	10
2.1	Testing Condition	10
2.2	The Worst Test Modes and Channel Details	
3	TRANSMITTER TEST RESULTS	11
3.1	Radiated Emission	11
3.2	20dB and Occupied Bandwidth	23
4	TEST LABORATORY INFORMATION	24



Release Record

Report No.	Version	Description	Issued Date
FR921907-01	Rev. 01	Initial issue	May 21, 2019

Report No.: FR921907-01 Page: 3 of 24



Summary of Test Results

FCC Rules	Test Items	Measured	Result
15.207	AC Power Line Conducted Emissions	Note ¹	N/A
15.249(a)	Field Strength of Fundamental	Meet the requirement of limit	Pass
15.249(a)(d)	Field Strength of Harmonics and Emissions Radiated outside of the Specified Frequency Bands	Meet the requirement of limit	Pass
15.215(c)	20dB bandwidth	Meet the requirement of limit	Pass
15.203	Antenna Requirement	Meet the requirement of limit	Pass

N/A means Not Applicable.

Note¹: The EUT consumes DC power from battery, so the test is not required.

Declaration of Conformity:

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

Comments and Explanations:

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

Report No.: FR921907-01 Page: 4 of 24



1 General Description

1.1 Information

1.1.1 Specification of the Equipment under Test (EUT)

RF General Information							
Frequency Range (MHz)	Modulation	Channel Number	Data Rate				
2400-2483.5	GFSK	2402-2480	0-78 [79]	250 KBPS			

1.1.2 Antenna Details

Ant. No.	Туре	Gain (dBi)	Connector	Remark
1	CHIP	-2.4	PCB SURFACE MOUNT	

1.1.3 Power Supply Type of Equipment under Test (EUT)

Power Supply Type	3Vdc from battery

1.1.4 Accessories

No.	Equipment	Description
1	Coin Battery	Brand Name: panasonic Model Name: CR2450 Power Rating: 3Vdc
2	Coin Battery	Brand Name: henlimax Model Name: CR2477 Power Rating: 3Vdc

Note: Two Coin Batterys had been covered during the pretest, and found that panasonic coin battery was the worst case and was selected for final test.

Report No.: FR921907-01 Page : 5 of 24



1.1.5 Channel List

Frequency band (MHz)					2400~	2483.5	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	20	2422	40	2442	60	2462
1	2403	21	2423	41	2443	61	2463
2	2404	22	2424	42	2444	62	2464
3	2405	23	2425	43	2445	63	2465
4	2406	24	2426	44	2446	64	2466
5	2407	25	2427	45	2447	65	2467
6	2408	26	2428	46	2448	66	2468
7	2409	27	2429	47	2449	67	2469
8	2410	28	2430	48	2450	68	2470
9	2411	29	2431	49	2451	69	2471
10	2412	30	2432	50	2452	70	2472
11	2413	31	2433	51	2453	71	2473
12	2414	32	2434	52	2454	72	2474
13	2415	33	2435	53	2455	73	2475
14	2416	34	2436	54	2456	74	2476
15	2417	35	2437	55	2457	75	2477
16	2418	36	2438	56	2458	76	2478
17	2419	37	2439	57	2459	77	2479
18	2420	38	2440	58	2460	78	2480
19	2421	39	2441	59	2461		

1.1.6 Test Tool and Duty Cycle

Test Tool	SmartRF_Studio 7, Version: 1.16.1		
Duty Cycle and Duty Factor	Duty Cycle (%)	Duty Factor (dB)	
Duty Cycle and Duty Factor	89.59	0.48	


Report No.: FR921907-01 Page: 6 of 24



1.2 Local Support Equipment List

	Support Equipment List							
No. Equipment Brand Model FCC ID Remark					Remarks			
1	Notebook	DELL	Latitude E5470	DoC				
2	Base Station	DIGI	BS-04		Provided by applicant.			

1.3 Test Setup Chart



Report No.: FR921907-01 Page: 7 of 24



1.4 The Equipment List

Test Item	Radiated Emission	Radiated Emission					
Test Site	966 chamber1 / (03CH01-WS)						
Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Until		
Spectrum Analyzer	R&S	FSV40	101498	Dec. 27, 2018	Dec. 26, 2019		
Receiver	R&S	ESR3	101658	Dec. 11, 2018	Dec. 10, 2019		
Bilog Antenna	SCHWARZBECK	VULB9168	VULB9168-522	Jul. 18, 2018	Jul. 17, 2019		
Horn Antenna 1G-18G	SCHWARZBECK	BBHA 9120 D	BBHA 9120 D 1096	Dec. 18, 2018	Dec. 17, 2019		
Horn Antenna 18G-40G	SCHWARZBECK	BBHA 9170	BBHA 9170517	Nov. 15, 2018	Nov. 14, 2019		
Loop Antenna	R&S	HFH2-Z2	100330	Nov. 09, 2018	Nov. 08, 2019		
Loop Antenna Cable	KOAX KABEL	101354-BW	101354-BW	Oct. 08, 2018	Oct. 07, 2019		
Preamplifier	EMC	EMC02325	980225	Jul. 20, 2018	Jul. 19, 2019		
Preamplifier	Agilent	83017A	MY39501308	Oct. 04, 2018	Oct. 03, 2019		
Preamplifier	EMC	EMC184045B	980192	Aug. 09, 2018	Aug. 08, 2019		
RF Cable	EMC	EMC104-SM-SM-80 00	181106	Oct. 08, 2018	Oct. 07, 2019		
RF Cable	HUBER+SUHNER	SUCOFLEX104	MY16019/4	Oct. 08, 2018	Oct. 07, 2019		
RF Cable	HUBER+SUHNER	SUCOFLEX104	MY16014/4	Oct. 08, 2018	Oct. 07, 2019		
LF cable 1M	EMC	EMCCFD400-NM-N M-1000	160502	Oct. 08, 2018	Oct. 07, 2019		
LF cable 3M	Woken	CFD400NL-LW	CFD400NL-001	Oct. 08, 2018	Oct. 07, 2019		
LF cable 10M	Woken	CFD400NL-LW	CFD400NL-002	Oct. 08, 2018	Oct. 07, 2019		
Measurement Software	AUDIX	e3	6.120210g	NA	NA		
	val of instruments liste	d above is one year.					

Report No.: FR921907-01 Page: 8 of 24



1.5 Test Standards

According to the specification of EUT, the EUT must comply with following standards and KDB documents.

47 CFR FCC Part 15.249

ANSI C63.10-2013

1.6 Deviation from Test Standard and Measurement Procedure

None

1.7 Measurement Uncertainty

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor (k=2)

Measurement Uncertainty				
Parameters	Uncertainty			
Bandwidth	±34.130 Hz			
Radiated emission ≤ 1GHz	±3.41 dB			
Radiated emission > 1GHz	±4.59 dB			

Report No.: FR921907-01 Page: 9 of 24



2 Test Configuration

2.1 Testing Condition

Test Item	Test Site	Ambient Condition	Tested By
Radiated Emissions	03CH01-WS	22-23°C / 63-65%	Akun Chung
RF Conducted	TH01-WS	23°C / 65%	Akun Chung

FCC Designation No.: TW2732FCC site registration No.: 181692

➤ ISED#: 10807A

➤ CAB identifier: TW2732

2.2 The Worst Test Modes and Channel Details

Test item	Mode	Test Frequency (MHz)	Data Rate	Test Configuration
Field Strength of Fundamental	GFSK	2402, 2441, 2480	250 KBPS	
Radiated Emissions ≤ 1GHz	GFSK	2480	250 KBPS	
Radiated Emissions > 1GHz	GFSK	2402, 2441, 2480	250 KBPS	
20dB bandwidth	GFSK	2402, 2441, 2480	250 KBPS	

NOTE:

Report No.: FR921907-01 Page: 10 of 24

^{1.} The EUT was pretested with 3 orientations placed on the table for the radiated emission measurement – X, Y, and Z-plane. The **Y-plane** results were found as the worst case and were shown in this report.



3 Transmitter Test Results

3.1 Radiated Emission

This section includes field strength of fundamental, field strength of harmonics and emissions radiated outside of the operating frequency bands.

3.1.1 Limit of field strength of fundamental and field strength of harmonics

Fundamental Frequency	Field strength of fundamental (millivolts/meter)	Field strength of harmonics (microvolts/meter)
2400–2483.5 MHz	50	500

3.1.2 Limit of Unwanted Emissions

Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in below table, whichever is the lesser attenuation.

Radiated emission limits							
Frequency Range (MHz)	Field Strength (uV/m)	Field Strength (dBuV/m)	Measure Distance (m)				
0.009~0.490	2400/F(kHz)	48.5 - 13.8	300				
0.490~1.705	24000/F(kHz)	33.8 - 23	30				
1.705~30.0	30	29	30				
30~88	100	40	3				
88~216	150	43.5	3				
216~960	200	46	3				
Above 960	500	54	3				

Note 1:

Qusai-Peak value is measured for frequency below 1GHz except for 9–90 kHz, 110–490 kHz frequency band. Peak and average value are measured for frequency above 1GHz. The limit on average radio frequency emission is as above table. The limit on peak radio frequency emissions is 20 dB above the maximum permitted average emission limit **Note 2:**

Measurements may be performed at a distance other than what is specified provided. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor as below, Frequency at or above 30 MHz: 20 dB/decade Frequency below 30 MHz: 40 dB/decade.

Report No.: FR921907-01 Page: 11 of 24



3.1.3 Test Procedures

- Measurement is made at a semi-anechoic chamber that incorporates a turntable allowing a EUT rotation of 360°. A continuously-rotating, remotely-controlled turntable is installed at the test site to support the EUT and facilitate determination of the direction of maximum radiation for each EUT emission frequency. The EUT is placed at test table. For emissions testing at or below 1 GHz, the table height is 80 cm above the reference ground plane. For emission measurements above 1 GHz, the table height is 1.5 m
- Measurement is made with the antenna positioned in both the horizontal and vertical planes of polarization. The measurement antenna is varied in height (1m ~ 4m) above the reference ground plane to obtain the maximum signal strength. Distance between EUT and antenna is 3 m.
- This investigation is performed with the EUT rotated 360°, the antenna height scanned between 1 m and 4 m, and the antenna rotated to repeat the measurements for both the horizontal and vertical antenna polarizations.

Note:

- Radiated emission below 1GHz
- 1. 120kHz measurement bandwidth of test receiver and Quasi-peak detector is for radiated emission
- Radiated emission above 1GHz / Peak value except fundamental 2. RBW=1MHz, VBW=3MHz and Peak detector

Radiated emission Average value for field strength of fundamental and harmonics The average value is: Average = Peak value + 20log(Duty cycle) Where the duty factor is calculated from following formula:

3.
$$20\log \text{ (Duty cycle)} = 20\log \frac{1*2.18841 \text{ ms}}{100 \text{ ms}} = -33.2 \text{dB}$$


Please see page 22 for plotted duty

- Radiated emission above 1GHz / Average value for other emissions RBW=1MHz, VBW=10Hz and Peak detector
- Radiated emission Peak value for fundamental 5. RBW=3MHz, VBW=10MHz and Peak detector

Report No.: FR921907-01 Page: 12 of 24




3.1.4 Test Setup



Report No.: FR921907-01 Page: 13 of 24



3.1.5 Transmitter Radiated Unwanted Emissions (Below 1GHz)



Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)


*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

Report No.: FR921907-01 Page: 14 of 24





*Factor includes antenna factor, cable loss and amplifier gain


Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

Report No.: FR921907-01 Page: 15 of 24



3.1.6 Transmitter Radiated Unwanted Emissions (Above 1GHz)



Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)


*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR921907-01 Page: 16 of 24



Modulation		GFSK	GFSK			Test Freq. (MHz)				2402		
Polarization		Vertical										
90	Level (dBu	ıV/m)										
90 80	Level (dBu	iV/m)										




	Freq.	Emission level	Limit	Margin	SA reading	Factor	Remark	ANT High	Turn Table
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB		cm	deg
1	2390.00	38.21	54.00	-15.79	41.28	-3.07	Average	105	217
2	2390.00	49.04	74.00	-24.96	52.11	-3.07	Peak	105	217
3	2400.00	40.42	54.00	-13.58	43.52	-3.10	Average	105	217
4	2400.00	54.11	74.00	-19.89	57.21	-3.10	Peak	105	217
5	2402.00	54.34	94.00	-39.66	57.43	-3.09	Average	105	217
6	2402.00	87.54	114.00	-26.46	90.63	-3.09	Peak	105	217
7	4804.00	30.89	54.00	-23.11	27.39	3.50	Average	226	157
8	4804.00	64.09	74.00	-9.91	60.59	3.50	Peak	226	157
9	7206.00	20.18	54.00	-33.82	11.54	8.64	Average	226	157
10	7206.00	53.38	74.00	-20.62	44.74	8.64	Peak	226	157

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB) *Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) - Limit (dBuV/m).

Report No.: FR921907-01 Page: 17 of 24






*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR921907-01 Page: 18 of 24






*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR921907-01 Page: 19 of 24






*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR921907-01 Page: 20 of 24



Modulation	GFSK	Test Freq. (MHz)	2480
Polarization	Vertical		




	Freq.	Emission level	l Limit	Margin	SA reading	Factor	Remark	ANT High	Turn Table
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB		cm	deg
1	2480.00	55.51	94.00	-38.49	58.72	-3.21	Average	108	215
2	2480.00	88.71	114.00	-25.29	91.92	-3.21	Peak	108	215
3	2483.50	38.36	54.00	-15.64	41.58	-3.22	Average	108	215
4	2483.50	52.00	74.00	-22.00	55.22	-3.22	Peak	108	215
5	4960.00	30.17	54.00	-23.83	26.31	3.86	Average	207	163
6	4960.00	63.37	74.00	-10.63	59.51	3.86	Peak	207	163
7	7440.00	19.75	54.00	-34.25	11.21	8.54	Average	100	220
8	7440.00	52.95	74.00	-21.05	44.41	8.54	Peak	100	220

*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR921907-01 Page: 21 of 24





Report No.: FR921907-01 Page: 22 of 24



3.2 20dB and Occupied Bandwidth

3.2.1 Test Procedures


- 1. Set resolution bandwidth (RBW) = 100 kHz, Video bandwidth = 300 kHz.
- 2. Detector = Peak(20 dB bandwidth) / Sample(Occupied bandwidth), Trace mode = max hold
- 3. Sweep = auto couple, Allow the trace to stabilize.
- 4. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower) that are attenuated by 20dB relative to the maximum level measured in the fundamental emission.
- 5. Use the occupied measurement function of specturm analyzer to measure 99% occupied bandwidth.

3.2.2 Test Setup



3.2.3 20dB and Occupied Bandwidth

Freq. (MHz)	20dB Bandwidth (MHz)	Occupied Bandwidth (MHz)
2402	0.64	0.75
2441	0.69	0.80
2480	0.73	0.82



Report No.: FR921907-01 Page: 23 of 24



4 Test laboratory information

Established in 2012, ICC provides foremost EMC & RF Testing and advisory consultation services by our skilled engineers and technicians. Our services employ a wide variety of advanced edge test equipment and one of the widest certification extents in the business.

International Certification Corp (EMC and Wireless Communication Laboratory), it is our definitive objective is to institute long term, trust-based associations with our clients. The expectation we set up with our clients is based on outstanding service, practical expertise and devotion to a certified value structure. Our passion is to grant our clients with best EMC / RF services by oriented knowledgeable and accommodating staff.

Our Test sites are located at Linkou District and Kwei Shan District. Location map can be found on our website http://www.icertifi.com.tw.

Linkou

Tel: 886-2-2601-1640 No. 30-2, Ding Fwu Tsuen, Lin Kou District, New Taipei City, Taiwan, R.O.C.

Kwei Shan

Tel: 886-3-271-8666 No. 3-1, Lane 6, Wen San 3rd St., Kwei Shan District, Tao Yuan City 333, Taiwan, R.O.C.

Kwei Shan Site II

Tel: 886-3-271-8640 No. 14-1, Lane 19, Wen San 3rd St., Kwei Shan District, Tao Yuan City 333, Taiwan, R.O.C.

If you have any suggestion, please feel free to contact us as below information.

Tel: 886-3-271-8666 Fax: 886-3-318-0155

Email: ICC_Service@icertifi.com.tw

___END___

Report No.: FR921907-01 Page: 24 of 24