




Fig.54. Conducted spurious emission: 8DPSK, Channel 39, 2441MHz




Fig.55. Conducted spurious emission: 8DPSK, Channel 39, 30MHz - 1GHz




Fig.56. Conducted spurious emission: 8DPSK, Channel 39, 1GHz - 3GHz




Fig.57. Conducted spurious emission: 8DPSK, Channel 39, 3GHz - 10GHz




Fig.58. Conducted spurious emission: 8DPSK, Channel 39, 10GHz – 26GHz




Fig.59. Conducted spurious emission: 8DPSK, Channel 78, 2480MHz




Fig.60. Conducted spurious emission: 8DPSK, Channel 78, 30MHz - 1GHz




Fig.61. Conducted spurious emission: 8DPSK, Channel 78, 1GHz - 3GHz




Fig.62. Conducted spurious emission: 8DPSK, Channel 78, 3GHz - 10GHz




Fig.63. Conducted spurious emission: 8DPSK, Channel 78, 10GHz - 26GHz

B.6. Transmitter Spurious Emission - Radiated

Method of Measurement: See ANSI C63.10-2013-clause 6.4 & 6.5 & 6.6

Measurement Limit:

Standard	Limit
FCC 47 CFR Part 15.247, 15.205, 15.209	20dB below peak output power

radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) (see § 15.205(c)).

Limit in restricted band:

Frequency (MHz)	Field strength(μ V/m)	Measurement distance (m)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30

Frequency of emission (MHz)	Field strength (μ V/m)	Field strength (dBuV/m)	Measurement distance (m)
30-88	100	40	3
88-216	150	43.5	3
216-960	200	46	3
Above 960	500	54	3

Set up:

Tabletop devices shall be placed on a nonconducting platform with nominal top surface dimensions 1 m by 1.5 m. For emissions testing at or below 1 GHz, the table height shall be 80 cm above the reference ground plane. For emission measurements above 1 GHz, the table height shall be 1.5 m

The EUT and transmitting antenna shall be centered on the turntable.

Note:

1. A "reference path loss" is established and the A_{Rpl} is the attenuation of "reference path loss", and including the gain of receive antenna, the gain of the preamplifier, the cable loss.

P_{Mea} is the field strength recorded from the instrument.

The measurement results are obtained as described below:

Result= $P_{Mea}+A_{Rpl}= P_{Mea}+Cable\ Loss+Antenna\ Factor$

2. The range of evaluated frequency is from 9 kHz to 26GHz. Measurement value showed here only up to 6 maximum emissions noted.

Peak Measurement results

GFSK Ch 0

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
2381.190	59.84	3.5	27.7	28.71	74.0	14.2	V
2382.319	59.89	3.5	27.7	28.75	74.0	14.1	V
4804.000	43.77	-28.9	33.9	38.80	74.0	30.2	V
7206.000	42.91	-26.8	35.6	34.14	74.0	31.1	H
9608.000	42.99	-26.9	36.9	32.98	74.0	31.0	V
12010.000	44.59	-26.4	38.9	32.08	74.0	29.4	H

GFSK Ch 39

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
2372.400	46.69	-32.0	31.9	46.80	74.0	27.3	V
2500.400	46.92	-31.8	32.0	46.71	74.0	27.1	V
4882.000	42.09	-29.2	34.0	37.32	74.0	31.9	V
7323.000	41.56	-27.3	35.6	33.25	74.0	32.4	V
9764.000	42.23	-27.4	37.1	32.49	74.0	31.8	H
12205.000	44.87	-25.3	38.9	31.22	74.0	29.1	V

GFSK Ch 78

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
2484.066	60.40	3.4	27.7	29.29	74.0	13.6	V
2485.406	60.11	3.4	27.7	29.01	74.0	13.9	H
4960.000	42.32	-28.9	34.0	37.26	74.0	31.7	H
7440.000	41.52	-27.8	35.6	33.69	74.0	32.5	V
9920.000	42.16	-27.0	37.3	31.90	74.0	31.8	H
12400.000	45.33	-24.8	38.9	31.24	74.0	28.7	H

$\pi/4$ DQPSK Ch 0

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
2364.679	60.14	3.3	27.7	29.15	74.0	13.9	H
2383.351	59.53	3.5	27.7	28.39	74.0	14.5	V
4804.000	43.60	-28.9	33.9	38.63	74.0	30.4	V
7206.000	41.84	-26.8	35.6	33.08	74.0	32.2	V
9608.000	42.48	-26.9	36.9	32.47	74.0	31.5	V
12010.000	45.06	-26.4	38.9	32.54	74.0	28.9	V

$\pi/4$ DQPSK Ch 39

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
2375.400	46.29	-31.9	31.9	46.31	74.0	27.7	H
2539.600	47.22	-31.9	32.1	47.05	74.0	26.8	V
4882.000	41.00	-29.2	34.0	36.23	74.0	33.0	V
7323.000	41.73	-27.3	35.6	33.41	74.0	32.3	H
9764.000	43.12	-27.4	37.1	33.39	74.0	30.9	V
12205.000	45.23	-25.3	38.9	31.58	74.0	28.8	H

$\pi/4$ DQPSK Ch 78

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
2484.222	60.80	3.4	27.7	29.69	74.0	13.2	V
2485.247	60.03	3.4	27.7	28.94	74.0	14.0	V
4960.000	42.49	-28.9	34.0	37.43	74.0	31.5	H
7440.000	40.68	-27.8	35.6	32.85	74.0	33.3	H
9920.000	42.84	-27.0	37.3	32.58	74.0	31.2	V
12400.000	45.12	-24.8	38.9	31.03	74.0	28.9	H

8DPSK Ch 0

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
2358.388	59.76	3.4	27.6	28.73	74.0	14.2	V
2380.648	59.84	3.5	27.7	28.71	74.0	14.2	H
4804.000	41.28	-28.9	33.9	36.30	74.0	32.7	V
7206.000	42.83	-26.8	35.6	34.06	74.0	31.2	H
9608.000	42.36	-26.9	36.9	32.35	74.0	31.6	V
12010.000	45.05	-26.4	38.9	32.53	74.0	29.0	V

8DPSK Ch 39

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
2366.400	46.07	-32.2	31.9	46.37	74.0	27.9	H
2507.200	46.62	-31.8	32.0	46.36	74.0	27.4	H
4882.000	41.74	-29.2	34.0	36.98	74.0	32.3	H
7323.000	41.23	-27.3	35.6	32.92	74.0	32.8	H
9764.000	43.76	-27.4	37.1	34.02	74.0	30.2	H
12205.000	44.31	-25.3	38.9	30.66	74.0	29.7	V

8DPSK Ch 78

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
2483.506	60.06	3.4	27.7	28.95	74.0	13.9	V
2484.647	60.08	3.4	27.7	28.98	74.0	13.9	H
4960.000	41.18	-28.9	34.0	36.11	74.0	32.8	V
7440.000	42.04	-27.8	35.6	34.20	74.0	32.0	V
9920.000	43.39	-27.0	37.3	33.13	74.0	30.6	H
12400.000	46.39	-24.8	38.9	32.30	74.0	27.6	V

Average Measurement results

GFSK Ch 0

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
2359.913	45.08	3.4	27.6	14.03	54.0	8.9	V
2375.925	45.03	3.4	27.7	13.98	54.0	9.0	V
4803.500	33.60	-28.9	33.9	28.62	54.0	20.4	H
7206.000	31.59	-26.8	35.6	22.82	54.0	22.4	V
9608.000	31.66	-26.9	36.9	21.64	54.0	22.3	V
12010.000	33.13	-26.4	38.9	20.61	54.0	20.9	V

GFSK Ch 39

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
2434.275	45.19	3.5	27.7	14.04	54.0	8.8	V
2447.288	45.21	3.5	27.7	14.04	54.0	8.8	V
4882.000	32.33	-29.2	34.0	27.56	54.0	21.7	V
7323.000	31.20	-27.3	35.6	22.88	54.0	22.8	H
9764.000	31.36	-27.4	37.1	21.62	54.0	22.6	H
12205.000	33.86	-25.3	38.9	20.21	54.0	20.1	V

GFSK Ch 78

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
2492.850	45.47	3.4	27.7	14.39	54.0	8.5	V
2501.963	45.47	3.5	27.7	14.29	54.0	8.5	V
4960.000	33.20	-28.9	34.0	28.13	54.0	20.8	H
7440.000	30.73	-27.8	35.6	22.89	54.0	23.3	V
9920.000	31.82	-27.0	37.3	21.56	54.0	22.2	H
12400.000	34.05	-24.8	38.9	19.96	54.0	19.9	H

$\pi/4$ DQPSK Ch 0

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
2376.825	45.13	3.4	27.7	14.06	54.0	8.9	V
2389.575	44.93	3.5	27.7	13.79	54.0	9.1	V
4803.500	33.68	-28.9	33.9	28.71	54.0	20.3	V
7206.000	31.74	-26.8	35.6	22.97	54.0	22.3	V
9608.000	31.69	-26.9	36.9	21.67	54.0	22.3	V
12010.000	33.26	-26.4	38.9	20.75	54.0	20.7	H

$\pi/4$ DQPSK Ch 39

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
2436.600	45.45	3.5	27.7	14.31	54.0	8.6	V
2444.550	45.26	3.5	27.7	14.11	54.0	8.7	V
4881.000	32.20	-29.2	34.0	27.42	54.0	21.8	H
7323.000	31.32	-27.3	35.6	23.00	54.0	22.7	H
9764.000	31.53	-27.4	37.1	21.79	54.0	22.5	H
12205.000	33.89	-25.3	38.9	20.24	54.0	20.1	H

$\pi/4$ DQPSK Ch 78

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
2495.550	45.52	3.4	27.7	14.41	54.0	8.5	V
2511.000	45.58	3.5	27.7	14.37	54.0	8.4	V
4959.500	33.38	-28.9	34.0	28.31	54.0	20.6	H
7440.000	30.90	-27.8	35.6	23.06	54.0	23.1	V
9920.000	32.09	-27.0	37.3	21.83	54.0	21.9	H
12400.000	34.12	-24.8	38.9	20.03	54.0	19.9	V

8DPSK Ch 0

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
2363.138	45.09	3.4	27.6	14.08	54.0	8.9	V
2377.875	45.09	3.4	27.7	14.00	54.0	8.9	V
4803.500	33.67	-28.9	33.9	28.70	54.0	20.3	V
7206.000	31.82	-26.8	35.6	23.05	54.0	22.2	H
9608.000	31.75	-26.9	36.9	21.73	54.0	22.3	H
12010.000	33.47	-26.4	38.9	20.95	54.0	20.5	V

8DPSK Ch 39

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
2436.563	45.49	3.5	27.7	14.35	54.0	8.5	V
2447.550	45.42	3.5	27.7	14.25	54.0	8.6	V
4881.500	31.82	-29.2	34.0	27.05	54.0	22.2	H
7323.000	31.53	-27.3	35.6	23.21	54.0	22.5	H
9764.000	31.67	-27.4	37.1	21.93	54.0	22.3	V
12205.000	34.20	-25.3	38.9	20.55	54.0	19.8	H

8DPSK Ch 78

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
2495.138	45.49	3.4	27.7	14.38	54.0	8.5	V
2510.850	45.53	3.5	27.7	14.32	54.0	8.5	V
4960.000	30.62	-28.9	34.0	25.56	54.0	23.4	H
7440.000	31.19	-27.8	35.6	23.36	54.0	22.8	V
9920.000	32.36	-27.0	37.3	22.10	54.0	21.6	H
12400.000	34.40	-24.8	38.9	20.30	54.0	19.6	H

Conclusion: Pass

B.7. Time of Occupancy (Dwell Time)

Method of Measurement: See ANSI C63.10-clause 7.8.4

The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:

- Span = zero span, centered on a hopping channel
- RBW = 1 MHz
- VBW $\geq$ RBW
- Sweep = as necessary to capture the entire dwell time per hopping channel
- Detector function = peak
- Trace = max hold

Measure a pulse time in time domain at middle frequency and then count the hopping number in 31.6s(which equals with 0.4 multiply 79) of middle frequency ,then multiply the pulse time and hopping number and record them.

Measurement Limit:

Standard	Limit (ms)
FCC 47 CFR Part 15.247(a) (1)(iii)	< 400

Measurement Result:

For GFSK

Channel	Packet	Pulse time (ms)		Number of Transmissions		Dwell Time (ms)	Conclusion
39	DH1	Fig.64	0.41	Fig.65	320	131.2	P
	DH3	Fig.66	1.66	Fig.67	119	197.54	P
	DH5	Fig.68	2.91	Fig.69	69	200.79	P

For $\pi/4$ DQPSK

Channel	Packet	Pulse time (ms)		Number of Transmissions		Dwell Time (ms)	Conclusion
39	2DH1	Fig.70	0.4	Fig.71	319	127.6	P
	2DH3	Fig.72	1.65	Fig.73	105	173.25	P
	2DH5	Fig.74	2.9	Fig.75	68	197.2	P

For 8DPSK

Channel	Packet	Pulse time (ms)		Number of Transmissions		Dwell Time (ms)	Conclusion
39	3DH1	Fig.76	0.4	Fig.77	320	128	P
	3DH3	Fig.78	1.65	Fig.79	108	178.2	P
	3DH5	Fig.80	2.9	Fig.81	74	214.6	P

Conclusion: PASS

Test graphs as below:




Fig.64. Time of occupancy (Dwell Time): Channel 39, Packet DH1




Fig.65. Number of Transmissions Measurement: Channel 39,Packet DH1




Fig.66. Time of occupancy (Dwell Time): Channel 39, Packet DH3




Fig.67. Number of Transmissions Measurement: Channel 39,Packet DH3




Fig.68. Time of occupancy (Dwell Time): Channel 39, Packet DH5




Fig.69. Number of Transmissions Measurement: Channel 39,Packet DH5




Fig.70. Time of occupancy (Dwell Time): Channel 39, Packet 2-DH1




Fig.71. Number of Transmissions Measurement: Channel 39,Packet 2-DH1




Fig.72. Time of occupancy (Dwell Time): Channel 39, Packet 2-DH3




Fig.73. Number of Transmissions Measurement: Channel 39,Packet 2-DH3




Fig.74. Time of occupancy (Dwell Time): Channel 39, Packet 2-DH5




Fig.75. Number of Transmissions Measurement: Channel 39, Packet 2-DH5




Fig.76. Time of occupancy (Dwell Time): Channel 39, Packet 3-DH1




Fig.77. Number of Transmissions Measurement: Channel 39,Packet 3-DH1




Fig.78. Time of occupancy (Dwell Time): Channel 39, Packet 3-DH3




Fig.79. Number of Transmissions Measurement: Channel 39,Packet 3-DH3




Fig.80. Time of occupancy (Dwell Time): Channel 39, Packet 3-DH5




Fig.81. Number of Transmissions Measurement: Channel 39,Packet 3-DH5

B.8. 20dB Bandwidth

Method of Measurement: See ANSI C63.10-clause 6.9.2

Measurement Procedure - Unwanted Emissions

1. Set RBW = 30kHz.
2. Set VBW = 100 kHz.
3. Set span to 3MHz
4. Detector = peak.
5. Trace Mode = max hold.
6. Sweep = auto couple.
7. Allow the trace to stabilize (this may take some time, depending on the extent of the span).

Measurement Limit:

Standard	Limit
FCC 47 CFR Part 15.247(a)(1)	NA *

Use NdB Down function of the SA to measure the 20dB Bandwidth

* Comment: This test case is not required according to the latest FCC 47 CFR Part 15.247. But the test results are necessary for “carrier frequency separation” test case, in Annex A.8.

Measurement Results:

For GFSK

Channel	20dB Bandwidth (kHz)		Conclusion
0	Fig.82	939.00	NA
39	Fig.83	938.25	NA
78	Fig.84	955.50	NA

For $\pi/4$ DQPSK

Channel	20dB Bandwidth (kHz)		Conclusion
0	Fig.85	1311.75	NA
39	Fig.86	1285.50	NA
78	Fig.87	1284.00	NA

For 8DPSK

Channel	20dB Bandwidth (kHz)		Conclusion
0	Fig.88	1284.00	NA
39	Fig.89	1285.50	NA
78	Fig.90	1284.00	NA

Conclusion: NA

Test graphs as below:




Fig.82. 20dB Bandwidth: GFSK, Channel 0




Fig.83. 20dB Bandwidth: GFSK, Channel 39




Fig.84. 20dB Bandwidth: GFSK, Channel 78




Fig.85. 20dB Bandwidth: $\pi/4$ DQPSK, Channel 0




Fig.86. 20dB Bandwidth: $\pi/4$ DQPSK, Channel 39




Fig.87. 20dB Bandwidth: $\pi/4$ DQPSK, Channel 78




Fig.88. 20dB Bandwidth: 8DPSK, Channel 0




Fig.89. 20dB Bandwidth: 8DPSK, Channel 39




Fig.90. 20dB Bandwidth: 8DPSK, Channel 78

B.9. Carrier Frequency Separation

Method of Measurement: See ANSI C63.10-clause 7.8.2

The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:

- Span = 3MHz
- RBW=300kHz
- VBW=300kHz
- Sweep = auto
- Detector function = peak
- Trace = max hold
- Allow the trace to stabilize

Search the peak marks of the middle frequency and adjacent channel, then record the separation between them.

* Comment: This limit should be over 25 kHz or $(2/3) * 20\text{dB}$ bandwidth, whichever is greater.

Measurement Limit:

Standard	Limit(kHz)
FCC 47 CFR Part 15.247(a)(1)	over 25 kHz or $(2/3) * 20\text{dB}$ bandwidth

Measurement Result:

For GFSK

Channel	Carrier frequency separation (kHz)		Conclusion
39	Fig.91	1329.75	P

For $\pi/4$ DQPSK

Channel	Carrier frequency separation (kHz)		Conclusion
39	Fig.92	1209.00	P

For 8DPSK

Channel	Carrier frequency separation (kHz)		Conclusion
39	Fig.93	1099.50	P

Conclusion: PASS

Test graphs as below:




Fig.91. Carrier frequency separation measurement: GFSK, Channel 39




Fig.92. Carrier frequency separation measurement: $\pi/4$ DQPSK, Channel 39




Fig.93. Carrier frequency separation measurement: 8DPSK, Channel 39

B.10. Number of Hopping Channels

Method of Measurement: See ANSI C63.10-clause 7.8.3

The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:

- Span = the frequency band of operation
- RBW = 500kHz
- VBW = 500kHz
- Sweep = auto
- Detector function = peak
- Trace = max hold
- Allow the trace to stabilize

It might prove necessary to break the span up into subranges to show clearly all of the hopping frequencies. Compliance of an EUT with the appropriate regulatory limit shall be determined for the number of hopping channels. A plot of the data shall be included in the test report.

Measurement Limit:

Standard	Limit
FCC 47 CFR Part 15.247(a) (1)(iii)	At least 15 non-overlapping channels

Measurement Result:

For GFSK

Channel	Number of hopping channels		Conclusion
0~39	Fig.94	79	P
40~78	Fig.95		

For $\pi/4$ DQPSK

Channel	Number of hopping channels		Conclusion
0~39	Fig.96	79	P
40~78	Fig.97		

For 8DPSK

Channel	Number of hopping channels		Conclusion
0~39	Fig.98	79	P
40~78	Fig.99		

Conclusion: PASS

Test graphs as below:




Fig.94. Number of hopping frequencies: GFSK, Channel 0 - 39




Fig.95. Number of hopping frequencies: GFSK, Channel 40 - 78




Fig.96. Number of hopping frequencies: $\pi/4$ DQPSK, Channel 0 - 39




Fig.97. Number of hopping frequencies: $\pi/4$ DQPSK, Channel 40 - 78




Fig.98. Number of hopping frequencies: 8DPSK, Channel 0 - 39




Fig.99. Number of hopping frequencies: 8DPSK, Channel 40 - 78

B.11. AC Powerline Conducted Emission

Method of Measurement:

See Clause 6.2 of ANSI C63.10-2013 specifically.

See Clause 4 and Clause 5 of ANSI C63.10-2013 generally.

The conducted emissions from the AC port of the EUT are measured in a shielding room. The EUT is connected to a Line Impedance Stabilization Network (LISN). An overview sweep with peak detection was performed. The measurements were performed with a quasi-peak detector and if required, an average detector.

The conducted emission measurements were made with the following detector of the test receiver: Quasi-Peak / Average Detector.


The measurement bandwidth is:

Frequency of Emission (MHz)	RBW/IF bandwidth
0.15-30	9kHz

Test Condition:

Voltage (V)	Frequency (Hz)
120	60

Measurement Setup



Measurement Result and limit:
EUT ID: UT19a

Bluetooth (Quasi-peak Limit)

Frequency range (MHz)	Quasi-peak Limit (dBμV)	Result (dBμV)		Conclusion
		With charger		
		bluetooth	Idle	
0.15 to 0.5	66 to 56	Fig.B.11.1	Fig.B.11.2	P
0.5 to 5	56			
5 to 30	60			
NOTE: The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.5 MHz.				

Bluetooth (Average Limit)

Frequency range (MHz)	Average Limit (dBμV)	Result (dBμV)		Conclusion
		With charger		
		bluetooth	Idle	
0.15 to 0.5	56 to 46	Fig.B.11.1	Fig.B.11.2	P
0.5 to 5	46			
5 to 30	50			
NOTE: The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.5 MHz.				

Conclusion: Pass
Test graphs as below:




Fig.B.11.1 AC Powerline Conducted Emission- bluetooth

Note: The graphic result above is the maximum of the measurements for both phase line and neutral line.

Final Result 1

Frequency (MHz)	QuasiPeak (dBμV)	Meas. Time (ms)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.294000	49.5	5000.0	9.000	On	L1	19.9	10.9	60.4
0.510000	42.7	5000.0	9.000	On	N	19.9	13.3	56.0
0.591000	48.7	5000.0	9.000	On	L1	19.8	7.3	56.0
0.694500	46.3	5000.0	9.000	On	L1	19.8	9.7	56.0
0.910500	42.1	5000.0	9.000	On	L1	19.7	13.9	56.0
1.302000	39.7	5000.0	9.000	On	L1	19.7	16.3	56.0

Final Result 2

Frequency (MHz)	Average (dBμV)	Meas. Time (ms)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.294000	33.1	5000.0	9.000	On	N	19.9	17.3	50.4
0.393000	32.6	5000.0	9.000	On	L1	19.9	15.4	48.0
0.510000	31.4	5000.0	9.000	On	L1	19.9	14.6	46.0
0.546000	33.9	5000.0	9.000	On	L1	19.9	12.1	46.0
0.609000	32.0	5000.0	9.000	On	L1	19.8	14.0	46.0
0.775500	32.4	5000.0	9.000	On	L1	19.8	13.6	46.0




Fig.B.11.2 AC Powerline Conducted Emission-Idle

Note: The graphic result above is the maximum of the measurements for both phase line and neutral line.

Final Result 1


Frequency (MHz)	QuasiPeak (dBμV)	Meas. Time (ms)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.199500	49.2	5000.0	9.000	On	L1	19.9	14.4	63.6
0.298500	47.9	5000.0	9.000	On	L1	19.9	12.4	60.3
0.582000	48.5	5000.0	9.000	On	L1	19.8	7.5	56.0
0.699000	42.2	5000.0	9.000	On	N	19.8	13.8	56.0
0.906000	46.2	5000.0	9.000	On	N	19.7	9.8	56.0
1.293000	45.2	5000.0	9.000	On	N	19.7	10.8	56.0

Final Result 2

Frequency (MHz)	Average (dBμV)	Meas. Time (ms)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.199500	35.4	5000.0	9.000	On	L1	19.9	18.2	53.6
0.298500	32.8	5000.0	9.000	On	N	19.9	17.5	50.3
0.496500	31.3	5000.0	9.000	On	N	19.9	14.7	46.1
0.582000	32.6	5000.0	9.000	On	N	19.8	13.4	46.0
0.771000	31.8	5000.0	9.000	On	N	19.8	14.2	46.0
1.320000	31.6	5000.0	9.000	On	N	19.7	14.4	46.0

Note: The measurement results showed here are worst cases of the combinations of different adaptor.

ANNEX C: Accreditation Certificate

United States Department of Commerce National Institute of Standards and Technology NVLAP[®]  ILAC-MRA	
Certificate of Accreditation to ISO/IEC 17025:2017	
NVLAP LAB CODE: 600118-0	
Telecommunication Technology Labs, CAICT Beijing China	
<i>is accredited by the National Voluntary Laboratory Accreditation Program for specific services, listed on the Scope of Accreditation, for:</i>	
Electromagnetic Compatibility & Telecommunications	
<i>This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2017. This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (refer to joint ISO-ILAC-IAF Communiqué dated January 2009).</i>	
2021-09-29 through 2022-09-30 <i>Effective Dates</i>	 DEPARTMENT OF COMMERCE UNITED STATES OF AMERICA  _____ <i>For the National Voluntary Laboratory Accreditation Program</i>

END OF REPORT