



Request for Modular/Limited Modular Approval

e: December 21, 2022				
ject: Manufacturer's Declaration for	oxtimes - Modular Approval	🗆 - Split Modula	r Approval	
	□ - Limited Modular Approval	☐ - Limited Split	Modular Ap	proval
fidentiality Request for: <u>2AEHJDSU84</u>	<u>0</u>			
		Was		
For Items Marked "NO(*)", the	Limited Module Description Must be	Filled Out on the Foll	owing Pages	
Modular A	Approval Requirement		Require	ment Met
does not have to rely upon the shielding pall modular transmitter emissions to comp between the RF circuitry of the module and is installed. Such coupling may result in n	rovided by the device into which it is in- ly with FCC limits. It is also intended to d any wires or circuits in the device into on-compliant operation. The physical c	stalled in order for o prevent coupling o which the module	⊠ - YES	□ - NO(*)
Details: The module contains a metal sh the board next to antenna connector	ield which covers all RF components a	and circuitry. The shi	ield is located	on the top of
			⊠ - YES	□ - NO(*)
Details: Data to the modulation circuit is	s buffered as described in the operation	nal description provid	led with the ap	pplication
to ensure that the module will comply with	h FCC requirements regardless of the de	esign of the power	⊠ - YES	□ - NO(*)
Details: The module contains its own pe	ower supply regulation. Please refer to	schematic filed with	this application	on
§§ 15.203, 15.204(b), 15.204(c), 15.212(a attached or employ a "unique" antenna c antenna, including the cable). The "profes), and 2.929(b). The antenna must either oupler (at all connections between the nessional installation" provision of § 15.2	r be permanently nodule and the 03 is not applicable	⊠ - YES	□ - NO(*)
	fidentiality Request for: 2AEHJDSU84 8 For Items Marked "NO(*)", the Modular Amount of the modular transmitter must have its own does not have to rely upon the shielding pall modular transmitter emissions to compute tween the RF circuitry of the module and is installed. Such coupling may result in note capacitors may be located external to the such a board next to antenna connector. The modular transmitter must have buffer ensure that the module will comply with for over-modulation. 15.212(a)(1)(ii) Details: Data to the modulation circuit is upplying circuitry in the device into whice the modular transmitter must have its own to ensure that the module will comply with supplying circuitry in the device into whice the modular transmitter must have its own to ensure that the module will comply with supplying circuitry in the device into whice the modular transmitter must have its own to ensure that the module contains its own particular transmitter must have its own to ensure that the module will comply with supplying circuitry in the device into whice the modular transmitter must have its own to ensure that the module will comply with supplying circuitry in the device into whice the modular transmitter must have its own to ensure that the module will comply with supplying circuitry in the device into whice the modular transmitter must have its own to ensure that the module will comply with supplying circuitry in the device into whice the modular transmitter must have its own to ensure that the module will comply with supplying circuitry in the device into whice the module will comply with supplying circuitry in the device into whice the module will comply with supplying circuitry in the device into whice the module will comply with supplying circuitry in the device into whice the module will comply with the module will comply with supplying circuitry in the device into whice the module will comply with the module will comply with supplying circuitry in the device into whice the module will comply with the mod	igidentiality Request for: 2AEHJDSU840 8 Basic Requirements − FCC Part 15.212(For Items Marked "NO(*)", the Limited Modular Approval Modular Approval Requirement The modular transmitter must have its own RF shielding. This is intended to ensu does not have to rely upon the shielding provided by the device into which it is in all modular transmitter emissions to comply with FCC limits. It is also intended to between the RF circuitry of the module and any wires or circuits in the device into is installed. Such coupling may result in non-compliant operation. The physical capacitors may be located external to the shielded radio elements. 15.212(a)(1)(i) Details: The module contains a metal shield which covers all RF components at the board next to antenna connector The modular transmitter must have buffered modulation/data inputs (if such input ensure that the module will comply with FCC requirements under conditions of e or over-modulation. 15.212(a)(1)(ii) Details: Data to the modulation circuit is buffered as described in the operation. The modular transmitter must have its own power supply regulation on the modul to ensure that the module will comply with FCC requirements regardless of the described in the device into which the module is installed. 15.212(a)(1). Details: The module contains its own power supply regulation. Please refer to the modular transmitter must accomply with the antenna and transmission system is \$15.203, 15.204(b), 15.204(c), 15.212(a), and 2.929(b). The antenna must eithe attached or employ a "unique" antenna coupler (at all connections between the nantenna, including the cable). The "professional installation" provision of § 15.2	Split Modular Approval	Split Modular Approval





	Details: The module connects to its antenna using an UFL connector which is considered a non-star antennas tested and approved with this device may be found in users manual provided with the applications.		tor. A list of
5	The modular transmitter must be tested in a stand-alone configuration, i.e., the module must not be inside another device during testing. This is intended to demonstrate that the module is capable of complying with Part 15 emission limits regardless of the device into which it is eventually installed. Unless the transmitter module will be battery powered, it must comply with the AC line conducted requirements found in Section 15.207. AC or DC power lines and data input/output lines connected to the module must not contain ferrites, unless they will be marketed with the module (see Section 15.27(a)). The length of these lines shall be length typical of actual use or, if that length is unknown, at least 10 centimeters to insure that there is no coupling between the case of the module and supporting equipment. Any accessories, peripherals, or support equipment connected to the module during testing shall be unmodified or commercially available (see Section 15.31(i)). 15.212(a)(1)(v)	⊠ - YES	□ - NO(*)
	Details: The module was tested stand-alone as shown in test setup photographs filed with this application	ation	





	Modular Approval Requirement	Require	ment Met
6.	The modular transmitter must be labeled with its own FCC ID number, or use an electron display (see KDB Publication 784748). If using a permanently affixed label with its own FCC ID number, if the FCC ID is not visible when the module is installed inside another device, then the outside of the device into which the module is installed must also display a label referring to the enclosed module. This exterior label can use wording such as the following: "Contains Transmitter Module FCC ID: XYZMODEL1" or "Contains FCC ID: XYZMODEL1." Any similar wording that expresses the same meaning may be used. The Grantee may either provide such a label, an example of which must be included in the application for equipment authorization, or, must provide adequate instructions along with the module which explain this requirement. In the latter case, a copy of these instructions must be included in the application for equipment authorization. If the modular transmitter uses an electronic display of the FCC identification number, the information must be readily accessible and visible on the modular transmitter or on the device in which it is installed. If the module is installed inside another device, then the outside of the device into which the module is installed must display a label referring to the enclosed module. This exterior label can use wording such as the following: "Contains FCC certified transmitter module(s)." Any similar wording that expresses the same meaning may be used. The user manual must include instructions on how to access the electronic display. A copy of these instructions must be included in the application for equipment authorization. 15.212(a)(1)(vi)	⊠ - YES	□ - NO(*)
	Details: There is a label on the module as shown in the labeling exhibit filed with this application. Histructions are shown in the installation manual filed with this application.	lost specific la	beling
7.	The modular transmitter must comply with all specific rule or operating requirements applicable to the transmitter, including all the conditions provided in the integration instructions by the grantee. A copy of these instructions must be included in the application for equipment authorization. For example, there are very strict operational and timing requirements that must be met before a transmitter is authorized for operation under Section 15.231. For instance, data transmission is prohibited, except for operation under Section 15.231(e), in which case there are separate field strength level and timing requirements. Compliance with these requirements must be assured. 15.212(a)(1)(vii)	⊠ - YES	□ - NO(*)
	Details: The module complies with FCC Part 15C requirements. Instructions to the OEM installer a installation manual filed with this application.	re provided in	the
8.	The modular transmitter must comply with any applicable RF exposure requirements. For example, FCC Rules in Sections 2.1091, 2.1093 and specific Sections of Part 15, including 15.319(i), 15.407(f), 15.253(f) and 15.255(g), require that Unlicensed PCS, UNII and millimeter wave devices perform routine environmental evaluation for RF Exposure to demonstrate compliance. In addition, spread spectrum transmitters operating under Section 15.247 are required to address RF Exposure compliance in accordance with Section 15.247(b)(4). Modular transmitters approved under other Sections of Part 15, when necessary, may also need to address certain RF Exposure concerns, typically by providing specific installation and operating instructions for users, installers and other interested parties to ensure compliance. 15.212(a)(1)(viii)	⊠ - YES	□ - NO(*)
	Details: The module meets Portable exclusion levels as shown in the RF exposure information filed to	with this appli	cation.





Limited Module Description – When Applicable
* If a module does NOT meet one or more of the above 8 requirements, the applicant may request Limited Modular Approval (LMA).
This Limited Modular Approval (LMA) is applied with the understanding that the applicant will demonstrate and will retain control
over the final installation of the device, such that compliance of the end product is always assured. The operating condition(s) for the
LMA; the module is only approved for use when installed in devices produced by grantee. A description regarding how control of the
end product, into which the module will be installed, will be maintained by the applicant/manufacturer, such that full compliance of
the end product is always ensured should be provided here.

Details: NA

	,		
	Software Considerations – KDB 594280 / KDB 442812 (One of the followin	g 2 items must be applied)	
	Requirement	Requirement M	et
1.	For <u>non-Software Defined Radio</u> transmitter modules where software is used to ensure compliance of the device, technical description must be provided about how such control is implemented to ensure prevention of third-party modification; see KDB Publication 594280.	□ - Provided in Separate Cover Letter	⊠ - N/A
	Details: The Radio Apparatus module is controlled by proprietary firmware. T firmware to operate the device on any other regulatory frequency bands, moduloutside of the FCC approved modes as granted.		
2.	For <u>Software Defined Radio (SDR)</u> devices, transmitter module applications must provide a software security description; see KDB Publication 442812.	- Provided in Separate Cover Letter	⊠ - N/A
	Details: N/A		×
7			

Split Modular Requirements		
Requirement	Provided in Manual	





 For split modular transmitters, specific descriptions for secure communications between front-end and control sections, including authentication and restrictions on third-party modifications; also, instructions to third-party integrators on how control is maintained. 	- Provided in Separate Cover Letter	⊠ - N/A
Details: N/A		-





OEM Integration Manual Guidance - KDB 996369 D03 Section 2 Clear and Specific Instructions Describing the Conditions, Limitations, and Procedures for third-parties to use and/or integrate the module into a host device. Requirement □ - No. If No, and LMA applies, the applicant can optionally choose to not make the following detailed info public. However there still needs to be basic integration instructions for a users manual and the X - YES Is this module intended for information below must still be included in the operational sale to third parties? description. If the applicant wishes to keep this info confidential, this will require a separate statement cover letter explaining the module is not for sale to third parties and that integration instructions are internal confidential documents. Items required to be in the manual – See KDB 996369 D03, Section 2 As of May 1, 2019, the FCC requires ALL the following information to be in the installation manual. Modular transmitter applicants should include information in their instructions for all these items indicating clearly when they are not applicable. For example information on trace antenna design could indicate "Not Applicable". Also if a module is limited to only a grantees own products and not intended for sale to third parties, the user instructions may not need to be detailed and the following items can be placed in the operational description, but this should include a cover letter as cited above. 1. List of applicable FCC rules. KDB 996369 D03, Section 2.2 □ - All Items shown to Only list rules related to the transmitter. the left are provided in 2. Summarize the specific operational use conditions. KDB 996369 D03, Section 2.3 a. Conditions such as limits on antennas, cable loss, reduction of power for point to point the Modular Integration systems, professional installation info Guide (or UM) for Full 3. Limited Module Procedures. KDB 996369 D03, Section 2.4 Modular Approval (MA) Describe alternative means that the grantee uses to verify the host meets the necessary or LMA. limiting conditions When RF exposure evaluation is necessary, state how control will be maintained such that compliance is ensured, such as Class II for new hosts, etc. 4. Trace antenna designs. KDB 996369 D03, Section 2.5 Layout of trace design, parts list, antenna, connectors, isolation requirements, tests for - An LMA applies and design verification, and production test procedures for ensuring compliance. If is approved ONLY for confidential, the method used to keep confidential must be identified and information use by the grantee in provided in the operational description. their own products, and 5. RF exposure considerations. KDB 996369 D03, Section 2.6 a. Clearly and explicitly state conditions that allow host manufacturers to use the module. not intended for sale to Two types of instructions are necessary: first to the host manufacturer to define 3rd parties as provided conditions (mobile, portable – xx cm from body) and second additional text needed to in a separate cover be provided to the end user in the host product manuals.





6. Antennas. KDB 996369 D03, Section 2.7 a. List of antennas included in the application and all applicable professional installer instructions when applicable. The antenna list shall also identify the antenna types (monopole, PIFA, dipole, etc – note that "omni-directional" is not considered a type)	letter. Therefore the information shown to the left is found in the
7. Label and compliance information. KDB 996369 D03, Section 2.8	theory of operation.
a. Advice to host integrators that they need to provide a physical or e-label stating	
"Contains FCC ID: " with their finished product	
8. Information on test modes and additional testing requirements. KDB 996369 D03, Section 2.9	
a. Test modes that should be taken into consideration by host integrators including	
clarifications necessary for stand-alone and simultaneous configurations.	
b. Provide information on how to configure test modes for evaluation	
9. Additional testing, Part 15 Subpart B disclaimer. KDB 996369 D03, Section 2.10	

Sincerely,

By:

(Signature/Title¹)

(Print name)

⁻ Must be signed by applicant contact given for applicant on the FCC site, or by the authorized agent if an appropriate authorized agent letter has been provided. Letters should be placed on appropriate letterhead.