

for a **Connected** World

Nanoblade

Internal Wireless Device Antenna



NANOBLADE INTERNAL EMBEDDED ANTENNA

The evolution of technology has brought the need to communicate everywhere and at all times without being confined to one space. Laird Technologies' internal wireless device antennas feature wide bandwidth to enhance the performance and application of portable wireless devices based on standards such as 802.11 and Bluetooth®. The antennas are specifically designed to be embedded inside devices for aesthetically pleasing integration with high durability.

FEATURES **✓** RoHS

- Covers 2.4 to 2.5 GHz for 802.11b, and 4.9 to 6 GHz for 802.11a and all US, European, and Japanese WLAN applications
- Coaxial cable pigtail with various connector choices
- Omnidirectional patterns at all frequencies with increased gain in upper bands for optimal coverage
- Conformance to European RoHS Directive 2002/95/EC

MARKETS

- Bluetooth® devices
- IEEE 802.11 devices
- WiMAX

global solutions: local support ™

Americas: +1.847 839.6907 IAS-AmericasEastSales@lairdtech.com

Europe: +1.32.80.7866.12 IAS-EUSales@lairdtech.com Asia: +1.65.6.243.8022 IAS-AsiaSales@lairdtech.com

www.lairdtech.com





Nanoblade Internal Wireless Device Antenna

| ELECTRICAL SPECIFICATIONS | | | |
|---------------------------|---|--|--|
| Frequency | 2.4 - 2.5 GHz, 4.9 - 6 GHz | | |
| Gain | 2 dBi (2.4-2.5 GHz), 3.9 dBi (5.15-5.35 GHz), 4 dBi (5.6 GHz) | | |
| Polarization | Vertical, Omnidirectional | | |
| Nominal Impedance | 50 ohms | | |
| VSWR | 2:1 max across all bands | | |
| Size | 2 in x 0.65 in | | |

CABLE AND CONNECTORS

| MODEL NUMBER | PART NUMBER | CABLE | CONNECTOR |
|-----------------|-------------|-----------------|-----------|
| NanoBlade-MMCX4 | CAF94504 | 100mm, rg-178 | RA-MMCX |
| NanoBlade-IP04 | CAF94505 | 100mm, Ø 1.13mm | IPEX MHF |

ELEVATION PATTERNS, PHI=0





