



Occupied Bandwidth

Channel



15MHz Bandwidth QPSK

15MHz Bandwidth 16QAM



Lowest



Middle



Highest





Occupied Bandwidth

Channel



20MHz Bandwidth QPSK

20MHz Bandwidth 16QAM



Lowest



Middle



Highest





Spurious Emissions at Antenna Terminal



Channel

1.4MHz Bandwidth QPSK



Lowest



Middle



Highest





Spurious Emissions at Antenna Terminal



Channel

3MHz Bandwidth QPSK



Lowest



Middle



Highest





Spurious Emissions at Antenna Terminal



Channel

5MHz Bandwidth QPSK



Lowest



Middle



Highest





Spurious Emissions at Antenna Terminal



Channel

10MHz Bandwidth QPSK



Lowest



Middle



Highest





Spurious Emissions at Antenna Terminal



Channel

15MHz Bandwidth QPSK



Lowest



Middle



Highest





Spurious Emissions at Antenna Terminal



Channel

20MHz Bandwidth QPSK



Lowest




iddle




Highest




Out of band emission, Band Edge




Out of band emission, Band Edge



Out of band emission, Band Edge



Out of band emission, Band Edge



4.13 Radiated Spurious Emissions

Serial Number:	1OGW	Test Date:	2022/11/20~2022/11/22
Test Site:	996-1/966-2	Test Mode:	Transmitting
Tester:	Carl Xue,coco	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	25.5~26.3	Relative Humidity: (%)	62~65	ATM Pressure: (kPa)	100.7~101.1
----------------------	-----------	---------------------------	-------	---------------------------	-------------

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Sunol Sciences	Antenna	JB6	A082520-5	2020/10/19	2023/10/18
R&S	EMI Test Receiver	ESR3	102724	2022/07/15	2023/07/14
TIMES MICROWAVE	Coaxial Cable	LMR-600-UltraFlex	C-0470-02	2022/07/17	2023/07/16
TIMES MICROWAVE	Coaxial Cable	LMR-600-UltraFlex	C-0780-01	2022/07/17	2023/07/16
EMCO	Adjustable Dipole Antenna	3121C	9109-756	N/A	N/A
MICRO-COAX	Coaxial Cable	UFA210B-0-0720-300300	99G1448	2022/07/17	2023/07/16
Agilent	Signal Generator	E8247C	MY43321352	2022/04/01	2023/03/31
ETS-Lindgren	Horn Antenna	3115	9912-5985	2020/10/13	2023/10/12
R&S	Spectrum Analyzer	FSV40	101591	2022/07/15	2023/07/14
MICRO-COAX	Coaxial Cable	UFA210A-1-1200-70U300	217423-008	2022/08/07	2023/08/06
MICRO-COAX	Coaxial Cable	UFA210A-1-2362-300300	235780-001	2022/08/07	2023/08/06
Mini	Pre-amplifier	ZVA-183-S+	5969001149	2022/11/09	2023/11/08
AH	Double Ridge Guide Horn Antenna	SAS-571	1396	2021/10/18	2024/10/17
MICRO-COAX	Coaxial Cable	UFA210B-0-0720-300300	99G1448	2022/07/17	2023/07/16
PASTERNAK	Horn Antenna	PE9852/2F-20	112002	2021/02/05	2024/02/04
PASTERNAK	Horn Antenna	PE9852/2F-20	112001	2021/02/05	2024/02/04
AH	Preamplifier	PAM-1840VH	190	2022/11/09	2023/11/08
PASTERNAK	Horn Antenna	PE9850/2F-20	072001	2021/02/05	2024/02/04
PASTERNAK	Horn Antenna	PE9850/2F-20	072002	2021/02/05	2024/02/04
MICRO-COAX	Coaxial Cable	UFB142A-1-2362-200200	235772-001	2022/08/07	2023/08/06

*** Statement of Traceability:** China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data:

Please refer to the below table and plots.

Note: The device can be mounted in multiple orientations, test was performed with X,Y, Z Axis according to C63.26 figure 5, the worst orientation was photographed and it's data was recorded.

Cellular Band (PART 22H)**30 MHz-10 GHz:**

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
GSM 850 Frequency:824.2MHz								
623.06	H	27.75	-45.99	0.00	0.48	-46.47	-13.00	33.47
623.06	V	39.31	-32.00	0.00	0.48	-32.48	-13.00	19.48
1648.400	H	63.83	-40.50	8.68	0.80	-32.62	-13.00	19.62
1648.400	V	58.82	-45.59	8.68	0.80	-37.71	-13.00	24.71
2472.600	H	75.64	-25.14	9.38	1.00	-16.76	-13.00	3.76
2472.600	V	71.33	-29.40	9.38	1.00	-21.02	-13.00	8.02
3296.800	H	44.51	-52.17	10.32	1.15	-43.00	-13.00	30.00
3296.800	V	42.37	-54.07	10.32	1.15	-44.90	-13.00	31.90
GSM 850 Frequency:836.6MHz								
634.08	H	27.24	-46.44	0.00	0.51	-46.95	-13.00	33.95
634.08	V	37.39	-33.72	0.00	0.51	-34.23	-13.00	21.23
1673.200	H	61.01	-43.30	8.71	0.85	-35.44	-13.00	22.44
1673.200	V	58.19	-46.22	8.71	0.85	-38.36	-13.00	25.36
2509.800	H	75.38	-25.23	9.42	1.01	-16.82	-13.00	3.82
2509.800	V	74.39	-26.23	9.42	1.01	-17.82	-13.00	4.82
3346.400	H	38.31	-58.86	10.34	1.16	-49.68	-13.00	36.68
3346.400	V	42.32	-54.71	10.34	1.16	-45.53	-13.00	32.53
GSM 850 Frequency:848.8MHz								
647.55	H	27.42	-46.18	0.00	0.52	-46.70	-13.00	33.70
647.55	V	37.15	-33.72	0.00	0.52	-34.24	-13.00	21.24
1697.600	H	48.93	-55.36	8.74	0.90	-47.52	-13.00	34.52
1697.600	V	51.03	-53.39	8.74	0.90	-45.55	-13.00	32.55
2546.400	H	74.88	-25.45	9.47	1.01	-16.99	-13.00	3.99
2546.400	V	72.37	-27.91	9.47	1.01	-19.45	-13.00	6.45
3395.200	H	36.88	-60.81	10.36	1.19	-51.64	-13.00	38.64
3395.200	V	39.41	-58.25	10.36	1.19	-49.08	-13.00	36.08

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
WCDMA Band 5 Frequency:826.4 MHz								
726.90	H	20.96	-51.82	0.00	0.52	-52.34	-13.00	39.34
687.28	V	21.29	-48.86	0.00	0.53	-49.39	-13.00	36.39
1652.800	H	37.12	-67.21	8.68	0.81	-59.34	-13.00	46.34
1652.800	V	38.89	-65.52	8.68	0.81	-57.65	-13.00	44.65
2479.200	H	34.38	-66.38	9.39	1.01	-58.00	-13.00	45.00
2479.200	V	36.12	-64.61	9.39	1.01	-56.23	-13.00	43.23
3305.600	H	34.56	-62.17	10.32	1.15	-53.00	-13.00	40.00
3305.600	V	33.86	-62.64	10.32	1.15	-53.47	-13.00	40.47
WCDMA Band 5 Frequency:836.6MHz								
719.30	H	21.39	-51.54	0.00	0.49	-52.03	-13.00	39.03
724.36	V	21.27	-48.12	0.00	0.51	-48.63	-13.00	35.63
1673.200	H	42.70	-61.61	8.71	0.85	-53.75	-13.00	40.75
1673.200	V	36.65	-67.76	8.71	0.85	-59.90	-13.00	46.90
2509.800	H	35.45	-65.16	9.42	1.01	-56.75	-13.00	43.75
2509.800	V	35.72	-64.90	9.42	1.01	-56.49	-13.00	43.49
3346.400	H	34.48	-62.69	10.34	1.16	-53.51	-13.00	40.51
WCDMA Band 5 Frequency:846.6MHz								
716.80	H	21.15	-51.83	0.00	0.50	-52.33	-13.00	39.33
578.89	V	20.93	-50.77	0.00	0.46	-51.23	-13.00	38.23
1693.200	H	35.94	-68.36	8.73	0.89	-60.52	-13.00	47.52
1693.200	V	37.67	-66.75	8.73	0.89	-58.91	-13.00	45.91
2539.800	H	35.86	-64.52	9.46	1.01	-56.07	-13.00	43.07
2539.800	V	34.92	-65.42	9.46	1.01	-56.97	-13.00	43.97
3386.400	H	34.67	-62.92	10.35	1.18	-53.75	-13.00	40.75
3386.400	V	34.26	-63.28	10.35	1.18	-54.11	-13.00	41.11

PCS Band (PART 24E)**30 MHz-20 GHz:**

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
GSM 1900 Frequency:1850.2MHz								
706.69	H	21.81	-51.37	0.00	0.54	-51.91	-13.00	38.91
692.22	V	21.21	-48.85	0.00	0.54	-49.39	-13.00	36.39
3700.400	H	71.43	-25.89	10.60	1.25	-16.54	-13.00	3.54
3700.400	V	71.36	-25.94	10.60	1.25	-16.59	-13.00	3.59
5550.600	H	52.19	-41.07	11.44	1.49	-31.12	-13.00	18.12
5550.600	V	52.95	-40.15	11.44	1.49	-30.20	-13.00	17.20
GSM 1900 Frequency:1880MHz								
586.84	H	21.76	-52.36	0.00	0.47	-52.83	-13.00	39.83
716.85	V	21.31	-48.24	0.00	0.50	-48.74	-13.00	35.74
3760.000	H	63.04	-33.37	10.66	1.24	-23.95	-13.00	10.95
3760.000	V	71.79	-24.50	10.66	1.24	-15.08	-13.00	2.08
5640.000	H	53.26	-40.19	11.33	1.54	-30.40	-13.00	17.40
5640.000	V	60.02	-33.31	11.33	1.54	-23.52	-13.00	10.52
GSM 1900 Frequency:1909.8MHz								
716.77	H	21.02	-51.96	0.00	0.50	-52.46	-13.00	39.46
729.35	V	21.71	-47.57	0.00	0.53	-48.10	-13.00	35.10
3819.600	H	69.84	-26.02	10.72	1.29	-16.59	-13.00	3.59
3819.600	V	64.02	-31.70	10.72	1.29	-22.27	-13.00	9.27
5729.400	H	45.42	-48.06	11.22	1.59	-38.43	-13.00	25.43
5729.400	V	50.63	-42.73	11.22	1.59	-33.10	-13.00	20.10

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
WCDMA Band II, Frequency:1852.4 MHz								
731.92	H	21.66	-51.02	0.00	0.53	-51.55	-13.00	38.55
726.93	V	21.13	-48.20	0.00	0.52	-48.72	-13.00	35.72
3704.800	H	34.70	-62.56	10.60	1.25	-53.21	-13.00	40.21
3704.800	V	34.96	-62.27	10.60	1.25	-52.92	-13.00	39.92
5557.200	H	34.46	-58.82	11.43	1.49	-48.88	-13.00	35.88
5557.200	V	34.28	-58.85	11.43	1.49	-48.91	-13.00	35.91
WCDMA Band II, Frequency:1880 MHz								
647.66	H	21.37	-52.23	0.00	0.52	-52.75	-13.00	39.75
589.21	V	21.05	-50.66	0.00	0.48	-51.14	-13.00	38.14
3760.000	H	35.67	-60.74	10.66	1.24	-51.32	-13.00	38.32
3760.000	V	34.76	-61.53	10.66	1.24	-52.11	-13.00	39.11
5640.000	H	33.56	-59.89	11.33	1.54	-50.10	-13.00	37.10
5640.000	V	33.92	-59.41	11.33	1.54	-49.62	-13.00	36.62
WCDMA Band II, Frequency:1907.6MHz								
729.58	H	20.87	-51.85	0.00	0.53	-52.38	-13.00	39.38
714.40	V	20.86	-48.75	0.00	0.50	-49.25	-13.00	36.25
3815.200	H	34.08	-61.77	10.72	1.29	-52.34	-13.00	39.34
3815.200	V	34.68	-61.01	10.72	1.29	-51.58	-13.00	38.58
5722.800	H	35.15	-58.34	11.23	1.58	-48.69	-13.00	35.69
5722.800	V	33.68	-59.67	11.23	1.58	-50.02	-13.00	37.02

AWS Band(Part 27)**30 MHz-20 GHz:**

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
WCDMA Band IV, Frequency:1712.4 MHz								
729.50	H	21.13	-51.59	0.00	0.53	-52.12	-13.00	39.12
729.56	V	21.44	-47.84	0.00	0.53	-48.37	-13.00	35.37
3424.800	H	35.95	-61.82	10.37	1.17	-52.62	-13.00	39.62
3424.800	V	35.01	-62.73	10.37	1.17	-53.53	-13.00	40.53
5137.200	H	33.80	-59.82	11.28	1.46	-50.00	-13.00	37.00
5137.200	V	35.38	-58.12	11.28	1.46	-48.30	-13.00	35.30
WCDMA Band IV, Frequency:1732.6 MHz								
729.35	H	21.71	-51.02	0.00	0.53	-51.55	-13.00	38.55
719.35	V	21.27	-48.23	0.00	0.49	-48.72	-13.00	35.72
3465.200	H	35.41	-62.40	10.39	1.15	-53.16	-13.00	40.16
3465.200	V	35.39	-62.38	10.39	1.15	-53.14	-13.00	40.14
5197.800	H	33.28	-60.85	11.32	1.44	-50.97	-13.00	37.97
5197.800	V	33.57	-60.41	11.32	1.44	-50.53	-13.00	37.53
WCDMA Band IV, Frequency:1752.6MHz								
729.54	H	21.07	-51.65	0.00	0.53	-52.18	-13.00	39.18
714.18	V	21.26	-48.35	0.00	0.50	-48.85	-13.00	35.85
3505.200	H	35.81	-62.02	10.41	1.18	-52.79	-13.00	39.79
3505.200	V	34.57	-63.20	10.41	1.18	-53.97	-13.00	40.97
5257.800	H	34.07	-59.66	11.35	1.47	-49.78	-13.00	36.78
5257.800	V	33.72	-59.79	11.35	1.47	-49.91	-13.00	36.91

LTE Bands:
(The Worst modulation and bandwidth was below)

LTE Band 2 (30MHz-20GHz):

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
QPSK, Frequency: 1850.7 MHz								
729.35	H	21.07	-51.66	0.00	0.53	-52.19	-13.00	39.19
719.19	V	21.10	-48.40	0.00	0.49	-48.89	-13.00	35.89
3701.400	H	34.09	-63.22	10.60	1.25	-53.87	-13.00	40.87
3701.400	V	33.44	-63.85	10.60	1.25	-54.50	-13.00	41.50
5552.100	H	33.27	-60.00	11.44	1.49	-50.05	-13.00	37.05
5552.100	V	33.64	-59.46	11.44	1.49	-49.51	-13.00	36.51
QPSK, Frequency: 1880 MHz								
661.29	H	20.86	-52.67	0.00	0.51	-53.18	-13.00	40.18
732.14	V	21.07	-48.15	0.00	0.53	-48.68	-13.00	35.68
3760.000	H	35.14	-61.27	10.66	1.24	-51.85	-13.00	38.85
3760.000	V	33.92	-62.37	10.66	1.24	-52.95	-13.00	39.95
5640.000	H	34.06	-59.39	11.33	1.54	-49.60	-13.00	36.60
5640.000	V	33.28	-60.05	11.33	1.54	-50.26	-13.00	37.26
QPSK, Frequency: 1909.3 MHz								
699.51	H	21.31	-52.01	0.00	0.55	-52.56	-13.00	39.56
721.94	V	21.18	-48.26	0.00	0.50	-48.76	-13.00	35.76
3818.600	H	35.76	-60.10	10.72	1.29	-50.67	-13.00	37.67
3818.600	V	34.38	-61.33	10.72	1.29	-51.90	-13.00	38.90
5727.900	H	34.26	-59.22	11.23	1.59	-49.58	-13.00	36.58
5727.900	V	33.19	-60.17	11.23	1.59	-50.53	-13.00	37.53

LTE Band 4 (30MHz-20GHz):

EYE Band 4 (50MHz - 20GHz).								
Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
QPSK, Frequency: 1710.7 MHz								
501.17	H	21.06	-54.75	0.00	0.45	-55.20	-13.00	42.20
724.36	V	21.60	-47.79	0.00	0.51	-48.30	-13.00	35.30
3421.400	H	34.31	-63.45	10.37	1.17	-54.25	-13.00	41.25
3421.400	V	35.13	-62.60	10.37	1.17	-53.40	-13.00	40.40
5132.100	H	34.06	-59.51	11.28	1.47	-49.70	-13.00	36.70
5132.100	V	33.13	-60.33	11.28	1.47	-50.52	-13.00	37.52
QPSK, Frequency: 1732.5 MHz								
724.26	H	21.11	-51.72	0.00	0.51	-52.23	-13.00	39.23
432.90	V	20.76	-53.48	0.00	0.41	-53.89	-13.00	40.89
3465.000	H	35.48	-62.33	10.39	1.15	-53.09	-13.00	40.09
3465.000	V	35.37	-62.40	10.39	1.15	-53.16	-13.00	40.16
5197.500	H	33.79	-60.34	11.32	1.44	-50.46	-13.00	37.46
5197.500	V	33.71	-60.27	11.32	1.44	-50.39	-13.00	37.39
QPSK, Frequency: 1754.3MHz								
750.32	H	20.73	-51.57	0.00	0.54	-52.11	-13.00	39.11
719.32	V	20.81	-48.69	0.00	0.49	-49.18	-13.00	36.18
3508.600	H	35.62	-62.21	10.41	1.18	-52.98	-13.00	39.98
3508.600	V	35.42	-62.35	10.41	1.18	-53.12	-13.00	40.12
5262.900	H	33.62	-60.11	11.35	1.47	-50.23	-13.00	37.23
5262.900	V	34.11	-59.40	11.35	1.47	-49.52	-13.00	36.52

LTE Band 5(30MHz-10GHz):

EYE Band 5 (35MHz to 3GHz).								
Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
QPSK, Frequency: 824.7 MHz								
719.93	H	21.65	-51.27	0.00	0.49	-51.76	-13.00	38.76
702.49	V	21.03	-48.84	0.00	0.55	-49.39	-13.00	36.39
1649.400	H	36.17	-68.16	8.68	0.80	-60.28	-13.00	47.28
1649.400	V	39.97	-64.44	8.68	0.80	-56.56	-13.00	43.56
2474.100	H	35.20	-65.58	9.38	1.00	-57.20	-13.00	44.20
2474.100	V	35.53	-65.20	9.38	1.00	-56.82	-13.00	43.82
3298.800	H	34.59	-62.09	10.32	1.15	-52.92	-13.00	39.92
3298.800	V	33.99	-62.45	10.32	1.15	-53.28	-13.00	40.28
QPSK, Frequency: 836.5 MHz								
565.35	H	21.02	-53.52	0.00	0.46	-53.98	-13.00	40.98
717.41	V	20.88	-48.66	0.00	0.50	-49.16	-13.00	36.16
1673.000	H	35.43	-68.88	8.71	0.85	-61.02	-13.00	48.02
1673.000	V	39.22	-65.19	8.71	0.85	-57.33	-13.00	44.33
2509.500	H	35.62	-64.99	9.42	1.01	-56.58	-13.00	43.58
2509.500	V	35.57	-65.05	9.42	1.01	-56.64	-13.00	43.64
3346.000	H	35.08	-62.08	10.34	1.16	-52.90	-13.00	39.90
3346.000	V	35.19	-61.83	10.34	1.16	-52.65	-13.00	39.65
QPSK, Frequency: 848.3 MHz								
573.32	H	21.85	-52.54	0.00	0.46	-53.00	-13.00	40.00
709.91	V	20.98	-48.72	0.00	0.52	-49.24	-13.00	36.24
1696.600	H	36.63	-67.66	8.74	0.89	-59.81	-13.00	46.81
1696.600	V	36.28	-68.14	8.74	0.89	-60.29	-13.00	47.29
2544.900	H	35.11	-65.23	9.47	1.01	-56.77	-13.00	43.77
2544.900	V	35.28	-65.02	9.47	1.01	-56.56	-13.00	43.56
3393.200	H	34.40	-63.27	10.36	1.19	-54.10	-13.00	41.10
3393.200	V	34.06	-63.57	10.36	1.19	-54.40	-13.00	41.40

LTE Band 7 (30MHz-26.5GHz):

Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)			
Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)				Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)
QPSK, Frequency: 2502.5 MHz								
729.47	H	20.94	-51.78	0.00	0.53	-52.31	-25.00	27.31
572.84	V	20.75	-50.94	0.00	0.46	-51.40	-25.00	26.40
5005.000	H	33.67	-59.29	11.20	1.47	-49.56	-25.00	24.56
5005.000	V	33.42	-59.40	11.20	1.47	-49.67	-25.00	24.67
7507.500	H	33.86	-55.93	10.90	1.95	-46.98	-25.00	21.98
7507.500	V	33.74	-56.55	10.90	1.95	-47.60	-25.00	22.60
QPSK, Frequency:2535 MHz								
661.15	H	21.21	-52.32	0.00	0.51	-52.83	-25.00	27.83
726.90	V	20.78	-48.55	0.00	0.52	-49.07	-25.00	24.07
5070.000	H	33.14	-60.05	11.24	1.47	-50.28	-25.00	25.28
5070.000	V	32.98	-60.11	11.24	1.47	-50.34	-25.00	25.34
7605.000	H	33.61	-55.86	10.88	2.01	-46.99	-25.00	21.99
7605.000	V	33.66	-56.53	10.88	2.01	-47.66	-25.00	22.66
QPSK, Frequency: 2567.5 MHz								
696.85	H	22.04	-51.30	0.00	0.55	-51.85	-25.00	26.85
729.35	V	22.20	-47.08	0.00	0.53	-47.61	-25.00	22.61
5135.000	H	33.56	-60.04	11.28	1.47	-50.23	-25.00	25.23
5135.000	V	33.92	-59.57	11.28	1.47	-49.76	-25.00	24.76
7702.500	H	33.15	-56.37	10.86	1.97	-47.48	-25.00	22.48
7702.500	V	33.71	-56.47	10.86	1.97	-47.58	-25.00	22.58

LTE Band 12 (30MHz-10GHz):

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
QPSK, Frequency: 699.7 MHz								
729.32	H	22.11	-50.62	0.00	0.53	-51.15	-13.00	38.15
729.32	V	22.13	-47.15	0.00	0.53	-47.68	-13.00	34.68
1399.400	H	38.95	-64.75	8.22	0.71	-57.24	-13.00	44.24
1399.400	V	38.12	-65.63	8.22	0.71	-58.12	-13.00	45.12
2099.100	H	35.03	-66.85	9.16	0.91	-58.60	-13.00	45.60
2099.100	V	35.26	-66.57	9.16	0.91	-58.32	-13.00	45.32
2798.800	H	35.08	-64.85	9.88	1.04	-56.01	-13.00	43.01
2798.800	V	35.34	-64.46	9.88	1.04	-55.62	-13.00	42.62
QPSK, Frequency: 707.5 MHz								
785.02	H	21.92	-49.68	0.00	0.56	-50.24	-13.00	37.24
739.60	V	21.43	-47.63	0.00	0.55	-48.18	-13.00	35.18
1415.000	H	36.32	-67.35	8.26	0.72	-59.81	-13.00	46.81
1415.000	V	36.86	-66.86	8.26	0.72	-59.32	-13.00	46.32
2122.500	H	34.92	-67.07	9.17	0.92	-58.82	-13.00	45.82
2122.500	V	34.61	-67.36	9.17	0.92	-59.11	-13.00	46.11
2830.000	H	35.96	-63.84	9.93	1.06	-54.97	-13.00	41.97
2830.000	V	35.42	-64.31	9.93	1.06	-55.44	-13.00	42.44
QPSK, Frequency: 715.3 MHz								
586.94	H	21.37	-52.75	0.00	0.47	-53.22	-13.00	40.22
638.42	V	21.13	-49.90	0.00	0.52	-50.42	-13.00	37.42
1430.600	H	36.62	-67.01	8.31	0.73	-59.43	-13.00	46.43
1430.600	V	35.86	-67.83	8.31	0.73	-60.25	-13.00	47.25
2145.900	H	34.84	-67.26	9.19	0.93	-59.00	-13.00	46.00
2145.900	V	34.81	-67.30	9.19	0.93	-59.04	-13.00	46.04
2861.200	H	35.35	-64.30	9.98	1.07	-55.39	-13.00	42.39
2861.200	V	34.93	-64.74	9.98	1.07	-55.83	-13.00	42.83

LTE Band 17 (30MHz-10GHz):

EYE Band 17 (50MHz to 3GHz).								
Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
QPSK, Frequency: 706.5 MHz								
580.81	H	20.81	-53.43	0.00	0.46	-53.89	-13.00	40.89
629.55	V	20.96	-50.24	0.00	0.48	-50.72	-13.00	37.72
1413.000	H	37.44	-66.23	8.26	0.72	-58.69	-13.00	45.69
1413.000	V	36.96	-66.76	8.26	0.72	-59.22	-13.00	46.22
2119.500	H	35.63	-66.34	9.17	0.92	-58.09	-13.00	45.09
2119.500	V	35.32	-66.63	9.17	0.92	-58.38	-13.00	45.38
2826.000	H	35.38	-64.43	9.92	1.06	-55.57	-13.00	42.57
2826.000	V	35.24	-64.50	9.92	1.06	-55.64	-13.00	42.64
QPSK, Frequency:710 MHz								
580.82	H	20.69	-53.55	0.00	0.46	-54.01	-13.00	41.01
578.78	V	20.48	-51.22	0.00	0.46	-51.68	-13.00	38.68
1420.000	H	35.86	-67.80	8.28	0.73	-60.25	-13.00	47.25
1420.000	V	38.12	-65.59	8.28	0.73	-58.04	-13.00	45.04
2130.000	H	35.24	-66.78	9.18	0.92	-58.52	-13.00	45.52
2130.000	V	36.25	-65.76	9.18	0.92	-57.50	-13.00	44.50
2840.000	H	35.27	-64.48	9.94	1.06	-55.60	-13.00	42.60
2840.000	V	36.60	-63.11	9.94	1.06	-54.23	-13.00	41.23
QPSK, Frequency: 713.5 MHz								
437.33	H	21.16	-55.95	0.00	0.41	-56.36	-13.00	43.36
558.86	V	21.05	-50.62	0.00	0.47	-51.09	-13.00	38.09
1427.000	H	36.96	-66.68	8.30	0.73	-59.11	-13.00	46.11
1427.000	V	37.84	-65.85	8.30	0.73	-58.28	-13.00	45.28
2140.500	H	35.16	-66.91	9.18	0.93	-58.66	-13.00	45.66
2140.500	V	35.74	-66.34	9.18	0.93	-58.09	-13.00	45.09
2854.000	H	35.25	-64.44	9.97	1.07	-55.54	-13.00	42.54
2854.000	V	35.43	-64.25	9.97	1.07	-55.35	-13.00	42.35

LTE Band 66(30MHz-20GHz):

			Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
QPSK, Frequency: 1710.7 MHz								
729.35	H	21.64	-51.09	0.00	0.53	-51.62	-13.00	38.62
716.68	V	21.54	-48.02	0.00	0.50	-48.52	-13.00	35.52
3421.400	H	35.61	-62.15	10.37	1.17	-52.95	-13.00	39.95
3421.400	V	36.64	-61.09	10.37	1.17	-51.89	-13.00	38.89
5132.100	H	33.95	-59.62	11.28	1.47	-49.81	-13.00	36.81
5132.100	V	34.07	-59.39	11.28	1.47	-49.58	-13.00	36.58
QPSK, Frequency:1745 MHz								
629.62	H	21.03	-52.67	0.00	0.48	-53.15	-13.00	40.15
729.52	V	21.40	-47.88	0.00	0.53	-48.41	-13.00	35.41
3490.000	H	33.83	-64.01	10.40	1.17	-54.78	-13.00	41.78
3490.000	V	34.42	-63.36	10.40	1.17	-54.13	-13.00	41.13
5235.000	H	34.03	-59.87	11.34	1.46	-49.99	-13.00	36.99
5235.000	V	33.25	-60.46	11.34	1.46	-50.58	-13.00	37.58
QPSK, Frequency: 1779.3 MHz								
724.40	H	21.36	-51.47	0.00	0.51	-51.98	-13.00	38.98
714.17	V	21.36	-48.25	0.00	0.50	-48.75	-13.00	35.75
3558.600	H	34.31	-63.36	10.46	1.22	-54.12	-13.00	41.12
3558.600	V	35.25	-62.32	10.46	1.22	-53.08	-13.00	40.08
5337.900	H	34.61	-58.86	11.40	1.47	-48.93	-13.00	35.93
5337.900	V	33.63	-59.70	11.40	1.47	-49.77	-13.00	36.77

Note:

- 1) The unit of Antenna Gain is dBd for frequency below 1GHz, and the unit of Antenna Gain is dBi for frequency above 1GHz.
- 2) Absolute Level = Substituted Level - Cable loss + Antenna Gain
- 3) Margin = Limit-Absolute Level

==== END OF REPORT =====