

GESTEK Lab.

FCC ID: EUNDESIGNOTE70

Report #: 984063F

No. 3, Pau-Tou-Tsuo Valley, Chia-Pau Tsuen, Lin Kou Hsiang, Taipei County, Taiwan, R.O.C. Tel: 886-2-2603-5321 Fax: 886-2-2603-5325

PENTIUM-266 266 MHz
2 TYPE LCDs

Test Report
Application for Certification
On Behalf Of
First International Computer Inc.
Notebook Computer

Model: 7100, 7100XT1D3

FCC ID: EUNDESIGNOTE70

Prepared For:
First International Computer Inc.
6F., Formosa Plastics Rear Bldg 201, Tung-Hwa N. Road,
Taipei, Taiwan, R.O.C.



Report By : Global EMC Standard Tech. Corp.
No.3 Pau-Tou-Tsuo Valley, Chia-Pau
Tsuen, Lin Kou Hsiang, Taipei County,
Taiwan, R.O.C.
Tel : (02) 2603-5321
Fax : (02) 2603-5325

TABLE OF CONTENTS

	Description	Page
1.	Test Report Certification	3
2.	General Information	4
1.1	Production Description.....	4
1.2	Tested System Details	5
1.3	Test Methodology	8
1.4	Test Facility.....	8
3.	Conducted Power Line Test	9
1.5	Test Equipments.....	9
1.6	Block Diagram of Test Setup.....	9
1.7	Conducted Powerline Emission Limit	10
1.8	EUT Configuration on Measurement.....	10
1.9	EUT Exercise Software.....	11
1.10	Conducted Emission Data.....	11
4.	Radiation Emission Test	14
1.11	Test Equipment	14
1.12	Test Setup.....	14
1.13	Radiated Emission Limit.....	15
1.14	EUT Configuration.....	16
1.15	Operating Condition of EUT.....	16
1.16	Radiated Emission Data	16
5.	Photographs	29
1.17	Test Photographs	29
6.	EUT Detail Photographs	33
7.	EMI Reduction Method During Compliance Testing	67
	Appendix A	68
	FCC ID	68
	Appendix B	70
	Circuit (Block) Diagram.....	70
	Appendix C	71
	User Manual	71

1. Test Report Certification

Applicant : First International Computer Inc.

Manufacturer : First International Computer Inc.

EUT Description : Notebook Computer

(A) FCC ID : EUNDESIGNOTE70

(B) Model No. : 7100, 7100XT1D3

(C) Serial No. : ProtoType

(D) Power : 110V/60Hz

(E) Rating DC-O/P : 20V

MEASUREMENT PROCEDURE USED :

CFR 47, Part 15 Radio Frequency Device Subpart B Unintentional Radiators Class **B** :1996
CISPR 22 Limits and methods of measurement of radio disturbance characteristics of
information technology equipment: 1993

ANSI C63.4 Methods of Measurements of Radio-Noise Emissions from Low-Voltage
Electrical and Electronic Equipment in the range of 9kHz to 40GHz. :1992

THE MEASUREMENT SHOWN IN THE ATTACHMENT WERE MADE IN ACCORDANCE
WITH THE PROCEDURES INDICATED, AND THE MAXIMUM ENERGY EMITTED BY
THE EQUIPMENT WAS FOUND TO BE WITHIN THE ABOVE LIMITS APPLICABLE.

NVLAP[®]

Sample Received Date : Apr. 28, 1998

Final Test Date : May, 05, 1998

Documented by : May Tseng

Test Engineer :

Approve & Authorized Signer :

Jackie Lin

Terry Chung

JACKIE LIN

TERRY CHUNG

This test data shown below is traceable to NIST.

2. General Information

1.1 Production Description

Description : Notebook Computer

Model Number : 7100, 7100XT1D3

Serial Number : Prototype

Applicant : First International Computer Inc.

Address : 6F., Formosa Plastics Rear Bldg 201, Tung-Hwa N. Road, Taipei,
Taiwan, R.O.C.

Manufacturer : First International Computer Inc.

Address : 6F., Formosa Plastics Rear Bldg 201, Tung-Hwa N. Road, Taipei,
Taiwan, R.O.C.

FCC ID : EUNDESIGNOTE70

CPU : Pentium 233/266MHz , Clock: 66/66MHz

Power Adaptor : I-LAN, 50W/ M/N: F1700C
AC-100~240V 1.8A/50-60Hz, DC O/P: 20V 2.8A

Mode 1: Model:7100, Pentium 233MHz, Clock: 66MHz, LCD 12.1" DSTN, Resolution 800x600.

Mode 2: Model: 7100XT1D3, Pentium 266MHz, Clock: 66MHz, LCD 14.1" TFT, Resolution 1024X768.

Note: 1.This Notebook computer can support different CPU/Clock frequency modes and can support different types of LCD panel. The test data of 233 MHz/Clock and 266MHz were investigated. The data in this test report reflects the worst-case data for each frequency/video resolution.

1.2 Tested System Details

The FCC IDs/Types for all equipment, plus descriptions of all cables used in the tested system (including inserted cards, which have grants) are:

☒ Host Notebook Computer (EUT)

Model Number	: 7100, 7100XT1D3
Serial Number	: N/A
FCC ID	: EUNDESIGNOTE70
Manufacturer	: First International Computer Inc.
CPU	: INTEL Pentium 233/266MHz, , Clock: 66/66MHz
L2 CACHE	: 512KB
SDRAM SO DIMM	: 16MB
1.44MB Floppy Disk Driver	: TEAC, FD-05HG-5661
2.1 GB Hard Disk Driver	: Hitachi, DK226A-21U (Mode 1)
3.2GB Hard Disk Driver	: Hitachi, DK226-32 (Mode 2)
12.1" FAST DSTN LCD	: HITACHI, SX31S003 (Mode 1)
14.1" TFT	: HITACHI, TX36D61VC (Mode 2)
CCD Camera	: AXIS, PCAM-QU (Mode 2)
DVD ROM	: Toshiba, SD-C2002X (Mode 1)
24X CD-ROM	: Toshiba, XM-1702B (Mode 2)
NIMH Battery Pack	: Simplo, SMP-36S
Power Adaptor	: I-LAN, 50W
Power Cord	: Non-Shielded, Detachable.

☒ Monitor

Model Number	: 4500DC
Serial Number	: 3652100181
FCC ID	: GWGMULTI82
Manufacturer	: OPTIQUEST, INC.
Data Cable	: Shielded, Undetachable, 1.2m
Power Cord	: Shielded, Detachable, 1.5m

☒ Keyboard(PS2)

Model Number	: 5140
Serial Number	: 867110685
FCC ID	: E5XKBM10410
Manufacturer	: BTC
Data Cable	: Sheiled, Undetachable, 1.2 m

☒ Printer

Model Number : C2642A(DJ-400)
Serial Number : MY7951C4J5
FCC ID : B94C2642X
Manufacturer : HP
Data Cable : Shielded, Detachable, 1.8m
Adaptor & Power Cord : AC 110V, 60Hz To DC 30V
: Non-Shielded, Detachable, 1.9m

☒ Modem

Model Number : 1414
Serial Number : 960018041
FCC ID : IFAXDM1414
Manufacturer : ACEEX
Adaptor & Power Cord : Non-Shielded, Detachable, 1.5m
Data Cable : Shielded, Detachable, 1.2m

☒ Earphone

Model Number : PH-12B
Serial Number : N/A
Manufacturer : PRO2 International Corp.
Power Cord : N/A
Data Cable : Non-Shielded, Undetachable, 1.2 m

☒ Microphone

Model Number : N/A
Serial Number : N/A
FCC ID : N/A
Manufacturer : AIWA
Data Cable : Non-Shielded, Undetachable, 1m

☒ Joystick

Model Number : 3001
Serial Number : AE62901417
FCC ID : N/A
Manufacturer : Logitech
Data Cable : Shielded, Undetachable, 0.8m

☒ Speaker

Model Number : DS-203
Serial Number : N/A
FCC ID : N/A
Manufacturer : Crocodile
Power Cord : N/A
Data Cable : Shielded, Undetachable, 1m

☒ Radio Receiver

Model Number : HS-GS162
Serial Number : LYJ1084567
FCC ID : N/A
Manufacturer : AIWA CO., LTD
Power Cord : N/A (Battery)

☒ LCD PROJECTOR

Model Number : CPJ-200
Serial Number : 87881
FCC ID : N/A
Manufacturer : SONY
Power Cord : Non-Shielded, Detachable, 1.8m
Data Cable : Shielded, Detachable, 1.2m*4

☒ Scanner (USB)

Model Number : S-UA1
Serial Number : LTC74803704
FCC ID : DZL211089
Manufacturer : Logitech
Power with Data cable : Shielded, Undetachable, 1.5m with DC 5V

1.3 Test Methodology

Both conducted and radiated testing were performed according to the procedures in ANSI C63.4-1992.

Radiated testing was performed at an antenna to EUT distance of 3 meters.

1.4 Test Facility

Ambient conditions in the laboratory:

Items	Required (IEC 68-1)	Actual
Temperature (°C)	15-35	21-27
Humidity (%RH)	25-75	60-65
Barometric pressure (mbar)	860-1060	950-1000

FCC Site Description : Aug. 10, 1995 File on
Federal Communication Commission
FCC Engineering Laboratory
7435 Oakland Mills Road
Columbia, MD 21046
Reference 31040/SIT1300F2

NVLAP Lab Code : 200085-0
United States Department of commerce
National Institute of Standards and Technology
National Voluntary Laboratory Accreditation Program

Name of firm : Global EMC Standard Tech. Corp.

Site location : No. 3 Pau-Tou Valley, Chia-Pau Tsuen, Lin Kou
Tsiang, Taipei Country, Taiwan, R.O.C.

3. Conducted Power Line Test


1.5 Test Equipments

The following test equipments are used during the conducted power line tests:

Instrument	Manufacturer	Type /Serial No.	Last Calibration	Location	C.E.
Test Receiver	Rohde & Schwarz	ESHS 30 / 8281091010	Dec. 24, 1997	Shield Room #1	✓
L.I.S.N.	Kyoritsu	KNW-407	Jul.1997	Shield Room #1	
L.I.S.N.	Solar	8012-50-R24 / 90038	Jun. 05, 1997	Shield Room #1	✓
L.I.S.N.	EMCO	3825/2 / 91111-1902	Jul.1997	Shield Room #1	
L.I.S.N.	Rohde & Schwarz	ESH3-Z5 / 840567/002	Jun. 05, 1997	Shield Room #1	✓
L.I.S.N.	Schwarzbeck	NNLK 8121	Apr. 10, 1998	Shield Room #1	
Pulse Limiter	Rohde & Schwarz	ESH3-Z2	Jan. 11, 1998	Shield Room #1	✓

Note: All equipment upon which need to calibrated are with calibration period of 1 year.

1.6 Block Diagram of Test Setup



1.7 Conducted Powerline Emission Limit

1.7.1 FCC Limits

Frequency	Maximum RF Line Voltage			
	Class A		Class B	
MHz	uV	dBuV	uV	dBuV
0.45 - 1.705	1000	60.0	250	48.0
1.705 - 30	3000	69.5	250	48.0

Remarks : 1. RF Line Voltage (dBuV) = $20 \log$ RF Line Voltage (uV)

2. In the Above Table, the tighter limit applies at the band edges.

1.7.2 CISPR Limits

Frequency	Maximum RF Line Voltage dB(uV)			
	Class A		Class B	
MHz	QUASI-PEAK	AVERAGE	QUASI-PEAK	AVERAGE
0.15 - 0.50	79	66	66-56	56-46
0.50-5.0	73	60	56	46
5.0 - 30	73	60	60	50

Remarks : In the Above Table, the tighter limit applies at the band edges.

1.8 EUT Configuration on Measurement

The equipments which is listed 3.2 are installed on Conducted Power Line Test to meet the Commission requirement and operating in a manner which tends to maximize its emission characteristics in a normal application.

1.9EUT Exercise Software

The EUT exercise program used during conducted testing was designed to exercise the EUT in a manner similar to a typical use. The exercise sequence is listed as below:

- 3.5.1 Setup the EUT and simulators as shown on 3.2.
- 3.5.2 Turn on the power of all equipments.
- 3.5.3 Boot the PC form Hard Disk.
- 3.5.4 Play CD Disk Music in windows environment.
- 3.5.5 Active CCD Camera operated program. (Mode 2)
- 3.5.5 PC sent "H" Pattern to Both LCD Panel And Ext. Monitor.
- 3.5.6 PC sent "H" Pattern to Parallel (printer) port.
- 3.5.7 PC sent "H" Pattern to Serial port.
- 3.5.8 Repeat 3.5.5 to 3.5.7

1.10Conducted Emission Data

The measurement range of conducted emission which is from **0.45 MHz to 30 MHz** was investigated. All readings are quasi-peak and average values with a resolution Bandwidth of 9 KHz. The initial step in collecting conducted data is a spectrum analyzer peak scan of the measurement range for all the test modes. Then the worst modes were reported the following data pages.

CONDUCTED EMISSION DATA

Date of Test	:	Apr. 29, 1998	Temperature	:	25.3 °C
EUT	:	Notebook Computer	Humidity	:	62.0 %
Test Mode	:	Mode 1	Display Pattern	:	H Pattern

FREQUENCY	READING LEVEL				LIMITS
	LINE 1		LINE 2		
MHz	dBuV	uV	dBuV	uV	uV
0.46366	31.2	36.31	33.9	49.55	250
3.31589	32.4	41.69	31.4	37.15	250
4.13374	36.0	63.10	32.4	41.69	250
**4.48353	37.0	70.79	38.0	79.43	250
6.23373	30.1	31.99	27.0	22.39	250
26.04338	29.0	28.18	26.0	19.95	250

Remarks : 1. All readings are Quasi-peak and average values.


2. “ * ” means that the quasi-peak reading level is lower then the average limits, it is not necessary to measure the average level.

3. “ ** ” means that this data is the worse case emission level.

Attached 2 individual pages of peak scan curve data sheets.


ROHDE & SCHWARZ ESHS 30
GesTek, PowerLine Conducted Emission

EUT: NOTEBOOK COMPUTER
Manuf: FIC
Operator: JACKIE
Test Spec: FCC CLASS B
Comment: Line 1
M/N: 7100



ROHDE & SCHWARZ ESHS 30
GesTek, PowerLine Conducted Emission

EUT: NOTEBOOK COMPUTER
Manuf: FIC
Operator: JACKIE
Test Spec: FCC CLASS B
Comment: Line 2
M/N: 7100



CONDUCTED EMISSION DATA

Date of Test	:	Apr. 24, 1998	Temperature	:	25.4 °C
EUT	:	Notebook Computer	Humidity	:	60.0 %
Test Mode	:	Mode 2	Display Pattern	:	H Pattern


FREQUENCY	READING LEVEL				LIMITS
	LINE 1		LINE 2		
MHz	DBuV	uV	dBuV	uV	uV
0.48349	31.0	35.48	28.6	26.92	250
0.54379	28.9	27.86	36.4	66.07	250
3.81881	35.0	56.23	36.1	63.83	250
**4.12010	37.3	73.28	40.4	104.71	250
6.23587	28.6	26.92	29.1	28.51	250
25.51830	35.0	56.23	32.0	39.81	250

- Remarks :
1. All readings are Quasi-peak and average values.
 2. " * " means that the quasi-peak reading level is lower then the average limits, it is not necessary to measure the average level.
 3. " ** " means that this data is the worse case emission level.

Attached 2 individual pages of peak scan curve data sheets.


ROHDE & SCHWARZ ESHS 30
GESTEK, PowerLine Conducted Emission

EUT: NOTEBOOK COMPUTER
Manuf: FIC
Operator: JACKIE
Test Spec: FCC CLASS B
Comment: Line 1
M/N: 7100XT1D3



ROHDE & SCHWARZ ESHS 30 GESTEK, Powerline Conducted Emission

EUT:
Manuf:
Operator:
Test Spec:
Comment:
FIC
JACKIE
FCC CLASS B
Line 2
M/N: 7100XT1D3



4. Radiation Emission Test

1.11 Test Equipment

The following test equipments are used during the radiated emission tests:


Radiated test was performed on : ☒ Site #1 ☐ Site #2

Instrument	Manufacturer	Type /Serial No.	Last Calibration	Site #1	Site #2
Test Receiver	Rohde & Schwarz	ESVS 30/829007/014	Nov. 15,1997	✓	
Spectrum Analyzer	Anristu	MA2601B/MT16442	Jun. 11,1997	✓	
Pre-Amplifier	HP	7447F/3113A04998	Nov. 16,1997	✓	
Test Receiver	Rohde & Schwarz	ESVS 10/8421122/001	Dec. 26,1997		✓
Spectrum Analyzer	HP	8568B/4315B05847	Jan. 05,1998		✓
Pre Amplifier	HP	8447D/3113A04487	Jan. 05,1998		✓
Antenna 30Mhz-2Ghz	Chase	CBL 6112/2039	Jan. 05,1998	✓	
Bilog Antenna	Chase	CBL6111/1380	May. 22,1997		✓
Dipole Antenna	Schwarzbeck	VHAP/719,UHAP/736	Jun.11,1997		


Note: All equipment upon which need to calibrated are with calibration period of 1 year.

1.12 Test Setup

1.12.1 Block Diagram of Connections between EUT and simulators



1.12.2 Open Test Site Setup Diagram



1.13 Radiated Emission Limit

1.13.1 FCC Class B Limits at 3m

Frequency MHz	Distance Meter	Field Strength	
		$\mu\text{V/M}$	$\text{dB}\mu\text{V/M}$
30 - 88	3	100	40.0
88 - 216	3	150	43.5
216 - 960	3	200	46.0
960 - 2000	3	500	54.0

1.13.2 CISPR Class B Limits at 10m

Frequency MHz	Distance Meter	Field Strength
		$\text{dB}(\mu\text{V/M})$
30 - 230	10	30
230 - 1000	10	37

- Remark :
1. The tighter limit shall apply at the edge between two frequency bands.
 2. Distance refers to the distance in meters between the measuring instrument antenna and the closed point of any part of the device or system.

1.14EUT Configuration

The equipments which is listed 4.2.1 are installed on Radiated Emission Test to meet the Commission requirement and operating in a manner which tends to maximize its emission characteristics in a normal application.

1.15Operating Condition of EUT

Same as Conducted Power Line Test which is listed in 3.5.

1.16Radiated Emission Data

The measurement range of radiated emission which is from 30 MHz to 2 GHz was investigated. All readings are quasi-peak values with a resolution Bandwidth of 120 KHz. The initial step in collecting radiated emission data is a spectrum analyzer peak scan of the measurement range for all the test modes. Then the worst modes were reported the following data pages.

Radiated Emission Data

Date of Test :04-29,1998 Wed Temperature :25.6 deg/C
 EUT :NOTEBOOK Humidity :63 %RH
 Test Mode :Mode 1 Display Pattern:H Pattern

Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Reading Level Horizontal (dBuV/m)	Emission Level Horizontal (dBuV/m)	(uV/m)	Limit (uV/m)
66.835	1.71	6.45	25.81	33.97	49.96	100
* 86.012	2.16	7.82	24.26	34.25	51.55	100
110.594	2.54	11.62	22.76	36.93	70.20	150
200.025	2.94	9.32	25.87	38.13	80.62	150
216.000	3.01	10.45	24.16	37.62	76.06	150
336.098	3.52	13.99	23.19	40.70	108.34	200
368.650	3.63	14.69	21.17	39.48	94.24	200
383.996	3.67	14.96	19.98	38.61	85.23	200
466.969	3.95	17.34	15.69	36.98	70.63	200
712.709	4.75	19.41	14.05	38.21	81.40	200

Remarks: 1. All Readings below 1GHz are Quasi-Peak, above are average value.
 2.“ * ”, means this data is worse case emission level.
 3.Emission Level = Reading Level + Antenna Factor + Cable loss
 4.Deviations from the specifications: None.

Radiated Emission Data

Date of Test : 04-29, 1998 Wed
 EUT : NOTEBOOK
 Humidity : 63 %RH
 Temperature : 25.6 deg/C
 Display Pattern: H Pattern
 Test Mode : Mode 1

Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Reading Level Vertical (dBuV/m)	Emission Level Vertical (dBuV/m)	Limit (uV/m)
-----------------	-----------------	-----------------------	---------------------------------	----------------------------------	--------------

33.361	0.95	16.65	8.09	25.68	19.23
66.673	1.71	6.78	20.39	28.88	27.80
86.019	2.16	8.40	24.24	34.81	54.99
110.585	2.54	11.74	26.19	40.48	105.65
128.875	2.62	12.04	19.13	33.80	48.96
145.348	2.70	11.70	18.97	33.37	46.59
200.018	2.94	10.00	22.52	35.46	59.31
216.000	3.01	10.95	23.49	37.45	74.56
221.188	3.04	11.30	22.07	36.41	66.15
368.640	3.63	16.03	17.83	37.49	74.90
436.600	3.85	17.20	18.96	40.00	100.04
467.975	3.95	17.86	21.01	42.82	138.38
600.831	4.39	19.32	7.80	31.51	37.63

Remarks: 1. All Readings below 1GHz are Quasi-Peak, above are average value.
 2. " * " , means this data is worse case emission level.
 3. Emission Level = Reading Level + Antenna Factor + Cable loss
 4. Deviations from the specifications: None.

Radiated Emission Data

Date of Test :04-29,1998 Wed	Temperature :25.6 deg/C
EUT :NOTEBOOK	Humidity :63 %RH
Test Mode :Mode 2	Display Pattern:H Pattern

Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Reading Level Horizontal (dBuV/m)	Emission Level Horizontal (dBuV/m)	(uV/m)	Limit (uV/m)
33.307	0.95	16.71	9.62	27.28	23.11	100
* 66.780	1.71	6.45	24.30	32.46	41.99	100
111.345	2.54	11.62	14.07	28.24	25.81	150
129.413	2.62	11.92	15.40	29.94	31.41	150
194.111	2.92	9.37	19.17	31.46	37.41	150
200.450	2.94	9.32	21.00	33.26	46.02	150
221.184	3.04	10.95	19.38	33.37	46.62	200
258.821	3.21	13.03	19.08	35.32	58.37	200
270.337	3.26	13.08	17.34	33.68	48.33	200
319.495	3.46	13.65	16.09	33.20	45.72	200
467.975	3.95	17.34	11.87	33.16	45.50	200
712.715	4.75	19.41	9.65	33.81	49.05	200

Remarks: 1. All Readings below 1GHz are Quasi-Peak, above are average value.
 2.“ * ”, means this data is worse case emission level.
 3.Emission Level = Reading Level + Antenna Factor + Cable loss
 4.Deviations from the specifications: None.

Radiated Emission Data

Date of Test :04-29,1998 Wed Temperature :25.6 deg/C
 EUT :NOTEBOOK Humidity :63 %RH
 Test Mode :Mode 2 Display Pattern:H Pattern

Frequency	Cable	Antenna	Reading Level	Emission Level		Limit
	Loss	Factor	Vertical	Vertical		
(MHz)	(dB)	(dB/m)	(dBuV/m)	(dBuV/m)	(uV/m)	(uV/m)
66.673	1.71	6.78	17.37	25.86	19.64	100
* 77.254	1.98	7.25	25.70	34.93	55.80	100
122.887	2.60	12.16	16.71	31.47	37.45	150
157.518	2.76	11.36	19.32	33.43	46.96	150
194.116	2.92	9.97	20.96	33.85	49.24	150
200.425	2.94	10.00	18.80	31.74	38.65	150
226.499	3.06	11.54	16.55	31.15	36.08	200
258.810	3.21	13.20	17.13	33.54	47.56	200
270.340	3.26	13.51	20.02	36.79	69.14	200
368.640	3.63	16.03	21.00	40.66	107.89	200
712.715	4.75	19.97	10.29	35.01	56.29	200

Remarks: 1. All Readings below 1GHz are Quasi-Peak, above are average value.
 2.“ * ”, means this data is worse case emission level.
 3.Emission Level = Reading Level + Antenna Factor + Cable loss
 4.Deviations from the specifications: None.

Radiated Emission Data

Date of Test :04-30,1998 Thu Temperature :26.1 deg/C
EUT :NOTEBOOK Humidity :64 %RH
Test Mode :Mode 1 (Peak) Display Pattern:H Pattern

Frequency	Cable	Antenna	Reading Level	Emission Level		Limit
	Loss	Factor	Horizontal	Horizontal		
(MHz)	(dB)	(dB/m)	(dBuV/m)	(dBuV/m)	(uV/m)	(uV/m)
1062.520	5.90	21.25	30.23	21.78	12.27	500
1195.335	6.30	22.07	28.32	21.30	11.61	500
1328.150	6.72	23.49	30.13	25.17	18.13	500

- Remarks:
1. All Readings below 1GHz are Quasi-Peak, above are average value.
 - 2.“ * ”, means this data is worse case emission level.
 - 3.Emission Level = Reading Level + Antenna Factor + Cable loss-
Amp Factor(35.60, 35.39, 35.18)
 - 4.Deviations from the specifications: None.

Radiated Emission Data

Date of Test :04-30,1998 Thu Temperature :26.1 deg/C
EUT :NOTEBOOK Humidity :64 %RH
Test Mode :Mode 1 (Peak) Display Pattern:H Pattern

Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Reading Level Vertical (dBuV/m)	Emission Level Vertical (dBuV/m)	(uV/m)	Limit (uV/m)
1062.340	5.90	21.95	29.63	21.88	12.42	500
1195.132	6.30	22.06	28.61	21.59	12.01	500
1327.925	6.71	23.44	30.33	25.30	18.41	500

- Remarks: 1. All Readings below 1GHz are Quasi-Peak, above are average value.
2.“ * ”, means this data is worse case emission level.
3.Emission Level = Reading Level + Antenna Factor + Cable loss-
Amp Factor(35.60, 35.39, 35.18)
4.Deviations from the specifications: None.

Radiated Emission Data

Date of Test :04-30,1998 Thu Temperature :26.1 deg/C
EUT :NOTEBOOK Humidity :64 %RH
Test Mode :Mode 1 (Average) Display Pattern:H Pattern

Frequency	Cable	Antenna	Reading Level	Emission Level	Limit	
(MHz)	Loss	Factor	Horizontal	Horizontal	(uV/m)	(uV/m)
	(dB)	(dB/m)	(dBuV/m)	(dBuV/m)		
1062.520	5.90	21.25	24.31	15.86	6.21	500
1195.335	6.30	22.07	23.25	16.23	6.48	500
1328.150	6.72	23.49	24.11	19.15	9.07	500

- Remarks: 1. All Readings below 1GHz are Quasi-Peak, above are average value.
2.“ * ”, means this data is worse case emission level.
3.Emission Level = Reading Level + Antenna Factor + Cable loss-
Amp Factor(35.60, 35.39, 35.18)
4.Deviations from the specifications: None.

Radiated Emission Data

Date of Test :04-30,1998 Thu Temperature :26.1 deg/C
 EUT :NOTEBOOK Humidity :64 %RH
 Test Mode :Mode 1 (Average) Display Pattern:H Pattern

Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Reading Level Vertical (dBuV/m)	Emission Level Vertical (dBuV/m)	(uV/m)	Limit (uV/m)
1062.340	5.90	21.95	23.70	15.95	6.27	500
1195.132	6.30	22.06	25.39	18.37	8.29	500
1327.925	6.71	23.44	24.87	19.84	9.82	500

Remarks: 1. All Readings below 1GHz are Quasi-Peak, above are average value.
 2.“ * ”, means this data is worse case emission level.
 3.Emission Level = Reading Level + Antenna Factor + Cable loss-
 Amp Factor(35.60, 35.39, 35.18)
 4.Deviations from the specifications: None.

Radiated Emission Data

Date of Test :04-30,1998 Thu Temperature :26.1 deg/C
EUT :NOTEBOOK Humidity :64 %RH
Test Mode :Mode 2 (Peak) Display Pattern:H Pattern

Frequency	Cable	Antenna	Reading Level	Emission Level	Limit	
	Loss	Factor	Horizontal	Horizontal		
(MHz)	(dB)	(dB/m)	(dBuV/m)	(dBuV/m)	(uV/m)	(uV/m)
1030.927	5.80	21.12	30.92	22.19	12.87	500
1145.475	6.15	21.72	30.42	22.83	13.85	500
1260.022	6.51	22.64	30.65	24.51	16.81	500

- Remarks: 1. All Readings below 1GHz are Quasi-Peak, above are average value.
2.“ * ”, means this data is worse case emission level.
3.Emission Level = Reading Level + Antenna Factor + Cable loss-
Amp Factor(35.65, 35.47, 35.28)
4.Deviations from the specifications: None.

Radiated Emission Data

Date of Test :04-30,1998 Thu Temperature :26.1 deg/C
EUT :NOTEBOOK Humidity :64 %RH
Test Mode :Mode 2 (Peak) Display Pattern:H Pattern

Frequency	Cable	Antenna	Reading Level	Emission Level	Limit
(MHz)	Loss	Factor	Vertical	Vertical	
	(dB)	(dB/m)	(dBuV/m)	(dBuV/m)	(uV/m)
1066.914	5.91	21.90	29.34	21.55	11.95
1185.460	6.27	21.99	30.17	23.03	14.17
1304.006	6.65	23.07	29.65	24.15	16.13

- Remarks: 1. All Readings below 1GHz are Quasi-Peak, above are average value.
2.“ * ”, means this data is worse case emission level.
3.Emission Level = Reading Level + Antenna Factor + Cable loss-
Amp Factor(35.59, 35.40, 35.21)
4.Deviations from the specifications: None.

Radiated Emission Data

Date of Test :04-30,1998 Thu Temperature :26.1 deg/C
EUT :NOTEBOOK Humidity :64 %RH
Test Mode :Mode 2 (Average) Display Pattern:H Pattern

Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Reading Level Horizontal (dBuV/m)	Emission Level Horizontal (dBuV/m)	(uV/m)	Limit (uV/m)
1030.927	5.80	21.12	24.32	15.59	6.02	500
1140.475	6.13	21.68	24.74	17.08	7.14	500
1260.022	6.51	22.64	25.23	19.09	9.01	500

- Remarks: 1. All Readings below 1GHz are Quasi-Peak, above are average value.
2.“ * ”, means this data is worse case emission level.
3.Emission Level = Reading Level + Antenna Factor + Cable loss-
Amp Factor(35.65, 35.48, 35.28)
4.Deviations from the specifications: None.

Radiated Emission Data

Date of Test :04-30,1998 Thu Temperature :26.1 deg/C
EUT :NOTEBOOK Humidity :64 %RH
Test Mode :Mode 2 (Average) Display Pattern:H Pattern

Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Reading Level Vertical (dBuV/m)	Emission Level Vertical (dBuV/m)	(uV/m)	Limit (uV/m)
1185.460	6.27	21.99	23.66	16.52	6.70	500
1304.006	6.65	23.07	23.15	17.65	7.63	500
1500.000	7.25	25.40	22.29	20.04	10.05	500

Remarks: 1. All Readings below 1GHz are Quasi-Peak, above are average value.
2.“ * ”, means this data is worse case emission level.
3.Emission Level = Reading Level + Antenna Factor + Cable loss-
Amp Factor(35.40, 35.21, 34.90)
4.Deviations from the specifications: None.

7. EMI Reduction Method During Compliance Testing

1. The gasket of eight pieces is addition between the backside of LCD panel and LCD holder. And the backside of LCD needs a sheet of Metal and conduct with LCD chassis.
2. The gasket of three pieces is addition between the aluminum sheet of L-type and the bottom of notebook PC.
3. The copper sheet of two pieces is stamping between the LCD panel and hinge.
4. The gasket of one piece is addition between the first cooling fan and the bottom of notebook PC. The first cooling fan at right side of notebook PC. The second cooling fan at up side of CPU.
5. The LCD cable requests a ferrite core and addition at near LVDS board.
6. For 12.1" CD panel, the LCD cable requests a ferrite core and addition at near LCD side.