



FCC RADIO TEST REPORT

Applicant : Everest Networks, Inc.

Address : 205 Ravendale Dr, Mountain View, CA 94043, USA

Equipment : AP300 3-Radio Omni-Directional Indoor Access Point

Model No. : AP23I300


Trade Name : **EVEREST**
N E T W O R K S

FCC ID : 2AGMRAP23I300

I HEREBY CERTIFY THAT :

The sample was received on Jul. 07, 2018 and the testing was carried out on Jul. 20, 2018 at CerpPASS Technology Corp. The test result refers exclusively to the test presented test model / sample. Without written approval of CerpPASS Technology Corp., the test report shall not be reproduced except in full.

Approved by:


Mark Liao / Assistant Manager

Tested by:


Spree Yei / Engineer

Laboratory Accreditation:

CerpPASS Technology Corporation Test Laboratory





Contents

1. Summary of Test Procedure and Test Results.....	4
1.1 Applicable Standards	4
2. Test Configuration of Equipment under Test.....	5
2.1 Feature of Equipment and Model Description.....	5
2.2 Test Mode and Test Software	6
2.3 Description of Test System.....	6
2.4 General Information of Test.....	7
2.5 Measurement Uncertainty	7
3. Test Equipment and Ancillaries Used for Tests	8
4. Test of AC Power Line Conducted Emission	9
4.1 Test Limit	9
4.2 Test Procedures	9
4.3 Typical Test Setup	10
4.4 Test Result and Data	11
4.5 Test Photographs	13
5. Test of Spurious Emission (Radiated)	14
5.1 Test Limit	14
5.2 Test Procedures	14
5.3 Typical Test Setup	15
5.4 Test Result and Data (9kHz ~ 30MHz).....	16
5.5 Test Result and Data (30MHz ~ 1GHz).....	16
5.6 Test Result and Data (1GHz ~ 40GHz).....	20
5.7 Restricted Bands of Operation	22
5.8 Test Photographs (30MHz ~ 1GHz)	23
5.9 Test Photographs (1GHz ~ 40GHz)	25



History of this test report

Report No.	Issue Date	Description
TEFU1811129	Nov. 30, 2018	Original



1. Summary of Test Procedure and Test Results

1.1 Applicable Standards

ANSI C63.4:2014

ANSI C63.10:2013

FCC Rule	Description of Test	Result
15.203	CO-LOCATION	Pass

This EUT has been also tested and compiled with the requirement of FCC Part 15, Subpart B, recorded in a separate test report.



2. Test Configuration of Equipment under Test

2.1 Feature of Equipment and Model Description

Equipment	AP300 3-Radio Omni-Directional Indoor Access Point
Model No.	AP23I300
Brand Name	EVEREST NETWORKS
Product Description	Please refer to User's Manual.
Connecting I/O Port(s)	Please refer to User's Manual.
AC ADAPTER	Adapter Brand: APD Model No.: WA-24Q12R I/P: AC 100-240V~, 50-60Hz, 0.7A MAX. ; O/P: DC 12V, 2.0A
PoE	48Vdc/0.67A
Memo	A1
Frequency Range	802.11b/g/n: 2400~2483.5 MHz 802.11a/n/ac: 5150~5250 MHz, 5725~5850 MHz
Modulation Type	OFDM, DSSS
Data Rate	2.4GHz: 802.11b: 1, 2, 5.5, 11Mbps 802.11g: 6, 9, 12, 18, 24, 36, 48, 54Mbps 802.11n: MCS0 – MCS15, HT20/40, VHT20/40 5GHz: 802.11a: 6, 9, 12, 18, 24, 36, 48, 54Mbps 802.11n: MCS0 – MCS15, HT20/40 802.11ac: MCS0 – MCS9, VHT20/40/80
Antenna Type	PIFA Antenna
Antenna Gain	2.4GHz: ANT A: 4.85 dBi ; ANT B: 4.4 dBi 5150MHz-5250MHz: ANT A: 4.18 dBi ; ANT B: 4.81 dBi 5725MHz-5850MHz: ANT A: 4.9 dBi ; ANT B: 4.18 dBi

Note: For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.



2.2 Test Mode and Test Software

- a. During testing, the interface cables and equipment positions were varied according to ANSI C63.4.
- b. The complete test system included remote workstation and EUT for RF test. The remote workstation included Notebook.
- c. An executive program, "QDART:39.1" under WIN 8 was executed to transmit and receive data via WLAN.
- d. The following test mode was performed for the test:

Conducted Emissions from the AC mains power ports	
Test Mode	Operating Description
1	802.11ac VHT20 CH06 + 802.11a CH48 + 802.11ac VHT20 CH165
Radiation Emissions (30MHz ~ 1GHz)	
Test Mode	Operating Description
1	802.11ac VHT20 CH06 + 802.11a CH48 + 802.11ac VHT20 CH165, Power from Adapter
2	802.11ac VHT20 CH06 + 802.11a CH48 + 802.11ac VHT20 CH165, Power from PoE
Radiation Emissions (1GHz ~ 40GHz)	
Test Mode	Operating Description
1	802.11ac VHT20 CH06 + 802.11a CH48 + 802.11ac VHT20 CH165, Power from Adapter

2.3 Description of Test System

Device	Manufacturer	Model No.	Description
Remote workstation			
Notebook	DELL	LatitudeE5450/5450	Power Cable, Unshielding, 1.8m



2.4 General Information of Test

Test Site	CerpPASS Technology Corporation Test Laboratory Address: No.10, Ln. 2, Lianfu St., Luzhu Dist., Taoyuan City 33848, Taiwan (R.O.C.) Tel:+886-3-3226-888 Fax:+886-3-3226-881 Address: No.68-1, Shihbachongsi, Shihding Township, New Taipei City 223, Taiwan, R.O.C. Tel: +886-2-2663-8582	
	FCC	TW1079, TW1061, TW1439
	IC	4934E-1, 4934E-2
	VCCI	T-2205 for Telecommunication Test C-4663 for Conducted emission test R-3428, R-4218 for Radiated emission test G-10812, G-10813 for radiated disturbance above 1GHz
Frequency Range Investigated:	Conducted: from 150kHz to 30 MHz Radiation: from 30 MHz to 40,000MHz	
Test Distance:	The test distance of radiated emission from antenna to EUT is 3 M.	

2.5 Measurement Uncertainty

Measurement Item	Uncertainty
Radiated Spurious Emission(9KHz~30MHz)	±5.007dB
Radiated Spurious Emission(30MHz~1GHz)	±5.157dB
Radiated Spurious Emission(1GHz~18GHz)	±6.383dB
Radiated Spurious Emission(18GHz~40GHz)	±6.648dB
Conducted Spurious Emission	±1.253dB
6dB Bandwidth	±6.89%
Power Spectral Density	±0.630dB
26 dB Occupied Bandwidth	±6.10%
Frequency Stability	±375KHz
Channel Frequencies Separation	±6.10%
20dB Bandwidth	±6.12%
Dwell Time	±1.34%
Peak Output Power(Conducted Power Meter)	±0.86dB
Temperature	±1.2℃
Humidity	±2.7%
Channel Move Time	±4.53%
Channel Closing Transmission Time	±6.61%
Threshold	±0.631dB
Non occupancy period	±1.17%



3. Test Equipment and Ancillaries Used for Tests

Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Valid Date
EMI Receiver	R&S	ESC13	100821	2017/09/08	2018/09/07
LISN	Schwarzbeck	NSLK 8127	8127-568	2018/02/26	2019/02/25
Pulse Limiter	R&S	ESH3-Z2	101934	2018/02/22	2019/02/21
Bilog Antenna	Schwarzbeck	VULB9168	275	2017/08/31	2018/08/30
Active Loop Antenna	EMCO	6507	40855	2018/05/22	2019/05/21
Horn Antenna	EMCO	3115	31601	2017/09/11	2018/09/10
Horn Antenna	EMCO	3116	31970	2018/03/23	2019/03/22
Preamplifier	EM	EM330	60658	2017/09/08	2018/09/07
Preamplifier	EMC INSTRUMENTS	EMC051845SE	980333	2017/09/20	2018/09/19
Preamplifier	EMC INSTRUMENTS	EMC184045	980065	2017/11/10	2018/11/09
MXG MW Analog Signal Generator	KEYSIGHT	N5183A	MY50142931	2018/04/10	2019/04/09
Spectrum Analyzer	R&S	FSP40	100219	2018/07/03	2019/07/02
BLUETOOTH TESTER	R&S	CBT	101133	2018/04/02	2019/04/01
Attenuator	KEYSIGHT	8491B	MY39250705	2017/09/04	2018/09/03
Rotary Attenuator	Agilent	8495B	MY42146680	2018/03/29	2019/03/28
Temp & Humi chamber	T-MACHINE	TMJ-9712	T-12-040111	2017/09/04	2018/09/03
Series Power Meter	Anritsu	ML2495A	1224005	2018/03/23	2019/03/22
Power Sensor	Anritsu	MA2411B	1207295	2018/03/23	2019/03/22
Software	Farad	Ez-EMC	ver.ct3a1	N/A	N/A
Software	AUDIX	E3	V8.2014-8-6	N/A	N/A
Software	Keysight	N7607B Signal Studio	V3.0.0.0	N/A	N/A
Software	Keysight	Inservice MonitorUtility	N/A	N/A	N/A



4. Test of AC Power Line Conducted Emission

4.1 Test Limit

Conducted Emissions were measured from 150 kHz to 30 MHz with a bandwidth of 9 KHz, according to the methods defined in ANSI C63.4-2014. The EUT was placed on a nonmetallic stand in a shielded room 0.8 meters above the ground plane. The interface cables and equipment positioning were varied within limits of reasonable applications to determine the position produced maximum conducted emissions.

Frequency (MHz)	Quasi Peak (dB μ V)	Average (dB μ V)
0.15 – 0.5	66-56*	56-46*
0.5 – 5.0	56	46
5.0 – 30.0	60	50


*Decreases with the logarithm of the frequency.

4.2 Test Procedures

- The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
- Connect EUT to the power mains through a line impedance stabilization network (LISN).
- All the support units are connecting to the other LISN.
- The LISN provides 50 ohm coupling impedance for the measuring instrument.
- The FCC states that a 50 ohm, 50 micro-Henry LISN should be used.
- Both sides of AC line were checked for maximum conducted interference.
- The frequency range from 150 kHz to 30 MHz was searched.
- Set the test-receiver system to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.




4.3 Typical Test Setup





4.4 Test Result and Data

Power	: AC 120V	Pol/Phase	: LINE
Test Mode	: Mode 1	Temperature	: 20 °C
Test Date	: Jul. 20, 2018	Humidity	: 40 %



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F
1	0.16	9.70	22.21	31.91	55.53	-23.62	Average	P
2	0.16	9.70	33.63	43.33	65.53	-22.20	QP	P
3	0.19	9.69	21.43	31.12	54.10	-22.98	Average	P
4	0.19	9.69	32.75	42.44	64.10	-21.66	QP	P
5	0.20	9.69	21.49	31.18	53.50	-22.32	Average	P
6	0.20	9.69	30.27	39.96	63.50	-23.54	QP	P
7	0.21	9.69	21.72	31.41	53.07	-21.66	Average	P
8	0.21	9.69	30.43	40.12	63.07	-22.95	QP	P
9	0.35	9.70	23.69	33.39	48.97	-15.58	Average	P
10	0.35	9.70	26.85	36.55	58.97	-22.42	QP	P
11	3.99	9.84	11.34	21.18	46.00	-24.82	Average	P
12	3.99	9.84	18.06	27.90	56.00	-28.10	QP	P


Note: Level = Reading + Factor

Margin = Level – Limit

Factor = (LISN, ISN, PLC or current probe) Factor + Cable Loss+ Attenuator



Power	: AC 120V	Pol/Phase	: NEUTRAL
Test Mode	: Mode 1	Temperature	: 20 °C
Test Date	: Jul. 20, 2018	Humidity	: 40 %



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F
1	0.15	9.70	23.96	33.66	55.94	-22.28	Average	P
2	0.15	9.70	34.42	44.12	65.94	-21.82	QP	P
3	0.16	9.70	23.77	33.47	55.63	-22.16	Average	P
4	0.16	9.70	33.36	43.06	65.63	-22.57	QP	P
5	0.19	9.70	22.29	31.99	54.08	-22.09	Average	P
6	0.19	9.70	32.55	42.25	64.08	-21.83	QP	P
7	0.22	9.70	22.81	32.51	52.98	-20.47	Average	P
8	0.22	9.70	31.53	41.23	62.98	-21.75	QP	P
9	0.35	9.70	26.77	36.47	48.96	-12.49	Average	P
10	0.35	9.70	29.75	39.45	58.96	-19.51	QP	P
11	0.38	9.70	22.63	32.33	48.22	-15.89	Average	P
12	0.38	9.70	28.11	37.81	58.22	-20.41	QP	P

Note: Level = Reading + Factor

Margin = Level – Limit

Factor = (LISN, ISN, PLC or current probe) Factor + Cable Loss+ Attenuator



5. Test of Spurious Emission (Radiated)

5.1 Test Limit

In any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. If the transmitter measurement is based on the maximum conducted output power, the attenuation required under this paragraph shall be 30dB instead of 20dB. In addition, radiated emissions which fall in section 15.205(a) the restricted bands must also comply with the radiated emission limit specified in section 15.209(a).

Frequency (MHz)	Field Strength (microvolt/meter)	Measurement Distance (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3


5.2 Test Procedures

- The EUT was placed on a rotatable table top 0.8 meter above ground.
- The EUT was set 3 meters from the interference receiving antenna which was mounted on the top of a variable height antenna tower.
- The table was rotated 360 degrees to determine the position of the highest radiation.
- The antenna is a broadband antenna and its height is varied between one meter and four meters above ground to find the maximum value of the field strength both horizontal polarization and vertical polarization of the antenna are set to make the measurement.
- For each suspected emission the EUT was arranged to its worst case and then tune the antenna tower (from 1 M to 4 M) and turn table (from 0 degree to 360 degrees) to find the maximum reading.
- Set the test-receiver system to Peak or CISPR quasi-peak Detect Function and specified bandwidth with Maximum Hold Mode.
- If the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method and reported.
- For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than average limit (that means the emission level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
- "Cone of radiation" has been considered to be 3dB bandwidth of the measurement antenna.




5.3 Typical Test Setup


Below 30MHz test setup



30MHz- 1GHz Test Setup



Above 1GHz Test Setup






5.4 Test Result and Data (9kHz ~ 30MHz)

The 9kHz - 30MHz spurious emission is under limit 20dB more.

5.5 Test Result and Data (30MHz ~ 1GHz)

Power	: AC 120V	Pol/Phase	: VERTICAL
Test Mode	: Mode 1	Temperature	: 23 °C
Test Date	: Jul. 07, 2018	Humidity	: 61 %



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	42.61	-10.93	47.60	36.67	40.00	-3.33	QP	100	171	P
2	83.35	-15.71	47.96	32.25	40.00	-7.75	QP	100	34	P
3	108.57	-14.45	52.13	37.68	43.50	-5.82	Peak	400	0	P
4	125.06	-12.88	51.66	38.78	43.50	-4.72	Peak	400	0	P
5	156.10	-10.93	51.40	40.47	43.50	-3.03	QP	100	354	P
6	213.33	-12.91	49.73	36.82	43.50	-6.68	Peak	400	0	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



Power	: AC 120V	Pol/Phase	: HORIZONTAL
Test Mode	: Mode 1	Temperature	: 23 °C
Test Date	: Jul. 07, 2018	Humidity	: 61 %



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	84.32	-15.85	48.95	33.10	40.00	-6.90	Peak	100	0	P
2	158.04	-10.88	50.10	39.22	43.50	-4.28	QP	152	133	P
3	182.29	-12.29	49.57	37.28	43.50	-6.22	Peak	100	0	P
4	216.24	-12.90	51.56	38.66	46.00	-7.34	Peak	100	0	P
5	250.19	-11.64	46.00	34.36	46.00	-11.64	Peak	100	0	P
6	557.68	-3.88	42.22	38.34	46.00	-7.66	Peak	100	0	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



Power	:	PoE	Pol/Phase	:	VERTICAL
Test Mode	:	Mode 2	Temperature	:	23 °C
Test Date	:	Jul. 07, 2018	Humidity	:	61 %



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	30.05	-11.65	44.58	32.93	40.00	-7.07	QP	100	326	P
2	36.88	-11.44	46.52	35.08	40.00	-4.92	QP	100	301	P
3	43.52	-10.87	46.44	35.57	40.00	-4.43	QP	100	294	P
4	51.47	-10.70	45.63	34.93	40.00	-5.07	QP	100	341	P
5	66.22	-12.26	48.91	36.65	40.00	-3.35	Peak	400	0	P
6	250.19	-11.64	42.63	30.99	46.00	-15.01	Peak	400	0	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



Power	: PoE	Pol/Phase	: HORIZONTAL
Test Mode	: Mode 2	Temperature	: 23 °C
Test Date	: Jul. 07, 2018	Humidity	: 61 %



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	51.44	-10.70	38.52	27.82	40.00	-12.18	Peak	100	0	P
2	194.33	-12.96	38.67	25.71	43.50	-17.79	Peak	100	0	P
3	250.50	-11.63	53.49	41.86	46.00	-4.14	Peak	100	0	P
4	308.64	-9.64	35.49	25.85	46.00	-20.15	Peak	100	0	P
5	631.55	-2.40	36.56	34.16	46.00	-11.84	Peak	100	0	P
6	707.42	-1.17	38.95	37.78	46.00	-8.22	Peak	100	0	P

Note: Level=Reading+Factor


Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



5.6 Test Result and Data (1GHz ~ 40GHz)

Power	: AC 120V	Pol/Phase	: VERTICAL
Test Mode	: Mode 1	Temperature	: 23 °C
Test Date	: Jul. 07, 2018	Humidity	: 61 %



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2802.00	-14.24	54.70	40.46	54.00	-13.54	Average	105	331	P
2	2802.00	-14.24	67.75	53.51	74.00	-20.49	Peak	105	331	P
3	3250.00	-12.65	55.60	42.95	54.00	-11.05	Average	100	340	P
4	3250.00	-12.65	61.60	48.95	74.00	-25.05	Peak	100	340	P
5	4874.00	-8.65	57.00	48.35	54.00	-5.65	Average	100	66	P
6	4874.00	-8.65	72.14	63.49	74.00	-10.51	Peak	100	66	P
7	10480.00	-0.78	45.21	44.43	54.00	-9.57	Average	100	116	P
8	10480.00	-0.78	58.29	57.51	74.00	-16.49	Peak	100	116	P
9	11650.00	0.91	45.01	45.92	54.00	-8.08	Average	100	155	P
10	11650.00	0.91	58.66	59.57	74.00	-14.43	Peak	100	155	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



Power	: AC 120V	Pol/Phase	: HORIZONTAL
Test Mode	: Mode 1	Temperature	: 23 °C
Test Date	: Jul. 07, 2018	Humidity	: 61 %



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2802.00	-14.24	57.90	43.66	54.00	-10.34	Average	103	292	P
2	2802.00	-14.24	71.77	57.53	74.00	-16.47	Peak	103	292	P
3	3250.00	-12.65	56.30	43.65	54.00	-10.35	Average	156	114	P
4	3250.00	-12.65	62.32	49.67	74.00	-24.33	Peak	156	114	P
5	4874.00	-8.65	55.65	47.00	54.00	-7.00	Average	112	335	P
6	4874.00	-8.65	71.53	62.88	74.00	-11.12	Peak	112	335	P
7	10480.00	-0.78	44.29	43.51	54.00	-10.49	Average	133	228	P
8	10480.00	-0.78	57.87	57.09	74.00	-16.91	Peak	133	228	P
9	11650.00	0.91	44.50	45.41	54.00	-8.59	Average	108	263	P
10	11650.00	0.91	58.20	59.11	74.00	-14.89	Peak	108	263	P

Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



5.7 Restricted Bands of Operation

Only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.09000 – 0.11000	16.42000 – 16.42300	399.9 – 410.0	4.500 – 5.250
0.49500 – 0.505**	16.69475 – 16.69525	608.0 – 614.0	5.350 – 5.460
2.17350 – 2.19050	16.80425 – 16.80475	960.0 – 1240.0	7.250 – 7.750
4.12500 – 4.12800	25.50000 – 25.67000	1300.0 – 1427.0	8.025 – 8.500
4.17725 – 4.17775	37.50000 – 38.25000	1435.0 – 1626.5	9.000 – 9.200
4.20725 – 4.20775	73.00000 – 74.60000	1645.5 – 1646.5	9.300 – 9.500
6.21500 – 6.21800	74.80000 – 75.20000	1660.0 – 1710.0	10.600 – 12.700
6.26775 – 6.26825	108.00000 – 121.94000	1718.8 – 1722.2	13.250 – 13.400
6.31175 – 6.31225	123.00000 – 138.00000	2200.0 – 2300.0	14.470 – 14.500
8.29100 – 8.29400	149.90000 – 150.05000	2310.0 – 2390.0	15.350 – 16.200
8.36200 – 8.36600	156.52475 – 156.52525	2483.5 – 2500.0	17.700 – 21.400
8.37625 – 8.38675	156.70000 – 156.90000	2655.0 – 2900.0	22.010 – 23.120
8.41425 – 8.41475	162.01250 – 167.17000	3260.0 – 3267.0	23.600 – 24.000
12.29000 – 12.29300	167.72000 – 173.20000	3332.0 – 3339.0	31.200 – 31.800
12.51975 – 12.52025	240.00000 – 285.00000	3345.8 – 3358.0	36.430 – 36.500
12.57675 – 12.57725	322.00000 – 335.40000	3600.0 – 4400.0	Above 38.6
13.36000 – 13.41000			

** : Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz