



FCC RF Exposure

EUT Description: Earring Bluetooth Earphones

Model No.: YX38, YX06, YX07, YX08, YX11, YX12, YX15, YX16, YX19, YX20, YX23, YX24, YX25, YX26, YX27, YX28, YX29, YX30, YX31, YX32, YX33, YX34, YX35, YX36, YX37, YX39, YX40, YX41, A8 pro ANC, A9 pro ANC, A10 pro, A11 pro, A12 pro, A13 pro, A14 pro, A15 pro

FCC ID: 2BF2R-YX38

Equipment type: Portable devices

According to KDB 447498 D01 General RF Exposure Guidance v06 and part 2.1093, Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numeric simulation, is not required when the corresponding SAR Test Exclusion Threshold condition(s), listed below, is (are) satisfied.

For 100 MHz to 6 GHz and test separation distances < 50 mm, the 1-g and 10-g SAR test exclusion thresholds are determined by the following:

$$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance mm})] \cdot [f(\text{GHz})] < 3.0 \text{ for 1-g SAR, and } < 7.5 \text{ for 10-g extremity SAR, where } f(\text{GHz}) \text{ is the RF channel transmit frequency in GHz}$$

Power and distance are rounded to the nearest mW and mm before calculation

The result is rounded to one decimal place for comparison

$$\text{EIRP} = \text{E}_{\text{Meas}} + 20 \log(d_{\text{meas}}) - 104.7$$

EIRP is the equivalent isotropically radiated power,

E_{Meas} in dBm is the field strength of the emission at the measurement distance, in dB u V/m

d_{meas} is the measurement distance, in m

Output power(dBm)	Max tune-up(mW)	Frequency(MHz)	Min. distance(mm)	Calc. thresholds	limit
-6.83	0.2075	2402	5	0.0643	3.0
-3.97	0.4009	2441	5	0.1253	3.0
-4.36	0.3664	2480	5	0.1154	3.0

Conclusion: No SAR is required