



Report No.: TW2108209E File reference No.: 2021-08-31

Applicant: Shenzhen Glory Star Technology Industrial Co., Ltd

Product: **ENC Gaming TWS**

Model No.: IAEBTG421B, GT96

Trademark: Glory Star

Test Standards: FCC Part 15.249

It is herewith confirmed and found to comply with the Test result:

requirements set up by ANSI C63.10 &FCC Part 15 Subpart C, for the evaluation

regulations 15.249 Paragraph

electromagnetic compatibility

Approved By

Jack Chung

Jack Chung

Manager

Dated: August 31, 2021

Results appearing herein relate only to the sample tested

The technical reports is issued errors and omissions exempt and is subject to withdrawal at

SHENZHEN TIMEWAY TESTING LABORATORIES

Zone C, 1st Floor, Block B, Jun Xiang Da Building, Zhongshan Park Road West, Tong Le Village, Nanshan District, Shenzhen, China

Tel (755) 83448688, Fax (755) 83442996, E-Mail:info@timeway-lab.com

Report No.: TW2108209E Page 2 of 45

Date: 2021-08-31



Special Statement:

The testing quality ability of our laboratory meet with "Quality Law of People's Republic of China" Clause 19.

The testing quality system of our laboratory meet with ISO/IEC-17025 requirements, which is approved by CNAS. This approval result is accepted by MRA of APLAC.

Our test facility is recognized, certified, or accredited by the following organizations:

CNAS-LAB Code: L2292

The EMC Laboratory has been assessed and in compliance with CNAS-CL01 accreditation criteria for testing Laboratories (identical to ISO/IEC 17025:2005 General Requirements) for the Competence of testing Laboratories.

FCC-Registration No.: 744189

The EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications commission. The acceptance letter from the FCC is maintained in our files. Registration No.: 744189.

Industry Canada (IC) — Registration No.:5205A

The EMC Laboratory has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 5205A.

A2LA (Certification Number:5013.01)

The EMC Laboratory has been accredited by the American Association for Laboratory Accreditation (A2LA). Certification Number:5013.01

Report No.: TW2108209E

Date: 2021-08-31



Test Report Conclusion

Conte	

1.0	General Details	4
1.1	Test Lab Details	4
1.2	Applicant Details	4
1.3	Description of EUT	4
1.4	Submitted Sample	4
1.5	Test Duration.	5
1.6	Test Uncertainty	5
1.7	Test By	5
2.0	List of Measurement Equipment	6
3.0	Technical Details	7
3.1	Summary of Test Results	7
3.2	Test Standards	7
4.0	EUT Modification.	7
5.0	Power Line Conducted Emission Test.	8
5.1	Schematics of the Test	8
5.2	Test Method and Test Procedure	8
5.3	Configuration of the EUT	8
5.4	EUT Operating Condition	9
5.5	Conducted Emission Limit.	9
5.6	Test Result	9
6.0	Radiated Emission test	12
6.1	Test Method and Test Procedure	12
6.2	Configuration of the EUT	13
6.3	EUT Operation Condition	13
6.4	Radiated Emission Limit	14
6.5	Test Result	15
7.0	Band Edge	23
7.1	Test Method and Test Procedure	23
7.2	Radiated Test Setup	23
7.3	Configuration of the EUT	23
7.4	EUT Operating Condition	23
7.5	Band Edge Limit.	23
7.6	Band Edge Test Result.	24
8.0	Antenna Requirement.	28
9.0	20dB bandwidth measurement	29
10.0	FCC ID Label	35
11.0	Photo of Test Setup and EUT View.	36

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

Date: 2021-08-31



1.0 General Details

1.1 Test Lab Details

Name: SHENZHEN TIMEWAY TESTING LABORATORIES.

Address: Zone C, 1st Floor, Block B, Jun Xiang Da Building, Zhongshan Park Road West, Tong Le

Village, Nanshan District, Shenzhen, China

Telephone: (755) 83448688 Fax: (755) 83442996

Site on File with the Federal Communications Commission – United Sates

Registration Number: 744189 For 3m Anechoic Chamber

1.2 Applicant Details

Applicant: Shenzhen Glory Star Technology Industrial Co., Ltd

Address: Room 2102, Block 1 st, Yi Luan Building, Xixiang Road 230, BaoAn District, Shenzhen,

China

Telephone: --Fax: --

1.3 Description of EUT

Product: ENC Gaming TWS

Manufacturer: Shenzhen Glory Star Technology Industrial Co., Ltd

Address: Room 2102, Block 1 st, Yi Luan Building, Xixiang Road 230, BaoAn District,

Shenzhen, China

Trademark: Glory Star Model Number: IAEBTG421B

Additional Model Name GT96

Family Model Just different design.

Statement:

Test Model: IAEBTG421B

Hardware Version: V1.0 Software Version: V2.2.1

Rating: DC5V input or Built-in DC3.7V, 40mAh Li-ion battery for earphones and DC5V

input or Built-in DC3.7V, 350mAh Li-ion battery for charger base.

Modulation Type: GFSK, Pi/4D-QPSK Operation Frequency: 2402-2480MHz

Channel Separate: 1MHz Channel Number: 79

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

Report No.: TW2108209E Page 5 of 45

Date: 2021-08-31



Antenna Designation Ceramic antenna with gain 2.0dBi Max (Declared by the applicant)

1.4 Submitted Sample: 1 pc

1.5 Test Duration

2021-08-18 to 2021-08-31

1.6 Test Uncertainty

Conducted Emissions Uncertainty =3.6dB

Radiated Emissions below 1GHz Uncertainty =4.7dB

Radiated Emissions above 1GHz Uncertainty =6.0dB

Conducted Power Uncertainty = 6.0dB

Occupied Channel Bandwidth Uncertainty =5%

Conducted Emissions Uncertainty =3.6dB

Note: The measurement uncertainty is for coverage factor of k=2 and a level of confidence of 95%.

1.7 Test Engineer

Terry Tang

The sample tested by

Print Name: Terry Tang

Page 6 of 45

Report No.: TW2108209E

Date: 2021-08-31



2.0 Test Equipment					
Instrument Type	Manufacturer	Model	Serial No.	Date of Cal.	Due Date
ESPI Test Receiver	R&S	ESPI 3	100379	2021-06-18	2022-06-17
LISN	R&S	EZH3-Z5	100294	2021-06-18	2022-06-17
LISN	R&S	EZH3-Z5	100253	2021-06-18	2022-06-17
Impuls-Begrenzer	R&S	ESH3-Z2	100281	2021-06-18	2022-06-17
Loop Antenna	EMCO	6507	00078608	2021-06-18	2024-06-17
Spectrum	R&S	FSIQ26	100292	2021-06-18	2022-06-17
Horn Antenna	A-INFO	LB-180400-KF	J211060660	2021-07-02	2022-07-01
Horn Antenna	R&S	BBHA 9120D	9120D-631	2021-07-02	2022-07-01
Power meter	Anritsu	ML2487A	6K00003613	2021-06-18	2022-06-17
Power sensor	Anritsu	MA2491A	32263	2021-06-18	2022-06-17
Bilog Antenna	Schwarebeck	VULB9163	9163/340	2021-07-02	2022-07-01
9*6*6 Anechoic			N/A	2021-07-02	2022-07-01
EMI Test Receiver	RS	ESVB	826156/011	2021-06-18	2022-06-17
EMI Test Receiver	RS	ESH3	860904/006	2021-06-18	2022-06-17
Spectrum	HP/Agilent	ESA-L1500A	US37451154	2021-06-18	2022-06-17
Spectrum	HP/Agilent	E4407B	MY50441392	2021-06-18	2022-06-17
Spectrum	RS	FSP	1164.4391.38	2021-01-16	2022-01-15
RF Cable	Zhengdi	ZT26-NJ-NJ-8M/FA		2021-06-18	2022-06-17
RF Cable	Zhengdi	7m		2021-06-18	2022-06-17
RF Switch	EM	EMSW18	060391	2021-06-18	2022-06-17
Pre-Amplifier	Schwarebeck	BBV9743	#218	2021-06-18	2022-06-17
Pre-Amplifier	HP/Agilent	8449B	3008A00160	2021-06-18	2022-06-17
LISN	SCHAFFNER	NNB42	00012	2021-01-06	2022-01-05

2.2 Automation Test Software

For Conducted Emission Test

Name	Version
EZ-EMC	Ver.EMC-CON 3A1.1

For Radiated Emissions

Name	Version
EMI Test Software BL410-EV18.91	V18.905
EMI Test Software BL410-EV18.806 High Frequency	V18.06

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

Page 7 of 45

Report No.: TW2108209E

Date: 2021-08-31



3.0 Technical Details

3.1 Summary of test results

The E	UT has	been	tested	accord	ling to	o the	following	specifications:

Standard	Test Type	Result	Notes
FCC Part 15, Paragraph 15.207	Conducted Emission Test	PASS	Complies
FCC Part 15 Subpart C Paragraph 15.249(a) & 15.249(b) Limit	Field Strength of Fundamental	PASS	Complies
FCC Part 15, Paragraph 15.209	Radiated Emission Test	PASS	Complies
FCC Part 15 Subpart C Paragraph 15.249(d) Limit	Band Edge Test	PASS	Complies

3.2 Test Standards

FCC Part 15 Subpart C, Paragraph 15.249, ANSI C63.4:2014 and ANSI C63.10:2013

4.0 EUT Modification

No modification by SHENZHEN TIMEWAY TESTING LABORATORIES


Report No.: TW2108209E

Date: 2021-08-31



5. Power Line Conducted Emission Test

5.1 Schematics of the test




EUT: Equipment Under Test

5.2 Test Method and test Procedure

The EUT was tested according to ANSI C63.10-2013. The Frequency spectrum from 0.15MHz to 30MHz was investigated. The LISN used was 50ohm/50uH as specified by section 5.1 of ANSI C63.10 –2013.

Test Voltage: 120V~, 60Hz Block diagram of Test setup



5.3 Configuration of the EUT

The EUT was configured according to ANSI C63.10-2013. All interface ports were connected to the appropriate peripherals. All peripherals and cables are listed below.

79 channels are provided to the EUT

A. EUT

Device	Manufacturer	Model	FCC ID
ENC Gaming TWS	Shenzhen Glory Star Technology	IAEBTG421B,	2AS7V-IAEBTG421B
	Industrial Co., Ltd	GT96	ZAS/V-IAEDIU4ZID

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

Report No.: TW2108209E Page 9 of 45

Date: 2021-08-31



B. Internal Device

Device	Manufacturer	Model	FCC ID/DOC
N/A			

C. Peripherals

Device	Manufacturer	Model	Rating
Power Supply	KEYU	KA23-0502000DEU	Input: 100-240V~, 50/60Hz, 0.35A;
			Output: DC5V, 2A

5.4 EUT Operating Condition

Operating condition is according to ANSI C63.10-2013

- A Setup the EUT and simulators as shown on follow
- B Enable AF signal and confirm EUT active to normal condition

5.5 Power line conducted Emission Limit according to Paragraph 15.207

Frequency	Limits (d	lB μV)
(MHz)	Quasi-peak Level	Average Level
$0.15 \sim 0.50$	66.0~56.0*	56.0~46.0*
$0.50 \sim 5.00$	56.0	46.0
5.00 ~ 30.00	60.0	50.0

Notes: 1. *Decreasing linearly with logarithm of frequency.

2. The tighter limit shall apply at the transition frequencies

5.6 Test Results:

Pass

Report No.: TW2108209E Page 10 of 45

Date: 2021-08-31



A: Conducted Emission on Live Terminal (150kHz to 30MHz)


EUT Operating Environment

Temperature: 25°C Humidity: 65%RH Atmospheric Pressure: 101 kPa

EUT set Condition: Charging and Communication by BT

Results: Pass

Please refer to following diagram for individual



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F
1	0.5205	26.97	9.77	36.74	56.00	-19.26	QP	Р
2	0.5205	18.57	9.77	28.34	46.00	-17.66	AVG	Р
3	1.4487	22.19	9.79	31.98	56.00	-24.02	QP	Р
4	1.4487	13.03	9.79	22.82	46.00	-23.18	AVG	Р
5	2.3691	21.21	9.82	31.03	56.00	-24.97	QP	Р
6	2.3691	11.11	9.82	20.93	46.00	-25.07	AVG	Р
7	12.1689	20.52	10.26	30.78	60.00	-29.22	QP	Р
8	12.1689	10.03	10.26	20.29	50.00	-29.71	AVG	Р

Date: 2021-08-31



B: Conducted Emission on Neutral Terminal (150kHz to 30MHz)


EUT Operating Environment

Temperature: 25°C Humidity: 65%RH Atmospheric Pressure: 101 kPa

EUT set Condition: Charging and Communication by BT

Results: Pass

Please refer to following diagram for individual



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F
1	0.2241	19.63	9.75	29.38	62.67	-33.29	QP	Р
2	0.2241	3.87	9.75	13.62	52.67	-39.05	AVG	Р
3	0.5633	22.00	9.77	31.77	56.00	-24.23	QP	Р
4	0.5633	11.24	9.77	21.01	46.00	-24.99	AVG	Р
5	2.4003	17.78	9.82	27.60	56.00	-28.40	QP	Р
6	2.4003	6.26	9.82	16.08	46.00	-29.92	AVG	Р
7	11.4591	14.02	10.22	24.24	60.00	-35.76	QP	Р
8	11.4591	4.44	10.22	14.66	50.00	-35.34	AVG	Р

Report No.: TW2108209E Page 12 of 45

Date: 2021-08-31




6 Radiated Emission Test

- 6.1 Test Method and test Procedure:
- (1) The EUT was tested according to ANSI C63.10-2013. The radiated test was performed at Timeway EMC Laboratory. This site is on file with the FCC laboratory division, Registration No. 744189
- (2) The EUT, peripherals were put on the turntable which table size is 1m x 1.5 m, table high 0.8 m. All set up is according to ANSI C63.10-2013.
- (3) The frequency spectrum from 30 MHz to 25 GHz was investigated. All readings from 30 MHz to 1 GHz are quasi-peak values with a resolution bandwidth of 120 kHz. All readings are above 1 GHz, peak values with a resolution bandwidth of 1 MHz (Note: for Fundamental frequency radiated emission measurement, RBW=3MHz, VBW=10MHz). Measurements were made at 3 meters.
- (4) The antenna high is varied from 1 m to 4 m high to find the maximum emission for each frequency.
- (5) The antenna polarization: Vertical polarization and Horizontal polarization.

Block diagram of Test setup

For radiated emissions from 9kHz to 30MHz




Page 13 of 45

Report No.: TW2108209E


Date: 2021-08-31



For radiated emissions from 30MHz to1GHz



For radiated emissions above 1GHz



- 6.2 Configuration of The EUT
 Same as section 5.3 of this report
- 6.3 EUT Operating Condition
 Same as section 5.4 of this report.

Report No.: TW2108209E Page 14 of 45

Date: 2021-08-31



6.4 Radiated Emission Limit

All emission from a digital device, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strength specified below:

A FCC Part 15 Subpart C Paragraph 15.249(a) Limit

Fundamental Frequency	Field Stre	ength of Fundame	ental (3m)	Field Strength of Harmonics (3m)			
(MHz)	mV/m	dBuV/m		uV/m	dBuV/m		
2400-2483.5	50	94 (Average)	114 (Peak)	500	54 (Average)	74 (Peak)	

Note:

- 1. RF Field Strength (dBuV) = 20 log RF Voltage (uV)
- 2.Distance refers to the distance in meters between the measuring instrument antenna and the closed point of any part of the device or system.
- 3. The emission limit in this paragraph is based on measurement instrumentation employing an average detector.

B. Frequencies in restricted band are complied to limit on Paragraph 15.209.

Frequency Range (MHz)	Distance (m)	Field strength (dB μ V/m)
30-88	3	40.0
88-216	3	43.5
216-960	3	46.0
Above 960	3	54.0

Note:

- 1. RF Voltage $(dBuV) = 20 \log RF \text{ Voltage } (uV)$
- 2. In the Above Table, the tighter limit applies at the band edges.
- 3. Distance refers to the distance in meters between the measuring instrument antenna and the EUT
- 4. This is a handhold device. The radiated emissions should be tested under 3-axes position (Lying, Side, and Stand), After pre-test. It was found that the worse radiated emission was get at the lying position.
- 5. All scanning using PK detector. And the final emission level was get using QP detector for frequency range from 30-1000MHz.As to 1G-25G, the final emission level got using PK. For fundamental measurement, PK detector used.
- 6. Battery full charged during tests.
- 7. The two modulation modes of GFSK and Pi/4D-QPSK were tested. And only the worst case was recorded in the test report. GFSK was the worst case.

Report No.: TW2108209E Page 15 of 45

Date: 2021-08-31




6.5 Test result

A Fundamental & Harmonics Radiated Emission Data

Please refer to the following test plots for details: Low Channel-2402MHz

Horizontal




No.	Frequency	Results	Factor	Limit	Over Limit	Detector	Table	Height	ANT	Verdict
	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dB)		(o)	(cm)		
1	2402.149	86.65	-3.57	114.0	-27.35	Peak	199.00	100	Horizontal	Pass
2	4802.799	56.25	3.12	74.0	-17.75	Peak	189.00	100	Horizontal	Pass
2**	4802.799	50.24	3.12	54.0	-3.76	AV	189.00	100	Horizontal	Pass

Report No.: TW2108209E Page 16 of 45

Date: 2021-08-31



Vertical



No.	Frequency	Results	Factor	Limit	Over Limit	Detector	Table (o)	Height	ANT	Verdict
	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dB)			(cm)		
1	2402.149	75.75	-3.57	114.0	-38.25	Peak	202.00	100	Vertical	Pass
2	4802.799	49.60	3.12	74.0	-24.40	Peak	146.00	100	Vertical	Pass


Report No.: TW2108209E Page 17 of 45

Date: 2021-08-31



Please refer to the following test plots for details: Middle Channel-2441MHz

Horizontal




No.	Frequency	Results	Factor	Limit	Over Limit	Detector	Table	Height	ANT	Verdict
	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dB)		(o)	(cm)		
1	2440.390	88.88	-3.57	114.0	-25.12	Peak	210.00	100	Horizontal	Pass
2	4883.529	51.43	3.20	74.0	-22.57	Peak	186.00	100	Horizontal	Pass

Report No.: TW2108209E Page 18 of 45

Date: 2021-08-31



Vertical



No.	Frequency	Results	Factor	Limit	Over Limit	Detector	Table	Height	ANT	Verdict
	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dB)		(0)	(cm)		
1	2440.390	74.95	-3.57	114.0	-39.05	Peak	351.00	100	Vertical	Pass


Report No.: TW2108209E Page 19 of 45

Date: 2021-08-31



Please refer to the following test plots for details: High Channel-2480MHz

Horizontal




No.	Frequency	Results	Factor	Limit	Over Limit	Detector	Table	Height	ANT	Verdict
	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dB)		(o)	(cm)		
1	2479.630	86.65	-3.57	114.0	-27.35	Peak	213.00	100	Horizontal	Pass
2	4960.010	49.26	3.36	74.0	-24.74	Peak	60.00	100	Horizontal	Pass

Report No.: TW2108209E Page 20 of 45

Date: 2021-08-31



Vertical



No.	Frequency	Results	Factor	Limit	Over Limit	Detector	Table	Height	ANT	Verdict
	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dB)		(o)	(cm)		
1	2479.630	76.27	-3.57	114.0	-37.73	Peak	191.00	100	Vertical	Pass

Note: (2) Emission Level = Reading Level + Antenna Factor + Cable Loss-Amplifier

- (3) Margin=Emission-Limits
- (4) According to section 15.35(b), the peak limit is 20dB higher than the average limit
- (5) For test purpose, keep EUT continuous transmitting
- (5) For emission above 18GHz and Below 30MHz, It is only the floor noise. No necessary to take down.
- (6) the measured PK value less than the AV limit.

Report No.: TW2108209E Page 21 of 45

Date: 2021-08-31




B. General Radiated Emission Data Radiated Emission In Horizontal (30MHz----1000MHz)

EUT set Condition: Keep Tx transmitting

Results: Pass

Please refer to following diagram for individual



No.	Frequency	Results	Factor	Limit	Over Limit	Detector	Table	Height	ANT	Verdict
	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dB)		(o)	(cm)		
1	53.032	15.53	-11.50	40.0	-24.47	Peak	19.00	100	Horizontal	Pass
2	104.671	12.80	-13.25	43.5	-30.70	Peak	0.00	100	Horizontal	Pass
3	705.921	23.37	-4.11	46.0	-22.63	Peak	31.00	100	Horizontal	Pass

Report No.: TW2108209E Page 22 of 45

Date: 2021-08-31




Radiated Emission In Vertical (30MHz----1000MHz)

EUT set Condition: Keep Tx transmitting

Results: Pass

Please refer to following diagram for individual



No.	Frequency	Results	Factor	Limit	Over Limit	Detector	Table	Height	ANT	Verdict
	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dB)		(o)	(cm)		
1	54.244	15.90	-11.60	40.0	-24.10	Peak	352.00	100	Vertical	Pass
2	101.520	13.41	-13.44	43.5	-30.09	Peak	313.00	100	Vertical	Pass
3	653.312	22.63	-4.48	46.0	-23.37	Peak	345.00	100	Vertical	Pass

Page 23 of 45

Report No.: TW2108209E

Date: 2021-08-31




7. Band Edge

7.1 Test Method and test Procedure:

- (1) The EUT was tested according to ANSI C63.10–2013. The radiated test was performed at Timeway EMC Laboratory. This site is on file with the FCC laboratory division, Registration No. 744189
- (2) Set Spectrum as RBW=1MHz, VBW=3MHz and Peak detector used for PK value. RBW=1MHz, VBW=10Hz and Peak detector used for AV value.
- (3) The antenna high is varied from 1 m to 4 m high to find the maximum emission for each frequency.
- (4) The antenna polarization: Vertical polarization and Horizontal polarization.

7. 2 Radiated Test Setup



For the actual test configuration, please refer to the related items – Photos of Testing

7.3 Configuration of The EUT

Same as section 5.3 of this report

7.4 EUT Operating Condition

Same as section 5.4 of this report.

7.5 Band Edge Limit

Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in Section 15.209, whichever is the lesser attenuation.

The report refers only to the sample tested and does not apply to the bulk.


Report No.: TW2108209E Page 24 of 45

Date: 2021-08-31



7.6 Test Result

Product:	ENC Gaming TWS	Polarity	Horizontal
Mode	Keeping Transmitting	Test Voltage	DC3.7V
Temperature	24 deg. C,	Humidity	56% RH
Test Result:	Pass		



No.	Frequency	Results	Factor	Limit	Over Limit	Detector	Table	Height	ANT	Verdict
	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dB)		(o)	(cm)		
2	2400.042	64.60	-3.57	74.0	-9.40	Peak	204.00	100	Horizontal	Pass
2**	2400.042	50.07	-3.57	54.0	-3.93	AV	204.00	100	Horizontal	Pass
3	2390.070	39.73	-3.53	74.0	-34.27	Peak	200.00	100	Horizontal	Pass

Report No.: TW2108209E Page 25 of 45

Date: 2021-08-31



	Product:	E	ENC Gami	ng TWS		Detector		Vertical		
	Mode	K	eeping Tra	nsmitting	Te	est Voltage		DC	3.7V	
Te	Temperature 24 deg. C, Humidity 56% RH									
Te	est Result:		Pass	s						
FCC Part 1	15C Class B 1GHz-18GHz	-2								
c	90-									
-	50							М	1	
8	30-									
7	70-								$\overline{}$	
								/	\	
6	50-							/	1	
_	50-					11.		1/12		
_	50-	rmodor Jakoth wat like okish	والمراجعة والمادية والمجاجعة	ather adversaring the earth of collection	. Nijibiyan da ka ji da da da	M3		y12 •	Muni	ark and phonesis
level (dBuV/m)	50-	n maraban lakka kalik ja mekalan menjan	i ish wiqinda ashlindhi i blirah qari	atan, adampan kahilikan kahilikan kahilikan ka	. Nijibbiq majo ka katoji alikipika	M3		¹²	N. A.	al angliness
level (dBuV/m)	10 - Maria de Maria	ye moodaa hadaddhaan dhaa dhaa dhaa dhaa dhaa	istinoista juliakti ykii kisio	adas adas quasis didas distribudo al la de	s sifithia _s eendus ha kate ji dhasibd			/12 *		ak anak bangi
level (dBuV/m)	50- 40- <u></u>	y ay shariffi ay shira a	يغريوا أرباط والمعارض فالمجتم الدارا	والمراب المساورة والمراجع ويساف والمراجع والمراع	. nejebbi _n metebbi _n metebbi	M3		y/12 •	W. W.	ak seak kanada
level (dBuV/m)	10	n mereben lektribilik mensistren mereben	visilopeinista assilvat kirjekis oleh peri	ana day anighterada kada da	. Kilithia _{gere} da, ba la _{la b} a dhèigh d	13		y/12	N. Market	art de le transfe
level (dBuV/m)	10	y sirvi da je kladistik je vene klavy venedani	risherida da alimbik yelenda ba d	now, by Hole White Statement & Ver-all	equency (MHz)			y/12 *	N. de de de la constantina della constantina del	2410
level (dBuV/m)	10 - 10 - 10 - 10 - 10 - 10 - 10 - 10 -	Results	Factor	now, by Hole White Statement & Ver-all		Detector	Table	Height	ANT	
level (dBuV/m)	10 - 10 - 10 - 10 - 10 - 10 - 10 - 10 -	1 and 1 as 12 lbd as all them, to a strong 1 years at		Fre	equency (MHz)		Table (o)	Height (cm)		2410
(m//mg) 44 22 22 22 22 22 22 22 22 22 22 22 22	50	Results	Factor	Fre	equency (MHz) Over Limit			_		2410
(w/\ngp) and 3	60 - 10 - 10 - 10 - 10 - 10 - 10 - 10 -	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	over Limit	Detector	(o)	(cm)	ANT	2410 Verdict

Report No.: TW2108209E Page 26 of 45

Date: 2021-08-31



Product: ENC Gaming TWS		ENC Gam	ing TWS		Polarity		He	orizontal	
Mode	K	Leeping Tra	ansmitting	r	Test Voltag	je	DC3.7V		
Temperature	Temperature 24 deg. C,		g. C,		Humidity		56% RH		
Test Result: Pass									
C Part 15C Class B 1GHz-180	Hz -2								
90-		- Com							
80-		$\longrightarrow \!$							
70-									
60-	1,44	/	M2						
50-	A Land Line Complete Market		· 1/2						
يقلن والمطلب سيلا الأفادوان بالبريديان	ALINE AND			A CHARLES AND A CHARLES	Marine Marine Marine Marine	والمالية وال		والمراجع المراجع المرا	-
40 - 17 17 17 17 17 17 17 17 17 17 17 17 17									
30-									
30-									
30-									
20-									
20-			2483.5 Fi	requency (MHz)					2500
30-	Results	Factor		requency (MHz) Over	Detector	Table	Height	ANT	25000

No.	Frequency	Results	Factor	Limit	Over	Detector	Table	Height	ANT	Verdict
	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	Limit (dB)		(o)	(cm)		
2	2483.369	54.67	-3.57	74.0	-19.33	Peak	207.00	100	Horizontal	Pass
2**	2483.369	50.14	-3.57	54.0	-3.86	AV	207.00	100	Horizontal	Pass

Report No.: TW2108209E Page 27 of 45

Date: 2021-08-31



]	Product: ENC Gaming TWS			ng TWS	Ι	Detector		Ve	rtical	
	Mode	K	eeping Tra	nsmitting	Tes	st Voltage		DC	23.7V	
Te	mperature		24 deg	g. C,	Н	Iumidity		569	% RH	
Te	est Result:		Pas	s						
1.0E+		-2								
	10-									
7	70-									
			/							
	60-		1							
5		المتعاديد والمتعاديد والمتعاد والمتعاديد وال		The state of the s	e husekestenselle stiefelgeslikse	والمرابعة والمرابعة			Judet de de de de la constitución de la constitució	raktas daktu
(ш/Angn) валаг	0-	ng ang dipangang ang dipang			thus heating all the distributions of the second distribut	والمساول والمساورة	indicated with the first terms.	المستعالم والمراجع المستعال والمستعال والمستعال والمستعادة والمستعاد والمستعادة والمستعادة والمستعادة والمستعادة والمستعادة والمستعا	i sudista salaminin di dina di sana di	rolles della
(W/Anng) 44	10 - 10 - 10 - 10 - 10 - 10 - 10 - 10 -	THE STREET STREET, STR			eleskerindik delelekte	المراجعة	والمراجعة	المسالسانية المسالسية	unkturishing.	rolus della
(W/nngp) Javan 3 2 2 1 0.	0-	ng ang makananan manjik padaklik b			s kashesingalik dalfalqalikes	والمرافع المرافع المرا	ud jetinakediphis	hugh abugh	zaki kalendari	
5 (iii/anga) 1 (iii/anga) 1 (iii/anga) 2 (iii/anga) 2 (iii/anga) 1 (ii		ng n		2483.5	equency (MHz)	at national and any displaying the	and white was head white the	ku ali sahi ka ku a k	under den de la	2500
(W/nngp) Java 3 2 2 1 0.	0-	Results (dBuV/m)	Factor (dB)	2483.5		Detector	Table (o)	Height (cm)	ANT	

Note: 1. The PK emission level less than the AV limit. No necessary to record the AV emission level.

- 2. This is a handhold device. The radiated emissions should be tested under 3-axes position (Lying, Side, and Stand), After pre-test. It was found that the worse radiated emission was get at the lying position.
- 3. The two modulation modes of GFSK and Pi/4D-QPSK were tested. And only the worst case was recorded in the test report. GFSK was the worst case.

Report No.: TW2108209E Page 28 of 45

Date: 2021-08-31



8.0 Antenna Requirement

Applicable Standard

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

This product has a Ceramic antenna with gain 2.0 dBi Max. It fulfills the requirement of this section.

Test Result: Pass

Report No.: TW2108209E Page 29 of 45

Date: 2021-08-31



9.0 20dB Bandwid	th Measurem	ent							
GFSK Modulation	n								
Product:		ENC Gami	ing TWS		Te	st Mode:		Keep tra	ansmitting
Mode	k	Keeping Tra	ınsmittin	g	Tes	t Voltage		DC	C3.7V
Temperature		24 deg	g. C,		Н	umidity		569	% RH
Test Result:		Pas	s		Г	etector]	PK
20dB Bandwidth		930.00	kHz						
Ref 10 de	3m	*Att 20) dB	*RBW 3(*VBW 1(SWT 5	00 kHz	2	.402012	.89 dBm 000 GHz	a.
10						ndB [T BW 930	1] 20 .000000	.00 dB 000 kHz	A
1 PK MAXH			\\ _\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\	~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~		Temp 2	.401538	в] .54 dВm	
30		T1/V			T2				
-40	N					4			
50							~~~		3DB
-60	V					, io	\~	wann	
-70									
80									
-90									

Date: 26.AUG.2021 15:01:09

Center 2.402 GHz

300 kHz/

Span 3 MHz


Page 30 of 45

Report No.: TW2108209E

Date: 2021-08-31



GFSK Modulation								
Product:	ENC Gaming TWS	Test Mode:	Keep transmitting					
Mode	Keeping Transmitting	Test Voltage	DC3.7V					
Temperature	24 deg. C,	Humidity	56% RH					
Test Result:	Pass	Detector	PK					
20dB Bandwidth	804.00kHz							



Date: 26.AUG.2021 15:02:49


Page 31 of 45

Report No.: TW2108209E

Date: 2021-08-31



GFSK Modulation								
Product:	ENC Gaming TWS	Test Mode:	Keep transmitting					
Mode	Keeping Transmitting	Test Voltage	DC3.7V					
Temperature	24 deg. C,	Humidity	56% RH					
Test Result:	Pass	Detector	PK					
20dB Bandwidth	804.00kHz							



Date: 26.AUG.2021 15:03:23


Page 32 of 45

Report No.: TW2108209E

Date: 2021-08-31



Pi/4D-QPSK Modulation								
Product:	ENC Gaming TWS	Test Mode:	Keep transmitting					
Mode	Keeping Transmitting	Test Voltage	DC3.7V					
Temperature	24 deg. C,	Humidity	56% RH					
Test Result:	Pass	Detector	PK					
20dB Bandwidth	1.230MHz							



Date: 26.AUG.2021 15:06:35


Page 33 of 45

Report No.: TW2108209E

Date: 2021-08-31



Pi/4D-QPSK Modulation								
Product:	ENC Gaming TWS	Test Mode:	Keep transmitting					
Mode	Keeping Transmitting	Test Voltage	DC3.7V					
Temperature	24 deg. C,	Humidity	56% RH					
Test Result:	Pass	Detector	PK					
20dB Bandwidth	1.236MHz							



Date: 26.AUG.2021 15:05:33


Page 34 of 45

Report No.: TW2108209E

Date: 2021-08-31



Pi/4D-QPSK Modulation								
Product:	ENC Gaming TWS	Test Mode:	Keep transmitting					
Mode	Keeping Transmitting	Test Voltage	DC3.7V					
Temperature	24 deg. C,	Humidity	56% RH					
Test Result:	Pass	Detector	PK					
20dB Bandwidth	1.236MHz							



Date: 26.AUG.2021 15:04:10

Report No.: TW2108209E Page 35 of 45

Date: 2021-08-31




10.0 FCC ID Label

FCC ID: 2AS7V-IAEBTG421B

The label must not be a stick-on paper label. The label on these products must be permanently affixed to the product and readily visible at the time of purchase and must last the expected lifetime of the equipment not be readily detachable.

Mark Location:



Page 36 of 45


Report No.: TW2108209E

Date: 2021-08-31



11.0 Photo of testing

11.1 Conducted test View--




Page 37 of 45

Report No.: TW2108209E

Date: 2021-08-31



Radiated emission test view



The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it. or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

Report No.: TW2108209E

Date: 2021-08-31



11.2 Photographs – EUT

Outside View - charger base



The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

Report No.: TW2108209E

Date: 2021-08-31



Photographs-EUT

Outside View - charger base



The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

Page 40 of 45

Report No.: TW2108209E

Date: 2021-08-31



Outside View - Left earphone



The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.


Page 41 of 45

Report No.: TW2108209E

Date: 2021-08-31



Outside View - Left earphone



The report refers only to the sample tested and does not apply to the bulk.


This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

Report No.: TW2108209E

Date: 2021-08-31



Outside View - Right earphone



The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

Page 43 of 45

Report No.: TW2108209E

Date: 2021-08-31



Outside View - Right earphone



The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.


Page 44 of 45


Report No.: TW2108209E

Date: 2021-08-31



Inside View





The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES.

will not, without the consent of the client enter into any

discussion of correspondence with any third party concerning the contents of the report.


In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.

Report No.: TW2108209E Page 45 of 45

Date: 2021-08-31



Inside View



-- End of the report--