## FCC ID: 2AOMQ-SPOON

## Portable device

According to §15.247(e)(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to KDB447498 D01 General RF Exposure Guidance V06

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)] \* [  $\sqrt{f(GHz)}$ ]  $\leq 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR, where

f(GHz) is the RF channel transmit frequency in GHz;

Power and distance are rounded to the nearest mW and mm before calculation;

The result is rounded to one decimal place for comparison;

The test exclusions are applicable only when the minimum test separation distance is  $\leq$  50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion. We use 5mm as separation distance to calculated.

## Bluetooth DSS:

Transmit Frequency (GHz)	Mode	Measured Power (dBm)	Tune-up power (dBm)	Max tune-up	Result calculation	1g SAR
2.402		2.91	2±1	3	0.6185	3
2.441	GFSK	2.85	2±1	3	0.6235	3
2.48		2.02	2±1	3	0.6284	3
2.402		1.63	1±1	2	0.4913	3
2.441	π/4-DQPSK	1.79	1±1	2	0.4952	3
2.48		1.15	1±1	2	0.4992	3
2.402		2.05	2±1	3	0.6185	3
2.441	8DPSK	2.11	2±1	3	0.6235	3
2.48		1.45	2±1	3	0.6284	3

## Bluetooth DTS:

Transmit Frequency (GHz)	Mode	Measured Power (dBm)	Tune-up power (dBm)	Max tune-up	Result	1g SAR
				power(dBm)	calculation	
2.402	GFSK	3.08	3±1	4	0.7786	3
2.44		3.08	3±1	4	0.7847	3
2.48		2.3	3±1	4	0.7911	3

Conclusion:

For the max result : 0.7911≤ 3.0 for 1g SAR, No SAR is required.

Jason chen Signature: **Date:** 2018-2-1

NAME AND TITLE (Please print or type): Jason Chen /Manager
COMPANY (Please print or type): Shenzhen NTEK Testing Technology Co., Ltd./ 1/F, Building E,
Fenda Science Park, Sanwei Community, Xixiang Street Bao'an District, Shenzhen P.R. China.