



ELECTRICAL SPECIFICATIONS

Frequency Range: 2.4-2.48/5.15-5.85/5.925-7.125 GHz
Gain (Client Serving): 8/10/10dBi
Gain (Scan): 7.8/9.5/10dBi
Polarization: 7 Vertical / 7 Horizontal (Detailed on Page 5)
Horizontal Beamwidth: 65°/40°/35°
Vertical Beamwidth: 65°/40°/35°
VSWR: <1.5:1 Max: 2.0
Isolation: >30dB
Impedance: 50 Ω



MECHANICAL SPECIFICATIONS

Dimensions: 15.35"x 15.35"x 2.25" (390x390x57mm)
Weight: 3 lb (1.3kg)

Installation: Flush Mount to Wall or Articulating
Wall/Pole Mount (included)

Radome Material: ABS
Connector: 4MPC(5GHz),
6MPC-BLK (6GHz and Scan),
6MPC-WHT (2.4/5/6GHz)
Number of Leads: 14
Cable Length: 36" (910mm)
Cable Type: ATS-100



ENVIRONMENTAL SPECIFICATIONS

Installation Environment: Indoor or Outdoor
IP Rating: IP66

WARRANTY



2 Year Limited



2.4/5/6 GHZ 8/10/10 DBI 14 ELEMENT INDOOR PATCH ANTENNA WITH MPC ATS-OP-2456-81010-14MPC-36 ATS-03951



VERTICAL HORIZONTAL 6GHZ RADIO (6MPC-BLK)

Frequency (MHz)	5900.0	6050.0	6150.0	6250.0	6350.0	6450.0	6550.0	6650.0	6750.0	6850.0	6950.0	7050.0	7125.0
Gain (dBi)	9.80	9.97	10.08	9.97	10.02	9.98	10.23	10.57	10.12	9.88	10.31	10.45	10.09
Efficiency	48.64	51.88	50.76	47.92	46.17	44.63	48.47	50.19	48.42	47.43	46.88	47.89	47.41



5GHZ RADIO (4MPC)

Frequency (MHz)	4900.0	5000.0	5100.0	5150.0	5250.0	5350.0	5450.0	5550.0	5650.0	5750.0	5850.0
Gain (dBi)	9.13	9.53	9.63	9.32	9.64	9.72	9.93	9.70	9.61	9.62	9.70
Efficiency (%)	49.97	52.01	50.99	47.37	49.52	48.09	51.47	48.37	46.89	45.39	44.37



The facts and figures herein are carefully compiled to the best of our knowledge and are intended for general informational purposes only. Responsibility for the use and application of AccelTex Solutions materials rests with the end user. All AccelTex Solutions products are sold pursuant to the AccelTex Solutions Terms and Conditions of Sale. © 2021 AccelTex Solutions. All Rights Reserved. AccelTex, AccelTex Solutions, the AccelTex Solutions Logo and other marks are trademarks or registered trademarks of AccelTex Solutions. Other products or service names may be the property of third parties.

1.888.406.8906
SALES@ACCELTEX.COM



VERTICAL



HORIZONTAL

TRIBAND RADIO (6MPC-WHT)

Frequency (MHz)	2400.0	2420.0	2440.0	2460.0	2484.0
Gain (dBi)	7.96	8.01	8.02	8.16	8.46
Efficiency (%)	61.54	60.05	60.84	60.63	62.93



Frequency (MHz)	5150.0	5250.0	5350.0	5450.0	5550.0	5650.0	5750.0	5850.0
Gain (dBi)	9.06	9.44	9.33	9.30	10.01	9.88	9.97	9.54
Efficiency (%)	50.89	50.86	46.64	45.01	49.30	47.21	45.68	41.51

Frequency (MHz)	5925.0	6050.0	6150.0	6250.0	6350.0	6450.0	6550.0	6650.0	6750.0	6850.0	6950.0	7050.0	7125.0
Gain (dBi)	9.47	9.96	10.00	9.29	9.13	9.14	9.36	9.81	9.92	9.63	9.83	9.32	9.12
Efficiency	49.11	48.87	49.81	47.03	45.82	45.10	48.13	49.23	47.59	46.72	48.13	47.67	47.12






2.4/5/6 GHZ 8/10/10 DBI 14 ELEMENT INDOOR
PATCH ANTENNA WITH MPC
ATS-OP-2456-81010-14MPC-36
ATS-03951




Polarization order

6MPC-BLK



6MPC-WHT



4MPC

