

RADIO TEST REPORT

Type of assessment:

MPE Calculation report

Applicant:

Echodyne Corporation

Product:

Ku Band Radar

Models:

700025-300-100, 700025-300-200,
700025-300-300, 700025-300-400,
700025-350-100, 700025-350-200,
700025-350-300, 700025-350-400

FCC ID:

2ANLB-MESA00055

Specifications:

- ◆ FCC 47 CFR Part 1 Subpart I, §§1.1307, 1.1310
- ◆ FCC 47 CFR Part 2 Subpart J, §2.1091
- ◆ FCC KDB 447498 D01 General RF Exposure Guidance v06

Date of issue: March 3, 2025

Andrey Adelberg, Senior EMC/RF Specialist

Prepared by



Signature

Nemko Canada Inc., a testing laboratory, is accredited by the Standards Council of Canada.
The tests included in this report are within the scope of this accreditation.
The SCC Accreditation Symbol is an official symbol of the Standards Council of Canada, used under licence.

SCC File Number: 15064 (Ottawa/Almonte); 151100 (Montreal); 151097 (Cambridge)

Lab locations

Company name	Nemko Canada Inc.			
Facilities	<i>Ottawa site:</i>	<i>Montréal site:</i>	<i>Cambridge site:</i>	<i>Almonte site:</i>
	303 River Road	292 Labrosse Avenue	1-130 Saltsman Drive	1500 Peter Robinson Road
	Ottawa, Ontario	Pointe-Claire, Québec	Cambridge, Ontario	West Carleton, Ontario
	Canada K1V 1H2	Canada H9R 5L8	Canada N3E 0B2	Canada K0A 1L0
	Tel: +1 613 737 9680	Tel: +1 514 694 2684	Tel: +1 519 650 4811	Tel: +1 613 256-9117
	Fax: +1 613 737 9691	Fax: +1 514 694 3528		
Test site identifier	Organization	Ottawa/Almonte	Montreal	Cambridge
	FCC:	CA2040	CA2041	CA0101
	ISED:	2040A-4	2040G-5	24676
Website	www.nemko.com			

Limits of responsibility

Note that the results contained in this report relate only to the items tested and were obtained in the period between the date of initial receipt of samples and the date of issue of the report.

This test report has been completed in accordance with the requirements of ISO/IEC 17025. All results contained in this report are within Nemko Canada's ISO/IEC 17025 accreditation.

Copyright notification

Nemko Canada Inc. authorizes the applicant to reproduce this report provided it is reproduced in its entirety and for use by the company's employees only. Any use which a third party makes of this report, or any reliance on or decisions to be made based on it, are the responsibility of such third parties. Nemko Canada Inc. accepts no responsibility for damages, if any, suffered by any third party as a result of decisions made or actions based on this report.
© Nemko Canada Inc.

Table of Contents

Table of Contents	3
Section 1 Evaluation summary	4
1.1 MPE calculation for standalone transmission	4

Section 1 Evaluation summary

1.1 MPE calculation for standalone transmission

1.1.1 References, definitions and limits

FCC §2.1091(d)

- (2) (2) For operations within the frequency range of 300 kHz and 6 GHz (inclusive), the limits for maximum permissible exposure (MPE), derived from whole-body SAR limits and listed in Table 1 in paragraph (e)(1) of this section, may be used instead of whole-body SAR limits as set forth in paragraphs (a) through (c) of this section to evaluate the environmental impact of human exposure to RF radiation as specified in §1.1307(b) of this part, except for portable devices as defined in §2.1093 of this chapter as these evaluations shall be performed according to the SAR provisions in §2.1093.

Table 1.1-1: Table 1 to §1.1310(e)(1)—Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(i) Limits for Occupational/Controlled Exposure				
0.3–3.0	614	1.63	*(100)	≤6
3.0–30	1842 / f	4.89 / f	*(900 / f ²)	<6
30–300	61.4	0.163	1.0	<6
300–1500			f / 300	<6
1500–100000			5	<6
(ii) Limits for General Population/Uncontrolled Exposure				
0.3–1.34	614	1.63	*(100)	<30
1.34–30	824 / f	2.19 / f	*(180 / f ²)	<30
30–300	27.5	0.073	0.2	<30
300–1500			f / 1500	<30
1500–100000			1.0	<30

Notes: f = frequency in MHz. * = Plane-wave equivalent power density.

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = \frac{PG}{4\pi R^2}$$

where: S = power density (mW/cm² or W/m²)
P = power input to the antenna (mW or W)
G = power gain of the antenna in the direction of interest relative to an isotropic radiator
R = distance to the center of radiation of the antenna (cm or m)

1.1.2 EUT technical information

Prediction frequency	16400 MHz
Antenna gain	27 dBi
Number of antennas	1
Maximum fundamental EIRP	75.51 dBm (170.74 dBμV/m)
Prediction distance declared	200 cm (occupational), 400 cm (uncontrolled)
Protocol based duty cycle	15 %

1.1.3 MPE calculation

Fundamental transmit (prediction) frequency:	16400 MHz
Maximum measured field strength at 3 m:	170.74 dBμV/m
Transmit duty cycle:	15 %
Maximum calculated average field strength:	25.61 dBμV/m
Single Antenna gain (typical):	27.00 dBi
Number of antennae:	1
Total system gain:	27.00 dBi
FCC limit:	
MPE limit for <u>uncontrolled</u> exposure at prediction frequency:	1.000000 mW/cm ²
	10.000000 W/m ²
MPE limit for <u>controlled</u> exposure at prediction frequency:	5.000000 mW/cm ²
	50.000000 W/m ²
Minimum calculated prediction distance for uncontr. compliance:	20 cm
Typical (declared) distance for uncontrolled environment:	400 cm
Minimum calculated prediction distance for contr. compliance:	20 cm
Typical (declared) distance for controlled environment:	200 cm
Average power density at prediction frequency (uncontrolled):	0.000000000000054 mW/cm ²
	0.0000000000000543 W/m ²
Average power density at prediction frequency (controlled):	0.000000000000217 mW/cm ²
	0.0000000000002172 W/m ²
Margin of Compliance for <u>uncontrolled</u> environment:	132.65 dB
with Maximum allowable antenna gain:	132.65 dBi
Margin of Compliance for <u>controlled</u> environment:	133.62 dB
with Maximum allowable antenna gain:	164.25 dBi

1.1.4 Verdict

The calculation is below the limit; therefore, the product is passing the RF Exposure requirements for the declared distance.

End of the test report