

RF EXPOSURE EVALUATION

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency(RF) Radiation as specified in §1.1307(b)

FCC ID: 2AXLB-EA2020E

EUT Specification

EUT	Intelligent Multi-rotor Plant Protection UAV
Frequency band (Operating)	☐ WLAN: 2.412GHz ~ 2.462GHz ☐ WLAN: 5.18GHz ~ 5.24GHz ☐ WLAN: 5.745GHz ~ 5.825GHz ☒ Others: 2.410GHz~2.474GHz 2.4G ☒ Others: 902.4MHz~912.2MHz
Device category	☐ Portable (<20cm separation) ☒ Mobile (>20cm separation) ☐ Others _____
Exposure classification	☐ Occupational/Controlled exposure (S = 5mW/cm ²) ☒ General Population/Uncontrolled exposure (S=1mW/cm ²)
Antenna diversity	☐ Single antenna ☒ Multiple antennas ☐ Tx diversity ☐ Rx diversity ☐ Tx/Rx diversity
Max. output power	2.4G:14.748dBm (0.0298W) 902.4MHz~912.2MHz: 22.209dBm (0.1663W)
Antenna gain (Max)	2.4G: 5 dBi 902.4MHz~912.2MHz: 3 dBi
Evaluation applied	☒ MPE Evaluation ☐ SAR Evaluation

Limits for Maximum Permissible Exposure(MPE)

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density(mW/cm ²)	Average Time
(A) Limits for Occupational/Control Exposures				
300-1500	--	--	F/300	6
1500-100000	--	--	5	6
(B) Limits for General Population/Uncontrol Exposures				
300-1500	--	--	F/1500	6
1500-100000	--	--	1	30

Friis transmission formula: $P_d = (P_{out} * G) / (4 * \pi * R^2)$

Where

P_d = Power density in mW/cm²

P_{out} = output power to antenna in Mw

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

P_d the limit of MPE, 1mW/cm². If we know the maximum gain of the antenna and total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

Measurement Result

2.4GHz :

Channel Frequency	Measured Power	Tune up tolerance	Max. Tune up Power	Antenna Gain	Power density at 20cm	Power density Limits (mW/cm ²)
(MHz)	(dBm)	(dBm)	(dBm)	(dBi)	(mW/ cm ²)	
2410	14.748	14.748±1	15.748	5	0.0236	1
2444	10.851	10.851±1	11.851	5	0.0096	1
2474	11.740	11.740±1	12.74	5	0.0118	1

Note: 2.4G cannot support simultaneous transmission.

902.4MHz~912.2MHz :

Channel Frequency	Measured Power	Tune up tolerance	Max. Tune up Power	Antenna Gain	Power density at 20cm	Power density Limits (mW/cm ²)
(MHz)	(dBm)	(dBm)	(dBm)	(dBi)	(mW/ cm ²)	
902.4	21.406	21.406±1	22.406	3	0.0691	1
907.2	21.508	21.508±1	22.508	3	0.0707	1
912.2	22.209	22.209±1	23.209	3	0.0831	1

Note: 902.4MHz~912.2MHz cannot support simultaneous transmission.