

## RF Exposure Evaluation Statement

**Product Name:** bluetooth headset

**Model No.: H1**

**FCC ID: 2AFTU-DD013**

## 1.1 RF Exposure Compliance Requirement

### 1.1.1 Standard Requirement

According to KDB447498D01 General RF Exposure Guidance v06

## Standalone SAR test exclusion considerations

Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Exclusion Threshold condition, listed below, is satisfied.

### 1.1.2 Limits

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot$$
$$[\sqrt{f}(\text{GHz})] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR, where}$$

$f(\text{GHz})$  is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation<sup>17</sup>

The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is  $\leq 50$  mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is  $< 5$  mm, a distance of 5 mm is applied to determine SAR test exclusion

### 1.1.3 EUT RF Exposure

| Operational Mode: EDR (8-DPSK worst case)               |                                                  |                               |                       |      |                  |                     |
|---------------------------------------------------------|--------------------------------------------------|-------------------------------|-----------------------|------|------------------|---------------------|
| Channel                                                 | Maximum Peak Conducted Output Power<br><br>(dBm) | Tune up tolerance<br><br>(dB) | Maximum tune-up Power |      | Calculated value | Exclusion threshold |
|                                                         |                                                  |                               | (dBm)                 | (mW) |                  |                     |
| 2402MHZ                                                 | 5.46                                             | ± 1                           | 6.46                  | 4.43 | 1.37             | 3.0                 |
| 2441MHZ                                                 | 6.67                                             | ± 1                           | 7.67                  | 5.85 | 1.82             |                     |
| 2480MHZ                                                 | 7.00                                             | ± 1                           | 8.00                  | 6.31 | 1.98             |                     |
|                                                         |                                                  |                               |                       |      |                  |                     |
| Operational Mode: BLE_1Mbps                             |                                                  |                               |                       |      |                  | 3.0                 |
| 2402MHZ                                                 | 2.18                                             | ± 1                           | 3.18                  | 2.08 | 0.64             |                     |
| 2442MHZ                                                 | 3.16                                             | ± 1                           | 4.16                  | 2.61 | 0.81             |                     |
| 2480MHZ                                                 | 3.51                                             | ± 1                           | 4.51                  | 2.82 | 0.89             |                     |
| Conclusion: the calculated value ≤3.0, SAR is exempted. |                                                  |                               |                       |      |                  |                     |