

<b>Report Reference ID:</b>	400107-12TRFWL
-----------------------------	----------------

<b>Test specification:</b>	Title 47 – Telecommunication Chapter I – Federal Communications Commission Subchapter B – Common carrier services Part 27 – Miscellaneous wireless communications services
----------------------------	---



<b>Applicant:</b>	TEKO Telecom Srl. Via Meucci, 24/a I-40024 Castel S. Pietro Terme (BO) (Italy)
-------------------	--

<b>Apparatus:</b>	Very Very High Power Module Amplifier
-------------------	---------------------------------------

<b>Model:</b>	MWHPA2001PCS-D2
---------------	-----------------

<b>FCC ID:</b>	XM2-WHPA19HN
----------------	--------------

<b>Testing laboratory:</b>	<b>Nemko Italy Spa</b> Via del Carroccio, 4 20853 Biassono (MB) – Italy Telephone: +39 039 2201201 Facsimile: +39 039 2201221
----------------------------	---

	Name and title	Date
<b>Tested by:</b> (name, function and signature)	 P. Barbieri (project handler)	2020-07-17
<b>Reviewed by:</b> (name, function and signature)	 R. Giampaglia (verifier)	2020-07-17

*This test report may not be partially reproduced, except with the prior written permission of Nemko Spa  
The test report merely corresponds to the tested sample.  
The phase of sampling / collection of equipment under test is carried out by the customer.*

**Nemko Spa, 20853 Biassono (MB) - Italy. All rights reserved.**

This publication may be reproduced in whole for non-commercial purposes as long as Nemko Spa is acknowledged as copyright owner and source of the material. Nemko Spa takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context. Nemko Spa accepts no responsibility for damages, if any, suffered by any third party as a result of decisions made or actions based on this report. This test report may not be partially reproduced, except with the prior written permission of Nemko Spa. The test report merely corresponds to the test sample. The phase of sampling / collection of equipment under test is carried out by the customer.

This Test Report, when bearing the Nemko name and logo is only valid when issued by a Nemko laboratory, or by a laboratory having special agreement with Nemko.

**Table of contents**

<b>Section 1: Report summary</b>	<b>3</b>
1.1 Test specification	3
1.2 Statement of compliance	3
1.3 Exclusions	3
1.4 Registration number	3
1.5 Test report revision history	3
1.6 Limits of responsibility	3
<b>Section 2: Summary of test results</b>	<b>4</b>
2.1 FCC Part 27, test results	4
<b>Section 3: Equipment under test (EUT) and application details</b>	<b>5</b>
3.1 Applicant details	5
3.2 Modular equipment	5
3.3 Product details	5
3.4 Application purpose	5
3.5 Composite/related equipment	6
3.6 Sample information	6
3.7 EUT technical specifications	6
3.8 Accessories and support equipment	7
3.9 Operation of the EUT during testing	8
3.10 EUT setup diagram	8
<b>Section 4: Engineering considerations</b>	<b>9</b>
4.1 Modifications incorporated in the EUT	9
4.2 Deviations from laboratory tests procedures	9
4.3 Technical judgment	9
<b>Section 5: Test conditions</b>	<b>10</b>
5.1 Deviations from laboratory tests procedures	10
5.2 Test conditions, power source and ambient temperatures	10
5.3 Measurement uncertainty	10
5.4 Test equipment	12
<b>Appendix A: Test results</b>	<b>13</b>
Clause 935210 D05v01 (3.2) AGC threshold	13
Clause 935210 D05v01 (3.3) Out of band rejection	14
Clause 27.53(h)(3) Occupied bandwidth	15
Clause 27.50(d) Peak output power at RF antenna connector	17
Clause 27.53(h) Spurious emissions at RF antenna connector	22
Clause 27.53(h) Radiated Spurious emissions	30
<b>Appendix B: Block diagrams of test set-ups</b>	<b>38</b>
<b>Appendix C: EUT Photos</b>	<b>39</b>

## Section 1: Report summary

### 1.1 Test specification

<b>Specifications</b>	<b>Part 27 – Miscellaneous wireless communications services</b>
-----------------------	---

### 1.2 Statement of compliance

<b>Compliance</b>	<p>In the configuration tested the EUT was found compliant                  Yes <input checked="" type="checkbox"/> No <input type="checkbox"/></p> <p>Test method: ANSI C63.26-2015, 662911 D01 Multiple Transmitter Output v02r01, 662911 D02 MIMO with Cross-Polarized Antennas v01</p>
-------------------	--

### 1.3 Exclusions

<b>Exclusions</b>	None
-------------------	------

### 1.4 Registration number

<b>Test site FCC ID number</b>	682159
--------------------------------	--------

### 1.5 Test report revision history

Revision #	Details of changes made to test report
TRF	Original report issued

### 1.6 Limits of responsibility

Note that the results contained in this report relate only to the items tested and were obtained in the period between the date of initial receipt of samples and the date of issue of the report.

This test report has been completed in accordance with the requirements of ISO/IEC 17025. Nemko Spa authorizes the applicant to reproduce this report provided it is reproduced in its entirety and for use by the company's employees only.

Any use which a third party makes of this report, or any reliance on or decisions to be made based on it, are the responsibility of such third parties.

Nemko Spa accepts no responsibility for damages, if any, suffered by any third party as a result of decisions made or actions based on this report.

## Section 2: Summary of test results

2.1 FCC Part 27, test results			
Part	Methods	Test description	Verdict
	§ 935210 D05v01r04 (3.2)	AGC threshold	Pass
	§ 935210 D05v01r04 (3.3)	Out of band rejection	Pass
§27.53(h)(3)	§ 935210 D05v01r04 (3.4)	Occupied bandwidth	Pass
§27.50(d)	§ 935210 D05v01r04 (3.5)	Peak output power at RF antenna connector	Pass
§27.53(h)	§ 935210 D05v01r04 (3.6)	Spurious emissions at RF antenna connector	Pass
§27.53(h)	§ 935210 D05v01r04 (3.8)	Radiated spurious emissions	Pass
§27.54	§ 935210 D05v01r04 (3.7)	Frequency stability	N/A a)
<p>Notes:</p> <p style="padding-left: 40px;">a) NOT APPLICABLE: Modulation/frequency conversion circuitry not in use. No frequency change in EUT (input and output have same frequency)</p>			

## Section 3: Equipment under test (EUT) and application details

### 3.1 Applicant details

<b>Applicant complete business name</b>	Name:	Teko Telecom Srl
	Federal Registration Number (FRN):	0018963462
	Grantee code	XM2
<b>Mailing address</b>	Address:	Via Meucci, 24/a
	City:	Castel S. Pietro Terme
	Province/State:	Bologna
	Post code:	40024
	Country:	Italy

### 3.2 Modular equipment

<b>a) Single modular approval</b>	Single modular approval Yes <input type="checkbox"/> No <input checked="" type="checkbox"/>
<b>b) Limited single modular approval</b>	Limited single modular approval Yes <input type="checkbox"/> No <input checked="" type="checkbox"/>

### 3.3 Product details

<b>FCC ID</b>	Grantee code:	XM2
	Product code:	-WHPA19HN
<b>Equipment class</b>	B2I	
<b>Description of product as it is marketed</b>	Booster	
	Model name/number:	MWHPA2001PCS-D2
	Serial number:	1017521002

### 3.4 Application purpose

<b>Type of application</b>	<input checked="" type="checkbox"/> Original certification <input type="checkbox"/> Change in identification of presently authorized equipment Original FCC ID: _____ Grant date: _____ <input type="checkbox"/> Class II permissive change or modification of presently authorized equipment
----------------------------	--

Section 3: Equipment under test

3.5 Composite/related equipment

<b>a) Composite equipment</b>	The EUT is a composite device subject to an additional equipment authorization Yes <input type="checkbox"/> No <input checked="" type="checkbox"/>
<b>b) Related equipment</b>	The EUT is part of a system that operates with, or is marketed with, another device that requires an equipment authorization Yes <input type="checkbox"/> No <input checked="" type="checkbox"/>
<b>c) Related FCC ID</b>	If either of the above is "yes": <input type="checkbox"/> has been granted under the FCC ID(s) listed below: <input type="checkbox"/> is in the process of being filled under the FCC ID(s) listed below: <input type="checkbox"/> is pending with the FCC ID(s) listed below: <input type="checkbox"/> has a mix of pending and granted statuses under the FCC ID(s) listed below: i FCC ID: ii FCC ID:

3.6 Sample information

<b>Receipt date:</b>	2020-05-18
<b>Nemko sample ID number:</b>	400107

3.7 EUT technical specifications

<b>Operating band:</b>	Down Link: 1995–2020 MHz
<b>Operating frequency:</b>	Wideband
<b>Modulation type:</b>	GSM, EDGE, CDMA, WCDMA, LTE (QAM and QPSK)
<b>Occupied bandwidth:</b>	GSM and EDGE: 200 kHz; CDMA: 1,25 MHz, WCDMA: 5 MHz LTE: 1.4 MHz, 3 MHz, 5 MHz, 10 MHz, 15 MHz, 20 MHz
<b>Channel spacing:</b>	standard
<b>Emission designator:</b>	GSM and EDGE: GXW; CDMA, WCDMA: F9W, LTE: D7W
<b>RF Output</b>	Down Link: 46dBm (40W) Up Link: N.A. (The EUT does not transmit over the air in the up-link direction)
<b>Gain</b>	Down Link: 51dB Up Link: N.A. (The EUT does not transmit over the air in the up-link direction)
<b>Antenna type:</b>	External Antenna is not provided, equipment that has an external 50 Ω RF connector
<b>Power source:</b>	28-30 Vdc

Section 3: Equipment under test

**3.8 Accessories and support equipment**  
 The following information identifies accessories used to exercise the EUT during testing:

Item # 1	
Type of equipment:	Power Supply
Brand name:	EA-PS
Model name or number:	8080-60
Serial number:	1421120002
Nemko sample number:	-----
Connection port:	To supply amplifier
Cable length and type:	-----
Item # 2	
Type of equipment:	Power supply
Brand name:	GWINSTEK
Model name or number:	GPS4303
Serial number:	GER846883
Nemko sample number:	-----
Connection port:	To supply cooling fan of heatsink
Cable length and type:	-----
Item # 3	
Type of equipment:	Management Module
Brand name:	Teko Telecom
Model name or number:	MSPVRUV0001
Serial number:	100739447
Nemko sample number:	-----
Connection port:	LAN Port, To manage amplifier module
Cable length and type:	-----
Item # 4	
Type of equipment:	
Brand name:	
Model name or number:	
Serial number:	
Nemko sample number:	
Connection port:	
Cable length and type:	

### 3.9 Operation of the EUT during testing

<b>Details:</b>	In down-link direction, normal working at max gain with max RF power output.
-----------------	--

### 3.10 EUT setup diagram

In this system, Very Very High Power Amplifier is the EUT and it is intended for mounting in Remote Unit and Digital Service Front-End (optical system with Master Unit that includes only management module and optical module, to convert RF signal in optical signal in down link direction and viceversa optical signal in RF signal in up link direction). As described in “Operational description”, master unit is connected directly to base station, so the system doesn’t use another equipment (under another FCC ID) to exercise the EUT. Signal generator is linked directly to the RF input connector.

**Test setup for output power, occupied bandwidth, spurious emissions:**



**Procedure**

Connect the signal modulated generator to the input of the EUT, so that the EUT works at the max gain. Raise the input level to the EUT until reach the maximum output power. Connect the spectrum analyzer to the RF output connector of the EUT.



## Section 4: Engineering considerations

### 4.1 Modifications incorporated in the EUT

<b>Modifications</b>	Modifications performed to the EUT during this assessment None <input checked="" type="checkbox"/> Yes <input type="checkbox"/> , performed by Client <input type="checkbox"/> or Nemko <input type="checkbox"/> Details:
----------------------	---

### 4.2 Deviations from laboratory tests procedures

<b>Deviations</b>	Deviations from laboratory test procedures None <input checked="" type="checkbox"/> Yes <input type="checkbox"/> - details are listed below:
-------------------	---

### 4.3 Technical judgment

<b>Judgment</b>	None
-----------------	------

## Section 5: Test conditions

### 5.1 Deviations from laboratory tests procedures

No deviations were made from laboratory test procedures.

### 5.2 Test conditions, power source and ambient temperatures

Normal temperature, humidity and air pressure test conditions	<p>Temperature: 15–30 °C                  Relative humidity: 20–75 %                  Air pressure: 86–106 kPa</p> <p>When it is impracticable to carry out tests under these conditions, a note to this effect stating the ambient temperature and relative humidity during the tests shall be recorded and stated.</p>
Power supply range:	<p>The normal test voltage for equipment to be connected to the mains shall be the nominal mains voltage. For the purpose of the present document, the nominal voltage shall be the declared voltage, or any of the declared voltages <math>\pm 5\%</math>, for which the equipment was designed.</p>

### 5.3 Measurement uncertainty

The measurement uncertainty was calculated for each test and quantity listed in this test report, according to CISPR 16-4-2 and other specific test standard and is documented in Nemko Spa working manual WML1002.

The assessment of conformity for each test performed on the equipment is performed not taking into account the measurement uncertainty. The two following possible verdicts are stated in the report:

P (Pass) - The measured values of the equipment respect the specification limit at the points tested. The specific risk of false accept is up to 50% when the measured result is close to the limit.

F (Fail) - One or more measured values of the equipment do not respect the specification limit at the points tested. The specific risk of false reject is up to 50% when the measured result is close to the limit.

Hereafter Nemko's measurement uncertainties are reported:

Section 5: Test conditions, continued

EUT	Type	Test	Range	Measurement Uncertainty	Notes	
Transmitter	Conducted	Frequency error	0.001 MHz ÷ 40 GHz	0.08 ppm	(1)	
		Carrier power RF Output Power	0.009 MHz ÷ 30 MHz	1.1 dB	(1)	
			30 MHz ÷ 18 GHz	1.5 dB	(1)	
			18 MHz ÷ 40 GHz	3.0 dB	(1)	
			40 MHz ÷ 140 GHz	5.0 dB	(1)	
		Adjacent channel power	1 MHz ÷ 18 GHz	1.4 dB	(1)	
		Conducted spurious emissions	0.009 MHz ÷ 18 GHz	3.0 dB	(1)	
			18 GHz ÷ 40 GHz	4.2 dB	(1)	
			40 GHz ÷ 220 GHz	6.0 dB	(1)	
		Intermodulation attenuation	1 MHz ÷ 18 GHz	2.2 dB	(1)	
		Attack time – frequency behaviour	1 MHz ÷ 18 GHz	2.0 ms	(1)	
		Attack time – power behaviour	1 MHz ÷ 18 GHz	2.5 ms	(1)	
		Release time – frequency behaviour	1 MHz ÷ 18 GHz	2.0 ms	(1)	
		Release time – power behaviour	1 MHz ÷ 18 GHz	2.5 ms	(1)	
		Transient behaviour of the transmitter– Transient frequency behaviour	1 MHz ÷ 18 GHz	0.2 kHz	(1)	
		Transient behaviour of the transmitter – Power level slope	1 MHz ÷ 18 GHz	9%	(1)	
		Frequency deviation - Maximum permissible frequency deviation	0.001 MHz ÷ 18 GHz	1.3%	(1)	
	Frequency deviation - Response of the transmitter to modulation frequencies above 3 kHz	0.001 MHz ÷ 18 GHz	0.5 dB	(1)		
	Dwell time	-	3%	(1)		
	Hopping Frequency Separation	0.01 MHz ÷ 18 GHz	1%	(1)		
Occupied Channel Bandwidth	0.01 MHz ÷ 18 GHz	2%	(1)			
Modulation Bandwidth	0.01 MHz ÷ 18 GHz	2%	(1)			
Radiated	Radiated spurious emissions	0.009 MHz ÷ 26.5 GHz	6.0 dB	(1)		
		26.5 GHz ÷ 66 GHz	8.0 dB	(1)		
		66 GHz ÷ 220 GHz	10 dB	(1)		
	Effective radiated power transmitter	10 kHz ÷ 26.5 GHz	6.0 dB	(1)		
		26.5 GHz ÷ 66 GHz	8.0 dB	(1)		
Receiver	Radiated	Radiated spurious emissions	0.009 MHz ÷ 26.5 GHz	6.0 dB	(1)	
			26.5 GHz ÷ 66 GHz	8.0 dB	(1)	
			66 GHz ÷ 220 GHz	10 dB	(1)	
	Conducted	Sensitivity measurement	1 MHz ÷ 18 GHz	6.0 dB	(1)	
			Conducted spurious emissions	0.009 MHz ÷ 18 GHz	3.0 dB	(1)
				18 GHz ÷ 40 GHz	4.2 dB	(1)
40 GHz ÷ 220 GHz	6.0 dB	(1)				

NOTES:

(1) The reported expanded uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor k = 2, which for a normal distribution corresponds to a coverage probability of approximately 95 %

Section 5: Test conditions, continued

5.4 Test equipment

Equipment	Manufacturer	Model No.	Asset/Serial No.	Next cal.
Vector Signal Generator	Keysight	N5172B EXG	MY53051238	2021-05
Vector Signal Generator	Keysight	N5172B EXG	MY56200267	2022-12
Spectrum Analyzer	Agilent	N9030A PXA	MY53120882	2020-12
Trilog Antenna (25 ÷ 8000 MHz)	Schwarzbeck Mess-Elektronik	VULB9162	9162-025	2021-07
Antenna (1 ÷ 18 GHz)	Schwarzbeck Mess-Elektronik	STLP9148	STLP 9148-152	2021-09
Double ridge horn antenna (4 ÷ 40 GHz)	RFSpin	DRH40	061106A40	2023-04
Broadband Amplifier (18 ÷ 40 GHz)	Sage	STB-1834034030-KFKF-L1	18490-01	2021-03
Broadband preamplifier (1 ÷ 18 GHz)	Schwarzbeck	BBV 9718	9718-137	2021-07
EMI receiver (2 Hz ÷ 44 GHz)	R&S	ESW44	101620	2020-08
Controller	Maturo	FCU3.0	10041	NCR
Tilt antenna mast	Maturo	TAM4.0-E	10042	NCR
Turntable	Maturo	TT4.0-5T	2.527	NCR
Semi-anechoic chamber	Nemko	10m semi-anechoic chamber	530	2021-09
Shielded room	Siemens	10m control room	1947	NCR

Note: N/A = Not Applicable, NCR = No Cal Required, COU = CAL On Use

# Appendix A: Test results

## Clause 935210 D05v01 (3.2) AGC threshold


Measure of EUT AGC Threshold

Test date: 2020-05-18 to 2020-06-05  
 Test results: Pass


### Special notes

- Narrowband amplifiers: MSK test signal used (GSM-TDMA signal)
- Broadband amplifiers: AWGN test signal used (5 MHz LTE channel)


### Test data




MSK Signal, Nominal Input Signal



MSK Signal, Nominal Input Signal +1dB



AWGN Signal, Nominal Input Signal



AWGN Signal, Nominal Input Signal +1dB


Clause 935210 D05v01 (3.3) Out of band rejection

Out of Band Rejection – Test for rejection of out of band signals.

Test date: 2020-05-18 to 2020-06-05  
 Test results: Pass

Special notes  
 –

Test data



## Clause 27.53(h)(3) Occupied bandwidth

A 26 dB bandwidth measurement shall be performed on the input signal and the output signal; alternatively, the 99% OBW can be measured and used.


Test date: 2020-05-18 to 2020-06-05  
 Test results: Pass

**Special notes**


- Narrowband amplifiers: MSK test signal used (GSM-TDMA signal)
- Broadband amplifiers: AWGN test signal used (5 MHz LTE channel)

## Test data


### MSK signal




MSK Signal, Nominal Input Signal, Output



MSK Signal, Nominal Input Signal, Input




MSK Signal, Nominal Input Signal +3dB, Output




MSK Signal, Nominal Input Signal +3dB, Input


AWGN signal




AWGN Signal, Nominal Input Signal, Output



AWGN Signal, Nominal Input Signal, Input



AWGN Signal, Nominal Input Signal +3dB, Output



AWGN Signal, Nominal Input Signal +3dB, Input



### Clause 27.50(d) Peak output power at RF antenna connector

**§ 27.50(d) The following power and antenna height requirements apply to stations transmitting in the 1695-1710 MHz, 1710-1755 MHz, 1755-1780 MHz, 1915-1920 MHz, 1995-2000 MHz, 2000-2020 MHz, 2110-2155 MHz, 2155-2180 MHz and 2180-2200 MHz bands:**

- (1) The power of each fixed or base station transmitting in the 1995-2000 MHz, 2110-2155 MHz, 2155-2180 MHz or 2180-2200 MHz band and located in any county with population density of 100 or fewer persons per square mile, based upon the most recently available population statistics from the Bureau of the Census, is limited to:
  - (i) An equivalent isotropically radiated power (EIRP) of 3280 watts when transmitting with an emission bandwidth of 1 MHz or less;
  - (ii) An EIRP of 3280 watts/MHz when transmitting with an emission bandwidth greater than 1 MHz.
- (2) The power of each fixed or base station transmitting in the 1995-2000 MHz, the 2110-2155 MHz 2155-2180 MHz band, or 2180-2200 MHz band and situated in any geographic location other than that described in paragraph (d)(1) of this section is limited to:
  - (i) An equivalent isotropically radiated power (EIRP) of 1640 watts when transmitting with an emission bandwidth of 1 MHz or less;
  - (ii) An EIRP of 1640 watts/MHz when transmitting with an emission bandwidth greater than 1 MHz.
- (5) Equipment employed must be authorized in accordance with the provisions of §24.51. Power measurements for transmissions by stations authorized under this section may be made either in accordance with a Commission-approved average power technique or in compliance with paragraph (d)(6) of this section. In measuring transmissions in this band using an average power technique, the peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.

Test date: 2020-05-18 to 2020-06-05

Test results: Pass

#### Special notes



- Narrowband amplifiers: MSK test signal used (GSM-TDMA signal)
- Broadband amplifiers: AWGN test signal used (5 MHz LTE channel)

Based on discussion in docket no. DA 13-2409 (para. 25 and 47) for operations in 2000-2020MHz in downlink, only 27.50 (d)(1) and 27.50 (d)(2) apply.

Test data

MSK signal, nominal input signal


Test data					
Direction	Modulation	Frequency (MHz)	RF output Power (dBm)	RF output channel Power (W)	PAR (dB)
Down-link	MSK (GSM, 200kHz)	2007.5	46.0	20.0	0.1



PAR measure is performed by the “CCDF” function installed on Spectrum analyzer that provides average power (the same measured with “Channel power” function), peak power and PAR.



**MSK signal, nominal input signal + 3dB**

Test data				
Direction	Modulation	Frequency (MHz)	RF output Power (dBm)	RF output channel Power (W)
Down-link	MSK (GSM, 200kHz)	2007.5	46.1	41.0



**AWGN signal, nominal input signal**


Test data						
Direction	Modulation	Frequency (MHz)	RF output Power (dBm)	RF output channel Power (W)	RF output Power (W/MHz)	PAR (dB)
Down-link	AWGN (LTE, 5MHz)	2007.5	46.0	40.0	8.0	9.6



PAR measure is performed by the “CCDF” function installed on Spectrum analyzer that provides average power (the same measured with “Channel power” function), peak power and PAR.

**AWGN signal, nominal input signal + 3dB**

Test data					
Direction	Modulation	Frequency (MHz)	RF output Power (dBm)	RF output channel Power (W)	RF output Power (W/MHz)
Down-link	AWGN (LTE, 5MHz)	2007.5	46.2	41.5	8.3



### Clause 27.53(h) Spurious emissions at RF antenna connector

(h) AWS emission limits:

(1) General protection levels. Except as otherwise specified below, for operations in the 1695-1710 MHz, 1710-1755 MHz, 1755-1780 MHz, 1915-1920 MHz, 1995-2000 MHz, 2000-2020 MHz, 2110-2155 MHz, 2155-2180 MHz, and 2180-2200 bands, the power of any emission outside a licensee's frequency block shall be attenuated below the transmitter power (P) in watts by at least  $43 + 10 \log_{10}(P)$  dB.

(2) Additional protection levels. Notwithstanding the foregoing paragraph (h)(1) of this section:

(ii) For operations in the 2000-2020 MHz band, the power of any emissions below 2000 MHz shall be attenuated below the transmitter power (P) in watts by at least  $70 + 10 \log_{10}(P)$  dB.

(iv) For operations in the 1995-2000 MHz band, the power of any emission between 2005-2020 MHz shall be attenuated below the transmitter power (P) in watts by at least  $70 + 10 \log_{10}(P)$  dB.

(3) Measurement procedure.

(i) Compliance with this provision is based on the use of measurement instrumentation employing a resolution bandwidth of 1 megahertz or greater. However, in the 1 megahertz bands immediately outside and adjacent to the licensee's frequency block, a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed. The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.

(ii) When measuring the emission limits, the nominal carrier frequency shall be adjusted as close to the licensee's frequency block edges, both upper and lower, as the design permits.

(iii) The measurements of emission power can be expressed in peak or average values, provided they are expressed in the same parameters as the transmitter power.

(4) Private agreements. (i) For AWS operations in the 2000-2020 MHz and 2180-2200 MHz bands, to the extent a licensee establishes unified operations across the AWS blocks, that licensee may choose not to observe the emission limit specified in paragraph (h)(1), above, strictly between its adjacent block licenses in a geographic area, so long as it complies with other Commission rules and is not adversely affecting the operations of other parties by virtue of exceeding the emission limit.

Test date: 2020-05-18 to 2020-06-05

Test results: Pass

#### Special notes

- Narrowband amplifiers: MSK test signal used (GSM-TDMA signal)
- Broadband amplifiers: AWGN test signal used (5 MHz LTE channel)

Based on discussion in docket no. DA 13-2409 (para. 25 and 47) for operations in 2000-2020MHz in downlink, only 27.53 (h)(1) and 27.53 (h)(3) apply.

Test data

**See Plots below**

Spurious emissions measurement results:

Frequency (MHz)	Spurious emission (dBm)	Limit (dBm)	Margin (dB)
First channel	Negligible	-13	
Mid channel	Negligible	-13	
Last channel	Negligible	-13	

MIMO consideration


In the final Remote Unit, the EUT could be used in MIMO configuration according to KDB 662911-D01 v02r01 and 662911-D02 v01 with signals completely uncorrelated. So, the maximum emission is calculated as follows:

- MIMO Maximum Emission = Emission at each path +  $10\log(Nant)$  dB =  
= Emission at each path +  $10\log(2)$  = Emission at each path + 3dB
- Spurious emission limit is -16dBm.


Test data, continued: spurious emissions at antenna terminal

**MSK signal**


(Plots are referred to modulated carrier at the Middle Channel)




MSK SIGNAL, 9kHz-150kHz



MSK SIGNAL, 150kHz-30MHz



MSK SIGNAL, 30MHz-1GHz




MSK SIGNAL, 1GHz-21GHz




**AWGN signal**


(Plots are referred to modulated carrier at the Middle Channel)




AWGN SIGNAL, 9kHz-150kHz



AWGN SIGNAL, 150kHz-30MHz




AWGN SIGNAL, 30MHz-1GHz




AWGN SIGNAL, 1GHz-21GHz

Test data, continued: band edges Inter modulation


MSK signal




MSK Signal, Nominal Input Signal, Low Band Edge, 1 Carrier




MSK Signal, Nominal Input Signal, High Band Edge, 1 Carrier




MSK Signal, Nominal Input Signal +3dB, Low Band Edge, 1 Carrier




MSK Signal, Nominal Input Signal +3dB, High Band Edge, 1 Carrier




MSK Signal, Nominal Input Signal, Low Band Edge, 2 Carrier



MSK Signal, Nominal Input Signal, High Band Edge, 2 Carrier




MSK Signal, Nominal Input Signal +3dB,  
Low Band Edge, 2 Carrier




MSK Signal, Nominal Input Signal +3dB,  
High Band Edge, 2 Carrier


AWGN signal




AWGN Signal, Nominal Input Signal, Low Band Edge, 1 Carrier




AWGN Signal, Nominal Input Signal, High Band Edge, 1 Carrier




AWGN Signal, Nominal Input Signal +3dB, Low Band Edge, 1 Carrier




AWGN Signal, Nominal Input Signal +3dB, High Band Edge, 1 Carrier




AWGN Signal, Nominal Input Signal, Low Band Edge, 2 Carrier



AWGN Signal, Nominal Input Signal, High Band Edge, 2 Carrier



AWGN Signal, Nominal Input Signal +3dB,  
 Low Band Edge, 2 Carrier



AWGN Signal, Nominal Input Signal +3dB,  
 High Band Edge, 2 Carrier

## Clause 27.53(h) Radiated Spurious emissions

(h) AWS emission limits:

(1) General protection levels. Except as otherwise specified below, for operations in the 1695-1710 MHz, 1710-1755 MHz, 1755-1780 MHz, 1915-1920 MHz, 1995-2000 MHz, 2000-2020 MHz, 2110-2155 MHz, 2155-2180 MHz, and 2180-2200 bands, the power of any emission outside a licensee's frequency block shall be attenuated below the transmitter power (P) in watts by at least  $43 + 10 \log_{10}(P)$  dB.

(2) Additional protection levels. Notwithstanding the foregoing paragraph (h)(1) of this section:

(ii) For operations in the 2000-2020 MHz band, the power of any emissions below 2000 MHz shall be attenuated below the transmitter power (P) in watts by at least  $70 + 10 \log_{10}(P)$  dB.

(iv) For operations in the 1995-2000 MHz band, the power of any emission between 2005-2020 MHz shall be attenuated below the transmitter power (P) in watts by at least  $70 + 10 \log_{10}(P)$  dB.

(3) Measurement procedure.

(i) Compliance with this provision is based on the use of measurement instrumentation employing a resolution bandwidth of 1 megahertz or greater. However, in the 1 megahertz bands immediately outside and adjacent to the licensee's frequency block, a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed. The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.

(ii) When measuring the emission limits, the nominal carrier frequency shall be adjusted as close to the licensee's frequency block edges, both upper and lower, as the design permits.

(iii) The measurements of emission power can be expressed in peak or average values, provided they are expressed in the same parameters as the transmitter power.

(4) Private agreements. (i) For AWS operations in the 2000-2020 MHz and 2180-2200 MHz bands, to the extent a licensee establishes unified operations across the AWS blocks, that licensee may choose not to observe the emission limit specified in paragraph (h)(1), above, strictly between its adjacent block licenses in a geographic area, so long as it complies with other Commission rules and is not adversely affecting the operations of other parties by virtue of exceeding the emission limit.

Test date: 2020-07-17

Test results: Pass


### Special notes

Based on discussion in docket no. DA 13-2409 (para. 25 and 47) for operations in 2000-2020MHz in downlink, only 27.53 (h)(1) and 27.53 (h)(3) apply.

Test data				
<p>The D.U.T. was positioned according to the radiated emissions set-up</p> <p>The D.U.T. antenna connector was terminated by a 50 Ω shielded dummy load.</p> <p>The spectrum was searched from 30 MHz to 1 GHz (RBW 100 kHz) &amp; 1 GHz (RBW 1 MHz) to the tenth harmonic of the carrier.</p> <p>There were no emissions detected above the noise floor which was at least 20 dB below the specification limit.</p>				
Spurious emissions measurement results:				
Frequency (MHz)	Polarization. V/H	Field strength (dBm)	Limit (dBm)	Margin (dB)
First Channel	V/H	Negligible	-13	
Mid channel	V/H	Negligible	-13	
Last Channel	V/H	Negligible	-13	
<p>Note: Field strength includes correction factor of antenna, cable loss, amplifier, and attenuators where applicable.</p>				


MIMO consideration
<p>In the final Remote Unit, the EUT could be used in MIMO configuration according to KDB 662911-D01 v02r01 and 662911-D02 v01 with signals completely uncorrelated. So, the maximum emission is calculated as follows:</p> <ul style="list-style-type: none"> <li>MIMO Maximum Emission = Emission at each path + 10log(Nant) dB = Emission at each path + 10log(2) = Emission at each path + 3dB</li> <li>Spurious emission limit is -16dBm.</li> </ul>

Test data




30 MHz – 1 GHz – H Pol







30 MHz – 1 GHz – V Pol




1 GHz – 18 GHz – H Pol



1 GHz – 18 GHz – V Pol




18 GHz – 21 GHz – H Pol




18 GHz – 21 GHz – V Pol

## Appendix B: Block diagrams of test set-ups

### Radiated emissions set-up



### Substitution method set-up



# Appendix C: EUT Photos

## Photo Set up








Photo EUT



END OF REPORT