

FCC TEST REPORT

(Part 15, Subpart C)

Applicant:	HMD Global Oy
Address:	Bertel Jungin aukio 9, 02600 Espoo, Finland

Manufacturer or Supplier:	HMD Global Oy
Address:	Bertel Jungin aukio 9, 02600 Espoo, Finland
Product:	Multi-band GSM/WCDMA/LTE phone with Bluetooth&WLAN
Brand Name:	NOKIA
Model Name:	TA-1412
FCC ID:	2AJOTTA-1412
Date of tests:	Nov. 25, 2021 ~ Dec. 12, 2021

The tests have been carried out according to the requirements of the following standard:

☒ **FCC Part 15, Subpart C, Section 15.247**

☒ **ANSI C63.10-2013**

CONCLUSION: The submitted sample was found to COMPLY with the test requirement

Prepared by Simon Wang Engineer / Mobile Department	Approved by Luke Lu Manager / Mobile Department
	
Date: Dec. 25, 2021	Date: Dec. 25, 2021

This report is governed by, and incorporates by reference, CPS Conditions of Service as posted at the date of issuance of this report at <http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions> and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.



TABLE OF CONTENTS

RELEASE CONTROL RECORD.....	6
1 SUMMARY OF TEST RESULTS.....	7
1.1 MEASUREMENT UNCERTAINTY.....	7
2 GENERAL INFORMATION.....	8
2.1 GENERAL DESCRIPTION OF EUT.....	8
2.2 DESCRIPTION OF TEST MODES.....	11
2.2.1 CONFIGURATION OF SYSTEM UNDER TEST.....	12
2.2.2 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL.....	12
2.3 DUTY CYCLE OF TEST SIGNAL.....	15
2.4 GENERAL DESCRIPTION OF APPLIED STANDARDS.....	16
2.5 DESCRIPTION OF SUPPORT UNITS.....	16
3 TEST TYPES AND RESULTS.....	17
3.1 CONDUCTED EMISSION MEASUREMENT.....	17
3.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT.....	17
3.1.2 TEST INSTRUMENTS.....	17
3.1.3 TEST PROCEDURES.....	18
3.1.4 DEVIATION FROM TEST STANDARD.....	18
3.1.5 TEST SETUP.....	19
3.1.6 EUT OPERATING CONDITIONS.....	19
3.1.7 TEST RESULTS.....	20
3.2 RADIATED EMISSION MEASUREMENT.....	22
3.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT.....	22
3.2.2 TEST INSTRUMENTS.....	23
3.2.3 TEST PROCEDURES.....	24
3.2.4 DEVIATION FROM TEST STANDARD.....	24
3.2.5 TEST SETUP.....	25
3.2.6 EUT OPERATING CONDITIONS.....	26
3.2.7 TEST RESULTS.....	27
3.3 6 DB BANDWIDTH MEASUREMENT.....	55
3.3.1 LIMITS OF 6DB BANDWIDTH MEASUREMENT.....	55
3.3.2 TEST INSTRUMENTS.....	55
3.3.3 TEST PROCEDURE.....	55
3.3.4 DEVIATION FROM TEST STANDARD.....	56



3.3.5	TEST SETUP.....	56
3.3.6	EUT OPERATING CONDITIONS.....	56
3.3.7	TEST RESULTS.....	57
3.4	CONDUCTED OUTPUT POWER.....	58
3.4.1	LIMITS OF CONDUCTED OUTPUT POWER MEASUREMENT.....	58
3.4.2	TEST SETUP.....	58
3.4.3	TEST INSTRUMENTS.....	58
3.4.4	TEST PROCEDURES.....	58
3.4.5	DEVIATION FROM TEST STANDARD.....	58
3.4.6	EUT OPERATING CONDITIONS.....	58
3.4.7	TEST RESULTS.....	59
3.4.7.1	MAXIMUM PEAK OUTPUT POWER.....	59
3.4.7.2	AVERAGE OUTPUT POWER (FOR REFERENCE).....	60
3.5	POWER SPECTRAL DENSITY MEASUREMENT.....	61
3.5.1	LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT.....	61
3.5.2	TEST SETUP.....	61
3.5.3	TEST INSTRUMENTS.....	61
3.5.4	TEST PROCEDURE.....	61
3.5.5	DEVIATION FROM TEST STANDARD.....	61
3.5.6	EUT OPERATING CONDITION.....	61
3.5.7	TEST RESULTS.....	62
3.6	OUT OF BAND EMISSION MEASUREMENT.....	63
3.6.1	LIMITS OF OUT OF BAND EMISSION MEASUREMENT.....	63
3.6.2	TEST SETUP.....	63
3.6.3	TEST INSTRUMENTS.....	63
3.6.4	TEST PROCEDURE.....	63
3.6.5	DEVIATION FROM TEST STANDARD.....	64
3.6.6	EUT OPERATING CONDITION.....	64
3.6.7	TEST RESULTS.....	64
4	PHOTOGRAPHS OF THE TEST CONFIGURATION.....	65
5	MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB	66
6	APPENDIX 1 BLE.....	67
	DTS BANDWIDTH.....	67
	TEST RESULT.....	67
	TEST GRAPHS.....	68
	OCCUPIED CHANNEL BANDWIDTH.....	74



TEST RESULT.....	74
TEST GRAPHS.....	75
MAXIMUM CONDUCTED OUTPUT POWER.....	81
PEAK POWER TEST RESULT.....	81
AVERAGE POWER TEST RESULT.....	81
MAXIMUM POWER SPECTRAL DENSITY.....	82
TEST RESULT.....	82
TEST GRAPHS.....	83
BAND EDGE MEASUREMENTS.....	89
TEST RESULT.....	89
TEST GRAPHS.....	90
CONDUCTED SPURIOUS EMISSION.....	94
TEST RESULT.....	94
TEST GRAPHS.....	95
DUTY CYCLE.....	114
TEST RESULT.....	114
TEST GRAPHS.....	115
7 APPENDIX 2 WLAN 2.4G.....	121
DTS BANDWIDTH.....	121
TEST RESULT.....	121
TEST GRAPHS.....	122
OCCUPIED CHANNEL BANDWIDTH.....	128
TEST RESULT.....	128
TEST GRAPHS.....	129
MAXIMUM CONDUCTED OUTPUT POWER.....	135
PEAK POWER TEST RESULT.....	135
AVERAGE POWER TEST RESULT.....	135
MAXIMUM POWER SPECTRAL DENSITY.....	136
TEST RESULT.....	136
TEST GRAPHS.....	137
BAND EDGE MEASUREMENTS.....	143
TEST RESULT.....	143
TEST GRAPHS.....	144
CONDUCTED SPURIOUS EMISSION.....	148
TEST RESULT.....	148
TEST GRAPHS.....	150



Test Report No.: W7L-P21100018-2RF02

DUTY CYCLE.....	168
TEST RESULT.....	168
TEST GRAPHS.....	169



BUREAU
VERITAS

Test Report No.: W7L-P21100018-2RF02

RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
W7L-P21100018-1RF02	Original release	Dec. 13, 2021
W7L-P21100018-2RF02	The model name is revised based on the W7L-P21100018-1RF02 report. The two models are only the difference between single SIM and double SIM, and the data reflects the original report data.	Dec. 25, 2021



1 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC PART 15, SUBPART C (SECTION 15.247)		
STANDARD SECTION	TEST TYPE AND LIMIT	RESULT
15.207	AC Power Conducted Emission	Compliance
15.205 15.209	Radiated Emissions	Compliance
15.247(d)	Out of band Emission Measurement	Compliance
15.247(a)(2)	6dB bandwidth	Compliance
15.247(b)	Conducted Output power	Compliance
15.247(e)	Power Spectral Density	Compliance
15.203	Antenna Requirement	Compliance

Note : Except RSE · other data please refer to Appendix 1 (for WIFI-2.4G) and Appendix 2 (for BLE)

1.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

MEASUREMENT	UNCERTAINTY
AC Power Conducted emissions	$\pm 2.70\text{dB}$
Radiated emissions (30MHz~1GMHz)	$\pm 4.98\text{dB}$
Radiated emissions (1GMHz ~6GMHz)	$\pm 4.70\text{dB}$
Radiated emissions (6GMHz ~18GMHz)	$\pm 4.60\text{dB}$
Radiated emissions (18GMHz ~40GMHz)	$\pm 4.12\text{dB}$
Conducted emissions	$\pm 4.01\text{dB}$
Occupied Channel Bandwidth	$\pm 43.58\text{KHz}$
Conducted Output power	$\pm 2.06\text{dB}$
Power Spectral Density	$\pm 0.85\text{ dB}$

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k = 2$.



2 GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

PRODUCT	Multi-band GSM/WCDMA/LTE phone with Bluetooth&WLAN
BRAND NAME	NOKIA
MODEL NAME	TA-1412
NOMINAL VOLTAGE	5.0/9.0/12.0Vdc(adapter or host equipment) 3.85Vdc (Li-ion, battery)
MODULATION	DSSS, OFDM, GFSK
TRANSMISSION RATE	802.11b: 11/ 5.5/ 2.0 / 1.0 Mbps 802.11g: 54/ 48/ 36 / 24 / 18 / 9/ 6 Mbps 802.11n20: up to 65 Mbps 802.11n40: up to 135 Mbps BT_LE: 0.125 Mbps /0.5 Mbps /1 Mbps/2 Mbps
OPERATING FREQUENCY	2412-2462MHz for 11b/g/n(HT20/ HT40) 2402-2480MHz for BT-LE(GFSK)
MAX. OUTPUT POWER	WLAN: 184.93mW (Maximum) BT-LE: 1.49mW (Maximum)
ANTENNA TYPE	Fixed Internal Antenna with 1.19dBi gain
HW VERSION	19655-1-11M12
SW VERSION	00WW_0_010
I/O PORTS	Refer to user's manual
CABLE SUPPLIED	USB1 cable: unshielded without ferrite, 1.0meter USB2 cable: unshielded without ferrite, 1.0meter USB3 cable: unshielded without ferrite, 1.0meter Earphone1: non-shielded cable, with w/o ferrite core, 1.2 meter Earphone2: non-shielded cable, with w/o ferrite core, 1.2 meter

NOTE:

1. For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.



2. The EUT incorporates a SISO function. Physically, the EUT provides one transmitter and one receiver.

MODULATION MODE	TX/RX FUNCTION
802.11b	1TX /1RX
802.11g	1TX /1RX
802.11n (20MHz)	1TX /1RX
802.11n (40MHz)	1TX /1RX
BT_LE(1MHz)	1TX /1RX
BT_LE(2MHz)	1TX /1RX
BT_LE(S2)	1TX /1RX
BT_LE(S8)	1TX /1RX

3. For the test results, the EUT had been tested with all conditions. But only the worst case was shown in test report.

List of Accessory:

ACCESSORIES	BRAND	MANUFACTURER	MODEL	SPECIFICATION
Battery	Nokia	Hunan Gaoyuan Battery Co., Ltd.	WT341	Capacity : 3.85 Vdc, 4900mAh
AC Adapter 1	Nokia	ShenZhenBaiJunDa ElectronicCO.,LTD.	AD-010U	I/P: 100-240Vac, 0.35A, O/P: 5.0Vdc, 2.0A
AC Adapter 2	Nokia	SHENZHEN TIANYIN ELECTRONICS CO., LTD.	CH-21U	I/P: 100-240Vac, 0.3A, O/P: 5.0Vdc, 2.0A
AC Adapter 3	Nokia	YuTong Electronics(HuiZhou) Co.,Ltd	PA-US5V2A-036	I/P: 100-240Vac, 0.5A, O/P: 5.0Vdc, 2.0A
AC Adapter 4	Nokia	Dongguan Aohai Technology Co., Ltd.	A829US	I/P: 100 - 240Vac, 0.5A, O/P:5.0 Vdc,3A/9.0 Vdc, 2.23A/12.0 Vdc,1.67A
Earphone 1	Nokia	NEW LEADER INDUSTRY CO.,LTD	HS-34	Signal Line, 1.2meter
Earphone 2	Nokia	Guangdong Wivtak Technology Co., Ltd.	HS-34	Signal Line, 1.2meter



**BUREAU
VERITAS**

Test Report No.: W7L-P21100018-2RF02

USB Cable 1	Nokia	HUIZHOU WASHIN ELECTRONICS CO.,LTD	CB-36A	Signal Line, 1.0meter
USB Cable 2	Nokia	Shenzhen BRL Technology Co.,Ltd.	CB-36A	Signal Line, 1.0meter
USB Cable 3	Nokia	Saibao(Jiangi) Communication Industrial Co.,Ltd	CB-12A	Signal Line, 1.0meter

NOTE:

BLE&WIFI test in the engineer mode,power setting at “ MAXIMUM CONDUCTED OUTPUT POWER”,
the steps for entering engineering mode are as follows:

1. In the finger plate, dial the code for entering Engineer mode: *##83781#*#*
2. EngineerMode->CONNECTIVITY->Wifi->Tx



2.2 DESCRIPTION OF TEST MODES

11 channels are provided for 802.11b, 802.11g and 802.11n (HT20):

CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
1	2412 MHz	7	2442 MHz
2	2417 MHz	8	2447 MHz
3	2422 MHz	9	2452 MHz
4	2427 MHz	10	2457 MHz
5	2432 MHz	11	2462 MHz
6	2437 MHz		

7 channels are provided for 802.11n (HT40):

CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
3	2422MHz	7	2442MHz
4	2427MHz	8	2447MHz
5	2432MHz	9	2452MHz
6	2437MHz		

40 channels are provided for BT-LE (GFSK):

CHANNEL	FREQ. (MHZ)	CHANNEL	FREQ. (MHZ)	CHANNEL	FREQ. (MHZ)	CHANNEL	FREQ. (MHZ)
0	2402	10	2422	20	2442	30	2462
1	2404	11	2424	21	2444	31	2464
2	2406	12	2426	22	2446	32	2466
3	2408	13	2428	23	2448	33	2468
4	2410	14	2430	24	2450	34	2470
5	2412	15	2432	25	2452	35	2472
6	2414	16	2434	26	2454	36	2474
7	2416	17	2436	27	2456	37	2476
8	2418	18	2438	28	2458	38	2478
9	2420	19	2440	29	2460	39	2480



2.2.1 CONFIGURATION OF SYSTEM UNDER TEST

Please see section 5 photographs of the test configuration for reference.

2.2.2 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis and antenna ports.

The worst case was found when positioned on Y axis for radiated emission. Following test modes were selected for the final test, and the final worst case is marked in boldface and recorded in the report:

EUT CONFIGURE MODE	APPLICABLE TO				MODE
	RE<1G	RE≥1G	PLC	APCM	
-	√	√	√	√	-

Where **RE<1G**: Radiated Emission below 1GHz

RE≥1G: Radiated Emission above 1GHz

PLC: Power Line Conducted Emission

APCM: Antenna Port Conducted Measurement

NOTE: No need to concern of Conducted Emission due to the EUT is powered by battery.

RADIATED EMISSION TEST (BELOW 1GHz):

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION	DATA RATE (Mbps)
802.11g	1 to 11	11	OFDM	6M
BT-LE	0 to 39	39	GFSK	2.0

**RADIATED EMISSION TEST (ABOVE 1GHz):**

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

☒ Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION	DATA RATE (Mbps)
802.11b	1 to 11	1, 6, 11	DSSS	1.0
802.11g	1 to 11	1, 6, 11	OFDM	6.0
802.11n HT20	1 to 11	1, 6, 11	OFDM	MCS0
802.11n HT40	3 to 9	3, 6, 9	OFDM	MCS0
BT-LE	0 to 39	0,19, 39	GFSK	0.125&0.5&1&2

POWER LINE CONDUCTED EMISSION TEST

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

☒ Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION	DATA RATE (Mbps)
802.11n HT20	1 to 11	11	OFDM	MCS0

BANDEDGE MEASUREMENT:

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

☒ Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION	DATA RATE (Mbps)
802.11b	1 to 11	1, 11	DSSS	1.0
802.11g	1 to 11	1, 11	OFDM	6.0
802.11n HT20	1 to 11	1, 11	OFDM	MCS0
802.11n HT40	3 to 9	3, 6, 9	OFDM	MCS0
BT-LE	0 to 39	0, 39	GFSK	0.125&0.5&1&2

**ANTENNA PORT CONDUCTED MEASUREMENT:**

- ☒ This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.
- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION	DATA RATE (Mbps)
802.11b	1 to 11	1, 6, 11	CCK	1.0
802.11g	1 to 11	1, 6, 11	OFDM	6.0
802.11n HT20	1 to 11	1, 6, 11	OFDM	MCS0
802.11n HT40	3 to 9	3, 6, 9	OFDM	MCS0
BT-LE	0 to 39	0,19, 39	GFSK	0.125&0.5&1&2

TEST CONDITION:

APPLICABLE TO	ENVIRONMENTAL CONDITIONS	TEST VOLTAGE	TESTED BY
RE<1G	23deg. C, 70%RH	DC 5V By Adapter	Star Le
RE≥1G	23deg. C, 70%RH	DC5V By Adapter	Star Le
PLC	25deg. C, 52%RH	DC5V By Adapter	Carl xie
APCM	25deg. C, 60%RH	DC 3.85V By Battery	Carl xie



2.3 Duty Cycle of Test Signal

Please Refer to Appendix1/2 Of this test report.

WORST-CASE DATA:

Measured Duty Cycle		
Mode		Duty Cycle [%]
		ANT1
WIFI 2.4GHz	11B	98.14
	11G	90.32
	11N20	88.06
	11N40	78.38
BT LE	BT4.0	87.23
	BT5.0	66.40
	BTS2	81.28
	BTS8	94.77

Note:

Duty cycle of test signal is < 98%, duty factor shall be considered.



2.4 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC Part 15, Subpart C, Section 15.247

KDB 558074 D01 DTS Meas Guidance v05r02

ANSI C63.10-2013

Note :

1. All test items have been performed and recorded as per the above standards.
2. The EUT is also considered as a kind of computer peripheral, because the connection to computer is necessary for typical use. It has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (Certification). The test report has been issued separately.

2.5 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	Desktop	Lenovo	M73 SFF	PC04GRQV	N/A
2	Desktop	Lenovo	M73 SFF	PC06CS27	N/A
3	Laptop	Lenovo	Thnikpad T450	PC-049PT1	N/A

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	AC Line: Unshielded, Detachable 1.5m
2	AC Line: Unshielded, Detachable 1.5m
3	AC Line: Unshielded, Detachable 1.5m



3 TEST TYPES AND RESULTS

3.1 CONDUCTED EMISSION MEASUREMENT

3.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dB μ V)	
	Quasi-peak	Average
0.15 ~ 0.5	66 to 56	56 to 46
0.5 ~ 5	56	46
5 ~ 30	60	50

NOTE: 1. The lower limit shall apply at the transition frequencies.

2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

3. All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

3.1.2 TEST INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
EMI Test Receiver	Rohde&Schwarz	ESR3	101900	Mar. 03,21	Mar. 02,22
EMC32 test software	Rohde&Schwarz	EMC32	NA	NA	NA
LISN network	Rohde&Schwarz	ENV216	101922	Feb. 25,21	Feb. 24,22

NOTE:

1. The test was performed in CE shielded room.

2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.



3.1.3 TEST PROCEDURES

- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- c. The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) was not recorded.


NOTE: All modes of operation were investigated and the worst-case emissions are reported.

3.1.4 DEVIATION FROM TEST STANDARD

No deviation.



3.1.5 TEST SETUP



Note: 1.Support units were connected to second LISN.

**2.Both of LISNs (AMN) are 80 cm from EUT and at least 80
from other units and other metal planes**

For the actual test configuration, please refer to the attached file (Test Setup Photo).

3.1.6 EUT OPERATING CONDITIONS

- a. Turned on the power and connected of all equipment.
- b. EUT was operated according to the type used was description in manufacturer's specifications or the User's Manual.



**BUREAU
VERITAS**

Test Report No.: W7L-P21100018-2RF02

3.1.7 TEST RESULTS

CONDUCTED WORST-CASE DATA:

Frequency Range	150KHz ~ 30MHz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9 kHz
Input Power	120Vac, 60Hz	Environmental Conditions	26deg. C, 51%RH
Tested By	Carl xie		

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
1.052000	---	18.33	46.00	27.67	L1	ON	9.7
1.052000	26.00	---	56.00	30.00	L1	ON	9.7
1.700000	---	23.03	46.00	22.97	L1	ON	9.7
1.700000	28.42	---	56.00	27.58	L1	ON	9.7
3.792000	---	27.31	46.00	18.69	L1	ON	9.7
3.792000	34.57	---	56.00	21.43	L1	ON	9.7
7.364000	---	37.76	50.00	12.24	L1	ON	9.7
7.364000	43.75	---	60.00	16.25	L1	ON	9.7
12.008000	---	36.14	50.00	13.86	L1	ON	9.8
12.008000	41.54	---	60.00	18.46	L1	ON	9.8
18.092000	---	25.34	50.00	24.66	L1	ON	9.8
18.092000	30.92	---	60.00	29.08	L1	ON	9.8

REMARKS: 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.

2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.


3. The emission levels of other frequencies were very low against the limit.

4. Margin value = Limit value - Emission level

5. Correction factor = Insertion loss + Cable loss

6. Emission Level = Correction Factor + Reading Value.

Full Spectrum





**BUREAU
VERITAS**


Test Report No.: W7L-P21100018-2RF02

Frequency Range	150KHz ~ 30MHz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9 kHz
Input Power	120Vac, 60Hz	Environmental Conditions	26deg. C, 51%RH
Tested By	Carl xie		

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
1.656000	---	21.18	46.00	24.82	N	ON	9.8
1.656000	27.22	---	56.00	28.78	N	ON	9.8
3.540000	---	24.94	46.00	21.06	N	ON	9.8
3.540000	30.99	---	56.00	25.01	N	ON	9.8
4.976000	---	29.88	46.00	16.12	N	ON	9.8
4.976000	36.11	---	56.00	19.89	N	ON	9.8
7.684000	---	38.41	50.00	11.59	N	ON	9.8
7.684000	44.34	---	60.00	15.66	N	ON	9.8
10.588000	---	36.65	50.00	13.35	N	ON	9.8
10.588000	42.06	---	60.00	17.94	N	ON	9.8
17.892000	---	25.50	50.00	24.50	N	ON	9.9
17.892000	30.93	---	60.00	29.07	N	ON	9.9

- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Limit value - Emission level
 5. Correction factor = Insertion loss + Cable loss
 6. Emission Level = Correction Factor + Reading Value.

Full Spectrum





3.2 RADIATED EMISSION MEASUREMENT

3.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT

Radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a).

FREQUENCIES (MHz)	FIELD STRENGTH (microvolts/meter)	MEASUREMENT DISTANCE (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.



3.2.2 TEST INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
3m Semi-anechoic Chamber	ETS-LINDGREN	9m*6m*6m	Euroshieldpn-CT0001143-1216	May. 19,20	May. 18,23
Bilog Antenna	ETS-LINDGREN	3143B	00161965	Mar. 05,21	Mar. 04,22
Horn Antenna	ETS-LINDGREN	3117	00168728	Apr. 02, 21	Apr. 01, 22
Horn Antenna (18GHz-40GHz)	N/A	QWH-SL-18-40-K-SG/QMS-00361	15433	Aug. 25, 21	Aug. 24, 22
Test Software	E3	V 9.160323	N/A	N/A	N/A
Test Software	ADT	ADT_Radiated_V7.6.15.9.2	N/A	N/A	N/A
10dB Attenuator	JFW/USA	50HF-010-SMA	1505	Jun. 03,21	Jun. 02,22
MXE EMI Receiver	KEYSIGHT	N9038A-544	MY54450026	Apr. 27,21	Apr. 26,22
Signal Pre-Amplifier	EMSI	EMC 9135	980249	Jun. 02,21	Jun. 01,22
Signal Pre-Amplifier	EMSI	EMC 012645B	980257	Jun. 02,21	Jun. 01,22
Signal Pre-Amplifier	EMSI	EMC 184045B	980259	Apr. 30,21	Apr. 29,22
DC Source	Kikusui/JP	PMX18-5A	0000001	Aug. 25,21	Aug. 24,22
Power Meter	Anritsu	ML2495A	1506002	Feb. 25,21	Feb. 24,22
Power Sensor	Anritsu	MA2411B	1339352	Feb. 25,21	Feb. 24,22
Loop Antenna	Schwarzbeck	FMZB 1519B	1519B-051	Feb 14,20	Feb. 13,23

- NOTE:**
1. The calibration interval of the above test instruments is 12 months or 3 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.
 2. The test was performed in 3m Chamber.
 3. The FCC Site Registration No. is 525120; The Designation No. is CN1171.



3.2.3 TEST PROCEDURES

- a. The EUT was placed on the top of a rotating table 0.8 meters (for below 1GHz) / 1.5 meters (for above 1GHz) above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, For battery operated equipment, the equipment tests shall be perform using fresh batteries. The turntable was rotated to maximize the emission level.

Note:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 3MHz for RMS Average (Duty cycle < 98%) for Average detection (AV) at frequency above 1GHz, then the measurement results was added to a correction factor ($10 \log(1/\text{duty cycle})$).
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 10Hz (Duty cycle $\geq 98\%$) for Average detection (AV) at frequency above 1GHz.
5. All modes of operation were investigated and the worst-case emissions are reported.

3.2.4 DEVIATION FROM TEST STANDARD

No deviation




BUREAU
VERITAS


Test Report No.: W7L-P21100018-2RF02

3.2.5 TEST SETUP


<Frequency Range 9KHz~30MHz >



< Frequency Range 30MHz~1GHz >



<Frequency Range above 1GHz>



Note: Above 1G is a directional antenna

Depends on the EUT height and the antenna 3dB beamwidth both, refer to section 7.3 of CISPR 16-2-3.

For the actual test configuration, please refer to the attached file (Test Setup Photo).

3.2.6 EUT OPERATING CONDITIONS

- Set the EUT under full load condition and placed them on a testing table.
- Set the transmitter part of EUT under transmission condition continuously at specific channel frequency.
- The necessary accessories enable the EUT in full functions.



**BUREAU
VERITAS**

Test Report No.: W7L-P21100018-2RF02

3.2.7 TEST RESULTS

BELOW 1GHz WORST-CASE DATA:


Note: For frequency below 30MHz, the emission was tested 20db below the limit so the data not recorded in the sheet.

30 MHz – 1GHz data:

802.11n (20MHz)

CHANNEL	TX Channel 11	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	30MHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
63.950	38.16	13.77	1.33	32.57	20.69	40.00	-19.31	QP
106.630	37.72	9.96	1.74	32.51	16.91	43.50	-26.59	QP
287.050	35.69	12.91	2.96	32.60	18.96	46.00	-27.04	QP
306.450	36.90	13.21	3.09	32.61	20.59	46.00	-25.41	QP
731.310	30.66	20.51	4.94	32.57	23.54	46.00	-22.46	QP
899.120	27.89	21.85	5.73	31.76	23.71	46.00	-22.29	QP




BUREAU
VERITAS

Test Report No.: W7L-P21100018-2RF02

CHANNEL	TX Channel 11	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	30MHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamplifier factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
38.730	47.54	14.28	0.98	32.60	30.20	40.00	-9.80	QP
160.950	37.67	13.92	2.18	32.56	21.21	43.50	-22.29	QP
335.550	36.82	13.78	3.19	32.64	21.15	46.00	-24.85	QP
731.310	30.30	20.51	4.94	32.57	23.18	46.00	-22.82	QP
768.170	30.18	20.85	5.07	32.53	23.57	46.00	-22.43	QP
981.570	26.97	22.64	5.83	31.14	24.30	54.00	-29.70	QP



**BUREAU
VERITAS**

Test Report No.: W7L-P21100018-2RF02

ABOVE 1GHz WORST-CASE DATA:

Note: For higher frequency, the emission is too low to be detected.

802.11b:

CHANNEL	TX Channel 1	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2310.000	45.03	27.38	4.08	35.68	40.81	74.00	-33.19	Peak
2390.000	52.15	27.56	4.16	35.88	47.99	74.00	-26.01	Peak
2413.500	107.27	27.61	4.17	35.93	103.12	74.00	29.12	Peak
2310.000	31.61	27.38	4.08	35.68	27.39	54.00	-26.61	Average
2389.375	36.51	27.56	4.16	35.87	32.36	54.00	-21.64	Average
2390.000	35.89	27.56	4.16	35.88	31.73	54.00	-22.27	Average
2412.750	102.86	27.61	4.17	35.93	98.71	54.00	44.71	Average

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2310.000	42.38	27.38	4.08	35.68	38.16	74.00	-35.84	Peak
2390.000	51.51	27.56	4.16	35.88	47.35	74.00	-26.65	Peak
2413.500	108.78	27.61	4.17	35.93	104.63	74.00	30.63	Peak
2310.000	31.57	27.38	4.08	35.68	27.35	54.00	-26.65	Average
2389.375	36.57	27.56	4.16	35.87	32.42	54.00	-21.58	Average
2390.000	36.01	27.56	4.16	35.88	31.85	54.00	-22.15	Average
2412.750	104.07	27.61	4.17	35.93	99.92	54.00	45.92	Average

REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Emission level – Limit value.
2. 2412MHz: Fundamental frequency.



**BUREAU
VERITAS**

Test Report No.: W7L-P21100018-2RF02

CHANNEL	TX Channel 6	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
4874.000	27.63	31.02	6.97	34.04	31.58	54.00	-22.42	Average
4874.000	40.59	31.02	6.97	34.04	44.54	74.00	-29.46	Peak
7311.000	27.01	35.65	8.95	34.48	37.13	54.00	-16.87	Average
7311.000	41.97	35.65	8.95	34.48	52.09	74.00	-21.91	Peak
9748.000	26.32	38.50	11.20	34.20	41.82	54.00	-12.18	Average
9748.000	39.33	38.50	11.20	34.20	54.83	74.00	-19.17	Peak
2437.000	106.00	27.66	4.18	35.99	101.85	74.00	27.85	Peak

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
4874.000	28.32	31.02	6.97	34.04	32.27	54.00	-21.73	Average
4874.000	40.98	31.02	6.97	34.04	44.93	74.00	-29.07	Peak
7311.000	34.77	35.65	8.95	34.48	44.89	54.00	-9.11	Average
7311.000	42.85	35.65	8.95	34.48	52.97	74.00	-21.03	Peak
9748.000	26.59	38.50	11.20	34.20	42.09	54.00	-11.91	Average
9748.000	39.34	38.50	11.20	34.20	54.84	74.00	-19.16	Peak
2437.000	106.10	27.66	4.18	35.99	101.95	74.00	27.95	Peak

REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Emission level – Limit value.
2. 2437MHz: Fundamental frequency.



**BUREAU
VERITAS**

Test Report No.: W7L-P21100018-2RF02

CHANNEL	TX Channel 11	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2460.620	109.24	27.71	4.19	36.05	105.09	74.00	31.09	Peak
2483.500	51.92	27.76	4.19	36.11	47.76	74.00	-26.24	Peak
2483.660	52.75	27.76	4.19	36.11	48.59	74.00	-25.41	Peak
2500.000	44.83	27.80	4.19	36.15	40.67	74.00	-33.33	Peak
2461.220	105.05	27.71	4.19	36.05	100.90	54.00	46.90	Average
2483.500	40.78	27.76	4.19	36.11	36.62	54.00	-17.38	Average
2486.060	41.16	27.77	4.19	36.12	37.00	54.00	-17.00	Average
2500.000	31.54	27.80	4.19	36.15	27.38	54.00	-26.62	Average

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2460.560	109.50	27.71	4.19	36.05	105.35	74.00	31.35	Peak
2483.500	52.55	27.76	4.19	36.11	48.39	74.00	-25.61	Peak
2483.660	52.93	27.76	4.19	36.11	48.77	74.00	-25.23	Peak
2500.000	44.67	27.80	4.19	36.15	40.51	74.00	-33.49	Peak
2461.220	105.05	27.71	4.19	36.05	100.90	54.00	46.90	Average
2483.500	41.40	27.76	4.19	36.11	37.24	54.00	-16.76	Average
2486.060	41.73	27.77	4.19	36.12	37.57	54.00	-16.43	Average
2500.000	31.54	27.80	4.19	36.15	27.38	54.00	-26.62	Average

REMARKS:

- Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Emission level – Limit value.
- 2462MHz: Fundamental frequency.

BUREAU
VERITAS

Test Report No.: W7L-P21100018-2RF02

802.11g

CHANNEL	TX Channel 1	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2310.000	44.59	27.38	4.08	35.68	40.37	74.00	-33.63	Peak
2390.000	66.26	27.56	4.16	35.88	62.10	74.00	-11.90	Peak
2415.875	109.56	27.61	4.17	35.94	105.40	74.00	31.40	Peak
2310.000	31.64	27.38	4.08	35.68	27.42	54.00	-26.58	Average
2390.000	45.04	27.56	4.16	35.88	40.88	54.00	-13.12	Average
2415.750	95.12	27.61	4.17	35.94	90.96	54.00	36.96	Average

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2310.000	43.80	27.38	4.08	35.68	39.58	74.00	-34.42	Peak
2390.000	65.47	27.56	4.16	35.88	61.31	74.00	-12.69	Peak
2415.750	110.77	27.61	4.17	35.94	106.61	74.00	32.61	Peak
2310.000	31.60	27.38	4.08	35.68	27.38	54.00	-26.62	Average
2390.000	45.92	27.56	4.16	35.88	41.76	54.00	-12.24	Average
2415.500	96.18	27.61	4.17	35.94	92.02	54.00	38.02	Average

REMARKS:

- Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Emission level – Limit value.
- 2412MHz: Fundamental frequency.



**BUREAU
VERITAS**

Test Report No.: W7L-P21100018-2RF02

CHANNEL	TX Channel 6	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
4874.000	27.60	31.02	6.97	34.04	31.55	54.00	-22.45	Average
4874.000	40.53	31.02	6.97	34.04	44.48	74.00	-29.52	Peak
7311.000	26.37	35.65	8.95	34.48	36.49	54.00	-17.51	Average
7311.000	41.06	35.65	8.95	34.48	51.18	74.00	-22.82	Peak
9748.000	26.97	38.50	11.20	34.20	42.47	54.00	-11.53	Average
9748.000	39.06	38.50	11.20	34.20	54.56	74.00	-19.44	Peak
2437.000	108.39	27.66	4.18	35.99	104.24	74.00	30.24	Peak

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
4874.000	27.68	31.02	6.97	34.04	31.63	54.00	-22.37	Average
4874.000	41.46	31.02	6.97	34.04	45.41	74.00	-28.59	Peak
7311.000	30.02	35.65	8.95	34.48	40.14	54.00	-13.86	Average
7311.000	44.03	35.65	8.95	34.48	54.15	74.00	-19.85	Peak
9748.000	27.01	38.50	11.20	34.20	42.51	54.00	-11.49	Average
9748.000	39.26	38.50	11.20	34.20	54.76	74.00	-19.24	Peak
2437.000	108.31	27.66	4.18	35.99	104.16	74.00	30.16	Peak

REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Emission level – Limit value.
2. 2437MHz: Fundamental frequency.



**BUREAU
VERITAS**

Test Report No.: W7L-P21100018-2RF02

CHANNEL	TX Channel 11	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2458.220	109.18	27.71	4.18	36.05	105.02	74.00	31.02	Peak
2483.500	73.28	27.76	4.19	36.11	69.12	74.00	-4.88	Peak
2500.000	45.20	27.80	4.19	36.15	41.04	74.00	-32.96	Peak
2459.720	95.08	27.71	4.18	36.05	90.92	54.00	36.92	Average
2483.500	46.81	27.76	4.19	36.11	42.65	54.00	-11.35	Average
2500.000	31.51	27.80	4.19	36.15	27.35	54.00	-26.65	Average

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2459.600	109.72	27.71	4.18	36.05	105.56	74.00	31.56	Peak
2483.500	73.73	27.76	4.19	36.11	69.57	74.00	-4.43	Peak
2500.000	44.53	27.80	4.19	36.15	40.37	74.00	-33.63	Peak
2459.540	95.87	27.71	4.18	36.05	91.71	54.00	37.71	Average
2483.500	47.62	27.76	4.19	36.11	43.46	54.00	-10.54	Average
2500.000	31.52	27.80	4.19	36.15	27.36	54.00	-26.64	Average

REMARKS:

- Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Emission level – Limit value.
- 2462MHz: Fundamental frequency.



**BUREAU
VERITAS**

Test Report No.: W7L-P21100018-2RF02

802.11n (20MHz)

CHANNEL	TX Channel 1	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2310.000	44.04	27.38	4.08	35.68	39.82	74.00	-34.18	Peak
2390.000	68.71	27.56	4.16	35.88	64.55	74.00	-9.45	Peak
2416.500	108.65	27.62	4.17	35.94	104.50	74.00	30.50	Peak
2310.000	31.63	27.38	4.08	35.68	27.41	54.00	-26.59	Average
2390.000	45.00	27.56	4.16	35.88	40.84	54.00	-13.16	Average
2415.250	96.21	27.61	4.17	35.94	92.05	54.00	38.05	Average

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2310.000	44.42	27.38	4.08	35.68	40.20	74.00	-33.80	Peak
2390.000	69.46	27.56	4.16	35.88	65.30	74.00	-8.70	Peak
2417.875	110.66	27.62	4.17	35.94	106.51	74.00	32.51	Peak
2310.000	31.63	27.38	4.08	35.68	27.41	54.00	-26.59	Average
2390.000	45.99	27.56	4.16	35.88	41.83	54.00	-12.17	Average
2415.250	97.65	27.61	4.17	35.94	93.49	54.00	39.49	Average

REMARKS:

- Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Emission level – Limit value.
- 2412MHz: Fundamental frequency.



**BUREAU
VERITAS**

Test Report No.: W7L-P21100018-2RF02

CHANNEL	TX Channel 6	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
4874.000	27.56	31.02	6.97	34.04	31.51	54.00	-22.49	Average
4874.000	41.33	31.02	6.97	34.04	45.28	74.00	-28.72	Peak
7311.000	26.30	35.65	8.95	34.48	36.42	54.00	-17.58	Average
7311.000	40.99	35.65	8.95	34.48	51.11	74.00	-22.89	Peak
9748.000	26.93	38.50	11.20	34.20	42.43	54.00	-11.57	Average
9748.000	39.08	38.50	11.20	34.20	54.58	74.00	-19.42	Peak
2437.000	108.44	27.66	4.18	35.99	104.29	74.00	30.29	Peak

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
4874.000	27.56	31.02	6.97	34.04	31.51	54.00	-22.49	Average
4874.000	40.56	31.02	6.97	34.04	44.51	74.00	-29.49	Peak
7311.000	26.95	35.65	8.95	34.48	37.07	54.00	-16.93	Average
7311.000	42.68	35.65	8.95	34.48	52.80	74.00	-21.20	Peak
9748.000	26.96	38.50	11.20	34.20	42.46	54.00	-11.54	Average
9748.000	40.04	38.50	11.20	34.20	55.54	74.00	-18.46	Peak
2437.000	109.20	27.66	4.18	35.99	105.05	74.00	31.05	Peak

REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Emission level – Limit value.
2. 2437MHz: Fundamental frequency.

BUREAU
VERITAS

Test Report No.: W7L-P21100018-2RF02

CHANNEL	TX Channel 11	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2460.560	108.68	27.71	4.19	36.05	104.53	74.00	30.53	Peak
2483.500	74.17	27.76	4.19	36.11	70.01	74.00	-3.99	Peak
2500.000	45.23	27.80	4.19	36.15	41.07	74.00	-32.93	Peak
2460.140	95.45	27.71	4.19	36.05	91.30	54.00	37.30	Average
2483.500	44.22	27.76	4.19	36.11	40.06	54.00	-13.94	Average
2500.000	31.56	27.80	4.19	36.15	27.40	54.00	-26.60	Average

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2460.560	108.66	27.71	4.19	36.05	104.51	74.00	30.51	Peak
2483.500	74.50	27.76	4.19	36.11	70.34	74.00	-3.66	Peak
2500.000	45.03	27.80	4.19	36.15	40.87	74.00	-33.13	Peak
2460.500	94.91	27.71	4.19	36.05	90.76	54.00	36.76	Average
2483.500	44.64	27.76	4.19	36.11	40.48	54.00	-13.52	Average
2500.000	31.51	27.80	4.19	36.15	27.35	54.00	-26.65	Average

REMARKS:

- Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Emission level – Limit value.
- 2462MHz: Fundamental frequency.



BUREAU VERITAS Test Report No.: W7L-P21100018-2RF02

802.11n (40MHz)

CHANNEL	TX Channel 3	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2310.000	44.50	27.38	4.08	35.68	40.28	74.00	-33.72	Peak
2390.000	71.46	27.56	4.16	35.88	67.30	74.00	-6.70	Peak
2427.350	107.80	27.64	4.18	35.97	103.65	74.00	29.65	Peak
2310.000	31.69	27.38	4.08	35.68	27.47	54.00	-26.53	Average
2390.000	49.57	27.56	4.16	35.88	45.41	54.00	-8.59	Average
2425.550	93.98	27.64	4.18	35.96	89.84	54.00	35.84	Average

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2310.000	45.10	27.38	4.08	35.68	40.88	74.00	-33.12	Peak
2390.000	68.27	27.56	4.16	35.88	64.11	74.00	-9.89	Peak
2425.100	106.96	27.64	4.18	35.96	102.82	74.00	28.82	Peak
2310.000	32.31	27.38	4.08	35.68	28.09	54.00	-25.91	Average
2390.000	48.65	27.56	4.16	35.88	44.49	54.00	-9.51	Average
2426.000	94.84	27.64	4.18	35.97	90.69	54.00	36.69	Average

REMARKS:

- Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Emission level – Limit value.
- 2412MHz: Fundamental frequency.



**BUREAU
VERITAS**

Test Report No.: W7L-P21100018-2RF02

CHANNEL	TX Channel 6	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
4874.000	27.59	31.02	6.97	34.04	31.54	54.00	-22.46	Average
4874.000	41.01	31.02	6.97	34.04	44.96	74.00	-29.04	Peak
7311.000	26.73	35.65	8.95	34.48	36.85	54.00	-17.15	Average
7311.000	40.99	35.65	8.95	34.48	51.11	74.00	-22.89	Peak
9748.000	26.94	38.50	11.20	34.20	42.44	54.00	-11.56	Average
9748.000	39.54	38.50	11.20	34.20	55.04	74.00	-18.96	Peak
2437.000	105.95	27.66	4.18	35.99	101.80	74.00	27.80	Peak

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
4874.000	27.52	31.02	6.97	34.04	31.47	54.00	-22.53	Average
4874.000	40.39	31.02	6.97	34.04	44.34	74.00	-29.66	Peak
7311.000	28.67	35.65	8.95	34.48	38.79	54.00	-15.21	Average
7311.000	41.72	35.65	8.95	34.48	51.84	74.00	-22.16	Peak
9748.000	26.90	38.50	11.20	34.20	42.40	54.00	-11.60	Average
9748.000	38.79	38.50	11.20	34.20	54.29	74.00	-19.71	Peak
2437.000	106.28	27.66	4.18	35.99	102.13	74.00	28.13	Peak

REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Emission level – Limit value.
2. 2437MHz: Fundamental frequency.



**BUREAU
VERITAS**

Test Report No.: W7L-P21100018-2RF02

CHANNEL	TX Channel 9	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2460.360	105.10	27.71	4.19	36.05	100.95	74.00	26.95	Peak
2483.500	73.07	27.76	4.19	36.11	68.91	74.00	-5.09	Peak
2484.075	73.79	27.76	4.19	36.11	69.63	74.00	-4.37	Peak
2500.000	46.09	27.80	4.19	36.15	41.93	74.00	-32.07	Peak
2460.530	93.79	27.71	4.19	36.05	89.64	54.00	35.64	Average
2483.500	51.46	27.76	4.19	36.11	47.30	54.00	-6.70	Average
2500.000	32.64	27.80	4.19	36.15	28.48	54.00	-25.52	Average

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2460.360	103.51	27.71	4.19	36.05	99.36	74.00	25.36	Peak
2483.500	74.82	27.76	4.19	36.11	70.66	74.00	-3.34	Peak
2500.000	46.58	27.80	4.19	36.15	42.42	74.00	-31.58	Peak
2458.660	91.92	27.71	4.18	36.05	87.76	54.00	33.76	Average
2483.500	51.28	27.76	4.19	36.11	47.12	54.00	-6.88	Average
2500.000	32.70	27.80	4.19	36.15	28.54	54.00	-25.46	Average

REMARKS:

- Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Emission level – Limit value.
- 2462MHz: Fundamental frequency.



**BUREAU
VERITAS**

Test Report No.: W7L-P21100018-2RF02

BELOW 1GHz WORST-CASE DATA:


Note: For frequency below 30MHz, the emission was tested 20db below the limit so the data not recorded in the sheet.

30 MHz – 1GHz data:

BT-LE (S2)

CHANNEL	TX Channel 19	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	30MHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M






**BUREAU
VERITAS**

Test Report No.: W7L-P21100018-2RF02

CHANNEL	TX Channel 19	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	30MHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M





**BUREAU
VERITAS**

Test Report No.: W7L-P21100018-2RF02

ABOVE 1GHz TEST DATA

Note: For higher frequency, the emission is too low to be detected.

BT-LE _1M

CHANNEL	TX Channel 0	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2310.000	41.67	27.38	4.08	35.68	37.45	74.00	-36.55	Peak
2338.535	44.50	27.44	4.11	35.75	40.30	74.00	-33.70	Peak
2390.000	42.17	27.56	4.16	35.88	38.01	74.00	-35.99	Peak
2402.375	96.66	27.59	4.17	35.91	92.51	74.00	18.51	Peak
2310.000	30.24	27.38	4.08	35.68	26.02	54.00	-27.98	Average
2390.000	30.89	27.56	4.16	35.88	26.73	54.00	-27.27	Average
2402.060	96.25	27.58	4.17	35.91	92.09	54.00	38.09	Average

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2310.000	41.86	27.38	4.08	35.68	37.64	74.00	-36.36	Peak
2370.770	44.33	27.52	4.14	35.83	40.16	74.00	-33.84	Peak
2390.000	42.72	27.56	4.16	35.88	38.56	74.00	-35.44	Peak
2402.270	96.57	27.58	4.17	35.91	92.41	74.00	18.41	Peak
2310.000	30.35	27.38	4.08	35.68	26.13	54.00	-27.87	Average
2390.000	30.75	27.56	4.16	35.88	26.59	54.00	-27.41	Average
2402.060	95.83	27.58	4.17	35.91	91.67	54.00	37.67	Average

REMARKS:

- Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Emission level – Limit value.
- 2402MHz: Fundamental frequency.



**BUREAU
VERITAS**

Test Report No.: W7L-P21100018-2RF02

CHANNEL	TX Channel 19	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
4880.000	29.69	31.03	7.01	34.03	33.70	54.00	-20.30	Average
4880.000	39.50	31.03	7.01	34.03	43.51	74.00	-30.49	Peak
7320.000	28.11	35.67	8.97	34.49	38.26	54.00	-15.74	Average
7320.000	38.26	35.67	8.97	34.49	48.41	74.00	-25.59	Peak
9760.000	28.98	38.51	11.16	34.20	44.45	54.00	-9.55	Average
9760.000	38.41	38.51	11.16	34.20	53.88	74.00	-20.12	Peak
2440.000	94.70	27.67	4.18	36.00	90.55	74.00	16.55	Peak

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
4880.000	29.36	31.03	7.01	34.03	33.37	54.00	-20.63	Average
4880.000	39.19	31.03	7.01	34.03	43.20	74.00	-30.80	Peak
7320.000	28.01	35.67	8.97	34.49	38.16	54.00	-15.84	Average
7320.000	37.75	35.67	8.97	34.49	47.90	74.00	-26.10	Peak
9760.000	28.86	38.51	11.16	34.20	44.33	54.00	-9.67	Average
9760.000	38.69	38.51	11.16	34.20	54.16	74.00	-19.84	Peak
2440.000	94.49	27.67	4.18	36.00	90.34	74.00	16.34	Peak

REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Emission level – Limit value.
2. 2440MHz: Fundamental frequency.



**BUREAU
VERITAS**

Test Report No.: W7L-P21100018-2RF02

CHANNEL	TX Channel 39	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2480.234	92.26	27.76	4.19	36.10	88.11	74.00	14.11	Peak
2483.500	43.13	27.76	4.19	36.11	38.97	74.00	-35.03	Peak
2484.524	45.37	27.77	4.19	36.11	41.22	74.00	-32.78	Peak
2500.000	41.37	27.80	4.19	36.15	37.21	74.00	-36.79	Peak
2479.937	92.26	27.76	4.19	36.10	88.11	54.00	34.11	Average
2483.500	31.37	27.76	4.19	36.11	27.21	54.00	-26.79	Average
2500.000	29.98	27.80	4.19	36.15	25.82	54.00	-28.18	Average

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2480.267	91.55	27.76	4.19	36.10	87.40	74.00	13.40	Peak
2483.500	42.13	27.76	4.19	36.11	37.97	74.00	-36.03	Peak
2483.897	44.15	27.76	4.19	36.11	39.99	74.00	-34.01	Peak
2500.000	42.00	27.80	4.19	36.15	37.84	74.00	-36.16	Peak
2480.003	90.94	27.76	4.19	36.10	86.79	54.00	32.79	Average
2483.500	31.06	27.76	4.19	36.11	26.90	54.00	-27.10	Average
2500.000	29.95	27.80	4.19	36.15	25.79	54.00	-28.21	Average

REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Emission level – Limit value.
2. 2480MHz: Fundamental frequency.



**BUREAU
VERITAS**

Test Report No.: W7L-P21100018-2RF02

BT-LE_2M

CHANNEL	TX Channel 0	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2310.000	42.44	27.38	4.08	35.68	38.22	74.00	-35.78	Peak
2310.920	44.74	27.38	4.08	35.68	40.52	74.00	-33.48	Peak
2390.000	42.23	27.56	4.16	35.88	38.07	74.00	-35.93	Peak
2402.585	96.85	27.59	4.17	35.91	92.70	74.00	18.70	Peak
2310.000	30.47	27.38	4.08	35.68	26.25	54.00	-27.75	Average
2390.000	30.86	27.56	4.16	35.88	26.70	54.00	-27.30	Average
2402.060	95.00	27.58	4.17	35.91	90.84	54.00	36.84	Average

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2310.000	43.11	27.38	4.08	35.68	38.89	74.00	-35.11	Peak
2389.250	45.80	27.56	4.16	35.87	41.65	74.00	-32.35	Peak
2390.000	43.35	27.56	4.16	35.88	39.19	74.00	-34.81	Peak
2401.535	96.36	27.58	4.17	35.90	92.21	74.00	18.21	Peak
2310.000	30.27	27.38	4.08	35.68	26.05	54.00	-27.95	Average
2390.000	30.91	27.56	4.16	35.88	26.75	54.00	-27.25	Average
2402.060	94.40	27.58	4.17	35.91	90.24	54.00	36.24	Average

REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Emission level – Limit value.
2. 2402MHz: Fundamental frequency.



CHANNEL	TX Channel 19	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
4880.000	30.69	31.03	7.01	34.03	34.70	54.00	-19.30	Average
4880.000	40.50	31.03	7.01	34.03	44.51	74.00	-29.49	Peak
7320.000	29.11	35.67	8.97	34.49	39.26	54.00	-14.74	Average
7320.000	39.26	35.67	8.97	34.49	49.41	74.00	-24.59	Peak
9760.000	29.98	38.51	11.16	34.20	45.45	54.00	-8.55	Average
9760.000	39.41	38.51	11.16	34.20	54.88	74.00	-19.12	Peak
2440.000	95.17	27.67	4.18	36.00	91.02	74.00	17.02	Peak

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
4880.000	30.36	31.03	7.01	34.03	34.37	54.00	-19.63	Average
4880.000	40.19	31.03	7.01	34.03	44.20	74.00	-29.80	Peak
7320.000	29.01	35.67	8.97	34.49	39.16	54.00	-14.84	Average
7320.000	38.75	35.67	8.97	34.49	48.90	74.00	-25.10	Peak
9760.000	29.86	38.51	11.16	34.20	45.33	54.00	-8.67	Average
9760.000	39.69	38.51	11.16	34.20	55.16	74.00	-18.84	Peak
2440.000	95.44	27.67	4.18	36.00	91.29	74.00	17.29	Peak

REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Emission level – Limit value.
2. 2440MHz: Fundamental frequency.



**BUREAU
VERITAS**

Test Report No.: W7L-P21100018-2RF02

CHANNEL	TX Channel 39	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2480.498	93.03	27.76	4.19	36.10	88.88	74.00	14.88	Peak
2483.500	52.45	27.76	4.19	36.11	48.29	74.00	-25.71	Peak
2483.732	54.98	27.76	4.19	36.11	50.82	74.00	-23.18	Peak
2500.000	43.12	27.80	4.19	36.15	38.96	74.00	-35.04	Peak
2479.970	90.91	27.76	4.19	36.10	86.76	54.00	32.76	Average
2483.500	32.02	27.76	4.19	36.11	27.86	54.00	-26.14	Average
2500.000	29.89	27.80	4.19	36.15	25.73	54.00	-28.27	Average

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2480.465	91.38	27.76	4.19	36.10	87.23	74.00	13.23	Peak
2483.500	54.10	27.76	4.19	36.11	49.94	74.00	-24.06	Peak
2483.600	56.50	27.76	4.19	36.11	52.34	74.00	-21.66	Peak
2500.000	42.92	27.80	4.19	36.15	38.76	74.00	-35.24	Peak
2480.003	89.27	27.76	4.19	36.10	85.12	54.00	31.12	Average
2483.500	31.20	27.76	4.19	36.11	27.04	54.00	-26.96	Average
2500.000	30.12	27.80	4.19	36.15	25.96	54.00	-28.04	Average

REMARKS:

- Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Emission level – Limit value.
- 2480MHz: Fundamental frequency.



**BUREAU
VERITAS**

Test Report No.: W7L-P21100018-2RF02

BT-LE _S2

CHANNEL	TX Channel 0	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2310.000	42.21	27.38	4.08	35.68	37.99	74.00	-36.01	Peak
2322.050	46.32	27.41	4.09	35.71	42.11	74.00	-31.89	Peak
2390.000	43.22	27.56	4.16	35.88	39.06	74.00	-34.94	Peak
2402.270	95.65	27.58	4.17	35.91	91.49	74.00	17.49	Peak
2310.000	29.94	27.38	4.08	35.68	25.72	54.00	-28.28	Average
2390.000	30.39	27.56	4.16	35.88	26.23	54.00	-27.77	Average
2402.060	95.46	27.58	4.17	35.91	91.30	54.00	37.30	Average

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2310.000	42.39	27.38	4.08	35.68	38.17	74.00	-35.83	Peak
2385.260	44.42	27.55	4.16	35.86	40.27	74.00	-33.73	Peak
2390.000	42.59	27.56	4.16	35.88	38.43	74.00	-35.57	Peak
2402.270	95.08	27.58	4.17	35.91	90.92	74.00	16.92	Peak
2310.000	29.91	27.38	4.08	35.68	25.69	54.00	-28.31	Average
2390.000	30.39	27.56	4.16	35.88	26.23	54.00	-27.77	Average
2402.060	94.55	27.58	4.17	35.91	90.39	54.00	36.39	Average

REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Emission level – Limit value.
2. 2402MHz: Fundamental frequency.



**BUREAU
VERITAS**

Test Report No.: W7L-P21100018-2RF02

CHANNEL	TX Channel 19	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
4880.000	31.69	31.03	7.01	34.03	35.70	54.00	-18.30	Average
4880.000	41.50	31.03	7.01	34.03	45.51	74.00	-28.49	Peak
7320.000	28.11	35.67	8.97	34.49	38.26	54.00	-15.74	Average
7320.000	38.26	35.67	8.97	34.49	48.41	74.00	-25.59	Peak
9760.000	30.98	38.51	11.16	34.20	46.45	54.00	-7.55	Average
9760.000	38.41	38.51	11.16	34.20	53.88	74.00	-20.12	Peak
2440.000	94.52	27.67	4.18	36.00	90.37	74.00	16.37	Peak

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
4880.000	31.36	31.03	7.01	34.03	35.37	54.00	-18.63	Average
4880.000	41.19	31.03	7.01	34.03	45.20	74.00	-28.80	Peak
7320.000	30.01	35.67	8.97	34.49	40.16	54.00	-13.84	Average
7320.000	37.75	35.67	8.97	34.49	47.90	74.00	-26.10	Peak
9760.000	28.86	38.51	11.16	34.20	44.33	54.00	-9.67	Average
9760.000	38.69	38.51	11.16	34.20	54.16	74.00	-19.84	Peak
2440.000	92.55	27.67	4.18	36.00	88.40	74.00	14.40	Peak

REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Emission level – Limit value.
2. 2440MHz: Fundamental frequency.



**BUREAU
VERITAS**

Test Report No.: W7L-P21100018-2RF02

CHANNEL	TX Channel 39	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2479.739	90.80	27.76	4.19	36.10	86.65	74.00	12.65	Peak
2483.500	43.28	27.76	4.19	36.11	39.12	74.00	-34.88	Peak
2487.758	43.89	27.77	4.19	36.12	39.73	74.00	-34.27	Peak
2500.000	41.62	27.80	4.19	36.15	37.46	74.00	-36.54	Peak
2480.003	91.21	27.76	4.19	36.10	87.06	54.00	33.06	Average
2483.500	30.97	27.76	4.19	36.11	26.81	54.00	-27.19	Average
2500.000	29.91	27.80	4.19	36.15	25.75	54.00	-28.25	Average

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2480.267	90.06	27.76	4.19	36.10	85.91	74.00	11.91	Peak
2483.500	42.64	27.76	4.19	36.11	38.48	74.00	-35.52	Peak
2485.514	44.14	27.77	4.19	36.11	39.99	74.00	-34.01	Peak
2500.000	42.50	27.80	4.19	36.15	38.34	74.00	-35.66	Peak
2480.003	89.37	27.76	4.19	36.10	85.22	54.00	31.22	Average
2483.500	30.69	27.76	4.19	36.11	26.53	54.00	-27.47	Average
2500.000	29.99	27.80	4.19	36.15	25.83	54.00	-28.17	Average

REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Emission level – Limit value.
2. 2480MHz: Fundamental frequency.



**BUREAU
VERITAS**

Test Report No.: W7L-P21100018-2RF02

BT-LE _S8

CHANNEL	TX Channel 0	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2310.000	42.21	27.38	4.08	35.68	37.99	74.00	-36.01	Peak
2382.530	44.94	27.54	4.15	35.86	40.77	74.00	-33.23	Peak
2390.000	43.02	27.56	4.16	35.88	38.86	74.00	-35.14	Peak
2402.270	95.98	27.58	4.17	35.91	91.82	74.00	17.82	Peak
2310.000	29.46	27.38	4.08	35.68	25.24	54.00	-28.76	Average
2390.000	29.85	27.56	4.16	35.88	25.69	54.00	-28.31	Average
2402.060	92.76	27.58	4.17	35.91	88.60	54.00	34.60	Average

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2310.000	42.31	27.38	4.08	35.68	38.09	74.00	-35.91	Peak
2356.385	44.26	27.48	4.13	35.79	40.08	74.00	-33.92	Peak
2390.000	42.35	27.56	4.16	35.88	38.19	74.00	-35.81	Peak
2402.270	94.22	27.58	4.17	35.91	90.06	74.00	16.06	Peak
2310.000	29.43	27.38	4.08	35.68	25.21	54.00	-28.79	Average
2390.000	29.82	27.56	4.16	35.88	25.66	54.00	-28.34	Average
2402.060	90.72	27.58	4.17	35.91	86.56	54.00	32.56	Average

REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Emission level – Limit value.
2. 2402MHz: Fundamental frequency.



**BUREAU
VERITAS**

Test Report No.: W7L-P21100018-2RF02

CHANNEL	TX Channel 19	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
4880.000	31.94	31.03	7.01	34.03	35.95	54.00	-18.05	Average
4880.000	41.99	31.03	7.01	34.03	46.00	74.00	-28.00	Peak
7320.000	29.43	35.67	8.97	34.49	39.58	54.00	-14.42	Average
7320.000	39.57	35.67	8.97	34.49	49.72	74.00	-24.28	Peak
9760.000	27.87	38.51	11.16	34.20	43.34	54.00	-10.66	Average
9760.000	38.12	38.51	11.16	34.20	53.59	74.00	-20.41	Peak
2440.000	94.95	27.67	4.18	36.00	90.80	74.00	16.80	Peak

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
4880.000	31.96	31.03	7.01	34.03	35.97	54.00	-18.03	Average
4880.000	42.50	31.03	7.01	34.03	46.51	74.00	-27.49	Peak
7320.000	29.29	35.67	8.97	34.49	39.44	54.00	-14.56	Average
7320.000	39.66	35.67	8.97	34.49	49.81	74.00	-24.19	Peak
9760.000	27.36	38.51	11.16	34.20	42.83	54.00	-11.17	Average
9760.000	38.16	38.51	11.16	34.20	53.63	74.00	-20.37	Peak
2440.000	92.03	27.67	4.18	36.00	87.88	74.00	13.88	Peak

REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Emission level – Limit value.
2. 2440MHz: Fundamental frequency.



**BUREAU
VERITAS**

Test Report No.: W7L-P21100018-2RF02

CHANNEL	TX Channel 39	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2480.234	91.20	27.76	4.19	36.10	87.05	74.00	13.05	Peak
2483.500	43.09	27.76	4.19	36.11	38.93	74.00	-35.07	Peak
2485.679	44.06	27.77	4.19	36.11	39.91	74.00	-34.09	Peak
2500.000	41.04	27.80	4.19	36.15	36.88	74.00	-37.12	Peak
2480.003	89.64	27.76	4.19	36.10	85.49	54.00	31.49	Average
2483.500	30.55	27.76	4.19	36.11	26.39	54.00	-27.61	Average
2500.000	29.26	27.80	4.19	36.15	25.10	54.00	-28.90	Average

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2480.234	91.95	27.76	4.19	36.10	87.80	74.00	13.80	Peak
2483.500	43.02	27.76	4.19	36.11	38.86	74.00	-35.14	Peak
2484.161	44.07	27.77	4.19	36.11	39.92	74.00	-34.08	Peak
2500.001	41.16	27.80	4.20	36.15	37.01	74.00	-36.99	Peak
2480.003	89.86	27.76	4.19	36.10	85.71	54.00	31.71	Average
2483.500	30.55	27.76	4.19	36.11	26.39	54.00	-27.61	Average
2500.000	29.22	27.80	4.19	36.15	25.06	54.00	-28.94	Average

REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Emission level – Limit value.
2. 2480MHz: Fundamental frequency.



3.3 6 dB BANDWIDTH MEASUREMENT

3.3.1 LIMITS OF 6dB BANDWIDTH MEASUREMENT

The minimum of 6dB Bandwidth Measurement is 0.5 MHz.

3.3.2 TEST INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
Power Meter	ANRITSU	ML2495A	1506002	Feb. 25,21	Feb. 24,22
EXA Signal Analyzer	KEYSIGHT	N9010A-526	MY54510322	Feb. 25,21	Feb. 24,22
EXA Signal Analyzer	KEYSIGHT	N9010A-544	MY54510355	Apr. 26,21	Apr. 25,22
Power Sensor	ANRITSU	MA2411B	1339352	Feb. 25,21	Feb. 24,22

NOTE:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.
2. The test was performed in RF Oven room.

3.3.3 TEST PROCEDURE


1. Set RBW = 100 kHz.
2. Set the video bandwidth (VBW) ≥ 3 RBW.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.



3.3.4 DEVIATION FROM TEST STANDARD

No deviation.

3.3.5 TEST SETUP



3.3.6 EUT OPERATING CONDITIONS

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.



Test Report No.: W7L-P21100018-2RF02

3.3.7 TEST RESULTS

Please Refer to Appendix1/2 Of this test report.




3.4 CONDUCTED OUTPUT POWER

3.4.1 LIMITS OF CONDUCTED OUTPUT POWER MEASUREMENT


For systems using digital modulation in the 2400–2483.5 MHz band: 1 Watt (30dBm)

3.4.2 TEST SETUP

BT:



2.4G wifi:



3.4.3 TEST INSTRUMENTS

Refer to section 3.2.2 to get information of above instrument.

3.4.4 TEST PROCEDURES

A peak power sensor was used on the output port of the EUT. A power meter was used to read the response of the peak power sensor. Record the power level.

3.4.5 DEVIATION FROM TEST STANDARD

No deviation.

3.4.6 EUT OPERATING CONDITIONS

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.



Test Report No.: W7L-P21100018-2RF02

3.4.7 TEST RESULTS

3.4.7.1 MAXIMUM PEAK OUTPUT POWER

Please Refer to Appendix1/2 Of this test report.



Test Report No.: W7L-P21100018-2RF02

3.4.7.2 AVERAGE OUTPUT POWER (FOR REFERENCE)

The average power sensor was used on the output port of the EUT. A power meter was used to read the response of the power sensor. Record the power level.

Please Refer to Appendix1/2 Of this test report.



3.5 POWER SPECTRAL DENSITY MEASUREMENT

3.5.1 LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT

The Maximum of Power Spectral Density Measurement is 8dBm/3KHz.

3.5.2 TEST SETUP



3.5.3 TEST INSTRUMENTS

Refer to section 3.3.2 to get information of above instrument.

3.5.4 TEST PROCEDURE

1. Set the span to 1.5 times the DTS bandwidth
2. Set the RBW = 3 kHz, VBW $\geq 3 \times$ RBW, Detector = peak.
3. Sweep time = auto couple, Trace mode = max hold, allow trace to fully stabilize.
4. Use the peak marker function to determine the maximum amplitude level.

3.5.5 DEVIATION FROM TEST STANDARD

No deviation.

3.5.6 EUT OPERATING CONDITION

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.



Test Report No.: W7L-P21100018-2RF02

3.5.7 TEST RESULTS

Please Refer to Appendix1/2 Of this test report.




3.6 OUT OF BAND EMISSION MEASUREMENT

3.6.1 LIMITS OF OUT OF BAND EMISSION MEASUREMENT

Below -20dB of the highest emission level of operating band (in 100kHz Resolution Bandwidth).

3.6.2 TEST SETUP



3.6.3 TEST INSTRUMENTS

Refer to section 3.3.2 to get information of above instrument.

3.6.4 TEST PROCEDURE

MEASUREMENT PROCEDURE REF

1. Set the RBW = 100 kHz.
2. Set the VBW $\geq$ 300 kHz.
3. Detector = peak.
4. Sweep time = auto couple.
5. Trace mode = max hold.
6. Allow trace to fully stabilize.
7. Use the peak marker function to determine the maximum power level in any 100 kHz band segment within the fundamental EBW.



MEASUREMENT PROCEDURE OOBE

1. Set RBW = 100 kHz.
2. Set VBW $\geq$ 300 kHz.
3. Set span to encompass the spectrum to be examined
4. Detector = peak.
5. Trace Mode = max hold.
6. Sweep = auto couple.

3.6.5 DEVIATION FROM TEST STANDARD

No deviation.

3.6.6 EUT OPERATING CONDITION

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

3.6.7 TEST RESULTS

The spectrum plots are attached on the following images. D1 line indicates the highest level. D2 line indicates the 20dB offset below D1. It shows compliance to the requirement.

Please Refer to Appendix 1/2 Of this test report.



Test Report No.: W7L-P21100018-2RF02

4 PHOTOGRAPHS OF THE TEST CONFIGURATION

Please refer to the attached file (Test Setup Photo).



Test Report No.: W7L-P21100018-2RF02

5 MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No any modifications are made to the EUT by the lab during the test.



BUREAU VERITAS Test Report No.: W7L-P21100018-2RF02

6 Appendix 1 BLE DTS BANDWIDTH

TEST RESULT

TestMode	Antenna	Channel	DTS BW [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
BLE_125K	Ant1	2402	0.628	2401.692	2402.320	0.5	PASS
		2440	0.612	2439.700	2440.312	0.5	PASS
		2480	0.684	2479.664	2480.348	0.5	PASS
BLE_1M	Ant1	2402	0.668	2401.668	2402.336	0.5	PASS
		2440	0.672	2439.672	2440.344	0.5	PASS
		2480	0.652	2479.684	2480.336	0.5	PASS
BLE_2M	Ant1	2402	1.144	2401.432	2402.576	0.5	PASS
		2440	1.172	2439.420	2440.592	0.5	PASS
		2480	1.236	2479.356	2480.592	0.5	PASS
BLE_500K	Ant1	2402	0.672	2401.676	2402.348	0.5	PASS
		2440	0.656	2439.684	2440.340	0.5	PASS
		2480	0.660	2479.684	2480.344	0.5	PASS




BUREAU
VERITAS


Test Report No.: W7L-P21100018-2RF02

TEST GRAPHS

BLE_125K_Ant1_2402



BLE_125K_Ant1_2440




BLE_125K_Ant1_2480



BUREAU
VERITAS

Test Report No.: W7L-P21100018-2RF02



BLE_1M_Ant1_2402



BLE_1M_Ant1_2440





BUREAU
VERITAS

Test Report No.: W7L-P21100018-2RF02



BLE_2M_Ant1_2440



BLE_2M_Ant1_2480




BUREAU
VERITAS


Test Report No.: W7L-P21100018-2RF02




BLE_500K_Ant1_2402



BLE_500K_Ant1_2440



BLE_500K_Ant1_2480





OCCUPIED CHANNEL BANDWIDTH

TEST RESULT

TestMode	Antenna	Channel	OCB [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
BLE_125K	Ant1	2402	1.0533	2401.477	2402.531	---	PASS
		2440	1.0570	2439.479	2440.536	---	PASS
		2480	1.0559	2479.477	2480.533	---	PASS
BLE_1M	Ant1	2402	1.0137	2401.502	2402.516	---	PASS
		2440	1.0187	2439.501	2440.519	---	PASS
		2480	1.0153	2479.500	2480.515	---	PASS
BLE_2M	Ant1	2402	2.0492	2401.001	2403.050	---	PASS
		2440	2.0543	2439.001	2441.055	---	PASS
		2480	2.0411	2478.993	2481.034	---	PASS
BLE_500K	Ant1	2402	1.0038	2401.497	2402.501	---	PASS
		2440	1.0165	2439.502	2440.518	---	PASS
		2480	1.0115	2479.501	2480.512	---	PASS



BUREAU
VERITAS

Test Report No.: W7L-P21100018-2RF02

TEST GRAPHS

BLE_125K_Ant1_2402



BLE_125K_Ant1_2440



BLE_125K_Ant1_2480



BUREAU
VERITAS

Test Report No.: W7L-P21100018-2RF02



BLE_1M_Ant1_2402



BLE_1M_Ant1_2440



BUREAU
VERITAS

Test Report No.: W7L-P21100018-2RF02



BLE_1M_Ant1_2480



BLE_2M_Ant1_2402



BUREAU
VERITAS

Test Report No.: W7L-P21100018-2RF02



BLE_2M_Ant1_2440



BLE_2M_Ant1_2480