
Q8说明书,正面两页,背面两页

USER MANUAL MAGNETIC WIRELESS CHARGER

Product Function Introduction



Matters Needing Attention

- Do not place the product in water or near the fire source, so as not to cause malfunction of the charging equipment and mobile phone.
- Do not drop the device from a high place to avoid damage to the device due to falling to the ground.
- 3 . If you need to clean the charger, make sure it is not connected to the power supply.
- 4 . Recommended to use QC3.0/PD power adapter to power the product.

Specification

Input voltage: 9V/3A

Phone output: 15W/10W/ 7.5W/ 5W

Frequency: 115-205KHz (5W,7.5W,10W,15W EPP) 360KHz(15W MPP)

Receiving distance : 0-4mm Conversion rate : ≥80%

Package Include

Magnetic Wireless charger x1
Type-C quick charge cable x1
User manual x1

LED Indicator Status Description

- Connected to power supply: blue light flashes 3 times and turns off after 30s
- 2. Standby : light off
- 3. Quick charging: blue light stays on for 60 seconds and then turns off
- 4. Charging exception alert : blue light keeps flashing.

Precautions

- Please use a qualified PD protocol or QC protocol power charger, otherwise it may cause unstable charging or abnormal flicker;
- If you need to use a protective case for your iPhone 12/13/14/15/16 during the charging, please use one with Mag safe;
- Do not use a mobile phone protective shell with metal back or a mobile phone protective shell with a thickness greater than 4mm;
- The receiving coil of a mobile phone that supports wireless charging is generally located at the center of the mobile phone.

Please place the center of the mobile phone at the center of the charging board to get a better charging experience;

- Do not put metal debris or magnetic cards on the charging board, which may cause metal hair, magnetic card damage, charger damage or other abnormalities;
- If the receiving coil or the transmitting board is overheated and the charging stops during the use, please remove the charging device, wait for it to cool down, and try charging again.
- Do not pull the power cord violently to avoid the power cord from breaking or falling off.
- Please do not disassemble the product or put it into fire or water to avoid short circuits and leakage.
- The standard temperature of wireless charger QI is 130°F, but our product temperature is controlled within 130°F. The charger will cut off the current when it is abnormally hot. Please contact us if any damage occurs.

FCC STATEMENT:

This device complies with Part 15 of the FCC Rules. Operation i s subject to the following two conditions:

- (1) This device may not cause harmful interference, and
- (2) This device must accept any i nterference received, includin g interference that may cause undesired operation.

Warning: Changes or modifications not exp ressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

NOTE: This equipment has been te sted and found to comply with the limits for a Class B digital device, pursuant to Par t 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates uses and

can radiate r adio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which c an be determined by by turning the equipment off and on, theuser is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving an tenna.
- Increase the separation bet ween the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

FCC Radiation Exposure Statement:

This equipment complies with FCC radiation exposure limits set forth for an uncontrolled environment. This equipment should be installed and operated with minimum distance 20cm between the radiator & your body.

