



FCC RADIO EXPOSURE TEST REPORT

FCC ID : Z8H89FT0016

Equipment : 5GHz Force 300-16

Brand Name : Cambium Networks

Model Name : 5GHz Force 300-16

Applicant : Cambium Networks Inc.
3800 Golf Road, Suite 360 Rolling Meadows, IL
60008, USA


Manufacturer : Cambium Networks Inc.
3800 Golf Road, Suite 360 Rolling Meadows, IL
60008, USA

Standard : 47 CFR Part 2.1091

The product was received on Mar. 15, 2018, and testing was started from Mar. 15, 2018 and completed on May 08, 2019. We, SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, would like to declare that the tested sample has been evaluated in accordance with the procedures given in 47 CFR Part 2.1091 and shown compliance with the applicable technical standards.

The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any agency of government.

The test results in this variant report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, the test report shall not be reproduced except in full.



Approved by: Sam Chen

SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory
No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.)



Table of Contents

History of this test report.....	3
Summary of Test Result.....	4
1 General Description	5
1.1 EUT General Information	5
1.2 Table for Class III Change.....	5
1.3 Testing Location	5
2 Maximum Permissible Exposure	6
2.1 Limit of Maximum Permissible Exposure	6
2.2 MPE Calculation Method.....	6
2.3 MPE Measurement Method.....	7
2.4 Measurement Result and Limit.....	8
2.5 List of Measuring Equipments	13
2.6 Calculated Result and Limit.....	14
Appendix A. Test Photos	
Photographs of EUT v01	



Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
2	-	Exposure evaluation	PASS	-

Note: From Sporton Project No.: 7O2407-03

Declaration of Conformity:

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

Comments and Explanations:

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

Reviewed by: Sam Chen

Report Producer: Viola Huang



1 General Description

1.1 EUT General Information

RF General Information			
Evaluation Mode	Frequency Range (MHz)	Operating Frequency (MHz)	Modulation Type
2.4GHz WLAN	2400-2483.5	2412-2462	802.11ac: OFDM (BPSK, QPSK, 16QAM, 64QAM, 256QAM)
5GHz WLAN	5150-5250 5250-5350 5470-5725 5725-5850	5180-5240 5260-5320 5500-5720 5745-5825	802.11ac: OFDM (BPSK, QPSK, 16QAM, 64QAM, 256QAM)

1.2 Table for Class III Change

This product is an extension of original one reported under Sporton project number: FA7O2407-04

Below is the table for the change of the product with respect to the original one.

Modifications	Performance Checking
1. Adding Band 2 and Band 3 (5250~5350 MHz, 5470~5725 MHz) in 20/80MHz.	Maximum Permissible Exposure

Note: RF Exposure Evaluation of 5GHz Band 1, 4 and 2.4GHz Band are based on original test report.

1.3 Testing Location

Testing Location		
☐	HWA YA	ADD : No. 52, Hwa Ya 1st Rd., Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C. TEL : 886-3-327-3456 FAX : 886-3-327-0973
☒	JHUBEI	ADD : No.8, Lane 724, Bo-ai St., Jhubei City, HsinChu County 302, Taiwan, R.O.C. TEL : 886-3-656-9065 FAX : 886-3-656-9085

Test site Designation No. TW0006 with FCC.

Test site registered number IC 4086B with Industry Canada.



2 Maximum Permissible Exposure

2.1 Limit of Maximum Permissible Exposure

(A) Limits for Occupational / Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842 / f	4.89 / f	(900 / f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-100,000			5	6

(B) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-100,000			1.0	30

Note: f = frequency in MHz ; *Plane-wave equivalent power density

2.2 MPE Calculation Method

The MPE was calculated at 73 cm to show compliance with the power density limit.

The following formula was used to calculate the Power Density:

$$E \text{ (V/m)} = \frac{\sqrt{30 \times P \times G}}{d} \quad \text{Power Density: } Pd \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

E = Electric field (V/m)

P = RF output power (W)


G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 \times P \times G}{377 \times d^2}$$

2.3 MPE Measurement Method



Horizontal Plane

1. Align Probe with antenna axis. Probe should same height as Antenna axis.
And take power density measurement with Probe.
 2. Rotate table 45 degree (30 degree if MPE distance is more 60cm).
Take power density measurement again.
 3. Repeat step 2, until complete 360 degree.
- Each measured power density should be less than MPE limit.

Vertical Plane

1. Align Probe with antenna axis. Move probe to height of 10cm above ground plane.
Take power density measurement.
Then repeat measure with 10cm increment of probe height until 180 cm.
2. Rotate table 45 degree (30 degree if MPE distance is more 60cm).
Repeat the power density measure from 10cm to 180cm
3. Repeat step 2, until complete 360 degree.

Spatial Average of same vertical plane should be less then MPE limit.

For Probe or measurement equipment requirement, please see FCC OET Bulletin 65 97-01

Note:

Either peak or spatially averaged results may be applied to determine compliance; and with respect to plane-wave equivalent power density limits when ≥ 300 MHz, and electric and magnetic field strength limits when < 300 MHz.



2.4 Measurement Result and Limit

For 5.8G;D1D (Ant.2)

Test Mode	VHT20	Test Frequency (MHz)	5745	MPE Distance (cm)	73	Power Setting	29	
EUT Plane	Horizontal							
Probe height (cm) \ Deg	0~45°	45~90°	90~135°	135~180°	180~225°	225~270°	270~315°	315~360°
	Max PSD (mW/cm²)	Max PSD (mW/cm²)	Max PSD (mW/cm²)	Max PSD (mW/cm²)	Max PSD (mW/cm²)	Max PSD (mW/cm²)	Max PSD (mW/cm²)	Max PSD (mW/cm²)
187	0.87485	0.03444	0.00453	0.00109	0.00155	0.00464	0.02667	0.86476
Max PSD (mW/cm²)	0.87485							
MPE Limit (mW/cm²)	1							
EUT Plane	Vertical							
Probe height (cm) \ Deg	0~45°	45~90°	90~135°	135~180°	180~225°	225~270°	270~315°	315~360°
	Max PSD (mW/cm²)	Max PSD (mW/cm²)	Max PSD (mW/cm²)	Max PSD (mW/cm²)	Max PSD (mW/cm²)	Max PSD (mW/cm²)	Max PSD (mW/cm²)	Max PSD (mW/cm²)
10	0.00462	0.00561	0.00075	0.00194	0.00286	0.00127	0.00161	0.04389
20	0.04849	0.00641	0.00095	0.00199	0.00171	0.00076	0.00214	0.04744
30	0.00984	0.00564	0.00113	0.00231	0.00231	0.00142	0.00286	0.01051
40	0.03951	0.00369	0.00136	0.00226	0.00194	0.00105	0.00198	0.03902
50	0.08636	0.00491	0.03410	0.00124	0.00132	0.00331	0.00493	0.06441
60	0.55698	0.00569	0.00495	0.00146	0.00145	0.00712	0.00948	0.46701
70	0.80726	0.01024	0.00791	0.00144	0.00109	0.00477	0.01542	0.68751
80	0.81898	0.01114	0.00768	0.00145	0.00128	0.00671	0.01643	0.77271
90	0.42573	0.00645	0.00338	0.00171	0.00131	0.00392	0.01044	0.34165
100	0.14579	0.00382	0.00381	0.00131	0.00128	0.00231	0.00475	0.12984
110	0.01840	0.00184	0.00205	0.00137	0.00139	0.00902	0.00255	0.01849
120	0.00252	0.00201	0.00072	0.00185	0.00211	0.00055	0.00117	0.00288
130	0.00379	0.00165	0.00067	0.00195	0.00206	0.00039	0.00108	0.00261
140	0.01388	0.00237	0.00084	0.00138	0.00135	0.00044	0.00107	0.01269
150	0.01403	0.00214	0.00072	0.00141	0.00143	0.00054	0.00081	0.01434
160	0.02043	0.00210	0.00210	0.00097	0.00082	0.00056	0.00110	0.01936
170	0.01349	0.00169	0.00059	0.00087	0.00081	0.00076	0.00910	0.01304
180	0.01434	0.00099	0.00099	0.00084	0.00065	0.00500	0.00096	0.01296
Spatial Average (mW/cm²)	0.169135556	0.004355	0.00415	0.001541667	0.001509444	0.002772222	0.004882222	0.15002
Max Spatial Average (mW/cm²)	0.16914							
MPE Limit (mW/cm²)	1							



Test Mode	VHT20	Test Frequency (MHz)	5785	MPE Distance (cm)	73	Power Setting	29	
EUT Plane	Horizontal							
Probe height (cm) \ Deg	0~45°	45~90°	90~135°	135~180°	180~225°	225~270°	270~315°	315~360°
	Max PSD (mW/cm²)	Max PSD (mW/cm²)	Max PSD (mW/cm²)	Max PSD (mW/cm²)	Max PSD (mW/cm²)	Max PSD (mW/cm²)	Max PSD (mW/cm²)	Max PSD (mW/cm²)
186	0.96695	0.02464	0.00351	0.00122	0.00109	0.00567	0.02826	0.96629
Max PSD (mW/cm²)	0.96695							
MPE Limit (mW/cm²)	1							
EUT Plane	Vertical							
Probe height (cm) \ Deg	0~45°	45~90°	90~135°	135~180°	180~225°	225~270°	270~315°	315~360°
	Max PSD (mW/cm²)	Max PSD (mW/cm²)	Max PSD (mW/cm²)	Max PSD (mW/cm²)	Max PSD (mW/cm²)	Max PSD (mW/cm²)	Max PSD (mW/cm²)	Max PSD (mW/cm²)
10	0.01918	0.00436	0.00059	0.00201	0.00259	0.00169	0.00288	0.02113
20	0.02509	0.00959	0.00092	0.00248	0.00258	0.00134	0.00367	0.02594
30	0.01262	0.00751	0.00106	0.00186	0.00118	0.00177	0.00425	0.01314
40	0.08391	0.00291	0.00171	0.00302	0.00302	0.0013	0.00232	0.07663
50	0.10151	0.00496	0.00412	0.00164	0.00174	0.00655	0.00744	0.10589
60	0.59442	0.00754	0.00559	0.0016	0.00141	0.00747	0.01207	0.6531
70	0.89654	0.01504	0.01038	0.00184	0.00858	0.00858	0.01981	0.86047
80	0.8244	0.01514	0.01021	0.0018	0.00186	0.00742	0.01963	0.80262
90	0.36411	0.00587	0.00375	0.00171	0.00128	0.00167	0.01191	0.35489
100	0.18441	0.00561	0.00572	0.00147	0.00102	0.00278	0.00762	0.1249
110	0.02404	0.00235	0.00215	0.00134	0.00139	0.00143	0.00294	0.02431
120	0.00234	0.00192	0.00101	0.00193	0.00183	0.00053	0.00101	0.00319
130	0.00426	0.00196	0.00068	0.00252	0.00249	0.00247	0.00138	0.00442
140	0.02107	0.00268	0.00054	0.00162	0.00084	0.0042	0.00134	0.02012
150	0.02078	0.00124	0.00131	0.00169	0.00168	0.00063	0.00115	0.02084
160	0.02649	0.00303	0.00067	0.00129	0.00137	0.00082	0.00319	0.002701
170	0.01441	0.00241	0.00046	0.00059	0.00063	0.00052	0.00239	0.01537
180	0.01658	0.00178	0.00107	0.00119	0.00072	0.00064	0.00141	0.01738
Spatial Average (mW/cm²)	0.179786667	0.005327778	0.002885556	0.001755556	0.002011667	0.002878333	0.005911667	0.1748355
Max Spatial Average (mW/cm²)	0.17979							
MPE Limit (mW/cm²)	1							



Test Mode	VHT20	Test Frequency (MHz)	5825	MPE Distance (cm)	73	Power Setting	29	
EUT Plane	Horizontal							
Probe height (cm) \ Deg	0~45°	45~90°	90~135°	135~180°	180~225°	225~270°	270~315°	315~360°
	Max PSD (mW/cm²)	Max PSD (mW/cm²)	Max PSD (mW/cm²)	Max PSD (mW/cm²)	Max PSD (mW/cm²)	Max PSD (mW/cm²)	Max PSD (mW/cm²)	Max PSD (mW/cm²)
186	0.79374	0.02509	0.00331	0.00067	0.00101	0.00406	0.02476	0.76046
Max PSD (mW/cm²)	0.79374							
MPE Limit (mW/cm²)	1							
EUT Plane	Vertical							
Probe height (cm) \ Deg	0~45°	45~90°	90~135°	135~180°	180~225°	225~270°	270~315°	315~360°
	Max PSD (mW/cm²)	Max PSD (mW/cm²)	Max PSD (mW/cm²)	Max PSD (mW/cm²)	Max PSD (mW/cm²)	Max PSD (mW/cm²)	Max PSD (mW/cm²)	Max PSD (mW/cm²)
10	0.03594	0.00856	0.00093	0.00244	0.00183	0.00178	0.00364	0.03681
20	0.01714	0.00181	0.00049	0.00225	0.00162	0.00132	0.00129	0.01809
30	0.01132	0.00341	0.00171	0.00209	0.00171	0.00221	0.00161	0.01033
40	0.00675	0.00258	0.00174	0.00127	0.00122	0.00217	0.00231	0.00907
50	0.12989	0.00393	0.00178	0.00282	0.00228	0.00339	0.00431	0.12068
60	0.16093	0.00674	0.00361	0.00144	0.00184	0.00561	0.01119	0.19636
70	0.41557	0.00804	0.00445	0.00159	0.00138	0.00486	0.01515	0.42427
80	0.53485	0.00799	0.00364	0.00199	0.00187	0.00461	0.01606	0.54852
90	0.44312	0.00873	0.00579	0.00129	0.00102	0.00423	0.01402	0.46448
100	0.19341	0.00389	0.00171	0.00099	0.00098	0.00168	0.00842	0.25251
110	0.10587	0.00212	0.00133	0.00124	0.00113	0.00218	0.00613	0.12041
120	0.02659	0.00192	0.00058	0.00132	0.00133	0.00094	0.00248	0.02966
130	0.00545	0.00195	0.00103	0.00138	0.00114	0.00048	0.00121	0.00505
140	0.01474	0.00191	0.00096	0.00102	0.00081	0.00058	0.00081	0.01448
150	0.01217	0.00172	0.00104	0.00258	0.00225	0.00049	0.00154	0.01102
160	0.01867	0.00161	0.00063	0.00076	0.00075	0.00064	0.00083	0.01868
170	0.01109	0.00251	0.00052	0.00093	0.00089	0.00066	0.00176	0.01178
180	0.02173	0.00173	0.00109	0.00076	0.00057	0.00063	0.00144	0.02016
Spatial Average (mW/cm²)	0.120290556	0.003952778	0.001834778	0.001564444	0.001367778	0.002136667	0.005233333	0.128464444
Max Spatial Average (mW/cm²)	0.12846							
MPE Limit (mW/cm²)	1							



Test Mode	VHT40	Test Frequency (MHz)	5755	MPE Distance (cm)	73	Power Setting	24	
EUT Plane	Horizontal							
Probe height (cm) \ Deg	0~45°	45~90°	90~135°	135~180°	180~225°	225~270°	270~315°	315~360°
	Max PSD (mW/cm²)	Max PSD (mW/cm²)	Max PSD (mW/cm²)	Max PSD (mW/cm²)	Max PSD (mW/cm²)	Max PSD (mW/cm²)	Max PSD (mW/cm²)	Max PSD (mW/cm²)
187	0.80923	0.02113	0.00329	0.00098	0.00073	0.00314	0.01972	0.78329
Max PSD (mW/cm²)	0.80923							
MPE Limit (mW/cm²)	1							
EUT Plane	Vertical							
Probe height (cm) \ Deg	0~45°	45~90°	90~135°	135~180°	180~225°	225~270°	270~315°	315~360°
	Max PSD (mW/cm²)	Max PSD (mW/cm²)	Max PSD (mW/cm²)	Max PSD (mW/cm²)	Max PSD (mW/cm²)	Max PSD (mW/cm²)	Max PSD (mW/cm²)	Max PSD (mW/cm²)
10	0.06044	0.00413	0.00074	0.00156	0.00165	0.00111	0.00281	0.06492
20	0.02249	0.00404	0.00103	0.00119	0.00064	0.00121	0.00213	0.02178
30	0.00793	0.00245	0.00076	0.00212	0.00129	0.00152	0.00158	0.00796
40	0.00525	0.00234	0.00231	0.00122	0.00079	0.00129	0.00192	0.00721
50	0.12521	0.00341	0.00172	0.00163	0.00094	0.00279	0.00344	0.11015
60	0.20234	0.00584	0.00404	0.00107	0.00111	0.00398	0.00771	0.17925
70	0.35205	0.00645	0.00342	0.00122	0.00107	0.00416	0.01075	0.31369
80	0.47344	0.00684	0.00469	0.00105	0.00098	0.00421	0.01073	0.47987
90	0.52326	0.00724	0.00452	0.00115	0.00086	0.00531	0.01125	0.58562
100	0.19991	0.00262	0.00132	0.00084	0.00088	0.00203	0.00701	0.17456
110	0.06172	0.00139	0.00077	0.00092	0.00092	0.00135	0.00341	0.06286
120	0.01491	0.00131	0.00061	0.00113	0.00106	0.00051	0.00169	0.01448
130	0.00369	0.00131	0.00051	0.00087	0.00088	0.00038	0.00094	0.00357
140	0.00231	0.00116	0.00045	0.00102	0.00116	0.00041	0.00081	0.00242
150	0.00991	0.00191	0.00046	0.00111	0.00074	0.00033	0.00101	0.00921
160	0.01219	0.00142	0.00058	0.00064	0.00052	0.00037	0.00065	0.01199
170	0.01575	0.00193	0.00038	0.00096	0.00067	0.00044	0.00102	0.01661
180	0.00922	0.00203	0.00042	0.00086	0.00083	0.00067	0.00103	0.00941
Spatial Average (mW/cm²)	0.116778889	0.003212222	0.001596111	0.001142222	0.000943889	0.001781667	0.003882778	0.115308889
Max Spatial Average (mW/cm²)	0.11678							
MPE Limit (mW/cm²)	1							



Test Mode	VHT40	Test Frequency (MHz)	5795	MPE Distance (cm)	73	Power Setting	24	
EUT Plane	Horizontal							
Probe height (cm) \ Deg	0~45°	45~90°	90~135°	135~180°	180~225°	225~270°	270~315°	315~360°
	Max PSD (mW/cm²)	Max PSD (mW/cm²)	Max PSD (mW/cm²)	Max PSD (mW/cm²)	Max PSD (mW/cm²)	Max PSD (mW/cm²)	Max PSD (mW/cm²)	Max PSD (mW/cm²)
187	0.87883	0.00201	0.00388	0.00098	0.00134	0.01034	0.02205	0.87351
Max PSD (mW/cm²)	0.87883							
MPE Limit (mW/cm²)	1							
EUT Plane	Vertical							
Probe height (cm) \ Deg	0~45°	45~90°	90~135°	135~180°	180~225°	225~270°	270~315°	315~360°
	Max PSD (mW/cm²)	Max PSD (mW/cm²)	Max PSD (mW/cm²)	Max PSD (mW/cm²)	Max PSD (mW/cm²)	Max PSD (mW/cm²)	Max PSD (mW/cm²)	Max PSD (mW/cm²)
10	0.02851	0.00539	0.00081	0.00206	0.00259	0.00128	0.00274	0.02881
20	0.01009	0.00531	0.00112	0.00121	0.00094	0.00147	0.00263	0.01011
30	0.02068	0.00262	0.00141	0.00285	0.00235	0.00129	0.00179	0.02049
40	0.01032	0.00252	0.00206	0.00132	0.00116	0.00145	0.00365	0.01068
50	0.18807	0.00413	0.00150	0.00171	0.00162	0.00311	0.00465	0.18804
60	0.35002	0.00841	0.00443	0.00136	0.00124	0.00597	0.01274	0.30097
70	0.49222	0.00703	0.00402	0.00169	0.00186	0.00554	0.01259	0.41012
80	0.54019	0.00816	0.00444	0.00149	0.00182	0.00426	0.01151	0.52173
90	0.43811	0.00789	0.00550	0.00091	0.00117	0.00636	0.01136	0.42542
100	0.13903	0.00236	0.00199	0.00095	0.00092	0.00226	0.00496	0.13399
110	0.03494	0.00151	0.00062	0.00091	0.00072	0.00142	0.00324	0.03531
120	0.00835	0.00152	0.00061	0.00124	0.00112	0.00065	0.00125	0.00834
130	0.00505	0.00145	0.00067	0.00107	0.00105	0.00037	0.00075	0.00476
140	0.00772	0.00148	0.00046	0.00097	0.00096	0.00042	0.00052	0.00745
150	0.01452	0.00248	0.00044	0.00129	0.00131	0.00039	0.00126	0.01206
160	0.01389	0.00215	0.00052	0.00057	0.00054	0.00051	0.00066	0.01396
170	0.01407	0.00208	0.00047	0.00132	0.00127	0.00049	0.00111	0.01301
180	0.01075	0.00222	0.00044	0.00064	0.00064	0.00057	0.00081	0.01023
Spatial Average (mW/cm²)	0.129251667	0.003817222	0.001750556	0.001308889	0.001293333	0.002100556	0.004345556	0.119748889
Max Spatial Average (mW/cm²)	0.12925							
MPE Limit (mW/cm²)	1							



2.5 List of Measuring Equipments

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Calibration Due Date	Remark
Isotropic Probe	ETS-LINDGREN	HI-6105	00130664	100kHz-6GHz	Nov. 15, 2017	Nov. 14, 2018	03CH01-CB

Note: Calibration Interval of instrument listed above is one year.

2.6 Calculated Result and Limit

Exposure Environment: General Population / Uncontrolled Exposure

For Ant. 1

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up EIRP (dBm)	Tune-up EIRP (W)	Distance (cm)	S (mW/cm ²)	S Limit (mW/cm ²)
2.4G;D1D	6.00	18.45	24.45	0.50	24.95	0.31261	73	0.00467	1.00000

For Ant. 2

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up EIRP (dBm)	Tune-up EIRP (W)	Distance (cm)	S (mW/cm ²)	S Limit (mW/cm ²)
5.2G;D1D	16.00	13.33	29.33	0.50	29.83	0.96161	73	0.01436	1.00000
5.3G;D1D	16.00	12.88	28.88	0.50	29.38	0.86696	73	0.01295	1.00000
5.6G;D1D	16.00	13.84	29.84	0.13	29.97	0.99312	73	0.01483	1.00000
5.8G;D1D	16.00	29.19	45.19	0.50	45.69	37.06807	73	0.96695	1.00000

For Ant. 3

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up EIRP (dBm)	Tune-up EIRP (W)	Distance (cm)	S (mW/cm ²)	S Limit (mW/cm ²)
5.2G;D1D	2.00	28.31	30.31	0.50	30.81	1.20504	73	0.01799	1.00000
5.3G;D1D	2.00	23.80	25.80	0.50	26.30	0.42658	73	0.00637	1.00000
5.6G;D1D	2.00	23.95	25.95	0.50	26.45	0.44157	73	0.00659	1.00000
5.8G;D1D	2.00	29.19	31.19	0.50	31.69	1.47571	73	0.02204	1.00000

Simultaneous Transmission Analysis Mode:

WLAN 2.4GHz + WLAN 5GHz_Ant. 2

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up EIRP (dBm)	Tune-up EIRP (W)	Distance (cm)	S (mW/cm ²)	S Limit (mW/cm ²)	Ratio (S/Limit)
2.4G;D1D	6.00	18.45	24.45	0.50	24.95	0.31261	73	0.00467	1.00000	0.00467
5.8G;D1D	16.00	29.19	45.19	0.50	45.69	37.06807	73	0.96695	1.00000	0.96695
									Sum Ratio	0.97164
									Ratio Limit	1.00000

WLAN 2.4GHz + WLAN 5GHz_Ant. 3

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up EIRP (dBm)	Tune-up EIRP (W)	Distance (cm)	S (mW/cm ²)	S Limit (mW/cm ²)	Ratio (S/Limit)
2.4G;D1D	6.00	18.45	24.45	0.50	24.95	0.31261	73	0.00467	1.00000	0.00467
5.8G;D1D	2.00	29.19	31.19	0.50	31.69	1.47571	73	0.02204	1.00000	0.02204
									Sum Ratio	0.02671
									Ratio Limit	1.00000