

TEST REPORT

Product Name : wireless charging
Model Number : WC010A-2UQxx-yy,
 WC010B-2UQxx-yy
FCC ID : 2BENG-WC010A

Prepared for : JIANGSU MULIN INTELLIGENCE ELECTRIC CO., LTD.
Address : No. 6, Xiajia Road, Henglin Town, Economic Development
Zone, Changzhou, Jiangsu, China

Prepared by : EMTEK (NINGBO) CO., LTD.
Address : No. 8, Building 8, Lane 216, Qingyi Road, Ningbo Hi-Tech
Zone, Ningbo, Zhejiang, China

Tel: +86-574-27907998
Fax: +86-574-27721538

Report Number : ENB2410210228W00103R
Date(s) of Tests : October 21, 2024 to November 09, 2024
Date of issue : November 11, 2024

Table of Contents

	Page
Test Report Description	Page
1 TEST RESULT CERTIFICATION	3
2 EUT TECHNICAL DESCRIPTION	5
3 SUMMARY OF TEST RESULT	6
4 TEST METHODOLOGY	7
4.1 GENERAL DESCRIPTION OF APPLIED STANDARDS.....	7
4.2 MEASUREMENT EQUIPMENT USED.....	7
4.3 DESCRIPTION OF TEST MODES	8
4.4 TEST SOFTWARE	8
5 FACILITIES AND ACCREDITATIONS	9
5.1 FACILITIES.....	9
5.2 LABORATORY ACCREDITATIONS AND LISTINGS	9
6 TEST SYSTEM UNCERTAINTY	10
7 SETUP OF EQUIPMENT UNDER TEST	11
7.1 RADIO FREQUENCY TEST SETUP 1	11
7.2 RADIO FREQUENCY TEST SETUP 2	11
7.3 CONDUCTED EMISSION TEST SETUP.....	12
7.4 SUPPORT EQUIPMENT	13
8 FREQUENCY HOPPING SYSTEM REQUIREMENTS	14
8.1 STANDARD APPLICABLE.....	14
8.2 EUT PSEUDORANDOM FREQUENCY HOPPING SEQUENCE	14
8.3 EQUAL HOPPING FREQUENCY USE.....	15
8.4 FREQUENCY HOPPING SYSTEM	15
9 TEST REQUIREMENTS	16
9.1 20DB BANDWIDTH.....	16
9.2 ARRIER FREQUENCY SEPARATION.....	22
9.3 UMBER OF HOPPING FREQUENCIES	28
9.4 AVERAGE TIME OF OCCUPANCY (DWELL TIME)	30
9.5 MAXIMUM PEAK CONDUCTED OUTPUT POWER.....	33
9.6 CONDUCTED SUPRIOS EMISSION.....	39
9.7 RADIATED SPURIOUS EMISSION	46
9.8 CONDUCTED EMISSION TEST	59
9.9 ANTENNA APPLICATION	62

1 TEST RESULT CERTIFICATION

Applicant : JIANGSU MULIN INTELLIGENCE ELECTRIC CO., LTD.
 Address : No. 6, Xiajia Road, Henglin Town, Economic Development Zone, Changzhou, Jiangsu, China
 Manufacturer : JIANGSU MULIN INTELLIGENCE ELECTRIC CO., LTD.
 Address : No. 6, Xiajia Road, Henglin Town, Economic Development Zone, Changzhou, Jiangsu, China
 EUT : wireless charging
 Model Name : WC010A-2UQxx-yy, WC010B-2UQxx-yy
 Trademark : N/A

Measurement Procedure Used:

APPLICABLE STANDARDS	
STANDARD	TEST RESULT
FCC 47 CFR Part 2, Subpart J	
FCC 47 CFR Part 15, Subpart C	PASS

The above equipment was tested by EMTEK (NINGBO) CO., LTD. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.10 (2013) and the energy emitted by the sample EUT tested as described in this report is in compliance with the requirements of FCC Rules Part 2 and Part 15.247

The test results of this report relate only to the tested sample identified in this report

Date of Test :

October 21, 2024 to November 09, 2024

Prepared by :

Neymar /Engineer

Reviewer :

June Gao /Superviso

Approve & Authorized Signer :

Tony wei/Manager

Modified Information

Version	Report No.	Revision Data	Summary
/	ENB2410210228W00103R	/	Original Report



2 EUT TECHNICAL DESCRIPTION

Characteristics	Description
Product Name	wireless charging
Model number	WC010A-2UQxx-yy, WC010B-2UQxx-yy Note: The difference between WC010A-2UQxx-yy and WC010B-2UQxx-yy is that WC010A-2UQxx-yy has a vibration board with 8 keys, WC010B-2UQxx-yy has 6 keys. "xx"=2 digits code indicates input voltage range from 12V-29V , "yy" =stands for serial number "01 -99"(only appearance is different). We chose WC010A-2UQ24-03 for RF test.
Sample number	ENB2410210228W001-1-1
Device Type	Bluetooth V5.3
Data Rate	1Mbps for GFSK modulation 2Mbps for pi/4-DQPSK modulation 3Mbps for 8DPSK modulation
Modulation	GFSK pi/4-DQPSK 8DPSK
Operating Frequency Range	2402-2480MHz
Number of Channels	79 channels
Max Transmit Power	3.0 dBm
Antenna Type	PCB Monopole Antenna
Gain	2.499 dBi
Power supply	DC 12-29V
Temperature Range	-30°C to +80°C
Date of Received	October 21, 2024

Note: for more details, please refer to the User's manual of the EUT.

3 SUMMARY OF TEST RESULT

FCC PartClause	Test Parameter	Verdict	Remark
15.247(a)(1)	20 dB Bandwidth	PASS	
15.247(a)(1)	Carrier Frequency Separation	PASS	
15.247(a)(1)	Number of Hopping Frequencies	PASS	
15.247(a)(1)	Average Time of Occupancy (Dwell Time)	PASS	
15.247(b)(1)	Maximum Peak Conducted Output Power	PASS	
15.247(c)	Conducted Spurious Emissions	PASS	
15.247(d) 15.209	Radiated Spurious Emissions	PASS	
15.207	Conducted Emission	PASS	
15.203	Antenna Application	PASS	
NOTE1:N/A (Not Applicable)			

RELATED SUBMITTAL(S) / GRANT(S):

This submittal(s) (test report) is intended for FCC ID: 2BENG-WC010A filing to comply with Section 15.247 of the FCC Part 15, Subpart C.

4 TEST METHODOLOGY

4.1 GENERAL DESCRIPTION OF APPLIED STANDARDS

According to its specifications, the EUT must comply with the requirements of the following standards:
 FCC 47 CFR Part 2, Subpart J
 FCC 47 CFR Part 15, Subpart C
 558074 D01 15.247 Meas Guidance V05r02

4.2 MEASUREMENT EQUIPMENT USED

4.2.1 Conducted Emission Test Equipment

Equ.No.	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
ENE-001	EMI Test Receiver	R & S	ESCI	101108	Dec 14, 2023	1 Year
ENE-335	L.I.S.N	Schwarzbeck	NSLK 8126	8126-05058	July 02 2024	1 Year
ENE-006	Pulse Limiter	MTS-systemtec hnik	IMP-136	2611115-001 -0033	July 02, 2024	1 Year
ENE-278	RF Switching Unit	HTEC	HRSU	222101	July 02 2024	1 Year
ENE-149	Conduction Test Room 1#	SKET	11.5*5*4m	/	Dec 17, 2023	3 Year

4.2.2 Radiated Emission Test Equipment

Equ. No.	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
ENE-185	EMI Test Receiver	R&S	ESR7	102480	Apr 25, 2024	1 Year
ENE-190	Antenna Multiple	Schwarzbeck	VULB 9163	01499	May 18, 2024	2 Year
ENE-195	Pre-Amplifier	JS Denki	PA09K03-40	JSPA21019	Apr 25, 2024	1 Year
ENE-204	Low Frequency Notch Filter RF Switching	JS Denki	JSDSW-F	JSDSW2211D 02	Apr 25, 2024	1 Year
ENE-251	6dB Attenuator	Mini-Circuits	UNAT-6+	11542	July 02, 2024	1 Year
ENE-144	3-Meter Anechoic Chamber2#	SKET	9*6*6m	/	June 19, 2022	3 Year

4.2.3 Radio Frequency Test Equipment

Equ. No.	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
ENE-256	EXA Signal Analyzer	Keysight	N9010B	MY62060219	July 02, 2024	1 Year
ENE-172	RF Control Unit	Tonscend	JS0806-2(V.6E)	21L8060521	February 27, 2024	1 Year
ENE-092	DC Power Supply	KEFUNA	KDP3603	2004D3062946	July 02, 2024	1 Year

4.3 DESCRIPTION OF TEST MODES

The EUT has been tested under its typical operating condition.

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

The Transmitter was operated in the normal operating mode. The TX frequency was fixed which was for the purpose of the measurements.

Test of channel included the lowest and middle and highest frequency to perform the test, then record on this report.

Those data rates (1Mbps for Bluetooth GFSK modulation; 2Mbps for Bluetooth pi/4-DQPSK modulation; 3Mbps for Bluetooth 8DPSK) were used for all test.

Pre-defined engineering program for regulatory testing used to control the EUT for staying in continuous transmitting and receiving mode is programmed.

Frequency and Channel list for Bluetooth V5.3

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	39	2441
1	2403	40	2442	76	2478
2	2404	41	2443	77	2479
...	78	2480

Note: $fc = 2402\text{MHz} + (k-1) \times 1\text{MHz}$ k=1 to 79

Test Frequency and Channel for Bluetooth V5.3

Lowest Frequency		Middle Frequency		Highest Frequency	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	39	2441	79	2480

4.4 TEST SOFTWARE

Item	Software
Radiated Emission:	JSDEMC-EMI(V 3.3)
Conducted Emission:	JSDEMC-EMI(V 3.3)

5 FACILITIES AND ACCREDITATIONS

5.1 FACILITIES

All measurement facilities used to collect the measurement data are located at

No. 8, Building 8, Lane 216, Qingyi Road, Ningbo Hi-Tech Zone, Ningbo, Zhejiang, China
The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.10 and CISPR Publication 32.

5.2 LABORATORY ACCREDITATIONS AND LISTINGS

Site Description

EMC Lab.

: Accredited by CNAS

The Certificate Registration Number is L6666.

The Laboratory has been assessed and proved to be in compliance with CNAS-CL01:2018 (identical to ISO/IEC 17025:2017)

Designation by FCC

Designation Number: CN1354

Test Firm Registration Number: 427606

Accredited by A2LA

The Certificate Number is 4321.03.

The certificate is valid until May 31, 2025

Designation by Industry Canada

The Conformity Assessment Body Identifier is CN0114

Name of Firm

Site Location

: EMTEK (NINGBO) CO., LTD.

: No. 8, Building 8, Lane 216, Qingyi Road, Hi-Tech Zone, Ningbo, Zhejiang, China

6 TEST SYSTEM UNCERTAINTY

The following measurement uncertainty levels have been estimated for tests performed on the apparatus:


Parameter	Uncertainty
Radio Frequency	$\pm 1 \times 10^{-5}$
Maximum Peak Output Power Test	$\pm 1.0 \text{dB}$
Conducted Emissions Test	$\pm 2.0 \text{dB}$
Radiated Emission Test	$\pm 2.0 \text{dB}$
Occupied Bandwidth Test	$\pm 1.0 \text{dB}$
Band Edge Test	$\pm 3 \text{dB}$
All emission, radiated	$\pm 3 \text{dB}$
Antenna Port Emission	$\pm 3 \text{dB}$
Temperature	$\pm 0.5^\circ\text{C}$
Humidity	$\pm 3\%$

Measurement Uncertainty for a level of Confidence of 95%

7 SETUP OF EQUIPMENT UNDER TEST

7.1 RADIO FREQUENCY TEST SETUP 1

The Bluetooth component's antenna port(s) of the EUT are connected to the measurement instrument per an appropriate attenuator. The EUT is controlled by PC/software to emit the specified signals for the purpose of measurements.



7.2 RADIO FREQUENCY TEST SETUP 2

The test site semi-anechoic chamber has met the requirement of NSA tolerance 4 dB according to the standards: ANSI C63.10. The test distance is 3m. The setup is according to the requirements in Section 13.1.4.1 of ANSI C63.10-2014 and CAN/CSA-CEI/IEC CISPR 22.

Below 30MHz:

The EUT is placed on a turntable 0.8 meters above the ground in the chamber, 3 meter away from the antenna (loop antenna). The Antenna should be positioned with its plane vertical at the specified distance from the EUT and rotated about its vertical axis for maximum response at each azimuth about the EUT. The center of the loop shall be 1 m above the ground. For certain applications, the loop antenna plane may also need to be positioned horizontally at the specified distance from the EUT.


30MHz-1GHz:

The EUT is placed on a turntable 0.8 meters above the ground in the chamber, 3 meter away from the antenna. The maximal emission value is acquired by adjusting the antenna height, polarisation and turntable azimuth. Normally, the height range of antenna is 1 m to 4 m, the azimuth range of turntable is 0° to 360°, and the receive antenna has two polarizations Vertical (V) and Horizontal (H).


Above 1GHz:

The EUT is placed on a turntable 1.5 meters above the ground in the chamber, 3 meter away from the antenna. The maximal emission value is acquired by adjusting the antenna height, polarisation and turntable azimuth. Normally, the height range of antenna is 1 m to 4 m, the azimuth range of turntable is 0° to 360°, and the receive antenna has two polarizations Vertical (V) and Horizontal (H).


(a) Radiated Emission Test Set-Up, Frequency Below 30MHz



(b) Radiated Emission Test Set-Up, Frequency Below 1000MHz



(c) Radiated Emission Test Set-Up, Frequency above 1000MHz




7.3 CONDUCTED EMISSION TEST SETUP

The mains cable of the EUT (Game fitness board) must be connected to LISN. The LISN shall be placed 0.8 m from the boundary of EUT and bonded to a ground reference plane for LISN mounted on top of the ground reference plane. This distance is between the closest points of the LISN and the EUT. All other units of the EUT and associated equipment shall be at least 0.8m from the LISN.

Ground connections, where required for safety purposes, shall be connected to the reference ground point of the LISN and, where not otherwise provided or specified by the manufacturer, shall be of same length as the mains cable and run parallel to the mains connection at a separation distance of not more than 0.1 m.

According to the requirements in Section 13.1.4.1 of ANSI C63.10-2014 Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30 MHz using CISPR Quasi-Peak and average detector mode.



7.4 SUPPORT EQUIPMENT

EUT Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite
/	/	/	/

Auxiliary Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite
/	/	/	/

Auxiliary Equipment List and Details			
Description	Manufacturer	Model	Serial Number
AC/DC ADAPTOR	/	ZB-H240020A-5E	/
CLASS 2 POWER SUPPLY	/	IVP12002000A	/
Vibrating plate	/	WC010A Vibrating plate	/
vibrator	/	4 ohm 10w	/
Low frequency speaker	/	6 ohm 30w	/
speaker	/	4 ohm 10w	/

Notes:

1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.

8 FREQUENCY HOPPING SYSTEM REQUIREMENTS

8.1 Standard Applicable

According to FCC Part 15.247(a)(1), The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudo randomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

(g) Frequency hopping spread spectrum systems are not required to employ all available hopping channels during each transmission. However, the system, consisting of both the transmitter and the receiver, must be designed to comply with all of the regulations in this section should the transmitter be presented with a continuous data (or information) stream. In addition, a system employing short transmission bursts must comply with the definition of a frequency hopping system and must distribute its transmissions over the minimum number of hopping channels specified in this section.

(h) The incorporation of intelligence within a frequency hopping spread spectrum system that permits the system to recognize other users within the spectrum band so that it individually and independently chooses and adapts its hopsets to avoid hopping on occupied channels is permitted. The coordination of frequency hopping systems in any other manner for the express purpose of avoiding the simultaneous occupancy of individual hopping frequencies by multiple transmitters is not permitted.

8.2 EUT Pseudorandom Frequency Hopping Sequence


The channel is represented by a pseudo-random hopping sequence hopping through the 79 RF channels.

The hopping sequence is unique for the piconet and is determined by the Bluetooth device address of the master; the phase in the hopping sequence is determined by the Bluetooth clock of the master. The channel is divided into time slots where each slot corresponds to an RF hop frequency. Consecutive hops correspond to different RF hop frequencies. The normal hop is 1 600 hops/s.


The pseudorandom sequence may be generated in a nine-stage shift register whose 5th and 9th stage outputs are added in a modulo-two addition stage, and the result is fed back to the input of the first stage. The sequence begins with the first ONE of 9 consecutive ONEs; i.e. the shift register is initialized with nine ones. Number of shift register stages: 9

Length of pseudo-random sequence: $2^9 - 1 = 524$ bits

Longest sequence of zeros: 8 (non-inverted signal)



Linear Feedback Shift Register for Generation of the PRBS sequence



Each frequency used equally on the average by each transmitter.

The system receiver have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shift frequencies in synchronization with the transmitted signals.

8.3 Equal Hopping Frequency Use

All Bluetooth units participating in the piconet are time and hop-synchronized to the channel.

Example of a 79 hopping sequence in data mode:

35, 27, 6, 44, 14, 61, 74, 32, 1, 11, 23, 2, 55, 65, 29, 3, 9, 52, 78, 58, 40, 25, 0, 7, 18, 26, 76, 60, 47, 50, 2, 5, 16, 37, 70, 63, 66, 54, 20, 13, 4, 8, 15, 21, 26, 10, 73, 77, 67, 69, 43, 24, 57, 39, 46, 72, 48, 33, 17, 31, 75, 19, 41, 62, 68, 28, 51, 66, 30, 56, 34, 59, 71, 22, 49, 64, 38, 45, 36, 42, 53

Each Frequency used equally on the average by each transmitter

8.4 Frequency Hopping System

This transmitter device is frequency hopping device, and complies with FCC part 15.247 rule.

This device uses Bluetooth radio which operates in 2402-2480 MHz band. Bluetooth uses a radio technology called frequency-hopping spread spectrum, which chops up the data being sent and transmits chunks of it on up to 40 bands (1 MHz each; centred from 2402 to 2480 MHz) in the range 2,420-2,459 MHz. The transmitter switches hop frequencies 1,600 times per second to assure a high degree of data security. All Bluetooth devices participating in a given piconet are synchronized to the frequency-hopping channel for the piconet. The frequency hopping sequence is determined by the master's device address and the phase of the hopping sequence (the frequency to hop at a specific time) is determined by the master's internal clock. Therefore, all slaves in a piconet must know the master's device address and must synchronize their clocks with the master's clock.

Adaptive Frequency Hopping (AFH) was introduced in the Bluetooth specification to provide an effective way for a Bluetooth radio to counteract normal interference. AFH identifies "bad" channels, where either other wireless devices are interfering with the Bluetooth signal or the Bluetooth signal is interfering with another device. The AFH- enabled Bluetooth device will then communicate with other devices within its piconet to share details of any identified bad channels. The devices will then switch to alternative available "good" channels, away from the areas of interference, thus having no impact on the bandwidth used.

9 TEST REQUIREMENTS

9.1 20DB BANDWIDTH

Applicable Standard

According to FCC Part 15.247(a)(1) and 558074 D01 15.247 Meas Guidance V05r02

Conformance Limit

No limit requirement.

Test Configuration

Test according to clause 7.1 radio frequency test setup 1

Test Procedure

The EUT was operating in Bluetooth V5.3 and controlled its channel. Printed out the test result from the spectrum by hard copy function.

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.

Set to the maximum power setting and enable the EUT transmit continuously

Set RBW = 30 kHz.

Set the video bandwidth (VBW) =100kHz.

Set Span= approximately 2 to 3 times the 20 dB bandwidth

Set Detector = Peak.

Set Trace mode = max hold.

Set Sweep = auto couple.

The EUT should be transmitting at its maximum data rate. Allow the trace to stabilize. Use the marker-to-peak function to set the marker to the peak of the emission. Use the marker-delta function to measure 20 dB down one side of the emission. Reset the markerdeltafunction, and move the marker to the other side of the emission, until it is (asclose as possible to) even with the reference marker level. The marker-delta reading atthis point is the 20 dB bandwidth of the emission.

If this value varies with differentmodes of operation (e.g., data rate, modulation format, etc.), repeat this test for eachvariation.

Measure and record the results in the test report.

Test Results

Temperature:

26°C

Test Date:

November 09, 2024


Humidity:


43%


Test By:


Victor

Modulation Mode	Channel Number	Channel Frequency (MHz)	20dB Bandwidth (kHz)
GFSK	0	2402	879.500
	39	2441	1005.000
	78	2480	991.800
pi/4-DQPSK	0	2402	1241.000
	39	2441	1309.000
	78	2480	1289.000
8DPSK	0	2402	1220.000
	39	2441	1294.000
	78	2480	1290.000











9.2 CARRIER FREQUENCY SEPARATION

Applicable Standard

According to FCC Part 15.247(a)(1) and 558074 D01 15.247 Meas Guidance V05r02

Conformance Limit

Frequency hopping systems operating in the 2400-2483.5MHz band shall have hopping channel carrier frequencies separated by a minimum of 25kHz or the 20dB bandwidth of the hopping channel, whichever is greater.

In case of an output power less than 125mW, the frequency hopping system may have channels separated by a minimum of 25kHz or two-thirds of the 20dB bandwidth of the hopping channel, whichever is greater.

Test Configuration

Test according to clause 7.1 radio frequency test setup 1

Test Procedure

■ According to FCC Part 15.247(a)(1)

The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:
Set the RBW = 100kHz. Set VBW = 300kHz.

Set the span = wide enough to capture the peaks of two adjacent channels

Set Sweep time = auto couple.

Set Detector = peak. Set Trace mode = max hold.

Allow the trace to stabilize. Use the marker-delta function to determine the separation between the peaks of the adjacent channels. The limit is specified in one of the subparagraphs of this Section. Submit this plot.

Test Results

Temperature: 26°C
Humidity: 43%

Test Date: November 09, 2024
Test By: Victor

Modulation Mode	Channel Number	Channel Frequency (MHz)	Measurement Bandwidth (kHz)	Limit (kHz)	Verdict
GFSK	0	2402	996.0	>664.00	PASS
	39	2441	969.0	>646.00	PASS
	78	2480	987.5	>658.33	PASS
pi/4-DQPSK	0	2402	999.0	>666.00	PASS
	39	2441	996.5	>664.33	PASS
	78	2480	894.0	>596.00	PASS
8DPSK	0	2402	999.0	>666.00	PASS
	39	2441	996.0	>664.00	PASS
	78	2480	987.5	>658.33	PASS


Note: Limit = 20dB bandwidth * 2/3, if it is greater than 25kHz and the output power is less than 125mW (21dBm).











9.3 NUMBER OF HOPPING FREQUENCIES

Applicable Standard

According to FCC Part 15.247(a)(1) (iii)and 558074 D01 15.247 Meas Guidance V05r02

Conformance Limit

Frequency hopping systems operating in the 2400-2483.5MHz band shall use at least 15 channels.

Test Configuration

Test according to clause 7.1 radio frequency test setup 1

Test Procedure

- According to FCC Part15.247(a)(1)(iii)

The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:

Span = the frequency band of operation

RBW = 100kHz

VBW ≥ RBW

Sweep = auto

Detector function = peak

Trace = max hold

Allow the trace to stabilize. It may prove necessary to break the span up to sections, inorder to clearly show all of the hopping frequencies.

Test Results

Temperature:

26°C

Test Date:

November 09, 2024

Humidity:

43%

Test By:

Victor

Hopping Channel Frequency Range	Quantity of Hopping Channel	Quantity of Hopping Channel limit
2402-2480 (GFSK)	79	>15

Note: Note: Both BR & EDR mode has same result .



9.4 AVERAGE TIME OF OCCUPANCY (DWELL TIME)

Applicable Standard

According to FCC Part 15.247(a)(1)(iii) and 558074 D01 15.247 Meas Guidance V05r02

Conformance Limit

For frequency hopping systems operating in the 2400-2483.5MHz band, the averagetime of occupancy on any channel shall not be greater than 0.4s within a period of 0.4smultiplied by the number of hopping channels employed.

Test Configuration

Test according to clause 7.1 radio frequency test setup 1

Test Procedure

- According to FCC Part15.247(a)(1)(iii)

The EUT must have its hopping function enabled. Use the following spectrum analyzersettings:

Span = zero span, centered on a hopping channel

RBW = 1 MHz

VBW \geq RBW

Sweep = as necessary to capture the entire dwell time per hopping channel

Detector function = peak

Trace = max hold

If possible, use the marker-delta function to determine the dwell time. If this value varies with different modes of operation (e.g., data rate, modulation format, etc.), repeat this test for each variation. The limit is specified in one of the subparagraphsof this Section.

Test Results

Temperature: 26°C
Humidity: 43%

Test Date: November 09, 2024
Test By: Victor


Modulation Mode	Channel Number	Packet type	Pluse width (ms)	DwellTime (ms)	Limit (ms)	Verdict
GFSK	0	DH1	0.364	116.480	<400	PASS
	0	DH3	1.631	260.960	<400	PASS
	0	DH5	2.884	307.627	<400	PASS


Note1: DwellTime(DH1)=PW*(1600/2/79)*31.6

DwellTime(DH3)=PW*(1600/4/79)*31.6

DwellTime(DH5)=PW*(1600/6/79)*31.6

Note2: Bluetooth (GFSK, pi/4-DQPSK, 8DPSK)mode have been tested, and the worst results has been recorded on the follow page.





9.5 MAXIMUM PEAK CONDUCTED OUTPUT POWER

Applicable Standard

According to FCC Part 15.247(b)(1) and 558074 D01 15.247 Meas Guidance V05r02

Conformance Limit

The max For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts.

Test Configuration

Test according to clause 7.1 radio frequency test setup 1

Test Procedure

- According to FCC Part15.247(b)(1)

As an alternative to a peak power measurement, compliance with the limit can be based on a measurement of the maximum conducted output power.

Use the following spectrum analyzer settings:

Set Span = approximately 5 times the 20 dB bandwidth, centered on a hopping channel(about 10MHz)

Set RBW > the 20 dB bandwidth of the emission being measured(about 3MHz)

Set VBW ≥ RBW

Set Sweep = auto

Set Detector function = peak

Set Trace = max hold

Allow the trace to stabilize. Use the marker-to-peak function to set the marker to the peak of the emissionto determine the peak amplitude level.

Test Results

Temperature: 26°C
Humidity: 43%


Test Date: November 09, 2024
Test By: Victor

Operation Mode	Channel Number	Channel Frequency (MHz)	MeasurementLevel (dBm)	Limit (dBm)	Verdict
GFSK	0	2402	3.00	21	PASS
	39	2441	2.70	21	PASS
	78	2480	1.38	21	PASS
pi/4-DQPSK	0	2402	-0.71	21	PASS
	39	2441	-0.92	21	PASS
	78	2480	-2.34	21	PASS
8DPSK	0	2402	-0.08	21	PASS
	39	2441	-0.49	21	PASS
	78	2480	-1.94	21	PASS


Note:N/A

Test Model	Maximum PeakConducted Output Power		
	Channel 0: 2402MHz		GFSK Modulation
	 <p>The screenshot shows a Keysight Spectrum Analyzer interface. The center frequency is set to 2.40200000 GHz. The span is 10.000000 MHz. The video bandwidth is 3.0 MHz. The sweep time is 1.00 ms (1001 pts). The reference level is 20.00 dBm, and the offset is 11.00 dB. The measurement marker Mkr1 shows a power of 3.00 dBm at 2.40169 GHz. The x-axis scale is logarithmic (Log).</p>		
Test Model	Maximum PeakConducted Output Power	Channel 39: 2441MHz	GFSK Modulation
 <p>The screenshot shows a Keysight Spectrum Analyzer interface. The center frequency is set to 2.44100000 GHz. The span is 10.000000 MHz. The video bandwidth is 3.0 MHz. The sweep time is 1.00 ms (1001 pts). The reference level is 20.00 dBm, and the offset is 11.00 dB. The measurement marker Mkr1 shows a power of 2.70 dBm at 2.44076 GHz. The x-axis scale is logarithmic (Log).</p>			

Test Model	Maximum PeakConducted Output Power		
	Channel 78: 2480MHz		GFSK Modulation
	 <p>Spectrum Analyzer 1 Swept SA</p> <p>KEYSIGHT Input: RF Coupling: DC Align: Auto</p> <p>Input Z: 50 Ω Corr CCorr Freq Ref. Int (S)</p> <p>#Atten: 30 dB μW Path: Standard PNO: Fast Gate: Off Avg Type: Log-Power IF Gain: Low Avg Hold >100/100 Sig Track: Off Trig: Free Run</p> <p>Mkr1 2.479 92 GHz 1.38 dBm</p> <p>Frequency: 2.480000000 GHz Span: 10.000000 MHz Center Frequency: 2.480000000 GHz Start Freq: 2.475000000 GHz Stop Freq: 2.485000000 GHz AUTO TUNE CF Step: 1.000000 MHz Auto / Man Freq Offset: 0 Hz X Axis Scale: Log / Lin Signal Track (Scan Zoom)</p> <p>1 Spectrum Scale/Div 10 dB Log</p> <p>Ref Lvl Offset 11.00 dB Ref Level 20.00 dBm</p> <p>1</p> <p>Center 2.480000 GHz #Video BW 3.0 MHz Span 10.00 MHz #Res BW 3.0 MHz Sweep 1.00 ms (1001 pts)</p> <p>Nov 09, 2024 4:54:18 PM</p>		
Test Model	Maximum PeakConducted Output Power		
	Channel 0: 2402MHz	pi/4-DQPSK Modulation	
 <p>Spectrum Analyzer 1 Swept SA</p> <p>KEYSIGHT Input: RF Coupling: DC Align: Auto</p> <p>Input Z: 50 Ω Corr CCorr Freq Ref. Int (S)</p> <p>#Atten: 30 dB μW Path: Standard PNO: Fast Gate: Off Avg Type: Log-Power IF Gain: Low Avg Hold >100/100 Sig Track: Off Trig: Free Run</p> <p>Mkr1 2.402 09 GHz -0.71 dBm</p> <p>Marker Select Marker Marker 1 Marker Frequency: 2.402090000 GHz Settings Peak Search Next Peak Pk Search Config Next Pk Right Next Pk Left Marker Function Minimum Peak Marker→ Pk-Pk Search Marker Delta Mkr→CF Mkr→Ref Lvl Continuous Peak Search On / Off</p> <p>1 Spectrum Scale/Div 10 dB Log</p> <p>Ref Lvl Offset 11.00 dB Ref Level 20.00 dBm</p> <p>1</p> <p>Center 2.402000 GHz #Video BW 3.0 MHz Span 10.00 MHz #Res BW 3.0 MHz Sweep 1.00 ms (1001 pts)</p> <p>Nov 09, 2024 4:58:42 PM</p>			



Test Model	Maximum PeakConducted Output Power		
	Channel 0: 2402MHz		8DPSK Modulation
	 <p>Spectrum Analyzer 1 Swept SA</p> <p>KEYSIGHT Input: RF Coupling: DC Align: Auto</p> <p>Input Z: 50 Ω Corr CCorr Freq Ref. Int (S)</p> <p>#Atten: 30 dB μW Path: Standard PNO: Fast Gate: Off IF Gain: Low Sig Track: Off</p> <p>Avg Type: Log-Power Avg Hold>100/100 Trig: Free Run</p> <p>1 2 3 4 5 6 M W W W W W P N N N N N</p> <p>Center Frequency 2.402000000 GHz Span 10.000000 MHz Full Span Start Freq 2.397000000 GHz Stop Freq 2.407000000 GHz AUTO TUNE CF Step 1.000000 MHz Auto / Man Freq Offset 0 Hz X Axis Scale Log / Lin Signal Track (Span Zoom)</p> <p>Ref Lvl Offset 11.00 dB Ref Level 20.00 dBm Mkr1 2.40199 GHz -0.08 dBm</p> <p>1 Spectrum Scale/Div 10 dB Log</p> <p>10.00 0.00 -10.00 -20.00 -30.00 -40.00 -50.00 -60.00 -70.00</p> <p>Center 2.402000 GHz #Video BW 3.0 MHz Span 10.00 MHz Sweep 1.00 ms (1001 pts) #Res BW 3.0 MHz Nov 09, 2024 5:01:32 PM</p>		
Maximum PeakConducted Output Power			
	Channel 39: 2441MHz	8DPSK Modulation	
 <p>Spectrum Analyzer 1 Swept SA</p> <p>KEYSIGHT Input: RF Coupling: DC Align: Auto</p> <p>Input Z: 50 Ω Corr CCorr Freq Ref. Int (S)</p> <p>#Atten: 30 dB μW Path: Standard PNO: Fast Gate: Off IF Gain: Low Sig Track: Off</p> <p>Avg Type: Log-Power Avg Hold>100/100 Trig: Free Run</p> <p>1 2 3 4 5 6 M W W W W W P N N N N N</p> <p>Center Frequency 2.441000000 GHz Span 10.000000 MHz Full Span Start Freq 2.436000000 GHz Stop Freq 2.446000000 GHz AUTO TUNE CF Step 1.000000 MHz Auto / Man Freq Offset 0 Hz X Axis Scale Log / Lin Signal Track (Span Zoom)</p> <p>Ref Lvl Offset 11.00 dB Ref Level 20.00 dBm Mkr1 2.44092 GHz -0.49 dBm</p> <p>1 Spectrum Scale/Div 10 dB Log</p> <p>10.00 0.00 -10.00 -20.00 -30.00 -40.00 -50.00 -60.00 -70.00</p> <p>Center 2.441000 GHz #Video BW 3.0 MHz Span 10.00 MHz Sweep 1.00 ms (1001 pts) #Res BW 3.0 MHz Nov 09, 2024 5:02:03 PM</p>			



9.6 CONDUCTED SUPRIOUS EMISSION

Applicable Standard

According to FCC Part 15.247(d) and 558074 D01 15.247 Meas Guidance V05r02

Conformance Limit

According to FCC Part 15.247(d):

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted, provided the transmitter demonstrates compliance with the peak conducted power limits.

Test Configuration

Test according to clause 7.1 radio frequency test setup 1

Test Procedure

The transmitter output (antenna port) was connected to the spectrum analyzer

■ Reference level measurement

Establish a reference level by using the following procedure:

Set instrument center frequency to DSS channel center frequency.

Set Span = approximately 5 times the 20 dB bandwidth, centered on a hopping channel.

Set the RBW = 100 kHz. Set the VBW \geq 3 x RBW.

Set Detector = peak. Set Sweep time = auto couple.

Set Trace mode = max hold. Allow trace to fully stabilize.

Use the peak marker function to determine the maximum Maximumconductedlevel.

Note that the channel found to contain the maximum conducted level can be used to establish the reference level.

■ Band-edge Compliance of RF Conducted Emissions

Use the following spectrum analyzer settings:

Span = wide enough to capture the peak level of the emission operating on the channel closest to the band-edge, as well as any modulation products which fall outside of the authorized band of operation

Set RBW \geq 1% of the span=100kHzSet VBW \geq RBW

Set Sweep = autoSetDetector function = peakSetTrace = max hold

Allow the trace to stabilize. Set the marker on the emission at the bandedge, or on the highest modulation product outside of the band, if this level is greater than that at the bandedge. Enable the marker-delta function, then use the marker-to-peak function to move the marker to the peak of the in-band emission. The marker-delta value now displayed must comply with the limit specified in this Section.

Now, using the same instrument settings, enable the hopping function of the EUT. Allow the trace to stabilize. Follow the same procedure listed above to determine if any spurious emissions caused by the hopping function also comply with the specified limit.

■ ConductedSpurious RF Conducted Emission

Use the following spectrum analyzer settings:

Span = wide enough to capture the peak level of the in-band emission and all spurious emissions (e.g., harmonics) from the lowest frequency generated in the EUT up through the 10th harmonic.(30MHz to 25GHz).Set RBW = 100 kHzSetVBW \geq RBW


Set Sweep = autoSetDetector function = peakSetTrace = max hold

Allow the trace to stabilize. Set the marker on the peak of any spurious emission recorded. The level displayed must comply with the limit specified in this Section.


Test Results


Bluetooth (GFSK, pi/4-DQPSK,8DPSK) mode have been tested, and the worst result(GFSK)was report as below:


Test Model	Maximum Conduced Level RBW=100kHz	
	Channel 0: 2402MHz	GFSK





Test Model	Conducted Spurious RF Conducted Emission(30 MHz-25GHz)	
	Channel 0: 2402MHz	GFSK









Test Model	Maximum Conducted Level RBW=100kHz		
	Hopping Mode		GFSK
	 <p>Ref Lvl Offset 11.00 dB Ref Level 20.00 dBm Mkr1 2.401 837.0 GHz 2.86 dBm</p> <p>Start 2.40000 GHz #Video BW 300 kHz Stop 2.48350 GHz Sweep 1.00 ms (1001 pts)</p> <p>Res BW 100 kHz</p> <p>Nov 09, 2024 3:30:58 PM</p>		
	 <p>Ref Lvl Offset 11.00 dB Ref Level 20.00 dBm Mkr1 23.980 0 GHz -41.20 dBm</p> <p>Start 30 MHz #Video BW 300 kHz Stop 25.00 GHz Sweep ~88.4 ms (30001 pts)</p> <p>#Res BW 100 kHz</p> <p>Nov 09, 2024 4:37:32 PM</p>		



9.7 RADIATED SPURIOUS EMISSION

Applicable Standard

According to FCC Part 15.247(d) and 15.209 and 558074 D01 15.247 Meas Guidance V05r02

Conformance Limit

According to FCC Part 15.247(d): radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).
According to FCC Part 15.205, Restricted bands

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
10.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(2)
13.36-13.41			

According to FCC Part 15.209, the level of any transmitter spurious emission in Restricted bands shall not exceed the level of the emission specified in the following table

Restricted Frequency(MHz)	Field Strength (μ V/m)	Field Strength ($dB\mu$ V/m)	Measurement Distance
0.009-0.490	2400/F(KHz)	20 log (μ V/m)	300
0.490-1.705	24000/F(KHz)	20 log (μ V/m)	30
1.705-30	30	29.5	30
30-88	100	40	3
88-216	150	43.5	3
216-960	200	46	3
Above 960	500	54	3

Test Configuration

Test according to clause 7.2 radio frequency test setup 2

Test Procedure

This test is required for any spurious emission that falls in a Restricted Band, as defined in Section 15.205. It must be performed with the highest gain of each type of antenna proposed for use with the EUT. Use the following spectrum analyzer settings:

The EUT was placed on a turn table which is 0.8m above ground plane.

Maximum procedure was performed on the highest emissions to ensure EUT compliance.

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz for $f \geq 1$ GHz(1GHz to 25GHz), 100 kHz for $f < 1$ GHz(30MHz to 1GHz)

VBW \geq RBW

Sweep = auto

Detector function = peak

Trace = max hold

Follow the guidelines in ANSI C63.10-2014 respect to maximizing the emission by rotating the EUT, measuring the emission while the EUT is situated in three orthogonal planes (if appropriate), adjusting the measurement antenna height and polarization, etc. A pre-amp and a high pass filter are required for this test, in order to provide the measuring system with sufficient sensitivity. Allow the trace to stabilize. The peak reading of the emission, after being corrected by the antenna factor, cable loss, pre-amp gain, etc., is the peak field strength, which must comply with the limit specified in Section 15.35(b). Submit this data.

Now set the VBW to 10 Hz, while maintaining all of the other instrument settings. This peak level, once corrected, must comply with the limit specified in Section 15.209. If the dwell time per channel of the hopping signal is less than 100 ms, then the reading obtained with the 10 Hz VBW may be further adjusted by a "duty cycle correction factor", derived from $20\log(\text{dwell time}/100 \text{ ms})$, in an effort to demonstrate compliance with the 15.209 limit. Submit this data.

Repeat above procedures until all frequency measured was complete.

Test Results

■ Spurious Emission below 30MHz(9KHz to 30MHz)

Temperature: 21°C
Humidity: 67%
Test mode: GFSK

Test Date: November 06, 2024
Test By: Victor

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
--	--	--	--	--	--	--	--

Note: the amplitude of spurious emission that is attenuated by more than 20dB below the permissible limit has no need to be reported.

Distance extrapolation factor = $40\log(\text{Specific distance}/\text{test distance})(\text{dB})$;
Limit line=Specific limits(dBuV) + distance extrapolation factor

■ Spurious Emission Above 1GHz(1GHz to 25GHz)

Bluetooth (GFSK, pi/4-DQPSK,8DPSK, non hopping) mode have been tested, and the worst result(GFSK)was report as below:

Temperature: 21°C
Humidity: 67%
Test mode: GFSK

Test Date: November 06, 2024
Test By: Victor
Frequency: Channel 0: 2402MHz

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
4840.000	V	44.36	30.78	74.00	54.00	-29.64	-23.22
7260.000	V	43.47	27.74	74.00	54.00	-30.53	-26.26
17584.500	V	54.99	40.38	74.00	54.00	-19.01	-13.62
4840.000	H	40.43	25.69	74.00	54.00	-33.57	-28.31
7360.000	H	51.26	37.58	74.00	54.00	-22.74	-16.42
17978.500	H	55.75	40.32	74.00	54.00	-18.25	-13.68

Temperature: 21°C Test Date: November 06, 2024
 Humidity: 67% Test By: Victor
 Test mode: GFSK Frequency: Channel 39: 2441MHz

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
4882.000	V	44.54	31.72	74.00	54.00	-29.46	-22.28
7323.000	V	46.65	32.81	74.00	54.00	-27.35	-21.19
17983.500	V	56.26	40.78	74.00	54.00	-17.74	-13.22
4882.000	H	43.05	27.95	74.00	54.00	-30.95	-26.05
7323.000	H	51.58	37.28	74.00	54.00	-22.42	-16.72
17978.000	H	55.22	30.75	74.00	54.00	-18.78	-23.25

Temperature: 21°C Test Date: November 06, 2024
 Humidity: 67% Test By: Victor
 Test mode: GFSK Frequency: Channel 78: 2480MHz

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
4918.000	V	43.58	28.94	74.00	54.00	-30.42	-25.06
7377.000	V	44.21	29.16	74.00	54.00	-29.79	-24.84
17994.500	V	55.81	40.37	74.00	54.00	-18.19	-13.63
4918.000	H	42.76	27.36	74.00	54.00	-31.24	-26.64
7377.000	H	51.98	37.29	74.00	54.00	-22.02	-16.71
17955.000	H	54.98	34.16	74.00	54.00	-19.02	-19.84

- Note:** (1) All Readings are Peak Value (VBW=3MHz) and Peak Value (VBW=10Hz).
 (2) Emission Level= Reading Level+Correct Factor +Cable Loss.
 (3) Correct Factor= Ant_F + Cab_L - Preamp
 (4) The reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

■ Spurious Emission in Restricted Band 2402-2480MHz

Bluetooth (GFSK, pi/4-DQPSK,8DPSK, non hopping) mode have been tested, and the worst result(GFSK, Hopping) was report as below:

Temperature:	21°C	Test Date:	November 06, 2024
Humidity:	67 %	Test By:	Victor
Test mode:	GFSK	Frequency:	Channel 0: 2402MHz

Frequency (MHz)	Polarity H/V	PK(dBuV/m) (VBW=3MHz)	Limit 3m (dBuV/m)	Over(dB)	AV(dBuV/m) (VBW=10Hz)	Limit 3m (dBuV/m)	Over (dB)
2342.240	H	57.95	74.00	-16.05	42.89	54.00	-11.11
2347.240	V	57.91	74.00	-16.09	43.55	54.00	-10.45


Temperature:	21°C	Test Date:	November 06, 2024
Humidity:	67 %	Test By:	Victor
Test mode:	GFSK	Frequency:	Channel 78: 2480MHz


Frequency (MHz)	Polarity H/V	PK(dBuV/m) (VBW=3MHz)	Limit 3m (dBuV/m)	Over(dB)	AV(dBuV/m) (VBW=10Hz)	Limit 3m (dBuV/m)	Over (dB)
2483.987	H	58.08	74.00	-15.92	44.28	54.00	-9.72
2491.032	V	58.94	74.00	-15.06	43.89	54.00	-0.11


Temperature:	21°C	Test Date:	November 06, 2024
Humidity:	67 %	Test By:	Victor
Test mode:	GFSK	Frequency:	Hopping

Frequency (MHz)	Polarity H/V	PK(dBuV/m) (VBW=3MHz)	Limit 3m (dBuV/m)	Over(dB)	AV(dBuV/m) (VBW=10Hz)	Limit 3m (dBuV/m)	Over (dB)
2399.984	H	64.34	74.00	-9.66	49.64	54.00	-4.36
2483.489	H	66.48	74.00	-7.52	51.47	54.00	-2.53
2399.984	V	65.22	74.00	-8.78	51.36	54.00	-2.64
2483.489	V	65.91	74.00	-8.09	51.64	54.00	-2.36

- Note:**
- (1) All Readings are Peak Value (VBW=3MHz) and Peak Value (VBW=10Hz).
 - (2) Emission Level= Reading Level+Correct Factor +Cable Loss.
 - (3) Correct Factor= Ant_F + Cab_L - Preamp
 - (4) The reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.








■ Spurious Emission below 1GHz(30MHz to 1GHz)


All modes of AC 120V and AC 240V have been tested, and the worst result recorded was report as below:

Project Information			
Mode:	TX 2402	Voltage:	AC 120V/60Hz
Environment:	Temp:22°C; Humi:68%	Engineer:	Victor




Freq. (MHz)	Reading (dB μ V)	Corr. (dB)	Meas. (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Det.	Height (cm)	Pol.	Azimuth (deg)	Verdict
100.519	52.50	-25.32	27.18	43.50	16.32	QPK	100	V	46.7	PASS
114.293	57.48	-26.5	30.98	43.50	12.52	QPK	100	V	34.7	PASS
159.883	57.18	-26.99	30.19	43.50	13.31	QPK	100	V	24.7	PASS
193.251	54.72	-25.24	29.48	43.50	14.02	QPK	100	V	0.0	PASS
213.233	57.57	-24.31	33.26	43.50	10.24	QPK	100	V	6.7	PASS
227.977	58.83	-23.83	35.00	46.00	11.00	QPK	100	V	0	PASS

Project Information			
Mode:	TX 2402	Voltage:	AC 120V/60Hz
Environment:	Temp:22°C; Humi:68%	Engineer:	Victor




Freq. (MHz)	Reading (dB μ V)	Corr. (dB)	Meas. (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Det.	Height (cm)	Pol.	Azimuth (deg)	Verdict
162.502	60.96	-26.91	34.05	43.50	9.45	QPK	100	H	16.4	PASS
176.082	60.93	-26.17	34.76	43.50	8.74	QPK	100	H	1.9	PASS
213.233	63.78	-24.31	39.47	43.50	4.03	QPK	100	H	10.4	PASS
228.074	58.44	-23.83	34.61	46.00	11.39	QPK	100	H	10.4	PASS
249.123	61.89	-22.75	39.14	46.00	6.86	QPK	100	H	0	PASS
311.203	58.94	-21.75	37.19	46.00	8.81	QPK	100	H	20.4	PASS

Project Information			
Mode:	TX 2441	Voltage:	AC 120V/60Hz
Environment:	Temp:22°C; Humi:68%	Engineer:	Victor




Freq. (MHz)	Reading (dB μ V)	Corr. (dB)	Meas. (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Det.	Height (cm)	Pol.	Azimuth (deg)	Verdict
51.340	51.81	-24.39	27.42	40.00	12.58	QPK	100	V	8.6	PASS
115.554	57.63	-26.63	31.00	43.50	12.50	QPK	100	V	25.6	PASS
160.174	57.92	-26.98	30.94	43.50	12.56	QPK	100	V	0	PASS
192.960	55.68	-25.26	30.42	43.50	13.08	QPK	100	V	1.0	PASS
225.067	57.93	-23.96	33.97	46.00	12.03	QPK	100	V	49.1	PASS
248.444	53.48	-22.79	30.69	46.00	15.31	QPK	100	V	1.0	PASS

Project Information			
Mode:	TX 2441	Voltage:	AC 120V/60Hz
Environment:	Temp:22°C; Humi:68%	Engineer:	Victor




Freq. (MHz)	Reading (dB μ V)	Corr. (dB)	Meas. (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Det.	Height (cm)	Pol.	Azimuth (deg)	Verdict
159.786	63.00	-26.99	36.01	43.50	7.49	QPK	100	H	42.7	PASS
166.091	61.99	-26.8	35.19	43.50	8.31	QPK	100	H	26.2	PASS
176.276	62.30	-26.15	36.15	43.50	7.35	QPK	100	H	0	PASS
213.136	59.94	-24.31	35.63	43.50	7.87	QPK	100	H	16.7	PASS
248.056	62.86	-22.81	40.05	46.00	5.95	QPK	100	H	0.0	PASS
312.076	60.66	-21.69	38.97	46.00	7.03	QPK	100	H	30.2	PASS

Project Information			
Mode:	TX 2480	Voltage:	AC 120V/60Hz
Environment:	Temp:22°C; Humi:68%	Engineer:	Victor



Freq. (MHz)	Reading (dB μ V)	Corr. (dB)	Meas. (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Det.	Height (cm)	Pol.	Azimuth (deg)	Verdict
114.293	58.38	-26.5	31.88	43.50	11.62	QPK	100	V	53.3	PASS
138.446	58.47	-28.02	30.45	43.50	13.05	QPK	100	V	19.3	PASS
146.400	58.28	-27.34	30.94	43.50	12.56	QPK	100	V	19.3	PASS
159.980	58.11	-26.99	31.12	43.50	12.38	QPK	100	V	64.3	PASS
224.582	58.64	-23.98	34.66	46.00	11.34	QPK	100	V	20.8	PASS
251.645	54.62	-22.71	31.91	46.00	14.09	QPK	100	V	1.5	PASS

Project Information			
Mode:	TX 2480	Voltage:	AC 120V/60Hz
Environment:	Temp:22°C; Humi:68%	Engineer:	Victor



Freq. (MHz)	Reading (dB μ V)	Corr. (dB)	Meas. (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Det.	Height (cm)	Pol.	Azimuth (deg)	Verdict
175.597	61.36	-26.21	35.15	43.50	8.35	QPK	100	H	351.5	PASS
211.681	59.75	-24.36	35.39	43.50	8.11	QPK	100	H	342.0	PASS
240.005	62.75	-23.27	39.48	46.00	6.52	QPK	100	H	358.8	PASS
248.250	63.17	-22.8	40.37	46.00	5.63	QPK	100	H	338.5	PASS
286.177	57.62	-22.6	35.02	46.00	10.98	QPK	100	H	331.5	PASS
319.836	57.78	-21.2	36.58	46.00	9.42	QPK	100	H	360	PASS

9.8 CONDUCTED EMISSION TEST

Applicable Standard

According to FCC Part 15.207(a)

Conformance Limit

Frequency(MHz)	Conducted Emission Limit	
	Quasi-peak	Average
0.15-0.5	66-56	56-46
0.5-5.0	56	46
5.0-30.0	60	50

Note: 1. The lower limit shall apply at the transition frequencies
2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

Test Configuration

Test according to clause 7.3 conducted emission test setup

Test Procedure


The EUT was placed on a table which is 0.1m above ground plane.
Maximum procedure was performed on the highest emissions to ensure EUT compliance.
Repeat above procedures until all frequency measured were complete.

Test Results

Pass.


All modes of AC 120V and AC 240V have been tested, and the worst result recorded was report as below:

Project Information			
Mode:	TX2402	Voltage:	AC 120V/60Hz
Environment:	Temp:23°C; Humi:65%	Engineer:	Elvis Xia



Freq. (MHz)	Reading (dB μ V)	Corr. (dB)	Meas. (dB μ V)	Limit (dB μ V)	Margin (dB)	Det.	Line	PE	Verdict
0.169	38.12	10.1	48.22	65.01	16.79	QPK	N	GND	PASS
0.169	19.67	10.1	29.77	55.01	25.24	AVG	N	GND	PASS
0.200	33.76	10.1	43.86	63.61	19.75	QPK	N	GND	PASS
0.200	16.45	10.1	26.55	53.61	27.06	AVG	N	GND	PASS
0.225	30.31	10.1	40.41	62.63	22.22	QPK	N	GND	PASS
0.225	13.37	10.1	23.47	52.63	29.16	AVG	N	GND	PASS
0.241	28.29	10.09	38.38	62.06	23.68	QPK	N	GND	PASS
0.241	11.77	10.09	21.86	52.06	30.20	AVG	N	GND	PASS
0.368	27.47	10.07	37.54	58.55	21.01	QPK	N	GND	PASS
0.368	22.28	10.07	32.35	48.55	16.20	AVG	N	GND	PASS
0.422	28.73	10.06	38.79	57.41	18.62	QPK	N	GND	PASS
0.422	22.35	10.06	32.41	47.41	15.00	AVG	N	GND	PASS

Project Information			
Mode:	TX2402	Voltage:	AC 120V/60Hz
Environment:	Temp:23°C; Humi:65%	Engineer:	Elvis Xia



Freq. (MHz)	Reading (dB μ V)	Corr. (dB)	Meas. (dB μ V)	Limit (dB μ V)	Margin (dB)	Det.	Line	PE	Verdict
0.160	39.72	10.11	49.83	65.46	15.63	QPK	L1	GND	PASS
0.160	23.19	10.11	33.30	55.46	22.16	AVG	L1	GND	PASS
0.187	34.94	10.1	45.04	64.17	19.13	QPK	L1	GND	PASS
0.187	17.12	10.1	27.22	54.17	26.95	AVG	L1	GND	PASS
0.237	28.04	10.1	38.14	62.20	24.06	QPK	L1	GND	PASS
0.237	10.32	10.1	20.42	52.20	31.78	AVG	L1	GND	PASS
0.250	26.83	10.09	36.92	61.76	24.84	QPK	L1	GND	PASS
0.250	10.96	10.09	21.05	51.76	30.71	AVG	L1	GND	PASS
0.364	24.80	10.07	34.87	58.64	23.77	QPK	L1	GND	PASS
0.364	18.49	10.07	28.56	48.64	20.08	AVG	L1	GND	PASS
0.422	28.55	10.06	38.61	57.41	18.80	QPK	L1	GND	PASS
0.422	22.15	10.06	32.21	47.41	15.20	AVG	L1	GND	PASS

9.9 ANTENNA APPLICATION

Antenna Requirement

Standard	Requirement
FCC CRF Part15.203	An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §15.211, §15.213, §15.217, §15.219, or §15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with §15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

Result

Pass.

The EUT has 1 PCB Antenna: The PCB Antenna Gain is 2.499 dBi;

- Note:
- Antenna use a permanently attached antenna which is not replaceable.
 - Not using a standard antenna jack or electrical connector for antenna replacement
 - The antenna has to be professionally installed (please provide method of installation)

which in accordance to section 15.203, please refer to the internal photos.

*** End of Report ***

声 明 Statement

1. 本报告无授权批准人签字及“检验检测专用章”无效；

This report will be void without authorized signature or special seal for testing report.

2. 未经许可本报告不得部分复制；

This report shall not be copied partly without authorization.

3. 本报告的检测结果仅对送测样品有效，委托方对样品的代表性和资料的真实性负责；

The test results or observations are applicable only to tested sample. Client shall be responsible for representativeness of the sample and authenticity of the material.

4. 本检测报告中检测项目标注有特殊符号则该项目不在资质认定范围内，仅作为客户委托、科研、教学或内部质量控制等目的使用；

The observations or tests with special mark fall outside the scope of accreditation, and are only used for purpose of commission, research, training, internal quality control etc.

5. 本检测报告以实测值进行符合性判定，未考虑不确定度所带来的风险，本实验室不承担相关责任，特别约定、标准或规范中有明确规定的除外；

The test results or observations are provided in accordance with measured value, without taking risks caused by uncertainty into account. Without explicit stipulation in special agreements, standards or regulations, EMTEK shall not assume any responsibility.

6. 对本检测报告若有异议，请于收到报告之日起 20 日内提出；

Objections shall be raised within 20 days from the date receiving the report.