

TEST REPORT

Application No.: KSCR2503000354AT
FCC ID: 2AL8S-0235CAKG
Applicant: Zhejiang Uniview Technologies Co., Ltd.
Address of Applicant: No. 369, Xietong Road, Xixing Sub-district, Binjiang District, Hangzhou City, 310051, Zhejiang Province, China
Manufacturer: Zhejiang Uniview Technologies Co., Ltd.
Address of Manufacturer: No. 369, Xietong Road, Xixing Sub-district, Binjiang District, Hangzhou City, 310051, Zhejiang Province, China
Factory: Zhejiang Uniview Systems Technology Co., Ltd.
Address of Factory: No.1277 South Qingfeng South Road, Tongxiang City, Jiaxing City, Zhejiang Province, China
Equipment Under Test (EUT):
EUT Name: IP Camera
Model No.: Uho-P2C-M4F4, Uho-P2C-xxxxxxx-yyy-yyyy-zzzz("x"can be 0-9,A-Z,a-z or blank,denoting difference in interface,"y"can be 0-9,A-Z,a-z or blank,denoting performance difference,"z"can be 0-9,A-Z,a-z or blank,denoting target regional,"-" is option) ♣
♣ Please refer to section 2 of this report which indicates which model was actually tested and which were electrically identical.
Standard(s) : 47 CFR Part 15, Subpart C 15.247
Date of Receipt: 2025-03-04
Date of Test: 2025-03-05 to 2025-03-24
Date of Issue: 2025-03-25

Test Result:	Pass*
---------------------	--------------

* In the configuration tested, the EUT complied with the standards specified above.


This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein.

Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.



Revision Record			
Version	Description	Date	Remark
00	Original	2025-03-25	/

Authorized for issue by:				
Tested By				
		Tommie_Tang/Project Engineer		
Approved By				
		Terry Hou /Reviewer		

2 Test Summary

Radio Spectrum Technical Requirement				
Item	Standard	Method	Requirement	Result
Antenna Requirement	47 CFR Part 15, Subpart C 15.247	N/A	47 CFR Part 15, Subpart C 15.203 & 15.247(b)(4)	Pass

Radio Spectrum Matter Part				
Item	Standard	Method	Requirement	Result
Conducted Emissions at AC Power Line (150kHz-30MHz)	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 6.2	47 CFR Part 15, Subpart C 15.207	Pass
Radiated Emissions which fall in the restricted bands		ANSI C63.10 (2013) Section 6.10.5	47 CFR Part 15, Subpart C 15.205 & 15.209	Pass
Radiated Spurious Emissions Below 1GHz		ANSI C63.10 (2013) Section 6.4,6.5	47 CFR Part 15, Subpart C 15.205 & 15.209	Pass
Radiated Spurious Emissions Above 1GHz		ANSI C63.10 (2013) Section 6.6	47 CFR Part 15, Subpart C 15.205 & 15.209	Pass
Conducted Average Output Power		ANSI C63.10 (2013) Section 11.9.2	47 CFR Part 15, Subpart C 15.247(b)(3)	Pass
Minimum 6dB Bandwidth		ANSI C63.10 (2013) Section 11.8.1	47 CFR Part 15, Subpart C 15.247a(2)	Pass
Power Spectrum Density		ANSI C63.10 (2013) Section 11.10.2	47 CFR Part 15, Subpart C 15.247(e)	Pass
Conducted Band Edges Measurement		ANSI C63.10 (2013) Section 11.13.3.2	47 CFR Part 15, Subpart C 15.247(d)	Pass
Conducted Spurious Emissions		ANSI C63.10 (2013) Section 11.11	47 CFR Part 15, Subpart C 15.247(d)	Pass

Declaration of EUT Family Grouping:

Note: There are series models mentioned in this report, and they are identical in electrical and electronic characters. Only the model Uho-P2C-M4F4 was tested since their differences were the model number and appearance.

3 Contents

	Page
1 COVER PAGE	1
2 Test Summary	3
3 Contents.....	4
4 General Information.....	5
4.1 Details of E.U.T.	5
4.2 Power level setting using in test.....	5
4.3 Description of Support Units	5
4.4 Measurement Uncertainty	6
4.5 Test Location	7
4.6 Test Facility	7
4.7 Deviation from Standards.....	7
4.8 Abnormalities from Standard Conditions.....	7
5 Equipment List	8
6 Radio Spectrum Technical Requirement.....	10
6.1 Antenna Requirement	10
7 Radio Spectrum Matter Test Results	11
7.1 Conducted Emissions at AC Power Line (150kHz-30MHz).....	11
7.2 Radiated Emissions which fall in the restricted bands	15
7.3 Radiated Spurious Emissions Below 1GHz	54
7.4 Radiated Spurious Emissions Above 1GHz.....	58
7.5 Conducted Average Output Power	90
7.6 Minimum 6dB Bandwidth.....	92
7.7 Power Spectrum Density	93
7.8 Conducted Band Edges Measurement	94
7.9 Conducted Spurious Emissions	95
8 Test Setup Photo	96
9 EUT Constructional Details (EUT Photos).....	96
10 Appendix.....	97

4 General Information

4.1 Details of E.U.T.

Power supply:	DC 12V,1A by adapter Adapter Model: DCT24W120150US-A3 Input: 100-240V, 50/60Hz, 0.7A max. Output: 12.0V, 1.5A
Operation Frequency:	802.11b/g/n(HT20)/ax(HE20): 2412MHz to 2462MHz; 802.11n(HT40)/ax(HE40): 2422MHz to 2452MHz
Modulation Type:	802.11b: DSSS (CCK, DQPSK, DBPSK), 802.11g/n: OFDM (BPSK, QPSK, 16QAM, 64QAM), 802.11ax: OFDMA (BPSK, QPSK, 16QAM, 64QAM, 256QAM)
Number of Channels:	802.11b/g/n(HT20)/ax(HE20):11;802.11n(HT40)/ax(HE40):7
Channel Spacing:	5MHz
Antenna Type:	FPC Antenna
Antenna Gain:	4.59dBi (Provided by the manufacturer)

4.2 Power level setting using in test

Channel	802.11b	802.11g	802.11n(HT20)	802.11ax(HEW20)
	Ant 1	Ant 1	Ant 1	Ant 1
1	12	15	15	15
6	12	15	15	15
11	12	15	15	15
Channel	802.11n(HT40)	802.11ax(HEW40)		
	Ant 1	Ant 1		
3	15	15		
6	15	15		
9	15	15		

4.3 Description of Support Units

Description	Manufacturer	Model No.	Serial No.
Notebook	LENOVO	K27	/

4.4 Measurement Uncertainty

No.	Item	Measurement Uncertainty
1	Radio Frequency	8.4×10^{-8}
2	Timeout	2s
3	Duty Cycle	0.37%
4	Occupied Bandwidth	3%
5	RF Conducted Power	0.6dB
6	RF Power Density	2.9dB
7	Conducted Spurious Emissions	0.75dB
8	RF Radiated Power	5.2dB (Below 1GHz)
		5.9dB (Above 1GHz)
9	Radiated Spurious Emission Test	4.2dB (Below 30MHz)
		4.5dB (30MHz-1GHz)
		5.1dB (1GHz-18GHz)
		5.4dB (Above 18GHz)
10	Temperature Test	1°C
11	Humidity Test	3%
12	Supply Voltages	1.5%
13	Time	3%
Note: The measurement uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.		

4.5 Test Location

All tests were performed at:

Compliance Certification Services (Kunshan) Inc.

No.10 Weiye Rd, Innovation park, Eco&Tec, Development Zone, Kunshan City, Jiangsu, China.

Tel: +86 512 5735 5888 Fax: +86 512 5737 0818

No tests were sub-contracted.

Note:

1. SGS is not responsible for wrong test results due to incorrect information (e.g., max. internal working frequency, antenna gain, cable loss, etc) is provided by the applicant. (If applicable).
2. SGS is not responsible for the authenticity, integrity and the validity of the conclusion based on results of the data provided by applicant. (If applicable).
3. Sample source: sent by customer.

4.6 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **A2LA**

Compliance Certification Services (Kunshan) Inc. is accredited by the American Association for Laboratory Accreditation (A2LA). Certificate No. 2541.01.

- **FCC**

Compliance Certification Services (Kunshan) Inc. has been recognized as an accredited testing laboratory. Designation Number: CN1172.

- **ISED**

Compliance Certification Services (Kunshan) Inc. has been recognized by Innovation, Science and Economic Development Canada (ISED) as an accredited testing laboratory. Company Number: 2324E

- **VCCI**

The 3m and 10m Semi-anechoic chamber and Shielded Room of Compliance Certification Services (Kunshan) Inc. has been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: R-20134, R-11600, C-11707, T-11499, G-10216 respectively.

4.7 Deviation from Standards

None

4.8 Abnormalities from Standard Conditions

None

5 Equipment List

Item	Equipment	Manufacturer	Model	Inventory No	Cal Date	Cal. Due Date
Conducted Emission at Mains Terminals						
1	EMI Test Receive	R&S	ESCI	KS301196	08/01/2024	07/31/2025
2	LISN	R&S	ENV216	KS301197	01/15/2025	01/14/2026
3	LISN	Schwarzbeck	NNLK 8129	KS301091	01/15/2025	01/14/2026
4	Pulse Limiter	R&S	ESH3-Z2	KUS1902E001	12/05/2024	12/04/2025
5	CE test Cable	Thermax	/	CZ301102	01/14/2025	01/13/2026
6	Test Software	Farad	EZ-EMC	/	N.C.R	N.C.R
RF Conducted Test						
1	Spectrum Analyzer	Keysight	N9020A	KUS1911E004-2	08/01/2024	07/31/2025
2	Spectrum Analyzer	Keysight	N9020A	KUS2001M001-2	08/01/2024	07/31/2025
3	Spectrum Analyzer	Keysight	N9030B	KSEM021-1	01/15/2025	01/14/2026
4	Signal Generator	R&S	SMBV100B	KSEM032	02/19/2025	02/18/2026
5	Signal Generator	R&S	SMW200A	KSEM020-1	08/02/2024	08/01/2025
6	Signal Generator	Agilent	N5182A	KUS2001M001-1	08/01/2024	07/31/2025
7	Radio Communication Test Station	Anritsu	MT8000A	KSEM001-1	08/01/2024	07/31/2025
8	Radio Communication Analyzer	Anritsu	MT8821C	KSEM002-1	02/19/2025	02/18/2026
9	Universal Radio Communication Tester	R&S	CMW500	KUS1911E004-1	08/13/2024	08/12/2025
10	Switcher	TST	FY562	KUS2001M001-4	01/15/2025	01/14/2026
11	AC Power Source	EXTECH	6605	KS301178	N.C.R	N.C.R
12	DC Power Supply	Aglient	E3632A	KS301180	N.C.R	N.C.R
13	Conducted Test Cable	Thermax	RF01-RF04	CZ301111-CZ301120	01/14/2025	01/13/2026
14	Temp. / Humidity Chamber	TERCHY	MHK-120AK	KSES104904	09/02/2024	09/01/2025
15	Temperature & Humidity Recorder	Renke Control	RS-WS-N01-6J	KSEM024-5	02/26/2025	02/25/2026
16	Software	BST	TST-PASS	/	NCR	NCR
RF Radiated Test						
1	Spectrum Analyzer	R&S	FSV40	KUS1806E003	08/06/2024	08/05/2025
2	Universal Radio Communication Tester	R&S	CMW500	KSEM009-1	02/18/2025	02/17/2026
3	Signal Generator	Agilent	E8257C	KS301066	08/06/2024	08/05/2025
4	Loop Antenna	COM-POWER	AL-130R	KUS1806E001	03/01/2025	02/28/2027
5	Bilog Antenna	TESEQ	CBL 6112D	KUS1806E005	06/29/2023	06/28/2025
6	Horn-antenna(1-18GHz)	Schwarzbeck	BBHA9120D	KS301079	03/23/2024	03/22/2026
7	Horn-antenna(1-18GHz)	ETS-LINDGREN	3117	KS301186	04/07/2023	04/06/2025
8	Horn Antenna(18-40GHz)	Schwarzbeck	BBHA9170	CZ301058	01/07/2024	01/06/2026

9	Amplifier(30MHz~18GHz)	PANSHAN TECHNOLOGY	LNA:1~18G	KSEM010-1	01/15/2025	01/14/2026
10	Amplifier(18~40GHz)	PANSHAN TECHNOLOGY	LNA180400G40	KSEM038	08/12/2024	08/11/2025
11	RE Test Cable	REBES MICROWAVE	/	CZ301097	08/23/2024	08/22/2025
12	Temperature & Humidity Recorder	Renke Control	RS-WS-N01-6J	KSEM024-4	02/26/2025	02/25/2026
13	Software	Faratronic	EZ_EMV-3A1	/	NCR	NCR
14	Software	ESE	E3_V 6.111221a	/	NCR	NCR

6 Radio Spectrum Technical Requirement

6.1 Antenna Requirement

6.1.1 Test Requirement:

47 CFR Part 15, Subpart C 15.203 & 15.247(b)(4)

6.1.2 Conclusion

Standard Requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

15.247(b) (4) requirement:

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

EUT Antenna:

The antenna is FPC Antenna on the main PCB and no consideration of replacement. The best case gain of the antenna is 4.59 dBi.

Antenna location: Refer to internal photo.

7 Radio Spectrum Matter Test Results

7.1 Conducted Emissions at AC Power Line (150kHz-30MHz)

Test Requirement 47 CFR Part 15, Subpart C 15.207

Test Method: ANSI C63.10 (2013) Section 6.2

Limit:

Frequency of emission(MHz)	Conducted limit(dBμV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50
*Decreases with the logarithm of the frequency.		
Detector: Peak for pre-scan (9kHz resolution bandwidth) 0.15M to 30MHz		

7.1.1 E.U.T. Operation

Operating Environment:

Temperature: 25.3 °C


Humidity: 46.3 % RH

Atmospheric Pressure: 1010 mbar

7.1.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	00	TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); data rate @ 13.5Mbps is the worst case of IEEE 802.11n(HT40); data rate @ MCS0 is the worst case of IEEE 802.11ax(HE20); data rate @ MCS0 is the worst case of IEEE 802.11ax(HE40). Only the data of worst case is recorded in the report.

7.1.3 Test Setup Diagram




7.1.4 Measurement Procedure and Data

- 1) The mains terminal disturbance voltage test was conducted in a shielded room.
- 2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a 50ohm/50μH + 5ohm linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded.
- 3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane.
- 4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2.
- 5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10 on conducted measurement.

Remark: Level=Read Level+ Cable Loss+ LISN Factor

Test Mode: 00; Line: Live line


Test Data :



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.3141	15.93	19.89	35.82	49.86	-14.04	Average
2	0.3141	21.00	19.89	40.89	59.86	-18.97	QP
3	0.4279	14.72	19.88	34.60	47.29	-12.69	Average
4	0.4279	19.93	19.88	39.81	57.29	-17.48	QP
5	0.5067	4.38	19.87	24.25	46.00	-21.75	Average
6	0.5067	9.44	19.87	29.31	56.00	-26.69	QP
7	0.6030	4.02	19.90	23.92	46.00	-22.08	Average
8	0.6030	9.10	19.90	29.00	56.00	-27.00	QP
9	0.6875	3.67	19.92	23.59	46.00	-22.41	Average
10	0.6875	8.70	19.92	28.62	56.00	-27.38	QP
11	1.0000	2.57	19.95	22.52	46.00	-23.48	Average
12	1.0000	7.56	19.95	27.51	56.00	-28.49	QP

Test Mode: 00; Line: Neutral Line

Test Data :



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.1895	7.68	19.94	27.62	54.06	-26.44	Average
2	0.1895	12.95	19.94	32.89	64.06	-31.17	QP
3	0.3180	15.88	19.92	35.80	49.76	-13.96	Average
4	0.3180	21.06	19.92	40.98	59.76	-18.78	QP
5	0.4772	14.58	19.89	34.47	46.39	-11.92	Average
6	0.4772	19.77	19.89	39.66	56.39	-16.73	QP
7	0.7973	3.27	19.92	23.19	46.00	-22.81	Average
8	0.7973	8.26	19.92	28.18	56.00	-27.82	QP
9	0.9291	2.78	19.88	22.66	46.00	-23.34	Average
10	0.9291	7.99	19.88	27.87	56.00	-28.13	QP
11	1.5040	0.21	19.90	20.11	46.00	-25.89	Average
12	1.5040	5.06	19.90	24.96	56.00	-31.04	QP

7.2 Radiated Emissions which fall in the restricted bands

Test Requirement 47 CFR Part 15, Subpart C 15.205 & 15.209

Test Method: ANSI C63.10 (2013) Section 6.10.5

Measurement Distance: 3M

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

7.2.1 E.U.T. Operation

Operating Environment:

Temperature: 23.3 °C


Humidity: 45.6 % RH

Atmospheric Pressure: 1010 mbar

7.2.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	00	TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); data rate @ 13.5Mbps is the worst case of IEEE 802.11n(HT40); data rate @ MCS0 is the worst case of IEEE 802.11ax(HE20); data rate @ MCS0 is the worst case of IEEE 802.11ax(HE40). Only the data of worst case is recorded in the report.

7.2.3 Test Setup Diagram



7.2.4 Measurement Procedure and Data

- a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- d. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- g. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- h. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- j. Repeat above procedures until all frequencies measured was complete.


Remark 1: $\text{Level} = \text{Read Level} + \text{Cable Loss} + \text{Antenna Factor} - \text{Preamp Factor}$

Remark 2: For frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.

Remark 3: The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 3MHz for Peak detection (PK) and Average detection (AV) at frequency above 1GHz.


Remark 4: For fundamental and harmonic signal measurement, the resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is $\geq 1/T$ (Duty cycle $< 98\%$) or 10Hz (Duty cycle $\geq 98\%$) for Average detection (AV) at frequency above 1GHz.

Test Mode: 00; Polarity: Horizontal; Modulation:802.11b; Bandwidth:20MHz; Channel:Low




No.	Frequency (MHz)	Reading (dBuV)	Correction factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2375.800	48.03	-0.86	47.17	74.00	-26.83	peak
2	2390.000	46.03	-0.79	45.24	74.00	-28.76	peak
3	2413.320	101.40	-0.68	100.72	74.00	26.72	peak

Test Mode: 00; Polarity: Vertical; Modulation:802.11b; Bandwidth:20MHz; Channel:Low




No.	Frequency (MHz)	Reading (dBuV)	Correction factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2371.740	49.40	-0.88	48.52	74.00	-25.48	peak
2	2390.000	46.22	-0.79	45.43	74.00	-28.57	peak
3	2411.080	103.02	-0.68	102.34	74.00	28.34	peak

Test Mode: 00; Polarity: Horizontal; Modulation:802.11b; Bandwidth:20MHz; Channel:High




No.	Frequency (MHz)	Reading (dBuV)	Correction factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2463.200	100.70	-0.43	100.27	74.00	26.27	peak
2	2483.500	47.03	-0.33	46.70	74.00	-27.30	peak
3	2491.250	52.77	-0.29	52.48	74.00	-21.52	peak
4	2500.000	46.72	-0.24	46.48	74.00	-27.52	peak

Test Mode: 00; Polarity: Vertical; Modulation:802.11b; Bandwidth:20MHz; Channel:High




No.	Frequency (MHz)	Reading (dBuV)	Correction factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2463.200	105.10	-0.43	104.67	74.00	30.67	peak
2	2483.500	51.69	-0.33	51.36	74.00	-22.64	peak
3	2487.050	52.80	-0.30	52.50	74.00	-21.50	peak
4	2500.000	47.94	-0.24	47.70	74.00	-26.30	peak

Test Mode: 00; Polarity: Horizontal; Modulation:802.11n; Bandwidth:20MHz; Channel:Low




Test Mode: 00; Polarity: Horizontal; Modulation:802.11n; Bandwidth:20MHz; Channel:Low




No.	Frequency (MHz)	Reading (dBuV)	Correction factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2388.400	43.66	-0.79	42.87	54.00	-11.13	AVG
2	2390.000	45.50	-0.79	44.71	54.00	-9.29	AVG
3	2412.900	97.43	-0.68	96.75	54.00	42.75	AVG

Test Mode: 00; Polarity: Vertical; Modulation:802.11n; Bandwidth:20MHz; Channel:Low




No.	Frequency (MHz)	Reading (dBuV)	Correction factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2387.000	74.51	-0.80	73.71	74.00	-0.29	peak
2	2390.000	73.49	-0.79	72.70	74.00	-1.30	peak
3	2410.800	110.58	-0.69	109.89	74.00	35.89	peak

Test Mode: 00; Polarity: Vertical; Modulation:802.11n; Bandwidth:20MHz; Channel:Low




No.	Frequency (MHz)	Reading (dBuV)	Correction factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2387.280	47.15	-0.80	46.35	54.00	-7.65	AVG
2	2390.000	50.87	-0.79	50.08	54.00	-3.92	AVG
3	2411.080	101.28	-0.68	100.60	54.00	46.60	AVG

Test Mode: 00; Polarity: Horizontal; Modulation:802.11n; Bandwidth:20MHz; Channel:High




Test Mode: 00; Polarity: Horizontal; Modulation:802.11n; Bandwidth:20MHz; Channel:High




No.	Frequency (MHz)	Reading (dBuV)	Correction factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2460.950	95.06	-0.44	94.62	54.00	40.62	AVG
2	2483.500	46.25	-0.33	45.92	54.00	-8.08	AVG
3	2485.250	43.22	-0.31	42.91	54.00	-11.09	AVG
4	2500.000	37.37	-0.24	37.13	54.00	-16.87	AVG

Test Mode: 00; Polarity: Vertical; Modulation:802.11n; Bandwidth:20MHz; Channel:High




No.	Frequency (MHz)	Reading (dBuV)	Correction factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2460.800	106.59	-0.44	106.15	74.00	32.15	peak
2	2483.500	70.58	-0.33	70.25	74.00	-3.75	peak
3	2490.350	73.81	-0.29	73.52	74.00	-0.48	peak
4	2500.000	61.43	-0.24	61.19	74.00	-12.81	peak

Test Mode: 00; Polarity: Vertical; Modulation:802.11n; Bandwidth:20MHz; Channel:High




No.	Frequency (MHz)	Reading (dBuV)	Correction factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2462.600	96.93	-0.43	96.50	54.00	42.50	AVG
2	2483.500	47.71	-0.33	47.38	54.00	-6.62	AVG
3	2484.200	46.61	-0.32	46.29	54.00	-7.71	AVG
4	2500.000	38.51	-0.24	38.27	54.00	-15.73	AVG

Test Mode: 00; Polarity: Horizontal; Modulation:802.11n; Bandwidth:40MHz; Channel:Low




Test Mode: 00; Polarity: Horizontal; Modulation:802.11n; Bandwidth:40MHz; Channel:Low




No.	Frequency (MHz)	Reading (dBuV)	Correction factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2387.700	46.17	-0.80	45.37	54.00	-8.63	AVG
2	2390.000	47.70	-0.79	46.91	54.00	-7.09	AVG
3	2420.320	91.67	-0.64	91.03	54.00	37.03	AVG

Test Mode: 00; Polarity: Vertical; Modulation:802.11n; Bandwidth:40MHz; Channel:Low




No.	Frequency (MHz)	Reading (dBuV)	Correction factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2388.260	71.80	-0.80	71.00	74.00	-3.00	peak
2	2390.000	74.64	-0.79	73.85	74.00	-0.15	peak
3	2418.220	105.81	-0.65	105.16	74.00	31.16	peak

Test Mode: 00; Polarity: Vertical; Modulation:802.11n; Bandwidth:40MHz; Channel:Low




No.	Frequency (MHz)	Reading (dBuV)	Correction factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2385.040	49.48	-0.81	48.67	54.00	-5.33	AVG
2	2390.000	52.55	-0.79	51.76	54.00	-2.24	AVG
3	2419.480	94.99	-0.64	94.35	54.00	40.35	AVG

Test Mode: 00; Polarity: Horizontal; Modulation:802.11n; Bandwidth:40MHz; Channel:High




No.	Frequency (MHz)	Reading (dBuV)	Correction factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2457.200	101.27	-0.45	100.82	74.00	26.82	peak
2	2483.500	71.06	-0.33	70.73	74.00	-3.27	peak
3	2500.000	60.02	-0.24	59.78	74.00	-14.22	peak
4	2506.840	57.27	-0.20	57.07	74.00	-16.93	peak

Test Mode: 00; Polarity: Horizontal; Modulation:802.11n; Bandwidth:40MHz; Channel:High




No.	Frequency (MHz)	Reading (dBuV)	Correction factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2449.890	91.28	-0.49	90.79	54.00	36.79	AVG
2	2483.500	50.82	-0.33	50.49	54.00	-3.51	AVG
3	2489.500	45.69	-0.29	45.40	54.00	-8.60	AVG
4	2500.000	38.26	-0.24	38.02	54.00	-15.98	AVG

Test Mode: 00; Polarity: Vertical; Modulation:802.11n; Bandwidth:40MHz; Channel:High




No.	Frequency (MHz)	Reading (dBuV)	Correction factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2449.210	103.83	-0.49	103.34	74.00	29.34	peak
2	2483.500	71.06	-0.33	70.73	74.00	-3.27	peak
3	2495.790	70.01	-0.26	69.75	74.00	-4.25	peak
4	2500.000	60.50	-0.24	60.26	74.00	-13.74	peak

Test Mode: 00; Polarity: Vertical; Modulation:802.11n; Bandwidth:40MHz; Channel:High




No.	Frequency (MHz)	Reading (dBuV)	Correction factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2449.210	93.89	-0.49	93.40	54.00	39.40	AVG
2	2483.500	51.81	-0.33	51.48	54.00	-2.52	AVG
3	2486.270	50.03	-0.31	49.72	54.00	-4.28	AVG
4	2500.000	39.36	-0.24	39.12	54.00	-14.88	AVG

Test Mode: 00; Polarity: Horizontal; Modulation:802.11ax(Full RU0); Bandwidth:20MHz; Channel:Low




No.	Frequency (MHz)	Reading (dBuV)	Correction factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2387.420	65.89	-0.80	65.09	74.00	-8.91	peak
2	2390.000	65.25	-0.79	64.46	74.00	-9.54	peak
3	2412.760	105.65	-0.68	104.97	74.00	30.97	peak

Test Mode: 00; Polarity: Horizontal; Modulation:802.11ax(Full RU0); Bandwidth:20MHz; Channel:Low




No.	Frequency (MHz)	Reading (dBuV)	Correction factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2387.140	39.97	-0.80	39.17	54.00	-14.83	AVG
2	2390.000	42.10	-0.79	41.31	54.00	-12.69	AVG
3	2411.220	95.02	-0.68	94.34	54.00	40.34	AVG

Test Mode: 00; Polarity: Vertical; Modulation:802.11ax(Full RU0); Bandwidth:20MHz; Channel:Low




No.	Frequency (MHz)	Reading (dBuV)	Correction factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2388.960	73.86	-0.79	73.07	74.00	-0.93	peak
2	2390.000	67.81	-0.79	67.02	74.00	-6.98	peak
3	2410.380	109.86	-0.69	109.17	74.00	35.17	peak

Test Mode: 00; Polarity: Vertical; Modulation:802.11ax(Full RU0); Bandwidth:20MHz; Channel:Low




No.	Frequency (MHz)	Reading (dBuV)	Correction factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2387.280	44.19	-0.80	43.39	54.00	-10.61	AVG
2	2390.000	46.58	-0.79	45.79	54.00	-8.21	AVG
3	2411.360	98.64	-0.68	97.96	54.00	43.96	AVG

Test Mode: 00; Polarity: Horizontal; Modulation:802.11ax(Full RU0); Bandwidth:20MHz; Channel:High




No.	Frequency (MHz)	Reading (dBuV)	Correction factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2462.450	106.76	-0.43	106.33	74.00	32.33	peak
2	2483.500	72.28	-0.33	71.95	74.00	-2.05	peak
3	2485.850	72.48	-0.31	72.17	74.00	-1.83	peak
4	2500.000	59.77	-0.24	59.53	74.00	-14.47	peak

Test Mode: 00; Polarity: Horizontal; Modulation:802.11ax(Full RU0); Bandwidth:20MHz; Channel:High




No.	Frequency (MHz)	Reading (dBuV)	Correction factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2463.350	94.67	-0.43	94.24	54.00	40.24	AVG
2	2483.500	46.87	-0.33	46.54	54.00	-7.46	AVG
3	2484.650	45.61	-0.32	45.29	54.00	-8.71	AVG
4	2500.000	37.45	-0.24	37.21	54.00	-16.79	AVG

Test Mode: 00; Polarity: Vertical; Modulation:802.11ax(Full RU0); Bandwidth:20MHz; Channel:High




No.	Frequency (MHz)	Reading (dBuV)	Correction factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2457.050	108.07	-0.45	107.62	74.00	33.62	peak
2	2483.500	70.32	-0.33	69.99	74.00	-4.01	peak
3	2486.750	73.19	-0.30	72.89	74.00	-1.11	peak
4	2500.000	60.45	-0.24	60.21	74.00	-13.79	peak

Test Mode: 00; Polarity: Vertical; Modulation:802.11ax(Full RU0); Bandwidth:20MHz; Channel:High




Test Mode: 00; Polarity: Horizontal; Modulation:802.11ax(Full RU0); Bandwidth:40MHz; Channel:Low




No.	Frequency (MHz)	Reading (dBuV)	Correction factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2387.700	67.66	-0.80	66.86	74.00	-7.14	peak
2	2390.000	68.68	-0.79	67.89	74.00	-6.11	peak
3	2424.380	103.79	-0.62	103.17	74.00	29.17	peak

Test Mode: 00; Polarity: Horizontal; Modulation: 802.11ax(Full RU0); Bandwidth: 40MHz; Channel: Low




No.	Frequency (MHz)	Reading (dBuV)	Correction factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2387.420	44.49	-0.80	43.69	54.00	-10.31	AVG
2	2390.000	45.89	-0.79	45.10	54.00	-8.90	AVG
3	2421.020	91.08	-0.64	90.44	54.00	36.44	AVG

Test Mode: 00; Polarity: Vertical; Modulation:802.11ax(Full RU0); Bandwidth:40MHz; Channel:Low




Test Mode: 00; Polarity: Vertical; Modulation:802.11ax(Full RU0); Bandwidth:40MHz; Channel:Low




No.	Frequency (MHz)	Reading (dBuV)	Correction factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2384.760	47.20	-0.82	46.38	54.00	-7.62	AVG
2	2390.000	50.88	-0.79	50.09	54.00	-3.91	AVG
3	2419.620	94.27	-0.64	93.63	54.00	39.63	AVG

Test Mode: 00; Polarity: Horizontal; Modulation:802.11ax(Full RU0); Bandwidth:40MHz; Channel:High




No.	Frequency (MHz)	Reading (dBuV)	Correction factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2449.380	104.20	-0.49	103.71	74.00	29.71	peak
2	2483.500	70.77	-0.33	70.44	74.00	-3.56	peak
3	2491.880	67.23	-0.28	66.95	74.00	-7.05	peak
4	2500.000	58.26	-0.24	58.02	74.00	-15.98	peak

Test Mode: 00; Polarity: Horizontal; Modulation:802.11ax(Full RU0); Bandwidth:40MHz; Channel:High




Test Mode: 00; Polarity: Vertical; Modulation:802.11ax(Full RU0); Bandwidth:40MHz; Channel:High



No.	Frequency (MHz)	Reading (dBuV)	Correction factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2447.170	105.52	-0.50	105.02	74.00	31.02	peak
2	2483.500	73.17	-0.33	72.84	74.00	-1.16	peak
3	2486.780	70.83	-0.30	70.53	74.00	-3.47	peak
4	2500.000	63.93	-0.24	63.69	74.00	-10.31	peak

Test Mode: 00; Polarity: Vertical; Modulation:802.11ax(Full RU0); Bandwidth:40MHz; Channel:High



No.	Frequency (MHz)	Reading (dBuV)	Correction factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2450.060	93.39	-0.49	92.90	54.00	38.90	AVG
2	2483.500	50.37	-0.33	50.04	54.00	-3.96	AVG
3	2485.420	49.72	-0.31	49.41	54.00	-4.59	AVG
4	2500.000	39.21	-0.24	38.97	54.00	-15.03	AVG

7.3 Radiated Spurious Emissions Below 1GHz

Test Requirement 47 CFR Part 15, Subpart C 15.205 & 15.209

Test Method: ANSI C63.10 (2013) Section 6.4,6.5

Measurement Distance: 3M

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
960-1000	500	3

7.3.1 E.U.T. Operation

Operating Environment:

Temperature: 23.3 °C


Humidity: 45.6 % RH

Atmospheric Pressure: 1010 mbar

7.3.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	00	TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); data rate @ 13.5Mbps is the worst case of IEEE 802.11n(HT40); data rate @ MCS0 is the worst case of IEEE 802.11ax(HE20); data rate @ MCS0 is the worst case of IEEE 802.11ax(HE40). Only the data of worst case is recorded in the report.

7.3.3 Test Setup Diagram



7.3.4 Measurement Procedure and Data


- For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using quasi-peak method as specified and then reported in a data sheet.
- Test the EUT in the lowest channel, the middle channel, the Highest channel.
- The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- Repeat above procedures until all frequencies measured was complete.

Remark:

- Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor
- Scan from 9kHz to 30MHz, the disturbance below 30MHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.

Test Mode: 00; Polarity: Horizontal


Test Data :



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Degree (deg.)	Remark
1	30.0000	5.96	19.42	25.38	40.00	-14.62	100	353	QP
2	51.8430	20.79	6.74	27.53	40.00	-12.47	200	18	QP
3	64.6590	21.46	6.45	27.91	40.00	-12.09	200	360	QP
4	104.5360	16.85	13.14	29.99	43.50	-13.51	100	318	QP
5	178.7580	12.11	11.96	24.07	43.50	-19.43	200	91	QP
6	282.9850	11.29	15.58	26.87	46.00	-19.13	100	331	QP

Test Mode: 00; Polarity: Vertical

Test Data :



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Degree (deg.)	Remark
1	38.8879	22.14	11.83	33.97	40.00	-6.03	100	349	QP
2	51.8430	30.76	6.74	37.50	40.00	-2.50	100	356	QP
3	53.8818	30.26	6.65	36.91	40.00	-3.09	100	360	QP
4	77.0505	26.11	9.72	35.83	40.00	-4.17	100	360	QP
5	88.6525	24.65	11.50	36.15	43.50	-7.35	100	360	QP
6	104.5360	27.16	13.14	40.30	43.50	-3.20	100	360	QP

7.4 Radiated Spurious Emissions Above 1GHz

Test Requirement 47 CFR Part 15, Subpart C 15.205 & 15.209

Test Method: ANSI C63.10 (2013) Section 6.6

Measurement Distance: 3M

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
Above 1000	500	3

7.4.1 E.U.T. Operation

Operating Environment:

Temperature: 23.3 °C


Humidity: 45.6 % RH

Atmospheric Pressure: 1010 mbar

7.4.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	00	TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); data rate @ 13.5Mbps is the worst case of IEEE 802.11n(HT40); data rate @ MCS0 is the worst case of IEEE 802.11ax(HE20); data rate @ MCS0 is the worst case of IEEE 802.11ax(HE40). Only the data of worst case is recorded in the report.

7.4.3 Test Setup Diagram




7.4.4 Measurement Procedure and Data

- a. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak or average method as specified and then reported in a data sheet.
- g. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- i. Repeat above procedures until all frequencies measured was complete.

Remark:


1. Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor
2. Scan from 1GHz to 25GHz, the disturbance above 18GHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.
3. As shown in this section, for frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 3MHz for Peak detection (PK) and Average detection (AV) at frequency above 1GHz.
- 5:For fundamental and harmonic signal measurement, the resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is $\geq 1/T$ (Duty cycle<98%) or 10Hz (Duty cycle $\geq$ 98%) for Average detection (AV) at frequency above 1GHz.

Test Mode: 00; Polarity: Horizontal; Modulation:802.11b; Bandwidth:20MHz; Channel:Low




No.	Frequency (MHz)	Reading (dBuV)	Correction factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4824.150	71.53	-16.97	54.56	74.00	-19.44	peak
2	4824.150	70.65	-16.97	53.68	54.00	-0.32	AVG
3	9489.800	55.22	-6.55	48.67	74.00	-25.33	peak
4	12493.700	55.27	-6.16	49.11	74.00	-24.89	peak

Test Mode: 00; Polarity: Vertical; Modulation:802.11b; Bandwidth:20MHz; Channel:Low




No.	Frequency (MHz)	Reading (dBuV)	Correction factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4824.150	65.98	-16.97	49.01	74.00	-24.99	peak
2	8859.950	57.14	-8.03	49.11	74.00	-24.89	peak
3	10417.150	56.05	-5.93	50.12	74.00	-23.88	peak

Test Mode: 00; Polarity: Horizontal; Modulation:802.11b; Bandwidth:20MHz; Channel:middle




No.	Frequency (MHz)	Reading (dBuV)	Correction factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4874.300	68.57	-16.87	51.70	74.00	-22.30	peak
2	9356.350	56.63	-6.89	49.74	74.00	-24.26	peak
3	12791.200	55.20	-6.00	49.20	74.00	-24.80	peak

Test Mode: 00; Polarity: Vertical; Modulation:802.11b; Bandwidth:20MHz; Channel:middle




No.	Frequency (MHz)	Reading (dBuV)	Correction factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4874.300	65.16	-16.87	48.29	74.00	-25.71	peak
2	9222.050	57.02	-7.23	49.79	74.00	-24.21	peak
3	12799.700	55.62	-6.00	49.62	74.00	-24.38	peak

Test Mode: 00; Polarity: Horizontal; Modulation:802.11b; Bandwidth:20MHz; Channel:High




No.	Frequency (MHz)	Reading (dBuV)	Correction factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4924.450	66.34	-16.78	49.56	74.00	-24.44	peak
2	9723.550	56.73	-5.96	50.77	74.00	-23.23	peak
3	13421.900	55.30	-5.58	49.72	74.00	-24.28	peak

Test Mode: 00; Polarity: Vertical; Modulation:802.11b; Bandwidth:20MHz; Channel:High




No.	Frequency (MHz)	Reading (dBuV)	Correction factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4923.600	62.57	-16.79	45.78	74.00	-28.22	peak
2	10102.650	56.31	-5.66	50.65	74.00	-23.35	peak
3	12062.750	55.67	-6.39	49.28	74.00	-24.72	peak

Test Mode: 00; Polarity: Horizontal; Modulation:802.11n; Bandwidth:20MHz; Channel:Low




No.	Frequency (MHz)	Reading (dBuV)	Correction factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4821.600	68.08	-16.98	51.10	74.00	-22.90	peak
2	9375.900	55.79	-6.84	48.95	74.00	-25.05	peak
3	12119.700	55.40	-6.35	49.05	74.00	-24.95	peak

Test Mode: 00; Polarity: Vertical; Modulation:802.11n; Bandwidth:20MHz; Channel:Low




No.	Frequency (MHz)	Reading (dBuV)	Correction factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4825.000	62.39	-16.97	45.42	74.00	-28.58	peak
2	8174.000	56.67	-9.02	47.65	74.00	-26.35	peak
3	9940.300	55.40	-5.60	49.80	74.00	-24.20	peak

Test Mode: 00; Polarity: Horizontal; Modulation:802.11n; Bandwidth:20MHz; Channel:middle




No.	Frequency (MHz)	Reading (dBuV)	Correction factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5459.950	57.30	-15.87	41.43	74.00	-32.57	peak
2	8446.000	56.12	-8.63	47.49	74.00	-26.51	peak
3	10402.700	55.33	-5.92	49.41	74.00	-24.59	peak

Test Mode: 00; Polarity: Vertical; Modulation:802.11n; Bandwidth:20MHz; Channel:middle




No.	Frequency (MHz)	Reading (dBuV)	Correction factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5290.800	57.47	-16.15	41.32	74.00	-32.68	peak
2	7306.150	57.77	-10.01	47.76	74.00	-26.24	peak
3	10053.350	55.60	-5.62	49.98	74.00	-24.02	peak

Test Mode: 00; Polarity: Horizontal; Modulation:802.11n; Bandwidth:20MHz; Channel:High




No.	Frequency (MHz)	Reading (dBuV)	Correction factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4924.450	61.28	-16.78	44.50	74.00	-29.50	peak
2	9845.950	54.82	-5.65	49.17	74.00	-24.83	peak
3	14811.650	54.48	-4.93	49.55	74.00	-24.45	peak

Test Mode: 00; Polarity: Vertical; Modulation:802.11n; Bandwidth:20MHz; Channel:High




No.	Frequency (MHz)	Reading (dBuV)	Correction factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4921.050	59.83	-16.79	43.04	74.00	-30.96	peak
2	9401.400	56.05	-6.77	49.28	74.00	-24.72	peak
3	10650.900	54.88	-6.12	48.76	74.00	-25.24	peak

Test Mode: 00; Polarity: Horizontal; Modulation:802.11n; Bandwidth:40MHz; Channel:Low




No.	Frequency (MHz)	Reading (dBuV)	Correction factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4845.400	62.97	-16.93	46.04	74.00	-27.96	peak
2	8945.800	55.63	-7.90	47.73	74.00	-26.27	peak
3	12935.700	55.40	-5.92	49.48	74.00	-24.52	peak

Test Mode: 00; Polarity: Vertical; Modulation:802.11n; Bandwidth:40MHz; Channel:Low




No.	Frequency (MHz)	Reading (dBuV)	Correction factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5363.900	57.16	-16.03	41.13	74.00	-32.87	peak
2	8151.900	56.18	-9.05	47.13	74.00	-26.87	peak
3	9950.500	55.03	-5.60	49.43	74.00	-24.57	peak

Test Mode: 00; Polarity: Horizontal; Modulation:802.11n; Bandwidth:40MHz; Channel:middle




No.	Frequency (MHz)	Reading (dBuV)	Correction factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4799.500	60.68	-17.01	43.67	74.00	-30.33	peak
2	10409.500	55.00	-5.92	49.08	74.00	-24.92	peak
3	14541.350	54.48	-5.17	49.31	74.00	-24.69	peak

Test Mode: 00; Polarity: Vertical; Modulation:802.11n; Bandwidth:40MHz; Channel:middle




No.	Frequency (MHz)	Reading (dBuV)	Correction factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5009.450	57.85	-16.62	41.23	74.00	-32.77	peak
2	7862.900	56.56	-9.46	47.10	74.00	-26.90	peak
3	10332.150	55.16	-5.86	49.30	74.00	-24.70	peak

Test Mode: 00; Polarity: Horizontal; Modulation:802.11n; Bandwidth:40MHz; Channel:High




No.	Frequency (MHz)	Reading (dBuV)	Correction factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	6943.200	55.71	-10.16	45.55	74.00	-28.45	peak
2	8156.150	56.33	-9.05	47.28	74.00	-26.72	peak
3	9808.550	55.39	-5.74	49.65	74.00	-24.35	peak

Test Mode: 00; Polarity: Vertical; Modulation:802.11n; Bandwidth:40MHz; Channel:High




No.	Frequency (MHz)	Reading (dBuV)	Correction factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5800.800	56.65	-14.66	41.99	74.00	-32.01	peak
2	9823.000	55.10	-5.71	49.39	74.00	-24.61	peak
3	12785.250	55.22	-6.00	49.22	74.00	-24.78	peak

Test Mode: 00; Polarity: Horizontal; Modulation:802.11ax(Full RU0); Bandwidth:20MHz; Channel:Low




No.	Frequency (MHz)	Reading (dBuV)	Correction factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4821.600	65.92	-16.98	48.94	74.00	-25.06	peak
2	8208.000	55.49	-8.98	46.51	74.00	-27.49	peak
3	10695.100	55.70	-6.15	49.55	74.00	-24.45	peak

Test Mode: 00; Polarity: Vertical; Modulation:802.11ax(Full RU0); Bandwidth:20MHz; Channel:Low




No.	Frequency (MHz)	Reading (dBuV)	Correction factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4819.900	61.37	-16.98	44.39	74.00	-29.61	peak
2	7236.450	56.29	-10.03	46.26	74.00	-27.74	peak
3	9720.150	54.95	-5.97	48.98	74.00	-25.02	peak

Test Mode: 00; Polarity: Horizontal; Modulation:802.11ax(Full RU0); Bandwidth:20MHz; Channel:middle




No.	Frequency (MHz)	Reading (dBuV)	Correction factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4876.000	64.64	-16.87	47.77	74.00	-26.23	peak
2	7298.500	56.99	-10.01	46.98	74.00	-27.02	peak
3	12420.600	55.57	-6.20	49.37	74.00	-24.63	peak

Test Mode: 00; Polarity: Vertical; Modulation:802.11ax(Full RU0); Bandwidth:20MHz; Channel:middle




No.	Frequency (MHz)	Reading (dBuV)	Correction factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7300.200	58.35	-10.01	48.34	74.00	-25.66	peak
2	9930.100	55.57	-5.61	49.96	74.00	-24.04	peak
3	12854.100	55.62	-5.97	49.65	74.00	-24.35	peak

Test Mode: 00; Polarity: Horizontal; Modulation:802.11ax(Full RU0); Bandwidth:20MHz; Channel:High




No.	Frequency (MHz)	Reading (dBuV)	Correction factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7752.400	56.55	-9.59	46.96	74.00	-27.04	peak
2	10038.900	55.82	-5.61	50.21	74.00	-23.79	peak
3	12864.300	54.54	-5.96	48.58	74.00	-25.42	peak

Test Mode: 00; Polarity: Vertical; Modulation:802.11ax(Full RU0); Bandwidth:20MHz; Channel:High




No.	Frequency (MHz)	Reading (dBuV)	Correction factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	6827.600	55.79	-10.31	45.48	74.00	-28.52	peak
2	9018.900	55.96	-7.74	48.22	74.00	-25.78	peak
3	12463.950	55.02	-6.18	48.84	74.00	-25.16	peak

Test Mode: 00; Polarity: Horizontal; Modulation:802.11ax(Full RU0); Bandwidth:40MHz; Channel:Low




No.	Frequency (MHz)	Reading (dBuV)	Correction factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4836.900	65.50	-16.95	48.55	74.00	-25.45	peak
2	8210.550	56.40	-8.97	47.43	74.00	-26.57	peak
3	12070.400	55.65	-6.38	49.27	74.00	-24.73	peak

Test Mode: 00; Polarity: Vertical; Modulation:802.11ax(Full RU0); Bandwidth:40MHz; Channel:Low




No.	Frequency (MHz)	Reading (dBuV)	Correction factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7731.150	56.53	-9.61	46.92	74.00	-27.08	peak
2	10048.250	55.79	-5.61	50.18	74.00	-23.82	peak
3	12424.000	54.94	-6.19	48.75	74.00	-25.25	peak

Test Mode: 00; Polarity: Horizontal; Modulation:802.11ax(Full RU0); Bandwidth:40MHz; Channel:middle




No.	Frequency (MHz)	Reading (dBuV)	Correction factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	6062.600	56.99	-13.52	43.47	74.00	-30.53	peak
2	8528.450	56.01	-8.51	47.50	74.00	-26.50	peak
3	12110.350	55.61	-6.36	49.25	74.00	-24.75	peak

Test Mode: 00; Polarity: Vertical; Modulation:802.11ax(Full RU0); Bandwidth:40MHz; Channel:middle




No.	Frequency (MHz)	Reading (dBuV)	Correction factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5193.050	57.85	-16.32	41.53	74.00	-32.47	peak
2	6896.450	56.01	-10.22	45.79	74.00	-28.21	peak
3	9504.250	56.52	-6.52	50.00	74.00	-24.00	peak

Test Mode: 00; Polarity: Horizontal; Modulation:802.11ax(Full RU0); Bandwidth:40MHz; Channel:High



No.	Frequency (MHz)	Reading (dBuV)	Correction factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5116.550	58.88	-16.44	42.44	74.00	-31.56	peak
2	9529.750	56.01	-6.44	49.57	74.00	-24.43	peak
3	13013.050	54.63	-5.87	48.76	74.00	-25.24	peak

Test Mode: 00; Polarity: Vertical; Modulation:802.11ax(Full RU0); Bandwidth:40MHz; Channel:High



No.	Frequency (MHz)	Reading (dBuV)	Correction factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	6926.200	55.80	-10.18	45.62	74.00	-28.38	peak
2	9377.600	56.90	-6.84	50.06	74.00	-23.94	peak
3	12122.250	54.95	-6.35	48.60	74.00	-25.40	peak

7.5 Conducted Average Output Power

Test Requirement 47 CFR Part 15, Subpart C 15.247(b)(3)

Test Method: ANSI C63.10 (2013) Section 11.9.2

Limit:

Frequency range(MHz)	Output power of the intentional radiator(watt)
902-928	1 for ≥ 50 hopping channels
	0.25 for $25 \leq$ hopping channels < 50
	1 for digital modulation
2400-2483.5	1 for ≥ 75 non-overlapping hopping channels
	0.125 for all other frequency hopping systems
	1 for digital modulation
5725-5850	1 for frequency hopping systems and digital modulation

7.5.1 E.U.T. Operation

Operating Environment:

Temperature: 25.3 °C


Humidity: 46.3 % RH

Atmospheric Pressure: 1010 mbar

7.5.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	00	TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); data rate @ 13.5Mbps is the worst case of IEEE 802.11n(HT40); data rate @ MCS0 is the worst case of IEEE 802.11ax(HE20); data rate @ MCS0 is the worst case of IEEE 802.11ax(HE40). Only the data of worst case is recorded in the report.

7.5.3 Test Setup Diagram



7.5.4 Measurement Procedure and Data

Note: Since the verify power the same operating range bandwidth and smaller power can be covered by the higher power.

Please Refer to Appendix for Details

7.6 Minimum 6dB Bandwidth

Test Requirement 47 CFR Part 15, Subpart C 15.247a(2)

Test Method: ANSI C63.10 (2013) Section 11.8.1

Limit:

≥500 kHz

7.6.1 E.U.T. Operation

Operating Environment:

Temperature: 25.3 °C

Humidity: 46.3 % RH

Atmospheric Pressure: 1010 mbar

7.6.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	00	TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); data rate @ 13.5Mbps is the worst case of IEEE 802.11n(HT40); data rate @ MCS0 is the worst case of IEEE 802.11ax(HE20); data rate @ MCS0 is the worst case of IEEE 802.11ax(HE40). Only the data of worst case is recorded in the report.

7.6.3 Measurement Procedure and Data

Please Refer to Appendix for Details

7.7 Power Spectrum Density

Test Requirement 47 CFR Part 15, Subpart C 15.247(e)

Test Method: ANSI C63.10 (2013) Section 11.10.2

Limit:

≤8dBm in any 3 kHz band during any time interval of continuous transmission

7.7.1 E.U.T. Operation

Operating Environment:

Temperature: 25.3 °C

Humidity: 46.3 % RH

Atmospheric Pressure: 1010 mbar

7.7.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	00	TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); data rate @ 13.5Mbps is the worst case of IEEE 802.11n(HT40); data rate @ MCS0 is the worst case of IEEE 802.11ax(HE20); data rate @ MCS0 is the worst case of IEEE 802.11ax(HE40). Only the data of worst case is recorded in the report.

7.7.3 Measurement Procedure and Data

Please Refer to Appendix for Details

7.8 Conducted Band Edges Measurement

Test Requirement 47 CFR Part 15, Subpart C 15.247(d)
Test Method: ANSI C63.10 (2013) Section 11.13.3.2

Limit:

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

7.8.1 E.U.T. Operation

Operating Environment:

Temperature: 25.3 °C

Humidity: 46.3 % RH

Atmospheric Pressure: 1010 mbar

7.8.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	00	TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); data rate @ 13.5Mbps is the worst case of IEEE 802.11n(HT40); data rate @ MCS0 is the worst case of IEEE 802.11ax(HE20); data rate @ MCS0 is the worst case of IEEE 802.11ax(HE40). Only the data of worst case is recorded in the report.

7.8.3 Measurement Procedure and Data

Please Refer to Appendix for Details

7.9 Conducted Spurious Emissions

Test Requirement 47 CFR Part 15, Subpart C 15.247(d)

Test Method: ANSI C63.10 (2013) Section 11.11

Limit:

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

7.9.1 E.U.T. Operation

Operating Environment:

Temperature: 25.3 °C

Humidity: 46.3 % RH

Atmospheric Pressure: 1010 mbar

7.9.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	00	TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); data rate @ 13.5Mbps is the worst case of IEEE 802.11n(HT40); data rate @ MCS0 is the worst case of IEEE 802.11ax(HE20); data rate @ MCS0 is the worst case of IEEE 802.11ax(HE40). Only the data of worst case is recorded in the report.

7.9.3 Measurement Procedure and Data

Please Refer to Appendix for Details



Report No.: KSCR250300035401

Page: 96 of 172

8 Test Setup Photo

Refer to Appendix - Test Setup Photo for KSCR2503000354AT

9 EUT Constructional Details (EUT Photos)

Refer to Appendix_Photographs of EUT Constructional Details for KSCR2503000354AT

10 Appendix

1. Duty Cycle

1.1 Test Result


1.1.1 Ant1

Ant1									
Mode	TX Type	Frequency (MHz)	RU	RU Pos	T_on (ms)	Period (ms)	Duty Cycle (%)	Duty Cycle Correction Factor (dB)	Max. DC Variation (%)
802.11b	SISO	2412	/	/	12.224	12.434	98.31	0.07	0.03
		2437	/	/	12.223	12.433	98.31	0.07	0.03
		2462	/	/	12.223	12.433	98.31	0.07	0.03
802.11g	SISO	2412	/	/	2.032	2.245	90.51	0.43	0.00
		2437	/	/	2.032	2.245	90.51	0.43	0.04
		2462	/	/	2.032	2.245	90.51	0.43	0.04
802.11n (HT20)	SISO	2412	/	/	1.892	2.105	89.88	0.46	0.03
		2437	/	/	1.892	2.105	89.88	0.46	0.03
		2462	/	/	1.892	2.104	89.92	0.46	0.03
802.11n (HT40)	SISO	2422	/	/	0.932	1.144	81.47	0.89	0.06
		2437	/	/	0.932	1.145	81.40	0.89	0.03
		2452	/	/	0.932	1.145	81.40	0.89	0.03
802.11ax (HEW20)	SISO	2412	SU	/	1.459	1.671	87.31	0.59	0.03
		2437	SU	/	1.458	1.671	87.25	0.59	0.03
		2462	SU	/	1.458	1.671	87.25	0.59	0.03
802.11ax (HEW40)	SISO	2422	SU	/	0.759	0.972	78.09	1.07	0.03
		2437	SU	/	0.759	0.972	78.09	1.07	0.00
		2452	SU	/	0.759	0.972	78.09	1.07	0.03


1.2 Test Graph

1.2.1 Ant1


802.11b_LCH_2412MHz_Ant1 (SISO)_NTNV




802.11b_MCH_2437MHz_Ant1 (SISO)_NTNV




802.11b_HCH_2462MHz_Ant1 (SISO)_NTNV




802.11g_LCH_2412MHz_Ant1 (SISO)_NTNV




802.11g_MCH_2437MHz_Ant1 (SISO)_NTNV




802.11g_HCH_2462MHz_Ant1 (SISO)_NTNV




802.11n(HT20)_LCH_2412MHz_Ant1 (SISO)_NTNV




802.11n(HT20)_MCH_2437MHz_Ant1 (SISO)_NTNV




802.11n(HT20)_HCH_2462MHz_Ant1 (SISO)_NTNV




802.11n(HT40)_LCH_2422MHz_Ant1 (SISO)_NTNV




802.11n(HT40)_MCH_2437MHz_Ant1 (SISO)_NTNV




802.11n(HT40)_HCH_2452MHz_Ant1 (SISO)_NTNV




802.11ax(HEW20)_LCH_2412MHz_SU / _Ant1 (SISO)_NTNV




802.11ax(HEW20)_MCH_2437MHz_SU / _Ant1 (SISO)_NTNV




802.11ax(HEW20)_HCH_2462MHz_SU_/_Ant1 (SISO)_NTNV




802.11ax(HEW40)_LCH_2422MHz_SU_/_Ant1 (SISO)_NTNV



802.11ax(HEW40)_MCH_2437MHz_SU_/_Ant1 (SISO)_NTNV



802.11ax(HEW40)_HCH_2452MHz_SU_/_Ant1 (SISO)_NTNV



2. Bandwidth

2.1 Test Result

2.1.1 OBW

Mode	TX Type	Frequency (MHz)	RU	RU Pos	ANT	99% Occupied Bandwidth (MHz)		Verdict
						Result	Limit	
802.11b	SISO	2412	/	/	1	13.976	/	Pass
		2437	/	/	1	13.987	/	Pass
		2462	/	/	1	13.982	/	Pass
802.11g	SISO	2412	/	/	1	16.416	/	Pass
		2437	/	/	1	16.424	/	Pass
		2462	/	/	1	16.457	/	Pass
802.11n (HT20)	SISO	2412	/	/	1	17.421	/	Pass
		2437	/	/	1	17.347	/	Pass
		2462	/	/	1	17.372	/	Pass
802.11n (HT40)	SISO	2422	/	/	1	35.332	/	Pass
		2437	/	/	1	35.427	/	Pass
		2452	/	/	1	35.443	/	Pass
802.11ax (HEW20)	SISO	2412	SU	/	1	18.168	/	Pass
		2437	SU	/	1	18.230	/	Pass
		2462	SU	/	1	18.137	/	Pass
802.11ax (HEW40)	SISO	2422	SU	/	1	36.435	/	Pass
		2437	SU	/	1	36.465	/	Pass
		2452	SU	/	1	36.398	/	Pass

2.1.2 6dB BW


Mode	TX Type	Frequency (MHz)	RU	RU Pos	ANT	6dB Bandwidth (MHz)		Verdict
						Result	Limit	
802.11b	SISO	2412	/	/	1	9.568	≥ 0.5	Pass
		2437	/	/	1	9.121	≥ 0.5	Pass
		2462	/	/	1	9.577	≥ 0.5	Pass
802.11g	SISO	2412	/	/	1	13.837	≥ 0.5	Pass
		2437	/	/	1	13.810	≥ 0.5	Pass
		2462	/	/	1	13.844	≥ 0.5	Pass
802.11n (HT20)	SISO	2412	/	/	1	13.844	≥ 0.5	Pass
		2437	/	/	1	13.853	≥ 0.5	Pass
		2462	/	/	1	13.840	≥ 0.5	Pass
802.11n (HT40)	SISO	2422	/	/	1	31.354	≥ 0.5	Pass
		2437	/	/	1	31.357	≥ 0.5	Pass

		2452	/	/	1	31.339	≥ 0.5	Pass
802.11ax (HEW20)	SISO	2412	SU	/	1	12.674	≥ 0.5	Pass
		2437	SU	/	1	13.856	≥ 0.5	Pass
		2462	SU	/	1	13.854	≥ 0.5	Pass
802.11ax (HEW40)	SISO	2422	SU	/	1	31.342	≥ 0.5	Pass
		2437	SU	/	1	31.363	≥ 0.5	Pass
		2452	SU	/	1	31.365	≥ 0.5	Pass


2.2 Test Graph

2.2.1 OBW


802.11b_LCH_2412MHz_Ant1 (SISO)_NTNV




802.11b_MCH_2437MHz_Ant1 (SISO)_NTNV




802.11b_HCH_2462MHz_Ant1 (SISO)_NTNV




802.11g_LCH_2412MHz_Ant1 (SISO)_NTNV




802.11g_MCH_2437MHz_Ant1 (SISO)_NTNV




802.11g_HCH_2462MHz_Ant1 (SISO)_NTNV




802.11n(HT20)_LCH_2412MHz_Ant1 (SISO)_NTNV




802.11n(HT20)_MCH_2437MHz_Ant1 (SISO)_NTNV




802.11n(HT20)_HCH_2462MHz_Ant1 (SISO)_NTNV




802.11n(HT40)_LCH_2422MHz_Ant1 (SISO)_NTNV




802.11n(HT40)_MCH_2437MHz_Ant1 (SISO)_NTNV




802.11n(HT40)_HCH_2452MHz_Ant1 (SISO)_NTNV




802.11ax(HEW20)_LCH_2412MHz_SU / _Ant1 (SISO)_NTNV




802.11ax(HEW20)_MCH_2437MHz_SU / _Ant1 (SISO)_NTNV




802.11ax(HEW20)_HCH_2462MHz_SU / _Ant1 (SISO)_NTNV




802.11ax(HEW40)_LCH_2422MHz_SU / _Ant1 (SISO)_NTNV



802.11ax(HEW40)_MCH_2437MHz_SU_/_Ant1 (SISO)_NTNV




802.11ax(HEW40)_HCH_2452MHz_SU_/_Ant1 (SISO)_NTNV




2.2.2 6dB BW


802.11b_LCH_2412MHz_Ant1 (SISO)_NTNV




802.11b_MCH_2437MHz_Ant1 (SISO)_NTNV




802.11b_HCH_2462MHz_Ant1 (SISO)_NTNV




802.11g_LCH_2412MHz_Ant1 (SISO)_NTNV




802.11g_MCH_2437MHz_Ant1 (SISO)_NTNV




802.11g_HCH_2462MHz_Ant1 (SISO)_NTNV




802.11n(HT20)_LCH_2412MHz_Ant1 (SISO)_NTNV




802.11n(HT20)_MCH_2437MHz_Ant1 (SISO)_NTNV




802.11n(HT20)_HCH_2462MHz_Ant1 (SISO)_NTNV




802.11n(HT40)_LCH_2422MHz_Ant1 (SISO)_NTNV




802.11n(HT40)_MCH_2437MHz_Ant1 (SISO)_NTNV




802.11n(HT40)_HCH_2452MHz_Ant1 (SISO)_NTNV




802.11ax(HEW20)_LCH_2412MHz_SU / _Ant1 (SISO)_NTNV




802.11ax(HEW20)_MCH_2437MHz_SU / _Ant1 (SISO)_NTNV




802.11ax(HEW20)_HCH_2462MHz_SU / _Ant1 (SISO)_NTNV




802.11ax(HEW40)_LCH_2422MHz_SU / _Ant1 (SISO)_NTNV



802.11ax(HEW40)_MCH_2437MHz_SU / _Ant1 (SISO)_NTNV



802.11ax(HEW40)_HCH_2452MHz_SU / _Ant1 (SISO)_NTNV



3. Maximum Conducted Output Power

3.1 Test Result


3.1.1 Power

Mode	TX Type	Frequency (MHz)	RU	RU Pos	Maximum Average Conducted Output Power (dBm)		Verdict
					ANT1	Limit	
802.11b	SISO	2412	/	/	9.89	<=30	Pass
		2437	/	/	9.63	<=30	Pass
		2462	/	/	9.48	<=30	Pass
802.11g	SISO	2412	/	/	10.37	<=30	Pass
		2437	/	/	9.78	<=30	Pass
		2462	/	/	9.18	<=30	Pass
802.11n (HT20)	SISO	2412	/	/	10.08	<=30	Pass
		2437	/	/	9.50	<=30	Pass
		2462	/	/	8.97	<=30	Pass
802.11n (HT40)	SISO	2422	/	/	11.41	<=30	Pass
		2437	/	/	11.03	<=30	Pass
		2452	/	/	10.64	<=30	Pass
802.11ax (HEW20)	SISO	2412	SU	/	9.76	<=30	Pass
		2437	SU	/	9.25	<=30	Pass
		2462	SU	/	8.59	<=30	Pass
802.11ax (HEW40)	SISO	2422	SU	/	11.22	<=30	Pass
		2437	SU	/	10.78	<=30	Pass
		2452	SU	/	10.33	<=30	Pass
Note1: Antenna Gain: Ant1: 4.59dBi;							


3.2 Test Graph

3.2.1 Power


802.11b_LCH_2412MHz_Ant1 (SISO)_NTNV




802.11b_MCH_2437MHz_Ant1 (SISO)_NTNV




802.11b_HCH_2462MHz_Ant1 (SISO)_NTNV




802.11g_LCH_2412MHz_Ant1 (SISO)_NTNV




802.11g_MCH_2437MHz_Ant1 (SISO)_NTNV




802.11g_HCH_2462MHz_Ant1 (SISO)_NTNV




802.11n(HT20)_LCH_2412MHz_Ant1 (SISO)_NTNV




802.11n(HT20)_MCH_2437MHz_Ant1 (SISO)_NTNV




802.11n(HT20)_HCH_2462MHz_Ant1 (SISO)_NTNV




802.11n(HT40)_LCH_2422MHz_Ant1 (SISO)_NTNV




802.11n(HT40)_MCH_2437MHz_Ant1 (SISO)_NTNV




802.11n(HT40)_HCH_2452MHz_Ant1 (SISO)_NTNV




802.11ax(HEW20)_LCH_2412MHz_SU_/_Ant1 (SISO)_NTNV




802.11ax(HEW20)_MCH_2437MHz_SU_/_Ant1 (SISO)_NTNV




802.11ax(HEW20)_HCH_2462MHz_SU_/_Ant1 (SISO)_NTNV




802.11ax(HEW40)_LCH_2422MHz_SU_/_Ant1 (SISO)_NTNV



802.11ax(HEW40)_MCH_2437MHz_SU_/_Ant1 (SISO)_NTNV



802.11ax(HEW40)_HCH_2452MHz_SU_/_Ant1 (SISO)_NTNV



4. Maximum Power Spectral Density

4.1 Test Result


4.1.1 PSD

Mode	TX Type	Frequency (MHz)	RU	RU Pos	Maximum PSD (dBm/3kHz)		Verdict
					ANT1	Limit	
802.11b	SISO	2412	/	/	-12.80	<=8	Pass
		2437	/	/	-13.00	<=8	Pass
		2462	/	/	-13.22	<=8	Pass
802.11g	SISO	2412	/	/	-13.10	<=8	Pass
		2437	/	/	-14.66	<=8	Pass
		2462	/	/	-14.60	<=8	Pass
802.11n (HT20)	SISO	2412	/	/	-12.76	<=8	Pass
		2437	/	/	-14.89	<=8	Pass
		2462	/	/	-14.55	<=8	Pass
802.11n (HT40)	SISO	2422	/	/	-14.78	<=8	Pass
		2437	/	/	-15.67	<=8	Pass
		2452	/	/	-14.83	<=8	Pass
802.11ax (HEW20)	SISO	2412	SU	/	-14.72	<=8	Pass
		2437	SU	/	-15.31	<=8	Pass
		2462	SU	/	-14.21	<=8	Pass
802.11ax (HEW40)	SISO	2422	SU	/	-16.29	<=8	Pass
		2437	SU	/	-15.92	<=8	Pass
		2452	SU	/	-16.52	<=8	Pass
Note1: Antenna Gain: Ant1: 4.59dBi;							


4.2 Test Graph

4.2.1 PSD


802.11b_LCH_2412MHz_Ant1 (SISO)_NTNV




802.11b_MCH_2437MHz_Ant1 (SISO)_NTNV




802.11b_HCH_2462MHz_Ant1 (SISO)_NTNV




802.11g_LCH_2412MHz_Ant1 (SISO)_NTNV




802.11g_MCH_2437MHz_Ant1 (SISO)_NTNV




802.11g_HCH_2462MHz_Ant1 (SISO)_NTNV




802.11n(HT20)_LCH_2412MHz_Ant1 (SISO)_NTNV




802.11n(HT20)_MCH_2437MHz_Ant1 (SISO)_NTNV




802.11n(HT20)_HCH_2462MHz_Ant1 (SISO)_NTNV




802.11n(HT40)_LCH_2422MHz_Ant1 (SISO)_NTNV




802.11n(HT40)_MCH_2437MHz_Ant1 (SISO)_NTNV




802.11n(HT40)_HCH_2452MHz_Ant1 (SISO)_NTNV




802.11ax(HEW20)_LCH_2412MHz_SU / _Ant1 (SISO)_NTNV




802.11ax(HEW20)_MCH_2437MHz_SU / _Ant1 (SISO)_NTNV




802.11ax(HEW20)_HCH_2462MHz_SU_/_Ant1 (SISO)_NTNV




802.11ax(HEW40)_LCH_2422MHz_SU_/_Ant1 (SISO)_NTNV



802.11ax(HEW40)_MCH_2437MHz_SU_/_Ant1 (SISO)_NTNV



802.11ax(HEW40)_HCH_2452MHz_SU_/_Ant1 (SISO)_NTNV



5. Unwanted Emissions In Non-restricted Frequency Bands

5.1 Test Result

5.1.1 Ref

Mode	TX Type	Frequency (MHz)	RU	RU Pos	ANT	Level of Reference (dBm)
802.11b	SISO	2412	/	/	1	1.71
		2437	/	/	1	1.11
		2462	/	/	1	1.15
802.11g	SISO	2412	/	/	1	-0.63
		2437	/	/	1	0.14
		2462	/	/	1	-0.44
802.11n (HT20)	SISO	2412	/	/	1	0.08
		2437	/	/	1	0.06
		2462	/	/	1	-0.51
802.11n (HT40)	SISO	2422	/	/	1	-1.34
		2437	/	/	1	-1.69
		2452	/	/	1	-2.52
802.11ax (HEW20)	SISO	2412	SU	/	1	0.50
		2437	SU	/	1	-0.61
		2462	SU	/	1	-0.60
802.11ax (HEW40)	SISO	2422	SU	/	1	-1.44
		2437	SU	/	1	-1.98
		2452	SU	/	1	-2.20
Note1: Refer to FCC Part 15.247 (d) and ANSI C63.10-2013, the channel contains the maximum PSD level was used to establish the reference level.						

5.1.2 CSE

Mode	TX Type	Frequency (MHz)	RU	RU Pos	ANT	Level of Reference (dBm)	Limit (dBm)	Verdict
802.11b	SISO	2412	/	/	1	1.71	-28.29	Pass
		2437	/	/	1	1.71	-28.29	Pass
		2462	/	/	1	1.71	-28.29	Pass
802.11g	SISO	2412	/	/	1	0.14	-29.86	Pass
		2437	/	/	1	0.14	-29.86	Pass


		2462	/	/	1	0.14	-29.86	Pass
802.11n (HT20)	SISO	2412	/	/	1	0.08	-29.92	Pass
		2437	/	/	1	0.08	-29.92	Pass
		2462	/	/	1	0.08	-29.92	Pass
802.11n (HT40)	SISO	2422	/	/	1	-1.34	-31.34	Pass
		2437	/	/	1	-1.34	-31.34	Pass
		2452	/	/	1	-1.34	-31.34	Pass
802.11ax (HEW20)	SISO	2412	SU	/	1	0.50	-29.50	Pass
		2437	SU	/	1	0.50	-29.50	Pass
		2462	SU	/	1	0.50	-29.50	Pass
802.11ax (HEW40)	SISO	2422	SU	/	1	-1.44	-31.44	Pass
		2437	SU	/	1	-1.44	-31.44	Pass
		2452	SU	/	1	-1.44	-31.44	Pass

Note1: Refer to FCC Part 15.247 (d) and ANSI C63.10-2013, the channel contains the maximum PSD level was used to establish the reference level.


5.2 Test Graph

5.2.1 Ref


802.11b_LCH_2412MHz_Ant1 (SISO)_NTNV




802.11b_MCH_2437MHz_Ant1 (SISO)_NTNV




802.11b_HCH_2462MHz_Ant1 (SISO)_NTNV




802.11g_LCH_2412MHz_Ant1 (SISO)_NTNV




802.11g_MCH_2437MHz_Ant1 (SISO)_NTNV




802.11g_HCH_2462MHz_Ant1 (SISO)_NTNV




802.11n(HT20)_LCH_2412MHz_Ant1 (SISO)_NTNV




802.11n(HT20)_MCH_2437MHz_Ant1 (SISO)_NTNV




802.11n(HT20)_HCH_2462MHz_Ant1 (SISO)_NTNV




802.11n(HT40)_LCH_2422MHz_Ant1 (SISO)_NTNV




802.11n(HT40)_MCH_2437MHz_Ant1 (SISO)_NTNV




802.11n(HT40)_HCH_2452MHz_Ant1 (SISO)_NTNV




802.11ax(HEW20)_LCH_2412MHz_SU_/_Ant1 (SISO)_NTNV




802.11ax(HEW20)_MCH_2437MHz_SU_/_Ant1 (SISO)_NTNV




802.11ax(HEW20)_HCH_2462MHz_SU / _Ant1 (SISO)_NTNV




802.11ax(HEW40)_LCH_2422MHz_SU / _Ant1 (SISO)_NTNV



802.11ax(HEW40)_MCH_2437MHz_SU_/_Ant1 (SISO)_NTNV




802.11ax(HEW40)_HCH_2452MHz_SU_/_Ant1 (SISO)_NTNV




5.2.2 CSE


802.11b_LCH_2412MHz_Ant1 (SISO)_NTNV




802.11b_LCH_2412MHz_Ant1 (SISO)_NTNV




802.11b_MCH_2437MHz_Ant1 (SISO)_NTNV




802.11b_HCH_2462MHz_Ant1 (SISO)_NTNV




802.11b_HCH_2462MHz_Ant1 (SISO)_NTNV




802.11g_LCH_2412MHz_Ant1 (SISO)_NTNV




802.11g_LCH_2412MHz_Ant1 (SISO)_NTNV




802.11g_MCH_2437MHz_Ant1 (SISO)_NTNV




802.11g_HCH_2462MHz_Ant1 (SISO)_NTNV




802.11g_HCH_2462MHz_Ant1 (SISO)_NTNV




802.11n(HT20)_LCH_2412MHz_Ant1 (SISO)_NTNV




802.11n(HT20)_LCH_2412MHz_Ant1 (SISO)_NTNV




802.11n(HT20)_MCH_2437MHz_Ant1 (SISO)_NTNV




802.11n(HT20)_HCH_2462MHz_Ant1 (SISO)_NTNV




802.11n(HT20)_HCH_2462MHz_Ant1 (SISO)_NTNV




802.11n(HT40)_LCH_2422MHz_Ant1 (SISO)_NTNV




802.11n(HT40)_LCH_2422MHz_Ant1 (SISO)_NTNV




802.11n(HT40)_MCH_2437MHz_Ant1 (SISO)_NTNV




802.11n(HT40)_HCH_2452MHz_Ant1 (SISO)_NTNV




802.11n(HT40)_HCH_2452MHz_Ant1 (SISO)_NTNV




802.11ax(HEW20)_LCH_2412MHz_SU / _Ant1 (SISO)_NTNV




802.11ax(HEW20)_LCH_2412MHz_SU / _Ant1 (SISO)_NTNV




802.11ax(HEW20)_MCH_2437MHz_SU / _Ant1 (SISO)_NTNV




802.11ax(HEW20)_HCH_2462MHz_SU / _Ant1 (SISO)_NTNV




802.11ax(HEW20)_HCH_2462MHz_SU / _Ant1 (SISO)_NTNV




802.11ax(HEW40)_LCH_2422MHz_SU / _Ant1 (SISO)_NTNV




802.11ax(HEW40)_LCH_2422MHz_SU_/_Ant1 (SISO)_NTNV




802.11ax(HEW40)_MCH_2437MHz_SU_/_Ant1 (SISO)_NTNV



802.11ax(HEW40)_HCH_2452MHz_SU_/_Ant1 (SISO)_NTNV



802.11ax(HEW40)_HCH_2452MHz_SU_/_Ant1 (SISO)_NTNV



- End of the Report -