

FCC Test Report

FCC ID : 2ALXJ-MTW200
Equipment : Meeting OWL™
Model No. : MTW200
Brand Name : OWLLabs™
Applicant : Owl Labs Inc
Address : 33-1/2 Union Sq
Somerville US 02143 United States Of America
Standard : 47 CFR FCC Part 15.247
Received Date : Jul. 17, 2019
Tested Date : Jul. 25 ~ Jul. 31, 2019

We, International Certification Corp., would like to declare that the tested sample has been evaluated and in compliance with the requirement of the above standards. The test results contained in this report refer exclusively to the product. It may be duplicated completely for legal use with the approval of the applicant. It shall not be reproduced except in full without the written approval of our laboratory.

Reviewed by:



Along Chen / Assistant Manager

Approved by:



Gary Chang / Manager



Table of Contents

1	GENERAL DESCRIPTION	5
1.1	Information.....	5
1.2	Local Support Equipment List	7
1.3	Test Setup Chart	7
1.4	Test Equipment List and Calibration Data.....	8
1.5	Test Standards	9
1.6	Deviation from Test Standard and Measurement Procedure.....	9
1.7	Measurement Uncertainty	9
2	TEST CONFIGURATION	10
2.1	Testing Condition	10
2.2	The Worst Test Modes and Channel Details	10
3	TRANSMITTER TEST RESULTS.....	11
3.1	Conducted Emissions.....	11
3.2	6dB and Occupied Bandwidth	16
3.3	RF Output Power.....	20
3.4	Power Spectral Density	23
3.5	Emissions in Restricted Frequency Bands.....	27
3.6	Emissions in non-restricted Frequency Bands.....	45
4	TEST LABORATORY INFORMATION	48

Release Record

Report No.	Version	Description	Issued Date
FR971702AE	Rev. 01	Initial issue	Aug. 12, 2019

Summary of Test Results

FCC Rules	Test Items	Measured	Result
15.207	AC Power Line Conducted Emissions	[dBuV]: 4.549MHz 50.32 (Margin -5.68dB) -QP	Pass
15.247(d) 15.209	Radiated Emissions	[dBuV/m at 3m]: 264.54MHz 35.93 (Margin -10.07dB) - PK	Pass
15.247(b)(3)	Maximum Output Power	Power [dBm]: 6.55	Pass
15.247(a)(2)	6dB Bandwidth	Meet the requirement of limit	Pass
15.247(e)	Power Spectral Density	Meet the requirement of limit	Pass
15.203	Antenna Requirement	Meet the requirement of limit	Pass

Declaration of Conformity:

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

Comments and Explanations:

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

1 General Description

1.1 Information

1.1.1 Specification of the Equipment under Test (EUT)

RF General Information				
Frequency Range (MHz)	Bluetooth Mode	Ch. Freq. (MHz)	Channel Number	Data Rate
2400-2483.5	V5.0 LE	2402-2480	0-39 [40]	1 Mbps
2400-2483.5	V5.0 LE	2402-2480	0-39 [40]	2 Mbps

Note 1: Bluetooth LE (Low energy) uses GFSK modulation.

1.1.2 Antenna Details

Ant. No.	Model	Type	Connector	Gain (dBi)	Remarks
1	SRF2W012-150	PCB	MHF IPEX	3.0dBi	---

1.1.3 Power Supply Type of Equipment under Test (EUT)

Power Supply Type	12Vdc from adapter
-------------------	--------------------

1.1.4 Accessories

Accessories		
No.	Equipment	Description
1	AC Adapter	Brand: HOLOTO Model: ADS-40SI-12-2 12036E Power Rating: I/P: 100-240Vac, 50/60Hz, 1A Max O/P: 12Vdc, 3A Power Line: DC 1.49m non-shielded without core AC 2.13m non-shielded without core
2	USB Cable	1.97m non-shielded without core

1.1.5 Channel List

Frequency band (MHz)				2400~2483.5			
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
37	2402	9	2422	18	2442	28	2462
0	2404	10	2424	19	2444	29	2464
1	2406	38	2426	20	2446	30	2466
2	2408	11	2428	21	2448	31	2468
3	2410	12	2430	22	2450	32	2470
4	2412	13	2432	23	2452	33	2472
5	2414	14	2434	24	2454	34	2474
6	2416	15	2436	25	2456	35	2476
7	2418	16	2438	26	2458	36	2478
8	2420	17	2440	27	2460	39	2480

1.1.6 Test Tool and Duty Cycle

Test Tool	QRCT, version: 3.0.298.0		
Duty Cycle and Duty Factor	Modulation Mode	Duty Cycle (%)	Duty Factor (dB)
	GFSK/1Mbps	63.89%	1.95
	GFSK/2Mbps	34.26%	4.65


1.1.7 Power Index of Test Tool

Modulation Mode	Test Frequency (MHz)		
	2402	2440	2480
GFSK/1Mbps	Default	Default	Default
GFSK/2Mbps	Default	Default	Default

1.2 Local Support Equipment List

Support Equipment List					
No.	Equipment	Brand	Model	FCC ID	Remarks
1	Notebook	DELL	Latitude E5470	DoC	---

1.3 Test Setup Chart



1.4 Test Equipment List and Calibration Data

Test Item	Conducted Emission				
Test Site	Conduction room 1 / (CO01-WS)				
Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Until
Receiver	R&S	ESR3	101657	Jan. 08, 2019	Jan. 07, 2020
LISN	R&S	ENV216	101579	Mar. 08, 2019	Mar. 07, 2020
LISN (Support Unit)	SCHWARZBECK	Schwarzbeck 8127	8127-666	Nov. 29, 2018	Nov. 28, 2019
RF Cable-CON	Woken	CFD200-NL	CFD200-NL-001	Oct. 23, 2018	Oct. 22, 2019
50 ohm terminal (Support Unit)	NA	50	04	May 28, 2019	May 27, 2020
Measurement Software	AUDIX	e3	6.120210k	NA	NA

Note: Calibration Interval of instruments listed above is one year.

Test Item	Radiated Emission				
Test Site	966 chamber1 / (03CH01-WS)				
Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Until
Spectrum Analyzer	R&S	FSV40	101498	Dec. 27, 2018	Dec. 26, 2019
Receiver	R&S	ESR3	101658	Dec. 11, 2018	Dec. 10, 2019
Bilog Antenna	SCHWARZBECK	VULB9168	VULB9168-522	Jul. 12, 2019	Jul. 11, 2020
Horn Antenna 1G-18G	SCHWARZBECK	BBHA 9120 D	BBHA 9120 D 1096	Dec. 18, 2018	Dec. 17, 2019
Horn Antenna 18G-40G	SCHWARZBECK	BBHA 9170	BBHA 9170517	Nov. 15, 2018	Nov. 14, 2019
Loop Antenna	R&S	HFH2-Z2	100330	Nov. 09, 2018	Nov. 08, 2019
Loop Antenna Cable	KOAX KABEL	101354-BW	101354-BW	Oct. 08, 2018	Oct. 07, 2019
Preamplifier	EMC	EMC02325	980225	Jul. 09, 2019	Jul. 08, 2020
Preamplifier	Agilent	83017A	MY39501308	Oct. 04, 2018	Oct. 03, 2019
Preamplifier	EMC	EMC184045B	980192	Aug. 09, 2018	Aug. 08, 2019
RF Cable	EMC	EMC104-SM-SM-8000	181106	Oct. 08, 2018	Oct. 07, 2019
RF Cable	HUBER+SUHNER	SUCOFLEX104	MY16019/4	Oct. 08, 2018	Oct. 07, 2019
RF Cable	HUBER+SUHNER	SUCOFLEX104	MY16014/4	Oct. 08, 2018	Oct. 07, 2019
LF cable 1M	EMC	EMCCFD400-NM-NM-1000	160502	Oct. 08, 2018	Oct. 07, 2019
LF cable 3M	Woken	CFD400NL-LW	CFD400NL-001	Oct. 08, 2018	Oct. 07, 2019
LF cable 10M	Woken	CFD400NL-LW	CFD400NL-002	Oct. 08, 2018	Oct. 07, 2019
Measurement Software	AUDIX	e3	6.120210g	NA	NA

Note: Calibration Interval of instruments listed above is one year.

Test Item	RF Conducted				
Test Site	(TH01-WS)				
Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Until
Spectrum Analyzer	R&S	FSV40	101063	Apr. 17, 2019	Apr. 16, 2020
Spectrum Analyzer	R&S	FSV40	101499	Jan. 07, 2019	Jan. 06, 2020
Power Meter	Anritsu	ML2495A	1241002	Oct. 09, 2018	Oct. 08, 2019
Power Sensor	Anritsu	MA2411B	1207366	Oct. 09, 2018	Oct. 08, 2019
DC POWER SOURCE	GW INSTEK	GPC-6030D	EM892433	Oct. 25, 2018	Oct. 24, 2019
AC POWER SOURCE	APC	AFC-500W	F312060012	Nov. 29, 2018	Nov. 28, 2019
Measurement Software	Sporton	Sporton_1	1.3.30	NA	NA
Note: Calibration Interval of instruments listed above is one year.					

1.5 Test Standards

According to the specification of EUT, the EUT must comply with following standards and KDB documents.

47 CFR FCC Part 15.247

ANSI C63.10-2013

FCC KDB 558074 D01 15.247 Meas Guidance v05r02

1.6 Deviation from Test Standard and Measurement Procedure

None

1.7 Measurement Uncertainty

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor ($k=2$))

Measurement Uncertainty	
Parameters	Uncertainty
Bandwidth	± 34.130 Hz
Conducted power	± 0.808 dB
Power density	± 0.583 dB
Conducted emission	± 2.715 dB
AC conducted emission	± 2.92 dB
Radiated emission ≤ 1 GHz	± 3.41 dB
Radiated emission > 1 GHz	± 4.59 dB

2 Test Configuration

2.1 Testing Condition

Test Item	Test Site	Ambient Condition	Tested By
AC Conduction	CO01-WS	24°C / 58%	Alex Tsai
Radiated Emissions	03CH01-WS	25-27°C / 65-66%	Akun Chung
RF Conducted	TH01-WS	24°C / 65%	Brad Wu

- FCC Designation No.: TW2732
- FCC site registration No.: 181692
- ISED#: 10807A
- CAB identifier: TW2732

2.2 The Worst Test Modes and Channel Details

Test item	Mode	Test Frequency (MHz)	Data Rate	Test Configuration
AC Power Line Conducted Emissions	BT LE	2480	1Mbps	---
Radiated Emissions \leq 1GHz	BT LE	2480	2Mbps	
Maximum Output Power				---
6dB bandwidth	BT LE	2402, 2440, 2480	1Mbps	
Power spectral density	BT LE	2402, 2440, 2480	2Mbps	
Radiated Emissions > 1GHz				

3 Transmitter Test Results

3.1 Conducted Emissions

3.1.1 Limit of Conducted Emissions

Conducted Emissions Limit		
Frequency Emission (MHz)	Quasi-Peak	Average
0.15-0.5	66 - 56 *	56 - 46 *
0.5-5	56	46
5-30	60	50

Note 1: * Decreases with the logarithm of the frequency.

3.1.2 Test Procedures


1. The device is placed on a test table, raised 80 cm above the reference ground plane. The vertical conducting plane is located 40 cm to the rear of the device.
2. The device is connected to line impedance stabilization network (LISN) and other accessories are connected to other LISN. Measured levels of AC power line conducted emission are across the 50 Ω LISN port.
3. AC conducted emission measurements is made over frequency range from 150 kHz to 30 MHz.
4. This measurement was performed with AC 120V/60Hz

3.1.3 Test Setup




- Note: 1. Support units were connected to second LISN.
 2. Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes

3.1.4 Test Result of Conducted Emissions

Modulation Mode	BT LE-1Mbps	Test Freq. (MHz)	2480																																																																																																																					
Power Phase	Line																																																																																																																							
 <p>The graph displays the conducted emission level in dBuV on the y-axis (0 to 80) against frequency in MHz on the x-axis (0.15 to 30). Two red lines represent the limits: CISPR/CNS/VCCI-B (upper) and CISPR/CNS/VCCI-B AV (lower). A blue line shows the measured emission level with several peaks labeled 1 through 12. The measured level is generally below the limits, with a notable peak at 4.454 MHz (labeled 6*) that is slightly above the AV limit.</p>																																																																																																																								
<table border="1"> <thead> <tr> <th></th> <th>Freq MHz</th> <th>Level dBuV</th> <th>Limit Line dBuV</th> <th>Over Limit dB</th> <th>Read Level dBuV</th> <th>LISN factor dB</th> <th>cable loss dB</th> <th>Remark</th> </tr> </thead> <tbody> <tr><td>1</td><td>0.171</td><td>21.02</td><td>54.90</td><td>-33.88</td><td>11.43</td><td>9.53</td><td>0.06</td><td>Average</td></tr> <tr><td>2</td><td>0.171</td><td>29.95</td><td>64.90</td><td>-34.95</td><td>20.36</td><td>9.53</td><td>0.06</td><td>QP</td></tr> <tr><td>3</td><td>3.700</td><td>26.24</td><td>46.00</td><td>-19.76</td><td>16.36</td><td>9.61</td><td>0.27</td><td>Average</td></tr> <tr><td>4</td><td>3.700</td><td>35.09</td><td>56.00</td><td>-20.91</td><td>25.21</td><td>9.61</td><td>0.27</td><td>QP</td></tr> <tr><td>5</td><td>4.454</td><td>30.22</td><td>46.00</td><td>-15.78</td><td>20.31</td><td>9.61</td><td>0.30</td><td>Average</td></tr> <tr><td>6*</td><td>4.454</td><td>45.17</td><td>56.00</td><td>-10.83</td><td>35.26</td><td>9.61</td><td>0.30</td><td>QP</td></tr> <tr><td>7</td><td>5.535</td><td>32.92</td><td>50.00</td><td>-17.08</td><td>22.96</td><td>9.62</td><td>0.34</td><td>Average</td></tr> <tr><td>8</td><td>5.535</td><td>38.58</td><td>60.00</td><td>-21.42</td><td>28.62</td><td>9.62</td><td>0.34</td><td>QP</td></tr> <tr><td>9</td><td>13.560</td><td>34.99</td><td>50.00</td><td>-15.01</td><td>24.81</td><td>9.65</td><td>0.53</td><td>Average</td></tr> <tr><td>10</td><td>13.560</td><td>38.44</td><td>60.00</td><td>-21.56</td><td>28.26</td><td>9.65</td><td>0.53</td><td>QP</td></tr> <tr><td>11</td><td>18.820</td><td>25.78</td><td>50.00</td><td>-24.22</td><td>15.53</td><td>9.66</td><td>0.59</td><td>Average</td></tr> <tr><td>12</td><td>18.820</td><td>31.07</td><td>60.00</td><td>-28.93</td><td>20.82</td><td>9.66</td><td>0.59</td><td>QP</td></tr> </tbody> </table>					Freq MHz	Level dBuV	Limit Line dBuV	Over Limit dB	Read Level dBuV	LISN factor dB	cable loss dB	Remark	1	0.171	21.02	54.90	-33.88	11.43	9.53	0.06	Average	2	0.171	29.95	64.90	-34.95	20.36	9.53	0.06	QP	3	3.700	26.24	46.00	-19.76	16.36	9.61	0.27	Average	4	3.700	35.09	56.00	-20.91	25.21	9.61	0.27	QP	5	4.454	30.22	46.00	-15.78	20.31	9.61	0.30	Average	6*	4.454	45.17	56.00	-10.83	35.26	9.61	0.30	QP	7	5.535	32.92	50.00	-17.08	22.96	9.62	0.34	Average	8	5.535	38.58	60.00	-21.42	28.62	9.62	0.34	QP	9	13.560	34.99	50.00	-15.01	24.81	9.65	0.53	Average	10	13.560	38.44	60.00	-21.56	28.26	9.65	0.53	QP	11	18.820	25.78	50.00	-24.22	15.53	9.66	0.59	Average	12	18.820	31.07	60.00	-28.93	20.82	9.66	0.59	QP
	Freq MHz	Level dBuV	Limit Line dBuV	Over Limit dB	Read Level dBuV	LISN factor dB	cable loss dB	Remark																																																																																																																
1	0.171	21.02	54.90	-33.88	11.43	9.53	0.06	Average																																																																																																																
2	0.171	29.95	64.90	-34.95	20.36	9.53	0.06	QP																																																																																																																
3	3.700	26.24	46.00	-19.76	16.36	9.61	0.27	Average																																																																																																																
4	3.700	35.09	56.00	-20.91	25.21	9.61	0.27	QP																																																																																																																
5	4.454	30.22	46.00	-15.78	20.31	9.61	0.30	Average																																																																																																																
6*	4.454	45.17	56.00	-10.83	35.26	9.61	0.30	QP																																																																																																																
7	5.535	32.92	50.00	-17.08	22.96	9.62	0.34	Average																																																																																																																
8	5.535	38.58	60.00	-21.42	28.62	9.62	0.34	QP																																																																																																																
9	13.560	34.99	50.00	-15.01	24.81	9.65	0.53	Average																																																																																																																
10	13.560	38.44	60.00	-21.56	28.26	9.65	0.53	QP																																																																																																																
11	18.820	25.78	50.00	-24.22	15.53	9.66	0.59	Average																																																																																																																
12	18.820	31.07	60.00	-28.93	20.82	9.66	0.59	QP																																																																																																																
<p>Note 1: Level (dBuV) = Read Level (dBuV) + LISN Factor (dB) + Cable Loss (dB). Note 2: Over Limit (dB) = Level (dBuV) – Limit Line (dBuV).</p>																																																																																																																								


Modulation Mode	BT LE-1Mbps	Test Freq. (MHz)	2480
Power Phase	Neutral		



	Freq	Level	Limit	Over	Read	LISN	cable	Remark
	MHz	dBuV	Line	Limit	Level	factor	loss	
			dBuV	dB	dBuV	dB	dB	
1	0.162	19.85	55.34	-35.49	10.22	9.57	0.06	Average
2	0.162	29.42	65.34	-35.92	19.79	9.57	0.06	QP
3	3.820	28.03	46.00	-17.97	18.10	9.66	0.27	Average
4	3.820	39.00	56.00	-17.00	29.07	9.66	0.27	QP
5	4.549	35.36	46.00	-10.64	25.39	9.67	0.30	Average
6*	4.549	50.32	56.00	-5.68	40.35	9.67	0.30	QP
7	5.447	32.80	50.00	-17.20	22.79	9.68	0.33	Average
8	5.447	37.97	60.00	-22.03	27.96	9.68	0.33	QP
9	13.560	35.25	50.00	-14.75	24.97	9.75	0.53	Average
10	13.560	38.96	60.00	-21.04	28.68	9.75	0.53	QP
11	19.122	26.65	50.00	-23.35	16.26	9.80	0.59	Average
12	19.122	32.89	60.00	-27.11	22.50	9.80	0.59	QP

Note 1: Level (dBuV) = Read Level (dBuV) + LISN Factor (dB) + Cable Loss (dB).
 2: Over Limit (dB) = Level (dBuV) – Limit Line (dBuV).


Modulation Mode	BT LE-2Mbps	Test Freq. (MHz)	2480
Power Phase	Line		



	Freq MHz	Level dBuV	Limit Line dBuV	Over Limit dB	Read Level dBuV	LISN factor dB	cable loss dB	Remark
1	0.150	21.97	56.00	-34.03	12.39	9.53	0.05	Average
2	0.150	30.60	66.00	-35.40	21.02	9.53	0.05	QP
3	3.472	28.73	46.00	-17.27	18.87	9.61	0.25	Average
4	3.472	38.16	56.00	-17.84	28.30	9.61	0.25	QP
5	4.478	32.32	46.00	-13.68	22.41	9.61	0.30	Average
6*	4.478	45.35	56.00	-10.65	35.44	9.61	0.30	QP
7	5.683	30.40	50.00	-19.60	20.43	9.63	0.34	Average
8	5.683	37.19	60.00	-22.81	27.22	9.63	0.34	QP
9	13.560	34.66	50.00	-15.34	24.48	9.65	0.53	Average
10	13.560	39.03	60.00	-20.97	28.85	9.65	0.53	QP
11	19.224	25.07	50.00	-24.93	14.82	9.66	0.59	Average
12	19.224	30.68	60.00	-29.32	20.43	9.66	0.59	QP

Note 1: Level (dBuV) = Read Level (dBuV) + LISN Factor (dB) + Cable Loss (dB).
 2: Over Limit (dB) = Level (dBuV) – Limit Line (dBuV).

Modulation Mode	BT LE-2Mbps	Test Freq. (MHz)	2480
Power Phase	Neutral		



	Freq MHz	Level dBuV	Limit Line dBuV	Over Limit dB	Read Level dBuV	LISN factor dB	cable loss dB	Remark
1	0.177	20.74	54.64	-33.90	11.10	9.58	0.06	Average
2	0.177	29.50	64.64	-35.14	19.86	9.58	0.06	QP
3	3.491	30.67	46.00	-15.33	20.75	9.66	0.26	Average
4	3.491	41.15	56.00	-14.85	31.23	9.66	0.26	QP
5	4.501	33.05	46.00	-12.95	23.08	9.67	0.30	Average
6*	4.501	49.62	56.00	-6.38	39.65	9.67	0.30	QP
7	5.653	31.15	50.00	-18.85	21.13	9.68	0.34	Average
8	5.653	37.94	60.00	-22.06	27.92	9.68	0.34	QP
9	13.561	35.87	50.00	-14.13	25.59	9.75	0.53	Average
10	13.561	39.61	60.00	-20.39	29.33	9.75	0.53	QP
11	18.820	26.88	50.00	-23.12	16.49	9.80	0.59	Average
12	18.820	31.99	60.00	-28.01	21.60	9.80	0.59	QP

Note 1: Level (dBuV) = Read Level (dBuV) + LISN Factor (dB) + Cable Loss (dB).
 Note 2: Over Limit (dB) = Level (dBuV) – Limit Line (dBuV).

3.2 6dB and Occupied Bandwidth

3.2.1 Limit of 6dB Bandwidth

The minimum 6dB bandwidth shall be at least 500 kHz.

3.2.2 Test Procedures


6dB Bandwidth

1. Set resolution bandwidth (RBW) = 100 kHz, Video bandwidth = 300 kHz.
2. Detector = Peak, Trace mode = max hold.
3. Sweep = auto couple, Allow the trace to stabilize.
4. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower) that are attenuated by 6dB relative to the maximum level measured in the fundamental emission.

Occupied Bandwidth

1. Set resolution bandwidth (RBW) = 1% ~ 5 % of OBW, Video bandwidth = 3 x RBW.
2. Detector = Sample, Trace mode = max hold.
3. Sweep = auto couple, Allow the trace to stabilize.
4. Use the OBW measurement function of spectrum analyzer to measure the occupied bandwidth.

3.2.3 Test Setup



3.2.4 Test Result of 6dB and Occupied Bandwidth

Summary

Mode	Max-N dB (Hz)	Max-OBW (Hz)	ITU-Code	Min-N dB (Hz)	Min-OBW (Hz)
2.4-2.4835GHz	-	-	-	-	-
BT-LE(1Mbps)	663.043k	1.024M	1M02F1D	655.797k	1.02M
BT-LE(2Mbps)	1.109M	2.033M	2M03F1D	1.094M	2.019M


Max-N dB = Maximum 6dB down bandwidth; **Max-OBW** = Maximum 99% occupied bandwidth;


Min-N dB = Minimum 6dB down bandwidth; **Min-OBW** = Minimum 99% occupied bandwidth;

Result

Mode	Result	Limit (Hz)	Port 1-N dB (Hz)	Port 1-OBW (Hz)
BT-LE(1Mbps)	-	-	-	-
2402MHz	Pass	500k	655.797k	1.02M
2440MHz	Pass	500k	663.043k	1.02M
2480MHz	Pass	500k	655.797k	1.024M
BT-LE(2Mbps)	-	-	-	-
2402MHz	Pass	500k	1.094M	2.019M
2440MHz	Pass	500k	1.109M	2.019M
2480MHz	Pass	500k	1.094M	2.033M

Port X-N dB = Port X 6dB down bandwidth; **Port X-OBW** = Port X 99% occupied bandwidth;





3.3 RF Output Power

3.3.1 Limit of RF Output Power


Conducted power shall not exceed 1 Watt.

Antenna gain $\leq 6\text{dBi}$, no any corresponding reduction is in output power limit.

3.3.2 Test Procedures

A broadband RF power meter is used for output power measurement. The video bandwidth of power meter is greater than DTS bandwidth of EUT. If duty cycle of test signal is not 100 %, trigger and gating function of power meter will be enabled to capture transmission burst for measuring output power.

3.3.3 Test Setup



3.3.4 Test Result of Maximum Output Power

Peak Power Summary

Mode	Power (dBm)	Power (W)
2.4-2.4835GHz	-	-
BT-LE(1Mbps)	6.29	0.00426
BT-LE(2Mbps)	6.55	0.00452

Result

Mode	Result	Gain (dBi)	Power (dBm)	Power Limit (dBm)
BT-LE(1Mbps)	-	-	-	-
2402MHz	Pass	3.00	4.79	30.00
2440MHz	Pass	3.00	4.28	30.00
2480MHz	Pass	3.00	6.29	30.00
BT-LE(2Mbps)	-	-	-	-
2402MHz	Pass	3.00	5.08	30.00
2440MHz	Pass	3.00	4.53	30.00
2480MHz	Pass	3.00	6.55	30.00

**Average Power
Summary**

Mode	Power (dBm)	Power (W)
2.4-2.4835GHz	-	-
BT-LE(1Mbps)	6.10	0.00407
BT-LE(2Mbps)	6.08	0.00406

Result

Mode	Result	Gain (dBi)	Power (dBm)	Power Limit (dBm)
BT-LE(1Mbps)	-	-	-	-
2402MHz	Pass	3.00	4.60	-
2440MHz	Pass	3.00	4.08	-
2480MHz	Pass	3.00	6.10	-
BT-LE(2Mbps)	-	-	-	-
2402MHz	Pass	3.00	4.59	-
2440MHz	Pass	3.00	4.04	-
2480MHz	Pass	3.00	6.08	-

Note: Average power is for reference only.

3.4 Power Spectral Density


3.4.1 Limit of Power Spectral Density

Power spectral density shall not be greater than 8 dBm in any 3 kHz band.

3.4.2 Test Procedures

1. Set the RBW = 3 kHz, VBW = 10 kHz.
2. Detector = Peak, Sweep time = auto couple.
3. Trace mode = max hold, allow trace to fully stabilize.
4. Use the peak marker function to determine the maximum amplitude level.

3.4.3 Test Setup




3.4.4 Test Result of Power Spectral Density


Summary

Mode	PD (dBm/RBW)
2.4-2.4835GHz	-
BT-LE(1Mbps)	-9.31
BT-LE(2Mbps)	-12.99

Result

Mode	Result	Gain (dBi)	PD (dBm/RBW)	PD Limit (dBm/RBW)
BT-LE(1Mbps)	-	-	-	-
2402MHz	Pass	3.00	-10.91	8.00
2440MHz	Pass	3.00	-11.46	8.00
2480MHz	Pass	3.00	-9.31	8.00
BT-LE(2Mbps)	-	-	-	-
2402MHz	Pass	3.00	-14.51	8.00
2440MHz	Pass	3.00	-14.95	8.00
2480MHz	Pass	3.00	-12.99	8.00





3.5 Emissions in Restricted Frequency Bands

3.5.1 Limit of Emissions in Restricted Frequency Bands

Restricted Band Emissions Limit			
Frequency Range (MHz)	Field Strength (uV/m)	Field Strength (dBuV/m)	Measure Distance (m)
0.009~0.490	2400/F(kHz)	48.5 - 13.8	300
0.490~1.705	24000/F(kHz)	33.8 - 23	30
1.705~30.0	30	29	30
30~88	100	40	3
88~216	150	43.5	3
216~960	200	46	3
Above 960	500	54	3

Note 1:
Quasi-Peak value is measured for frequency below 1GHz except for 9–90 kHz, 110–490 kHz frequency band. Peak and average value are measured for frequency above 1GHz. The limit on average radio frequency emission is as above table. The limit on peak radio frequency emissions is 20 dB above the maximum permitted average emission limit

Note 2:
Measurements may be performed at a distance other than what is specified provided. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor as below, Frequency at or above 30 MHz: 20 dB/decade Frequency below 30 MHz: 40 dB/decade.

3.5.2 Test Procedures


1. Measurement is made at a semi-anechoic chamber that incorporates a turntable allowing a EUT rotation of 360°. A continuously-rotating, remotely-controlled turntable is installed at the test site to support the EUT and facilitate determination of the direction of maximum radiation for each EUT emission frequency. The EUT is placed at test table. For emissions testing at or below 1 GHz, the table height is 80 cm above the reference ground plane. For emission measurements above 1 GHz, the table height is 1.5 m
2. Measurement is made with the antenna positioned in both the horizontal and vertical planes of polarization. The measurement antenna is varied in height (1m ~ 4m) above the reference ground plane to obtain the maximum signal strength. Distance between EUT and antenna is 3 m.
3. This investigation is performed with the EUT rotated 360°, the antenna height scanned between 1 m and 4 m, and the antenna rotated to repeat the measurements for both the horizontal and vertical antenna polarizations.

Note:


1. 120kHz measurement bandwidth of test receiver and Quasi-peak detector is for radiated emission below 1GHz.
2. RBW=1MHz, VBW=3MHz and Peak detector is for peak measured value of radiated emission above 1GHz.
3. RBW=1MHz, VBW=1/T and Peak detector is for average measured value of radiated emission above 1GHz.

3.5.3 Test Setup


Radiated Emissions below 1 GHz




Radiated Emissions above 1 GHz



3.5.4 Transmitter Radiated Unwanted Emissions (Below 1GHz)

Modulation	BT-LE (1Mbps)	Test Freq. (MHz)	2480																																																																						
Polarization	Horizontal																																																																								
																																																																									
	<table border="1"> <thead> <tr> <th>Freq.</th> <th>Emission level</th> <th>Limit</th> <th>Margin</th> <th>SA reading</th> <th>Factor</th> <th>Remark</th> <th>ANT High cm</th> <th>Turn Table deg</th> </tr> <tr> <th>MHz</th> <th>dBuV/m</th> <th>dBuV/m</th> <th>dB</th> <th>dBuV</th> <th>dB</th> <th></th> <th></th> <th></th> </tr> </thead> <tbody> <tr> <td>1</td> <td>120.35</td> <td>24.20</td> <td>43.50</td> <td>-19.30</td> <td>34.88</td> <td>-10.68</td> <td>Peak</td> <td>---</td> </tr> <tr> <td>2</td> <td>204.81</td> <td>23.54</td> <td>43.50</td> <td>-19.96</td> <td>35.73</td> <td>-12.19</td> <td>Peak</td> <td>---</td> </tr> <tr> <td>3</td> <td>241.31</td> <td>30.77</td> <td>46.00</td> <td>-15.23</td> <td>40.97</td> <td>-10.20</td> <td>Peak</td> <td>---</td> </tr> <tr style="border: 2px solid black;"> <td>4</td> <td>264.54</td> <td>35.93</td> <td>46.00</td> <td>-10.07</td> <td>45.31</td> <td>-9.38</td> <td>Peak</td> <td>---</td> </tr> <tr> <td>5</td> <td>312.58</td> <td>35.25</td> <td>46.00</td> <td>-10.75</td> <td>42.90</td> <td>-7.65</td> <td>Peak</td> <td>---</td> </tr> <tr> <td>6</td> <td>490.51</td> <td>30.25</td> <td>46.00</td> <td>-15.75</td> <td>33.67</td> <td>-3.42</td> <td>Peak</td> <td>---</td> </tr> </tbody> </table>	Freq.	Emission level	Limit	Margin	SA reading	Factor	Remark	ANT High cm	Turn Table deg	MHz	dBuV/m	dBuV/m	dB	dBuV	dB				1	120.35	24.20	43.50	-19.30	34.88	-10.68	Peak	---	2	204.81	23.54	43.50	-19.96	35.73	-12.19	Peak	---	3	241.31	30.77	46.00	-15.23	40.97	-10.20	Peak	---	4	264.54	35.93	46.00	-10.07	45.31	-9.38	Peak	---	5	312.58	35.25	46.00	-10.75	42.90	-7.65	Peak	---	6	490.51	30.25	46.00	-15.75	33.67	-3.42	Peak	---
Freq.	Emission level	Limit	Margin	SA reading	Factor	Remark	ANT High cm	Turn Table deg																																																																	
MHz	dBuV/m	dBuV/m	dB	dBuV	dB																																																																				
1	120.35	24.20	43.50	-19.30	34.88	-10.68	Peak	---																																																																	
2	204.81	23.54	43.50	-19.96	35.73	-12.19	Peak	---																																																																	
3	241.31	30.77	46.00	-15.23	40.97	-10.20	Peak	---																																																																	
4	264.54	35.93	46.00	-10.07	45.31	-9.38	Peak	---																																																																	
5	312.58	35.25	46.00	-10.75	42.90	-7.65	Peak	---																																																																	
6	490.51	30.25	46.00	-15.75	33.67	-3.42	Peak	---																																																																	
<p>Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB) *Factor includes antenna factor , cable loss and amplifier gain Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m). Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.</p>																																																																									

Modulation	BT-LE (1Mbps)	Test Freq. (MHz)	2480
Polarization	Vertical		



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	68.24	25.31	40.00	-14.69	35.51	-10.20	Peak	---	---
2	131.25	26.20	43.50	-17.30	35.82	-9.62	Peak	---	---
3	159.70	26.44	43.50	-17.06	34.94	-8.50	Peak	---	---
4	264.24	29.63	46.00	-16.37	39.03	-9.40	Peak	---	---
5	312.24	32.54	46.00	-13.46	40.20	-7.66	Peak	---	---
6	456.81	31.74	46.00	-14.26	35.72	-3.98	Peak	---	---


Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

Modulation	BT-LE (2Mbps)	Test Freq. (MHz)	2480
Polarization	Horizontal		



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	121.54	24.54	43.50	-18.96	35.10	-10.56	Peak	---	---
2	204.31	23.41	43.50	-20.09	35.59	-12.18	Peak	---	---
3	241.61	31.28	46.00	-14.72	41.47	-10.19	Peak	---	---
4	262.99	35.88	46.00	-10.12	45.36	-9.48	Peak	---	---
5	312.54	33.88	46.00	-12.12	41.53	-7.65	Peak	---	---
6	490.54	29.52	46.00	-16.48	32.94	-3.42	Peak	---	---


Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

Modulation	BT-LE (2Mbps)	Test Freq. (MHz)	2480
Polarization	Vertical		



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	68.24	25.31	40.00	-14.69	35.51	-10.20	Peak	---	---
2	131.24	25.95	43.50	-17.55	35.58	-9.63	Peak	---	---
3	159.60	26.82	43.50	-16.68	35.31	-8.49	Peak	---	---
4	262.41	29.24	46.00	-16.76	38.76	-9.52	Peak	---	---
5	311.52	31.82	46.00	-14.18	39.51	-7.69	Peak	---	---
6	456.21	30.87	46.00	-15.13	34.88	-4.01	Peak	---	---


Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).


Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

3.5.5 Transmitter Radiated Unwanted Emissions (Above 1GHz)

Modulation	BT-LE (1Mbps)	Test Freq. (MHz)	2402						
Polarization	Horizontal								
									
	Freq.	Emission level	Limit	Margin	SA reading	Factor	Remark	ANT High	Turn Table
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB		cm	deg
1	2390.00	39.74	54.00	-14.26	42.81	-3.07	Average	100	186
2	2390.00	51.45	74.00	-22.55	54.52	-3.07	Peak	100	182
3	4804.00	37.03	54.00	-16.97	33.53	3.50	Average	100	101
4	4804.00	46.72	74.00	-27.28	43.22	3.50	Peak	100	101
5	12010.00	43.11	54.00	-10.89	29.85	13.26	Average	100	109
6	12010.00	56.22	74.00	-17.78	42.96	13.26	Peak	100	109

Note 1: Emission Level (dBUV/m) = SA Reading (dBUV/m) + Factor* (dB)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBUV/m) – Limit (dBUV/m).

Modulation	BT-LE (1Mbps)	Test Freq. (MHz)	2402
Polarization	Vertical		




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	39.75	54.00	-14.25	42.82	-3.07	Average	247	92
2	2390.00	51.45	74.00	-22.55	54.52	-3.07	Peak	247	92
3	4804.00	40.02	54.00	-13.98	36.52	3.50	Average	100	156
4	4804.00	47.53	74.00	-26.47	44.03	3.50	Peak	100	156
5	12010.00	43.81	54.00	-10.19	30.55	13.26	Average	100	147
6	12010.00	55.73	74.00	-18.27	42.47	13.26	Peak	100	147

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	BT-LE (1Mbps)	Test Freq. (MHz)	2440
Polarization	Horizontal		




	Freq. MHz	Emission level dBUV/m	Limit dBUV/m	Margin dB	SA reading dBUV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	39.75	54.00	-14.25	42.82	-3.07	Average	100	182
2	2390.00	49.79	74.00	-24.21	52.86	-3.07	Peak	100	182
3	2483.50	39.73	54.00	-14.27	42.95	-3.22	Average	100	182
4	2483.50	49.71	74.00	-24.29	52.93	-3.22	Peak	100	182
5	4880.00	35.82	54.00	-18.18	32.21	3.61	Average	100	109
6	4880.00	46.72	74.00	-27.28	43.11	3.61	Peak	100	109
7	7320.00	38.33	54.00	-15.67	29.53	8.80	Average	100	101
8	7320.00	51.31	74.00	-22.69	42.51	8.80	Peak	100	101

Note 1: Emission Level (dBUV/m) = SA Reading (dBUV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBUV/m) – Limit (dBUV/m).

Modulation	BT-LE (1Mbps)	Test Freq. (MHz)	2440
Polarization	Vertical		




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	39.75	54.00	-14.25	42.82	-3.07	Average	247	90
2	2390.00	49.90	74.00	-24.10	52.97	-3.07	Peak	247	90
3	2483.50	39.62	54.00	-14.38	42.84	-3.22	Average	247	90
4	2483.50	50.28	74.00	-23.72	53.50	-3.22	Peak	247	90
5	4880.00	38.49	54.00	-15.51	34.88	3.61	Average	100	153
6	4880.00	46.50	74.00	-27.50	42.89	3.61	Peak	100	153
7	7320.00	38.74	54.00	-15.26	29.94	8.80	Average	100	148
8	7320.00	52.03	74.00	-21.97	43.23	8.80	Peak	100	148

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	BT-LE (1Mbps)	Test Freq. (MHz)	2480
Polarization	Horizontal		




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2483.50	40.02	54.00	-13.98	43.24	-3.22	Average	100	184
2	2483.50	53.36	74.00	-20.64	56.58	-3.22	Peak	100	184
3	4960.00	38.25	54.00	-15.75	34.39	3.86	Average	100	105
4	4960.00	47.22	74.00	-26.78	43.36	3.86	Peak	100	105
5	7440.00	38.15	54.00	-15.85	29.61	8.54	Average	100	102
6	7440.00	51.43	74.00	-22.57	42.89	8.54	Peak	100	102

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	BT-LE (1Mbps)	Test Freq. (MHz)	2480
Polarization	Vertical		




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2483.50	40.66	54.00	-13.34	43.88	-3.22	Average	245	87
2	2483.50	54.18	74.00	-19.82	57.40	-3.22	Peak	245	87
3	4960.00	41.22	54.00	-12.78	37.36	3.86	Average	100	152
4	4960.00	48.25	74.00	-25.75	44.39	3.86	Peak	100	152
5	7440.00	38.82	54.00	-15.18	30.28	8.54	Average	100	150
6	7440.00	52.40	74.00	-21.60	43.86	8.54	Peak	100	150

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	BT-LE (2Mbps)	Test Freq. (MHz)	2402
Polarization	Horizontal		




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	39.14	54.00	-14.86	42.21	-3.07	Average	114	182
2	2390.00	50.75	74.00	-23.25	53.82	-3.07	Peak	114	182
3	4804.00	36.68	54.00	-17.32	33.18	3.50	Average	100	111
4	4804.00	47.36	74.00	-26.64	43.86	3.50	Peak	100	111
5	12010.00	43.20	54.00	-10.80	29.94	13.26	Average	100	102
6	12010.00	57.11	74.00	-16.89	43.85	13.26	Peak	100	102

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	BT-LE (2Mbps)	Test Freq. (MHz)	2402
Polarization	Vertical		




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	39.88	54.00	-14.12	42.95	-3.07	Average	263	87
2	2390.00	40.77	74.00	-33.23	43.84	-3.07	Peak	263	87
3	4804.00	38.65	54.00	-15.35	35.15	3.50	Average	100	158
4	4804.00	46.79	74.00	-27.21	43.29	3.50	Peak	100	158
5	12010.00	43.50	54.00	-10.50	30.24	13.26	Average	100	159
6	12010.00	56.50	74.00	-17.50	43.24	13.26	Peak	100	159

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	BT-LE (2Mbps)	Test Freq. (MHz)	2440
Polarization	Horizontal		




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	39.48	54.00	-14.52	42.55	-3.07	Average	115	185
2	2390.00	49.73	74.00	-24.27	52.80	-3.07	Peak	115	185
3	2483.50	39.92	54.00	-14.08	43.14	-3.22	Average	115	185
4	2483.50	49.74	74.00	-24.26	52.96	-3.22	Peak	115	185
5	4882.00	35.46	54.00	-18.54	31.85	3.61	Average	100	107
6	4882.00	46.75	74.00	-27.25	43.14	3.61	Peak	100	107
7	7323.00	38.93	54.00	-15.07	30.14	8.79	Average	100	104
8	7323.00	52.03	74.00	-21.97	43.24	8.79	Peak	100	104

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	BT-LE (2Mbps)	Test Freq. (MHz)	2440
Polarization	Vertical		




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	39.86	54.00	-14.14	42.93	-3.07	Average	263	88
2	2390.00	49.57	74.00	-24.43	52.64	-3.07	Peak	263	88
3	2483.50	39.48	54.00	-14.52	42.70	-3.22	Average	263	88
4	2483.50	49.71	74.00	-24.29	52.93	-3.22	Peak	263	88
5	4882.00	36.86	54.00	-17.14	33.25	3.61	Average	100	158
6	4882.00	47.44	74.00	-26.56	43.83	3.61	Peak	100	158
7	7323.00	39.64	54.00	-14.36	30.85	8.79	Average	100	166
8	7323.00	52.04	74.00	-21.96	43.25	8.79	Peak	100	166

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	BT-LE (2Mbps)	Test Freq. (MHz)	2480
Polarization	Horizontal		




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2483.50	39.71	54.00	-14.29	42.93	-3.22	Average	113	184
2	2483.50	56.83	74.00	-17.17	60.05	-3.22	Peak	113	184
3	4960.00	37.68	54.00	-16.32	33.82	3.86	Average	100	109
4	4960.00	47.28	74.00	-26.72	43.42	3.86	Peak	100	109
5	7440.00	38.42	54.00	-15.58	29.88	8.54	Average	100	110
6	7440.00	51.78	74.00	-22.22	43.24	8.54	Peak	100	110

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	BT-LE (2Mbps)	Test Freq. (MHz)	2480
Polarization	Vertical		



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2483.50	40.25	54.00	-13.75	43.47	-3.22	Average	260	84
2	2483.50	57.38	74.00	-16.62	60.60	-3.22	Peak	260	84
3	4960.00	40.03	54.00	-13.97	36.17	3.86	Average	100	153
4	4960.00	47.38	74.00	-26.62	43.52	3.86	Peak	100	153
5	7440.00	39.06	54.00	-14.94	30.52	8.54	Average	100	162
6	7440.00	52.08	74.00	-21.92	43.54	8.54	Peak	100	162

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

3.6 Emissions in non-restricted Frequency Bands

3.6.1 Emissions in non-restricted frequency bands limit

Peak power in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz

3.6.2 Test Procedures


Reference level measurement

1. Set RBW=100kHz, VBW = 300kHz , Detector = Peak, Sweep time = Auto
2. Trace = max hold , Allow Trace to fully stabilize
3. Use the peak marker function to determine the maximum PSD level


Emission level measurement


1. Set RBW=100kHz, VBW = 300kHz , Detector = Peak, Sweep time = Auto
2. Trace = max hold , Allow Trace to fully stabilize
3. Scan Frequency range is up to 25GHz
4. Use the peak marker function to determine the maximum amplitude level

3.6.3 Test Setup



3.6.4 Test Result of Emissions in non-restricted Frequency Bands





4 Test laboratory information

Established in 2012, ICC provides foremost EMC & RF Testing and advisory consultation services by our skilled engineers and technicians. Our services employ a wide variety of advanced edge test equipment and one of the widest certification extents in the business.

International Certification Corp (EMC and Wireless Communication Laboratory), it is our definitive objective is to institute long term, trust-based associations with our clients. The expectation we set up with our clients is based on outstanding service, practical expertise and devotion to a certified value structure. Our passion is to grant our clients with best EMC / RF services by oriented knowledgeable and accommodating staff.

Our Test sites are located at Linkou District and Kwei Shan District. Location map can be found on our website <http://www.icertifi.com.tw>.

Linkou

Tel: 886-2-2601-1640

No. 30-2, Ding Fwu Tsuen, Lin
Kou District, New Taipei City,
Taiwan, R.O.C.

Kwei Shan

Tel: 886-3-271-8666

No. 3-1, Lane 6, Wen San 3rd St.,
Kwei Shan District, Tao Yuan City
333, Taiwan, R.O.C.

Kwei Shan Site II

Tel: 886-3-271-8640

No. 14-1, Lane 19, Wen San 3rd
St., Kwei Shan District, Tao Yuan
City 333, Taiwan, R.O.C.

If you have any suggestion, please feel free to contact us as below information.

Tel: 886-3-271-8666

Fax: 886-3-318-0155

Email: ICC_Service@icertifi.com.tw

==END==