



MEASUREMENT REPORT

FCC PART 15.247 / WLAN 802.11n-HT40

FCC ID: HD5-CN85L1N
APPLICANT: Honeywell International Inc
Application Type: Class II Permissive Change
Product: Mobile computer
Model No.: CN85L1N
FCC Classification: (DTS) Digital Transmission System
FCC Rule Part(s): Part 15.247
Test Procedure(s): ANSI C63.10-2013
Received Date: January 2, 2020
Test Date: January 6 ~ April 9, 2020

Tested By: 
(Fran Chen)

Reviewed By: 
(Paddy Chen)

Approved By: 
(Chenz Ker)



The test results only relate to the samples tested.

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI 63.10-2013. Test results reported herein relate only to the item(s) tested.

The test report shall not be reproduced except in full without the written approval of MRT Technology (Taiwan) Co., Ltd.

Revision History

Report No.	Version	Description	Issue Date	Note
2001TW0107-U1	1.0	Original Report	2020-04-14	

CONTENTS

Description	Page
§2.1033 General Information	5
1. INTRODUCTION	6
1.1. Scope.....	6
1.2. MRT Test Location	6
2. PRODUCT INFORMATION	7
2.1. Equipment Description	7
2.2. Working Frequencies for this Report	8
2.3. Test Mode	8
2.4. Test Software	9
2.5. EMI Suppression Device(s)/Modifications	9
2.6. Labeling Requirements	9
3. DESCRIPTION of TEST	10
3.1. Evaluation Procedure	10
3.2. AC Line Conducted Emissions	10
3.3. Radiated Emissions	11
4. ANTENNA REQUIREMENTS	12
5. TEST EQUIPMENT CALIBRATION DATE	13
6. MEASUREMENT UNCERTAINTY	14
7. TEST RESULT	15
7.1. Summary.....	15
7.2. 6dB Bandwidth Measurement	16
7.2.1. Test Limit.....	16
7.2.2. Test Procedure used	16
7.2.3. Test Setting	16
7.2.4. Test Setup	16
7.2.5. Test Result	17
7.3. Output Power Measurement.....	19
7.3.1. Test Limit.....	19
7.3.2. Test Procedure Used.....	19
7.3.3. Test Setting	19
7.3.4. Test Setup	19
7.3.5. Test Result of Output Power	20
7.4. Power Spectral Density Measurement	21
7.4.1. Test Limit.....	21
7.4.2. Test Procedure Used.....	21
7.4.3. Test Setting	21
7.4.4. Test Setup	21
7.4.5. Test Result	22
7.5. Out-of-Band Spurious Emissions Emissions Measurement	24
7.5.1. Test Limit.....	24

7.5.2.	Test Procedure Used	24
7.5.3.	Test Settling	24
7.5.4.	Test Setup	25
7.5.5.	Test Result	26
7.6.	Radiated Spurious Emission Measurement.....	31
7.6.1.	Test Limit.....	31
7.6.2.	Test Procedure Used.....	31
7.6.3.	Test Setting	31
7.6.4.	Test Setup	33
7.6.5.	Test Result	35
7.7.	Radiated Restricted Band Edge Measurement.....	43
7.7.1.	Test Limit.....	43
7.7.2.	Test Procedure Used.....	43
7.7.3.	Test Setting	43
7.7.4.	Test Setup	45
7.7.5.	Test Result	46
7.8.	AC Conducted Emissions Measurement	54
7.8.1.	Test Limit.....	54
7.8.2.	Test Setup	54
7.8.3.	Test Result	55
8.	CONCLUSION	57

§2.1033 General Information

Applicant	Honeywell International Inc
Applicant Address	9680 Old Bailes Rd, Fort Mill, SC 29707 USA
Manufacturer	Honeywell International Inc
Manufacturer Address	9680 Old Bailes Rd, Fort Mill, SC 29707 USA
Test Site	MRT Technology (Taiwan) Co., Ltd
Test Site Address	No. 38, Fuxing Second Rd., Guishan Dist., Taoyuan City 333, Taiwan (R.O.C)
Test Device Serial No.	N/A <input type="checkbox"/> Production <input checked="" type="checkbox"/> Pre-Production <input type="checkbox"/> Engineering

Test Facility / Accreditations

1. MRT facility is a FCC registered (Reg. No. 291082) test facility with the site description report on file and is designated by the FCC as an Accredited Test Firm.
2. MRT facility is an IC registered (MRT Reg. No. 21723) test laboratory with the site description on file at Industry Canada.
3. MRT Lab is accredited to ISO 17025 by the Taiwan Accreditation Foundation (TAF Cert. No. 3261) in EMC, Telecommunications and Radio testing for FCC (Designation Number: TW3261), Industry Taiwan, EU and TELEC Rules.


1. INTRODUCTION

1.1. Scope

Measurement and determination of electromagnetic emissions (EMC) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission and the Industry Canada Certification and Engineering Bureau.

1.2. MRT Test Location

The map below shows the location of the MRT LABORATORY, its proximity to the Taoyuan City. These measurement tests were conducted at the MRT Technology (Taiwan) Co., Ltd. Facility located at No.38, Fuxing 2nd Rd., Guishan Dist., Taoyuan City 33377, Taiwan (R.O.C).



2. PRODUCT INFORMATION

2.1. Equipment Description

Product Name	Mobile computer
Model No.	CN85L1N
Serial Number (S/N)	18325D8507
Brand Name	Honeywell
Supports Radios Spec.	WLAN: 2.4G: 802.11b/ g/ n(HT20)/ n(HT40); 5G: 802.11a/ n(HT20)/ ac(VHT20)/ n(HT40)/ ac(VHT40)/ac(VHT80) Bluetooth Dual Mode: V2.1+EDR/ V5.0 LE NFC 13.56MHz Zigbee
Wi-Fi Specification	802.11b/g/n
Frequency Range	For 802.11n(HT40): 2422 ~ 2452 MHz
2.4GHz Maximum Output Power (Peak)	802.11n(HT40): 26.20dBm
Type of Modulation	802.11n(HT40): OFDM, BPSK, QPSK, 16QAM, 64QAM

Note: This case is for adding WLAN 802.11n40 (Open 802.11n-H40 2.4GHz frequency band via software and we attest that there is no hardware change to this EUT), The model name shall be same as before, so the FCC C2PC is executed.

FCC Original Report Grant Date: 11/09/2018, FCC ID: HD5-CN85L1N.


2.2. Working Frequencies for this Report

802.11n-HT40

Channel	Frequency	Channel	Frequency	Channel	Frequency
03	2422 MHz	04	2427 MHz	05	2432 MHz
06	2437 MHz	07	2442 MHz	08	2447 MHz
09	2452 MHz	--	--	--	--

Duty Cycle

Test Mode	Duty Cycle
802.11 n-HT40	91%



2.3. Test Mode

Test Mode	Mode 1: Transmit by 802.11n-HT40
-----------	----------------------------------

Note:

- Regarding to the operation frequency, the lowest, middle and highest frequency are selected to perform the test.

2.4. Test Software

The test utility software used during testing was “QRCT”, and the version was 3.0.268.0.

Power Setting

WiFi Mode	Freq	Power Setting Final
802.11 n40	2422MHz	12
	2437MHz	14
	2452MHz	12.5

2.5. EMI Suppression Device(s)/Modifications

No EMI suppression device(s) were added and/or no modifications were made during testing.

2.6. Labeling Requirements

Per 2.1074 & 15.19; Docket 95-19

The label shall be permanently affixed at a conspicuous location on the device; instruction manual or pamphlet supplied to the user and be readily visible to the purchaser at the time of purchase. However, when the device is so small wherein placement of the label with specified statement is not practical, only the FCC ID must be displayed on the device per Section 15.19(a)(5). Please see attachment for FCC ID label and label location.

3. DESCRIPTION of TEST

3.1. Evaluation Procedure

The measurement procedures described in the American National Standard for Testing Unlicensed Wireless Devices (ANSI C63.10-2013), and the guidance provided in KDB 558074 D01v05r02 were used in the measurement of the device.

Deviation from measurement procedure.....None

3.2. AC Line Conducted Emissions

The line-conducted facility is located inside an 9'x4'x3' shielded enclosure. A 1m x 2m wooden table 80cm high is placed 40cm away from the vertical wall and 80cm away from the sidewall of the shielded room. Two 10kHz-30MHz, 50Ω/50uH Line-Impedance Stabilization Networks (LISNs) are bonded to the shielded room floor. Power to the LISNs is filtered by external high-current high-insertion loss power line filters. These filters attenuate ambient signal noise from entering the measurement lines. These filters are also bonded to the shielded enclosure.

The EUT is powered from one LISN and the support equipment is powered from the second LISN. All interconnecting cables more than 1 meter were shortened to a 1 meter length by non-inductive bundling (serpentine fashion) and draped over the back edge of the test table. All cables were at least 40cm above the horizontal reference ground-plane. Power cables for support equipment were routed down to the second LISN while ensuring that that cables were not draped over the second LISN.

Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The RF output of the LISN was connected to the receiver and exploratory measurements were made to determine the frequencies producing the maximum emission from the EUT. The receiver was scanned from 150kHz to 30MHz. The detector function was set to peak mode for exploratory measurements while the bandwidth of the analyzer was set to 9kHz. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Each emission was also maximized by varying: power lines, the mode of operation or data exchange speed, or support equipment which determined the worst-case emission. Once the worst case emissions have been identified, the one EUT cable configuration/arrangement and mode of operation that produced these emissions are used for final measurements on the same test site. The analyzer is set to CISPR quasi-peak and average detectors with a 9kHz resolution bandwidth for final measurements.

An extension cord was used to connect to a single LISN which powered by EUT. The extension cord was calibrated with LISN, the impedance and insertion loss are compliance with the requirements as stated in ANSI C63.10-2013.

3.3. Radiated Emissions

The radiated test facilities consisted of an indoor 3 meter semi-anechoic chamber used for final measurements and exploratory measurements, when necessary. The measurement area is contained within the semi-anechoic chamber which is shielded from any ambient interference. For measurements above 1GHz absorbers are arranged on the floor between the turn table and the antenna mast in such a way so as to maximize the reduction of reflections. For measurements below 1GHz, the absorbers are removed. A MF Model 210SS turntable is used for radiated measurement. It is a continuously rotatable, remote controlled, metallic turntable and 2 meters (6.56 ft.) in diameter. The turn table is flush with the raised floor of the chamber in order to maintain its function as a ground plane. An 80cm high PVC support structure is placed on top of the turntable. For all measurements, the spectrum was scanned through all EUT azimuths and from 1 to 4 meter receive antenna height using a broadband antenna from 30MHz up to the upper frequency shown in 15.33(b)(1) depending on the highest frequency generated or used in the device or on which the device operates or tunes. For frequencies above 1GHz, linearly polarized double ridge horn antennas were used. For frequencies below 30MHz, a calibrated loop antenna was used. When exploratory measurements were necessary, they were performed at 1 meter test distance inside the semi-anechoic chamber using broadband antennas, broadband amplifiers, and spectrum analyzers to determine the frequencies and modes producing the maximum emissions. Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The test set-up for frequencies below 1GHz was placed on top of the 0.8 meter high, 1 x 1.5 meter table; and test set-up for frequencies 1-40GHz was placed on top of the 1.5 meter high, 1 x 1.5 meter table. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Appropriate precaution was taken to ensure that all emissions from the EUT were maximized and investigated. The system configuration, clock speed, mode of operation or video resolution, if applicable, turntable azimuth, and receive antenna height was noted for each frequency found.

Final measurements were made in the semi-anechoic chamber using calibrated, linearly polarized broadband and horn antennas. The test setup was configured to the setup that produced the worst case emissions. The spectrum analyzer was set to investigate all frequencies required for testing to compare the highest radiated disturbances with respect to the specified limits. The turntable containing the EUT was rotated through 360 degrees and the height of the receive antenna was varied 1 to 4 meters and stopped at the azimuth and height producing the maximum emission. Each emission was maximized by changing the orientation of the EUT through three orthogonal planes and changing the polarity of the receive antenna, which produced the worst-case emissions. According to 3dB Beam-Width of horn antenna, the horn antenna should be always directed to the EUT when rising height.

4. ANTENNA REQUIREMENTS

Excerpt from §15.203 of the FCC Rules/Regulations:

“An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.”

- The antenna of the **Mobile computer**, is permanently attached.
- There are no provisions for connection to an external antenna.

Conclusion:

The EUT unit complies with the requirement of §15.203.

Antenna List

No.	Manufacturer	Part No.	Antenna Type	Peak Gain
1	N/A	N/A	PIFA	Ant0: 0.4dBi for 2.4GHz
				Ant1: 1.7dBi for 2.4GHz

5. TEST EQUIPMENT CALIBRATION DATE

Conducted Emissions – SR2

Instrument	Manufacturer	Type No.	Asset No.	Cali. Interval	Cali. Due Date
Two-Line V-Network	R&S	ENV216	MRTTWA00019	1 year	2020/4/25
Cable	Rosnol	N1C50-RG400- B1C50-500CM	MRTTWE00013	1 year	2020/6/18
EMI Test Receiver	R&S	ESR3	MRTTWA00009	1 year	2020/3/25

Radiated Emissions – AC1

Instrument	Manufacturer	Type No.	Asset No.	Cali. Interval	Cali. Due Date
Broadband TRILOG Antenna	SCHWARZBECK	VULB 9162	MRTTWA00001	1 year	2020/6/4
EMI Test Receiver	R&S	ESR3	MRTTWA00009	1 year	2020/3/25
Active Loop Antenna	Schwarzbeck	FMZB 1519B	MRTTWA00002	1 year	2020/4/29
Broadband Horn antenna	SCHWARZBECK	BBHA 9120D	MRTTWA00003	1 year	2020/4/22
Breitband Hornantenna	Schwarzbeck	BBHA 9170	MRTTWA00004	1 year	2020/4/23
Broadband Amplifier	Schwarzbeck	BBV 9721	MRTTWA00006	1 year	2020/4/24
Broadband Preamplifier	SCHWARZBECK	BBV 9718	MRTTWA00005	1 year	2020/4/24
Cable	HUBERSUHNER	SF106	MRTTWE00010	1 year	2020/4/22
Cable	Rosnol	K1K50-UP0264- K1K50-4M	MRTTWE00012	1 year	2020/6/18

Conducted Test Equipment – SR2

Instrument	Manufacturer	Type No.	Asset No.	Cali. Interval	Cali. Due Date
EXA Signal Analyzer	KEYSIGHT	N9010A	MRTTWA00012	1 year	2020/10/2
EXA Signal Analyzer	KEYSIGHT	N9010B	MRTTWA00074	1 year	2020/7/11
USB Wideband Power Sensor	KEYSIGHT	U2021XA	MRTTWA00015	1 year	2020/3/26

Test Software

Software	Version	Function
e3	9.160520a	EMI Test Software
EMI	V3	EMI Test Software

6. MEASUREMENT UNCERTAINTY

Where relevant, the following test uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k = 2$.

Conducted Emission- Power Line
Measuring Uncertainty for a Level of Confidence of 95% ($U=2U_c(y)$): 0.15MHz~30MHz: $\pm 2.53\text{dB}$
Radiated Spurious Emission
Measuring Uncertainty for a Level of Confidence of 95% ($U=2U_c(y)$): 9kHz~30MHz: $\pm 3.92\text{dB}$ 30MHz~1GHz: $\pm 4.25\text{dB}$ 1GHz~18GHz: $\pm 4.40\text{dB}$ 18GHz~40GHz: $\pm 4.45\text{dB}$
Frequency Error
Measuring Uncertainty for a Level of Confidence of 95% ($U=2U_c(y)$): $\pm 78.4\text{Hz}$
Conducted Power
Measuring Uncertainty for a Level of Confidence of 95% ($U=2U_c(y)$): $\pm 0.84\text{dB}$
Conducted Spurious Emission
Measuring Uncertainty for a Level of Confidence of 95% ($U=2U_c(y)$): $\pm 2.65\text{dB}$
Occupied Bandwidth
Measuring Uncertainty for a Level of Confidence of 95% ($U=2U_c(y)$): 3.3%
Temp. / Humidity
Measuring Uncertainty for a Level of Confidence of 95% ($U=2U_c(y)$): $\pm 0.82^\circ\text{C}$ / $\pm 3\%$
DC Voltage
Measuring Uncertainty for a Level of Confidence of 95% ($U=2U_c(y)$): $\pm 0.3\%$

7. TEST RESULT

7.1. Summary

FCC Part Section(s)	Test Description	Test Limit	Test Condition	Test Result	Reference
15.247(a)(2)	6dB Bandwidth	$\geq 500\text{kHz}$	Conducted	Pass	Section 7.2
15.247(b)(3)	Output Power	$\leq 30.00\text{dBm}$		Pass	Section 7.3
15.247(e)	Power Spectral Density	$\leq 8.00\text{dBm}/3\text{kHz}$		Pass	Section 7.4
15.247(d)	Out-of-Band Emissions	Conducted $\geq 20\text{dBc}$		Pass	Section 7.5
15.205 15.209	Spurious Emission	$< \text{FCC } 15.209 \text{ limits}$	Radiated	Pass	Section 7.6
15.205 15.209	Band Edge Measurement	$\leq 74\text{dBuV/m(Peak)}$ $\leq 54\text{dBuV/m(Average)}$		Pass	Section 7.7
15.207	AC Conducted Emissions 150kHz - 30MHz	$< \text{FCC } 15.207 \text{ limits}$	Line Conducted	Pass	Section 7.8

Notes:

- Determining compliance is based on the test results met the regulation limits or requirements declared by clients, and the test results don't take into account the value of measurement uncertainty.
- All modes of operation and data rates were investigated. For radiated emission test, every axis (X, Y, Z) was also verified. The test results shown in the following sections represent the worst case emissions.
- The analyzer plots shown in this section were all taken with a correction table loaded into the analyzer. The correction table was used to account for the losses of the cables and attenuators used as part of the system to connect the EUT to the analyzer at all frequencies of interest.
- All antenna port conducted emissions testing was performed on a test bench with the antenna port of the EUT connected to the spectrum analyzer through calibrated cables and attenuators.

7.2. 6dB Bandwidth Measurement

7.2.1. Test Limit

The minimum 6dB bandwidth shall be at least 500 kHz.


7.2.2. Test Procedure used

ANSI C63.10-2013 - Section 11.8 (6dB bandwidth)

7.2.3. Test Setting

1. The Spectrum's automatic bandwidth measurement capability was used to perform the 6dB bandwidth measurement. The "X" dB bandwidth parameter was set to $X = 6$. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
2. Set RBW = 100 kHz
3. $VBW \geq 3 \times RBW$
4. Detector = Peak
5. Trace mode = max hold
6. Sweep = auto couple
7. Allow the trace was allowed to stabilize


7.2.4. Test Setup




7.2.5. Test Result

6dB Bandwidth


Test Mode	Channel No.	Frequency (MHz)	6dB Bandwidth (MHz) Ant0	6dB Bandwidth (MHz) Ant1	Limit (MHz)	Result
802.11n-HT40	03	2422	35.430	36.390	≥ 0.5	Pass
802.11n-HT40	06	2437	36.140	36.360	≥ 0.5	Pass
802.11n-HT40	09	2452	36.410	36.400	≥ 0.5	Pass




802.11 n-HT40 CH03 (2422MHz) Ant 1



802.11 n-HT40 CH06 (2437MHz) Ant 1



802.11 n-HT40 CH09 (2452MHz) Ant 1



7.3. Output Power Measurement

7.3.1. Test Limit

The maximum out power shall be less 1 Watt (30dBm).

7.3.2. Test Procedure Used

ANSI C63.10 - Section 11.9.1.3

ANSI C63.10 - Section 11.9.2.3

7.3.3. Test Setting


Method PKPM1 (Peak Power Measurement)

Peak power measurements were performed only when the EUT was transmitting at its maximum power control level using a broadband power meter with a pulse sensor. The pulse sensor employs a VBW = 50MHz so this method was only used for signals whose DTS bandwidth was less than or equal to 50MHz.

Method AVGPM-G (Measurement using a gated RF average-reading power meter)

Measurements may be performed using a wideband gated RF power meter provided that the gate parameters are adjusted such that the power is measured only when the EUT is transmitting at its maximum power control level. Since this measurement is made only during the ON time of the transmitter, no duty cycle correction is required.

7.3.4. Test Setup



7.3.5. Test Result of Output Power

2.4GHz 802.11n-HT40 RF Output Power (dBm) Ant0											
Channel No.	Frequency (MHz)	Average Power For different Data Rate (Mbps)								Peak Power MCS0	Limit (dBm)
		MCS0	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7		
03	2422	12.60								22.08	30
06	2437	14.38	14.28	14.11	13.98	13.82	13.80	13.78	13.75	22.86	30
09	2452	13.03								22.05	30
2.4GHz 802.11n-HT40 RF Output Power (dBm) Ant1											
Channel No.	Frequency (MHz)	Average Power For different Data Rate (Mbps)								Peak Power MCS0	Limit (dBm)
		MCS0	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7		
03	2422	11.93								22.43	30
06	2437	14.02	13.85	13.72	13.48	13.25	13.16	13.04	12.93	23.60	30
09	2452	11.89								22.59	30
2.4GHz 802.11n-HT40 RF Output Power (dBm) Ant0+1											
Channel No.	Frequency (MHz)	Average Power For different Data Rate (Mbps)								Peak Power MCS0	Limit (dBm)
		MCS0	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7		
03	2422	15.29								25.27	30
06	2437	17.21	17.08	16.93	16.75	16.55	16.50	16.44	16.37	26.26	30
09	2452	15.51								25.34	30

Note: Output power =Reading value on power meter + cable loss °

7.4. Power Spectral Density Measurement

7.4.1. Test Limit

The maximum permissible power spectral density is 8dBm in any 3 kHz band.

7.4.2. Test Procedure Used


ANSI C63.10 - Section 11.10.2

7.4.3. Test Setting

This procedure shall be used if maximum peak conducted output power was used to demonstrate compliance, and is optional if the maximum conducted (average) output power was used to demonstrate compliance.


- a) Set analyzer center frequency to DTS channel center frequency.
- b) Set the span to 1.5 times the DTS bandwidth.
- c) Set the RBW to: 3 kHz.
- d) Set the VBW $\geq 3 \times$ RBW.
- e) Detector = peak.
- f) Sweep time = auto couple.
- g) Trace mode = max hold.
- h) Allow trace to fully stabilize.
- i) Use the peak marker function to determine the maximum amplitude level within the RBW.

7.4.4. Test Setup




7.4.5. Test Result


Test Mode	Channel No.	Freq. (MHz)	PSD Ant 0 (dBm/3KHz)	PSD Ant 1 (dBm/3KHz)	Total PSD Ant 0+1 (dBm/3KHz)	Limit (dBm/3KHz)	Result
11n-HT40	3	2422	-16.047	-16.482	-13.249	≤ 8	Pass
11n-HT40	6	2437	-13.677	-14.043	-10.846	≤ 8	Pass
11n-HT40	9	2452	-15.901	-15.359	-12.611	≤ 8	Pass




802.11 n-HT40 CH03 (2422MHz) Ant 1



802.11 n-HT40 CH06 (2437MHz) Ant 1



802.11 n-HT40 CH09 (2452MHz) Ant 1



7.5. Out-of-Band Spurious Emissions Emissions Measurement

7.5.1. Test Limit

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on RF conducted measurement, provided the transmitter demonstrates compliance with the peak conducted power limits.

7.5.2. Test Procedure Used

ANSI C63.10-2013- Section 11.11

7.5.3. Test Settling

Reference level measurement


1. Set instrument center frequency to DTS channel center frequency
2. Set the span to ≥ 1.5 times the DTS bandwidth
3. Set the RBW = 100 kHz
4. Set the VBW $\geq 3 \times$ RBW
5. Detector = peak
6. Sweep time = auto couple
7. Trace mode = max hold
8. Allow trace to fully stabilize

Emission level measurement

1. Set the center frequency and span to encompass frequency range to be measured
2. RBW = 100kHz
3. VBW = 300kHz
4. Detector = Peak
5. Trace mode = max hold
6. Sweep time = auto couple

7. The trace was allowed to stabilize

7.5.4. Test Setup




7.5.5. Test Result

Test Mode	Channel No.	Frequency (MHz)	Limit	Result
802.11n-HT40	03	2422	20dBc	Pass
802.11n-HT40	06	2437	20dBc	Pass
802.11n-HT40	09	2452	20dBc	Pass


802.11n-HT40 CH03 (2422MHz) Ant 0




802.11n-HT40 CH03 (2422MHz) Ant 0



802.11n-HT40 CH03 (2422MHz) Ant 0




802.11n-HT40 CH03 (2422MHz) Ant 0




802.11n-HT40 CH06 (2437MHz) Ant 0




802.11n-HT40 CH06 (2437MHz) Ant 0



802.11n-HT40 CH06 (2437MHz) Ant 0




802.11n-HT40 CH06 (2437MHz) Ant 0




802.11n-HT40 CH09 (2452MHz) Ant 0




802.11n-HT40 CH09 (2452MHz) Ant 0



802.11n-HT40 CH09 (2452MHz) Ant 0




802.11n-HT40 CH09 (2452MHz) Ant 0




802.11n-HT40 CH03 (2422MHz) Ant 1




802.11n-HT40 CH03 (2422MHz) Ant 1



802.11n-HT40 CH03 (2422MHz) Ant 1




802.11n-HT40 CH03 (2422MHz) Ant 1




802.11n-HT40 CH06 (2437MHz) Ant 1




802.11n-HT40 CH06 (2437MHz) Ant 1



802.11n-HT40 CH06 (2437MHz) Ant 1




802.11n-HT40 CH06 (2437MHz) Ant 1




802.11n-HT40 CH09 (2452MHz) Ant 1




802.11n-HT40 CH09 (2452MHz) Ant 1



802.11n-HT40 CH09 (2452MHz) Ant 1



802.11n-HT40 CH09 (2452MHz) Ant 1



7.6. Radiated Spurious Emission Measurement

7.6.1. Test Limit

All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47 CFR must not exceed the limits shown in Table per Section 15.209.

FCC Part 15 Subpart C Paragraph 15.209		
Frequency [MHz]	Field Strength [uV/m]	Measured Distance [Meters]
0.009 - 0.490	2400/F (kHz)	300
0.490 - 1.705	24000/F (kHz)	30
1.705 - 30	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

7.6.2. Test Procedure Used

ANSI C63.10 Section 11.12.2.3 (quasi-peak measurements)

ANSI C63.10 Section 11.12.2.4 (peak power measurements)

ANSI C63.10 Section 11.12.2.5 (average power measurements)

7.6.3. Test Setting

Peak Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = as specified in Table 1
3. VBW = 3MHz
4. Detector = peak
5. Sweep time = auto couple

6. Trace mode = max hold

7. Trace was allowed to stabilize

Table 1 - RBW as a function of frequency

Frequency	RBW
9 ~ 150 kHz	200 ~ 300 Hz
0.15 ~ 30 MHz	9 ~ 10 kHz
30 ~ 1000 MHz	100 ~ 120 kHz
> 1000 MHz	1 MHz

Average Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest

2. RBW = 1MHz

3. VBW $\geq 1/T$

4. De As an alternative, the instrument may be set to linear detector mode. Ensure that video filtering is applied in linear voltage domain (rather than in a log or dB domain). Some instruments require linear display mode in order to accomplish this. Others have a setting for Average-VBW Type, which can be set to “Voltage” regardless of the display mode

5. Detector = Peak


6. Sweep time = auto

7. Trace mode = max hold


8. Allow max hold to run for at least 50 times (1/duty cycle) traces

7.6.4. Test Setup


9kHz ~ 30MHz Test Setup:



30MHz ~ 1GHz Test Setup:




Above 1G Test Setup:



7.6.5. Test Result

EUT	Mobile computer	Date of Test	2020-01-06
Factor	VULB 9162	Temp. / Humidity	25°C /59%
Polarity	Horizontal	Site / Test Engineer	AC1 / Jay
Test Mode	802.11n40_TX_CH6_ANT 0+1	Test Voltage	By Battery




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	62.980	12.72	19.03	31.74	-8.26	40.00	100	200	QP
2	* 160.950	19.50	16.14	35.64	-7.86	43.50	100	300	QP
3	263.770	15.90	20.62	36.52	-9.48	46.00	200	150	QP
4	326.820	13.93	22.49	36.42	-9.58	46.00	300	400	QP
5	395.690	5.69	24.10	29.79	-16.21	46.00	100	355	QP
6	666.320	3.05	28.61	31.65	-14.35	46.00	100	5	QP

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Mobile computer	Date of Test	2020-01-06
Factor	VULB 9162	Temp. / Humidity	25°C /59%
Polarity	Vertical	Site / Test Engineer	AC1 / Jay
Test Mode	802.11n40_TX_CH6_ANT 0+1	Test Voltage	By Battery




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	32.910	9.06	18.59	27.65	-12.35	40.00	100	0	QP
2	61.040	10.44	19.73	30.17	-9.83	40.00	100	100	QP
3	206.540	15.14	18.71	33.86	-9.64	43.50	100	350	QP
4	262.800	16.35	20.61	36.96	-9.04	46.00	100	55	QP
5	* 328.760	15.19	22.57	37.76	-8.24	46.00	200	215	QP
6	391.810	7.89	24.04	31.93	-14.07	46.00	300	400	QP

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Mobile computer	Date of Test	2020-01-16
Factor	BBHA 9120D & BBHA 9170	Temp. / Humidity	23°C /58%
Polarity	Horizontal	Site / Test Engineer	AC1 / Kaunaz
Test Mode	802.11n40_TX_CH3_ANT 0+1	Test Voltage	By Battery




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	4844.000	36.97	3.24	40.20	-33.80	74.00	150	400	Peak
2	7266.000	34.80	11.19	45.99	-28.01	74.00	150	400	Peak
3	* 9688.000	33.24	14.24	47.47	-26.53	74.00	150	400	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB) – Preamplifier(dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Mobile computer	Date of Test	2020-01-16
Factor	BBHA 9120D & BBHA 9170	Temp. / Humidity	23°C /58%
Polarity	Vertical	Site / Test Engineer	AC1 / Kaunaz
Test Mode	802.11n40_TX_CH3_ANT 0+1	Test Voltage	By Battery




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	4844.000	37.10	3.24	40.34	-33.66	74.00	150	400	Peak
2	7266.000	34.04	11.19	45.23	-28.77	74.00	150	400	Peak
3	* 9688.000	31.81	14.24	46.05	-27.95	74.00	150	400	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB) – Preamplifier(dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Mobile computer	Date of Test	2020-01-16
Factor	BBHA 9120D & BBHA 9170	Temp. / Humidity	23°C /58%
Polarity	Horizontal	Site / Test Engineer	AC1 / Kaunaz
Test Mode	802.11n40_TX_CH6_ANT 0+1	Test Voltage	By Battery




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	4874.000	36.86	3.30	40.16	-33.84	74.00	150	400	Peak
2	7311.000	34.35	11.29	45.65	-28.35	74.00	150	400	Peak
3	* 9748.000	34.13	14.43	48.56	-25.44	74.00	150	400	Peak

Note:

- "*", means this data is the worst emission level.
- C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB) – Preamplifier(dB).
- Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
- The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Mobile computer	Date of Test	2020-01-16
Factor	BBHA 9120D & BBHA 9170	Temp. / Humidity	23°C /58%
Polarity	Vertical	Site / Test Engineer	AC1 / Kaunaz
Test Mode	802.11n40_TX_CH6_ANT 0+1	Test Voltage	By Battery




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	4874.000	32.35	3.30	35.65	-38.35	74.00	150	400	Peak
2	7311.000	33.02	11.29	44.31	-29.69	74.00	150	400	Peak
3	* 9748.000	31.22	14.43	45.65	-28.35	74.00	150	400	Peak

Note:

- "*", means this data is the worst emission level.
- C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB) – Preamplifier(dB).
- Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
- The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Mobile computer	Date of Test	2020-01-16
Factor	BBHA 9120D & BBHA 9170	Temp. / Humidity	23°C /58%
Polarity	Horizontal	Site / Test Engineer	AC1 / Kaunaz
Test Mode	802.11n40_TX_CH9_ANT 0+1	Test Voltage	By Battery




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	4904.000	36.42	3.36	39.78	-34.22	74.00	150	400	Peak
2	7356.000	34.13	11.39	45.52	-28.48	74.00	150	400	Peak
3	* 9808.000	34.49	14.63	49.12	-24.88	74.00	150	400	Peak

Note:

- "*", means this data is the worst emission level.
- C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB) – Preamplifier(dB).
- Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
- The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Mobile computer	Date of Test	2020-01-16
Factor	BBHA 9120D & BBHA 9170	Temp. / Humidity	23°C /58%
Polarity	Vertical	Site / Test Engineer	AC1 / Kaunaz
Test Mode	802.11n40_TX_CH9_ANT 0+1	Test Voltage	By Battery



No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	4904.000	35.57	3.36	38.93	-35.07	74.00	150	400	Peak
2	7356.000	32.77	11.39	44.16	-29.84	74.00	150	400	Peak
3	* 9808.000	33.27	14.63	47.90	-26.10	74.00	150	400	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB) – Preamplifier(dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

7.7. Radiated Restricted Band Edge Measurement

7.7.1. Test Limit

All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47 CFR must not exceed the limits shown in Table per Section 15.209.

FCC Part 15 Subpart C Paragraph 15.209		
Frequency [MHz]	Field Strength [uV/m]	Measured Distance [Meters]
0.009 - 0.490	2400/F (kHz)	300
0.490 - 1.705	24000/F (kHz)	30
1.705 – 30	30	30
30 – 88	100	3
88 – 216	150	3
216 – 960	200	3
Above 960	500	3

7.7.2. Test Procedure Used

1. ANSI C63.10 Section 6.3 (General Requirements)
2. ANSI C63.10 Section 6.6 (Standard test method above 1GHz)

7.7.3. Test Setting

Peak Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = as specified in Table 1
3. VBW = 3 * RBW
4. Detector = peak
5. Sweep time = auto couple

6. Trace mode = max hold
7. Trace was allowed to stabilize

Table 1 - RBW as a function of frequency


Frequency	RBW
9 ~ 150 kHz	200 ~ 300 Hz
0.15 ~ 30 MHz	9 ~ 10 kHz
30 ~ 1000 MHz	100 ~ 120 kHz
> 1000 MHz	1 MHz

Average Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1MHz
3. VBW $\geq 1/T$
4. De As an alternative, the instrument may be set to linear detector mode. Ensure that video filtering is applied in linear voltage domain (rather than in a log or dB domain). Some instruments require linear display mode in order to accomplish this. Others have a setting for Average-VBW Type, which can be set to "Voltage" regardless of the display mode
5. Detector = Peak
6. Sweep time = auto
7. Trace mode = max hold
8. Allow max hold to run for at least 50 times (1/duty cycle) traces


7.7.4. Test Setup

1GHz ~ 18GHz Test Setup:



7.7.5. Test Result

EUT	Mobile computer	Date of Test	2020-03-09
Factor	BBHA 9120D	Temp. / Humidity	18°C /52%
Polarity	Horizontal	Site / Test Engineer	AC1 / Jay
Test Mode	802.11n40_TX_CH3_ANT 0+1	Test Voltage	By Battery




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	* 2388.680	34.15	32.27	66.41	-7.59	74.00	150	140	Peak
2	2390.000	32.25	32.27	64.53	-9.47	74.00	150	140	Peak
3	2425.080	71.66	32.44	104.09	N/A	N/A	150	140	Peak

Note:

- "*", means this data is the worst emission level.
- C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB).
- Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
- The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Mobile computer	Date of Test	2020-03-09
Factor	BBHA 9120D	Temp. / Humidity	18°C /52%
Polarity	Horizontal	Site / Test Engineer	AC1 / Jay
Test Mode	802.11n40_TX_CH3_ANT 0+1	Test Voltage	By Battery




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2388.680	16.83	32.27	49.10	-4.90	54.00	150	140	Average
2	* 2390.000	17.63	32.27	49.90	-4.10	54.00	150	140	Average
3	2425.080	60.57	32.44	93.01	N/A	N/A	150	140	Average

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Mobile computer	Date of Test	2020-03-09
Factor	BBHA 9120D	Temp. / Humidity	18°C /52%
Polarity	Vertical	Site / Test Engineer	AC1 / Jay
Test Mode	802.11n40_TX_CH3_ANT 0+1	Test Voltage	By Battery




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2385.740	33.50	32.25	65.75	-8.25	74.00	150	280	Peak
2	* 2390.000	38.72	32.27	71.00	-3.00	74.00	150	280	Peak
3	2417.380	74.62	32.40	107.02	N/A	N/A	150	280	Peak

Note:

- "*", means this data is the worst emission level.
- C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB).
- Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
- The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Mobile computer	Date of Test	2020-03-09
Factor	BBHA 9120D	Temp. / Humidity	18°C /52%
Polarity	Vertical	Site / Test Engineer	AC1 / Jay
Test Mode	802.11n40_TX_CH3_ANT 0+1	Test Voltage	By Battery




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2385.740	15.71	32.25	47.96	-6.04	54.00	150	280	Average
2	* 2390.000	19.14	32.27	51.42	-2.58	54.00	150	280	Average
3	2417.380	62.77	32.40	95.17	N/A	N/A	150	280	Average

Note:

- "*", means this data is the worst emission level.
- C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB).
- Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
- The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Mobile computer	Date of Test	2020-03-09
Factor	BBHA 9120D	Temp. / Humidity	18°C /52%
Polarity	Horizontal	Site / Test Engineer	AC1 / Jay
Test Mode	802.11n40_TX_CH9_ANT 0+1	Test Voltage	By Battery




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2456.575	72.76	32.58	105.34	N/A	N/A	150	50	Peak
2	2483.500	37.20	32.70	69.90	-4.10	74.00	150	50	Peak
3	* 2484.325	37.38	32.71	70.09	-3.91	74.00	150	50	Peak

Note:

- "*", means this data is the worst emission level.
- C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB) .
- Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
- The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Mobile computer	Date of Test	2020-03-09
Factor	BBHA 9120D	Temp. / Humidity	18°C /52%
Polarity	Horizontal	Site / Test Engineer	AC1 / Jay
Test Mode	802.11n40_TX_CH9_ANT 0+1	Test Voltage	By Battery




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2456.575	61.13	32.58	93.71	N/A	N/A	150	50	Average
2	* 2483.500	17.27	32.70	49.97	-4.03	54.00	150	50	Average
3	2484.325	17.00	32.71	49.71	-4.29	54.00	150	50	Average

Note:

- "*", means this data is the worst emission level.
- C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB).
- Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
- The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Mobile computer	Date of Test	2020-03-09
Factor	BBHA 9120D	Temp. / Humidity	18°C /52%
Polarity	Vertical	Site / Test Engineer	AC1 / Jay
Test Mode	802.11n40_TX_CH9_ANT 0+1	Test Voltage	By Battery




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2443.750	74.06	32.52	106.58	N/A	N/A	150	275	Peak
2	2483.500	36.30	32.70	69.00	-5.00	74.00	150	275	Peak
3	* 2484.400	38.64	32.71	71.35	-2.65	74.00	150	275	Peak

Note:

- "*", means this data is the worst emission level.
- C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB).
- Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
- The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Mobile computer	Date of Test	2020-03-09
Factor	BBHA 9120D	Temp. / Humidity	18°C /52%
Polarity	Vertical	Site / Test Engineer	AC1 / Jay
Test Mode	802.11n40_TX_CH9_ANT 0+1	Test Voltage	By Battery



No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2443.750	62.58	32.52	95.11	N/A	N/A	150	275	Average
2	2483.500	16.36	32.70	49.07	-4.93	54.00	150	275	Average
3	* 2484.400	16.46	32.71	49.17	-4.83	54.00	150	275	Average

Note:

- "*", means this data is the worst emission level.
- C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB).
- Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
- The emission levels of other frequencies are very lower than the limit and not show in test report.

7.8. AC Conducted Emissions Measurement


7.8.1. Test Limit

FCC Part 15 Subpart C Paragraph 15.207 / RSS-Gen Limits		
Frequency (MHz)	QP (dB μ V)	Average (dB μ V)
0.15 - 0.50	66 - 56	56 - 46
0.50 - 5.0	56	46
5.0 - 30	60	50

Note 1: The lower limit shall apply at the transition frequencies.


Note 2: The limit decreases linearly with the logarithm of the frequency in the range 0.15MHz to 0.5MHz.

7.8.2. Test Setup



7.8.3. Test Result

EUT	Mobile computer	Date of Test	2020-02-14
Factor	CE_ENV216-L1 (Filter ON)	Temp. / Humidity	25.2°C /59%
Polarity	Line1	Site / Test Engineer	SR2 / Jay
Test Mode	802.11n40_TX_CH6_ANT 0+1	Test Voltage	AC 120V/60Hz




No		Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Remark (QP/PK/AV)
1		0.154	21.99	9.60	31.59	-34.16	65.75	QP
2		0.154	8.13	9.60	17.73	-38.02	55.75	Average
3		0.190	17.23	9.59	26.82	-37.20	64.01	QP
4		0.190	9.13	9.59	18.71	-35.30	54.01	Average
5	*	0.334	19.93	9.61	29.53	-29.81	59.34	QP
6		0.334	15.49	9.61	25.10	-24.24	49.34	Average
7		0.690	15.62	9.62	25.24	-30.76	56.00	QP
8	*	0.690	12.92	9.62	22.55	-23.45	46.00	Average
9		1.558	14.00	9.68	23.68	-32.32	56.00	QP
10		1.558	10.55	9.68	20.22	-25.78	46.00	Average
11		17.469	15.38	9.96	25.34	-34.66	60.00	QP
12		17.469	10.46	9.96	20.42	-29.58	50.00	Average

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).

EUT	Mobile computer	Date of Test	2020-02-14
Factor	CE_ENV216-N (Filter ON)	Temp. / Humidity	25.2°C /59%
Polarity	Neutral	Site / Test Engineer	SR2 / Jay
Test Mode	802.11n40_TX_CH6_ANT 0+1	Test Voltage	AC 120V/60Hz



No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Remark (QP/PK/AV)
1	0.168	20.40	9.61	30.00	-35.06	65.06	QP
2	0.168	0.59	9.61	10.20	-44.86	55.06	Average
3	0.235	13.17	9.61	22.78	-39.47	62.25	QP
4	0.235	6.40	9.61	16.01	-36.24	52.25	Average
5	0.366	20.22	9.61	29.83	-28.76	58.59	QP
6	*	0.366	9.61	28.84	-19.75	48.59	Average
7	*	1.761	9.68	31.64	-24.36	56.00	QP
8		1.761	9.68	24.92	-21.08	46.00	Average
9		3.273	9.70	24.45	-31.55	56.00	QP
10		3.273	9.70	18.11	-27.89	46.00	Average
11		17.770	10.01	27.75	-32.25	60.00	QP
12		17.770	10.01	21.52	-28.48	50.00	Average

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).

8. CONCLUSION

The data collected relate only the item(s) tested and show that the **Mobile computer** is in compliance with FCC Part 15C of the FCC Rules.

_____ The End _____