

RF Exposure Evaluation Report

Product : WIFI+BT Module
Trade mark : GSD
Model/Type reference : WCT5LM2001
Serial Number : N/A
Report Number : EED32L00242604
FCC ID : 2AC23-WCT5L
Date of Issue : Dec. 04, 2019
Test Standards : IEEE C95.1 2005
KDB 447498 D03
47 C.F.R. Part 1, Subpart I, Section 1.1310
47 C.F.R. Part 2, Subpart J, Section 2.1091
Test result : PASS

Prepared for:

Hui Zhou Gaoshengda Technology Co.,LTD
NO.75 Zhongkai Development Area,Huizhou,Guangdong, China

Prepared by:

Centre Testing International Group Co., Ltd.
Hongwei Industrial Zone, Bao'an 70 District,
Shenzhen, Guangdong, China
TEL: +86-755-3368 3668
FAX: +86-755-3368 3385

Tested By:

mark.chen.

Mark Chen

Compiled by:

Smile Zhong

Smile Zhong

Reviewed by:

Ware Xin

Ware Xin

Approved by:

Kevin Yang

Kevin Yang

Date:

Dec. 04, 2019

Check No.: 3096388499



2 Version

Version No.	Date	Description
00	Dec. 04, 2019	Original

3 Contents

	Page
1 COVER PAGE.....	1
2 VERSION.....	2
3 CONTENTS.....	3
4 GENERAL INFORMATION.....	4
4.1 CLIENT INFORMATION.....	4
4.2 GENERAL DESCRIPTION OF EUT.....	4
4.3 PRODUCT SPECIFICATION SUBJECTIVE TO THIS STANDARD.....	4
4.4 TEST LOCATION.....	6
4.5 DEVIATION FROM STANDARDS.....	6
4.6 ABNORMALITIES FROM STANDARD CONDITIONS.....	6
4.7 OTHER INFORMATION REQUESTED BY THE CUSTOMER.....	6
5 RF EXPOSURE EVALUATION.....	7
5.1 RF EXPOSURE COMPLIANCE REQUIREMENT.....	7
5.2 MAXIMUM PERMISSIBLE EXPOSURE.....	8
PHOTOGRAPHS OF EUT CONSTRUCTIONAL DETAILS.....	11

4 General Information

4.1 Client Information

Applicant:	Hui Zhou Gaoshengda Technology Co.,LTD
Address of Applicant:	NO.75 Zhongkai Development Area,Huizhou,Guangdong, China
Manufacturer:	Hui Zhou Gaoshengda Technology Co.,LTD
Address of Manufacturer:	NO.75 Zhongkai Development Area,Huizhou,Guangdong, China
Factory:	Hui Zhou Gaoshengda Technology Co.,LTD
Address of Factory:	NO.75 Zhongkai Development Area,Huizhou,Guangdong, China

4.2 General Description of EUT

Product Name:	WIFI+BT Module
Model No.(EUT):	WCT5LM2001
Trade Mark:	GSD
EUT Supports Radios application	BT 5.0 Dual mode 2.4G WiFi: 802.11b/g/n(20MHz)/n(40MHz) 5G WiFi: 802.11a/n(HT20)/n(HT40)/ac(HT20)/ac(HT40)/ac(HT80)

4.3 Product Specification subjective to this standard

Frequency Range:	BT 5.0 Dual mode: 2402MHz~2480MHz 2.4G WIFI: IEEE 802.11b/g/n(HT20): 2412MHz to 2462MHz IEEE 802.11n(HT40): 2422MHz to 2452MHz 5G WiFi: U-NII-1: 5.15-5.25GHz; U-NII-2a: 5.25-5.355GHz; U-NII-2c: 5.47-5.6GHz; U-NII-3: 5.725-5.85GHz			
Modulation Type:	GFSK, 8DPSK, π /4DQPSK OFDM, DSSS			
Test Software of EUT:	2.4G/5G WI-FI: MT7688 QA 0.0.2.6 BT: WCN Combo Tool			
Antenna Type:	PIFA antenna			
Antenna Gain:	BT 2 dBi / 2.4GHz 2 dBi / 5GHz 3dBi			
Antenna Specification	Bluetooth :	Antenna Gain :	2.00 dBi	(Numeric gain: 1.58)
	2.4GHz	Antenna Gain :	2.00 dBi	(Numeric gain: 1.58)
	5GHz	Antenna Gain :	3.00 dBi	(Numeric gain: 2.00)

Maximum tune up power	SISO		
	Bluetooth:	5.50 dBm	(3.548 mW)
	2.4G WIFI		
	IEEE 802.11b Mode:	19.00 dBm	(79.433 mW)
	IEEE 802.11g Mode:	22.50 dBm	(177.828 mW)
	IEEE 802.11n HT 20 Mode:	21.00 dBm	(125.893 mW)
	IEEE 802.11n HT 40 Mode:	21.00 dBm	(125.893 mW)
	5G WIFI		
	IEEE 802.11a Mode:	18.00 dBm	(63.096 mW)
	IEEE 802.11n HT 20 Mode:	16.00 dBm	(39.811 mW)
	IEEE 802.11n HT 40 Mode:	16.00 dBm	(39.811 mW)
	IEEE 802.11ac VHT 20 Mode:	16.00 dBm	(39.811 mW)
	IEEE 802.11ac VHT 40 Mode:	15.00 dBm	(31.623 mW)
	IEEE 802.11ac VHT 80 Mode:	11.00 dBm	(12.589 mW)
	MIMO		
	2.4G WIFI		
	IEEE 802.11n HT 20 Mode:	24.50 dBm	(281.838 mW)
	IEEE 802.11n HT 40 Mode:	24.50 dBm	(281.838 mW)
	5G WIFI		
	IEEE 802.11n HT 20 Mode:	19.00 dBm	(79.433 mW)
	IEEE 802.11n HT 40 Mode:	19.00 dBm	(79.433 mW)
	IEEE 802.11ac VHT 20 Mode:	19.00 dBm	(79.433 mW)
	IEEE 802.11ac VHT 40 Mode:	19.50 dBm	(89.125 mW)
	IEEE 802.11ac VHT 80 Mode:	14.00 dBm	(25.119 mW)
Power Supply:	DC 3.3V		
Sample Received Date:	Aug. 29, 2019		
Sample tested Date:	Aug. 29, 2019 to Nov. 04, 2019		

4.4 Test Location

All tests were performed at:

Centre Testing International Group Co., Ltd

Building C, Hongwei Industrial Park Block 70, Bao'an District, Shenzhen, China

Telephone: +86 (0) 755 33683668 Fax: +86 (0) 755 33683385

No tests were sub-contracted.

FCC Designation No.: CN1164

4.5 Deviation from Standards

None.

4.6 Abnormalities from Standard Conditions

None.

4.7 Other Information Requested by the Customer

None.

5 RF Exposure Evaluation

5.1 RF Exposure Compliance Requirement

Given $E = \frac{\sqrt{30 \times P \times G}}{d}$ & $S = \frac{E^2}{377}$

Where E = Field strength in Volts / meter

P = Power in Watts

G = Numeric antenna gain

d = Distance in meters

S = Power density in milliwatts / square centimeter

Combining equations and re-arranging the terms to express the distance as a function of the remaining variables yields:

$$S = \frac{30 \times P \times G}{377d^2}$$

Changing to units of mW and cm, using:

$$P \text{ (mW)} = P \text{ (W)} / 1000 \text{ and}$$

$$d \text{ (cm)} = d \text{ (m)} / 100$$

Yields

$$S = \frac{30 \times (P/1000) \times G}{377 \times (d/100)^2} = 0.0796 \times \frac{P \times G}{d^2} \quad \text{Equation 1}$$

Where d = Distance in cm

P = Power in mW

G = Numeric antenna gain

S = Power density in mW / cm²

5.2 Maximum Permissible Exposure

Substituting the MPE safe distance using $d = 20$ cm into Equation 1:

$$S = 0.000199 \times P \times G$$

Where P = Power in mW

G = Numeric antenna gain

S = Power density in mW / cm²

SISO Bluetooth:

Ch.	Frq.(MHz)	P(mW)	Gain(num.)	D(cm)	Power density in mW/cm ²	Limit(mW/cm ²)
78	2480	5.548	1.58	20	0.0017	1

2.4G WIFI IEEE 802.11b mode:

Ch.	Frq.(MHz)	P(mW)	Gain(num.)	D(cm)	Power density in mW/cm ²	Limit(mW/cm ²)
6	2437	90.991	1.58	20	0.0287	1

IEEE 802.11g mode:

Ch.	Frq.(MHz)	P(mW)	Gain(num.)	D(cm)	Power density in mW/cm ²	Limit(mW/cm ²)
6	2437	229.087	1.58	20	0.0723	1

IEEE 802.11n HT20 mode:

Ch.	Frq.(MHz)	P(mW)	Gain(num.)	D(cm)	Power density in mW/cm ²	Limit(mW/cm ²)
6	2437	145.211	1.58	20	0.0458	1

IEEE 802.11n HT40 mode:

Ch.	Frq.(MHz)	P(mW)	Gain(num.)	D(cm)	Power density in mW/cm ²	Limit(mW/cm ²)
9	2452	152.055	1.58	20	0.0480	1

5G WIFI
IEEE 802.11a mode:

Ch.	Frq.(MHz)	P(mW)	Gain(num.)	D(cm)	Power density in mW/cm ²	Limit(mW/cm ²)
157	5785	67.298	2	20	0.0267	1

IEEE 802.11 HT20 mode:

Ch.	Frq.(MHz)	P(mW)	Gain(num.)	D(cm)	Power density in mW/cm ²	Limit(mW/cm ²)
64	5320	55.719	2	20	0.0221	1

IEEE 802.11 HT40 mode:

Ch.	Frq.(MHz)	P(mW)	Gain(num.)	D(cm)	Power density in mW/cm ²	Limit(mW/cm ²)
62	5310	59.566	2	20	0.0237	1

IEEE 802.11ac VHT20 mode:

Ch.	Frq.(MHz)	P(mW)	Gain(num.)	D(cm)	Power density in mW/cm ²	Limit(mW/cm ²)
64	5320	56.494	2	20	0.0224	1

IEEE 802.11ac VHT40 mode:

Ch.	Frq.(MHz)	P(mW)	Gain(num.)	D(cm)	Power density in mW/cm ²	Limit(mW/cm ²)
38	5190	48.529	2	20	0.0193	1

IEEE 802.11ac VHT80 mode:

Ch.	Frq.(MHz)	P(mW)	Gain(num.)	D(cm)	Power density in mW/cm ²	Limit(mW/cm ²)
42	5210	14.825	2	20	0.0059	1

MIMO
2.4G WIFI
IEEE 802.11n HT20 mode:

Ch.	Frq.(MHz)	P(mW)	Gain(num.)	D(cm)	Power density in mW/cm ²	Limit(mW/cm ²)
6	2437	299.226	1.58	20	0.0944	1

Report No. : EED32L00242604

Page 10 of 11

IEEE 802.11n HT40 mode:

Ch.	Frq.(MHz)	P(mW)	Gain(num.)	D(cm)	Power density in mW/cm ²	Limit(mW/cm ²)
3	2422	307.610	1.58	20	0.0970	1

5G WIFI

IEEE 802.11 HT20 mode:

Ch.	Frq.(MHz)	P(mW)	Gain(num.)	D(cm)	Power density in mW/cm ²	Limit(mW/cm ²)
157	5785	98.628	2	20	0.0392	1

IEEE 802.11 HT40 mode:

Ch.	Frq.(MHz)	P(mW)	Gain(num.)	D(cm)	Power density in mW/cm ²	Limit(mW/cm ²)
159	5795	96.161	2	20	0.0382	1

IEEE 802.11ac VHT20 mode:

Ch.	Frq.(MHz)	P(mW)	Gain(num.)	D(cm)	Power density in mW/cm ²	Limit(mW/cm ²)
157	5785	96.161	2	20	0.0382	1

IEEE 802.11ac VHT40 mode:

Ch.	Frq.(MHz)	P(mW)	Gain(num.)	D(cm)	Power density in mW/cm ²	Limit(mW/cm ²)
159	5795	100.693	2	20	0.0400	1

IEEE 802.11ac VHT80 mode:

Ch.	Frq.(MHz)	P(mW)	Gain(num.)	D(cm)	Power density in mW/cm ²	Limit(mW/cm ²)
155	5775	31.261	2	20	0.0124	1

PHOTOGRAPHS OF EUT Constructional Details

Refer to Report No. EED32L00242601 for EUT external and internal photos.

*** End of Report ***

The test report is effective only with both signature and specialized stamp, The result(s) shown in this report refer only to the sample(s) tested. Without written approval of CTI, this report can't be reproduced except in full.