

FCC Test Report

Report No.: AGC11034221102FE08

FCC ID	:	2A4AS-2211A
APPLICATION PURPOSE	:	Original Equipment
PRODUCT DESIGNATION	:	IP Camera
BRAND NAME	:	Reolink
MODEL NAME	:	Reolink Duo 2 LTE
APPLICANT	:	EZTECH DIGITAL INC.
DATE OF ISSUE	:	Dec. 08, 2022
STANDARD(S)	:	FCC Part 22H & 24E& 27L Rules
REPORT VERSION	:	V1.0







REPORT REVISE RECORD

Report Version	Revise Time	Issued Date Valid Version Not		Notes
V1.0	/	Dec. 08, 2022	Valid	Initial Release



Report No.: AGC11034221102FE08 Page 3 of 55

TABLE OF CONTENTS

1. GENERAL INFORMATION	5
2. PRODUCT INFORMATION	6
2.1 PRODUCT TECHNICAL DESCRIPTION	6
2.2 RELATED SUBMITTAL(S) / GRANT (S)	7
2.3 TEST METHODOLOGY	7
2.4 DEVICE CAPABILITIES	7
2.5 SPECIAL ACCESSORIES	7
2.6 EQUIPMENT MODIFICATIONS	7
2.7 EMISSION DESIGNATOR	7
3. TEST ENVIRONMENT	9
3.1 ADDRESS OF THE TEST LABORATORY	9
3.2 TEST FACILITY	9
3.3 ENVIRONMENTAL CONDITIONS	
3.4 MEASUREMENT UNCERTAINTY	
3.5 LIST OF TEST EQUIPMENT	11
4. SYSTEM TEST CONFIGURATION	13
4.1 EUT CONFIGURATION	13
4.2 EUT EXERCISE	13
4.3 CONFIGURATION OF EUT SYSTEM	13
4.4 EQUIPMENT USED IN TESTED SYSTEM	13
5. SUMMARY OF TEST RESULTS	14
5.1 TEST CONDITION : CONDUCTED TEST	14
5.2 TEST CONDITION : RADIATED TEST	14
6. DESCRIPTION OF TEST MODES	15
7. CONDUCTED OUTPUT POWER	
7.1 PROVISIONS APPLICABLE	
7.2 MEASUREMENT METHOD	
7.3 MEASUREMENT SETUP	
7.4 MEASUREMENT RESULT	
8. RADIATED OUTPUT POWER	
8.1 PROVISIONS APPLICABLE	
8.2 MEASUREMENT METHOD	
8.3 MEASUREMENT SETUP	
8.4 MEASUREMENT RESULT	



Report No.: AGC11034221102FE08 Page 4 of 55

9.1 PROVISIONS APPLICABLE	24
9.2 MEASUREMENT METHOD	24
9.3 MEASUREMENT SETUP	25
9.4 MEASUREMENT RESULT	
10. OCCUPIED BANDWIDTH	27
10.1 PROVISIONS APPLICABLE	
10.2 MEASUREMENT METHOD	
10.3 MEASUREMENT SETUP	
10.4 MEASUREMENT RESULT	
11. BAND EDGE EMISSIONS AT ANTENNA TERMINAL	
11.1 MEASUREMENT OVERVIEW	
11.2 MEASUREMENT METHOD	
11.3 MEASUREMENT METHOD	
11.4 MEASUREMENT RESULT	
12. SPURIOUS EMISSIONS AT ANTENNA TERMINAL	
12.1 PROVISIONS APPLICABLE	
12.2 MEASUREMENT METHOD	
12.3 MEASUREMENT SETUP	
12.4 MEASUREMENT RESULT	
13. RADIATED SPURIOUS EMISSION	40
13.1. PROVISIONS APPLICABLE	
13.2. MEASUREMENT PROCEDURE	
13.3. MEASUREMENT SETUP	
13.4 MEASUREMENT RESULT	
14. FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE	
14.1 PROVISIONS APPLICABLE	
14.2 MEASUREMENT METHOD	
14.3 MEASUREMENT SETUP	
14.4 MEASUREMENT RESULT	
APPENDIX A: PHOTOGRAPHS OF TEST SETUP	55
APPENDIX B: PHOTOGRAPHS OF EUT	



1. GENERAL INFORMATION

Applicant	EZTECH DIGITAL INC.
Address	251 Little Falls Drive Wilmington Delaware 19808 United States
Manufacturer	Reolink Innovation Limited
Address	FLAT/RM 705 7/F FA YUEN COMMERCIAL BUILDING 75-77 FA YUEN STREET MONG KOK KL HONG KONG
Factory	Shenzhen Reolink Technology Co., Ltd
Address	2-4th Floor, Building 2, Yuanling Industrial Park, ShangWu, Shiyan Street, Bao'an District, Shenzhen, China
Product Designation	IP Camera
Brand Name	Reolink
Test Model	Reolink Duo 2 LTE
Date of receipt of test item	Nov. 21, 2022
Date of test	Nov. 21, 2022~Dec. 08, 2022
Deviation	No any deviation from the test method.
Condition of Test Sample	Normal

WE HEREBY CERTIFY THAT:

The above equipment was tested by Attestation of Global Compliance(Shenzhen) Co., Ltd. The data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI/TIA-603-E-2016. The sample tested as described in this report is in compliance with the FCC Rules Part 22H, 24E and 27L. The test results of this report relate only to the tested sample identified in this report.

Bibo 2hang Prepared By Bibo Zhang Dec. 08, 2022 (Project Engineer) alin Lin r) Dec **Reviewed By** Calvin Liu Dec. 08, 2022 (Reviewer) ax Zhan Approved By Max Zhang Dec. 08, 2022 Authorized Officer



2. PRODUCT INFORMATION

2.1 PRODUCT TECHNICAL DESCRIPTION

A major technical description of EUT is described as following:

Product Designation:	IP Camera			
Hardware Version:	N29C04 V110 L3G09 V	N29C04 V110 L3G09 V110		
Software Version:	BIPC_529MIX4G32M2	1B17B6MP		
Support Networks:	WCDMA, HSDPA, HSU	IPA		
	UMTS FDD Band II	UMTS FDD Band IV		
Frequency Bands:	UMTS FDD Band V (U.S. Bands)		
	UMTS FDD Band I	UMTS FDD Band VIII (N	on-U.S. Bands)	
Type of Modulation:	BPSK,QPSK Modulatio	n For WCDMA/HSDPA/H	SUPA	
	WCDMA Band II: 1852.	4MHz-1907.6 MHz		
Frequency Range:	WCDMA Band IV: 1712	.4-1752.6 MHz		
	WCDMA Band V: 826.4	-846.6 MHz		
	WCDMA Band II:	4M18F9W		
Emission Designator:	WCDMA Band IV:	and IV: 4M18F9W		
	WCDMA Band V:	4M18F9W		
Antenna Type:	External Antenna			
Antenna gain:	WCDMA850:1.98dBi	WCDMA1700:4.19dBi	WCDMA1900:4.6dBi	
Power Supply:	DC3.65V from battery			
Battery parameter:	DC 3.65V 10000mAh			
Single Card:	WCDMA Card Slot			
Extreme Vol. Limits:	DC3.10V to 4.20V (Normal: DC 3.65V)			
Extreme Temp. Tolerance	-30 °C to +50 °C			
Temperature range:	-20℃ to +50℃			

WCDMA SLOT:

	Maximum ERP/EIRP	Max. Average
	(dBm)	Burst Power (dBm)
UMTS BAND V	22.52	23.41
UMTS BAND II	21.95	23.03
UMTS BAND IV	22.02	23.04



2.2 RELATED SUBMITTAL(S) / GRANT (S)

This submittal(s) (test report) is intended for **FCC ID: 2A4AS-2211A**, filing to comply with the FCC Part 22H&24E&27L requirements.

2.3 TEST METHODOLOGY

The tests were performed according to following standards:

No.	Identity	Document Title
1	47 CFR FCC Part 2	Frequency allocations and radio treaty matters, general rules and regulations.
2	47 CFR FCC Part 22	Public Mobile Services.
3	47 CFR FCC Part 24	Personal Communications Services.
4	47 CFR FCC Part 27	Miscellaneous Wireless Communications Services.
F		American National Standard for Compliance Testing of Transmitters
5	ANSI 003.20-2015	Used in Licensed Radio Services
6		Land Mobile FM or PM Communications Equipment Measurement and
0	ANSI/11A-003-E-2010	Performance Standards
7	KDB 971168	D01 v03r01 Measurement Guidance For Certification Of Licensed Digital
		Transmitters.

2.4 DEVICE CAPABILITIES

850/1700/1900 WCDMA/HSPA, Multi-Band LTE,.

For emissions from 1GHz – 18GHz, low, mid, and high channels were tested with highest power and worst case configuration.

The emissions below 1GHz and above 18GHz were tested with the highest transmitting power channel and the worst case configuration.

The EUT was manipulated through three orthogonal planes of X-orientation (flatbed), Y-orientation

(landscape), and Z-orientation (portrait) during the testing. Only the worst case emissions were reported in this test report.

2.5 SPECIAL ACCESSORIES

The battery was supplied by the applicant were used as accessories and being tested with EUT intended for FCC grant together.

2.6 EQUIPMENT MODIFICATIONS

Not available for this EUT intended for grant.

2.7 EMISSION DESIGNATOR



Report No.: AGC11034221102FE08 Page 8 of 55

GSM Emission Designator

Emission Designator = 249KGXW GSM BW = 249 kHz G = Phase Modulation X = Cases not otherwise covered W = Combination (Audio/Data)

WCDMA Emission Designator

Emission Designator = 4M17F9W WCDMA BW = 4.17 MHz F = Frequency Modulation 9 = Composite Digital Info W = Combination (Audio/Data)

QAM Modulation

Emission Designator = 4M48W7D

LTE BW = 4.48 MHz W = Amplitude/Angle Modulated 7 = Quantized/Digital Info D = Data transmission; telemetry; telecommand

EDGE Emission Designator

Emission Designator = 249KG7W GSM BW = 249 kHz G = Phase Modulation 7 = Quantized/Digital Info W = Combination (Audio/Data)

QPSK Modulation

Emission Designator = 4M48G7D

LTE BW = 4.48 MHz G = Phase Modulation 7 = Quantized/Digital Info D = Data transmission; telemetry; telecommand



3. TEST ENVIRONMENT

3.1 ADDRESS OF THE TEST LABORATORY

Laboratory: Attestation of Global Compliance (Shenzhen) Co., Ltd

Address: 1-2/F, Building 19, Junfeng Industrial Park, Chongqing Road, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China

3.2 TEST FACILITY

The test facility is recognized, certified, or accredited by the following organizations:

CNAS-Lab Code: L5488

Attestation of Global Compliance (Shenzhen) Co., Ltd. has been assessed and proved to be in compliance with CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories (identical to ISO/IEC17025: 2017 General Requirements) for the Competence of Testing and Calibration Laboratories

A2LA-Lab Cert. No.: 5054.02

Attestation of Global Compliance (Shenzhen) Co., Ltd. EMC Laboratory has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025: 2017 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

FCC-Registration No.: 975832

Attestation of Global Compliance (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files with Registration 975832.

IC-Registration No.: 24842

Attestation of Global Compliance (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the Certification and Engineering Bureau of Industry Canada. The acceptance letter from the IC is maintained in our files with Registration 24842



3.3 ENVIRONMENTAL CONDITIONS

	NORMAL CONDITIONS	EXTREME CONDITIONS			
Temperature range	15~35 ℃	-20° ℃ ~50° ℃			
Humidty range	20 % to 75 %.	20 % to 75 %.			
Pressure range	86-106kPa	86-106kPa			
Power supply	DC 3.65V	DC3.10V or 4.20V			
Neter The Extense Teachant and Extense Matterney destants of the second statement					

Note: The Extreme Temperature and Extreme Voltages declared by the manufacturer.

3.4 MEASUREMENT UNCERTAINTY

Test	Measurement Uncertainty	Notes
Transmitter power conducted	±0.57 dB	(1)
Transmitter power Radiated	±2.20 dB	(1)
Conducted spurious emission 9KHz-40 GHz	±2.20 dB	(1)
Occupied Bandwidth	±0.01ppm	(1)
Radiated Emission 30~1000MHz	±4.10dB	(1)
Radiated Emission Above 1GHz	±4.32dB	(1)
Conducted Disturbance0.15~30MHz	±3.20dB	(1)
Radio Frequency	± 6.5 x 10-8	(1)
RF Power, Conducted	± 0.9 dB	(1)

Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.



3.5 LIST OF TEST EQUIPMENT

Equipment	Manufacturer	Model	S/N	Cal. Date	Cal. Due
TEST RECEIVER	R&S	ESPI	101206	Aug. 04, 2022	Aug. 03, 2023
LISN	R&S	ESH2-Z5	100086	Jun. 08, 2022	Jun. 07, 2023
TEST RECEIVER	R&S	ESCI	10096	Mar. 28, 2022	Mar. 27, 2023
EXA Signal Analyzer	Aglient	N9010A	MY53470504	Aug. 04, 2022	Aug. 03, 2023
Horn antenna	SCHWARZBECK	BBHA 9170	#768	Sep. 19, 2021	Sep. 18, 2023
preamplifier	ChengYi	EMC184045S E	980508	Oct. 29, 2021	Oct. 28, 2023
Double-Ridged Waveguide Horn	ETS LINDGREN	3117	00034609	Apr. 23, 2021	Apr. 22, 2023
Broadband Preamplifier	SCHWARZBECK	BBV 9718	9718-205	Jun.06, 2022	Jun.05, 2023
ANTENNA	SCHWARZBECK	VULB9168	D69250	Apr. 28, 2021	Apr. 27, 2023
ANTENNA	SCHWARZBECK	VULB9168	VULB9168-494	Jan. 08, 2021	Jan. 07, 2023
SIGNAL ANALYZER	Agilent	N9020A	MY52090123	Aug. 04, 2022	Aug. 03, 2023
USB Wideband Power Sensor	Agilent	U2021XA	MY54110007	May 11, 2021	May 10, 2025
Universal Radio Communication Tester	R&S	CMU200	120237	Jun. 08, 2022	Jun. 07, 2023
Universal Radio Communication Tester	Agilent	8960	GB46200384	Aug. 04, 2022	Aug. 03, 2023
Power Splitter	Agilent	11636A	34	Jun.06, 2022	Jun.05, 2023
Attenuator	JFW	50FHC-006-50	N/A	Jun.06, 2022	Jun.05, 2023
Horn Ant (18G-40GHz)	Schwarzbeck	BBHA 9170		Sep. 17, 2022	Sep. 16, 2023
Horn Ant (18G-40GHz)	ETS	QWH_SL_18_ 40_K_SG		Sep. 17, 2022	Sep. 16, 2023
Power Splitter	Agilent	11636A	/	Sep.12, 2022	Sep.11, 2023



Report No.: AGC11034221102FE08 Page 12 of 55

CMU200	R&S	120237	/	Jun. 07, 2022	Jun. 06, 2023
Artificial Mains					
Network	R&S	101242	/	Jun. 07, 2022	Jun. 06, 2023
ENV216					
Filter Bank					
Notch		010	/	Feb. 21, 2022	Feb. 20, 2023
1(880-915MHz)	5				
Filter Bank					
Notch 2		009	/	Feb. 21, 2022	Feb. 20, 2023
(1710-1785MHz)	5				
Filter Bank					
Notch 3		008	/	Feb. 21, 2022	Feb. 20, 2023
(1920-1980MHz)	3				



4. SYSTEM TEST CONFIGURATION

4.1 EUT CONFIGURATION

The EUT configuration for testing is installed on RF field strength measurement to meet the Commission's requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

4.2 EUT EXERCISE

The Transmitter was operated in the maximum output power mode through Communication Tester. The TX frequency was fixed which was for the purpose of the measurements.

4.3 CONFIGURATION OF EUT SYSTEM



Table 2-1 Equipment Used in EUT System

4.4 EQUIPMENT USED IN TESTED SYSTEM

The Following Peripheral Devices And Interface Cables Were Connected During The Measurement:

\boxtimes	Test Accessorie	s Come F	From The	Laboratory
-------------	-----------------	----------	----------	------------

Item	Equipment	Model No.	Identifier	Note
1	Adapter	HW-050200C01	Input: AC 100~240V 50/60Hz,0.5A Output: DC 5.0V 2A	Accessories

☑ Test Accessories Come From The Manufacturer

Item	Equipment	Model No.	Identifier	Note
1	IP Camera	Reolink Duo 2 LTE	2A4AS-2211A	EUT
2	Battery	Battery-Li8	DC 3.65V 10000mAh	Accessories
3	USB Cable	N/A	N/A	Accessories



5. SUMMARY OF TEST RESULTS

5.1 TEST CONDITION : CONDUCTED TEST

ltem	Test Description	FCC Rules	Result
1	Occupied Bandwidth	§2.1049	Pass
2	Band Edge / Spurious and Harmonic Emissions at Antenna Terminal	§2.1051, §22.917(a), §24.238(a) §27.53(h)	Pass
5	Conducted Output Power	§2.1046	Pass
6	Frequency stability / variation of ambient temperature	§2.1055, § 22.355, §24.235, §27.54	Pass
7	Peak- to- Average Ratio	§24.232(d), §27.50(d)(5),	Pass

5.2 TEST CONDITION : RADIATED TEST

Item	Test Description	FCC Rules	Result
1	Effective Radiated Power	§22.913(a)(5)	Pass
2	Equivalent Isotropic Radiated Power	§24.232(c), §27.50(d)(4)	Pass
3	Radiated Spurious and Harmonic Emissions	§2.1053, §22.917(a), §24.238(a), §27.53(h)	Pass



6. DESCRIPTION OF TEST MODES

			RF Channel	Channel	
Bands	Tx/Rx Frequency	Low(L)	Middle(M)	High(H)	
	ТХ	Channel 4132	Channel 4182	Channel 4233	
WCDMA band V	(824 MHz ~ 849 MHz)	826.4 MHz	836.4 MHz	846.6 MHz	

Bands		RF Channel		
Danas	TX/IX/Trequency	Low(L)	Middle(M)	High(H)
	ТХ	Channel 9262	Channel 9400	Channel 9538
WCDMA Band II	(1850 MHz-1910 MHz)	1852.4 MHz	1880.0 MHz	1907.6 MHz

		RF Channel		
Bands	Tx/Rx Frequency	Low(L)	Middle(M)	High(H)
	ТХ	Channel 1312	Channel 1412	Channel 1513
WCDMA Band IV	(1710 MHz-1755 MHz)	1712.4 MHz	1732.4 MHz	1752.6 MHz

Pre-scan all bandwidth and RB, find worse case mode are chosen to the report, the worse mode applicability and tested channel detail as below:

Band	Radiated	Conducted
WCDMA Band II/IV/V	RMC 12.2kbps Link	RMC 12.2kbps Link



ACCORDING TO 3GPP 25.101 SUB-CLAUSE 6.2.2 , THE MAXIMUM OUTPUT POWER IS ALLOWED TO BE REDUCED BY FOLLOWING THE TABLE.

Table 6.1aA: UE maximum output power with HS-DPCCH and E-DCH

UE Transmit Channel Configuration	CM(db)	MPR(db)		
For all combinations of ,DPDCH,DPCCH	0< CM<2.5			
HS-DPDCH, E-DPDCH and E-DPCCH				
Note: CM=1 for β_c/β_d =12/15, β_{hs}/β_c =24/15. For all other combinations of DPDCH, DPCCH, HS-DPCCH,				

E-DPDCH and E-DPCCH the MPR is based on the relative CM difference.

The device supports MPR to solve linearity issues (ACLR or SEM) due to the higher peak-to average ratios (PAR) of the HSUPA signal. This prevents saturating the full range of the TX DAC inside of device and provides a reduced power output to the RF transceiver chip according to the Cubic Metric (a function of the combinations of DPDCH, DPCCH, HS-DPCCH, E-DPDCH and E-DPCCH).

When E-DPDCH channels are present the beta gains on those channels are reduced firsts to try to get the power under the allowed limit. If the beta gains are lowered as far as possible, then a hard limiting is applied at the maximum allowed level.

The SW currently recalculates the cubic metric every time the beta gains on the E-DPDCH are reduced. The cubic metric will likely get lower each time this is done .However, there is no reported reduction of maximum output power in the HSUPA mode since the device also provides a compensate for the power back-off by increasing the gain of TX_AGC in the transceiver (PA) device.

The end effect is that the DUT output power is identical to the case where there is no MPR in the device.



7. CONDUCTED OUTPUT POWER

7.1 PROVISIONS APPLICABLE

The conduction test is carried out in a shielded room.

According to the test, connect the device under test to the antenna port on the non-conductive platform directly to the test device for evaluation and measurement (ANSI-C63.26-2015 Clause 5.4)

7.2 MEASUREMENT METHOD

- The transmitter output port was connected to base station.
- The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.
- The path loss was compensated to the results for each measurement.

Measure the maximum burst average power and average power for other modulation signal.

The EUT was setup for the max output power with pseudo random data modulation. Power was measured with Spectrum Analyzer. The measurements were performed on all mode (WCDMA/HSPA band II, WCDMA/HSPA band IV ,WCDMA/HSPA band V)at 3 typical channels (the Top Channel, the Middle Channel and the Bottom Channel) for each band.

7.3 MEASUREMENT SETUP





7.4 MEASUREMENT RESULT

WCDMA Band II Maximum Average Power (dBm)					
Channel	9262	9400	9538		
Frequency(MHz)	1852.4 MHz	1880.0 MHz	1907.6 MHz		
RMC 12.2kbps	23.03	22.98	22.90		
HSDPA Subtest-1	22.01	21.93	21.86		
HSDPA Subtest-2	21.27	21.29	21.20		
HSDPA Subtest-3	21.31	21.21	21.23		
HSDPA Subtest-4	21.25	21.30	21.22		
HSUPA Subtest-1	19.87	19.69	19.57		
HSUPA Subtest-2	19.92	19.78	19.67		
HSUPA Subtest-3	20.82	20.65	20.58		
HSUPA Subtest-4	19.39	19.22	19.09		
HSUPA Subtest-5	19.04	18.63	18.56		

WCDMA Band IV Maximum Average Power (dBm)					
Channel	1312	1412	1513		
Frequency(MHz)	1712.4 MHz	1732.4 MHz	1752.6 MHz		
RMC 12.2kbps	23.04	22.89	22.97		
HSDPA Subtest-1	22.01	22.03	22.05		
HSDPA Subtest-2	21.28	21.28	21.28		
HSDPA Subtest-3	21.41	21.36	21.28		
HSDPA Subtest-4	21.37	21.28	21.22		
HSUPA Subtest-1	19.84	19.76	19.80		
HSUPA Subtest-2	19.95	19.86	19.87		
HSUPA Subtest-3	20.87	20.77	20.79		
HSUPA Subtest-4	19.45	19.31	19.30		
HSUPA Subtest-5	18.98	18.92	18.94		



WCDMA Band V Maximum Average Power (dBm)							
Channel	4132	4182	4233				
Frequency(MHz)	826.4 MHz	836.4 MHz	846.6 MHz				
RMC 12.2kbps	23.39	23.40	23.41				
HSDPA Subtest-1	22.41	22.47	22.39				
HSDPA Subtest-2	21.58	21.66	21.63				
HSDPA Subtest-3	21.52	21.62	21.48				
HSDPA Subtest-4	21.50	21.49	21.45				
HSUPA Subtest-1	20.09	20.16	20.05				
HSUPA Subtest-2	20.18	20.21	20.03				
HSUPA Subtest-3	20.93	21.01	21.14				
HSUPA Subtest-4	19.61	19.71	19.70				
HSUPA Subtest-5	19.07	19.17	19.44				



8. RADIATED OUTPUT POWER

8.1 PROVISIONS APPLICABLE

The radiation test is carried out in a semi-anechoic chamber.

According to the test, put the device under test on a non-conductive platform 3 meters away from the receiving antenna (ANSI/TIA-603-E-2016 Article 2.2.17).

The following rules are for the maximum radiated power limit requirements of the product:

Mode	Nominal Peak Power
WCDMA Band II	< 2 Watts max. EIRP (33dBm)
WCDMA Band IV	< 1 Watts max. EIRP (30dBm)
WCDMA Band V	< 7 Watts max. ERP (38.45dBm)

8.2 MEASUREMENT METHOD

1. Radiated power measurements are performed using the signal analyzer's "channel power"

measurement capability for signals with continuous operation.

- 2. RBW = 1 5% of the expected OBW, not to exceed 1MHz
- 3. VBW \ge 3 x RBW
- 4. Span = 1.5 times the OBW
- 5. No. of sweep points > 2 x span / RBW
- 6. Detector = RMS
- 7. Trigger is set to "free run" for signals with continuous operation with the sweep times set to "auto".
- 8. The integration bandwidth was roughly set equal to the measured OBW of the signal for signals with continuous operation.
- 9. Trace mode = trace averaging (RMS) over 100 sweeps
- 10. The trace was allowed to stabilize.



Radiation Construction Method:

- 1. The turntable is rotated through 360 degrees, and the receiving antenna scans in order to determine the level of the maximized emission.
- 2. A half wave dipole is then substituted in place of the EUT. For emissions above 1GHz, a horn antenna is substituted in place of the EUT. The substitute antenna is driven by a signal generator and the previously recorded signal was duplicated.

The power is calculated by the following formula:

Pd(dBm) = Pg(dBm) - cable loss (dB) + antenna gain (dB)

Where: Pd is the dipole equivalent power and Pg is the generator output power into the substitution antenna.

- 3. The maximum value is calculated by adding the forward power to the calibrated source plus its appropriate gain value. These steps are repeated with the receiving antenna in both vertical and horizontal polarization. the difference between the gain of the horn and an isotropic antenna are taken into consideration
- 4. The EUT was tested in three orthogonal planes (X, Y, Z) and in all possible test configurations and positioning.
- 5. All measurements are performed as RMS average measurements while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies.

8.3 MEASUREMENT SETUP



Radiated Power 30MHz to 1GHz Test setup





Radiated Power Above 1GHz Test setup





8.4 MEASUREMENT RESULT

	Ch./ Freq.		Substitute	Ant.			Limit	EF	RP
Mode	channel	Freq. (MHz)	LEVEL (dBm)	Gain (dBd)	C.L	Pol.	w	w	dBm
WCDMA850	4132	826.4	27.21	5.90	1.21	Н		0.179	22.52
	4183	836.6	26.61	5.90	1.25	Н		0.157	21.96
	4233	846.6	26.84	5.90	1.24	н	. 7.00	0.165	22.18
	4132	826.4	25.31	5.90	1.21	н	- < 7.00	0.115	20.62
HSPA	4183	836.6	24.88	5.90	1.25	н		0.105	20.23
	4233	846.6	25.18	5.90	1.24	Н		0.113	20.52

	Ch./ Freq.		Substitute	Ant.			Limit		EIRP
Mode	channel	Freq. (MHz)	LEVEL (dBm)	Gain (dBi)	C.L	Pol.	w	w	dBm
	9262	1852.4	28.43	8.6	2.11	н		0.156	21.94
WCDMA	9400	1880.0	28.33	8.6	2.15	Н		0.154	21.88
1900	9538	1907.6	28.40	8.6	2.15	Н	< 2.00	0.157	21.95
HSPA	9262	1852.4	27.34	8.6	2.11	Н	< 2.00	0.122	20.85
	9400	1880.0	27.15	8.6	2.15	Н		0.117	20.70
	9538	1907.6	27.32	8.6	2.15	Н		0.122	20.87
	1312	1712.4	28.27	8.3	2.05	Н		0.159	22.02
WCDMA	1412	1732.4	28.14	8.3	2.05	Н		0.155	21.89
1700	1513	1752.6	28.23	8.3	2.06	н	. 1 00	0.158	21.99
HSPA	1312	1712.4	25.99	8.3	2.05	Н	< 1.00	0.094	19.74
	1412	1732.4	26.10	8.3	2.05	н	1	0.097	19.85
	1513	1752.6	26.02	8.3	2.06	Н		0.095	19.78

Note:1._EIRP/ERP = Substitute LEVEL (dBm) + Ant. Gain – C.L (Cable Loss)

2. All polarizations and modes have been tested, only the worst mode is recorded in the report



9. PEAK-TO-AVERAGE RATIO

9.1 PROVISIONS APPLICABLE

This is the test for the Peak-to-Average Ratio from the EUT.

Power Complementary Cumulative Distribution Function (CCDF) curves provide a means for characterizing the power peaks of a digitally modulated signal on a statistical basis. A CCDF curve depicts the probability of the peak signal amplitude exceeding the average power level. Most contemporary measurement instrumentation include the capability to produce CCDF curves for an input signal provided that the instrument's resolution bandwidth can be set wide enough to accommodate the entire input signal bandwidth. In measuring transmissions in this band using an average power technique, the peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.

9.2 MEASUREMENT METHOD

① CCDF Procedure for PAPR :

1. Set resolution/measurement bandwidth ≥ signal's occupied bandwidth;

- 2. Set the number of counts to a value that stabilizes the measured CCDF curve;
- 3. Set the measurement interval as follows:

-for continuous transmissions, set to 1 ms,

-or burst transmissions, employ an external trigger that is synchronized with the EUT burst timing sequence, or use the internal burst trigger with a trigger level that allows the burst to stabilize and set the measurement interval to a time

that is less than or equal to the burst duration.

4. Record the maximum PAPR level associated with a probability of 0.1%.

② Alternate Procedure for PAPR:

Use one of the procedures presented in 5.2(ANSI C63.26-2015) to measure the total peak power and record as PPk. Use one of the applicable procedures presented 5.2(ANSI C63.26-2015) to measure the total average power and record PAvg. Determine the P.A.R. from:

P.A.R(dB) = PPk (dBm) – PAvg (dBm) (PAvg = Average Power + Duty cycle Factor)

Allow trace to fully stabilize.

Use the peak marker function to determine the peak amplitude level.

Test Settings(Peak Power):

The measurement instrument must have a RBW that is greater than or equal to the OBW of the

signal to be measured and a VBW \ge 3 × RBW.

- 1. Set the RBW \geq OBW.
- 2. Set VBW \geq 3 × RBW.
- 3. Set span \geq 2 × OBW.

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

 Attestation of Global Compliance(Shenzhen)Co., Ltd

 Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd

 Tel: +86-755 2523 4088
 E-mail: agc@agccert.com

 Web: http://www.agccert.com/



- 4. Sweep time \geq 10 × (number of points in sweep) × (transmission symbol period).
- 5. Detector = peak.
- 6. Trace mode = max hold.
- 7. Allow trace to fully stabilize.
- 8. Use the peak marker function to determine the peak amplitude level.

Test Settings(Average Power)

- 1. Set span to $2 \times to 3 \times the OBW$.
- 2. Set RBW ≥ OBW.
- 3. Set VBW ≥ 3 × RBW.
- 4. Set number of measurement points in sweep \geq 2 × span / RBW.
- 5. Sweep time: Set ≥ [10 × (number of points in sweep) × (transmission period)] for single sweep (automation-compatible) measurement. The transmission period is the (on + off) time.
- 6. Detector = power averaging (rms).
- 7. Set sweep trigger to "free run."
- 8. Trace average at least 100 traces in power averaging (rms) mode if sweep is set to auto-couple. (To accurately determine the average power over the on and off period of the transmitter, it can be necessary to increase the number of traces to be averaged above 100 or, if using a manually configured sweep time, increase the sweep time.)
- 9. Use the peak marker function to determine the maximum amplitude level.
- 10. Add [10 log (1/duty cycle)] to the measured maximum power level to compute the average power during continuous transmission. For example, add [10 log (1/0.25)] = 6 dB if the duty cycle is a constant 25%.

9.3 MEASUREMENT SETUP





9.4 MEASUREMENT RESULT

Bands	Modulation	Peak-t	o-average rat	io (dB)	Limit	Result
Banas	modulation	Lowest	Middle	Highest	(dB)	Result
WCDMA Band II	RMC 12.2kbps	3.03	3.00	3.01	13	Pass
WCDMA Band II	HSUPA	3.14	3.58	3.15	13	Pass
WCDMA Band II	HSDPA	5.43	5.21	5.47	13	Pass
WCDMA Band IV	RMC 12.2kbps	3.86	5.19	6.02	13	Pass
WCDMA Band IV	HSUPA	4.03	4.87	4.98	13	Pass
WCDMA Band IV	HSDPA	4.25	5.01	5.77	13	Pass
WCDMA Band V	RMC 12.2kbps	4.16	3.01	3.01	13	Pass
WCDMA Band V	HSUPA	2.86	3.21	2.90	13	Pass
WCDMA Band V	HSDPA	4.25	5.11	5.09	13	Pass



10. OCCUPIED BANDWIDTH

10.1 PROVISIONS APPLICABLE

The width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5 % of the total mean power of a given emission. The EUT makes a call to the communication simulator.

The conducted occupied bandwidth used the power splitter via EUT RF power connector between simulation base station and spectrum analyzer.

The communication simulator station system controlled a EUT to export maximum output power under transmission mode and specific channel frequency. Use OBW measurement function of Spectrum analyzer to measure 99 % occupied bandwidth

10.2 MEASUREMENT METHOD

- 1. The signal analyzer's automatic bandwidth measurement capability was used to perform the 99% occupied bandwidth and the 26dB bandwidth. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
- 2. RBW = 1 5% of the expected OBW
- 3. VBW \geq 3 x RBW
- 4. Detector = Peak
- 5. Trace mode = max hold
- 6. Sweep = auto couple
- 7. The trace was allowed to stabilize
- 8. If necessary, steps 2 7 were repeated after changing the RBW such that it would be within
 - 1-5% of the 99% occupied bandwidth observed in Step 7

10.3 MEASUREMENT SETUP





10.4 MEASUREMENT RESULT

Test Band	Test Mode	Test Channel	Occupied Bandwidth (KHz)	Emission Bandwidth (KHz)	Verdict
WCDMA 850	UMTS	LCH 4170.		4721	PASS
		MCH	4181.6	4724	PASS
		НСН	4182.5	4737	PASS

Tost Band	Tost Modo	Tost Channol	Occupied Bandwidth	Emission Bandwidth	Vordict
Test Danu	Test Mode	lest Channel	(KHz)	(KHz)	Vertuict
WCDMA 1900	UMTS	LCH	4169.1	4716	PASS
		MCH	4156.5	4727	PASS
		HCH	4184.7	4718	PASS

Tost Bond	Test Mode	Tast Channel	Occupied Bandwidth	Emission Bandwidth	Vordict	
Test Danu	Test Mode	Test Channel	(KHz)	(KHz)	VEIGICI	
WCDMA 1700	UMTS	LCH	4174.0	4718	PASS	
		MCH	4178.7	4716	PASS	
		HCH	4172.5	4723	PASS	











11. BAND EDGE EMISSIONS AT ANTENNA TERMINAL

11.1 MEASUREMENT OVERVIEW

All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates were investigated to determine the worst case configuration. All modes of operation were investigated and the worst case configuration results are reported in this section.

11.2 MEASUREMENT METHOD

- 1. Start and stop frequency were set such that the band edge would be placed in the center of the plot
- 2. Span was set large enough so as to capture all out of band emissions near the band edge
- 3. RBW > 1% of the emission bandwidth
- 4. VBW > $3 \times RBW$
- 5. Detector = RMS
- 6. Number of sweep points \geq 2 x Span/RBW
- 7. Trace mode = trace average
- 8. Sweep time = auto couple
- 9. The trace was allowed to stabilize

TEST NOTE

According to FCC 22.917, 24.238, 27.53 specified that power of any emission outside of The authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least 43 + 10 log(P) dB.In the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed. All measurements were done at 2 channels(low and high operational frequency range.) The band edge measurement used the power splitter via EUT RF power connector between simulation base station and spectrum analyzer.

11.3 MEASUREMENT METHOD





Report No.: AGC11034221102FE08 Page 32 of 55

11.4 MEASUREMENT RESULT









12. SPURIOUS EMISSIONS AT ANTENNA TERMINAL

12.1 PROVISIONS APPLICABLE

The level of the carrier and the various conducted spurious and harmonic frequencies is measured by means of a calibrated spectrum analyzer. The spectrum is scanned from the lowest frequency generated in the equipment up to a frequency including its 10th harmonic. All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates were investigated to determine the worst case configuration. All modes of operation were investigated and the worst case configuration results are reported in this section.

12.2 MEASUREMENT METHOD

Test Settings (GSM)

- 1. RBW = 1 MHz
- 2. VBW ≥ 3 MHz
- 3. Detector = Peak
- 4. Trace Mode = max hold
- 5. Sweep time = auto
- 6. Number of points in sweep $\ge 2 \times \text{Span} / \text{RBW}$

Test Settings (WCDMA)

- 1. RBW = 1 MHz
- 2. VBW ≥ 3 MHz
- 3. Detector = RMS
- 4. Trace Mode = trace average
- 5. Sweep time = auto
- 6. Number of points in sweep $\ge 2 \times \text{Span} / \text{RBW}$

12.3 MEASUREMENT SETUP





Report No.: AGC11034221102FE08 Page 35 of 55

12.4 MEASUREMENT RESULT













WCDMA 1700_RMC 12.2kps_LCH		WCDMA 1700_RMC 12.2kps_LCH			
Spectrum Analyzer 1 Swept SA Image: Comparing		Spectrum Analyzer 1 Swept 5A KEVSIGHT Invok RF RL Coccesson DC Align Autor Align Autor St Coc	D dB PNO Fast Avg Typo Power (RMS) 2 3 4 5 6 Gale Off AvgHold 35100 M w w w w w Sq Track off A A A A A A		
Spectrum Ref Lvi Offset 14.63 dB Scale/Div 10 dB Ref Level 30.00 dBm 20 0 0 10 0 0	Mkr1 939.8 MHz -38.37 dBm -0.1-00ra	2 1 Spectrum 1 Spectrum 2 1 Spectrum 2 0 0 1 0 1	Ref Level 30.00 dBm	Mkr2 5.678 8 GHz -30.44 dBm	
200 300 40	۲ ۲ ۲ ۲ ۲ ۲ ۲ ۲ ۲ ۲ ۲ ۲ ۲ ۲	200 300 <td>wyKland, wywystaff ffiliau y fan ifferiau y fan iff</td> <td>2 Stop 7,000 GHz Stop 7,000 GHz Sweep ~11.4 ms (6200 pts)</td>	wyKland, wywystaff ffiliau y fan ifferiau y fan iff	2 Stop 7,000 GHz Stop 7,000 GHz Sweep ~11.4 ms (6200 pts)	
WCDMA 1700_RMC 12.2kps_LCH		WCDMA 1	700_RMC 12.2kps_LC	Η	
Spectrum Analyzer 1 Swapt SA Image SA Angl Type Power (RMS) 2 ≥ 4 5 0 KEYSIGHT Input RF RL Input Z 50 0 Align Auto #Atten 30 dB Peamp Off PNO Feat Cale Off Angl Type Power (RMS) 2 ≥ 4 5 0 RL Cogning DG Align Auto Freq Ref Int (S) Peamp Off Cale Off Angl Type Power (RMS) 2 ≥ 4 5 0 Tot Align Auto Freq Ref Int (S) Peamp Off Cale Off Angl Type Power (RMS) 2 ≥ 4 5 0		Spectrum Analyzer 1 Swept SA KEYSIGHT Input RF Rt Contectors 0 Augur Auto Contectors 0 Freq Ref. Int (S)	D dB PNO Fast Avg Typo: Power (RMS) 1 2 3 4 5 6 D dE Cate: Off Avg/Exid: 15/100 M W W W W W W W W W W W W W W W W W W W W W W W W W W W W W W W W W W W W W W W W W W W W W W W W W W W W W W W W W W<		
1 Spectrum Ref Lvi Offset 15.26 dB Scale/DV 10 dB Ref Level 30.00 dBm 20.0 10.0 000 10.0	Mkr1 9.157 9 GHz -33.05 dBm	I Spectrum • Scale/Div 10 dB Log 20 0 - 10 0 - 0 0 -	Ref Level 30.00 dBm	Mkr1 18.755 8 GHz -31.25 dBm	
-100 -20 -2		- 180 - 200 - 400 - 400 - 400	an air an		
Start 7,000 GHz Ress BW 1.0 MHz Ress BW 1.0 MHz Start 7,000 GHz Ress BW 1.0 MHz P 12/209 PM	Stop 13.600 GH Sweep ~12.6 ms (6800 pts	z Start 13.800 GHz J Res BW 10 MHz C C C C C C C C C C C C C C C C C C C	#Video BW 3.0 MHz*	Stop 20.000 GHz Sweep -13.1 ms (6400 pts)	
WCDMA 1700_RMC 12.2kps_MCH		WCDMA 17	700_RMC 12.2kps_MC	;H	
Spectrum Analyzer 1 + Swept SA Input Z 50 Ω #Atten 30 dB KEYSIGHT Input RF Input Z 50 Ω #Atten 30 dB RL Augn Type Rower (RMS) 2 3 4 5 6 Augn Type Rower (RMS) W W W W RL Augn Type Rower (RMS) W W W W Column Free Ref. Int (S) Free Ref. Int (S)		Spectrum Analyzer 1 Swept SA KEYSIGHT Input RF RL Algon Auto Algon Auto Freq Ref. Int (S)	0.d8 PNO Finat Avg Type Power (RMS) 1, 2, 3, 4, 5, 6 24 Gate Oft AvgRedd SS100 M W W W W W IF Gan Low Ting Fine Run A ∧ ∧ ∧ ∧ ∧		
1 Sportum Ref Lvi Offset 14.63 dB Scale/DV 10 dB Ref Level 30.00 dBm 20 0 0 30 0 0	Mkr1 554.3 MHz -38.81 dBm	2 1 Spectrum 1 Spectrum 1 Spectrum 1 Spectrum 1 Spectrum 1 Spectrum 1 Spectrum	Ref Level 30.00 dBm	Mkr2 4.669 3 GHz -29.95 dBm	
100 200 	11,1,-3,3,4,2,4,4,4,4,4,4,4,4,4,4,4,4,4,4,4,4,	400 400 400 400 400 400	€2 Endin _{in the} west distant of the second state of the second state of the second state of the second state of the		
Start 0.0300 GHz #Video BW 3.0 MHz" #Res BW 1.0 MHz	Stop 1.0000 GH Sweep ~1.40 ms (1000 pt	z Start 1.000 GHz) #Res BW 1.0 MHz	≇Video BW 3.0 MHz*	Stop 7.000 GHz Sweep ~11.4 ms (6200 pts)	





Note: 1. Below 30MHZ no Spurious found and Above is the worst mode data.

2. As no emission found in standby or receive mode, no recording in this report.



13. RADIATED SPURIOUS EMISSION

13.1. PROVISIONS APPLICABLE

(A) On any frequency outside a licensee's frequency block (e.g. A, D, B, etc.) within the USPCS spectrum, the power of any emission shall be attenuated below the transmitter power (P, in Watts) by at least 43+10Log(P) dB. The specification that emissions shall be attenuated below the transmitter power (P) by at least 43 + 10 log (P) dB, translates in the relevant power range (1 to 0.001 W) to -13 dBm.

At 1 W the specified minimum attenuation becomes 43 dB and relative to a 30 dBm (1 W) carrier becomes a limit of -13 dBm. At 0.001 W (0 dBm) the minimum attenuation is 13 dB, which again yields a limit of -13 dBm. In this way a translation of the specification from relative to absolute terms is carried out.

(B) For specific criteria, please refer to the description in section 9.2 of the report for corresponding evaluation.

13.2. MEASUREMENT PROCEDURE

- 1. The EUT was placed on the top of the turntable 0.8 or 1.5 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
- 2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
- 3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
- 4. For each suspected emissions, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
- 5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
- 6. For emissions above 1GHz, use 1MHz VBW and RBW for peak reading. Then 1MHz RBW and 10Hz VBW for average reading in spectrum analyzer. Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
- 7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum values.
- 8.If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.



- 9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
- 10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High Low scan is not required in this case.
- 11. For spurious emissions above 1GHz, a horn antenna is substituted in place of the EUT.

The substitute antenna is driven by a signal generator and the previously recorded signal was duplicated. The spurious emissions is calculated by the following formula;

Result(dBm) = Pg(dBm) + Factor(dB)

Factor(dB) = Ant Gain(dB)-Cable Loss(dB) + Power Splitter(dB) (Above 1GHz)

Factor(dB) = Ant Gain(dB)-Cable Loss(dB) (Below 1GHz)

Where: Pgis the generator output power into the substitution antenna.

If the fundalmatal frequency is below 1GHz, RF output power has been converted to EIRP. EIRP(dBm) = ERP(dBm) + 2.15

13.3. MEASUREMENT setup



Radiated Emissions Above 1GHz Test setup



Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

 Attestation of Global Compliance(Shenzhen)Co., Ltd

 Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd

 Tel: +86-755 2523 4088
 E-mail: agc@agccert.com

 Web: http://www.agccert.com/



13.4 MEASUREMENT RESULT

The measurement Below 1GHz data as follows:

	WCDMA Band II								
No.	Frequency	SA Reading	Correction factor	EIRP Result	Limit	Margin	Ant. Pol.		
	(MHz)	(dBm)	(dB/m)	(dBm)	(dBm)	(dB)			
			RMC 12.2kbp	s_ Lowest Ch	annel				
1	159.759	-66.14	15.52	-50.62	-13.00	-37.62	Horizontal		
2	240.144	-62.38	16.75	-45.63	-13.00	-32.63	Horizontal		
3	754.963	-59.85	19.35	-40.50	-13.00	-27.5	Horizontal		
4	46.708	-64.81	10.44	-54.37	-13.00	-41.37	Vertical		
5	433.340	-61.54	17.75	-43.79	-13.00	-30.79	Vertical		
6	502.247	-59.11	18.66	-40.45	-13.00	-27.45	Vertical		
			RMC 12.2kbp	os_ Middle Ch	annel				
1	31.735	-62.85	9.78	-53.07	-13.00	-40.07	Horizontal		
2	159.759	-63.75	13.75	-50.00	-13.00	-37.00	Horizontal		
3	240.144	-61.88	16.75	-45.13	-13.00	-32.13	Horizontal		
4	43.233	-63.96	10.23	-53.73	-13.00	-40.73	Vertical		
5	433.340	-62.69	17.75	-44.94	-13.00	-31.94	Vertical		
6	498.730	-58.96	18.02	-40.94	-13.00	-27.94	Vertical		
			RMC 12.2kbp	s_ Highest Ch	annel				
1	159.759	-63.65	13.75	-49.90	-13.00	-36.9	Horizontal		
2	240.144	-62.13	16.75	-45.38	-13.00	-32.38	Horizontal		
3	679.435	-59.21	19.01	-40.20	-13.00	-27.20	Horizontal		
4	43.233	-62.99	10.23	-52.76	-13.00	-39.76	Vertical		
5	433.340	-62.17	17.75	-44.42	-13.00	-31.42	Vertical		
6	498.730	-58.86	18.02	-40.84	-13.00	-27.84	Vertical		



	WCDMA Band IV									
No	Frequency	SA Reading	Correction factor	EIRP Result	Limit	Margin	Ant Pol			
110.	(MHz)	(dBm)	(dB/m)	(dBm)	(dBm)	(dB)				
			RMC 12.2kbp	s_ Lowest Ch	annel					
1	159.759	-66.22	15.52	-50.70	-13.00	-37.70	Horizontal			
2	240.144	-62.70	16.75	-45.95	-13.00	-32.95	Horizontal			
3	754.963	-59.30	19.35	-39.95	-13.00	-26.95	Horizontal			
4	46.708	-64.71	10.44	-54.27	-13.00	-41.27	Vertical			
5	433.340	-61.00	17.75	-43.25	-13.00	-30.25	Vertical			
6	502.247	-59.13	18.66	-40.47	-13.00	-27.47	Vertical			
	·		RMC 12.2kbp	os_ Middle Cha	annel					
1	31.735	-63.49	9.78	-53.71	-13.00	-40.71	Horizontal			
2	159.759	-64.01	13.75	-50.26	-13.00	-37.26	Horizontal			
3	240.144	-61.29	16.75	-44.54	-13.00	-31.54	Horizontal			
4	43.233	-63.76	10.23	-53.53	-13.00	-40.53	Vertical			
5	433.340	-62.54	17.75	-44.79	-13.00	-31.79	Vertical			
6	498.730	-59.36	18.02	-41.34	-13.00	-28.34	Vertical			
			RMC 12.2kbp	s_ Highest Ch	annel					
1	159.759	-63.76	13.75	-50.01	-13.00	-37.01	Horizontal			
2	240.144	-62.54	16.75	-45.79	-13.00	-32.79	Horizontal			
3	679.435	-59.41	19.01	-40.40	-13.00	-27.4	Horizontal			
4	43.233	-63.58	10.23	-53.35	-13.00	-40.35	Vertical			
5	433.340	-62.29	17.75	-44.54	-13.00	-31.54	Vertical			
6	498.730	-59.22	18.02	-41.20	-13.00	-28.2	Vertical			



	WCDMA Band V									
No	Frequency	SA Reading	Correction factor	EIRP Result	Limit	Margin	Ant Pol			
110.	(MHz)	(dBm)	(dB/m)	(dBm)	(dBm)	(dB)				
			RMC 12.2kbp	s_ Lowest Ch	annel					
1	159.759	-65.53	15.52	-50.01	-13.00	-37.01	Horizontal			
2	240.144	-62.23	16.75	-45.48	-13.00	-32.48	Horizontal			
3	754.963	-57.88	19.35	-38.53	-13.00	-25.53	Horizontal			
4	46.708	-62.99	10.44	-52.55	-13.00	-39.55	Vertical			
5	433.340	-60.74	17.75	-42.99	-13.00	-29.99	Vertical			
6	502.247	-56.79	18.66	-38.13	-13.00	-25.13	Vertical			
			RMC 12.2kbp	os_ Middle Ch	annel					
1	31.735	-61.70	9.78	-51.92	-13.00	-38.92	Horizontal			
2	159.759	-62.71	13.75	-48.96	-13.00	-35.96	Horizontal			
3	240.144	-60.64	16.75	-43.89	-13.00	-30.89	Horizontal			
4	43.233	-63.23	10.23	-53.00	-13.00	-40.00	Vertical			
5	433.340	-61.00	17.75	-43.25	-13.00	-30.25	Vertical			
6	498.730	-57.30	18.02	-39.28	-13.00	-26.28	Vertical			
			RMC 12.2kbp	s_ Highest Ch	annel					
1	159.759	-62.88	13.75	-49.13	-13.00	-36.13	Horizontal			
2	240.144	-60.53	16.75	-43.78	-13.00	-30.78	Horizontal			
3	679.435	-58.27	19.01	-39.26	-13.00	-26.26	Horizontal			
4	43.233	-61.83	10.23	-51.60	-13.00	-38.60	Vertical			
5	433.340	-61.47	17.75	-43.72	-13.00	-30.72	Vertical			
6	498.730	-57.95	18.02	-39.93	-13.00	-26.93	Vertical			



The measurement Above 1GHz data as follows:

WCDMA Band II													
No	Frequency	SA Reading	Correction factor	EIRP Result	Limit	Margin	Ant Pol						
Nor	(MHz)	(dBm)	(dB/m)	(dBm)	(dBm)	(dB)							
RMC 12.2kbps_ Lowest Channel													
1	3704.800	-66.36	31.09	-51.44	-13.00	-38.44	Horizontal						
2	5557.200	-71.49	34.14	-55.11	-13.00	-42.11	Horizontal						
3	3704.800	-62.37	33.13	-47.47	-13.00	-34.47	Vertical						
4	5557.200	-69.52	32.66	-52.65	-13.00	-39.65	Vertical						
			RMC 12.2kbp	os_ Middle Cha	annel								
1	3760.000	-63.16	31.09	-48.13	-13.00	-35.13	Horizontal						
2	5640.000	-70.47	34.14	-53.91	-13.00	-40.91	Horizontal						
3	3760.000	-61.43	33.13	-46.40	-13.00	-33.40	Vertical						
4	5640.000	-68.63	32.66	-51.59	-13.00	-38.59	Vertical						
			RMC 12.2kbp	s_ Highest Ch	annel								
1	3815.200	-66.75	31.09	-51.61	-13.00	-38.61	Horizontal						
2	5722.800	-68.24	34.14	-51.32	-13.00	-38.32	Horizontal						
3	3815.200	-64.12	33.13	-48.95	-13.00	-35.95	Vertical						
4	5722.800	-67.74	32.66	-50.37	-13.00	-37.37	Vertical						





	WCDMA Band IV												
No	Frequency	SA Reading	Correction factor	EIRP Result	Limit	Margin	Ant Pol						
110.	(MHz)	(dBm)	(dB/m)	(dBm)	(dBm)	(dB)							
RMC 12.2kbps_ Lowest Channel													
1	3424.800	-71.38	32.11	-57.75	-13.00	-44.75	Horizontal						
2	5137.200	-70.08	34.13	-54.26	-13.00	-41.26	Horizontal						
3	3424.800	-71.60	32.11	-58.18	-13.00	-45.18	Vertical						
4	5137.200	-69.28	34.13	-53.11	-13.00	-40.11	Vertical						
			RMC 12.2kbp	os_ Middle Ch	annel								
1	3464.800	-70.55	32.11	-56.67	-13.00	-43.67	Horizontal						
2	5197.200	-69.37	34.13	-53.35	-13.00	-40.35	Horizontal						
3	3464.800	-71.53	32.11	-57.80	-13.00	-44.80	Vertical						
4	5197.200	-68.74	34.13	-52.34	-13.00	-39.34	Vertical						
			RMC 12.2kbp	s_ Highest Ch	annel								
1	3505.200	-71.18	32.11	-57.05	-13.00	-44.05	Horizontal						
2	5257.800	-68.99	34.13	-52.87	-13.00	-39.87	Horizontal						
3	3505.200	-70.91	32.11	-56.87	-13.00	-43.87	Vertical						
4	5257.800	-68.18	34.13	-51.66	-13.00	-38.66	Vertical						



	WCDMA Band V											
No	Frequency	SA Reading	Correction factor	EIRP Result	Limit	Margin	Ant Pol					
NO.	(MHz)	(dBm)	(dB/m)	(dBm)	(dBm)	(dB)						
RMC 12.2kbps_ Lowest Channel												
1	1652.800	-83.50	23.12	-60.38	-13.00	-47.38	Horizontal					
2	2479.200	-85.56	28.47	-57.09	-13.00	-44.09	Horizontal					
3	1652.800	-82.82	23.12	-59.70	-13.00	-46.70	Vertical					
4	2479.200	-82.77	28.47	-54.30	-13.00	-41.30	Vertical					
			RMC 12.2kbp	s_ Middle Cha	annel							
1	1672.800	-81.48	23.12	-58.36	-13.00	-45.36	Horizontal					
2	2509.200	-83.20	28.47	-54.73	-13.00	-41.73	Horizontal					
3	1672.800	-82.82	23.12	-59.70	-13.00	-46.70	Vertical					
4	2509.200	-81.48	28.47	-53.01	-13.00	-40.01	Vertical					
			RMC 12.2kbp	s_ Highest Ch	annel							
1	1693.200	-80.33	23.12	-57.72	-13.00	-44.21	Horizontal					
2	2539.800	-81.99	28.47	-53.61	-13.00	-40.52	Horizontal					
3	1693.200	-80.6	23.12	-58.30	-13.00	-44.48	Vertical					
4	2539.800	-80.49	28.47	-53.30	-13.00	-39.02	Vertical					

Note:

1.Correct Factor = Antenna Factor + Cable Loss - Amplifier Gain, the value was added to Original Receiver Reading by the software automatically.

2.Result = Reading + Correct Factor.

3.Margin = Result - Limit

4.he device is investigated from 30MHz to 10 times of fundamental signal for radiated spurious emission test. Subsequently, only the worst case emissions are reported.



14. FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE

14.1 PROVISIONS APPLICABLE

14.1.1 For Hand carried battery powered equipment

Frequency stability testing is performed in accordance with the guidelines of ANSI/TIA-603-E-2016. The frequency stability of the transmitter is measured by:

- a.) Temperature: The temperature is varied from -20°C to +50°C in 10°C increments using an environmental chamber.
- b.) Primary Supply Voltage: The primary supply voltage is varied from 85% to 115% of the nominal value for non hand-carried battery and AC powered equipment. For hand-carried, battery-powered equipment, primary supply voltage is reduced to the battery operating end point which shall be specified by the manufacturer.

For Part 22, the frequency stability of the transmitter shall be maintained within $\pm 0.00025\%$ (± 2.5 ppm) of the center frequency. For Part 24 and Part 27, the frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block.

14.1.2 For equipment powered by primary supply voltage

- 1 The carrier frequency of the transmitter is measured at room temperature (20°C to provide a
- 2 reference).
- 3 The equipment is turned on in a "standby" condition for fifteen minutes before applying power to
- 4 the transmitter. Measurement of the carrier frequency of the transmitter is made within one minute after applying power to the transmitter.
- 5 Frequency measurements are made at 10°C intervals ranging from -20°C to +50°C. A period of at
- 6 least one half-hour is provided to allow stabilization of the equipment at each temperature level.

14.2 MEASUREMENT METHOD

In order to measure the carrier frequency under the condition of AFC lock, it is necessary to make measurements with the EUT in a "call mode". This is accomplished with the use of R&S CMW500 DIGITAL RADIO COMMUNICATION TESTER.

7 Measure the carrier frequency at room temperature.

8 Subject the EUT to overnight soak at -30°C. With the EUT, powered via nominal voltage, connected to the CMW500 and in a simulated call on channel 20175 for LTE band 4 measure the carrier frequency. These measurements should be made within 2 minutes of Powering up the EUT, to prevent significant self-warming.

9 Repeat the above measurements at 10° increments from -30° to $+50^{\circ}$. Allow at least 1 1/2 hours at each temperature, unpowered, before making measurements.

10 Re-measure carrier frequency at room temperature with nominal voltage. Vary supply voltage from



minimum voltage to maximum voltage, in 0.1Volt increments re-measuring carrier frequency at each voltage. Pause at nominal voltage for 1 1/2 hours unpowered, to allow any self-heating to stabilize, before continuing.

11 Subject the EUT to overnight soak at $+50^{\circ}$ C.

12 With the EUT, powered via nominal voltage, connected to the CMW500 and in a simulated call on the centre channel, measure the carrier frequency. These measurements should be made within 2 minutes of Powering up the EUT, to prevent significant self-warming.

13 Repeat the above measurements at 10° C increments from +50 $^{\circ}$ C to -30 $^{\circ}$ C. Allow at least 1 1/2 hours at each temperature, unpowered, before making measurements.

14 At all temperature levels hold the temperature to +/- 0.5° C during the measurement procedure.

14.3 MEASUREMENT SETUP





14.4 MEASUREMENT RESULT

Frequency Error vs. Voltage:

Test	Test	Test	Test	Test	Freq.Error	Freq.vs.rated	Limit	Vardiat
Band	Mode	Channel	Temp.	Volt.(V)	(Hz)	(ppm)	(ppm)	verdict
			ΤN	VL	-15.20	-0.018393	±2.5	PASS
		LCH	ΤN	VN	-12.39	-0.014993	±2.5	PASS
			TN	VH	-16.51	-0.019978	±2.5	PASS
	UMTS		ΤN	VL	-12.91	-0.015435	±2.5	PASS
WCDMA850		UMTS MCH	TN	VN	-11.23	-0.013427	±2.5	PASS
			TN	VH	-16.72	-0.019990	±2.5	PASS
			ΤN	VL	-11.09	-0.013099	±2.5	PASS
			TN	VN	-9.49	-0.011210	±2.5	PASS
			ΤN	VH	-7.83	-0.009249	±2.5	PASS

Test	Test	Test	Test	Test	Freq.Error	Freq.vs.rated	Vordiat	
Band	Mode	Channel	Temp.	Volt.(V)	(Hz)	(ppm)	Verdict	
			TN	VL	-16.08	-0.009390	PASS	
		LCH	TN	VN	-15.88	-0.009273	PASS	
	UMTS		TN	VH	-13.08	-0.007638	PASS	
		МСН	TN	VL	-23.91	-0.013801	PASS	
WCDMA1700			TN	VN	-20.63	-0.011908	PASS	
			TN	VH	-14.65	-0.008456	PASS	
			TN	VL	-15.44	-0.008810	PASS	
		НСН	TN	VN	-12.83	-0.007321	PASS	
			ΤN	VH	-10.93	-0.006237	PASS	

Note: Based on the results of the frequency stability test at the center channel the frequency deviation results measured are very small. As such it is determined that channels at the band edge would remain in-band when the maximum measured frequency deviation noted during the frequency stability tests is applied. Therefore the device is determined to remain operating in band over the temperature and voltage range as tested.



Report No.: AGC11034221102FE08 Page 51 of 55

Test	Test	Test	Test	Test	Freq.Error	Freq.vs.rated	Vordict
Band	Mode	Channel	Temp.	Volt.(V)	(Hz)	(ppm)	verdict
			TN	VL	-21.93	-0.011839	PASS
		LCH	TN	VN	-22.81	-0.012314	PASS
	UMTS		TN	VH	-23.21	-0.012530	PASS
		МСН	TN	VL	-15.79	-0.008399	PASS
WCDMA1900			TN	VN	-15.79	-0.008399	PASS
			TN	VH	-18.04	-0.009596	PASS
			TN	VL	-16.46	-0.008629	PASS
		НСН	TN	VN	-11.11	-0.005824	PASS
			TN	VH	-14.56	-0.007633	PASS

Note: Based on the results of the frequency stability test at the center channel the frequency deviation results measured are very small. As such it is determined that channels at the band edge would remain in-band when the maximum measured frequency deviation noted during the frequency stability tests is applied. Therefore the device is determined to remain operating in band over the temperature and voltage range as tested.



Frequency Error vs. Temperature:

Test	Test	Test	Test	Test	Freq.Error	Freq.vs.rated	Limit	Vordict	
Band	Mode	Channel	Volt.	Temp.	(Hz)	(ppm)	(ppm)	verdict	
			VN	-30	-21.06	-0.025484	±2.5	PASS	
			VN	-20	-18.39	-0.022253	±2.5	PASS	
			VN	-10	-11.20	-0.013553	±2.5	PASS	
			VN	0	-14.34	-0.017352	±2.5	PASS	
	UMTS	LCH	VN	10	-12.79	-0.015477	±2.5	PASS	
000			VN	20	-14.24	-0.017231	±2.5	PASS	
			VN	30	-19.00	-0.022991	±2.5	PASS	
			VN	40	-17.32	-0.020958	±2.5	PASS	
			VN	50	-15.40	-0.018635	±2.5	PASS	
			VN	-30	-16.62	-0.020111	±2.5	PASS	
	UMTS		VN	-20	-10.44	-0.012633	±2.5	PASS	
			VN	-10	-12.60	-0.015065	±2.5	PASS	
				VN	0	-15.67	-0.018735	±2.5	PASS
		МСН	VN	10	-16.51	-0.019739	±2.5	PASS	
000			VN	20	-10.03	-0.011992	±2.5	PASS	
			VN	30	-11.78	-0.014084	±2.5	PASS	
			VN	40	-11.03	-0.013187	±2.5	PASS	
			VN	50	-12.31	-0.014718	±2.5	PASS	
			VN	-30	-9.52	-0.011382	±2.5	PASS	
			VN	-20	-20.78	-0.024545	±2.5	PASS	
			VN	-10	-16.16	-0.019088	±2.5	PASS	
			VN	0	-14.37	-0.016974	±2.5	PASS	
WCDMA 850	UMTS	НСН	VN	10	-16.53	-0.019525	±2.5	PASS	
			VN	20	-14.01	-0.016549	±2.5	PASS	
			VN	30	-17.99	-0.021250	±2.5	PASS	
			VN	40	-14.13	-0.016690	±2.5	PASS	
			VN	50	-12.21	-0.014422	±2.5	PASS	



Report No.: AGC11034221102FE08 Page 53 of 55

Test	Test	Test	Test	Test	Freq.Error	Freq.vs.rated	Limit	Verdict
Band	Mode	Channel	Volt.	Temp.	(Hz)	(ppm)	(ppm)	DACC
				-30	-21.24	-0.012403	±2.5	PASS
			VIN	-20	-15.72	-0.009180	±2.5	PASS
			VN	-10	-17.03	-0.009945	±2.5	PASS
WCDMA			VN	0	-14.34	-0.008374	±2.5	PASS
1700	UMTS	LCH	VN	10	-17.59	-0.010272	±2.5	PASS
			VN	20	-17.30	-0.010102	±2.5	PASS
			VN	30	-11.87	-0.006931	±2.5	PASS
			VN	40	-12.04	-0.007031	±2.5	PASS
			VN	50	-12.54	-0.007323	±2.5	PASS
			VN	-30	-15.40	-0.008889	±2.5	PASS
	UMTS	МСН	VN	-20	-12.18	-0.007030	±2.5	PASS
			VN	-10	-12.01	-0.006932	±2.5	PASS
			VN	0	-16.45	-0.009495	±2.5	PASS
			VN	10	-20.32	-0.011729	±2.5	PASS
1700			VN	20	-19.23	-0.011100	±2.5	PASS
			VN	30	-15.56	-0.008981	±2.5	PASS
			VN	40	-16.30	-0.009408	±2.5	PASS
			VN	50	-20.14	-0.011625	±2.5	PASS
			VN	-30	-21.88	-0.012485	±2.5	PASS
			VN	-20	-9.99	-0.005700	±2.5	PASS
			VN	-10	-15.43	-0.008805	±2.5	PASS
			VN	0	-11.72	-0.006688	±2.5	PASS
WCDMA	UMTS	НСН	VN	10	-12.18	-0.006950	±2.5	PASS
1700			VN	20	-17.04	-0.009723	±2.5	PASS
			VN	30	-10.94	-0.006243	±2.5	PASS
			VN	40	-11.67	-0.006659	±2.5	PASS
			VN	50	-9.46	-0.005398	±2.5	PASS

Note: Based on the results of the frequency stability test at the center channel the frequency deviation results measured are very small. As such it is determined that channels at the band edge would remain in-band when the maximum measured frequency deviation noted during the frequency stability tests is applied. Therefore the device is determined to remain operating in band over the temperature and voltage range as tested.



Report No.: AGC11034221102FE08 Page 54 of 55

Test	Test	Test	Test	Test	Freq.Error	Freq.vs.rated	Limit) (a rali at
Band	Mode	Channel	Volt.	Temp.	(Hz)	(ppm)	(ppm)	verdict
			VN	-30	-15.88	-0.008573	±2.5	PASS
			VN	-20	-20.25	-0.010932	±2.5	PASS
			VN	-10	-17.76	-0.009588	±2.5	PASS
			VN	0	-16.62	-0.008972	±2.5	PASS
	UMTS	LCH	VN	10	-24.78	-0.013377	±2.5	PASS
1900			VN	20	-18.72	-0.010106	±2.5	PASS
			VN	30	-15.56	-0.008400	±2.5	PASS
			VN	40	-18.28	-0.009868	±2.5	PASS
			VN	50	-17.58	-0.009490	±2.5	PASS
			VN	-30	-18.45	-0.009960	±2.5	PASS
	UMTS	МСН	VN	-20	-16.82	-0.009080	±2.5	PASS
			VN	-10	-16.91	-0.008995	±2.5	PASS
			VN	0	-17.82	-0.009479	±2.5	PASS
			VN	10	-25.04	-0.013319	±2.5	PASS
1900			VN	20	-21.26	-0.011309	±2.5	PASS
			VN	30	-21.07	-0.011207	±2.5	PASS
			VN	40	-14.42	-0.007670	±2.5	PASS
			VN	50	-15.38	-0.008181	±2.5	PASS
			VN	-30	-20.61	-0.010963	±2.5	PASS
			VN	-20	-20.26	-0.010777	±2.5	PASS
			VN	-10	-10.24	-0.005368	±2.5	PASS
			VN	0	-8.88	-0.004655	±2.5	PASS
	UMTS	НСН	VN	10	-13.09	-0.006862	±2.5	PASS
1900			VN	20	-13.96	-0.007318	±2.5	PASS
			VN	30	-20.20	-0.010589	±2.5	PASS
			VN	40	-21.33	-0.011182	±2.5	PASS
			VN	50	-16.45	-0.008623	±2.5	PASS

Note: Based on the results of the frequency stability test at the center channel the frequency deviation results measured are very small. As such it is determined that channels at the band edge would remain in-band when the maximum measured frequency deviation noted during the frequency stability tests is applied. Therefore the device is determined to remain operating in band over the temperature and voltage range as tested.



Report No.: AGC11034221102FE08 Page 55 of 55

APPENDIX A: PHOTOGRAPHS OF TEST SETUP

Refer to the Report No.: AGC11034221102AP0

APPENDIX B: PHOTOGRAPHS OF EUT

Refer to the Report No.: AGC02931200602AP03

----END OF REPORT----



Conditions of Issuance of Test Reports

1. All samples and goods are accepted by the Attestation of Global Compliance (Shenzhen) Co., Ltd (the "Company") solely for testing and reporting in accordance with the following terms and conditions. The company provides its services on the basis that such terms and conditions constitute express agreement between the company and any person, firm or company requesting its services (the "Clients").

2. Any report issued by Company as a result of this application for testing services (the "Report") shall be issued in confidence to the Clients and the Report will be strictly treated as such by the Company. It may not be reproduced either in its entirety or in part and it may not be used for advertising or other unauthorized purposes without the written consent of the Company. The Clients to whom the Report is issued may, however, show or send it, or a certified copy thereof prepared by the Company to its customer, supplier or other persons directly concerned. The Company will not, without the consent of the Clients, enter into any discussion or correspondence with any third party concerning the contents of the Report, unless required by the relevant governmental authorities, laws or court orders.

3. The Company shall not be called or be liable to be called to give evidence or testimony on the Report in a court of law without its prior written consent, unless required by the relevant governmental authorities, laws or court orders.

4. In the event of the improper use of the report as determined by the Company, the Company reserves the right to withdraw it, and to adopt any other additional remedies which may be appropriate.

5. Samples submitted for testing are accepted on the understanding that the Report issued cannot form the basis of, or be the instrument for, any legal action against the Company.

6. The Company will not be liable for or accept responsibility for any loss or damage however arising from the use of information contained in any of its Reports or in any communication whatsoever about its said tests or investigations.

7.Clients wishing to use the Report in court proceedings or arbitration shall inform the Company to that effect prior to submitting the sample for testing.

8. The Company is not responsible for recalling the electronic version of the original report when any revision is made to them. The Client assumes the responsibility to providing the revised version to any interested party who uses them.

9. Subject to the variable length of retention time for test data and report stored hereinto as otherwise specifically required by individual accreditation authorities, the Company will only keep the supporting test data and information of the test report for a period of six years. The data and information will be disposed of after the aforementioned retention period has elapsed. Under no circumstances shall we provide any data and information which has been disposed of after retention period. Under no circumstances shall we be liable for damage of any kind, including (but not limited to) compensatory damages, lost profits, lost data, or any form of special, incidental, indirect, consequential or punitive damages of any kind, whether based on breach of contract of warranty, tort (including negligence), product liability or otherwise, even if we are informed in advance of the possibility of such damages.