

# FCC PART 22H, PART 24E

# **TEST REPORT**

For

# **Advanced Mobile Payment Inc.**

Units 401-403, 15 Wertheim Court. Richmond Hill, Ontario L4B 3H7 Canada

# FCC ID: 2AKJB-AMP7000-3

<b>Report Type:</b> Original Report		<b>Product Type:</b> POS Payment Terminal						
Report Number:	RSZ170511007	-00C						
Report Date:	2017-05-25							
	Oscar Ye	Oscar. Ye						
<b>Reviewed By:</b>	Engineer	CONSIGNATION (CONSIGNATION)						
Prepared By:	Bay Area Comp No.248 Chengh China Tel: +86-0512-8 Fax: +86-0512- www.baclcorp.c	Diance Laboratories Corp. (Kunshan) u Road, Kunshan, Jiangsu province, 86175000 88934268 com.cn						

**Note**: This test report is prepared for the customer shown above and for the equipment described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp.

Report No.: RSZ170511007-00C

Bay Area Compliance Laboratories Corp. (Kunshan)

# **TABLE OF CONTENTS**

GENERAL INFORMATION	3
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	3
Objective	3
RELATED SUBMITTAL(S)/GRANT(S)	3
Test Methodology	3
MEASUREMENT UNCERTAINTY	4
TEST FACILITY	4
SYSTEM TEST CONFIGURATION	5
DESCRIPTION OF TEST CONFIGURATION	5
Equipment Modifications	5
SUPPORT EQUIPMENT LIST AND DETAILS	5
BLOCK DIAGRAM OF TEST SETUP	5
SUMMARY OF TEST RESULTS	6
TEST EQUIPMENT LIST	7
FCC §1.1307 & §2.1093 - RF EXPOSURE	8
Applicable Standard	8
Test Result	8
FCC §2.1047 - MODULATION CHARACTERISTIC	9
FCC § 2.1046, § 22.913 (A) & § 24.232 (C) - RF OUTPUT POWER	10
Applicable Standard	10
Test Procedure	10
TEST DATA	10
FCC §2.1053, §22.917 & §24.238 - SPURIOUS RADIATED EMISSIONS	12
APPLICABLE STANDARD	12
Test Procedure	12
TEST DATA	12

Bay Area Compliance Laboratories Corp. (Kunshan)

## **GENERAL INFORMATION**

#### **Product Description for Equipment under Test (EUT)**

The Advanced Mobile Payment Inc.'s product, model number: AMP 7000-FA (FCC ID: 2AKJB-AMP7000-3) in this report is a POS Payment Terminal, which was measured approximately: 190 mm (L) \* 89.5 mm (W) \*56 mm (H), rated with input voltage: DC 7.4V battery or DC 9.5V from adapter.

Adapter Information: Model: ADS-25SG-12-2 09524E Input: AC 100-240V, 50/60Hz, 0.7A max Output: DC 9.5V, 2.5A

\* All measurement and test data in this report was gathered from production sample serial number: 1700957 (Assigned by BACL, Kunshan). The EUT supplied by the applicant was received on 2017-05-11.

#### Objective

This test report is prepared on behalf of *Advanced Mobile Payment Inc* .in accordance with Part 2-Subpart J, Part 22-Subpart H and Part 24-Subpart E of the Federal Communication Commissions rules.

The objective is to determine the compliance of the EUT with FCC rules for output power, modulation characteristic, occupied bandwidth, and spurious emission at antenna terminal, spurious radiated emission, frequency stability and band edge.

#### **Related Submittal(s)/Grant(s)**

FCC 15.225 DXX and Part 15B JBP submissions with FCC ID: 2AKJB-AMP7000-3.

#### **Test Methodology**

All tests and measurements indicated in this document were performed in accordance with the Code of Federal Regulations Title 47 Part 2-Subpart J as well as the following parts:

Part 22 Subpart H - Public Mobile Services Part 24 Subpart E - Personal Communication Services

Applicable Standards: TIA/EIA 603-D.

All emissions measurement was performed at Bay Area Compliance Laboratories Corp. (Kunshan). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

#### **Measurement Uncertainty**

	Item	Uncertainty
RF conducted	d test with spectrum	±0.9dB
	30MHz~1GHz	±5.91dB
Radiated emission	Above 1G	±4.92dB
Occupi	ed Bandwidth	±0.5kHz
Ter	mperature	±1.0°C
Н	Iumidity	±6%

#### **Test Facility**

The test site used by Bay Area Compliance Laboratories Corp. (Kunshan) to collect test data is located on the No.248 Chenghu Road, Kunshan, Jiangsu province, China.

Test site at Bay Area Compliance Laboratories Corp. (Kunshan) has been fully described in reports submitted to the Federal Communication Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on November 06, 2014. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2014.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 815570. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

## SYSTEM TEST CONFIGURATION

#### **Description of Test Configuration**

The EUT was configured for testing according to TIA/EIA-603-D.

The final qualification test was performed with the EUT operating at normal mode.

### **Equipment Modifications**

No modification was made to the EUT.

### **Support Equipment List and Details**

Manufacturer	Description	Model	Serial Number	
Rohde & Schwarz	Universal Radio Communication Tester	CMU200	110605	

### **Block Diagram of Test Setup**



FCC Part 22H/24E

## SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§1.1307, §2.1093	RF Exposure (SAR)	Compliance
§2.1046; § 22.913 (a); § 24.232 (c)	RF Output Power	Compliance
§ 2.1047	Modulation Characteristics	Not Applicable
§ 2.1049; § 22.905 § 22.917; § 24.238	Bandwidth	Compliance*
§ 2.1051, § 22.917 (a); § 24.238 (a)	Spurious Emissions at Antenna Terminal	Compliance*
§ 2.1053 § 22.917 (a); § 24.238 (a)	Field Strength of Spurious Radiation	Compliance
§ 22.917 (a); § 24.238 (a)	Out of band emission, Band Edge	Compliance*
\$ 2.1055 \$ 22.355; \$ 24.235	Frequency stability vs. temperature Frequency stability vs. voltage	Compliance*

Note: Compliance\*: The EUT is identical with the product which the Model named AMP 7000-FD and FCC ID is 2AKJB-AMP7000-2, the difference is the Wifi module was removed. So these test items please referred to FCC ID: 2AKJB-AMP7000-2 that has been certified on 2017-04-05, report No.: RSZ161123004-00C, which was tested by Bay Area Compliance Laboratories Corp.

## **TEST EQUIPMENT LIST**

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
	I	Radiated Emissio	n Test		
Sonoma Instrunent	Amplifier	330	171377	2016-10-21	2017-10-21
Rohde & Schwarz	EMI Test Receiver	ESCI	100195	2016-11-25	2017-11-25
Sunol Sciences	Broadband Antenna	JB3	A090314-2	2016-01-09	2019-01-08
Sunol Sciences	Broadband Antenna	JB3	A090314-1	2016-01-09	2019-01-08
Narda	Pre-amplifier	AFS42- 00101800	2001270	2016-09-08	2017-09-08
EMCO	Horn Antenna	3116	00084159	2016-10-18	2019-10-17
Rohde & Schwarz	Signal Analyzer	FSIQ26	100048	2016-11-25	2017-11-25
ETS	Horn Antenna	3115	6229	2016-12-12	2019-12-12
ETS	Horn Antenna	3115	9311-4159	2016-12-12	2019-12-12
R&S	Auto test Software	EMC32	V 09.10.0	NCR	NCR
haojintech	Coaxial Cable	Cable-1	001	2016-12-12	2017-12-12
haojintech	Coaxial Cable	Cable-2	002	2016-12-12	2017-12-12
haojintech	Coaxial Cable	Cable-3	003	2016-12-12	2017-12-12
MICRO-COAX	Coaxial Cable	Cable-4	004	2016-12-12	2017-12-12
MICRO-COAX	Coaxial Cable	Cable-5	005	2016-12-12	2017-12-12
MICRO-COAX	Coaxial Cable	Cable-7	007	2016-12-12	2017-12-12
HP	Signal Generator	8341B	2624A00116	2016-08-29	2017-08-29

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Kunshan) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

# FCC §1.1307 & §2.1093 - RF EXPOSURE

## Applicable Standard

FCC§1.1310 and §2.1093.

## **Test Result**

Compliance, please refer to the SAR report: RSZ170511007-20.

# FCC §2.1047 - MODULATION CHARACTERISTIC

According to FCC § 2.1047(d), Part 22H & 24E there is no specific requirement for digital modulation, therefore modulation characteristic is not presented.

#### Bay Area Compliance Laboratories Corp. (Kunshan)

## FCC § 2.1046, § 22.913 (a) & § 24.232 (c) - RF OUTPUT POWER

#### **Applicable Standard**

According to FCC §2.1046 and §22.913 (a), the ERP of mobile transmitters and auxiliary test transmitters must not exceed 7 watts.

According to FCC §2.1046 and §24.232 (C), mobile and portable stations are limited to 2 watts EIRP and the equipment must employ a means for limiting power to the minimum necessary for successful communications.

### **Test Procedure**

#### Conducted method:

The RF output of the transmitter was connected to the wireless test set and the spectrum analyzer through sufficient attenuation.



Radiated method:

TIA 603-D section 2.2.17

#### **Test Data**

#### **Environmental Conditions**

Temperature:	24 °C
<b>Relative Humidity:</b>	49 %
ATM Pressure:	101.0 kPa

The testing was performed by Echo Wu on 2017-05-23.

EUT operation mode: Transmitting

### **Radiated Power**

### **GPRS Mode:**

Frequency Receiver Curntable Reading (MHz) (dBµV) Degree	Turntable	Rx Antenna		Substituted			Absolute					
	Reading (dBµV)	deading Angle dBμV) Degree	Height (m)	Polar (H/V)	Level (dBm)	Cable loss (dB)	Antenna Gain (dB)	Level (dBm)	(dBm)	(dB)		
ERP for Cellular Band (Part 22H), Middle channel												
836.6	94.42	207	2.0	Н	24.2	0.26	4.75	28.69	38.45	9.76		
836.6	91.24	331	1.8	V	17.0	0.26	4.75	21.49	38.45	16.96		
	EIRP for PCS Band (Part 24E), Middle channel											
1888.0	78.49	291	2.3	Н	17.0	0.45	8.84	25.39	33	7.61		
1888.0	76.82	52	2.4	V	13.1	0.45	8.84	21.49	33	11.51		

#### WCDMA Mode:

Frequency (MHz) Rec (dl	Receiver	Receiver Turntable	Rx Antenna		Substituted			Absolute	[			
	Reading (dBµV)	Angle Degree	Height (m)	Polar (H/V)	Level (dBm)	Cable loss (dB)	Antenna Gain (dB)	Level (dBm)	(dBm)	(dB)		
ERP for Cellular Band (Part 22H), Middle channel												
836.6	88.42	26	1.5	Н	18.2	0.26	4.75	22.69	38.45	15.76		
836.6	85.04	176	2.5	V	10.8	0.26	4.75	15.29	38.45	23.16		
	EIRP for PCS Band (Part 24E), Middle channel											
1880.00	74.29	44	1.1	Н	12.8	0.45	8.84	21.19	33	11.81		
1880.00	72.22	99	1.1	V	8.5	0.45	8.84	16.89	33	16.11		

#### Note:

All above data were tested with no amplifier. Absolute Level = Substituted Level - Cable loss + Antenna Gain Margin = Limit- Absolute Level

## FCC §2.1053, §22.917 & §24.238 - SPURIOUS RADIATED EMISSIONS

#### **Applicable Standard**

FCC § 2.1053, §22.917 and § 24.238.

#### **Test Procedure**

The transmitter was placed on a wooden turntable, and it was transmitting into a non-radiating load which was also placed on the turntable.

The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the receiving antenna height and polarization as well as EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. The test was performed by placing the EUT on 3-orthogonal axis.

The frequency range up to tenth harmonic of the fundamental frequency was investigated.

Remove the EUT and replace it with substitution antenna. A signal generator was connected to the substitution antenna by a non-radiating cable. The absolute levels of the spurious emissions were measured by the substitution.

Spurious emissions in dB =  $10 \lg (TXpwr in Watts/0.001)$  – the absolute level

Spurious attenuation limit in  $dB = 43 + 10 \text{ Log}_{10}$  (power out in Watts)

#### **Test Data**

#### **Environmental Conditions**

Temperature:	24 °C
<b>Relative Humidity:</b>	49 %
ATM Pressure:	101.0 kPa

The testing was performed by Layne Li on 2017-05-23.

EUT operation mode: Transmitting

Pre-scan with Low, Middle and High channel, the worst case as below:

### **30 MHz ~ 10 GHz:**

Frequency (MHz)	Dessiver	Turntable Angle Degree	Rx Antenna		Substituted			Absoluto		
	Reading (dBµV)		Height (m)	Polar (H/V)	Level (dBm)	Cable Loss (dB)	Antenna Gain (dB)	Level (dBm)	Limit (dBm)	Margin (dB)
GPRS Mode, Middle channel										
399.88	65.96	286	1.8	Н	-36.7	0.23	4.65	-32.28	-13	19.28
399.88	70.20	96	2.3	V	-35.6	0.23	4.65	-31.18	-13	18.18
1673.20	52.60	32	1.7	Н	-49.2	0.40	8.52	-41.08	-13	28.08
1673.20	53.17	68	1.6	V	-50.6	0.40	8.52	-42.48	-13	29.48

## Cellular Band (Part 22H)

**30 MHz ~ 20 GHz:** 

#### PCS Band (Part 24E)

Frequency (MHz) Re (d	Receiver	iver Turntable ling Angle IV) Degree	Rx Antenna		Substituted			Absoluto			
	Reading (dBµV)		Height (m)	Polar (H/V)	Level (dBm)	Cable Loss (dB)	Antenna Gain (dB)	Level (dBm)	Limit (dBm)	Margin (dB)	
	GPRS Mode, Middle channel										
399.88	64.46	318	2.4	Н	-38.2	0.23	4.65	-33.78	-13	20.78	
399.88	69.40	6	1.5	V	-36.4	0.23	4.65	-31.98	-13	18.98	
3760.00	57.52	179	2.1	Н	-38.5	0.59	9.72	-29.37	-13	16.37	
3760.00	62.51	175	1.3	V	-34.6	0.59	9.72	-25.47	-13	12.47	

### **30 MHz ~ 10 GHz:**

#### Cellular Band (Part 22H)

Frequency (MHz)	Receiver Reading (dBµV)	Turntable Angle Degree	Rx Antenna		Substituted			Absolute				
			Height (m)	Polar (H/V)	Level (dBm)	Cable Loss (dB)	Antenna Gain (dB)	Level (dBm)	Limit (dBm)	Margin (dB)		
WCDMA Mode, Middle channel												
399.88	63.46	138	1.3	Н	-39.2	0.23	4.65	-34.78	-13	21.78		
399.88	67.60	102	1.8	V	-38.2	0.23	4.65	-33.78	-13	20.78		
1673.20	49.70	32	2.2	Н	-52.1	0.40	8.52	-43.98	-13	30.98		
1673.20	53.17	233	2.4	V	-50.6	0.40	8.52	-42.48	-13	29.48		

#### **30 MHz ~ 20 GHz:**

#### PCS Band (Part 24E)

Frequency (MHz)	Receiver Reading (dBµV)	Turntable Angle Degree	Rx Antenna		Substituted			Absolute				
			Height (m)	Polar (H/V)	Level (dBm)	Cable Loss (dB)	Antenna Gain (dB)	Level (dBm)	Limit (dBm)	Margin (dB)		
WCDMA Mode, Middle channel												
399.88	62.46	112	2.1	Н	-40.2	0.23	4.65	-35.78	-13	22.78		
399.88	66.60	66	2.5	V	-39.2	0.23	4.65	-34.78	-13	21.78		
3760.00	56.22	107	1.6	Н	-39.8	0.59	9.72	-30.67	-13	17.67		
3760.00	53.71	266	2.4	V	-43.4	0.59	9.72	-34.27	-13	21.27		

#### Note:

1) Absolute Level = SG Level - Cable loss + Antenna Gain

2) Margin = Limit- Absolute Level

#### \*\*\*\*\* END OF REPORT \*\*\*\*\*