

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/0 Aug01,2022

Report No.: SZCR230200035201


Page: 1 of 148

FCC SAR TEST REPORT

Application No.: SZCR2302000352AT(FYCR2302000045AT)
Applicant: PAX Technology Limited
Address of Applicant: Room 2416, 24/F., Sun Hung Kai Centre, 30 Harbour, Hong Kong, China
Manufacturer: PAX Computer Technology (Shenzhen) Co., Ltd.
Address of Manufacturer: 401 and 402, Building 3, Shenzhen Software Park, Nanshan District, Shenzhen City, Guangdong Province, P.R.C
Product Name: Smart Handheld Computer
Model No.(EUT): A6650
Trade Mark: PAX
FCC ID: V5PA6650
Standard(s) : FCC 47CFR §2.1093
Date of Receipt: 2023-04-18
Date of Test: 2023-04-18 to 2023-05-06
Date of Issue: 2023-05-09

Test Result:	Pass*
---------------------	--------------

* In the configuration tested, the EUT complied with the standards specified above.



Keny Xu
EMC Laboratory Manager



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Testing & Calibration Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com



SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/0 Aug01,2022

Report No.: SZCR230200035201

Page: 2 of 148

Revision Record			
Version	Description	Date	Remark
00	Original	2023-05-09	/

Authorized for issue by:				
		Owen Xiao		
		Owen Xiao / Project Engineer		
		Eric Fu		
		Eric Fu / Reviewer		



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

Member of the SGS Group (SGS SA)

TEST SUMMARY

Frequency Band	Maximum Reported SAR(W/kg)	
	Body	Extremity
LTE Band 2	0.23	0.37
LTE Band 4	0.73	1.12
LTE Band 5	0.40	0.55
LTE Band 7	0.61	0.90
LTE Band 12	0.16	0.31
LTE Band 13	0.23	0.53
LTE Band 14	0.22	0.48
LTE Band 17	0.16	0.24
LTE Band 25	0.46	0.92
LTE Band 26a	0.43	0.50
LTE Band 26b	0.40	0.49
LTE Band 41	0.13	0.21
LTE Band 66	0.76	1.03
LTE Band 71	0.10	0.27
WI-FI (2.4GHz)	0.20	0.36
Bluetooth	0.06	0.24
WI-FI (5GHz)	0.74	0.57
SAR Limited(W/kg)	1.6	4
Maximum Simultaneous Transmission SAR (W/kg)		
Scenario	Body	Extremity
Sum SAR	1.50	1.69
SPLSR	N/A	N/A
SPLSR Limited	0.04	0.1

CONTENTS

1	GENERAL INFORMATION	6
1.1	GENERAL DESCRIPTION OF EUT	6
1.1.1	DUT Antenna Locations	8
1.2	TEST SPECIFICATION.....	9
1.3	RF EXPOSURE LIMITS	10
1.4	TEST LOCATION	11
1.5	TEST FACILITY	11
2	LABORATORY ENVIRONMENT	12
3	SAR MEASUREMENTS SYSTEM CONFIGURATION.....	13
3.1	THE SAR MEASUREMENT SYSTEM	13
3.2	ISOTROPIC E-FIELD PROBE EX3DV4	15
3.3	DATA ACQUISITION ELECTRONICS (DAE)	16
3.4	SAM TWIN PHANTOM.....	16
3.5	ELI PHANTOM.....	17
3.6	DEVICE HOLDER FOR TRANSMITTERS.....	18
3.7	MEASUREMENT PROCEDURE.....	19
3.7.1	Scanning procedure	19
3.7.2	Data Storage	21
3.7.3	Data Evaluation by SEMCAD.....	21
4	SAR MEASUREMENT VARIABILITY AND UNCERTAINTY	23
4.1	SAR MEASUREMENT VARIABILITY	23
4.2	SAR MEASUREMENT UNCERTAINTY	24
5	DESCRIPTION OF TEST POSITION	26
5.1	EXTREMITY EXPOSURE CONDITIONS	26
6	SAR SYSTEM VERIFICATION PROCEDURE	27
6.1	TISSUE SIMULATE LIQUID.....	27
6.1.1	Recipes for Tissue Simulate Liquid.....	27
6.1.2	Test Liquids Confirmation.....	28
6.1.3	Measurement for Tissue Simulate Liquid.....	29
6.2	SAR SYSTEM CHECK	30
6.2.1	Justification for Extended SAR Dipole Calibrations	31
6.2.2	Summary System Check Result(s)	32
6.2.3	Detailed System Check Results	32
6.2.4	Wi-Fi Test Configuration.....	33
6.2.5	LTE Test Configuration.....	39
6.2.6	BluetoothTest Configuration.....	41
7	TEST RESULT	42



SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/0 Aug01,2022

Report No.: SZCR230200035201

Page: 5 of 148

7.1	MEASUREMENT OF RF CONDUCTED POWER	42
7.1.1	Conducted Power Of LTE	42
7.1.2	Conducted Power Of Wi-Fi.....	67
7.1.3	Conducted Power Of BT.....	70
7.2	MEASUREMENT OF SAR DATA.....	71
7.2.1	SAR Result Of LTE Band 2	72
7.2.2	SAR Result Of LTE Band 4	73
7.2.3	SAR Result Of LTE Band 5	74
7.2.4	SAR Result Of LTE Band 7	75
7.2.5	SAR Result Of LTE Band 12	76
7.2.6	SAR Result Of LTE Band 13	77
7.2.7	SAR Result Of LTE Band 14	78
7.2.8	SAR Result Of LTE Band 17	79
7.2.9	SAR Result Of LTE Band 25	80
7.2.10	SAR Result Of LTE Band 26a.....	81
7.2.11	SAR Result Of LTE Band 26b.....	82
7.2.12	SAR Result Of LTE Band 41	83
7.2.13	SAR Result Of LTE Band 66.....	84
7.2.14	SAR Result Of LTE Band 71	85
7.2.15	SAR Result Of 2.4GHz Wi-Fi	86
7.2.16	SAR Result Of Bluetooth.....	87
7.2.17	SAR Result Of 5G WiFi.....	88
7.3	MULTIPLE TRANSMITTER EVALUATION.....	90
7.3.1	Simultaneous SAR SAR test evaluation.....	90
8	EQUIPMENT LIST	94
9	CALIBRATION CERTIFICATE	96
10	PHOTOGRAPHS	96
	APPENDIX A: DETAILED SYSTEM CHECK RESULTS	97
	APPENDIX B: DETAILED TEST RESULTS	107
	APPENDIX C: CALIBRATION CERTIFICATE	148
	APPENDIX D: PHOTOGRAPHS.....	148



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
 中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

1 General Information

1.1 General Description of EUT

Product Phase:	Production unit		
Device Type :	Portable device		
Exposure Category:	Uncontrolled environment / general population		
SN:	2750000172		
Hardware Version:	A6650		
Software Version:	V0.0.0.1		
Antenna Gain:	BT/2.4G WIFI antenna gain:-0.22dBi 5G WIFI antenna gain:3.01dBi B2: -1.4dBi; B4: -1.64dBi; B5: -2.9dBi; B7: -0.42dBi; B12: -3.63dBi; B13: -1.33dBi; B14: -1.49dBi; B17: -3.63dBi; B25: -1.28dBi; B26: -2.7dBi; B41: -0.42dBi; B66: -1.64dBi; B71: -4.78dBi		
Antenna Type:	FPC antenna		
Device Operating Configurations:			
Modulation Mode:	LTE:QPSK,16QAM,64QAM; WIFI: CCK, DSSS, OFDM;BT: GFSK, π /4DQPSK, 8DPSK		
	1, tested with power control Max Power (LTE Band 2/4/5/7/12/13/14/17/25/26/41/66/71)		
Frequency Bands:	Band	Tx (MHz)	Rx (MHz)
	LTE Band 2	1850-1910	1930-1990
	LTE Band 4	1710-1755	2110- 2155
	LTE Band 5	824-849	869-894
	LTE Band 7	2500-2570	2620- 2690
	LTE Band 12	699-716	729-746
	LTE Band 13	777-787	746-756
	LTE Band 14	788-798	758-768
	LTE Band 17	704-716	734-746
	LTE Band 25	1850-1915	1930-1995
	LTE Band 26	814-849	859-894
	LTE Band 41	2496-2690	2496-2690
	LTE Band 66	1710~1780	2110~2180
	LTE Band 71	617-652	663-698
	WIFI2.4G	2412-2462	2412-2462
	BT	2402-2480	2402-2480
	WIFI(U-NII-1)	5150~5250	5150~5250
	WIFI(U-NII-2A)	5250~5350	5250~5350
	WIFI(U-NII-2C)	5470~5725	5470~5725
	WIFI(U-NII-3)	5725~5850	5725~5850



SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/0 Aug01,2022

Report No.: SZCR230200035201

Page: 7 of 148

Battery Information:	Model:	IDS152GA
	Normal Voltage :	DC3.7V
	Rated capacity :	5400mAh
	Battery Type:	Rechargeable Li-ion Battery
	Manufacturer:	ICON ENERGY SYSTEM (SHENZHEN) CO.,LTD.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Technical Services Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

Member of the SGS Group (SGS SA)



SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/0 Aug01,2022

Report No.: SZCR230200035201

Page: 8 of 148

1.1.1 DUT Antenna Locations

Please see the Appendix D



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch (SZEMC-TRF-01) Laboratory

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.ssgroup.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

Member of the SGS Group (SGS SA)

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/0 Aug01,2022

Report No.: SZCR230200035201

Page: 9 of 148

1.2 Test Specification

Identity	Document Title
FCC 47CFR §2.1093	Radio frequency Radiation Exposure Evaluation: Portable Devices
IEEE Std C95.1 – 1992	IEEE Standard for Safety Levels with Respect to Human Exposure to Electric, Magnetic, and Electromagnetic Fields, 0 Hz to 300 GHz
IEEE Std 1528-2013	Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques
KDB 447498 D04v01	RF Exposure Procedures and Equipment Authorization Policies for Mobile and Portable Devices
KDB 248227 D01 v02r02	SAR GUIDANCE FOR IEEE 802.11 (Wi-Fi) TRANSMITTERS
KDB 941225 D05 v02r05	SAR EVALUATION CONSIDERATIONS FOR LTE DEVICES
KDB 941225 D06 v02r01	SAR EVALUATION PROCEDURES FOR PORTABLE DEVICES WITH WIRELESS ROUTER CAPABILITIES
KDB 865664 D01 v01r04	SAR Measurement Requirements for 100 MHz to 6 GHz
KDB 865664 D01 v01r02	RF Exposure Compliance Reporting and Documentation Considerations



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
 中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

1.3 RF exposure limits

Human Exposure	Uncontrolled Environment General Population	Controlled Environment Occupational
Spatial Peak SAR* (Brain*Trunk)	1.60 W/kg	8.00 W/kg
Spatial Average SAR** (Whole Body)	0.08 W/kg	0.40 W/kg
Spatial Peak SAR*** (Hands/Feet/Ankle/Wrist)	4.00 W/kg	20.00 W/kg

Notes:

* The Spatial Peak value of the SAR averaged over any 1 gram of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time

** The Spatial Average value of the SAR averaged over the whole body.

*** The Spatial Peak value of the SAR averaged over any 10 grams of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.

Uncontrolled Environments are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure.

Controlled Environments are defined as locations where there is exposure that may be incurred by persons who are aware of the potential for exposure, (i.e. as a result of employment or occupation.)

1.4 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen Branch

No. 1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China. 518057.

Tel: +86 755 2601 2053 Fax: +86 755 2671 0594

No tests were sub-contracted.

1.5 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

• A2LA (Certificate No. 3816.01)

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 3816.01.

• VCCI (Member No. 1937)

The 3m Fully-anechoic chamber for above 1GHz, 10m Semi-anechoic chamber for below 1GHz, Shielded Room for Mains Port Conducted Interference Measurement and Telecommunication Port Conducted Interference Measurement of SGS-CSTC Standards Technical Services Co., Ltd.

Shenzhen EMC laboratory have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-20026, R-14188, C-12383 and T-11153 respectively.

• FCC –Designation Number: CN1336

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized as an accredited testing laboratory.

Designation Number: CN1336. Test Firm Registration Number: 787754.

• Innovation, Science and Economic Development Canada

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized by ISED as an accredited testing laboratory.

CAB identifier: CN0006.

IC#: 4620C.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch EMC Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

2 Laboratory Environment

Temperature	Min. = 18°C, Max. = 25 °C
Relative humidity	Min. = 30%, Max. = 70%
Ground system resistance	< 0.5 Ω
Ambient noise is checked and found very low and in compliance with requirement of standards. Reflection of surrounding objects is minimized and in compliance with requirement of standards.	



3 SAR Measurements System Configuration

3.1 The SAR Measurement System

This SAR Measurement System uses a Computer-controlled 3-D stepper motor system (SPEAG DASY5 professional system). A E-field probe is used to determine the internal electric fields. The SAR can be obtained from the equation $SAR = \sigma (|E|^2) / \rho$ where σ and ρ are the conductivity and mass density of the tissue-Simulate.

The DASY5 system for performing compliance tests consists of the following items:


A standard high precision 6-axis robot (Stabile RX family) with controller, teach pendant and software .An arm extension for accommodation the data acquisition electronics (DAE).

A dosimetric probe, i.e., an isotropic E-field probe optimized and calibrated for usage in tissue simulating liquid. The probe is equipped with an optical surface detector system.

A data acquisition electronics (DAE) which performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.

The Electro-optical converter (EOC) performs the conversion between optical and electrical of the signals for the digital communication to DAE and for the analog signal from the optical surface detection. The EOC is connected to the measurement server.







F-1. SAR Measurement System Configuration

- The function of the measurement server is to perform the time critical tasks such as signal filtering, control of the robot operation and fast movement interrupts.
- A probe alignment unit which improves the (absolute) accuracy of the probe positioning.
- A computer operating Windows 7.
- DASY5 software.
- Remote control with teach pendant and additional circuitry for robot safety such as warning lamps, etc.
- The SAM twin phantom enabling testing left-hand, right-hand and Body Worn usage.
- The device holder for handheld mobile phones.
- Tissue simulating liquid mixed according to the given recipes.
- Validation dipole kits allowing to validate the proper functioning of the system.


3.2 Isotropic E-field Probe EX3DV4

	<p>Symmetrical design with triangular core Built-in shielding against static charges PEEK enclosure material (resistant to organic solvents, e.g., DGBE)</p>
Calibration	<p>ISO/IEC 17025 calibration service available.</p>
Frequency	<p>10 MHz to > 6 GHz Linearity: ± 0.2 dB (30 MHz to 6 GHz)</p>
Directivity	<p>± 0.3 dB in TSL (rotation around probe axis) ± 0.5 dB in TSL (rotation normal to probe axis)</p>
Dynamic Range	<p>10 μW/g to > 100 mW/g Linearity: ± 0.2 dB (noise: typically < 1 μW/g)</p>
Dimensions	<p>Overall length: 337 mm (Tip: 20 mm) Tip diameter: 2.5 mm (Body: 12 mm) Typical distance from probe tip to dipole centers: 1 mm</p>
Application	<p>High precision dosimetric measurements in any exposure scenario (e.g., very strong gradient fields); the only probe that enables compliance testing for frequencies up to 6 GHz with precision of better 30%.</p>
Compatibility	<p>DASY3, DASY4, DASY52 SAR and higher, EASY4/MRI</p>

3.3 Data Acquisition Electronics (DAE)

Model	DAE4	
Construction	Signal amplifier, multiplexer, A/D converter and control logic. Serial optical link for communication with DASY4/5 embedded system (fully remote controlled). Two step probe touch detector for mechanical surface detection and emergency robot stop.	
Measurement Range	-100 to +300 mV (16 bit resolution and two range settings: 4mV,400mV)	
Input Offset Voltage	< 5μV (with auto zero)	
Input Bias Current	< 50 f A	
Dimensions	60 x 60 x 68 mm	


3.4 SAM Twin Phantom

Material	Vinylester, glass fiber reinforced (VE-GF)	
Liquid Compatibility	Compatible with all SPEAG tissue simulating liquids (incl. DGBE type)	
Shell Thickness	2 ± 0.2 mm (6 ± 0.2 mm at ear point)	
Dimensions (incl. Wooden Support)	Length: 1000 mm Width: 500 mm Height: adjustable feet	
Filling Volume	approx. 25 liters	
Wooden Support	SPEAG standard phantom table	

The shell corresponds to the specifications of the Specific Anthropomorphic Mannequin (SAM) phantom defined in IEEE 1528 and IEC 62209-1. It enables the dosimetric evaluation of left and right hand phone usage as well as body mounted usage at the flat phantom region. A cover prevents evaporation of the liquid. Reference markings on the phantom allow the complete setup of all predefined phantom positions and measurement grids by teaching three points with the robot.

Twin SAM V5.0 has the same shell geometry and is manufactured from the same material as Twin SAM V4.0, but has reinforced top structure.

3.5 ELI Phantom

Material	Vinylester, glass fiber reinforced (VE-GF)	
Liquid Compatibility	Compatible with all SPEAG tissue simulating liquids (incl. DGBE type)	
Shell Thickness	2.0 ± 0.2 mm (bottom plate)	
Dimensions	Major axis: 600 mm Minor axis: 400 mm	
Filling Volume	approx. 30 liters	
Wooden Support	SPEAG standard phantom table	

Phantom for compliance testing of handheld and body-mounted wireless devices in the frequency range of 30 MHz to 6 GHz. ELI is fully compatible with the IEC 62209-2 standard and all known tissue simulating liquids. ELI has been optimized regarding its performance and can be integrated into our standard phantom tables. A cover prevents evaporation of the liquid. Reference markings on the phantom allow installation of the complete setup, including all predefined phantom positions and measurement grids, by teaching three points. The phantom is compatible with all SPEAG dosimetric probes and dipoles.

ELI V5.0 has the same shell geometry and is manufactured from the same material as ELI4, but has reinforced top structure.

3.6 Device Holder for Transmitters



F-2. Device Holder for Transmitters

- The DASY device holder is designed to cope with different positions given in the standard. It has two scales for the device rotation (with respect to the body axis) and the device inclination (with respect to the line between the ear reference points). The rotation centres for both scales are the ear reference point (ERP). Thus the device needs no repositioning when changing the angles.
- The DASY device holder has been made out of low-loss POM material having the following dielectric parameters: relative permittivity $\epsilon=3$ and loss tangent $\delta=0.02$. The amount of dielectric material has been reduced in the closest vicinity of the device, since measurements have suggested that the influence of the clamp on the test results could thus be lowered.

3.7 Measurement procedure

3.7.1 Scanning procedure

Step 1: Power reference measurement

The “reference” and “drift” measurements are located at the beginning and end of the batch process. They measure the field drift at one single point in the liquid over the complete procedure.

Step 2: Area scan

The SAR distribution at the exposed side of the head was measured at a distance of 4mm from the inner surface of the shell. The area covered the entire dimension of the head and the horizontal grid spacing was 15mm*15mm or 12mm*12mm or 10mm*10mm. Based on the area scan data, the area of the maximum absorption was determined by spline interpolation.

Step 3: Zoom scan

Around this point, a volume of 30mm*30mm*30mm (fine resolution volume scan, zoom scan) was assessed by measuring 5x5x7 points ($\leq 2\text{GHz}$) and 7x7x7 points ($\geq 2\text{GHz}$). On this basis of this data set, the spatial peak SAR value was evaluated with the following procedure:

The data at the surface was extrapolated, since the centre of the dipoles is 2.0mm away from the tip of the probe and the distance between the surface and the lowest measuring point is 1.2mm. (This can be variable. Refer to the probe specification). The extrapolation was based on a least square algorithm. A polynomial of the fourth order was calculated through the points in z-axes. This polynomial was then used to evaluate the points between the surface and the probe tip. The maximum interpolated value was searched with a straight-forward algorithm. Around this maximum the SAR values averaged over the spatial volumes (1g or 10g) were computed using the 3D-Spline interpolation algorithm. The volume was integrated with the trapezoidal algorithm. One thousand points were interpolated to calculate the average. All neighbouring volumes were evaluated until no neighboring volume with a higher average value was found.

The area and zoom scan resolutions specified in the table below must be applied to the SAR measurements. Probe boundary effect error compensation is required for measurements with the probe tip closer than half a probe tip diameter to the phantom surface. Both the probe tip diameter and sensor offset distance must satisfy measurement protocols; to ensure probe boundary effect errors are minimized and the higher fields closest to the phantom surface can be correctly measured and extrapolated to the phantom surface for computing 1-g SAR. Tolerances of the post-processing algorithms must be verified by the test laboratory for the scan resolutions used in the SAR measurements, according to the reference distribution functions specified in IEEE Std. 1528-2013.

		≤ 3 GHz	> 3 GHz
Maximum distance from closest measurement point (geometric center of probe sensors) to phantom surface		5 ± 1 mm	$\frac{1}{2} \cdot \delta \cdot \ln(2) \pm 0.5 \text{ mm}$
Maximum probe angle from probe axis to phantom surface normal at the measurement location		30° ± 1°	20° ± 1°
Maximum area scan spatial resolution: $\Delta x_{\text{Area}}, \Delta y_{\text{Area}}$		≤ 2 GHz: ≤ 15 mm 2 – 3 GHz: ≤ 12 mm	3 – 4 GHz: ≤ 12 mm 4 – 6 GHz: ≤ 10 mm
		When the x or y dimension of the test device, in the measurement plane orientation, is smaller than the above, the measurement resolution must be ≤ the corresponding x or y dimension of the test device with at least one measurement point on the test device.	
Maximum zoom scan spatial resolution: $\Delta x_{\text{Zoom}}, \Delta y_{\text{Zoom}}$		≤ 2 GHz: ≤ 8 mm 2 – 3 GHz: ≤ 5 mm*	3 – 4 GHz: ≤ 5 mm* 4 – 6 GHz: ≤ 4 mm*
Maximum zoom scan spatial resolution, normal to phantom surface	uniform grid: $\Delta z_{\text{Zoom}}(n)$	≤ 5 mm	3 – 4 GHz: ≤ 4 mm 4 – 5 GHz: ≤ 3 mm 5 – 6 GHz: ≤ 2 mm
	graded grid $\Delta z_{\text{Zoom}}(1)$: between 1 st two points closest to phantom surface	≤ 4 mm	3 – 4 GHz: ≤ 3 mm 4 – 5 GHz: ≤ 2.5 mm 5 – 6 GHz: ≤ 2 mm
	$\Delta z_{\text{Zoom}}(n>1)$: between subsequent points	≤ 1.5 · $\Delta z_{\text{Zoom}}(n-1)$	
Minimum zoom scan volume	x, y, z	≥ 30 mm	3 – 4 GHz: ≥ 28 mm 4 – 5 GHz: ≥ 25 mm 5 – 6 GHz: ≥ 22 mm
<p>Note: δ is the penetration depth of a plane-wave at normal incidence to the tissue medium; see draft standard IEEE P1528-2011 for details.</p> <p>* When zoom scan is required and the <u>reported</u> SAR from the <u>area scan based 1-g SAR estimation</u> procedures of KDB 447498 is ≤ 1.4 W/kg, ≤ 8 mm, ≤ 7 mm and ≤ 5 mm zoom scan resolution may be applied, respectively, for 2 GHz to 3 GHz, 3 GHz to 4 GHz and 4 GHz to 6 GHz.</p>			

Step 4: Power reference measurement (drift)

The Power Drift Measurement job measures the field at the same location as the most recent power reference measurement job within the same procedure, and with the same settings. The indicated drift is mainly the variation of the DUT's output power and should vary max. ± 5 %



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

3.7.2 Data Storage

The DASY software stores the acquired data from the data acquisition electronics as raw data (in microvolt readings from the probe sensors), together with all necessary software parameters for the data evaluation (probe calibration data, liquid parameters and device frequency and modulation data) in measurement files with the extension ".DAE3". The software evaluates the desired unit and format for output each time the data is visualized or exported. This allows verification of the complete software setup even after the measurement and allows correction of incorrect parameter settings. For example, if a measurement has been performed with a wrong crest factor parameter in the device setup, the parameter can be corrected afterwards and the data can be re-evaluated. The measured data can be visualized or exported in different units or formats, depending on the selected probe type ([V/m], [A/m], [°C], [m W/g], [m W/cm²], [dBrel], etc.). Some of these units are not available in certain situations or show meaningless results, e.g., a SAR output in a lossless media will always be zero. Raw data can also be exported to perform the evaluation with other software packages.

3.7.3 Data Evaluation by SEMCAD

The SEMCAD software automatically executes the following procedures to calculate the field units from the microvolt readings at the probe connector. The parameters used in the evaluation are stored in the configuration modules of the software:

Probe parameters:	- Sensitivity	Normi, ai0, ai1, ai2
- Conversion factor	ConvFi	
- Diode compression point	Dcpi	
Device parameters:	- Frequency	f
- Crest factor	cf	
Media parameters:	- Conductivity	ε
- Density	ρ	

These parameters must be set correctly in the software. They can be found in the component documents or they can be imported into the software from the configuration files issued for the DASY components. In the direct measuring mode of the multimeter option, the parameters of the actual system setup are used. In the scan visualization and export modes, the parameters stored in the corresponding document files are used.

The first step of the evaluation is a linearization of the filtered input signal to account for the compression characteristics of the detector diode. The compensation depends on the input signal, the diode type and the DC-transmission factor from the diode to the evaluation electronics.

If the exciting field is pulsed, the crest factor of the signal must be known to correctly compensate for peak power. The formula for each channel can be given as:

$$V_i = U_i + U_i^2 \cdot cf / dcpi$$

With V_i = compensated signal of channel i (i = x, y, z)

U_i = input signal of channel i (i = x, y, z)



cf = crest factor of exciting field (DASY parameter)

dcp i = diode compression point (DASY parameter)

From the compensated input signals the primary field data for each channel can be evaluated:

E-field probes:

$$E_i = (V_i / Norm_i \cdot ConvF)^{1/2}$$

H-field probes:

$$H_i = (V_i)^{1/2} \cdot (a_{i0} + a_{i1}f + a_{i2}f^2) / f$$

With V_i = compensated signal of channel i (i = x, y, z)

$Norm_i$ = sensor sensitivity of channel i (i = x, y, z)

[mV/(V/m)²] for E-field Probes

ConvF = sensitivity enhancement in solution

a_{ij} = sensor sensitivity factors for H-field probes

f = carrier frequency [GHz]

E_i = electric field strength of channel i in V/m

H_i = magnetic field strength of channel i in A/m

The RSS value of the field components gives the total field strength (Hermitian magnitude):

$$E_{tot} = (E_x^2 + E_y^2 + E_z^2)^{1/2}$$

The primary field data are used to calculate the derived field units.

$$SAR = (E_{tot}^2 \cdot \sigma) / (\epsilon \cdot 1000)$$

With SAR = local specific absorption rate in mW/g

E_{tot} = total field strength in V/m

σ = conductivity in [mho/m] or [Siemens/m]

ϵ = equivalent tissue density in g/cm³

Note that the density is normally set to 1 (or 1.06), to account for actual brain density rather than the density of the simulation liquid. The power flow density is calculated assuming the excitation field to be a free space field.

$$P_{pwe} = E_{tot}^2 / 3770 \quad \text{or} \quad P_{pwe} = H_{tot}^2 \cdot 37.7$$

with P_{pwe} = equivalent power density of a plane wave in mW/cm²

E_{tot} = total electric field strength in V/m

H_{tot} = total magnetic field strength in A/m



4 SAR measurement variability and uncertainty

4.1 SAR measurement variability

Per KDB865664 D01 SAR measurement 100 MHz to 6 GHz v01r04, SAR measurement variability must be assessed for each frequency band, which is determined by the SAR probe calibration point and tissue-equivalent medium used for the device measurements. The additional measurements are repeated after the completion of all measurements requiring the same head or body tissue-equivalent medium in a frequency band. The test device should be returned to ambient conditions (normal room temperature) with the battery fully charged before it is re-mounted on the device holder for the repeated measurement(s) to minimize any unexpected variations in the repeated results.

- 1) Repeated measurement is not required when the original highest measured SAR is < 0.80 W/kg; steps 2) through 4) do not apply.
- 2) When the original highest measured SAR is ≥ 0.80 W/kg, repeat that measurement once.
- 3) Perform a second repeated measurement only if the ratio of largest to smallest SAR for the original and first repeated measurements is > 1.20 or when the original or repeated measurement is ≥ 1.45 W/kg ($\sim 10\%$ from the 1-g SAR limit).
- 4) Perform a third repeated measurement only if the original, first or second repeated measurement is ≥ 1.5 W/kg and the ratio of largest to smallest SAR for the original, first and second repeated measurements is > 1.20 .

The same procedures should be adapted for measurements according to extremity and occupational exposure limits by applying a factor of 2.5 for extremity exposure and a factor of 5 for occupational exposure to the corresponding SAR thresholds.



4.2 SAR measurement uncertainty

Per KDB865664 D01 SAR Measurement 100 MHz to 6 GHz, when the highest measured 1-g SAR within a frequency band is < 1.5 W/kg, the extensive SAR measurement uncertainty analysis described in IEEE Std 1528-2013 is not required in SAR reports submitted for equipment approval. The equivalent ratio (1.5/1.6) is applied to extremity and occupational exposure conditions.

Measurement uncertainty evaluation									
A	b1	c	d	e=f(d,K)	f	g	i=C*g/e	i=C*g/e	k
Uncertainty Component	Section in P1528	Tol (%)	Prob. Dist	Div.	C _i (1g)	C _i (10g)	1-g ui(%)	10-g ui(%)	V _i (Veff)
Measurement System									
Probe Calibration (k=1)	E.2.1	6.3	N	1	1	1	6.30	6.30	∞
Axial Isotropy	E.2.2	0.5	R	√3	0.7	0.7	0.20	0.20	∞
Hemispherical Isotropy	E.2.2	2.6	R	√3	0.7	0.7	1.06	1.06	∞
Boundary Effect	E.2.3	1.0	R	√3	1	1	0.58	0.58	∞
Linearity	E.2.4	0.6	R	√3	1	1	0.35	0.35	∞
System Detection LimitS	E.2.4	0.25	R	√3	1	1	0.14	0.14	∞
Modulation Response	E.2.5	2.4	R	√3	1	1	1.39	1.39	∞
Readout Electronics	E.2.6	0.3	N	1	1	1	0.30	0.30	∞
Response Time	E.2.7	0.0	R	√3	1	1	0.00	0.00	∞
Integration Time	E.2.8	2.6	R	√3	1	1	1.50	1.50	∞
RF Ambient Condition-Noise	E.6.1	3.0	R	√3	1	1	1.73	1.73	∞
RF Ambient Condition-Reflections	E.6.1	3.0	R	√3	1	1	1.73	1.73	∞
Probe Positioning-Mechanical Tolerance	E.6.2	1.5	R	√3	1	1	0.87	0.87	∞
Probe Positioning-with Respect to Phantom	E.6.3	2.9	R	√3	1	1	1.67	1.67	∞
Max. SAR Evaluation	E.5	1.0	R	√3	1	1	0.58	0.58	∞
Test sample Related									
Test sample Positioning	E.4.2	3.7	N	1	1	1	3.70	3.70	9
Device Holder Uncertainty	E.4.1	3.6	N	1	1	1	3.60	3.60	∞
Output Power Variation-SAR Drift Measurement	E.2.9	5	R	√3	1	1	2.89	2.89	∞
Output Power Variation-SAR Drift Measurement	E.6.5	0	R	√3	1	1	0.00	0.00	∞
Phantom and Tissue Parameters									
Phantom Uncertainty(Shape and Thickness Tolerances)	E.3.1	4	R	√3	1	1	2.31	2.31	∞
SAR Correction	E.3.2	1.9	N	1	1	0.84	1.90	1.60	∞
Liquid Conductivity (Measurement Uncertainty)	E.3.3	3.75	N	1	0.78	0.71	2.93	2.663	5
Liquid Permittivity (Measurement Uncertainty)	E.3.3	1.62	N	1	0.23	0.26	0.37	0.421	5
Liquid Conductivity (Temperature Uncertainty)	E.3.4	4.2	R	√3	0.78	0.71	1.89	1.72	∞



SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/0 Aug01,2022

Report No.: SZCR230200035201

Page: 25 of 148

Liquid Permittivity (Temperature Uncertainty)	E.3.4	3.7	R	$\sqrt{3}$	0.23	0.26	0.49	0.56	∞
Combined Standard Uncertainty				RSS			10.58	10.43	430
Expanded Uncertainty (95% Confidence Interval)				$k=2$			21.16%	20.87%	



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Technical Services Laboratory

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

Member of the SGS Group (SGS SA)

5 Description of Test Position

5.1 Extremity exposure conditions

Devices that are designed or intended for use on extremities, or mainly operated in extremity only exposure conditions, i.e., hands, wrists, feet and ankles, may require extremity SAR evaluation. When the device also operates in close proximity to the user's body, SAR compliance for the body is also required. The 1-g body and 10-g extremity SAR Test Exclusion Thresholds in 8.2 should be applied to determine SAR test requirements. When extremity SAR testing is required, a flat phantom must be used if the exposure condition is more conservative than the actual use conditions; otherwise, a KDB inquiry is required to determine the phantom and test requirements. Body SAR compliance is also tested with a flat phantom. For devices with irregular shapes or form factors that do not conform to a flat phantom, and/or unusual operating configurations and exposure conditions, a KDB inquiry is also required to determine the appropriate SAR measurement procedures. Unless it is specified differently in the published RF exposure KDB procedures, when simultaneous transmission applies to extremity exposure, the simultaneous transmission SAR test exclusion provisions should be applied. When simultaneous transmission SAR measurement is required, the enlarged zoom scan and volume scan post-processing procedures in KDB Publication 865664 D01 should be applied.

SAR can test the sides near the antenna, the surface of the device should be tested for SAR compliance with the device touching the phantom. The SAR Exclusion Threshold in KDB 447498 D04 can be applied to determine SAR test exclusion for adjacent edge configurations. The closest distance from the antenna to an adjacent device surface is used to determine if SAR testing is required for the adjacent surfaces, with the adjacent surface positioned against the phantom and the surface containing the antenna positioned perpendicular to the phantom.

6 SAR System Verification Procedure

6.1 Tissue Simulate Liquid

6.1.1 Recipes for Tissue Simulate Liquid

The following tables give the recipes for tissue simulating liquids to be used in different frequency bands:

Ingredients (% by weight)	Frequency (MHz)									
	450		835		915		1900		2450	
Tissue Type	Head	Body	Head	Body	Head	Body	Head	Body	Head	Body
Water	38.56	51.16	41.45	52.4	41.05	56.0	54.9	40.4	62.7	73.2
Salt (NaCl)	3.95	1.49	1.45	1.4	1.35	0.76	0.18	0.5	0.5	0.04
Sugar	56.32	46.78	56.0	45.0	56.5	41.76	0.0	58.0	0.0	0.0
HEC	0.98	0.52	1.0	1.0	1.0	1.21	0.0	1.0	0.0	0.0
Bactericide	0.19	0.05	0.1	0.1	0.1	0.27	0.0	0.1	0.0	0.0
Triton X-100	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	36.8	0.0
DGBE	0.0	0.0	0.0	0.0	0.0	0.0	44.92	0.0	0.0	26.7
Dielectric Constant	43.42	58.0	42.54	56.1	42.0	56.8	39.9	54.0	39.8	52.5
Conductivity (S/m)	0.85	0.83	0.91	0.95	1.0	1.07	1.42	1.45	1.88	1.78

HSL5GHz is composed of the following ingredients:

Water: 50-65%

Mineral oil: 10-30%

Emulsifiers: 8-25%

Sodium salt: 0-1.5%

MSL5GHz is composed of the following ingredients:

Water: 64-78%

Mineral oil: 11-18%

Emulsifiers: 9-15%

Sodium salt: 2-3%

6.1.2 Test Liquids Confirmation

Simulated tissue liquid parameter confirmation

The dielectric parameters were checked prior to assessment using the SPEAG DAK3.5 dielectric probe kit. The dielectric parameters measured are reported in each correspondent section.

IEEE SCC-34/SC-2 P1528 recommended tissue dielectric parameters

The head tissue dielectric parameters recommended by the IEEE SCC-34/SC-2 in P1528 have been incorporated in the following table. These head parameters are derived from planar layer models simulating the highest expected SAR for the dielectric properties and tissue thickness variations in a human head. Other head and body tissue parameters that have not been specified in P1528 are derived from the tissue dielectric parameters computed from the 4-Cole-Cole equations and extrapolated according to the head parameters specified in P1528

Target Frequency (MHz)	Head		Body	
	ϵ_r	σ (S/m)	ϵ_r	σ (S/m)
150	52.3	0.76	61.9	0.80
300	45.3	0.87	58.2	0.92
450	43.5	0.87	56.7	0.94
835	41.5	0.90	55.2	0.97
900	41.5	0.97	55.0	1.05
915	41.5	0.98	55.0	1.06
1450	40.5	1.20	54.0	1.30
1610	40.3	1.29	53.8	1.40
1800-2000	40.0	1.40	53.3	1.52
2450	39.2	1.80	52.7	1.95
3000	38.5	2.40	52.0	2.73
5800	35.3	5.27	48.2	6.00

(ϵ_r = relative permittivity, σ = conductivity and $\rho = 1000 \text{ kg/m}^3$)


6.1.3 Measurement for Tissue Simulate Liquid

The dielectric properties for this Tissue Simulate Liquids were measured by using the SPEAG DAK3.5 dielectric probe kit in conjunction with Agilent E5071B Network Analyzer (300 KHz-8500 MHz). The Conductivity (σ) and Permittivity (ρ) are listed in bellow table. For the SAR measurement given in this report. The temperature variation of the Tissue Simulate Liquids was $22\pm 2^{\circ}\text{C}$.

Measurement for Tissue Simulate Liquid										
Tissue Type	Measured Frequency (MHz)	Conductivity (σ)	Permittivity (ϵ_r)	Conductivity Target (σ)	Permittivity Target (ϵ_r)	Delta (σ) (%)	Delta (ϵ_r) (%)	Limit (%)	Liquid Temp. ($^{\circ}\text{C}$)	Date
750 Head	750	0.902	42.012	0.89	41.90	1.35	0.27	± 5	22.1	2023/4/24
835 Head	835	0.916	42.052	0.90	41.50	1.78	1.33	± 5	22.1	2023/4/27
1800 Head	1800	1.383	39.873	1.40	40.00	-1.21	-0.32	± 5	22.2	2023/5/4
1900 Head	1900	1.410	40.095	1.40	40.00	0.71	0.24	± 5	22.3	2023/5/6
2450 Head	2450	1.817	39.995	1.80	39.20	0.94	2.03	± 5	22	2023/4/18
2600 Head	2600	1.967	39.725	1.96	39.00	0.36	1.86	± 5	22.1	2023/4/22
5250 Head	5250	4.659	35.855	4.71	35.95	-1.08	-0.26	± 5	22.2	2023/4/19
5600 Head	5600	5.038	34.807	5.07	35.50	-0.63	-1.95	± 5	22.2	2023/4/20
5750 Head	5750	5.229	35.406	5.22	35.35	0.17	0.16	± 5	22.2	2023/4/21

6.2 SAR System Check

The microwave circuit arrangement for system check is sketched in bellow figure. The daily system accuracy verification occurs within the flat section of the SAM phantom. A SAR measurement was performed to see if the measured SAR was within +/- 10% from the target SAR values. The tests were conducted on the same days as the measurement of the EUT. The obtained results from the system accuracy verification are displayed in the following table. During the tests, the ambient temperature of the laboratory was in the range $22\pm 2^{\circ}\text{C}$, the relative humidity was in the range 60% and the liquid depth above the ear reference points was above 15 cm in all the cases. It is seen that the system is operating within its specification, as the results are within acceptable tolerance of the reference values.



F-3. the microwave circuit arrangement used for SAR system verification

6.2.1 Justification for Extended SAR Dipole Calibrations

1) Referring to KDB865664 D01 requirements for dipole calibration, instead of the typical annual calibration recommended by measurement standards, longer calibration intervals of up to three years may be considered when it is demonstrated that the SAR target, impedance and return loss of a dipole have remain stable according to the following requirements. Each measured dipole is expected to evaluate with the following criteria at least on annual interval in Appendix C.

- a) There is no physical damage on the dipole;
- b) System check with specific dipole is within 10% of calibrated value;
- c) Return-loss is within 10% of calibrated measurement;
- d) Impedance is within 5Ω from the previous measurement.

2) Network analyzer probe calibration against air, distilled water and a shorting block performed before measuring liquid parameters.



6.2.2 Summary System Check Result(s)

SAR System Validation Result(s)											
Validation Kit		Measured SAR 250mW	Measured SAR 250mW	Measured SAR (normalized to 1w)	Measured SAR (normalized to 1w)	Target SAR (normalized to 1w) (±10%)	Target SAR (normalized to 1w) (±10%)	Deviation (Within ±10%)		Liquid Temp. (°C)	Measured Date
		1g (W/kg)	10g (W/kg)	1g (W/kg)	10g (W/kg)	1-g(W/kg)	10-g(W/kg)	1-g(W/kg)	10-g(W/kg)		
D750V2	Head	2.06	1.36	8.24	5.44	8.23	5.41	0.12%	0.55%	22.1	2023/4/24
D835V2	Head	2.36	1.58	9.44	6.32	9.41	6.25	0.32%	1.12%	22.1	2023/4/27
D1800V2	Head	9.88	5.19	39.52	20.76	38.4	20.2	2.92%	2.77%	22.2	2023/5/4
D1900V2	Head	10.1	5.19	40.4	20.76	39.7	20.5	1.76%	1.27%	22.3	2023/5/6
D2450V2	Head	13.1	6.12	52.4	24.48	53	24.6	-1.13%	-0.49%	22	2023/4/18
D2600V2	Head	14.4	6.33	57.6	25.32	56.2	25	2.49%	1.28%	22.1	2023/4/22
Validation Kit		Measured SAR 100mW	Measured SAR 100mW	Measured SAR (normalized to 1w)	Measured SAR (normalized to 1w)	Target SAR (normalized to 1w) (±10%)	Target SAR (normalized to 1w) (±10%)	Deviation (Within ±10%)		Liquid Temp. (°C)	Measured Date
		1g (W/kg)	10g (W/kg)	1g (W/kg)	10g (W/kg)	1-g(W/kg)	10-g(W/kg)	1-g(W/kg)	10-g(W/kg)		
D5GHzV2	Head(5.25GHz)	7.73	2.16	77.3	21.6	77.7	22.4	-0.51%	-3.57%	22.2	2023/4/19
	Head(5.6GHz)	8.33	2.41	83.3	24.1	81.2	23.5	2.59%	2.55%	22.2	2023/4/20
	Head(5.75GHz)	8.14	2.33	81.4	23.3	78.9	22.7	3.17%	2.64%	22.2	2023/4/21

6.2.3 Detailed System Check Results


Please see the Appendix A

6.2.4 Wi-Fi Test Configuration


A Wi-Fi device must be configured to transmit continuously at the required data rate, channel bandwidth and signal modulation, using the highest transmission duty factor supported by the test mode tools for SAR measurement.

6.2.4.1 Duty cycle

2.4GWLAN duty cycle: 98.57%



5GWLAN duty cycle: 98.22%



6.2.4.2 Initial Test Position SAR Test Reduction Procedure

DSSS and OFDM configurations are considered separately according to the required SAR procedures. SAR is measured in the initial test position using the 802.11 transmission mode configuration required by the DSSS procedure or initial test configuration and subsequent test configuration(s) according to the OFDM procedures. The initial test position procedure is described in the following:

- 1) .When the reported SAR of the initial test position is ≤ 0.4 W/kg, further SAR measurement is not required for the other (remaining) test positions in that exposure configuration and 802.11 transmission mode combinations within the frequency band or aggregated band. SAR is also not required for that exposure configuration in the subsequent test configuration(s).
- 2) .When the reported SAR of the initial test position is > 0.4 W/kg, SAR is repeated for the 802.11 transmission mode configuration tested in the initial test position using subsequent highest extrapolated or estimated 1-g SAR conditions determined by area scans or next closest/smallest test separation distance and maximum RF coupling test positions based on manufacturer justification, on the highest maximum output power channel, until the reported SAR is ≤ 0.8 W/kg or all required test positions (left, right, touch, tilt or subsequent surfaces and edges) are tested.
- 3) .For all positions/configurations tested using the initial test position and subsequent test positions, when the reported SAR is > 0.8 W/kg, SAR is measured for these test positions/configurations on the subsequent next highest measured output power channel(s) until the reported SAR is ≤ 1.2 W/kg or all required channels are tested. a) Additional power measurements may be required for this step, which should be limited to those necessary for identifying the subsequent highest output power channels.

6.2.4.3 Initial Test Configuration Procedures

An initial test configuration is determined for OFDM transmission modes according to the channel bandwidth, modulation and data rate combination(s) with the highest maximum output power specified for production units in each standalone and aggregated frequency band. SAR is measured using the highest measured maximum output power channel. For configurations with the same specified or measured maximum output power, additional transmission mode and test channel selection procedures are required. SAR test reduction for subsequent highest output test channels is determined according to *reported* SAR of the initial test configuration.

For next to the ear, hotspot mode and UMC mini-tablet exposure configurations where multiple test positions are required, the initial test position procedure is applied to minimize the number of test positions required for SAR measurement using the initial test configuration transmission mode. For fixed exposure conditions that do not have multiple SAR test positions, SAR is measured in the transmission mode determined by the initial test configuration.

When the *reported* SAR of the initial test configuration is > 0.8 W/kg, SAR measurement is required for subsequent next highest measured output power channel(s) in the initial test configuration until *reported* SAR is ≤ 1.2 W/kg or all required channels are tested.

6.2.4.4 Subsequent Test Configuration Procedures

SAR measurement requirements for the remaining 802.11 transmission mode configurations that have not been tested in the initial test configuration are determined separately for each standalone and aggregated frequency band, in each exposure condition, according to the maximum output power specified for production units. The



initial test position procedure is applied to next to the ear, UMPC mini-tablet and hotspot mode configurations. When the same maximum output power is specified for multiple transmission modes, additional power measurements may be required to determine if SAR measurements are required for subsequent highest output power channels in a subsequent test configuration. The subsequent test configuration and SAR measurement procedures are described in the following.

- 1) . When SAR test exclusion provisions of KDB Publication 447498 are applicable and SAR measurement is not required for the initial test configuration, SAR is also not required for the next highest maximum output power transmission mode subsequent test configuration(s) in that frequency band or aggregated band and exposure configuration.
- 2) . When the highest *reported* SAR for the initial test configuration (when applicable, include subsequent highest output channels), according to the initial test position or fixed exposure position requirements, is adjusted by the ratio of the subsequent test configuration to initial test configuration specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg, SAR is not required for that subsequent test configuration.
- 3) . The number of channels in the initial test configuration and subsequent test configuration can be different due to differences in channel bandwidth. When SAR measurement is required for a subsequent test configuration and the channel bandwidth is smaller than that in the initial test configuration, all channels in the subsequent test configuration that overlap with the larger bandwidth channel tested in the initial test configuration should be used to determine the highest maximum output power channel. This step requires additional power measurement to identify the highest maximum output power channel in the subsequent test configuration to determine SAR test reduction.
 - a) SAR should first be measured for the channel with highest measured output power in the subsequent test configuration.
 - b) SAR for subsequent highest measured maximum output power channels in the subsequent test configuration is required only when the *reported* SAR of the preceding higher maximum output power channel(s) in the subsequent test configuration is > 1.2 W/kg or until all required channels are tested. i) For channels with the same measured maximum output power, SAR should be measured using the channel closest to the center frequency of the larger channel bandwidth channel in the initial test configuration.
- 4) . SAR measurements for the remaining highest specified maximum output power OFDM transmission mode configurations that have not been tested in the initial test configuration (highest maximum output) or subsequent test configuration(s) (subsequent next highest maximum output power) is determined by recursively applying the subsequent test configuration procedures in this section to the remaining configurations according to the following:
 - a) replace "subsequent test configuration" with "next subsequent test configuration" (i.e., subsequent next highest specified maximum output power configuration)
 - b) replace "initial test configuration" with "all tested higher output power configurations"

6.2.4.5 2.4 GHz Wi-Fi SAR Procedures

Separate SAR procedures are applied to DSSS and OFDM configurations in the 2.4 GHz band to simplify DSSS test requirements. For 802.11b DSSS SAR measurements, DSSS SAR procedure applies to fixed exposure test position and initial test position procedure applies to multiple exposure test positions. When SAR measurement is required for an OFDM configuration, the initial test configuration, subsequent test configuration and initial test position procedures are applied. The SAR test exclusion requirements for 802.11g/n OFDM configurations are described in following.

• 802.11b DSSS SAR Test Requirements

SAR is measured for 2.4 GHz 802.11b DSSS using either a fixed test position or, when applicable, the initial test position procedure. SAR test reduction is determined according to the following:

- 1) . When the reported SAR of the highest measured maximum output power channel for the exposure



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

configuration is ≤ 0.8 W/kg, no further SAR testing is required for 802.11b DSSS in that exposure configuration.

- 2) . When the reported SAR is > 0.8 W/kg, SAR is required for that exposure configuration using the next highest measured output power channel. When any reported SAR is > 1.2 W/kg, SAR is required for the third channel; i.e., all channels require testing.

- **2.4 GHz 802.11g/n OFDM SAR Test Exclusion Requirements**

When SAR measurement is required for 2.4 GHz 802.11g/n OFDM configurations, the measurement and test reduction procedures for OFDM are applied (section 5.3, including sub-sections). SAR is not required for the following 2.4 GHz OFDM conditions.

- 1) . When KDB Publication 447498 SAR test exclusion applies to the OFDM configuration.
- 2) . When the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg.

6.2.4.6 5 GHz Wi-Fi SAR Procedures

- **U-NII-1 and U-NII-2A Bands**

For devices that operate in only one of the U-NII-1 and U-NII-2A bands, the normally required SAR procedures for OFDM configurations are applied. For devices that operate in both U-NII bands using the same transmitter and antenna(s), SAR test reduction is determined according to the following:

- 1) When the same maximum output power is specified for both bands, begin SAR measurement in U-NII-2A band by applying the OFDM SAR requirements. If the highest reported SAR for a test configuration is ≤ 1.2 W/kg, SAR is not required for U-NII-1 band for that configuration (802.11 mode and exposure condition); otherwise, both bands are tested independently for SAR.
- 2) When different maximum output power is specified for the bands, begin SAR measurement in the band with higher specified maximum output power. The highest reported SAR for the tested configuration is adjusted by the ratio of lower to higher specified maximum output power for the two bands. When the adjusted SAR is ≤ 1.2 W/kg, SAR is not required for the band with lower maximum output power in that test configuration; otherwise, both bands are tested independently for SAR.
- 3) The two U-NII bands may be aggregated to support a 160 MHz channel on channel number 50. Without additional testing, the maximum output power for this is limited to the lower of the maximum output power certified for the two bands. When SAR measurement is required for at least one of the bands and the highest reported SAR adjusted by the ratio of specified maximum output power of aggregated to standalone band is > 1.2 W/kg, SAR is required for the 160 MHz channel. This procedure does not apply to an aggregated band with maximum output higher than the standalone band(s); the aggregated band must be tested independently for SAR. SAR is not required when the 160 MHz channel is operating at a reduced maximum power and also qualifies for SAR test exclusion.

- **U-NII-2C and U-NII-3 Bands**

The frequency range covered by these bands is 380 MHz (5.47 – 5.85 GHz), which requires a minimum of at least two SAR probe calibration frequency points to support SAR measurements. when Terminal Doppler Weather Radar (TDWR) restriction applies, all channels that operate at 5.60 – 5.65 GHz must be included to apply the SAR test reduction and measurement procedures.

When the same transmitter and antenna(s) are used for U-NII-2C band and U-NII-3 band or 5.8 GHz band of §15.247, the bands may be aggregated to enable additional channels with 20, 40 or 80 MHz bandwidth to span across the band gap, as illustrated in Appendix B. The maximum output power for the additional band gap



channels is limited to the lower of those certified for the bands. Unless band gap channels are permanently disabled, they must be considered for SAR testing. The frequency range covered by these bands is 380 MHz (5.47 – 5.85 GHz), which requires a minimum of at least two SAR probe calibration frequency points to support SAR measurements. To maintain SAR measurement accuracy and to facilitate test reduction, the channels in U-NII-2C band above 5.65 GHz may be grouped with the 5.8 GHz channels in U-NII-3 or §15.247 band to enable two SAR probe calibration frequency points to cover the bands, including the band gap channels. When band gap channels are supported and the bands are not aggregated for SAR testing, band gap channels must be considered independently in each band according to the normally required OFDM SAR measurement and probe calibration frequency points requirements.

• OFDM Transmission Mode SAR Test Configuration and Channel Selection Requirements

The initial test configuration for 5 GHz OFDM transmission modes is determined by the 802.11 configuration with the highest maximum output power specified for production units, including tune-up tolerance, in each standalone and aggregated frequency band. SAR for the initial test configuration is measured using the highest maximum output power channel determined by the default power measurement procedures. When multiple configurations in a frequency band have the same specified maximum output power, the initial test configuration is determined according to the following steps applied sequentially.

- 1) The largest channel bandwidth configuration is selected among the multiple configurations with the same specified maximum output power.
- 2) If multiple configurations have the same specified maximum output power and largest channel bandwidth, the lowest order modulation among the largest channel bandwidth configurations is selected.
- 3) If multiple configurations have the same specified maximum output power, largest channel bandwidth and lowest order modulation, the lowest data rate configuration among these configurations is selected.
- 4) When multiple transmission modes (802.11a/g/n/ac) have the same specified maximum output power, largest channel bandwidth, lowest order modulation and lowest data rate, the lowest order 802.11 mode is selected; i.e., 802.11a is chosen over 802.11n then 802.11ac or 802.11g is chosen over 802.11n. After an initial test configuration is determined, if multiple test channels have the same measured maximum output power, the channel chosen for SAR measurement is determined according to the following. These channel selection procedures apply to both the initial test configuration and subsequent test configuration(s), with respect to the default power measurement procedures or additional power measurements required for further SAR test reduction. The same procedures also apply to subsequent highest output power channel(s) selection.
 - a) The channel closest to mid-band frequency is selected for SAR measurement.
 - b) For channels with equal separation from mid-band frequency; for example, high and low channels or two mid-band channels, the higher frequency (number) channel is selected for SAR measurement.

• SAR Test Requirements for OFDM configurations

When SAR measurement is required for 802.11 a/n/ac OFDM configurations, each standalone and frequency aggregated band is considered separately for SAR test reduction. When the same transmitter and antenna(s) are used for U-NII-1 and U-NII-2A bands, additional SAR test reduction applies. When band gap channels between U-NII-2C band and 5.8 GHz U-NII-3 or §15.247 band are supported, the highest maximum output power transmission mode configuration and maximum output power channel across the bands must be used to determine SAR test reduction, according to the initial test configuration and subsequent test configuration requirements. In applying the initial test configuration and subsequent test configuration procedures, the 802.11 transmission configuration with the highest specified maximum output power and the channel within a test configuration with the highest measured maximum output power should be clearly distinguished to apply the





SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/0 Aug01,2022

Report No.: SZCR230200035201

Page: 38 of 148

procedures.



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch (CMAA) Testing Laboratory

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

Member of the SGS Group (SGS SA)

6.2.5 LTE Test Configuration

LTE modes were tested according to FCC KDB 941225 D05 publication. Please see notes after the tabulated SAR data for required test configurations. Establishing connections with base station simulators ensure a consistent means for testing SAR and are recommended for evaluating SAR [4]. The R&S CMW500 was used for LTE output power measurements and SAR testing. Max power control was used so the UE transmits with maximum output power during SAR testing. SAR must be measured with the maximum TTI (transmit time interval) supported by the device in each LTE configuration.

A) Spectrum Plots for RB Configurations

A properly configured base station simulator was used for SAR tests and power measurements. Therefore, spectrum plots for RB configurations were not required to be included in this report.

B) MPR

MPR is permanently implemented for this device by the manufacturer. The specific manufacturer target MPR is indicated alongside the SAR results. MPR is enabled for this device, according to 3GPP TS36.101 V13.5.0 (201609) Section 6.2.3 – 6.2.5 under Table 6.2.3-1.

Modulation	Channel bandwidth / Transmission bandwidth (N_{RB})						MPR (dB)
	1.4 MHz	3.0 MHz	5 MHz	10 MHz	15 MHz	20 MHz	
QPSK	> 5	> 4	> 8	> 12	> 16	> 18	≤ 1
16 QAM	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	≤ 1
16 QAM	> 5	> 4	> 8	> 12	> 16	> 18	≤ 2

C) A-MPR

A-MPR (Additional MPR) has been disabled for all SAR tests by setting NS=01 on the base station simulator.

D) Largest channel bandwidth standalone SAR test requirements

1) QPSK with 1 RB allocation

Start with the largest channel bandwidth and measure SAR for QPSK with 1 RB allocation, using the RB offset and required test channel combination with the highest maximum output power for RB offsets at the upper edge, middle and lower edge of each required test channel. When the reported SAR is ≤ 0.8 W/kg, testing of the remaining RB offset configurations and required test channels is not required for 1 RB allocation; otherwise, SAR is required for the remaining required test channels and only for the RB offset configuration with the highest output power for that channel. When the reported SAR of a required test channel is > 1.45 W/kg, SAR is required for all three RB offset configurations for that required test channel.

2) QPSK with 50% RB allocation

The procedures required for 1 RB allocation in 1) are applied to measure the SAR for QPSK with 50% RB allocation.

3) QPSK with 100% RB allocation

For QPSK with 100% RB allocation, SAR is not required when the highest maximum output power for 100 % RB allocation is less than the highest maximum output power in 50% and 1 RB allocations and the highest reported SAR for 1 RB and 50% RB allocation in 1) and 2) are ≤ 0.8 W/kg. Otherwise, SAR is measured for the highest output power channel and if the reported SAR is > 1.45 W/kg, the remaining required test channels must also be tested.

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/0 Aug01,2022

Report No.: SZCR230200035201

Page: 40 of 148

4) Higher order modulations

For each modulation besides QPSK; e.g., 16-QAM, 64-QAM, apply the QPSK procedures in above sections to determine the QAM configurations that may need SAR measurement. For each configuration identified as required for testing, SAR is required only when the highest maximum output power for the configuration in the higher order modulation is $> \frac{1}{2}$ dB higher than the same configuration in QPSK or when the reported SAR for the QPSK configuration is > 1.45 W/kg.

E) Other channel bandwidth standalone SAR test requirements

For the other channel bandwidths used by the device in a frequency band, apply all the procedures required for the largest channel bandwidth in section A) to determine the channels and RB configurations that need SAR testing and only measure SAR when the highest maximum output power of a configuration requiring testing in the smaller channel bandwidth is $> \frac{1}{2}$ dB higher than the equivalent channel configurations in the largest channel bandwidth configuration or the reported SAR of a configuration for the largest channel bandwidth is > 1.45 W/kg.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com


No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn
 中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

6.2.6 BluetoothTest Configuration

For the Bluetooth SAR tests, a communication link is set up with the test mode software for BT mode test. Bluetooth USES frequency hopping technology to divide the transmitted data into packets and transmit the packets respectively through 79 designated Bluetooth channels, 1MHz Bandwidth, frequency hops at 1600 hops/second per the Bluetooth standard. The Radio Frequency Channel Number (RFCN) is allocated to 0, 39 and 78 respectively in the case of 2402~2480 MHz during the test at each test frequency channel, the EUT is operated at the RF continuous emission mode.

6.2.6.1 Duty cycle

Bluetooth duty cycle: 78.3%



7 Test Result

7.1 Measurement of RF Conducted Power

7.1.1 Conducted Power Of LTE

LTE Band 2				Conducted Power(dBm)			
Bandwidth	Modulation	RB size	RB offset	Channel	Channel	Channel	Tune up
				18607	18900	19193	
1.4MHz	QPSK	1	0	22.67	22.85	22.8	23.5
	QPSK	1	2	22.75	22.81	22.84	23.5
	QPSK	1	5	22.71	22.83	22.81	23.5
	QPSK	3	0	22.65	22.89	22.82	23
	QPSK	3	2	22.7	22.93	22.87	23
	QPSK	3	3	22.67	22.87	22.85	23
	QPSK	6	0	21.65	21.89	21.79	23
	16QAM	1	0	21.72	21.93	21.94	22.5
	16QAM	1	2	21.71	21.92	21.98	22.5
	16QAM	1	5	21.74	21.88	21.96	22.5
	16QAM	3	0	21.64	22.03	21.79	22.5
	16QAM	3	2	21.75	22.14	21.92	22.5
	16QAM	3	3	21.68	22.04	21.86	22.5
	16QAM	6	0	20.63	20.91	20.88	22.5
Bandwidth	Modulation	RB size	RB offset	Channel	Channel	Channel	Tune up
				18615	18900	19185	
3MHz	QPSK	1	0	22.74	22.95	22.91	23.5
	QPSK	1	7	22.69	22.93	22.89	23.5
	QPSK	1	14	22.63	22.84	22.8	23.5
	QPSK	8	0	21.71	21.93	21.82	23
	QPSK	8	4	21.68	21.91	21.87	23
	QPSK	8	7	21.68	21.9	21.83	23
	QPSK	15	0	21.72	21.9	21.82	23
	16QAM	1	0	22.36	22.12	21.95	22.5
	16QAM	1	7	22.41	22.1	21.87	22.5
	16QAM	1	14	22.26	22	21.77	22.5
	16QAM	8	0	20.89	20.86	20.92	22.5
	16QAM	8	4	20.86	20.89	20.94	22.5
	16QAM	8	7	20.83	20.84	20.91	22.5
	16QAM	15	0	20.78	20.88	20.87	22.5
Bandwidth	Modulation	RB size	RB	Channel	Channel	Channel	Tune up



SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/0 Aug01,2022

Report No.: SZCR230200035201

Page: 43 of 148

			offset				
				18625	18900	19175	
5MHz	QPSK	1	0	22.65	22.99	22.94	23.5
	QPSK	1	13	22.89	22.97	22.94	23.5
	QPSK	1	24	22.74	22.82	22.79	23.5
	QPSK	12	0	21.77	21.96	21.87	23
	QPSK	12	6	21.73	21.92	21.82	23
	QPSK	12	13	21.64	21.89	21.79	23
	QPSK	25	0	21.74	21.96	21.84	23
	16QAM	1	0	21.71	22.24	22.1	22.5
	16QAM	1	13	21.68	22.25	22.05	22.5
	16QAM	1	24	21.66	22.06	21.97	22.5
	16QAM	12	0	20.76	21.03	20.88	22.5
	16QAM	12	6	20.74	20.97	20.82	22.5
	16QAM	12	13	20.66	20.91	20.79	22.5
	16QAM	25	0	20.73	20.91	20.88	22.5
Bandwidth	Modulation	RB size	RB offset	Channel	Channel	Channel	Tune up
				18650	18900	19150	
10MHz	QPSK	1	0	22.73	22.98	22.98	23.5
	QPSK	1	25	22.79	23.07	22.84	23.5
	QPSK	1	49	22.76	22.79	22.59	23.5
	QPSK	25	0	21.67	21.8	21.75	23
	QPSK	25	13	21.73	21.82	21.76	23
	QPSK	25	25	21.62	21.83	21.76	23
	QPSK	50	0	21.71	21.86	21.79	23
	16QAM	1	0	22.49	22.2	21.96	22.5
	16QAM	1	25	22.4	22.19	21.86	22.5
	16QAM	1	49	22.3	22.04	21.63	22.5
	16QAM	25	0	20.72	20.86	20.83	22.5
	16QAM	25	13	20.74	20.9	20.84	22.5
	16QAM	25	25	20.71	20.81	20.9	22.5
	16QAM	50	0	20.71	20.87	20.76	22.5
Bandwidth	Modulation	RB size	RB offset	Channel	Channel	Channel	Tune up
				18675	18900	19125	
15MHz	QPSK	1	0	22.92	23.14	23.12	23.5
	QPSK	1	38	22.7	22.96	22.95	23.5
	QPSK	1	74	22.92	23.1	22.94	23.5
	QPSK	36	0	21.79	21.94	21.91	23
	QPSK	36	18	21.78	21.99	21.83	23
	QPSK	36	39	21.79	21.92	21.85	23
	QPSK	75	0	21.79	21.93	21.91	23



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
 中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/0 Aug01,2022

Report No.: SZCR230200035201

Page: 44 of 148

	16QAM	1	0	22.34	22.26	22.36	22.5
	16QAM	1	38	22.24	22.2	22.37	22.5
	16QAM	1	74	22.41	22.3	22.4	22.5
	16QAM	36	0	20.81	20.92	20.88	22.5
	16QAM	36	18	20.83	20.95	20.87	22.5
	16QAM	36	39	20.81	20.97	20.85	22.5
	16QAM	75	0	20.77	20.95	20.92	22.5
Bandwidth	Modulation	RB size	RB offset	Channel	Channel	Channel	Tune up
				18700	18900	19100	
20MHz	QPSK	1	0	22.91	23.11	23.1	23.5
	QPSK	1	50	22.87	22.95	22.88	23.5
	QPSK	1	99	22.65	22.71	22.68	23.5
	QPSK	50	0	21.88	22	21.98	23
	QPSK	50	25	21.89	21.95	21.93	23
	QPSK	50	50	21.78	21.85	21.78	23
	QPSK	100	0	21.85	21.95	21.93	23
	16QAM	1	0	22.26	22.32	22.44	22.5
	16QAM	1	50	22.17	22.29	22.39	22.5
	16QAM	1	99	22	21.98	22.23	22.5
	16QAM	50	0	20.84	21	20.95	22.5
	16QAM	50	25	20.86	20.98	20.92	22.5
	16QAM	50	50	20.79	20.87	20.85	22.5
	16QAM	100	0	20.89	20.93	20.95	22.5

LTE Band 4				Conducted Power(dBm)			
Bandwidth	Modulation	RB size	RB offset	Channel	Channel	Channel	Tune up
				19957	20175	20393	
1.4MHz	QPSK	1	0	22.5	22.23	22.37	23
		1	2	22.5	22.35	22.42	23
		1	5	22.43	22.35	22.37	23
		3	0	22.41	22.31	22.43	22.5
		3	2	22.43	22.4	22.47	22.5
		3	3	22.49	22.37	22.41	22.5
	16QAM	6	0	21.47	21.35	21.44	22
		1	0	21.62	21.32	21.44	22
		1	2	21.65	21.35	21.49	22
		1	5	21.57	21.41	21.44	22
		3	0	21.45	21.37	21.38	21.5
		3	2	21.49	21.47	21.48	21.5
		3	3	21.43	21.41	21.46	21.5



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Technical Services Laboratory

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.
Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/0 Aug01,2022

Report No.: SZCR230200035201

Page: 45 of 148

Bandwidth	Modulation	6	0	20.47	20.32	20.45	21.5
Bandwidth	Modulation	RB size	RB offset	Channel	Channel	Channel	Tune up
				19965	20175	20385	
3MHz	QPSK	1	0	22.58	22.35	22.51	23
		1	7	22.49	22.39	22.53	23
		1	14	22.42	22.32	22.44	23
		8	0	21.54	21.41	21.45	22
		8	4	21.53	21.39	21.5	22
		8	7	21.47	21.41	21.45	22
		15	0	21.57	21.36	21.45	22
	16QAM	1	0	21.49	21.52	21.51	22
		1	7	21.64	21.57	21.52	22
		1	14	21.67	21.55	21.48	22
		8	0	20.74	20.35	20.55	21
		8	4	20.74	20.36	20.52	21
		8	7	20.64	20.35	20.51	21
		15	0	20.61	20.35	20.51	21
Bandwidth	Modulation	RB size	RB offset	Channel	Channel	Channel	Tune up
Bandwidth	Modulation	RB size	RB offset	19975	20175	20375	Tune up
				19975	20175	20375	
5MHz	QPSK	1	0	22.71	22.42	22.66	23
		1	13	22.61	22.42	22.54	23
		1	24	22.43	22.35	22.45	23
		12	0	21.58	21.38	21.58	22
		12	6	21.5	21.37	21.48	22
		12	13	21.49	21.41	21.42	22
		25	0	21.52	21.39	21.46	22
	16QAM	1	0	21.59	21.73	21.83	22
		1	13	21.46	21.7	21.69	22
		1	24	21.37	21.59	21.59	22
		12	0	20.6	20.39	20.57	21
		12	6	20.55	20.4	20.44	21
		12	13	20.47	20.4	20.43	21
		25	0	20.52	20.38	20.48	21
Bandwidth	Modulation	RB size	RB offset	Channel	Channel	Channel	Tune up
Bandwidth	Modulation	RB size	RB offset	20000	20175	20350	Tune up
				20000	20175	20350	
10MHz	QPSK	1	0	22.89	22.53	22.88	23
		1	25	22.51	22.37	22.73	23
		1	49	22.6	22.67	22.86	23
		25	0	21.58	21.37	21.49	22
		25	13	21.51	21.4	21.55	22
		25	25	21.54	21.46	21.57	22
		50	0	21.58	21.42	21.63	22



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/0 Aug01,2022

Report No.: SZCR230200035201

Page: 46 of 148

		1	0	21.64	21.72	21.83	22
		1	25	21.44	21.57	21.72	22
		1	49	21.75	21.79	21.79	22
	16QAM	25	0	20.65	20.35	20.64	21
		25	13	20.58	20.37	20.63	21
		25	25	20.66	20.44	20.65	21
		50	0	20.59	20.47	20.64	21
Bandwidth	Modulation	RB size	RB offset	Channel	Channel	Channel	Tune up
				20025	20175	20325	
15MHz	QPSK	1	0	22.72	22.45	22.51	23
		1	38	22.49	22.38	22.46	23
		1	74	22.16	22.45	22.36	23
		36	0	21.65	21.38	21.4	22
		36	18	21.53	21.39	21.47	22
		36	39	21.34	21.4	21.41	22
		75	0	21.53	21.42	21.39	22
	16QAM	1	0	21.47	21.55	21.68	22
		1	38	21.69	21.53	21.89	22
		1	74	21.68	21.63	21.75	22
		36	0	20.67	20.41	20.42	21
		36	18	20.59	20.44	20.47	21
		36	39	20.39	20.43	20.4	21
		75	0	20.55	20.44	20.36	21
Bandwidth	Modulation	RB size	RB offset	Channel	Channel	Channel	Tune up
				20050	20175	20300	
20MHz	QPSK	1	0	22.49	22.36	22.29	23
		1	50	22.52	22.65	22.49	23
		1	99	21.94	22.52	22.39	23
		50	0	21.39	21.53	21.38	22
		50	25	21.34	21.35	21.37	22
		50	50	21.28	21.39	21.37	22
		100	0	21.47	21.39	21.39	22
	16QAM	1	0	21.78	21.46	21.89	22
		1	50	21.74	21.54	21.99	22
		1	99	21.32	21.75	21.91	22
		50	0	20.52	20.34	20.37	21
		50	25	20.46	20.39	20.35	21
		50	50	20.33	20.39	20.34	21
		100	0	20.53	20.37	20.41	21

LTE Band 5	Conducted Power(dBm)
------------	----------------------



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/0 Aug01,2022

Report No.: SZCR230200035201

Page: 47 of 148

Bandwidth	Modulation	RB size	RB offset	Channel 20407	Channel 20525	Channel 20643	Tune up
1.4MHz	QPSK	1	0	22.81	22.79	22.7	23.5
		1	2	22.88	22.8	22.76	23.5
		1	5	22.82	22.78	22.7	23.5
		3	0	22.83	22.75	22.82	23
		3	2	22.85	22.88	22.81	23
		3	3	22.8	22.82	22.75	23
	16QAM	6	0	21.85	21.85	21.78	23
		1	0	21.93	21.77	21.7	23
		1	2	22.01	21.77	21.75	23
		1	5	21.92	21.77	21.75	23
		3	0	21.79	21.83	21.97	22.5
		3	2	21.89	21.9	22.02	22.5
		3	3	21.78	21.86	21.95	22.5
		6	0	20.82	20.76	20.76	22.5
Bandwidth	Modulation	RB size	RB offset	Channel 20415	Channel 20525	Channel 20635	Tune up
3MHz	QPSK	1	0	22.85	22.78	22.81	23.5
		1	7	22.84	22.9	22.83	23.5
		1	14	22.82	22.81	22.71	23.5
		8	0	21.84	21.81	21.81	23
		8	4	21.84	21.88	21.83	23
		8	7	21.81	21.83	21.84	23
		15	0	21.85	21.87	21.81	23
	16QAM	1	0	22.49	21.92	21.85	23
		1	7	22.49	22.01	21.85	23
		1	14	22.43	21.92	21.72	23
		8	0	20.99	20.78	20.86	22.5
		8	4	21	20.84	20.87	22.5
		8	7	21	20.78	20.9	22.5
		15	0	20.9	20.86	20.89	22.5
Bandwidth	Modulation	RB size	RB offset	Channel 20425	Channel 20525	Channel 20625	Tune up
5MHz	QPSK	1	0	22.99	22.88	22.94	23.5
		1	13	23	22.93	22.9	23.5
		1	24	22.91	22.87	22.6	23.5
		12	0	21.88	21.85	21.85	23
		12	6	21.89	21.78	21.9	23
		12	13	21.87	21.82	21.79	23
		25	0	21.92	21.9	21.91	23
	16QAM	1	0	21.86	22.13	22.06	23



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Technical Services Laboratory

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No. 1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/0 Aug01,2022

Report No.: SZCR230200035201

Page: 48 of 148

		1	13	21.85	22.17	22.02	23
		1	24	21.81	22.1	21.78	23
		12	0	20.93	20.88	20.82	22.5
		12	6	20.89	20.86	20.88	22.5
		12	13	20.89	20.88	20.77	22.5
		25	0	20.94	20.89	20.87	22.5
Bandwidth	Modulation	RB size	RB offset	Channel	Channel	Channel	Tune up
				20450	20525	20600	
10MHz	QPSK	1	0	23.09	23.1	23.04	23.5
		1	25	22.87	22.91	22.94	23.5
		1	49	23.01	22.96	22.8	23.5
		25	0	22.16	22.32	22.1	22.5
		25	13	21.92	21.93	21.94	23
		25	25	21.97	21.98	21.9	23
		50	0	21.93	21.96	22	23
	16QAM	1	0	22.7	22.12	22.06	23
		1	25	22.49	22.07	21.89	23
		1	49	22.75	21.98	21.57	23
		25	0	20.99	20.86	21	22.5
		25	13	21.02	20.93	21	22.5
		25	25	21.05	20.94	20.97	22.5
		50	0	20.95	20.95	20.97	22.5

LTE Band 7				Conducted Power(dBm)			
Bandwidth	Modulation	RB size	RB offset	Channel	Channel	Channel	Tune up
				20775	21100	21425	
5MHz	QPSK	1	0	23.16	22.98	22.91	23.5
		1	13	23.01	22.93	22.9	23.5
		1	24	22.97	22.89	22.78	23.5
		12	0	22.12	21.95	21.89	23
		12	6	22.14	21.96	21.87	23
		12	13	22	21.9	21.83	23
		25	0	22.09	21.97	21.85	23
	16QAM	1	0	22.05	22.19	22.04	23
		1	13	21.94	22.23	21.95	23
		1	24	21.9	22.15	21.9	23
		12	0	21.14	20.96	20.86	22.5
		12	6	21.12	20.97	20.82	22.5
		12	13	20.99	20.93	20.8	22.5
		25	0	21.12	20.95	20.87	22.5
Bandwidth	Modulation	RB size	RB	Channel	Channel	Channel	Tune up



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
 中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com



SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/0 Aug01,2022

Report No.: SZCR230200035201

Page: 49 of 148

			offset	20800	21100	21400	
10MHz	QPSK	1	0	23.09	22.96	22.84	23.5
		1	25	22.8	22.73	22.64	23.5
		1	49	22.74	22.7	22.46	23.5
		25	0	21.86	21.74	21.72	23
		25	13	21.76	21.73	21.62	23
		25	25	21.83	21.69	21.63	23
		50	0	21.83	21.77	21.67	23
	16QAM	1	0	22.48	22.15	21.95	23
		1	25	22.4	21.94	21.72	23
		1	49	22.35	21.91	21.67	23
		25	0	20.9	20.75	20.85	22.5
		25	13	20.88	20.74	20.71	22.5
		25	25	20.86	20.7	20.68	22.5
		50	0	20.82	20.73	20.67	22.5
Bandwidth	Modulation	RB size	RB offset	Channel 20825	Channel 21100	Channel 21375	Tune up
15MHz	QPSK	1	0	23	22.85	22.79	23.5
		1	38	22.83	22.74	22.68	23.5
		1	74	22.83	22.72	22.57	23.5
		36	0	21.97	21.89	21.75	23
		36	18	21.93	21.83	21.79	23
		36	39	21.86	21.73	21.71	23
		75	0	21.93	21.79	21.77	23
	16QAM	1	0	22.5	22.03	22.16	23
		1	38	22.48	21.93	22.08	23
		1	74	22.39	21.91	22	23
		36	0	21.04	20.86	20.75	22.5
		36	18	20.97	20.85	20.76	22.5
		36	39	20.87	20.74	20.7	22.5
		75	0	20.91	20.81	20.74	22.5
Bandwidth	Modulation	RB size	RB offset	Channel 20850	Channel 21100	Channel 21350	Tune up
20MHz	QPSK	1	0	23.1	22.86	22.86	23.5
		1	50	22.93	22.81	22.67	23.5
		1	99	22.79	22.77	22.61	23.5
		50	0	21.99	21.89	21.8	23
		50	25	21.93	21.84	21.73	23
		50	50	21.86	21.81	21.72	23
		100	0	21.94	21.82	21.72	23
	16QAM	1	0	22.44	22.12	22.46	23
		1	50	22.27	22.1	22.24	23



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Technical Services Laboratory

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.
Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

Member of the SGS Group (SGS SA)



SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/0 Aug01,2022

Report No.: SZCR230200035201

Page: 50 of 148

		1	99	22.15	21.97	22.2	23
		50	0	21.03	20.83	20.79	22.5
		50	25	20.99	20.8	20.72	22.5
		50	50	20.9	20.85	20.71	22.5
		100	0	20.98	20.8	20.73	22.5

LTE FDD Band 12				Conducted Power(dBm)			
Bandwidth	Modulation	RB size	RB offset	Channel	Channel	Channel	Tune up
				23017	23095	23173	
1.4MHz	QPSK	1	0	22.63	22.51	22.75	23.5
		1	2	22.7	22.68	22.83	23.5
		1	5	22.72	22.59	22.79	23.5
		3	0	22.79	22.66	22.87	23
		3	2	22.76	22.62	22.86	23
		3	3	22.73	22.62	22.78	23
		6	0	21.69	21.56	21.82	22.5
	16QAM	1	0	21.88	21.6	21.77	22.5
		1	2	21.9	21.7	21.85	22.5
		1	5	21.87	21.62	21.84	22.5
		3	0	21.77	21.67	22.02	22
		3	2	21.74	21.66	22.03	22
		3	3	21.71	21.6	22	22
		6	0	20.69	20.48	20.85	22
Bandwidth	Modulation	RB size	RB offset	Channel	Channel	Channel	Tune up
				23025	23095	23165	
3MHz	QPSK	1	0	22.78	22.58	22.85	23.5
		1	7	22.7	22.59	22.87	23.5
		1	14	22.64	22.63	22.89	23.5
		8	0	21.77	21.64	21.84	22.5
		8	4	21.72	21.6	21.86	22.5
		8	7	21.78	21.63	21.89	22.5
		15	0	21.7	21.58	21.85	22.5
	16QAM	1	0	22.39	21.85	21.86	22.5
		1	7	22.27	21.83	21.85	22.5
		1	14	22.21	21.75	21.88	22.5
		8	0	20.93	20.61	20.91	21.5
		8	4	20.9	20.6	20.93	21.5
		8	7	20.9	20.6	20.92	21.5
		15	0	20.79	20.61	20.89	21.5
Bandwidth	Modulation	RB size	RB offset	Channel	Channel	Channel	Tune up
				23035	23095	23155	



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Technical Services Laboratory

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

Member of the SGS Group (SGS SA)

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/0 Aug01,2022

Report No.: SZCR230200035201

Page: 51 of 148

5MHz	QPSK	1	0	22.83	22.66	22.81	23.5
		1	13	22.77	22.85	22.92	23.5
		1	24	22.7	22.72	22.88	23.5
		12	0	21.81	21.74	21.76	22.5
		12	6	21.81	21.71	21.8	22.5
		12	13	21.68	21.67	21.79	22.5
		25	0	21.81	21.65	21.81	22.5
	16QAM	1	0	21.72	22.02	21.9	22.5
		1	13	21.61	22.03	22	22.5
		1	24	21.57	22.01	22.02	22.5
		12	0	20.83	20.74	20.76	21.5
		12	6	20.77	20.75	20.78	21.5
		12	13	20.67	20.7	20.8	21.5
		25	0	20.85	20.58	20.81	21.5
Bandwidth	Modulation	RB size	RB offset	Channel 23060	Channel 23095	Channel 23130	Tune up
10MHz	QPSK	1	0	23.01	22.94	22.98	23.5
		1	25	22.63	22.83	22.97	23.5
		1	49	22.84	22.8	22.88	23.5
		25	0	21.91	21.86	21.9	22.5
		25	13	21.78	21.61	21.89	22.5
		25	25	21.75	21.78	21.87	22.5
		50	0	21.77	21.66	21.85	22.5
	16QAM	1	0	22.23	22.22	21.97	22.5
		1	25	22.32	21.99	21.88	22.5
		1	49	22.38	21.97	21.92	22.5
		25	0	20.87	20.77	20.87	21.5
		25	13	20.81	20.71	20.93	21.5
		25	25	20.77	20.74	20.92	21.5
		50	0	20.8	20.66	20.89	21.5

LTE FDD Band 13				Conducted Power(dBm)			
Bandwidth	Modulation	RB size	RB offset	Channel 23205	Channel 23230	Channel 23255	Tune up
5MHz	QPSK	1	0	22.7	22.96	22.99	23.5
		1	13	23	23.08	23.09	23.5
		1	24	22.98	23.01	22.99	23.5
		12	0	21.83	22.08	21.96	23
		12	6	21.88	22.07	22.03	23
		12	13	21.95	22.05	21.92	23
		25	0	21.9	22.07	21.99	23



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/0 Aug01,2022

Report No.: SZCR230200035201

Page: 52 of 148

		1	0	21.64	22.29	22.1	23
		1	13	21.85	22.35	22.13	23
		1	24	21.82	22.27	22.1	23
	16QAM	12	0	20.81	21.07	20.91	22.5
		12	6	20.87	21.07	20.98	22.5
		12	13	20.95	21.06	20.9	22.5
		25	0	20.92	21.04	21.01	22.5
Bandwidth	Modulation	RB size	RB offset	Channel	Channel	Channel	Tune up
				NA	23230	NA	
10MHz	QPSK	1	0	NA	23.15	NA	23.5
		1	25	NA	22.98	NA	23.5
		1	49	NA	23.14	NA	23.5
		25	0	NA	22.13	NA	23
		25	13	NA	22.1	NA	23
		25	25	NA	22.12	NA	23
		50	0	NA	22.12	NA	23
	16QAM	1	0	NA	22.77	NA	23
		1	25	NA	22.66	NA	23
		1	49	NA	22.81	NA	23
		25	0	NA	21.17	NA	22.5
		25	13	NA	21.14	NA	22.5
		25	25	NA	21.16	NA	22.5
		50	0	NA	21.12	NA	22.5

LTE Band 14				Conducted Power(dBm)			
Bandwidth	Modulation	RB size	RB offset	Channel	Channel	Channel	Tune up
				23305	23330	23355	
5MHz	QPSK	1	0	22.59	22.65	22.62	23
		1	13	22.71	22.64	22.72	23
		1	24	22.52	22.54	22.52	23
		12	0	21.59	21.55	21.6	22
		12	6	21.55	21.57	21.61	22
		12	13	21.58	21.56	21.57	22
		25	0	21.61	21.57	21.58	22
	16QAM	1	0	21.49	21.85	21.73	22.5
		1	13	21.59	21.91	21.84	22.5
		1	24	21.37	21.7	21.65	22.5
		12	0	20.61	20.59	20.58	21.5
		12	6	20.52	20.6	20.58	21.5



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Technical Services Laboratory

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com
No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com



SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/0 Aug01,2022

Report No.: SZCR230200035201

Page: 53 of 148

		12	13	20.51	20.59	20.55	21.5
		25	0	20.67	20.53	20.59	21.5
Bandwidth	Modulation	RB size	RB offset	Channel	Channel	Channel	Tune up
				NA	23330	NA	
10MHz	QPSK	1	0	NA	22.84	NA	23
		1	25	NA	22.67	NA	23
		1	49	NA	22.38	NA	23
		25	0	NA	21.68	NA	22
		25	13	NA	21.58	NA	22
		25	25	NA	21.55	NA	22
		50	0	NA	21.67	NA	22
	16QAM	1	0	NA	22.47	NA	22.5
		1	25	NA	22.38	NA	22.5
		1	49	NA	22.11	NA	22.5
		25	0	NA	20.77	NA	21.5
		25	13	NA	20.62	NA	21.5
		25	25	NA	20.65	NA	21.5
		50	0	NA	20.65	NA	21.5

LTE FDD Band 17				Conducted Power(dBm)			
Bandwidth	Modulation	RB size	RB offset	Channel	Channel	Channel	Tune up
				23755	23790	23825	
5MHz	QPSK	1	0	22.68	22.67	22.93	23
		1	13	22.79	22.73	23	23
		1	24	22.83	22.73	22.91	23
		12	0	21.69	21.64	21.84	22
		12	6	21.69	21.74	21.88	22
		12	13	21.79	21.75	21.9	22
		25	0	21.75	21.8	21.97	22
	16QAM	1	0	21.57	21.87	22.04	22.5
		1	13	21.7	21.98	22.07	22.5
		1	24	21.73	21.93	22.04	22.5
		12	0	20.71	20.68	20.82	21.5
		12	6	20.72	20.8	20.9	21.5
		12	13	20.78	20.8	20.9	21.5
		25	0	20.71	20.74	20.97	21.5
Bandwidth	Modulation	RB size	RB offset	Channel	Channel	Channel	Tune up
				23780	23790	23800	
10MHz	QPSK	1	0	22.89	22.91	22.95	23
		1	25	22.69	22.9	22.81	23



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Technical Services Laboratory

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

Member of the SGS Group (SGS SA)



SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/0 Aug01,2022

Report No.: SZCR230200035201

Page: 54 of 148

		1	49	22.63	22.68	22.87	23
		25	0	21.75	21.76	21.73	22
		25	13	21.63	21.76	21.79	22
		25	25	21.77	21.83	21.93	22
		50	0	21.8	21.81	21.8	22
	16QAM	1	0	22.36	21.98	21.95	22.5
		1	25	22.42	22.13	21.91	22.5
		1	49	22.33	21.76	21.85	22.5
		25	0	20.82	20.79	20.83	21.5
		25	13	20.73	20.8	20.85	21.5
		25	25	20.87	20.79	20.92	21.5
		50	0	20.79	20.74	20.8	21.5

LTE Band 25				Conducted Power(dBm)			
Bandwidth	Modulation	RB size	RB offset	Channel	Channel	Channel	Tune up
				26047	26365	26683	
1.4MHz	QPSK	1	0	22.72	22.73	22.68	23
		1	2	22.76	22.75	22.6	23
		1	5	22.75	22.73	22.61	23
		3	0	22.47	22.39	22.39	22.5
		3	2	22.49	22.41	22.44	22.5
		3	3	22.41	22.36	22.35	22.5
	16QAM	6	0	21.77	21.68	21.67	22.5
		1	0	21.89	21.74	21.69	22.5
		1	2	21.94	21.75	21.67	22.5
		1	5	21.9	21.81	21.71	22.5
		3	0	21.49	21.42	21.45	21.5
		3	2	21.49	21.44	21.43	21.5
		3	3	21.5	21.38	21.23	21.5
		6	0	20.8	20.62	20.69	21.5
Bandwidth	Modulation	RB size	RB offset	Channel	Channel	Channel	Tune up
				26055	26365	26675	
3MHz	QPSK	1	0	22.77	22.75	22.78	23
		1	7	22.76	22.79	22.87	23
		1	14	22.67	22.7	22.62	23
		8	0	21.81	21.78	21.73	22.5
		8	4	21.81	21.77	21.76	22.5
		8	7	21.69	21.77	21.72	22.5
		15	0	21.83	21.72	21.77	22.5
	16QAM	1	0	21.98	21.77	22.4	22.5
		1	7	22.05	21.73	22.37	22.5



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/0 Aug01,2022

Report No.: SZCR230200035201

Page: 55 of 148

		1	14	21.86	21.73	22.16	22.5
		8	0	20.79	20.84	20.89	21.5
		8	4	20.81	20.75	20.93	21.5
		8	7	20.69	20.82	20.88	21.5
		15	0	20.8	20.72	20.78	21.5
Bandwidth	Modulation	RB size	RB offset	Channel	Channel	Channel	Tune up
				26065	26365	26665	
5MHz	QPSK	1	0	22.95	22.84	22.89	23
		1	13	22.8	22.8	22.84	23
		1	24	22.75	22.75	22.64	23
		12	0	21.86	21.79	21.81	22.5
		12	6	21.77	21.73	21.79	22.5
		12	13	21.76	21.72	21.76	22.5
		25	0	21.81	21.75	21.79	22.5
	16QAM	1	0	21.81	22.08	22.1	22.5
		1	13	21.78	22.04	22.05	22.5
		1	24	21.69	22	21.78	22.5
		12	0	20.86	20.8	20.81	21.5
		12	6	20.78	20.79	20.76	21.5
		12	13	20.75	20.72	20.73	21.5
		25	0	20.77	20.7	20.79	21.5
Bandwidth	Modulation	RB size	RB offset	Channel	Channel	Channel	Tune up
				26090	26365	26640	
10MHz	QPSK	1	0	22.94	22.9	22.97	23
		1	25	22.71	22.88	22.74	23
		1	49	22.8	22.8	22.73	23
		25	0	21.78	21.7	21.78	22.5
		25	13	21.76	21.73	21.78	22.5
		25	25	21.79	21.79	21.8	22.5
		50	0	21.74	21.74	21.84	22.5
	16QAM	1	0	22.55	22.09	21.94	22.5
		1	25	22.3	21.92	21.85	22.5
		1	49	22.32	22.02	21.75	22.5
		25	0	20.83	20.73	20.88	21.5
		25	13	20.78	20.73	20.85	21.5
		25	25	20.83	20.77	20.88	21.5
		50	0	20.73	20.71	20.84	21.5
Bandwidth	Modulation	RB size	RB offset	Channel	Channel	Channel	Tune up
				26115	26365	26615	
15MHz	QPSK	1	0	22.77	22.93	22.95	23
		1	38	22.57	22.87	22.8	23
		1	74	22.73	22.9	22.82	23



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Inspection & Testing Services Laboratory

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No. 1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/0 Aug01,2022

Report No.: SZCR230200035201

Page: 56 of 148

		36	0	21.66	21.88	21.97	22.5
		36	18	21.76	21.94	21.86	22.5
		36	39	21.81	21.98	22	22.5
		75	0	21.71	21.95	22.02	22.5
	16QAM	1	0	22.38	22.08	22.35	22.5
		1	38	22.18	22.01	22.34	22.5
		1	74	22.3	22.1	22.32	22.5
		36	0	20.7	20.87	20.96	21.5
		36	18	20.79	20.93	20.84	21.5
		36	39	20.83	20.99	20.99	21.5
		75	0	20.7	20.95	20.95	21.5
Bandwidth	Modulation	RB size	RB offset	Channel	Channel	Channel	Tune up
				26140	26365	26590	
20MHz	QPSK	1	0	22.56	22.97	22.76	23
		1	50	22.67	22.99	22.77	23
		1	99	22.52	22.74	22.57	23
		50	0	21.72	21.77	21.74	22.5
		50	25	21.73	21.9	21.82	22.5
		50	50	21.67	21.84	21.79	22.5
		100	0	21.72	21.82	22	22.5
	16QAM	1	0	22.11	22.18	22.66	22.5
		1	50	21.99	22.26	22.5	22.5
		1	99	21.76	21.91	22.25	22.5
		50	0	20.66	20.76	20.93	21.5
		50	25	20.67	20.85	20.8	21.5
		50	50	20.69	20.89	20.78	21.5
		100	0	20.75	20.8	21.01	21.5

LTE Band 26a(814-824MHz)				Conducted Power(dBm)			
Bandwidth	Modulation	RB size	RB offset	Channel	Channel	Channel	Tune up
				26697	26740	26783	
1.4MHz	QPSK	1	0	22.7	22.71	22.68	23.5
		1	2	22.79	22.85	22.73	23.5
		1	5	22.77	22.84	22.69	23.5
		3	0	22.84	22.84	22.73	23
		3	2	22.83	22.87	22.73	23
		3	3	22.81	22.81	22.7	23
		6	0	21.82	21.86	21.71	23
	16QAM	1	0	21.95	21.85	21.66	22.5
		1	2	21.84	22.03	21.86	22.5



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/0 Aug01,2022

Report No.: SZCR230200035201

Page: 57 of 148

		1	5	21.85	21.87	21.86	22.5
		3	0	21.8	21.89	21.8	22
		3	2	22.06	21.9	21.79	22
		3	3	21.88	22.06	21.72	22
		6	0	20.79	20.75	20.67	22
Bandwidth	Modulation	RB size	RB offset	Channel	Channel	Channel	Tune up
				26705	26740	26775	
3MHz	QPSK	1	0	22.83	22.75	22.82	23.5
		1	7	22.86	22.77	22.81	23.5
		1	14	22.71	22.83	22.7	23.5
		8	0	21.78	21.85	21.71	22
		8	4	21.76	21.85	21.74	22
		8	7	21.71	21.9	21.72	22
		15	0	21.75	21.89	21.74	22
	16QAM	1	0	21.93	21.92	21.84	22.5
		1	7	22.4	22.4	21.89	22.5
		1	14	21.77	21.77	22.26	22.5
		8	0	20.82	20.76	20.76	21.5
		8	4	20.76	20.97	20.69	21.5
		8	7	20.94	20.81	20.89	21.5
		15	0	20.79	20.77	20.73	21.5
Bandwidth	Modulation	RB size	RB offset	Channel	Channel	Channel	Tune up
				26715	26740	26765	
5MHz	QPSK	1	0	22.86	22.83	22.86	23.5
		1	13	22.83	22.84	22.82	23.5
		1	24	22.81	22.87	22.75	23.5
		12	0	21.79	21.86	21.82	22
		12	6	21.83	21.81	21.71	22
		12	13	21.82	21.81	21.71	22
		25	0	21.79	21.82	21.74	22
	16QAM	1	0	21.97	22.1	22.14	22.5
		1	13	22.1	21.73	21.66	22.5
		1	24	21.95	21.93	21.87	22.5
		12	0	20.83	20.84	20.83	21.5
		12	6	20.84	20.8	20.75	21.5
		12	13	20.76	20.77	20.69	21.5
		25	0	20.78	20.83	20.71	21.5
Bandwidth	Modulation	RB size	RB offset	Channel	Channel	Channel	Tune up
					26740		
10MHz	QPSK	1	0	/	23.06	/	23.5
		1	25	/	22.88	/	23.5
		1	49	/	22.95	/	23.5



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Inspection & Testing Laboratory

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No. 1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/0 Aug01,2022

Report No.: SZCR230200035201

Page: 58 of 148

		25	0	/	21.93	/	22
		25	13	/	21.96	/	22
		25	25	/	21.89	/	22
		50	0	/	21.88	/	22
	16QAM	1	0	/	22.17	/	22.5
		1	25	/	22.4	/	22.5
		1	49	/	21.93	/	22.5
		25	0	/	20.88	/	21.5
		25	13	/	20.88	/	21.5
		25	25	/	20.93	/	21.5
		50	0	/	20.9	/	21.5

LTE Band 26b(824-849MHz)				Conducted Power(dBm)			
Bandwidth	Modulation	RB size	RB offset	Channel	Channel	Channel	Tune up
				26797	26915	27033	
1.4MHz	QPSK	1	0	22.74	22.83	22.51	23.5
		1	2	22.82	22.85	22.51	23.5
		1	5	22.76	22.81	22.52	23.5
		3	0	22.79	22.86	22.57	23
		3	1	22.8	22.87	22.54	23
		3	3	22.74	22.82	22.52	23
	16QAM	6	0	21.8	21.86	21.55	22.5
		1	0	21.81	21.85	21.56	22.5
		1	2	21.98	21.92	21.58	22.5
		1	5	21.81	21.93	21.55	22.5
		3	0	21.33	21.45	21.48	21.5
		3	1	21.36	21.36	21.49	21.5
		3	3	21.38	21.34	21.39	21.5
		6	0	20.77	20.71	20.52	21.5
Bandwidth	Modulation	RB size	RB offset	Channel	Channel	Channel	Tune up
				26805	26915	27025	
3MHz	QPSK	1	0	22.74	22.82	22.65	23.5
		1	7	22.75	22.86	22.56	23.5
		1	14	22.71	22.8	22.53	23.5
		8	0	21.69	21.9	21.65	22.5
		8	4	21.75	21.91	21.64	22.5
		8	7	21.75	21.84	21.62	22.5
		15	0	21.75	21.82	21.64	22.5
	16QAM	1	0	21.74	21.9	22.18	22.5
		1	7	21.81	21.95	21.61	22.5



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Technical Services Laboratory

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.
Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com
No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

Member of the SGS Group (SGS SA)



SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/0 Aug01,2022

Report No.: SZCR230200035201

Page: 59 of 148

		1	14	21.87	22.35	21.7	22.5
		8	0	20.87	20.88	20.79	21.5
		8	4	20.8	20.81	20.72	21.5
		8	7	20.7	20.91	20.59	21.5
		15	0	20.74	20.86	20.65	21.5
Bandwidth	Modulation	RB size	RB offset	Channel	Channel	Channel	Tune up
				26815	26915	27015	
5MHz	QPSK	1	0	22.85	22.86	22.75	23.5
		1	13	22.84	22.83	22.72	23.5
		1	24	22.83	22.76	22.59	23.5
		12	0	21.75	21.9	21.74	22.5
		12	6	21.77	21.84	21.68	22.5
		12	13	21.78	21.83	21.63	22.5
		25	0	21.82	21.82	21.69	22.5
	16QAM	1	0	21.69	22	21.89	22.5
		1	13	22.11	22.09	21.98	22.5
		1	24	21.68	21.64	21.47	22.5
		12	0	20.76	20.86	20.74	21.5
		12	6	20.79	20.86	20.75	21.5
		12	13	20.78	20.88	20.65	21.5
		25	0	20.81	20.86	20.69	21.5
Bandwidth	Modulation	RB size	RB offset	Channel	Channel	Channel	Tune up
				26840	26915	26990	
10MHz	QPSK	1	0	23.08	22.99	23.09	23.5
		1	25	22.88	22.73	22.71	23.5
		1	49	23.12	22.97	22.71	23.5
		25	0	21.84	21.89	21.81	22.5
		25	13	21.84	21.82	21.77	22.5
		25	25	21.84	21.97	21.69	22.5
		50	0	21.87	21.88	21.82	22.5
	16QAM	1	0	21.99	22.02	22.68	22.5
		1	25	21.83	21.96	22.46	22.5
		1	49	22.1	21.39	22.32	22.5
		25	0	20.9	20.97	20.91	21.5
		25	13	20.93	20.86	20.81	21.5
		25	25	20.92	20.99	20.8	21.5
		50	0	20.87	20.86	20.77	21.5
Bandwidth	Modulation	RB size	RB offset	Channel	Channel	Channel	Tune up
				26865	26915	26965	
15MHz	QPSK	1	0	23.05	23.12	23.07	23.5



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Inspection & Testing Laboratory

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com
No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

Member of the SGS Group (SGS SA)



SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/0 Aug01,2022

Report No.: SZCR230200035201

Page: 60 of 148

		1	38	22.77	22.79	22.74	23.5
		1	74	23.09	23.16	23.08	23.5
		36	0	22.05	22.09	22.08	22.5
		36	18	21.99	21.86	21.88	22.5
		36	39	21.85	21.69	21.72	22.5
		75	0	22.01	21.82	21.82	22.5
		75	0	21	20.82	20.82	21.5
	16QAM	1	0	22.33	22.27	22.5	22.5
		1	38	22.35	21.97	22.16	22.5
		1	74	22.38	22.4	22.43	22.5
		36	0	21.19	21.04	21.09	21.5
		36	18	20.98	20.82	20.91	21.5
		36	39	20.9	20.69	20.69	21.5
		75	0	21	20.82	20.82	21.5

LTE Band 41				Conducted Power(dBm)					
Bandwidth	Modulation	RB size	RB offset	Channel	Channel	Channel	Channel	Channel	Tune up
				39675	40148	40620	41093	41565	
5MHz	QPSK	1	0	22.79	22.76	23	22.82	22.93	23.5
		1	13	22.63	22.55	22.81	22.58	22.89	23.5
		1	24	22.62	22.52	22.86	22.58	22.79	23.5
		12	0	21.72	21.76	21.86	21.7	21.84	22.5
		12	6	21.75	21.74	21.89	21.68	21.79	22.5
		12	13	21.67	21.68	21.84	21.68	21.78	22.5
		25	0	21.68	21.72	21.82	21.77	21.78	22.5
	16QAM	1	0	21.9	21.95	22.19	21.87	22	22.5
		1	13	21.89	21.81	22.13	21.95	21.89	22.5
		1	24	21.53	21.6	21.86	21.5	21.79	22.5
		12	0	20.74	20.77	20.87	20.78	20.84	21.5
		12	6	20.74	20.78	20.83	20.64	20.81	21.5
		12	13	20.66	20.76	20.77	20.58	20.69	21.5
		25	0	20.72	20.63	20.79	20.77	20.8	21.5
Bandwidth	Modulation	RB size	RB offset	Channel	Channel	Channel	Channel	Channel	Tune up
				39700	40160	40620	41080	41540	
10MHz	QPSK	1	0	22.9	22.84	23.07	22.92	23.1	23.5
		1	25	22.74	22.7	22.87	22.73	22.86	23.5
		1	49	22.43	22.49	22.55	22.35	22.81	23.5
		25	0	21.76	21.74	21.94	21.66	21.81	22.5
		25	13	21.64	21.71	21.87	21.71	21.78	22.5
		25	25	21.63	21.73	21.8	21.57	21.74	22.5
		50	0	21.67	21.6	21.86	21.69	21.74	22.5
	16QAM	1	0	21.79	21.81	21.9	21.83	21.78	22.5



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Inspection & Testing Laboratory

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.
Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com
No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

Member of the SGS Group (SGS SA)



SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/0 Aug01,2022

Report No.: SZCR230200035201

Page: 61 of 148

		1	25	21.88	21.84	21.78	21.9	21.52	22.5
		1	49	21.49	21.46	21.58	21.42	21.42	22.5
		25	0	20.76	20.71	20.89	20.82	20.8	21.5
		25	13	20.65	20.62	20.84	20.62	20.74	21.5
		25	25	20.61	20.68	20.8	20.59	20.77	21.5
		50	0	20.67	20.72	20.86	20.62	20.75	21.5
Bandwidth	Modulation	RB size	RB offset	Channel 39725	Channel 40173	Channel 40620	Channel 41068	Channel 41515	Tune up
15MHz	QPSK	1	0	22.67	22.67	22.89	22.76	22.75	23.5
		1	38	22.59	22.58	22.71	22.58	22.81	23.5
		1	74	22.44	22.51	22.61	22.52	22.58	23.5
		36	0	21.65	21.62	21.8	21.61	21.77	22.5
		36	18	21.66	21.75	21.82	21.6	21.77	22.5
		36	39	21.58	21.55	21.76	21.51	21.69	22.5
		75	0	21.59	21.64	21.76	21.59	21.79	22.5
	16QAM	1	0	21.77	21.81	21.63	21.82	21.92	22.5
		1	38	21.38	21.41	21.61	21.36	22.14	22.5
		1	74	21.33	21.28	21.41	21.4	21.46	22.5
		36	0	20.63	20.58	20.78	20.65	20.69	21.5
		36	18	20.57	20.65	20.72	20.6	20.79	21.5
		36	39	20.5	20.53	20.71	20.54	20.68	21.5
		75	0	20.58	20.68	20.78	20.59	20.75	21.5
Bandwidth	Modulation	RB size	RB offset	Channel 39750	Channel 40185	Channel 40620	Channel 41055	Channel 41490	Tune up
20MHz	QPSK	1	0	22.73	22.69	22.93	22.82	22.83	23.5
		1	50	22.59	22.52	22.82	22.68	22.72	23.5
		1	99	22.23	22.24	22.44	22.22	22.67	23.5
		50	0	21.64	21.7	21.78	21.63	21.73	22.5
		50	25	21.63	21.66	21.71	21.7	21.68	22.5
		50	50	21.53	21.6	21.71	21.58	21.71	22.5
		100	0	21.61	21.56	21.75	21.64	21.73	22.5
	16QAM	1	0	21.76	21.68	21.64	21.76	21.94	22.5
		1	50	21.62	21.61	21.56	21.57	21.24	22.5
		1	99	21.5	21.5	21.79	21.41	21.78	22.5
		50	0	20.65	20.68	20.88	20.63	20.77	21.5
		50	25	20.6	20.53	20.78	20.62	20.64	21.5
		50	50	20.51	20.6	20.69	20.45	20.7	21.5
		100	0	20.55	20.47	20.76	20.48	20.66	21.5

LTE Band 66				Conducted Power(dBm)			
Bandwidth	Modulation	RB size	RB offset	Channel 131979	Channel 132322	Channel 132665	Tune up



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing/inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
 中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

Member of the SGS Group (SGS SA)

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/0 Aug01,2022

Report No.: SZCR230200035201

Page: 62 of 148

1.4MHz	QPSK	1	0	22.55	22.54	22.73	23
		1	2	22.56	22.59	22.81	23
		1	5	22.46	22.48	22.68	23
		3	0	22.46	22.5	22.46	22.5
		3	1	22.48	22.5	22.41	22.5
		3	3	22.49	22.47	22.45	22.5
		6	0	21.55	21.48	21.66	22
	16QAM	1	0	21.67	21.45	21.64	22
		1	2	21.72	21.45	21.71	22
		1	5	21.63	21.44	21.64	22
		3	0	21.61	21.44	21.78	22
		3	1	21.67	21.47	21.86	22
		3	3	21.63	21.43	21.83	22
		6	0	20.53	20.52	20.66	21
Bandwidth	Modulation	RB size	RB offset	Channel 131987	Channel 132322	Channel 132657	Tune up
3MHz	QPSK	1	0	22.63	22.57	22.72	23
		1	7	22.54	22.6	22.72	23
		1	14	22.42	22.57	22.67	23
		8	0	21.62	21.54	21.7	22
		8	4	21.59	21.58	21.72	22
		8	7	21.53	21.56	21.65	22
		15	0	21.61	21.53	21.71	22
	16QAM	1	0	21.78	21.51	21.94	22
		1	7	21.67	21.55	21.95	22
		1	14	21.59	21.53	21.89	22
		8	0	20.63	20.57	20.74	21
		8	4	20.58	20.59	20.69	21
		8	7	20.54	20.54	20.66	21
		15	0	20.46	20.58	20.64	21
Bandwidth	Modulation	RB size	RB offset	Channel 131997	Channel 132322	Channel 132647	Tune up
5MHz	QPSK	1	0	22.79	22.66	22.7	23
		1	13	22.7	22.58	22.68	23
		1	24	22.65	22.57	22.63	23
		12	0	21.75	21.59	21.69	22
		12	6	21.63	21.55	21.71	22
		12	13	21.66	21.56	21.65	22
		25	0	21.67	21.56	21.69	22
	16QAM	1	0	21.86	21.83	21.96	22



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Technical Services Laboratory

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.
Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com
No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/0 Aug01,2022

Report No.: SZCR230200035201

Page: 63 of 148

		1	13	21.95	21.77	21.96	22
		1	24	21.84	21.73	21.96	22
		12	0	20.74	20.52	20.74	21
		12	6	20.65	20.52	20.7	21
		12	13	20.67	20.53	20.71	21
		25	0	20.64	20.53	20.71	21
Bandwidth	Modulation	RB size	RB offset	Channel	Channel	Channel	Tune up
				132022	132322	132622	
10MHz	QPSK	1	0	22.14	22.09	22.02	23
		1	25	22.63	22.57	22.65	23
		1	49	22.77	23.01	23.04	23
		25	0	21.62	21.53	21.57	22
		25	13	21.67	21.63	21.67	22
		25	25	21.73	21.73	21.74	22
		50	0	21.65	21.56	21.69	22
	16QAM	1	0	21.39	21.14	20.85	22
		1	25	21.8	21.67	21.43	22
		1	49	21.88	22.04	21.79	22
		25	0	20.68	20.59	20.52	21
		25	13	20.78	20.64	20.71	21
		25	25	20.8	20.76	20.71	21
		50	0	20.7	20.58	20.69	21
Bandwidth	Modulation	RB size	RB offset	Channel	Channel	Channel	Tune up
				132047	132322	132597	
15MHz	QPSK	1	0	22.86	22.94	22.87	23
		1	38	22.64	22.59	22.41	23
		1	74	22.35	22.75	22.63	23
		36	0	21.78	21.61	21.52	22
		36	18	21.66	21.53	21.42	22
		36	39	21.49	21.46	21.37	22
		75	0	21.68	21.51	21.46	22
	16QAM	1	0	21.69	21.99	21.82	22
		1	38	21.85	21.62	21.44	22
		1	74	21.51	21.88	21.66	22
		36	0	20.79	20.58	20.54	21
		36	18	20.64	20.47	20.43	21
		36	39	20.47	20.44	20.41	21
		75	0	20.66	20.48	20.5	21
Bandwidth	Modulation	RB size	RB offset	Channel	Channel	Channel	Tune up
				132072	132322	132572	



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Technical Services Laboratory

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.
Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com
No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com



SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/0 Aug01,2022

Report No.: SZCR230200035201

Page: 64 of 148

20MHz	QPSK	1	0	22.61	22.54	22.51	23
		1	50	22.44	22.7	22.44	23
		1	99	21.98	22.89	22.63	23
		50	0	21.44	21.45	21.47	22
		50	25	21.42	21.48	21.46	22
		50	50	21.49	21.56	21.48	22
		100	0	21.56	21.55	21.5	22
	16QAM	1	0	21.76	21.32	21.24	22
		1	50	21.69	21.45	21.11	22
		1	99	21.19	21.75	21.35	22
		50	0	20.57	20.42	20.53	21
		50	25	20.51	20.47	20.49	21
		50	50	20.57	20.52	20.52	21
		100	0	20.56	20.54	20.54	21



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Technical Services Laboratory

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

Member of the SGS Group (SGS SA)

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/0 Aug01,2022

Report No.: SZCR230200035201

Page: 65 of 148

LTE Band 71				Conducted Power(dBm)			
Bandwidth	Modulation	RB size	RB offset	Channel	Channel	Channel	Tune up
				133147	133297	133447	
5MHz	QPSK	1	0	23	23.06	22.91	23.5
		1	13	23.08	22.97	22.88	23.5
		1	24	22.86	22.92	22.72	23.5
		12	0	22	22.05	21.95	22.5
		12	6	22.01	22.01	21.92	22.5
		12	13	21.91	22.04	21.9	22.5
		25	0	22	22.04	21.91	22.5
	16QAM	1	0	22.21	22.24	22.12	22.5
		1	13	22.42	22.2	22.14	22.5
		1	24	22.12	22.18	22.02	22.5
		12	0	21.02	21.03	20.96	21.5
		12	6	20.99	20.93	21	21.5
		12	13	20.9	20.95	20.91	21.5
		25	0	21	20.98	20.9	21.5
Bandwidth	Modulation	RB size	RB offset	Channel	Channel	Channel	Tune up
				133172	133297	133422	
10MHz	QPSK	1	0	23.44	23.36	23.22	23.5
		1	25	23.25	23.09	22.94	23.5
		1	49	23.16	23.01	22.64	23.5
		25	0	22.27	22.12	21.99	22.5
		25	13	22.2	22.06	21.93	22.5
		25	25	22.07	21.98	21.89	22.5
		50	0	22.23	22.1	21.99	22.5
	16QAM	1	0	22.39	22.52	22.36	22.5
		1	25	22.08	22.13	22.09	22.5
		1	49	21.97	22.19	21.67	22.5
		25	0	21.2	21.24	21.01	21.5
		25	13	21.17	21.1	20.99	21.5
		25	25	21.03	21.09	20.89	21.5
		50	0	21.19	21.08	20.96	21.5



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
 中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/0 Aug01,2022

Report No.: SZCR230200035201

Page: 66 of 148

Bandwidth	Modulation	RB size	RB offset	Channel	Channel	Channel	Tune up
				133197	133297	133397	
15MHz	QPSK	1	0	23.32	23.35	23.36	23.5
		1	38	22.83	22.79	22.81	23.5
		1	74	23.02	22.9	22.77	23.5
		36	0	22.26	22.21	22.2	22.5
		36	18	21.98	21.89	21.88	22.5
		36	39	21.88	21.8	21.75	22.5
		75	0	22.08	22.02	21.89	22.5
	16QAM	1	0	22.45	22.43	22.43	22.5
		1	38	22.04	21.95	21.93	22.5
		1	74	22.21	22.01	21.75	22.5
		36	0	21.27	21.19	21.17	21.5
		36	18	21	20.88	20.86	21.5
		36	39	20.85	20.84	20.76	21.5
		75	0	21.07	20.94	20.93	21.5
Bandwidth	Modulation	RB size	RB offset	Channel	Channel	Channel	Tune up
				133222	133297	133372	
20MHz	QPSK	1	0	22.94	23	22.92	23.5
		1	50	22.75	22.83	22.71	23.5
		1	99	22.58	22.59	22.54	23.5
		50	0	22.29	22.39	22.17	22.5
		50	25	22	21.91	21.89	22.5
		50	50	21.79	21.84	21.75	22.5
		100	0	22.01	22.03	21.89	22.5
	16QAM	1	0	22.09	21.78	21.76	22.5
		1	50	21.91	21.68	21.44	22.5
		1	99	21.74	21.42	21.39	22.5
		50	0	21.32	21.17	21.14	21.5
		50	25	20.92	20.86	20.84	21.5
		50	50	20.78	20.81	20.74	21.5
		100	0	21.06	21.02	20.88	21.5

7.1.2 Conducted Power Of Wi-Fi

Mode	Channel	Frequency(MHz)	Data Rate(Mbps)	Average Power (dBm)	Tune up
802.11b	1	2412	1	16.32	17
	6	2437		16.39	17
	11	2462		16.48	17
802.11g	1	2412	6	15.00	16
	6	2437		15.09	16
	11	2462		15.15	16
802.11n HT20 SISO	1	2412	6.5	14.76	15
	6	2437		14.78	15
	11	2462		14.80	15
802.11nHT40 SISO	3	2422	13.5	14.87	16
	6	2437		15.25	16
	9	2452		15.13	16

Note:

- Power must be measured at each transmit antenna port according to the DSSS and OFDM transmission configurations in each standalone and aggregated frequency band.
- Power measurement is required for the transmission mode configuration with the highest maximum output power specified for production units.
 - When the same highest maximum output power specification applies to multiple transmission modes, the largest channel bandwidth configuration with the lowest order modulation and lowest data rate is measured.
 - When the same highest maximum output power is specified for multiple largest channel bandwidth configurations with the same lowest order modulation or lowest order modulation and lowest data rate, power measurement is required for all equivalent 802.11 configurations with the same maximum output power.
- For each transmission mode configuration, power must be measured for the highest and lowest channels; and at the mid-band channel(s) when there are at least 3 channels. For configurations with multiple mid-band channels, due to an even number of channels, both channels should be measured.





SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/0 Aug01,2022

Report No.: SZCR230200035201

Page: 68 of 148

5GHz	mode	Channel	Frequency(MHz)	Data Rate(Mbps)	Average Power (dBm)	Tune up
802.11a	U-NII-1	36	5180	6	14.42	15
		40	5200		14.61	15
		48	5240		14.39	15
	U-NII-2A	52	5260		14.57	15
		60	5300		14.64	15
		64	5320		14.62	15
	U-NII-2C	100	5500		14.2	16
		116	5580		14.45	16
		140	5700		15.35	16
	U-NII-3	149	5745		15.21	16
		157	5785		14.87	16
		165	5825		14.84	16
5GHz	mode	Channel	Frequency(MHz)	Data Rate(Mbps)	Average Power (dBm)	Tune up
802.11n-HT20	U-NII-1	36	5180	MCS0	14.64	15
		40	5200		14.68	15
		48	5240		14.1	15
	U-NII-2A	52	5260		14.62	15
		60	5300		14.7	15
		64	5320		13.92	15
	U-NII-2C	100	5500		14.23	15
		116	5580		14.49	15
		140	5700		14.01	15
	U-NII-3	149	5745		15.28	16
		157	5785		14.9	16
		165	5825		14.33	16
5GHz	mode	Channel	Frequency(MHz)	Data Rate(Mbps)	Average Power (dBm)	Tune up
802.11n-HT40	U-NII-1	38	5190	MCS0	13.23	14
		46	5230		15.18	16
	U-NII-2A	54	5270		15.52	16
		62	5310		15.26	16
	U-NII-2C	102	5510		15.77	16
		110	5550		15.04	16
		134	5670		15.75	16
	U-NII-3	151	5755		15.41	16
		159	5795		15.34	16



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Technical Services Laboratory

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

Member of the SGS Group (SGS SA)

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/0 Aug01,2022

Report No.: SZCR230200035201

Page: 69 of 148

5GHz	mode	Channel	Frequency(MHz)	Data Rate(Mbps)	Average Power (dBm)	Tune up
802.11ac 20M	U-NII-1	36	5180	MCS0	15.17	16
		40	5200		15.26	16
		48	5240		14.63	16
	U-NII-2A	52	5260		15.1	16
		60	5300		15.22	16
		64	5320		14.9	16
	U-NII-2C	100	5500		14.66	16
		116	5580		14.96	16
		140	5700		15.42	16
	U-NII-3	149	5745		15.75	16
		157	5785		15.4	16
		165	5825		14.92	16
5GHz	mode	Channel	Frequency(MHz)	Data Rate(Mbps)	Average Power (dBm)	Tune up
802.11ac 40M	U-NII-1	38	5190	MCS0	13.43	14
		46	5230		15.57	16
	U-NII-2A	54	5270		15.91	16
		62	5310		14.92	16
	U-NII-2C	102	5510		15.96	17
		110	5550		15.83	17
		134	5670		16.24	17
	U-NII-3	151	5755		16.36	17
		159	5795		16.24	17
5GHz	mode	Channel	Frequency(MHz)	Data Rate(Mbps)	Average Power (dBm)	Tune up
802.11ac 80M	U-NII-1	42	5210	MCS0	13.68	14
	U-NII-2A	58	5290		13.88	14
	U-NII-2C	106	5530		13.87	15
		122	5610		14.24	15
	U-NII-3	155	5775		15.12	16



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
 中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

7.1.3 Conducted Power Of BT

BT			Average Conducted Power(dBm)	Tune up (dBm)
Modulation	Channel	Frequency(MHz)		
GFSK	0	2402	7.32	9
	39	2441	8.53	10
	78	2480	9.12	11
$\pi/4$ DQPSK	0	2402	8.23	9
	39	2441	9.42	10
	78	2480	10.02	11
8DPSK	0	2402	8.36	9
	39	2441	9.56	10
	78	2480	10.04	11

BLE			Average Conducted Power(dBm)	Tune up (dBm)
Modulation	Channel	Frequency(MHz)		
GFSK	0	2402	0.35	2
	19	2440	1.23	2
	39	2480	1.2	2

7.2 Measurement of SAR Data

Note:

- 1) The maximum Scaled SAR value is marked in bold. Graph Results refer to Appendix B
- 2) Per FCC KDB Publication 447498 D04, if the reported (scaled) SAR measured at the middle channel or highest output power channel for each test configuration is ≤ 0.8 W/kg (2.0W/kg for 10g) then testing at the other channels is not required for such test configuration(s).
- 3) “*” is repeated measurement.

WiFi 2.4G:

- 1) When the highest reported SAR for the initial test configuration is adjusted by the ratio of the subsequent test configuration to initial test configuration specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg, SAR test for the other 802.11 modes are not required.

WiFi 5G:

- 1) When the highest reported SAR for the initial test configuration is adjusted by the ratio of the subsequent test configuration to initial test configuration specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg, SAR test for the other 802.11 modes are not required.





SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/0 Aug01,2022

Report No.: SZCR230200035201

Page: 72 of 148

7.2.1 SAR Result Of LTE Band 2

LTE Band 2 SAR Test Record													
Test position	Test mode	Test Ch./Freq.	Duty Cycle	SAR (W/kg) 1-g	SAR (W/kg) 10-g	Power Drift (dB)	Conducted power (dBm)	Tune up Limit (dBm)	Scaled factor	Scaled SAR (W/kg) 1-g	Scaled SAR (W/kg) 10-g	Liquid Temp.	SAR limit (W/kg)
Body Test data(Separate 10mm)													
Front side	20M_QPSK 1RB_0	18900/1880	1:1	0.079	0.041	0.02	23.1	23.5	1.094	0.086	0.045	22.3	1.6
Front side	20M_QPSK 50RB_0	18900/1880	1:1	0.065	0.032	0.09	22.0	23.0	1.259	0.082	0.040	22.3	1.6
Back side	20M_QPSK 1RB_0	18900/1880	1:1	0.213	0.113	0.03	23.1	23.5	1.094	0.233	0.124	22.3	1.6
Back side	20M_QPSK 50RB_0	18900/1880	1:1	0.139	0.078	-0.12	22.0	23.0	1.259	0.175	0.098	22.3	1.6
Left side	20M_QPSK 1RB_0	18900/1880	1:1	0.057	0.033	0.03	23.1	23.5	1.094	0.062	0.036	22.3	1.6
Left side	20M_QPSK 50RB_0	18900/1880	1:1	0.048	0.022	0.16	22.0	23.0	1.259	0.060	0.028	22.3	1.6
Right side	20M_QPSK 1RB_0	18900/1880	1:1	0.148	0.085	-0.14	23.1	23.5	1.094	0.162	0.093	22.3	1.6
Right side	20M_QPSK 50RB_0	18900/1880	1:1	0.126	0.071	0.19	22.0	23.0	1.259	0.159	0.089	22.3	1.6
Top side	20M_QPSK 1RB_0	18900/1880	1:1	0.031	0.015	0.03	23.1	23.5	1.094	0.034	0.016	22.3	1.6
Top side	20M_QPSK 50RB_0	18900/1880	1:1	0.024	0.012	0.18	22.0	23.0	1.259	0.030	0.015	22.3	1.6
Bottom side	20M_QPSK 1RB_0	18900/1880	1:1	0.096	0.044	-0.13	23.1	23.5	1.094	0.105	0.049	22.3	1.6
Bottom side	20M_QPSK 50RB_0	18900/1880	1:1	0.078	0.036	0.03	22.0	23.0	1.259	0.098	0.045	22.3	1.6
Back side	20M_QPSK 1RB_0	18700/1860	1:1	0.198	0.088	0.06	22.9	23.5	1.146	0.227	0.101	22.3	1.6
Back side	20M_QPSK 1RB_0	19100/1900	1:1	0.186	0.075	0.11	23.1	23.5	1.096	0.204	0.082	22.3	1.6
Body Test data at the worst case with SIM2(Separate 10mm)													
Back side	20M_QPSK 1RB_0	18900/1880	1:1	0.189	0.099	0.09	23.1	23.5	1.094	0.207	0.108	22.3	1.6
Extremity Test data(Separate 0mm)													
Front side	20M_QPSK 1RB_0	18900/1880	1:1	0.328	0.173	0.06	23.1	23.5	1.094	0.359	0.189	22.3	4
Front side	20M_QPSK 50RB_0	18900/1880	1:1	0.267	0.140	-0.07	22.0	23.0	1.259	0.336	0.176	22.3	4
Back side	20M_QPSK 1RB_0	18900/1880	1:1	0.591	0.293	0.08	23.1	23.5	1.094	0.647	0.321	22.3	4
Back side	20M_QPSK 50RB_0	18900/1880	1:1	0.477	0.235	0.05	22.0	23.0	1.259	0.601	0.296	22.3	4
Left side	20M_QPSK 1RB_0	18900/1880	1:1	0.214	0.104	0.15	23.1	23.5	1.094	0.234	0.114	22.3	4
Left side	20M_QPSK 50RB_0	18900/1880	1:1	0.173	0.084	0.1	22.0	23.0	1.259	0.218	0.106	22.3	4
Right side	20M_QPSK 1RB_0	18900/1880	1:1	0.703	0.337	-0.04	23.1	23.5	1.094	0.769	0.369	22.3	4
Right side	20M_QPSK 50RB_0	18900/1880	1:1	0.571	0.277	0.09	22.0	23.0	1.259	0.719	0.349	22.3	4
Top side	20M_QPSK 1RB_0	18900/1880	1:1	0.075	0.034	0.19	23.1	23.5	1.094	0.082	0.037	22.3	4
Top side	20M_QPSK 50RB_0	18900/1880	1:1	0.068	0.029	-0.08	22.0	23.0	1.259	0.086	0.037	22.3	4
Bottom side	20M_QPSK 1RB_0	18900/1880	1:1	0.309	0.168	0.17	23.1	23.5	1.094	0.338	0.184	22.3	4
Bottom side	20M_QPSK 50RB_0	18900/1880	1:1	0.297	0.162	-0.16	22.0	23.0	1.259	0.374	0.204	22.3	4
Right side	20M_QPSK 1RB_0	18700/1860	1:1	0.675	0.315	0.08	22.9	23.5	1.146	0.773	0.361	22.3	4
Right side	20M_QPSK 1RB_0	19100/1900	1:1	0.674	0.314	-0.18	23.1	23.5	1.096	0.739	0.344	22.3	4
Extremity Test data at the worst case with SIM2(Separate 0mm)													
Right side	20M_QPSK 1RB_0	18900/1880	1:1	0.7	0.331	-0.16	23.1	23.5	1.094	0.766	0.362	22.3	4



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

Member of the SGS Group (SGS SA)



SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/0 Aug01,2022

Report No.: SZCR230200035201

Page: 73 of 148

7.2.2 SAR Result Of LTE Band 4

LTE Band 4 SAR Test Record													
Test position	Test mode	Test Ch./Freq.	Duty Cycle	SAR (W/kg) 1-g	SAR (W/kg) 10-g	Power Drift (dB)	Conducted power (dBm)	Tune up Limit (dBm)	Scale d factor	Scaled SAR (W/kg) 1-g	Scaled SAR (W/kg) 10-g	Liquid Temp.	SAR limit (W/kg)
Body Test data(Separate 10mm)													
Front side	20M_QPSK 1RB_50	20175/1732.5	1:1	0.157	0.101	-0.03	22.65	23	1.084	0.170	0.109	22.2	1.6
Front side	20M_QPSK 50RB_0	20175/1732.5	1:1	0.146	0.086	-0.07	21.53	22	1.114	0.163	0.096	22.2	1.6
Back side	20M_QPSK 1RB_50	20175/1732.5	1:1	0.670	0.383	-0.16	22.65	23	1.084	0.726	0.415	22.2	1.6
Back side	20M_QPSK 50RB_0	20175/1732.5	1:1	0.621	0.316	-0.03	21.53	22	1.114	0.692	0.352	22.2	1.6
Left side	20M_QPSK 1RB_50	20175/1732.5	1:1	0.148	0.087	-0.04	22.65	23	1.084	0.160	0.094	22.2	1.6
Left side	20M_QPSK 50RB_0	20175/1732.5	1:1	0.116	0.072	-0.17	21.53	22	1.114	0.129	0.080	22.2	1.6
Right side	20M_QPSK 1RB_50	20175/1732.5	1:1	0.321	0.19	-0.09	22.65	23	1.084	0.348	0.206	22.2	1.6
Right side	20M_QPSK 50RB_0	20175/1732.5	1:1	0.286	0.167	-0.1	21.53	22	1.114	0.319	0.186	22.2	1.6
Top side	20M_QPSK 1RB_50	20175/1732.5	1:1	0.064	0.029	0.16	22.65	23	1.084	0.069	0.031	22.2	1.6
Top side	20M_QPSK 50RB_0	20175/1732.5	1:1	0.046	0.011	-0.11	21.53	22	1.114	0.051	0.012	22.2	1.6
Bottom side	20M_QPSK 1RB_50	20175/1732.5	1:1	0.356	0.209	0.17	22.65	23	1.084	0.386	0.227	22.2	1.6
Bottom side	20M_QPSK 50RB_0	20175/1732.5	1:1	0.311	0.111	-0.08	21.53	22	1.114	0.347	0.124	22.2	1.6
Back side	20M_QPSK 1RB_50	20300/1745	1:1	0.638	0.368	0.05	22.52	23	1.117	0.713	0.411	22.2	1.6
Back side	20M_QPSK 1RB_50	20050/1720	1:1	0.342	0.371	-0.09	22.49	23	1.125	0.385	0.417	22.2	1.6
Body Test data at the worst case with SIM2(Separate 10mm)													
Back side	20M_QPSK 1RB_50	20175/1732.5	1:1	0.659	0.374	0.17	22.65	23	1.084	0.714	0.405	22.2	1.6
Extremity Test data(Separate 0mm)													
Front side	20M_QPSK 1RB_50	20175/1732.5	1:1	0.73	0.422	0.14	22.65	23	1.084	0.791	0.457	22.2	4
Front side	20M_QPSK 50RB_0	20175/1732.5	1:1	0.689	0.398	0.09	21.53	22	1.114	0.768	0.443	22.2	4
Back side	20M_QPSK 1RB_50	20175/1732.5	1:1	2.05	1.03	-0.07	22.65	23	1.084	2.222	1.116	22.2	4
Back side	20M_QPSK 50RB_0	20175/1732.5	1:1	1.87	0.972	-0.15	21.53	22	1.114	2.084	1.083	22.2	4
Left side	20M_QPSK 1RB_50	20175/1732.5	1:1	0.351	0.192	-0.09	22.65	23	1.084	0.380	0.208	22.2	4
Left side	20M_QPSK 50RB_0	20175/1732.5	1:1	0.336	0.179	-0.08	21.53	22	1.114	0.374	0.199	22.2	4
Right side	20M_QPSK 1RB_50	20175/1732.5	1:1	1.23	0.648	-0.1	22.65	23	1.084	1.333	0.702	22.2	4
Right side	20M_QPSK 50RB_0	20175/1732.5	1:1	1.12	0.621	-0.17	21.53	22	1.114	1.248	0.692	22.2	4
Top side	20M_QPSK 1RB_50	20175/1732.5	1:1	0.112	0.052	-0.12	22.65	23	1.084	0.121	0.056	22.2	4
Top side	20M_QPSK 50RB_0	20175/1732.5	1:1	0.101	0.049	0.08	21.53	22	1.114	0.113	0.055	22.2	4
Bottom side	20M_QPSK 1RB_50	20175/1732.5	1:1	0.864	0.512	-0.15	22.65	23	1.084	0.937	0.555	22.2	4
Bottom side	20M_QPSK 50RB_0	20175/1732.5	1:1	0.842	0.489	0.02	21.53	22	1.114	0.938	0.545	22.2	4
Back side	20M_QPSK 1RB_50	20300/1745	1:1	1.86	0.875	0.14	22.52	23	1.117	2.077	0.977	22.2	4
Back side	20M_QPSK 1RB_50	20050/1720	1:1	1.89	0.889	-0.09	22.49	23	1.125	2.126	1.000	22.2	4
Extremity Test data at the worst case with SIM2(Separate 0mm)													
Back side	20M_QPSK 1RB_50	20175/1732.5	1:1	2.01	0.999	0.11	22.65	23	1.084	2.179	1.083	22.2	4



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing/inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com



SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/0 Aug01,2022

Report No.: SZCR230200035201

Page: 74 of 148

7.2.3 SAR Result Of LTE Band 5

LTE Band 5 SAR Test Record													
Test position	Test mode	Test Ch./Freq.	Duty Cycle	SAR (W/kg) 1-g	SAR (W/kg) 10-g	Power Drift (dB)	Conducted power (dBm)	Tune up Limit (dBm)	Scaled factor	Scaled SAR (W/kg) 1-g	Scaled SAR (W/kg) 10-g	Liquid Temp.	SAR limit (W/kg)
Body Test data (Separate 10mm)													
Front side	10M_QPSK 1RB_0	20525/836.5	1:1	0.112	0.078	0.14	23.1	23.5	1.096	0.123	0.086	22.1	1.6
Front side	10M_QPSK 25RB_0	20525/836.5	1:1	0.101	0.064	0.09	22.32	23.0	1.169	0.118	0.075	22.1	1.6
Back side	10M_QPSK 1RB_0	20525/836.5	1:1	0.361	0.204	0.05	23.1	23.5	1.096	0.396	0.224	22.1	1.6
Back side	10M_QPSK 25RB_0	20525/836.5	1:1	0.336	0.176	0.04	22.32	23.0	1.169	0.393	0.206	22.1	1.6
Left side	10M_QPSK 1RB_0	20525/836.5	1:1	0.045	0.023	0.05	23.1	23.5	1.096	0.049	0.025	22.1	1.6
Left side	10M_QPSK 25RB_0	20525/836.5	1:1	0.031	0.019	-0.13	22.32	23.0	1.169	0.036	0.022	22.1	1.6
Right side	10M_QPSK 1RB_0	20525/836.5	1:1	0.062	0.043	0.16	23.1	23.5	1.096	0.068	0.047	22.1	1.6
Right side	10M_QPSK 25RB_0	20525/836.5	1:1	0.041	0.026	0.09	22.32	23.0	1.169	0.048	0.030	22.1	1.6
Top side	10M_QPSK 1RB_0	20525/836.5	1:1	0.010	0.003	-0.04	23.1	23.5	1.096	0.011	0.003	22.1	1.6
Top side	10M_QPSK 25RB_0	20525/836.5	1:1	0.005	0.001	0.08	22.32	23.0	1.169	0.006	0.001	22.1	1.6
Bottom side	10M_QPSK 1RB_0	20525/836.5	1:1	0.181	0.111	-0.16	23.1	23.5	1.096	0.198	0.122	22.1	1.6
Bottom side	10M_QPSK 25RB_0	20525/836.5	1:1	0.168	0.101	-0.06	22.32	23.0	1.169	0.196	0.118	22.1	1.6
Back side	10M_QPSK 1RB_0	20450/829	1:1	0.168	0.101	-0.19	23.09	23.5	1.099	0.185	0.111	22.1	1.6
Back side	10M_QPSK 1RB_0	20600/844	1:1	0.168	0.101	0.11	23.04	23.5	1.112	0.187	0.112	22.1	1.6
Body Test data at the worst case with SIM2 (Separate 10mm)													
Back side	10M_QPSK 1RB_0	20525/836.5	1:1	0.354	0.198	0.11	23.1	23.5	1.096	0.388	0.217	22.1	1.6
Extremity Test data (Separate 0mm)													
Front side	10M_QPSK 1RB_0	20525/836.5	1:1	0.32	0.209	-0.18	23.10	23.5	1.096	0.351	0.229	22.1	4
Front side	10M_QPSK 25RB_0	20525/836.5	1:1	0.298	0.175	0.07	22.32	23.0	1.169	0.349	0.205	22.1	4
Back side	10M_QPSK 1RB_0	20525/836.5	1:1	0.871	0.451	0.01	23.10	23.5	1.096	0.955	0.495	22.1	4
Back side	10M_QPSK 25RB_0	20525/836.5	1:1	0.854	0.446	0.14	22.32	23.0	1.169	0.999	0.522	22.1	4
Left side	10M_QPSK 1RB_0	20525/836.5	1:1	0.84	0.43	-0.08	23.10	23.5	1.096	0.921	0.471	22.1	4
Left side	10M_QPSK 25RB_0	20525/836.5	1:1	0.831	0.428	0.18	22.32	23.0	1.169	0.972	0.501	22.1	4
Right side	10M_QPSK 1RB_0	20525/836.5	1:1	0.162	0.096	-0.15	23.10	23.5	1.096	0.178	0.105	22.1	4
Right side	10M_QPSK 25RB_0	20525/836.5	1:1	0.154	0.085	-0.16	22.32	23.0	1.169	0.180	0.099	22.1	4
Top side	10M_QPSK 1RB_0	20525/836.5	1:1	0.031	0.014	-0.06	23.10	23.5	1.096	0.034	0.015	22.1	4
Top side	10M_QPSK 25RB_0	20525/836.5	1:1	0.028	0.011	0.11	22.32	23.0	1.169	0.033	0.013	22.1	4
Bottom side	10M_QPSK 1RB_0	20525/836.5	1:1	0.701	0.403	0.16	23.10	23.5	1.096	0.769	0.442	22.1	4
Bottom side	10M_QPSK 25RB_0	20525/836.5	1:1	0.684	0.385	0.17	22.32	23.0	1.169	0.800	0.450	22.1	4
Back side	10M_QPSK 25RB_0	20450/829	1:1	0.871	0.453	0.01	22.16	23.0	1.213	1.057	0.550	22.1	4
Back side	10M_QPSK 25RB_0	20600/844	1:1	0.842	0.437	0.14	22.10	23.0	1.230	1.036	0.538	22.1	4
Extremity Test data at the worst case with SIM2 (Separate 0mm)													
Back side	10M_QPSK 25RB_0	20450/829	1:1	0.862	0.45	0.19	22.16	23.0	1.213	1.046	0.546	22.1	4



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com



SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/0 Aug01,2022

Report No.: SZCR230200035201

Page: 75 of 148

7.2.4 SAR Result Of LTE Band 7

LTE Band 7 SAR Test Record													
Test position	Test mode	Test Ch./Freq.	Duty Cycle	SAR (W/kg) 1-g	SAR (W/kg) 10-g	Power Drift (dB)	Conducted power (dBm)	Tune up Limit (dBm)	Scaled factor	Scaled SAR (W/kg) 1-g	Scaled SAR (W/kg) 10-g	Liquid Temp.	SAR limit (W/kg)
Body Test data(Separate 10mm)													
Front side	20M_QPSK 1RB_0	20850/2510	1:1	0.042	0.012	0.03	23.10	23.50	1.096	0.046	0.013	22.1	1.6
Front side	20M_QPSK 50RB_0	20850/2510	1:1	0.031	0.010	-0.13	21.99	23.00	1.262	0.039	0.013	22.1	1.6
Back side	20M_QPSK 1RB_0	20850/2510	1:1	0.500	0.250	-0.03	23.10	23.50	1.096	0.548	0.274	22.1	1.6
Back side	20M_QPSK 50RB_0	20850/2510	1:1	0.486	0.242	0.09	21.99	23.00	1.262	0.613	0.305	22.1	1.6
Left side	20M_QPSK 1RB_0	20850/2510	1:1	0.047	0.019	-0.16	23.10	23.50	1.096	0.052	0.020	22.1	1.6
Left side	20M_QPSK 50RB_0	20850/2510	1:1	0.035	0.010	0.16	21.99	23.00	1.262	0.044	0.013	22.1	1.6
Right side	20M_QPSK 1RB_0	20850/2510	1:1	0.152	0.085	-0.17	23.10	23.50	1.096	0.167	0.093	22.1	1.6
Right side	20M_QPSK 50RB_0	20850/2510	1:1	0.143	0.069	-0.1	21.99	23.00	1.262	0.180	0.087	22.1	1.6
Top side	20M_QPSK 1RB_0	20850/2510	1:1	0.032	0.013	0.06	23.10	23.50	1.096	0.035	0.014	22.1	1.6
Top side	20M_QPSK 50RB_0	20850/2510	1:1	0.028	0.009	0.13	21.99	23.00	1.262	0.035	0.011	22.1	1.6
Bottom side	20M_QPSK 1RB_0	20850/2510	1:1	0.212	0.104	-0.11	23.10	23.50	1.096	0.232	0.114	22.1	1.6
Bottom side	20M_QPSK 50RB_0	20850/2510	1:1	0.201	0.086	0.11	21.99	23.00	1.262	0.254	0.109	22.1	1.6
Back side	20M_QPSK 50RB_0	21100/2535.5	1:1	0.473	0.236	0.17	21.89	23.00	1.291	0.611	0.305	22.1	1.6
Back side	20M_QPSK 50RB_0	21350/2560	1:1	0.462	0.222	-0.13	21.80	23.00	1.318	0.609	0.293	22.1	1.6
Body Test data at the worst case with SIM2(Separate 10mm)													
Back side	20M_QPSK 50RB_0	20850/2510	1:1	0.482	0.24	-0.06	21.99	23.00	1.262	0.608	0.303	22.1	1.6
Extremity Test data(Separate 0mm)													
Front side	20M_QPSK 1RB_0	20850/2510	1:1	0.294	0.154	0.03	23.10	23.50	1.096	0.322	0.169	22.1	4
Front side	20M_QPSK 50RB_0	20850/2510	1:1	0.286	0.149	-0.19	21.99	23.00	1.262	0.361	0.188	22.1	4
Back side	20M_QPSK 1RB_0	20850/2510	1:1	1.57	0.725	-0.12	23.10	23.50	1.096	1.721	0.795	22.1	4
Back side	20M_QPSK 50RB_0	20850/2510	1:1	1.45	0.716	0.08	21.99	23.00	1.262	1.830	0.903	22.1	4
Left side	20M_QPSK 1RB_0	20850/2510	1:1	0.114	0.051	-0.05	23.10	23.50	1.096	0.125	0.056	22.1	4
Left side	20M_QPSK 50RB_0	20850/2510	1:1	0.108	0.046	-0.16	21.99	23.00	1.262	0.136	0.058	22.1	4
Right side	20M_QPSK 1RB_0	20850/2510	1:1	0.738	0.357	-0.03	23.10	23.50	1.096	0.809	0.391	22.1	4
Right side	20M_QPSK 50RB_0	20850/2510	1:1	0.726	0.349	-0.07	21.99	23.00	1.262	0.916	0.440	22.1	4
Top side	20M_QPSK 1RB_0	20850/2510	1:1	0.087	0.046	0.09	23.10	23.50	1.096	0.095	0.050	22.1	4
Top side	20M_QPSK 50RB_0	20850/2510	1:1	0.076	0.039	0.1	21.99	23.00	1.262	0.096	0.049	22.1	4
Bottom side	20M_QPSK 1RB_0	20850/2510	1:1	1.49	0.616	-0.01	23.10	23.50	1.096	1.634	0.675	22.1	4
Bottom side	20M_QPSK 50RB_0	20850/2510	1:1	1.35	0.598	-0.15	21.99	23.00	1.262	1.703	0.755	22.1	4
Back side	20M_QPSK 50RB_0	21100/2535.5	1:1	1.46	0.698	0.19	21.89	23.00	1.291	1.885	0.901	22.1	4
Back side	20M_QPSK 50RB_0	21350/2560	1:1	1.33	0.676	-0.05	21.80	23.00	1.318	1.753	0.891	22.1	4
Extremity Test data at the worst case with SIM2(Separate 0mm)													
Back side	20M_QPSK 50RB_0	20850/2510	1:1	1.45	0.71	0.03	21.99	23.00	1.262	1.830	0.896	22.1	4



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com



SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/0 Aug01,2022

Report No.: SZCR230200035201

Page: 76 of 148

7.2.5 SAR Result Of LTE Band 12

LTE Band 12 SAR Test Record													
Test position	Test mode	Test Ch./Freq.	Duty Cycle	SAR (W/kg) 1-g	SAR (W/kg) 10-g	Power Drift (dB)	Conducted power (dBm)	Tune up Limit (dBm)	Scaled factor	Scaled SAR (W/kg) 1-g	Scaled SAR (W/kg) 10-g	Liquid Temp.	SAR limit (W/kg)
Body Test data(Separate 10mm)													
Front side	10M_QPSK 1RB_0	23060/704	1:1	0.087	0.063	0.06	23.01	23.5	1.119	0.098	0.070	22.1	1.6
Front side	10M_QPSK 25RB_0	23060/704	1:1	0.079	0.056	-0.07	21.91	22.5	1.146	0.090	0.064	22.1	1.6
Back side	10M_QPSK 1RB_0	23060/704	1:1	0.140	0.110	-0.02	23.01	23.5	1.119	0.157	0.123	22.1	1.6
Back side	10M_QPSK 25RB_0	23060/704	1:1	0.132	0.101	-0.1	21.91	22.5	1.146	0.151	0.116	22.1	1.6
Left side	10M_QPSK 1RB_0	23060/704	1:1	0.071	0.050	0.09	23.01	23.5	1.119	0.080	0.056	22.1	1.6
Left side	10M_QPSK 25RB_0	23060/704	1:1	0.064	0.038	0.09	21.91	22.5	1.146	0.073	0.044	22.1	1.6
Right side	10M_QPSK 1RB_0	23060/704	1:1	0.115	0.079	-0.15	23.01	23.5	1.119	0.129	0.089	22.1	1.6
Right side	10M_QPSK 25RB_0	23060/704	1:1	0.098	0.065	0.01	21.91	22.5	1.146	0.112	0.074	22.1	1.6
Top side	10M_QPSK 1RB_0	23060/704	1:1	0.023	0.009	-0.02	23.01	23.5	1.119	0.026	0.010	22.1	1.6
Top side	10M_QPSK 25RB_0	23060/704	1:1	0.015	0.002	-0.04	21.91	22.5	1.146	0.017	0.002	22.1	1.6
Bottom side	10M_QPSK 1RB_0	23060/704	1:1	0.058	0.034	0.17	23.01	23.5	1.119	0.065	0.038	22.1	1.6
Bottom side	10M_QPSK 25RB_0	23060/704	1:1	0.058	0.034	-0.07	21.91	22.5	1.146	0.067	0.039	22.1	1.6
Back side	10M_QPSK 1RB_0	23095/707.5	1:1	0.134	0.098	-0.04	22.94	23.5	1.138	0.152	0.111	22.1	1.6
Back side	10M_QPSK 1RB_0	23130/711	1:1	0.131	0.095	0.16	22.98	23.5	1.127	0.148	0.107	22.1	1.6
Body Test data at the worst case with SIM2(Separate 10mm)													
Back side	10M_QPSK 1RB_0	23060/704	1:1	0.139	0.109	-0.06	23.01	23.5	1.119	0.156	0.122	22.1	1.6
Extremity Test data(Separate 0mm)													
Front side	10M_QPSK 1RB_0	23060/704	1:1	0.163	0.104	-0.01	23.01	23.5	1.119	0.182	0.116	22.1	4
Front side	10M_QPSK 25RB_0	23060/704	1:1	0.159	0.098	-0.11	21.91	22.5	1.146	0.182	0.112	22.1	4
Back side	10M_QPSK 1RB_0	23060/704	1:1	0.487	0.273	-0.1	23.01	23.5	1.119	0.545	0.306	22.1	4
Back side	10M_QPSK 25RB_0	23060/704	1:1	0.472	0.262	-0.19	21.91	22.5	1.146	0.541	0.300	22.1	4
Left side	10M_QPSK 1RB_0	23060/704	1:1	0.214	0.122	-0.16	23.01	23.5	1.119	0.240	0.137	22.1	4
Left side	10M_QPSK 25RB_0	23060/704	1:1	0.198	0.116	-0.01	21.91	22.5	1.146	0.227	0.133	22.1	4
Right side	10M_QPSK 1RB_0	23060/704	1:1	0.097	0.060	0.11	23.01	23.5	1.119	0.109	0.067	22.1	4
Right side	10M_QPSK 25RB_0	23060/704	1:1	0.085	0.051	-0.13	21.91	22.5	1.146	0.097	0.058	22.1	4
Top side	10M_QPSK 1RB_0	23060/704	1:1	0.034	0.016	-0.19	23.01	23.5	1.119	0.038	0.018	22.1	4
Top side	10M_QPSK 25RB_0	23060/704	1:1	0.029	0.009	-0.09	21.91	22.5	1.146	0.033	0.010	22.1	4
Bottom side	10M_QPSK 1RB_0	23060/704	1:1	0.292	0.164	0.07	23.01	23.5	1.119	0.327	0.184	22.1	4
Bottom side	10M_QPSK 25RB_0	23060/704	1:1	0.275	0.153	0.1	21.91	22.5	1.146	0.315	0.175	22.1	4
Back side	10M_QPSK 1RB_0	23095/707.5	1:1	0.476	0.262	-0.09	22.94	23.5	1.138	0.542	0.298	22.1	4
Back side	10M_QPSK 1RB_0	23130/711	1:1	0.472	0.255	-0.05	22.98	23.5	1.127	0.532	0.287	22.1	4
Extremity Test data at the worst case with SIM2(Separate 0mm)													
Back side	10M_QPSK 1RB_0	23060/704	1:1	0.485	0.27	0.12	23.01	23.5	1.119	0.543	0.302	22.1	4



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com