

FCC 47 CFR MPE REPORT

GUANGDONG ROULE ELECTRONICS CO., LTD.

WiFi Remote Video Doorbell

Model Number: RL-IP02C

Additional Model: RL-IP02C-1; RL-IP02B; RL-IP02B-1

FCC ID: YI6RL-IP02

Prepared for : GUANGDONG ROULE ELECTRONICS CO., LTD.

**No. 12, Pingdong 3rd Road, Nanping Industry Community,
Zhuhai City, GuangDong, 519060 ,China.**

Prepared By : EST Technology Co., Ltd.

San Tun Management Zone, Houjie District, Dongguan, China

Tel: 86-769-83081888-808

Report Number: ESTE-R1610030

Date of Test : September20~ October 13, 2016

Date of Report : October 17, 2016

Maximum Permissible Exposure

1、Applicable Standard

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 0.2m normally can be maintained between the user and the device.

(a)、Limits for Occupational / Controlled Exposure

Frequency Range (MHz)	Electric Field Strength E (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Times E 2 , H 2 or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842/f	4.89/f	(900/f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-10000			5	6

(b)、Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength E (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Times E 2 , H 2 or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-10000			1.0	30

Note: f=frequency in MHz; *Plane-wave equivalent power density

2、MPE Calculation Method

$$E \text{ (V/m)} = (30 \cdot P \cdot G)^{0.5} / d \quad \text{Power Density: } Pd \text{ (W/m}^2\text{)} = E^2 / 377$$

E = Electric Field (V/m)

P = Peak RF output Power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = (30 \cdot P \cdot G) / (377 \cdot d^2)$$

From the peak EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the gain of the used antenna, the RF power density can be obtained

3、Calculated Result and Limit

Mode	Frequency (MHz)	Peak output power (dBm)	Peak output power (mW)	Target power (dBm)	Antenna gain		Power Density (S) (mW /cm2)	Limited of Power Density (S) (mW /cm2)	Test Result
					(dBi)	(Linear)			
802.11b	2412	14.10	25.704	14 ± 2	2.00	1.585	0.01255	1	Compiles
	2437	14.96	31.333	14 ± 2	2.00	1.585	0.01255	1	Compiles
	2462	14.62	28.973	14 ± 2	2.00	1.585	0.01255	1	Compiles
802.11g	2412	8.14	6.516	8 ± 2	2.00	1.585	0.00315	1	Compiles
	2437	8.61	7.261	8 ± 2	2.00	1.585	0.00315	1	Compiles
	2462	8.35	6.839	8 ± 2	2.00	1.585	0.00315	1	Compiles
802.11n HT20	2412	8.24	6.668	8 ± 2	2.00	1.585	0.00315	1	Compiles
	2437	8.29	6.745	8 ± 2	2.00	1.585	0.00315	1	Compiles
	2462	7.73	5.929	7 ± 2	2.00	1.585	0.00250	1	Compiles
802.11n HT40	2422	5.19	3.304	5 ± 2	2.00	1.585	0.00158	1	Compiles
	2437	5.83	3.828	5 ± 2	2.00	1.585	0.00158	1	Compiles
	2452	6.10	4.074	6 ± 2	2.00	1.585	0.00199	1	Compiles