


	TEST REPOR	T			
FCC ID:	2ADDH-33834-1				
Test Report No::	TCT220919E023	(3)			
Date of issue::	Sep. 30, 2022				
Testing laboratory:	SHENZHEN TONGCE TESTING	G LAB			
Testing location/ address:	2101 & 2201, Zhenchang Factor Subdistrict, Bao'an District, Sher People's Republic of China				
Applicant's name::	Monoprice, Inc.	(C)			
Address::	1 Pointe Drive Suite 400, Brea, (	California 92821, United S	tates		
Manufacturer's name:	Monoprice, Inc.				
Address::	1 Pointe Drive Suite 400, Brea, California 92821, United States				
Standard(s):	KDB 447498 D01 General RF Exposure Guidance v06				
Product Name::	BT-300ANC Bluetooth Wireless Over Ear Headphones with Active Noise Cancelling (ANC)				
Trade Mark:	N/A				
Model/Type reference:	33834	(c)			
Rating(s)::	Rechargeable Li-ion Battery DC	3.7V			
Date of receipt of test item:	Sep. 19, 2022				
Date (s) of performance of test:	Sep. 19, 2022 - Sep. 30, 2022				
Tested by (+signature):	Yannie ZHONG	Yannie Tokeci			
Check by (+signature):	Beryl ZHAO	Boy CONTO			
Approved by (+signature):	Tomsin	fomsites so	(0)		

#### General disclaimer:

This report shall not be reproduced except in full, without the written approval of SHENZHEN TONGCE TESTING LAB. This document may be altered or revised by SHENZHEN TONGCE TESTING LAB personnel only, and shall be noted in the revision section of the document. The test results in the report only apply to the tested sample.





# **Table of Contents**

1.7 2. Go 2.7 2.3 3. Fa 3.7 3.2	eneral Pro 1. EUT deso 2. Model(s) eneral Info 1. Test envi 2. Descripti acilities ar 1. Facilities 2. Location	cription listormation ironment a ion of Sup nd Accre	and mode. port Units				34455
4. Te	est Result	s and Me	easureme	ent Data.	/		6



Report No.: TCT220919E023

# 1. General Product Information

## 1.1. EUT description

Product Name:	BT-300ANC Bluetooth Wireless Over Ear Headphones with Active Noise Cancelling (ANC)
Model/Type reference:	33834
Sample Number:	TCT220919E022-0101
Operation Frequency:	2402MHz~2480MHz
Modulation Type:	GFSK, π/4-DQPSK, 8DPSK
Antenna Type:	FPC Antenna
Antenna Gain:	-1.51dBi
Rating(s):	Rechargeable Li-ion Battery DC 3.7V

Note: The antenna gain listed in this report is provided by applicant, and the test laboratory is not responsible for this parameter.

1.2. Model(s) list None.								



Report No.: TCT220919E023

## 2. General Information

#### 2.1. Test environment and mode

Item	Normal condition							
Temperature	+25°C							
Voltage	DC 3.7V							
Humidity	56%							
Atmospheric Pressure:	1008 mbar							
Test Mode:								
Engineering mode:	Keep the EUT in continuous transmitting by select channel							

## 2.2. Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Equipment	Model No.	Serial No.	FCC ID	Trade Name	
			1	1	

#### Note:

- 1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
- 2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.
- 3. For conducted measurements (Output Power, 20dB Occupied Bandwidth, Carrier Frequencies Separation, Hopping Channel Number, Dwell Time, Spurious Emissions), the antenna of EUT is connected to the test equipment via temporary antenna connector, the antenna connector is soldered on the antenna port of EUT, and the temporary antenna connector is listed in the Test Instruments.



TESTING CENTRE TECHNOLOGY Report No.: TCT220919E023

## 3. Facilities and Accreditations

#### 3.1. Facilities

The test facility is recognized, certified, or accredited by the following organizations:

• FCC - Registration No.: 645098

SHENZHEN TONGCE TESTING LAB

**Designation Number: CN1205** 

The testing lab has been registered and fully described in a report with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files.

IC - Registration No.: 10668A-1

SHENZHEN TONGCE TESTING LAB

CAB identifier: CN0031

The testing lab has been recognized by Innovation, Science and Economic Development Canada for radio equipment testing.

## 3.2. Location

SHENZHEN TONGCE TESTING LAB

Address: 2101 & 2201, Zhenchang Factory Renshan Industrial Zone, Fuhai Subdistrict, Bao'an District, Shenzhen, Guangdong, 518103, People's Republic of China

TEL: +86-755-27673339





Report No.: TCT220919E023

### 4. Test Results and Measurement Data

According to KDB 447498 D01 General RF Exposure Guidance v06, systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the commission's guidance.

The 1-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW) / (min. test separation distance, mm)]  $\cdot [\sqrt{f(GHz)}] \le 3.0$  for 1-g SAR, where

- f(GHz) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- When the minimum test separation distance is < 5 mm, a distance of 5 mm according is applied to determine SAR test exclusion.
- The result is rounded to one decimal place for comparison

#### BDR+EDR:

Channel	Frequency (GHz)	Max. Power (dBm)	Tune up Power (dBm)	Max. Tune up Power (dBm)	Max. Tune up Power (mW)	Test distance (mm)	Result	exclusion thresholds for 1-g SAR
CH 78	2.480	6.25	6±1	7	5.01	5	1.58	3.0

#### Result:

Base on the calculation value, No SAR measurement is required.

\*\*\*\*\*END OF REPORT\*\*\*\*

Page 6 of 6

Hotline: 400-6611-140 Tel: 86-755-27673339 Fax: 86-755-27673332 http://www.tct-lab.com