

User Manual



Y2

- ① Windproof net
- ② Hide switch
- ③ Menu key
- ④ Back Clip
- ⑤ Charging port
- ⑥ Indicator light
- ⑦ indicator light
- ⑧ Type-C Lighting port
- ⑨ Type-C Lighting charging port (Note: For iPhone, Receiver need Lightning cable)
- ⑩ Charging case battery indicator

The product has two configurations: 1T1R and 2T1R. The manual is general, please take the real object as the standard.

- ② can control the microphone recording and Pause/Resume recording. Pause refers to U menu for details (Note: Make recording just stop microphone recording, Phone recording will still continue)

1

1

Function	How to use	Light	Notice
Power on	Slide 1 bit of the charging slot	The white and blue lights flash	Press the key for 1s
Power off	Push 1 into the charging slot	The white light flashes three times	Press and hold the key for 3s
Power with EIS		The blue light on	Automatically paired
Multi-track recording	Toggle switch-up	Blue light flashes twice quickly or two seconds	Alternate operation can continue recording
Dimming-head	Slide the key once	Blue light breathing	Click again to exit
RTV mode	press the key twice	White-light breathing	Click again to exit
Life battery	Push the sliding into the charging slot	The white light flashes quickly twice every 3s	
Charging		White-light switches off after fully charged	It charges with case a

Function	How to use	Light	Notice
Power on	Plug in the device	The blue light flashes	
Power off	Push off the device	The light off	
Pairing with FS	Blue light on	Automatically paired	
Reconnect using		The blue light flashes	

1

Battery level test	The four LEDs from left to right indicate 20%, 50%, 75% and 100% battery level. Three LEDs are on, indicating 75% battery level. For every 20% decrease in battery level, turn off one LED until you see the first blinking LED, indicating charging starts. During the charging process, the current battery level LED blinks, and the four indicators are always on after full charge.
Charging status indicator	When the microcontroller enters the Charging state, it will automatically increase the DAC. During the charging process, the green light of the charge is always on. After the SOC is 80, the red will enter the sleep state of turning off the light.
Charging status output	Please use the DV output to change the charging state. During the charging process, the current battery level LED blinks, and the four indicators are always on after full charge.

- (1) Microphone Transmitter (TX)
- (2) Receiver (RX)
- (3) Charging case
- (4) Type-C charging cable
- (5) User manual

Notice: The T10K Wireless Microphone is the same as that of 2T2H Wireless Microphone function operation. This user manual is shared.

If this equipment does cause harmful interference to radio or television reception,
which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

The device has been evaluated to meet general RF exposure requirement. The device can be used in portable exposure condition without restriction

7