

FCC SAR EVALUATION REPORT

**In accordance with the requirements of
FCC 47 CFR Part 2(2.1093), ANSI/IEEE C95.1-1992 and
IEEE Std 1528-2013**

Product Name : Smart Phone

Trademark : OUKITEL

Model Name : WP3

Family Model : N/A

Report No. : S19091101603001

FCC ID : 2ANMU-WP3

Prepared for

SHENZHEN YUNJI INTELLIGENT TECHNOLOGY CO.,LTD
A-SIDE A2 BUILDING 2/F ENET NEW INDUSTRIAL PARK,NO.20 DAFU INDUSTRIAL
ZONE, AOBEL COMMUNITY, GUANLAN, LONGHUA NEW DISTRICT,SHENZHEN CHINA

Prepared by

Shenzhen NTEK Testing Technology Co., Ltd.
1/F, Building E, Fenda Science Park Sanwei, Xixiang, Bao'an District,
Shenzhen, Guangdong, China
Tel.: +86-755-6115 6588 Fax.: +86-755-6115 6599
Website: <http://www.ntek.org.cn>

TEST RESULT CERTIFICATION

Applicant's name.....: SHENZHEN YUNJI INTELLIGENT TECHNOLOGY CO.,LTD
A-SIDE A2 BUILDING 2/F ENET NEW INDUSTRIAL PARK,NO.20
Address.....: DAFU INDUSTRIAL ZONE, AOBEL COMMUNITY, GUANLAN,
LONGHUA NEW DISTRICT,SHENZHEN CHINA
Manufacturer's Name.....: SHENZHEN YUNJI INTELLIGENT TECHNOLOGY CO.,LTD
A-SIDE A2 BUILDING 2/F ENET NEW INDUSTRIAL PARK,NO.20
Address.....: DAFU INDUSTRIAL ZONE, AOBEL COMMUNITY, GUANLAN,
LONGHUA NEW DISTRICT,SHENZHEN CHINA

Product description

Product name.....: Smart Phone
Trademark: OUKITEL
Model Name: WP3
Family Model.....: N/A
FCC 47 CFR Part 2(2.1093)

Standards.....: ANSI/IEEE C95.1-1992
IEEE Std 1528-2013
Published RF exposure KDB procedures

This device described above has been tested by Shenzhen NTEK. In accordance with the measurement methods and procedures specified in IEEE Std 1528-2013 and KDB 865664 D01. Testing has shown that this device is capable of compliance with localized specific absorption rate (SAR) specified in FCC 47 CFR Part 2(2.1093) and ANSI/IEEE C95.1-1992. The test results in this report apply only to the tested sample of the stated device/equipment. Other similar device/equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties.


This report shall not be reproduced except in full, without the written approval of Shenzhen NTEK, this document may be altered or revised by Shenzhen NTEK, personal only, and shall be noted in the revision of the document.

Date of Test

Date (s) of performance of tests.....: Sep. 16, 2019 ~ Sep. 23, 2019

Date of Issue: Nov. 01, 2019

Test Result: **Pass**

Prepared By : 
(Test Engineer) :
(Cheng Jiawen)

Approved By : 
(Lab Manager) :
(Sam Chen)

※ ※ Revision History ※ ※

REV.	DESCRIPTION	ISSUED DATE	REMARK
Rev.1.0	Initial Test Report Release	Nov. 01, 2019	Cheng Jiawen

TABLE OF CONTENTS

1. General Information	6
1.1. RF exposure limits.....	6
1.2. Statement of Compliance	7
1.3. EUT Description	7
1.4. Test specification(s)	10
1.5. Ambient Condition.....	10
2. SAR Measurement System	11
2.1. SATIMO SAR Measurement Set-up Diagram	11
2.2. Robot	12
2.3. E-Field Probe.....	13
2.3.1. E-Field Probe Calibration	13
2.4. SAM phantoms	14
2.4.1. Technical Data	15
2.5. Device Holder	16
2.6. Test Equipment List	17
3. SAR Measurement Procedures	19
3.1. Power Reference	19
3.2. Area scan & Zoom scan.....	19
3.3. Description of interpolation/extrapolation scheme	21
3.4. Volumetric Scan	21
3.5. Power Drift	21
4. System Verification Procedure	22
4.1. Tissue Verification	22
4.1.1. Tissue Dielectric Parameter Check Results	23
4.2. System Verification Procedure	24
4.2.1. System Verification Results	25
5. SAR Measurement variability and uncertainty	26
5.1. SAR measurement variability.....	26
5.2. SAR measurement uncertainty	26
6. RF Exposure Positions	27
6.1. Ear and handset reference point	27
6.2. Definition of the cheek position	27
6.3. Definition of the tilt position	29
6.4. Body Worn Accessory	29
6.5. Wireless Router Devices	30
7. RF Output Power	31
7.1. GSM Conducted Power	31
7.2. WCDMA Conducted Power	31
7.3. LTE Conducted Power	33

7.4. WLAN & Bluetooth Output Power	46
7.4.1. Output Power Results Of WLAN	46
7.4.2. Output Power Results Of Bluetooth.....	47
8. Antenna Location.....	48
9. Stand-alone SAR test exclusion.....	49
10. SAR Results	50
10.1. SAR measurement results	50
10.1.1. SAR measurement Result of GSM850	50
10.1.2. SAR measurement Result of GSM1900.....	51
10.1.3. SAR measurement Result of WCDMA Band 2	52
10.1.4. SAR measurement Result of WCDMA Band 4	52
10.1.5. SAR measurement Result of WCDMA Band 5	53
10.1.6. SAR measurement Result of LTE Band 2	54
10.1.7. SAR measurement Result of LTE Band 4	56
10.1.8. SAR measurement Result of LTE Band 5	58
10.1.9. SAR measurement Result of LTE Band 7	60
10.1.10. SAR measurement Result of LTE Band 12	62
10.1.11. SAR measurement Result of LTE Band 17	63
10.1.12. SAR measurement Result of LTE Band 19	65
10.1.13. SAR measurement Result of WLAN 2.4G	67
10.2. SAR Summation Scenario.....	68
11. Appendix A. Photo documentation	78
12. Appendix B. System Check Plots.....	78
13. Appendix C. Plots of High SAR Measurement.....	103
14. Appendix D. Calibration Certificate	156

1. General Information

1.1. RF exposure limits

(A).Limits for Occupational/Controlled Exposure (W/kg)

Whole-Body	Partial-Body	Hands, Wrists, Feet and Ankles
0.4	8.0	20.0

(B).Limits for General Population/Uncontrolled Exposure (W/kg)

Whole-Body	Partial-Body	Hands, Wrists, Feet and Ankles
0.08	1.6	4.0

NOTE: **Whole-Body SAR** is averaged over the entire body, **partial-body SAR** is averaged over any 1 gram of tissue defined as a tissue volume in the shape of a cube. **SAR for hands, wrists, feet and ankles** is averaged over any 10 grams of tissue defined as a tissue volume in the shape of a cube.

Occupational/Controlled Environments:

Are defined as locations where there is exposure that may be incurred by people who are aware of the potential for exposure, (i.e. as a result of employment or occupation).

General Population/Uncontrolled Environments:

Are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure.

NOTE
 HEAD AND TRUNK LIMIT
 1.6 W/kg
 APPLIED TO THIS EUT

1.2. Statement of Compliance

The maximum results of Specific Absorption Rate (SAR) found during testing for WP3 are as follows.

Band	Max Reported SAR Value(W/kg)			
	1-g Head	1-g Body-Worn (Separation distance of 10mm)	1-g Hotspot (Separation distance of 10mm)	Max Simultaneous Tx
GSM 850	0.285	0.520	0.520	1.345
GSM 1900	0.316	0.436	0.436	
WCDMA Band 2	0.452	0.661	0.661	
WCDMA Band 4	0.553	1.112	1.112	
WCDMA Band 5	0.125	0.214	0.214	
LTE Band 2	0.365	0.719	0.719	
LTE Band 4	0.446	1.191	1.191	
LTE Band 5	0.129	0.226	0.226	
LTE Band 7	0.399	1.196	1.196	
LTE Band 12	0.035	0.068	0.068	
LTE Band 17	0.082	0.073	0.073	
LTE Band 19	0.096	0.178	0.178	
WLAN 2.4G	0.701	0.149	0.149	

Note: The Max Simultaneous Tx is calculated based on the same configuration and test position. This device is in compliance with Specific Absorption Rate (SAR) for general population/uncontrolled exposure limits (1.6 W/kg) specified in FCC 47 CFR Part 2(2.1093) and ANSI/IEEE C95.1-1992, and had been tested in accordance with the measurement methods and procedures specified in IEEE Std 1528-2013 & KDB 865664 D01.

1.3. EUT Description

Device Information	
Product Name	Smart Phone
Trade Name	OUKITEL
Model Name	WP3
Family Model	N/A
FCC ID	2ANMU-WP3
Device Phase	Identical Prototype
Exposure Category	General population / Uncontrolled environment
Antenna	FPC Antenna
Battery Information	DC 3.85V, 5200mAh, 20.02Wh
Device Operating Configurations	
Supporting Mode(s)	GSM 850/1900, WCDMA Band 2/4/5, LTE Band

	2/4/5/7/12/17/19, WLAN 2.4G, Bluetooth		
Test Modulation	GSM(GMSK/8PSK), WCDMA(QPSK), LTE(QPSK/16QAM), WLAN(DSSS/OFDM), Bluetooth(GFSK, $\pi/4$ -DQPSK, 8DPSK)		
Device Class	B		
Operating Frequency Range(s)	Band	Tx (MHz)	Rx (MHz)
	GSM 850	824-849	869-894
	GSM 1900	1850-1910	1930-1990
	WCDMA Band 2	1850-1910	1930-1990
	WCDMA Band 4	1710-1755	2110-2155
	WCDMA Band 5	824-849	869-894
	LTE Band 2	1850-1910	1930-1990
	LTE Band 4	1710-1755	2110-2155
	LTE Band 5	824-849	869-894
	LTE Band 7	2500-2570	2620-2690
	LTE Band 12	699-716	729-746
	LTE Band 17	704-716	734-746
	LTE Band 19	830-845	875-890
	WLAN 2.4G	2412-2462	
	Bluetooth	2402-2480	
GPRS Multislot Class(12)	Max Number of Timeslots in Uplink		4
	Max Number of Timeslots in Downlink		4
	Max Total Timeslot		5
EDGE Multislot Class(12)	Max Number of Timeslots in Uplink		4
	Max Number of Timeslots in Downlink		4
	Max Total Timeslot		5
Power Class	4, tested with power level 5(GSM 850)		
	1, tested with power level 0(GSM 1900)		
	3, tested with power control "all 1"(WCDMA Band 2)		
	3, tested with power control "all 1"(WCDMA Band 4)		
	3, tested with power control "all 1"(WCDMA Band 5)		
	3, tested with power control all Max.(LTE Band 2)		
	3, tested with power control all Max.(LTE Band 4)		
	3, tested with power control all Max.(LTE Band 5)		
	3, tested with power control all Max.(LTE Band 7)		
	3, tested with power control all Max.(LTE Band 12)		
	3, tested with power control all Max.(LTE Band 17)		
	3, tested with power control all Max.(LTE Band 19)		
Test Channels (low-mid-high)	128-189-251(GSM 850)		
	512-661-810(GSM 1900)		
	9262-9400-9538(WCDMA Band 2)		

1312-1413-1513(WCDMA Band 4)
4132-4182-4233(WCDMA Band 5)
18607-18900-19193(LTE Band 2 BW=1.4MHz)
18615-18900-19185(LTE Band 2 BW=3MHz)
18625-18900-19175(LTE Band 2 BW=5MHz)
18650-18900-19150(LTE Band 2 BW=10MHz)
18675-18900-19125(LTE Band 2 BW=15MHz)
18700-18900-19100(LTE Band 2 BW=20MHz)
19957-20175-20393(LTE Band 4 BW=1.4MHz)
19965-20175-20385(LTE Band 4 BW=3MHz)
19975-20175-20375(LTE Band 4 BW=5MHz)
20000-20175-20350(LTE Band 4 BW=10MHz)
20025-20175-20325(LTE Band 4 BW=15MHz)
20050-20175-20300(LTE Band 4 BW=20MHz)
20407-20525-20643(LTE Band 5 BW=1.4MHz)
20415-20525-20635(LTE Band 5 BW=3MHz)
20425-20525-20625(LTE Band 5 BW=5MHz)
20450-20525-20600(LTE Band 5 BW=10MHz)
20775-21100-21425(LTE Band 7 BW=5MHz)
20800-21100-21400(LTE Band 7 BW=10MHz)
20825-21100-21375(LTE Band 7 BW=15MHz)
20850-21100-21350(LTE Band 7 BW=20MHz)
23017-23095-23173 (LTE Band 12 BW=1.4MHz)
23025-23095-23165 (LTE Band 12 BW=3MHz)
23035-23095-23155 (LTE Band 12 BW=5MHz)
23060-23095-23130 (LTE Band 12 BW=10MHz)
23755-23790-23825(LTE Band 17 BW=5MHz)
23780-23790-23800(LTE Band 17 BW=10MHz)
24025-24075-24125(LTE Band 19 BW=5MHz)
24050-24075-24100(LTE Band 19 BW=10MHz)
24075 (LTE Band 19 BW=15MHz)
1-3-6-9-11(WLAN 2.4G)

1.4. Test specification(s)


FCC 47 CFR Part 2(2.1093)
ANSI/IEEE C95.1-1992
IEEE Std 1528-2013
KDB 865664 D01 SAR measurement 100 MHz to 6 GHz
KDB 865664 D02 RF Exposure Reporting
KDB 447498 D01 General RF Exposure Guidance
KDB 248227 D01 802.11 Wi-Fi SAR
KDB 941225 D01 3G SAR Procedures
KDB 941225 D05 SAR for LTE Devices
KDB 941225 D06 Hotspot SAR
KDB 648474 D04 Handset SAR

1.5. Ambient Condition

Ambient temperature	20°C – 24°C
Relative Humidity	30% – 70%

2. SAR Measurement System

2.1. SATIMO SAR Measurement Set-up Diagram



These measurements were performed with the automated near-field scanning system OPENSAR from SATIMO. The system is based on a high precision robot (working range: 901 mm), which positions the probes with a positional repeatability of better than ± 0.03 mm. The SAR measurements were conducted with dosimetric probe (manufactured by SATIMO), designed in the classical triangular configuration and optimized for dosimetric evaluation.

The first step of the field measurement is the evaluation of the voltages induced on the probe by the device under test. Probe diode detectors are nonlinear. Below the diode compression point, the output voltage is proportional to the square of the applied E-field; above the diode compression point, it is linear to the applied E-field. The compression point depends on the diode, and a calibration procedure is necessary for each sensor of the probe.

The Keithley multimeter reads the voltage of each sensor and send these three values to the PC. The corresponding E field value is calculated using the probe calibration factors, which are stored in the working directory. This evaluation includes linearization of the diode characteristics. The field calculation is done separately for each sensor. Each component of the E field is displayed on the "Dipole Area Scan Interface" and the total E field is displayed on the "3D Interface"

2.2. Robot

The SATIMO SAR system uses the high precision robots from KUKA. For the 6-axis controller system, the robot controller version (KUKA) from KUKA is used. The KUKA robot series have many features that are important for our application:



- High precision (repeatability ± 0.03 mm)
- High reliability (industrial design)
- Jerk-free straight movements
- Low ELF interference (the closed metallic construction shields against motor control fields)

2.3. E-Field Probe

This E-field detection probe is composed of three orthogonal dipoles linked to special Schottky diodes with low detection thresholds. The probe allows the measurement of electric fields in liquids such as the one defined in the IEEE and CENELEC standards.

For the measurements the Specific Dosimetric E-Field Probe SN 41/18 EPGO330 with following specifications is used



- Dynamic range: 0.01-100 W/kg
 - Tip Diameter: 2.5 mm
 - Distance between probe tip and sensor center: 1 mm
 - Distance between sensor center and the inner phantom surface: 2 mm (repeatability better than ± 1 mm).
 - Probe linearity: ± 0.10 dB
 - Axial isotropy: 0.06 dB
 - Hemispherical Isotropy: 0.09 dB
 - Calibration range: 650MHz to 5900MHz for head & body simulating liquid.
 - Lower detection limit: 9mW/kg
- Angle between probe axis (evaluation axis) and surface normal line: less than 30° .

2.3.1. E-Field Probe Calibration

Each probe needs to be calibrated according to a dosimetric assessment procedure with accuracy better than $\pm 10\%$. The spherical isotropy shall be evaluated and within ± 0.25 dB. The sensitivity parameters (Norm X, Norm Y, and Norm Z), the diode compression parameter (DCP) and the conversion factor (Conv F) of the probe are tested. The calibration data can be referred to appendix D of this report.

2.4. SAM phantoms

Photo of SAM phantom SN 16/15 SAM119




The SAM phantom is used to measure the SAR relative to people exposed to electro-magnetic field radiated by mobile phones.

The test, based on ultrasonic system, allows measuring the thickness with an accuracy of 10 μm .

2.5. Device Holder

The positioning system allows obtaining cheek and tilting position with a very good accuracy. In compliance with CENELEC, the tilt angle uncertainty is lower than 1 degree.



Serial Number	Holder Material	Permittivity	Loss Tangent
SN 16/15 MSH100	Delrin	3.7	0.005

2.6. Test Equipment List

This table gives a complete overview of the SAR measurement equipment.

Devices used during the test described are marked ☒

	Manufacturer	Name of Equipment	Type/Model	Serial Number	Calibration	
					Last Cal.	Due Date
☒	MVG	E FIELD PROBE	SSE2	SN 41/18 EPG0330	May 21, 2019	May 20, 2020
☒	MVG	750 MHz Dipole	SID750	SN 03/15 DIP 0G750-355	Apr. 19, 2018	Apr. 18, 2021
☒	MVG	835 MHz Dipole	SID835	SN 03/15 DIP 0G835-347	Apr. 19, 2018	Apr. 18, 2021
☐	MVG	900 MHz Dipole	SID900	SN 03/15 DIP 0G900-348	Apr. 19, 2018	Apr. 18, 2021
☒	MVG	1800 MHz Dipole	SID1800	SN 03/15 DIP 1G800-349	Apr. 19, 2018	Apr. 18, 2021
☒	MVG	1900 MHz Dipole	SID1900	SN 03/15 DIP 1G900-350	Apr. 19, 2018	Apr. 18, 2021
☐	MVG	2000 MHz Dipole	SID2000	SN 03/15 DIP 2G000-351	Apr. 19, 2018	Apr. 18, 2021
☒	MVG	2450 MHz Dipole	SID2450	SN 03/15 DIP 2G450-352	Apr. 19, 2018	Apr. 18, 2021
☒	MVG	2600 MHz Dipole	SID2600	SN 03/15 DIP 2G600-356	Apr. 19, 2018	Apr. 18, 2021
☐	MVG	5000 MHz Dipole	SWG5500	SN 13/14 WGA 33	Apr. 19, 2018	Apr. 18, 2021
☒	MVG	Liquid measurement Kit	SCLMP	SN 21/15 OCPG 72	NCR	NCR
☒	MVG	Power Amplifier	N.A	AMPLISAR_28/14_003	NCR	NCR
☒	KEITHLEY	Millivoltmeter	2000	4072790	NCR	NCR
☒	R&S	Universal radio communication tester	CMU200	117858	Aug. 06, 2019	Aug. 05, 2020
☒	R&S	Wideband radio communication tester	CMW500	103917	Aug. 28, 2019	Aug. 27, 2020
☒	HP	Network Analyzer	8753D	3410J01136	Aug. 06, 2019	Aug. 05, 2020
☒	Agilent	PSG Analog Signal Generator	E8257D	MY51110112	Aug. 06, 2019	Aug. 05, 2020

☒	Agilent	Power meter	E4419B	MY45102538	Aug. 06, 2019	Aug. 05, 2020
☒	Agilent	Power sensor	E9301A	MY41495644	Aug. 06, 2019	Aug. 05, 2020
☒	Agilent	Power sensor	E9301A	US39212148	Aug. 06, 2019	Aug. 05, 2020
☒	MCLI/USA	Directional Coupler	CB11-20	0D2L51502	Aug. 06, 2019	Aug. 05, 2020

3. SAR Measurement Procedures

The measurement procedures are as follows:

<Conducted power measurement>

- (a) For WWAN power measurement, use base station simulator to configure EUT WWAN transmission in conducted connection with RF cable, at maximum power in each supported wireless interface and frequency band.
- (b) Read the WWAN RF power level from the base station simulator.
- (c) For WLAN/Bluetooth power measurement, use engineering software to configure EUT WLAN/Bluetooth continuously transmission, at maximum RF power in each supported wireless interface and frequency band.
- (d) Connect EUT RF port through RF cable to the power meter, and measure WLAN/Bluetooth output power.

<SAR measurement>

- (a) Use base station simulator to configure EUT WWAN transmission in radiated connection, and engineering software to configure EUT WLAN/Bluetooth continuously transmission, at maximum RF power, in the highest power channel.
- (b) Place the EUT in the positions as Appendix A demonstrates.
- (c) Set scan area, grid size and other setting on the OPENSAR software.
- (d) Measure SAR results for the highest power channel on each testing position.
- (e) Find out the largest SAR result on these testing positions of each band.
- (f) Measure SAR results for other channels in worst SAR testing position if the reported SAR of highest power channel is larger than 0.8 W/kg.

According to the test standard, the recommended procedure for assessing the peak spatial-average SAR value consists of the following steps:

- (a) Power reference measurement
- (b) Area scan
- (c) Zoom scan
- (d) Power drift measurement

3.1. Power Reference

The Power Reference Measurement and Power Drift Measurements are for monitoring the power drift of the device under test in the batch process. The minimum distance of probe sensors to surface determines the closest measurement point to phantom surface. This distance cannot be smaller than the distance of sensor calibration points to probe tip as defined in the probe properties.

3.2. Area scan & Zoom scan

The area scan is a 2D scan to find the hot spot location on the DUT. The zoom scan is a 3D scan above the hot spot to calculate the 1g and 10g SAR value.

Measurement of the SAR distribution with a grid of 8 to 16 mm * 8 to 16 mm and a constant distance to the inner surface of the phantom. Since the sensors cannot directly measure at the inner phantom surface, the values between the sensors and the inner phantom surface are extrapolated. With these values the area of the maximum SAR is calculated by an interpolation scheme. Around this point, a cube of 30 * 30 * 30 mm or 32 * 32 * 32 mm is assessed by measuring 5 or 8 * 5 or 8 * 4 or 5 mm. With these data, the peak spatial-average SAR value can be calculated.

From the scanned SAR distribution, identify the position of the maximum SAR value, in addition identify the positions of any local maxima with SAR values within 2 dB of the maximum value that will not be within the zoom scan of other peaks; additional peaks shall be measured only when the primary peak is within 2 dB of the SAR compliance limit (e.g., 1 W/kg for 1,6 W/kg 1 g limit, or 1,26 W/kg for 2 W/kg, 10 g limit).

Area scan & Zoom scan scan parameters extracted from FCC KDB 865664 D01 SAR measurement 100 MHz to 6 GHz.

			≤ 3 GHz	> 3 GHz
Maximum distance from closest measurement point (geometric center of probe sensors) to phantom surface			5 ± 1 mm	$\frac{1}{2} \cdot \delta \cdot \ln(2) \pm 0.5$ mm
Maximum probe angle from probe axis to phantom surface normal at the measurement location			$30^\circ \pm 1^\circ$	$20^\circ \pm 1^\circ$
Maximum area scan spatial resolution: $\Delta x_{\text{Area}}, \Delta y_{\text{Area}}$			≤ 2 GHz: ≤ 15 mm 2 – 3 GHz: ≤ 12 mm	3 – 4 GHz: ≤ 12 mm 4 – 6 GHz: ≤ 10 mm
			When the x or y dimension of the test device, in the measurement plane orientation, is smaller than the above, the measurement resolution must be $\leq$ the corresponding x or y dimension of the test device with at least one measurement point on the test device.	
Maximum zoom scan spatial resolution: $\Delta x_{\text{Zoom}}, \Delta y_{\text{Zoom}}$			≤ 2 GHz: ≤ 8 mm 2 – 3 GHz: ≤ 5 mm *	3 – 4 GHz: ≤ 5 mm * 4 – 6 GHz: ≤ 4 mm *
Maximum zoom scan spatial resolution, normal to phantom surface	uniform grid: $\Delta z_{\text{Zoom}}(n)$		≤ 5 mm	3 – 4 GHz: ≤ 4 mm 4 – 5 GHz: ≤ 3 mm 5 – 6 GHz: ≤ 2 mm
	graded grid	$\Delta z_{\text{Zoom}}(1)$: between 1 st two points closest to phantom surface	≤ 4 mm	3 – 4 GHz: ≤ 3 mm 4 – 5 GHz: ≤ 2.5 mm 5 – 6 GHz: ≤ 2 mm
		$\Delta z_{\text{Zoom}}(n>1)$: between subsequent points	$\leq 1.5 \cdot \Delta z_{\text{Zoom}}(n-1)$	
Minimum zoom scan volume	x, y, z		≥ 30 mm	3 – 4 GHz: ≥ 28 mm 4 – 5 GHz: ≥ 25 mm 5 – 6 GHz: ≥ 22 mm

Note: δ is the penetration depth of a plane-wave at normal incidence to the tissue medium; see draft standard IEEE P1528-2011 for details.

* When zoom scan is required and the *reported* SAR from the *area scan based 1-g SAR estimation* procedures of KDB 447498 is ≤ 1.4 W/kg, ≤ 8 mm, ≤ 7 mm and ≤ 5 mm zoom scan resolution may be applied, respectively, for 2 GHz to 3 GHz, 3 GHz to 4 GHz and 4 GHz to 6 GHz.

3.3. Description of interpolation/extrapolation scheme

The local SAR inside the phantom is measured using small dipole sensing elements inside a probe body. The probe tip must not be in contact with the phantom surface in order to minimise measurements errors, but the highest local SAR will occur at the surface of the phantom.

An extrapolation is using to determinate this highest local SAR values. The extrapolation is based on a fourth-order least-square polynomial fit of measured data. The local SAR value is then extrapolated from the liquid surface with a 1 mm step.

The measurements have to be performed over a limited time (due to the duration of the battery) so the step of measurement is high. It could vary between 5 and 8 mm. To obtain an accurate assessment of the maximum SAR averaged over 10 grams and 1 gram requires a very fine resolution in the three dimensional scanned data array.

3.4. Volumetric Scan

The volumetric scan consists to a full 3D scan over a specific area. This 3D scan is useful form multi Tx SAR measurement. Indeed, it is possible with OpenSAR to add, point by point, several volumetric scan to calculate the SAR value of the combined measurement as it is define in the standard IEEE1528 and IEC62209.

3.5. Power Drift

All SAR testing is under the EUT install full charged battery and transmit maximum output power. In OpenSAR measurement software, the power reference measurement and power drift measurement procedures are used for monitoring the power drift of EUT during SAR test. Both these procedures measure the field at a specified reference position before and after the SAR testing. The software will calculate the field difference in V/m. If the power drifts more than $\pm 5\%$, the SAR will be retested.


4. System Verification Procedure

4.1. Tissue Verification

The following tissue formulations are provided for reference only as some of the parameters have not been thoroughly verified. The composition of ingredients may be modified accordingly to achieve the desired target tissue parameters required for routine SAR evaluation.

Ingredients (% of weight)	Head Tissue									
Frequency Band (MHz)	750	835	900	1800	1900	2000	2450	2600	5200	5800
Water	34.40	34.40	34.40	55.36	55.36	57.87	57.87	57.87	65.53	65.53
NaCl	0.79	0.79	0.79	0.35	0.35	0.16	0.16	0.16	0.00	0.00
1,2-Propanediol	64.81	64.81	64.81	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Triton X-100	0.00	0.00	0.00	30.45	30.45	19.97	19.97	19.97	24.24	24.24
DGBE	0.00	0.00	0.00	13.84	13.84	22.00	22.00	22.00	10.23	10.23
Ingredients (% of weight)	Body Tissue									
Frequency Band (MHz)	750	835	900	1800	1900	2000	2450	2600	5200	5800
Water	50.30	50.30	50.30	69.91	69.91	71.88	71.88	71.88	79.54	79.54
NaCl	0.60	0.60	0.60	0.13	0.13	0.16	0.16	0.16	0.00	0.00
1,2-Propanediol	49.10	49.10	49.10	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Triton X-100	0.00	0.00	0.00	9.99	9.99	19.97	19.97	19.97	11.24	11.24
DGBE	0.00	0.00	0.00	19.97	19.97	7.99	7.99	7.99	9.22	9.22

For SAR measurement of the field distribution inside the phantom, the phantom must be filled with homogeneous tissue simulating liquid to a depth of at least 15 cm. For head SAR testing, the liquid depth from the ear reference point (ERP) of the phantom to the liquid top surface is larger than 15 cm.

Photo of Liquid depth for Head Position	Photo of Liquid depth for Body Position
	

4.1.1. Tissue Dielectric Parameter Check Results

The simulating liquids should be checked at the beginning of a series of SAR measurements to determine if the dielectric parameters are within the tolerances of the specified target values. The measured conductivity and relative permittivity should be within $\pm 5\%$ of the target values.


Tissue Type	Measured Frequency (MHz)	Target Tissue		Measured Tissue		Liquid Temp.	Test Date
		ϵ_r ($\pm 5\%$)	σ (S/m) ($\pm 5\%$)	ϵ_r	σ (S/m)		
Head 750	750	41.96 (39.86~44.06)	0.89 (0.85~0.93)	41.32	0.92	21.5 °C	Sep. 23, 2019
Body 750	750	55.55 (52.77~58.33)	0.96 (0.91~1.01)	55.51	0.98	21.5 °C	Sep. 23, 2019
Head 850	835	41.50 (39.43~43.58)	0.90 (0.86~0.95)	40.72	0.93	21.6 °C	Sep. 16, 2019
Body 850	835	55.20 (52.44~57.96)	0.97 (0.92~1.02)	54.45	1.00	21.2 °C	Sep. 17, 2019
Head 1800	1800	40.00 (38.00~42.00)	1.40 (1.33~1.47)	38.56	1.40	21.0 °C	Sep. 18, 2019
Body 1800	1800	53.30 (50.64~55.97)	1.52 (1.44~1.60)	53.24	1.56	21.8 °C	Sep. 19, 2019
Head 1900	1900	40.00 (38.00~42.00)	1.40 (1.33~1.47)	40.98	1.45	21.4 °C	Sep. 18, 2019
Body 1900	1900	53.30 (50.64~55.97)	1.52 (1.44~1.60)	52.66	1.56	21.5 °C	Sep. 18, 2019
Head 2450	2450	39.20 (37.24~41.16)	1.80 (1.71~1.89)	38.96	1.83	21.5 °C	Sep. 20, 2019
Body 2450	2450	52.70 (50.07~55.34)	1.95 (1.85~2.05)	52.27	2.02	21.5 °C	Sep. 21, 2019
Head 2600	2600	39.01 (37.06~40.96)	1.96 (1.86~2.06)	38.47	2.02	21.4 °C	Sep. 19, 2019
Body 2600	2600	52.51 (49.88~55.14)	2.16 (2.05~2.27)	52.68	2.21	21.2 °C	Sep. 20, 2019

NOTE: The dielectric parameters of the tissue-equivalent liquid should be measured under similar ambient conditions and within 2 °C of the conditions expected during the SAR evaluation to satisfy protocol requirements.

4.2. System Verification Procedure

The system verification is performed for verifying the accuracy of the complete measurement system and performance of the software. The dipole is connected to the signal source consisting of signal generator and amplifier via a directional coupler, N-connector cable and adaption to SMA. It is fed with a power of 100mW (below 5GHz) or 100mW (above 5GHz). To adjust this power a power meter is used. The power sensor is connected to the cable before the system verification to measure the power at this point and do adjustments at the signal generator. At the outputs of the directional coupler both return loss as well as forward power are controlled during the system verification to make sure that emitted power at the dipole is kept constant. This can also be checked by the power drift measurement after the test (result on plot).

The system verification is shown as below picture:



4.2.1. System Verification Results

Comparing to the original SAR value provided by SATIMO, the verification data should be within its specification of $\pm 10\%$. Below table shows the target SAR and measured SAR after normalized to 1W input power. The table below indicates the system performance verification can meet the variation criterion and the plots can be referred to Appendix B of this report.

System Verification	Target SAR (1W) ($\pm 10\%$)		Measured SAR (Normalized to 1W)		Liquid Temp.	Test Date
	1-g (W/Kg)	10-g (W/Kg)	1-g (W/Kg)	10-g (W/Kg)		
750MHz Head	8.56 (7.70~9.42)	5.55 (5.00~6.11)	8.49	5.37	21.5 °C	Sep. 23, 2019
750MHz Body	8.85 (7.97~9.74)	5.91 (5.32~6.50)	8.66	5.78	21.5 °C	Sep. 23, 2019
835MHz Head	9.55 (8.60~10.51)	6.10 (5.49~6.71)	9.15	5.99	21.6 °C	Sep. 16, 2019
835MHz Body	9.83 (8.85~10.81)	6.45 (5.81~7.10)	9.46	6.12	21.2 °C	Sep. 17, 2019
1800MHz Head	38.11 (34.30~41.92)	20.05 (18.05~22.06)	36.48	20.17	21.0 °C	Sep. 18, 2019
1800MHz Body	38.13 (34.32~41.94)	20.65 (18.59~22.72)	37.16	20.01	21.8 °C	Sep. 19, 2019
1900MHz Head	38.92 (35.03~42.81)	20.09 (18.08~22.10)	36.60	21.19	21.4 °C	Sep. 18, 2019
1900MHz Body	39.02 (35.12~42.92)	20.57 (18.51~22.63)	37.21	21.39	21.5 °C	Sep. 18, 2019
2450MHz Head	53.76 (48.38~59.14)	24.12 (21.71~26.53)	53.01	24.12	21.5 °C	Sep. 20, 2019
2450MHz Body	52.90 (47.61~58.19)	24.09 (21.68~26.50)	49.01	23.30	21.5 °C	Sep. 21, 2019
2600MHz Head	55.60 (50.04~61.16)	24.60 (22.14~27.06)	52.17	23.14	21.4 °C	Sep. 19, 2019
2600MHz Body	52.49 (47.24~57.74)	23.74 (21.37~26.11)	50.44	22.28	21.2 °C	Sep. 20, 2019

5. SAR Measurement variability and uncertainty

5.1. SAR measurement variability

Per KDB865664 D01 SAR measurement 100 MHz to 6 GHz, SAR measurement variability must be assessed for each frequency band, which is determined by the SAR probe calibration point and tissue-equivalent medium used for the device measurements. The additional measurements are repeated after the completion of all measurements requiring the same head or body tissue-equivalent medium in a frequency band. The test device should be returned to ambient conditions (normal room temperature) with the battery fully charged before it is re-mounted on the device holder for the repeated measurement(s) to minimize any unexpected variations in the repeated results.

- 1) Repeated measurement is not required when the original highest measured SAR is < 0.80 W/kg; steps 2) through 4) do not apply.
- 2) When the original highest measured SAR is ≥ 0.80 W/kg, repeat that measurement once.
- 3) Perform a second repeated measurement only if the ratio of largest to smallest SAR for the original and first repeated measurements is > 1.20 or when the original or repeated measurement is ≥ 1.45 W/kg ($\sim 10\%$ from the 1-g SAR limit).
- 4) Perform a third repeated measurement only if the original, first or second repeated measurement is ≥ 1.5 W/kg and the ratio of largest to smallest SAR for the original, first and second repeated measurements is > 1.20 .

5.2. SAR measurement uncertainty

Per KDB865664 D01 SAR Measurement 100 MHz to 6 GHz, when the highest measured 1-g SAR within a frequency band is < 1.5 W/kg, the extensive SAR measurement uncertainty analysis described in IEEE Std 1528-2013 is not required in SAR reports submitted for equipment approval. The equivalent ratio (1.5/1.6) is applied to extremity and occupational exposure conditions.

6. RF Exposure Positions

6.1. Ear and handset reference point

Figure 6.1.1 shows the front, back, and side views of the SAM phantom. The center-of-mouth reference point is labeled “M”, the left ear reference point (ERP) is marked “LE”, and the right ERP is marked “RE”.



Fig 6.1.1 Front, back, and side views of SAM phantom

6.2. Definition of the cheek position

1. Define two imaginary lines on the handset, the vertical centerline and the horizontal line. The vertical centerline passes through two points on the front side of the handset: the midpoint of the width w_t of the handset at the level of the acoustic output (point A in Figure 6.2.1 and Figure 6.2.2), and the midpoint of the width w_b of the bottom of the handset (point B). The horizontal line is perpendicular to the vertical centerline and passes through the center of the acoustic output (see Figure 6.2.1). The two lines intersect at point A. Note that for many handsets, point A coincides with the center of the acoustic output; however, the acoustic output may be located elsewhere on the horizontal line. Also note that the vertical centerline is not necessarily parallel to the front face of the handset (see Figure 6.2.2), especially for clamshell handsets, handsets with flip covers, and other irregularly-shaped handsets.
2. Position the handset close to the surface of the phantom such that point A is on the (virtual) extension of the line passing through points RE and LE on the phantom (see Figure 6.2.3), such that the plane defined by the vertical centerline and the horizontal line of the handset is approximately parallel to the sagittal plane of the phantom.
3. Translate the handset towards the phantom along the line passing through RE and LE until handset point A touches the pinna at the ERP
4. While maintaining the handset in this plane, rotate it around the LE-RE line until the vertical centerline is in the plane normal to the plane containing B-M and N-F lines, i.e., the Reference Plane.
5. Rotate the handset around the vertical centerline until the handset (horizontal line) is parallel to the N-F line.

6. While maintaining the vertical centerline in the Reference Plane, keeping point A on the line passing through RE and LE, and maintaining the handset contact with the pinna, rotate the handset about the N-F line until any point on the handset is in contact with a phantom point below the pinna on the cheek. See Figure 6.2.3. The actual rotation angles should be documented in the test report.




Fig 6.2.1 Handset vertical and horizontal reference lines—"fixed case"




Fig 6.2.2 Handset vertical and horizontal reference lines—"clam-shell case"




Fig 6.2.3 cheek or touch position. The reference points for the right ear (RE), left ear (LE), and mouth (M), which establish the Reference Plane for handset positioning, are indicated.

6.3. Definition of the tilt position

1. While maintaining the orientation of the handset, retract the handset parallel to the reference plane far enough away from the phantom to enable a rotation of the device by 15 degree.
2. Rotate the Handset around the horizontal line by 15 degree (see Figure 6.3.1).
3. While maintaining the orientation of the handset, move the handset towards the phantom on a line passing through RE and LE until any part of the handset touches the ear. The tilt position is obtained when the contact is on the pinna. If the contact is at any location other than the pinna, e.g., the antenna with the back of the phantom head, the angle of the handset shall be reduced. In this case, the tilt position is obtained if any part of the handset is in contact with the pinna as well as a second part of the handset is in contact with the phantom, e.g., the antenna with the back of the head.




Figure 6.3.1 – Tilt position of the wireless device on the left side of SAM

6.4. Body Worn Accessory

1. Body-worn operating configurations are tested with the belt-clips and holsters attached to the device and positioned against a flat phantom in a normal use configuration (see Figure 6.4.1). Per KDB 648474 D04, body-worn accessory exposure is typically related to voice mode operations when handsets are carried in body-worn accessories. The body-worn accessory procedures in FCC KDB 447498 D01 should be used to test for body-worn accessory SAR compliance, without a headset connected to it. This enables the test results for such configuration to be compatible with that required for hotspot mode when the body-worn accessory test separation distance is greater than or equal to that required for hotspot mode, when applicable. When the reported SAR for body-worn accessory, measured without a headset connected to the handset is $< 1.2 \text{ W/kg}$, the highest reported SAR configuration for that wireless mode and frequency band should be repeated for that body-worn accessory with a headset attached to the handset.
2. Accessories for body-worn operation configurations are divided into two categories: those that do not contain metallic components and those that do contain metallic components and those that do contain metallic components. When multiple accessories that do not contain metallic components are supplied with the device, the device is tested with only the accessory that dictates the closest

spacing to the body. Then multiple accessories that contain metallic components are test with the device with each accessory. If multiple accessories share an identical metallic component (i.e. the same metallic belt-clip used with different holsters with no other metallic components) only the accessory that dictates the closest spacing to the body is tested.




Figure 6.4.1 – Test positions for body-worn devices

6.5. Wireless Router Devices

Some battery-operated handsets have the capability to transmit and receive user through simultaneous transmission of WLAN simultaneously with a separate licensed transmitter. The FCC has provided guidance in FCC KDB Publication 941225 D06 where SAR test considerations for handsets ($L \times W \geq 9 \text{ cm} \times 5 \text{ cm}$) are based on a composite test separation distance of 10mm from the front, back and edges of the device containing transmitting antennas within 2.5cm of their edges, determined from general mixed use conditions for this type of devices. Since the hotspot SAR results may overlap with the body-worn accessory SAR requirements, the more conservative configurations can be considered, thus excluding some body-worn accessory SAR tests.

When the user enables the personal wireless router functions for the handset, actual operations include simultaneous transmission of both the WLAN transmitter and another licensed transmitter. Both transmitters often do not transmit at the same transmitting frequency and thus cannot be evaluated for SAR under actual use conditions due to the limitations of the SAR assessment probes. Therefore, SAR must be evaluated for each frequency transmission and mode separately and spatially summed with the WLAN transmitter according to FCC KDB Publication 447498 D01 publication procedures. The “Portable Hotspot” feature on the handset was NOT activated during SAR assessments, to ensure the SAR measurements were evaluated for a single transmission frequency RF signal at a time.

7. RF Output Power

7.1. GSM Conducted Power

Band GSM850	Burst-Averaged output Power (dBm)				Frame-Averaged output Power (dBm)			
Tx Channel	Tune-up	128	189	251	Tune-up	128	189	251
Frequency (MHz)	(dBm)	824.2	836.4	848.8	(dBm)	824.2	836.4	848.8
GSM (GMSK)	33.00	32.38	32.47	32.28	23.97	23.35	23.44	23.25
GPRS(GMSK, 1 TS)	33.00	32.54	32.62	32.42	23.97	23.51	23.59	23.39
GPRS(GMSK, 2 TS)	32.00	31.79	31.84	31.61	25.98	25.77	25.82	25.59
GPRS(GMSK, 3 TS)	30.00	29.95	30.00	29.77	25.74	25.69	25.74	25.51
GPRS(GMSK, 4 TS)	29.00	28.81	28.85	28.56	25.99	25.80	25.84	25.55
EDGE(8PSK, 1 TS)	29.00	28.50	28.33	28.47	19.97	19.47	19.30	19.44
EDGE(8PSK, 2 TS)	28.00	27.11	26.84	27.02	21.98	21.09	20.82	21.00
EDGE(8PSK, 3 TS)	26.00	25.02	24.69	24.82	21.74	20.76	20.43	20.56
EDGE(8PSK, 4 TS)	24.00	23.62	23.32	23.37	20.99	20.61	20.31	20.36
Band GSM1900	Burst-Averaged output Power (dBm)				Frame-Averaged output Power (dBm)			
Tx Channel	Tune-up	512	661	810	Tune-up	512	661	810
Frequency (MHz)	(dBm)	1850.2	1880.0	1909.8	(dBm)	1850.2	1880.0	1909.8
GSM (GMSK)	29.00	28.86	28.82	28.50	19.97	19.83	19.79	19.47
GPRS(GMSK, 1 TS)	29.00	28.93	28.88	28.57	19.97	19.90	19.85	19.54
GPRS(GMSK, 2 TS)	29.00	28.20	28.13	27.83	22.98	22.18	22.11	21.81
GPRS(GMSK, 3 TS)	27.00	26.43	26.37	26.09	22.74	22.17	22.11	21.83
GPRS(GMSK, 4 TS)	26.00	25.30	25.23	24.97	22.99	22.29	22.22	21.96
EDGE(8PSK, 1 TS)	26.00	24.75	24.73	25.02	16.97	15.72	15.70	15.99
EDGE(8PSK, 2 TS)	25.00	23.79	24.05	24.19	18.98	17.77	18.03	18.17
EDGE(8PSK, 3 TS)	22.00	21.80	21.75	21.89	17.74	17.54	17.49	17.63
EDGE(8PSK, 4 TS)	21.00	20.56	20.54	20.57	17.99	17.55	17.53	17.56

Note: The frame-averaged power is linearly scaled the maximum burst averaged power over 8 time slots.

The calculated method are shown as below:

Frame-averaged power = Maximum burst averaged power (1 TS) - 9.03 dB

Frame-averaged power = Maximum burst averaged power (2 TS) - 6.02 dB

Frame-averaged power = Maximum burst averaged power (3 TS) - 4.26 dB

Frame-averaged power = Maximum burst averaged power (4 TS) - 3.01 dB

7.2. WCDMA Conducted Power

Band	WCDMA Band 2			
Tx Channel	Tune-up	9262	9400	9538
Frequency (MHz)		1852.4	1880	1907.6

RMC 12.2Kbps	24.00	23.00	23.10	23.29
HSDPA Subtest-1	23.00	22.07	22.13	22.32
HSDPA Subtest-2	22.00	21.37	21.41	21.90
HSDPA Subtest-3	21.00	20.43	20.56	20.94
HSDPA Subtest-4	21.00	20.36	20.94	20.94
HSUPA Subtest-1	22.00	21.85	21.88	21.81
HSUPA Subtest-2	23.00	22.04	22.12	22.18
HSUPA Subtest-3	22.00	20.79	20.64	21.02
HSUPA Subtest-4	23.00	22.06	22.13	22.33
HSUPA Subtest-5	22.00	21.47	21.41	21.38
Band	WCDMA Band 4			
Tx Channel	Tune-up	1312	1413	1513
Frequency (MHz)		1712.4	1732.6	1752.6
RMC 12.2Kbps	23.50	23.47	23.23	23.18
HSDPA Subtest-1	23.00	22.55	22.32	22.20
HSDPA Subtest-2	23.00	22.07	21.92	21.71
HSDPA Subtest-3	22.00	21.05	20.38	20.66
HSDPA Subtest-4	22.00	21.03	20.69	20.72
HSUPA Subtest-1	23.00	22.09	22.02	21.68
HSUPA Subtest-2	23.00	22.45	22.19	22.06
HSUPA Subtest-3	22.00	21.43	20.98	20.61
HSUPA Subtest-4	23.00	22.53	22.30	22.25
HSUPA Subtest-5	22.00	21.82	21.55	21.48
Band	WCDMA Band 5			
Tx Channel	Tune-up	4132	4182	4233
Frequency (MHz)		826.4	836.4	846.6
RMC 12.2Kbps	23.00	22.79	22.97	22.88
HSDPA Subtest-1	23.00	21.16	22.06	21.94
HSDPA Subtest-2	22.00	21.31	21.45	21.35
HSDPA Subtest-3	21.00	20.11	20.54	20.71
HSDPA Subtest-4	21.00	20.67	20.59	20.31
HSUPA Subtest-1	22.00	21.84	21.83	21.55
HSUPA Subtest-2	22.00	21.98	21.96	21.91
HSUPA Subtest-3	21.00	20.75	20.84	20.38
HSUPA Subtest-4	23.00	22.01	22.05	21.95
HSUPA Subtest-5	22.00	21.23	21.29	20.89

7.3. LTE Conducted Power

Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		
			RB Size	RB Offset		18607/1850.7	18900/1880	19193/1909.3
LTE Band 2	1.4MHz	QPSK	1	0	23.00	22.62	22.67	22.83
			1	2	23.00	22.64	22.87	22.96
			1	5	23.00	22.60	22.67	22.80
			3	0	23.00	22.64	22.72	22.93
			3	1	23.00	22.63	22.77	22.96
			3	2	23.00	22.58	22.74	22.90
			6	0	22.00	21.63	21.67	21.92
		16QAM	1	0	23.00	21.37	21.83	22.03
			1	2	23.00	21.55	21.95	22.13
			1	5	23.00	21.37	21.83	22.00
			3	0	23.00	21.77	21.91	22.12
			3	1	23.00	21.76	21.91	22.18
			3	2	23.00	21.76	21.88	22.11
			6	0	21.00	20.78	20.83	20.98
Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		
			RB Size	RB Offset		18615/1851.5	18900/1880	19185/1908.5
LTE Band 2	3MHz	QPSK	1	0	24.00	22.60	22.74	22.84
			1	7	24.00	22.87	23.00	23.10
			1	14	24.00	22.59	22.63	22.81
			8	0	22.00	21.54	21.65	21.79
			8	4	22.00	21.59	21.68	21.88
			8	7	22.00	21.54	21.62	21.87
			15	0	22.00	21.53	21.60	21.79
		16QAM	1	0	23.00	21.44	22.10	22.02
			1	7	23.00	21.69	22.45	22.23
			1	14	23.00	21.43	22.05	21.98
			8	0	21.00	20.57	20.65	20.81
			8	4	21.00	20.58	20.68	20.83
			8	7	21.00	20.54	20.63	20.79
			15	0	21.00	20.64	20.65	20.70
Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		

			RB Size	RB Offset		18625/1852.5	18900/1880	19175/1907.5
LTE Band 2	5MHz	QPSK	1	0	24.00	22.49	22.56	22.79
			1	12	24.00	22.84	22.98	23.18
			1	24	24.00	22.51	22.55	22.79
			12	0	22.00	21.53	21.62	21.80
			12	6	22.00	21.56	21.65	21.81
			12	11	22.00	21.51	21.59	21.83
			25	0	22.00	21.55	21.67	21.82
		16QAM	1	0	23.00	21.76	21.90	22.31
			1	12	23.00	22.18	22.13	22.63
			1	24	23.00	21.80	21.83	22.24
			12	0	21.00	20.50	20.70	20.83
			12	6	21.00	20.60	20.69	20.86
			12	11	21.00	20.53	20.64	20.77
			25	0	21.00	20.59	20.55	20.76
Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		
			RB Size	RB Offset		18650/1855	18900/1880	19150/1905
LTE Band 2	10MHz	QPSK	1	0	23.00	22.55	22.63	22.75
			1	24	23.00	22.70	22.78	22.94
			1	49	23.00	22.52	22.61	22.85
			25	0	22.00	21.55	21.68	21.87
			25	12	22.00	21.55	21.64	21.81
			25	24	22.00	21.61	21.66	21.92
			50	0	22.00	21.59	21.66	21.86
		16QAM	1	0	23.00	21.37	22.02	21.90
			1	24	23.00	21.42	22.11	22.10
			1	49	23.00	21.32	21.99	21.94
			25	0	21.00	20.56	20.67	20.82
			25	12	21.00	20.57	20.56	20.79
			25	24	21.00	20.59	20.65	20.80
			50	0	21.00	20.57	20.65	20.85
Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		
			RB Size	RB Offset		18675/1857.5	18900/1880	19125/1902.5
LTE Band	15MHz	QPSK	1	0	24.00	22.58	22.63	22.66
			1	37	24.00	22.82	23.02	23.04

2			1	74	24.00	22.49	22.57	22.69
			36	0	22.00	21.61	21.69	21.83
			36	18	22.00	21.62	21.67	21.86
			36	37	22.00	21.60	21.70	21.88
			75	0	22.00	21.67	21.73	21.90
		16QAM	1	0	23.00	21.93	21.78	21.76
			1	37	23.00	22.19	22.07	22.06
			1	74	23.00	21.85	21.71	21.84
			36	0	21.00	20.63	20.75	20.82
			36	18	21.00	20.67	20.75	20.82
			36	37	21.00	20.64	20.75	20.82
			75	0	21.00	20.62	20.64	20.85
Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		
			RB Size	RB Offset		18700/1860	18900/1880	19100/1900
LTE Band 2	20MHz	QPSK	1	0	23.00	22.51	22.58	22.64
			1	49	23.00	22.68	22.80	22.92
			1	99	23.00	22.50	22.59	22.74
			50	0	22.00	21.46	21.66	21.86
			50	24	22.00	21.57	21.71	21.82
			50	49	22.00	21.57	21.67	21.82
			100	0	22.00	21.54	21.63	21.79
		16QAM	1	0	23.00	21.74	21.81	21.91
			1	49	23.00	21.92	22.00	22.20
			1	99	23.00	21.70	21.77	22.02
			50	0	21.00	20.51	20.70	20.85
			50	24	21.00	20.62	20.70	20.80
			50	49	21.00	20.56	20.66	20.82
			100	0	21.00	20.58	20.67	20.79

Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		
			RB Size	RB Offset		19957/1710.7	20175/1732.5	20393/1754.3
LTE Band 4	1.4MHz	QPSK	1	0	23.00	22.82	22.68	22.41
			1	2	23.00	22.98	22.81	22.60
			1	5	23.00	22.85	22.60	22.45
			3	0	23.00	22.86	22.72	22.56
			3	1	23.00	22.96	22.74	22.55

			3	2	23.00	22.91	22.71	22.57
			6	0	22.00	21.84	21.62	21.48
		16QAM	1	0	22.00	21.71	21.80	21.69
			1	2	22.00	21.83	21.91	21.76
			1	5	22.00	21.69	21.76	21.64
			3	0	23.00	22.08	21.88	21.80
			3	1	23.00	22.14	21.94	21.80
			3	2	23.00	22.12	21.90	21.81
			6	0	22.00	21.05	20.86	20.65
Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		
			RB Size	RB Offset		19965/1711.5	20175/1732.5	20385/1753.5
LTE Band 4	3MHz	QPSK	1	0	24.00	22.80	22.69	22.60
			1	7	24.00	23.11	23.01	22.87
			1	14	24.00	22.83	22.64	22.47
			8	0	22.00	21.84	21.65	21.50
			8	4	22.00	21.87	21.68	21.51
			8	7	22.00	21.85	21.64	21.51
			15	0	22.00	21.84	21.60	21.49
		16QAM	1	0	23.00	22.06	21.53	22.04
			1	7	23.00	22.12	21.83	22.31
			1	14	23.00	22.05	21.43	21.91
			8	0	21.00	20.91	20.67	20.57
			8	4	21.00	20.91	20.70	20.61
			8	7	21.00	20.90	20.67	20.57
			15	0	21.00	20.86	20.72	20.56
Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		
			RB Size	RB Offset		19975/1712.5	20175/1732.5	20375/1752.5
LTE Band 4	5MHz	QPSK	1	0	24.00	22.81	22.54	22.48
			1	12	24.00	23.33	23.07	22.88
			1	24	24.00	22.74	22.50	22.35
			12	0	22.00	21.79	21.67	21.54
			12	6	22.00	21.87	21.67	21.53
			12	11	22.00	21.86	21.53	21.46
			25	0	22.00	21.89	21.64	21.51
		16QAM	1	0	23.00	22.34	21.83	21.77
			1	12	23.00	22.73	22.32	22.07

			1	24	23.00	22.30	21.92	21.73
			12	0	21.00	20.93	20.65	20.58
			12	6	21.00	20.95	20.71	20.67
			12	11	21.00	20.91	20.56	20.57
			25	0	21.00	20.83	20.67	20.50
Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		
			RB Size	RB Offset		20000/1715	20175/1732.5	20350/1750
LTE Band 4	10MHz	QPSK	1	0	23.00	22.85	22.64	22.55
			1	24	23.00	22.97	22.76	22.67
			1	49	23.00	22.82	22.65	22.45
			25	0	22.00	21.83	21.73	21.61
			25	12	22.00	21.93	21.69	21.57
			25	24	22.00	21.93	21.63	21.57
			50	0	22.00	21.91	21.69	21.62
		16QAM	1	0	23.00	21.74	22.10	21.74
			1	24	23.00	21.78	22.13	21.84
			1	49	23.00	21.63	22.05	21.66
			25	0	21.00	20.88	20.78	20.62
			25	12	21.00	20.90	20.72	20.62
			25	24	21.00	20.96	20.65	20.60
			50	0	21.00	20.89	20.75	20.68
Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		
			RB Size	RB Offset		20025/1717.5	20175/1732.5	20325/1747.5
LTE Band 4	15MHz	QPSK	1	0	24.00	22.78	22.65	22.51
			1	37	24.00	23.05	22.96	22.89
			1	74	24.00	22.63	22.51	22.37
			36	0	22.00	21.83	21.71	21.64
			36	18	22.00	21.84	21.72	21.65
			36	37	22.00	21.85	21.63	21.60
			75	0	22.00	21.85	21.74	21.64
		16QAM	1	0	23.00	22.25	21.80	21.67
			1	37	23.00	22.43	22.10	21.95
			1	74	23.00	22.05	21.74	21.49
			36	0	21.00	20.89	20.84	20.64
			36	18	21.00	20.94	20.80	20.62
			36	37	21.00	20.89	20.74	20.57

			75	0	21.00	20.86	20.72	20.68
Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		
			RB Size	RB Offset		20050/1720	20175/1732.5	20300/1745
LTE Band 4	20MHz	QPSK	1	0	23.00	22.71	22.64	22.57
			1	49	23.00	22.87	22.77	22.72
			1	99	23.00	22.54	22.56	22.42
			50	0	22.00	21.77	21.73	21.70
			50	24	22.00	21.81	21.71	21.64
			50	49	22.00	21.78	21.57	21.60
			100	0	22.00	21.77	21.67	21.63
		16QAM	1	0	23.00	22.08	21.85	21.81
			1	49	23.00	22.20	21.99	21.98
			1	99	23.00	21.90	21.79	21.67
			50	0	21.00	20.85	20.77	20.82
			50	24	21.00	20.93	20.74	20.70
			50	49	21.00	20.87	20.58	20.67
			100	0	21.00	20.77	20.68	20.65

Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		
			RB Size	RB Offset		20407/824.7	20525/836.5	20643/848.3
LTE Band 5	1.4MHz	QPSK	1	0	23.00	22.80	22.76	22.61
			1	2	23.00	22.93	22.89	22.78
			1	5	23.00	22.71	22.76	22.61
			3	0	23.00	22.81	22.84	22.68
			3	1	23.00	22.85	22.86	22.71
			3	2	23.00	22.82	22.84	22.67
			6	0	22.00	21.77	21.79	21.68
		16QAM	1	0	23.00	21.86	21.94	21.43
			1	2	23.00	21.99	22.06	21.59
			1	5	23.00	21.89	21.93	21.42
			3	0	23.00	21.99	22.04	21.79
			3	1	23.00	21.98	22.05	21.78
			3	2	23.00	21.96	22.03	21.80
			6	0	21.00	21.00	20.98	20.86
Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		

			RB Size	RB Offset		20415/825.5	20525/836.5	20635/847.5
LTE Band 5	3MHz	QPSK	1	0	24.00	22.82	22.81	22.71
			1	7	24.00	23.08	23.08	22.93
			1	14	24.00	22.77	22.77	22.66
			8	0	22.00	21.78	21.80	21.66
			8	4	22.00	21.80	21.81	21.77
			8	7	22.00	21.77	21.78	21.65
			15	0	22.00	21.74	21.78	21.65
		16QAM	1	0	23.00	22.12	21.97	21.51
			1	7	23.00	22.41	22.24	21.80
			1	14	23.00	22.16	21.92	21.45
			8	0	21.00	20.85	20.86	20.71
			8	4	21.00	20.88	20.87	20.71
			8	7	21.00	20.83	20.84	20.68
			15	0	21.00	20.85	20.78	20.79
Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		
			RB Size	RB Offset		20425/826.5	20525/836.5	20625/846.5
LTE Band 5	5MHz	QPSK	1	0	24.00	22.68	22.73	22.65
			1	12	24.00	23.08	23.16	23.01
			1	24	24.00	22.69	22.67	22.53
			12	0	22.00	21.73	21.78	21.69
			12	6	22.00	21.84	21.80	21.70
			12	11	22.00	21.74	21.71	21.63
			25	0	22.00	21.79	21.80	21.69
		16QAM	1	0	23.00	21.97	22.20	21.92
			1	12	23.00	22.34	22.61	22.26
			1	24	23.00	21.93	22.16	21.79
			12	0	21.00	20.81	20.88	20.71
			12	6	21.00	20.90	20.92	20.74
			12	11	21.00	20.81	20.80	20.66
			25	0	21.00	20.80	20.82	20.73
Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		
			RB Size	RB Offset		20450/829	20525/836.5	20600/844
LTE Band	10MHz	QPSK	1	0	23.00	22.75	22.80	22.72
			1	24	23.00	22.88	22.91	22.83

5			1	49	23.00	22.80	22.74	22.64
			25	0	22.00	21.85	21.88	21.80
			25	12	22.00	21.83	21.82	21.73
			25	24	22.00	21.80	21.80	21.73
			50	0	22.00	21.77	21.81	21.75
		16QAM	1	0	23.00	21.91	21.65	22.07
			1	24	23.00	22.07	21.76	22.22
			1	49	23.00	21.96	21.59	21.97
			25	0	21.00	20.84	20.92	20.84
			25	12	21.00	20.83	20.87	20.81
			25	24	21.00	20.83	20.83	20.79
			50	0	21.00	20.91	20.89	20.82

Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		
			RB Size	RB Offset		20775/2502.5	21100/2535	21425/2567.5
LTE Band 7	5MHz	QPSK	1	0	24.00	22.90	22.98	23.14
			1	12	24.00	23.19	23.51	23.45
			1	24	24.00	22.87	22.95	23.21
			12	0	23.00	21.93	21.98	22.11
			12	6	23.00	21.99	22.02	22.17
			12	11	23.00	21.98	21.98	22.16
			25	0	23.00	21.97	22.01	22.14
		16QAM	1	0	23.00	22.00	22.37	22.27
			1	12	23.00	22.46	22.76	22.70
			1	24	23.00	22.07	22.35	22.23
			12	0	22.00	20.93	21.11	21.10
			12	6	22.00	20.99	21.14	21.16
			12	11	22.00	21.03	21.03	21.14
			25	0	22.00	20.87	21.05	21.19
Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		
			RB Size	RB Offset		20800/2505	21100/2535	21400/2565
LTE Band 7	10MHz	QPSK	1	0	24.00	22.98	23.02	22.90
			1	24	24.00	23.08	23.13	22.75
			1	49	24.00	22.95	23.03	22.69
			25	0	23.00	21.98	22.11	21.73
			25	12	23.00	21.99	22.05	21.79

			25	24	23.00	22.05	22.03	21.81
			50	0	23.00	22.04	22.08	21.83
		16QAM	1	0	23.00	21.97	21.81	22.01
			1	24	23.00	22.14	21.89	22.02
			1	49	23.00	22.10	21.72	21.97
			25	0	22.00	20.90	21.06	20.74
			25	12	22.00	20.97	21.11	20.74
			25	24	22.00	21.03	21.06	20.77
			50	0	22.00	20.98	21.03	20.76
Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		
			RB Size	RB Offset		20825/2507.5	21100/2535	21375/2562.5
LTE Band 7	15MHz	QPSK	1	0	24.00	22.91	22.44	22.51
			1	37	24.00	23.27	22.83	22.81
			1	74	24.00	22.87	22.48	22.60
			36	0	23.00	22.13	21.69	21.81
			36	18	23.00	22.05	21.69	21.87
			36	37	23.00	22.06	21.66	21.87
			75	0	22.00	21.94	21.72	21.91
		16QAM	1	0	23.00	21.69	21.67	21.69
			1	37	23.00	22.13	22.07	22.10
			1	74	23.00	21.81	21.64	21.69
			36	0	21.00	20.55	20.70	20.73
			36	18	21.00	20.64	20.74	20.80
			36	37	21.00	20.61	20.71	20.79
			75	0	21.00	20.55	20.62	20.85
Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		
			RB Size	RB Offset		20850/2510	21100/2535	21350/2560
LTE Band 7	20MHz	QPSK	1	0	23.00	22.34	22.44	22.47
			1	49	23.00	22.53	22.74	22.80
			1	99	23.00	22.36	22.49	22.64
			50	0	22.00	21.51	21.58	21.68
			50	24	22.00	21.58	21.62	21.77
			50	49	22.00	21.55	21.51	21.75
			100	0	22.00	21.54	21.56	21.70
		16QAM	1	0	23.00	21.48	21.70	21.80
			1	49	23.00	21.76	21.92	22.07

			1	99	23.00	21.63	21.69	21.83
			50	0	21.00	20.46	20.65	20.73
			50	24	21.00	20.51	20.68	20.81
			50	49	21.00	20.53	20.64	20.79
			100	0	21.00	20.52	20.58	20.77

Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		
			RB Size	RB Offset		23017/699.7	23095/707.5	23173/715.3
LTE Band 12	1.4MHz	QPSK	1	0	23.00	22.51	22.51	22.40
			1	2	23.00	22.78	22.64	22.56
			1	5	23.00	22.54	22.52	22.33
			3	0	23.00	22.62	22.60	22.52
			3	1	23.00	22.64	22.60	22.53
			3	2	23.00	22.58	22.52	22.50
			6	0	22.00	21.59	21.54	21.51
		16QAM	1	0	22.00	21.42	21.78	21.61
			1	2	22.00	21.57	21.90	21.78
			1	5	22.00	21.50	21.81	21.51
			3	0	22.00	21.77	21.86	21.79
			3	1	22.00	21.80	21.89	21.83
			3	2	22.00	21.89	21.84	21.75
			6	0	21.00	20.69	20.76	20.64
Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		
			RB Size	RB Offset		23025/700.5	23095/707.5	23165/714.5
LTE Band 12	3MHz	QPSK	1	0	23.00	22.57	22.54	22.45
			1	7	23.00	22.96	22.75	22.72
			1	14	23.00	22.61	22.41	22.43
			8	0	22.00	21.56	21.56	21.52
			8	4	22.00	21.63	21.57	21.56
			8	7	22.00	21.64	21.53	21.53
			15	0	22.00	21.61	21.55	21.49
		16QAM	1	0	23.00	21.45	22.08	21.72
			1	7	23.00	21.80	22.30	21.99
			1	14	23.00	21.53	21.98	21.57
			8	0	21.00	20.51	20.58	20.53
			8	4	21.00	20.60	20.61	20.53

			8	7	21.00	20.62	20.58	20.48
			15	0	21.00	20.68	20.59	20.43
Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		
			RB Size	RB Offset		23035/701.5	23095/707.5	23155/713.5
LTE Band 12	5MHz	QPSK	1	0	24.00	22.51	22.44	22.37
			1	12	24.00	23.05	22.85	22.74
			1	24	24.00	22.62	22.43	22.31
			12	0	22.00	21.54	21.52	21.54
			12	6	22.00	21.69	21.61	21.55
			12	11	22.00	21.65	21.60	21.50
			25	0	22.00	21.64	21.63	21.56
		16QAM	1	0	23.00	22.03	21.88	21.79
			1	12	23.00	22.56	22.23	22.15
			1	24	23.00	22.16	21.81	21.63
			12	0	21.00	20.63	20.57	20.55
			12	6	21.00	20.73	20.59	20.66
			12	11	21.00	20.68	20.58	20.59
			25	0	21.00	20.61	20.63	20.52
Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		
			RB Size	RB Offset		23060/704	23095/707.5	23130/711
LTE Band 12	10MHz	QPSK	1	0	23.00	22.58	22.60	22.52
			1	24	23.00	22.74	22.61	22.58
			1	49	23.00	22.54	22.51	22.40
			25	0	22.00	21.70	21.66	21.59
			25	12	22.00	21.67	21.66	21.63
			25	24	22.00	21.71	21.74	21.61
			50	0	22.00	21.72	21.70	21.65
		16QAM	1	0	23.00	21.49	22.00	21.80
			1	24	23.00	21.67	22.17	21.81
			1	49	23.00	21.49	21.99	21.49
			25	0	21.00	20.70	20.75	20.45
			25	12	21.00	20.68	20.68	20.54
			25	24	21.00	20.71	20.73	20.63
			50	0	21.00	20.70	20.72	20.60

Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		
			RB Size	RB Offset		23755/706.5	23790/710	23825/713.5
LTE Band 17	5MHz	QPSK	1	0	23.00	22.57	22.56	22.49
			1	12	23.00	22.98	22.94	22.93
			1	24	23.00	22.53	22.53	22.45
			12	0	22.00	21.71	21.65	21.61
			12	6	22.00	21.73	21.67	21.68
			12	11	22.00	21.71	21.65	21.53
			25	0	22.00	21.72	21.67	21.61
		16QAM	1	0	23.00	22.00	22.13	21.87
			1	12	23.00	22.34	22.56	22.17
			1	24	23.00	21.93	22.08	21.76
			12	0	21.00	20.76	20.69	20.59
			12	6	21.00	20.77	20.71	20.64
			12	11	21.00	20.72	20.65	20.55
			25	0	21.00	20.67	20.63	20.62
Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		
			RB Size	RB Offset		23780/709	23790/710	23800/711
LTE Band 17	10MHz	QPSK	1	0	23.00	22.63	22.59	22.60
			1	24	23.00	22.74	22.71	22.71
			1	49	23.00	22.52	22.52	22.52
			25	0	22.00	21.69	21.68	21.67
			25	12	22.00	21.69	21.67	21.68
			25	24	22.00	21.71	21.70	21.66
			50	0	22.00	21.68	21.71	21.65
		16QAM	1	0	23.00	22.09	21.82	21.56
			1	24	23.00	22.18	21.93	21.61
			1	49	23.00	21.91	21.72	21.40
			25	0	21.00	20.68	20.65	20.63
			25	12	21.00	20.72	20.71	20.59
			25	24	21.00	20.71	20.67	20.62
			50	0	21.00	20.69	20.68	20.63

Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		
			RB Size	RB Offset		24025/832.5	24075/837.5	24125/842.5
LTE Band 19	5MHz	QPSK	1	0	23.00	22.64	22.19	22.08
			1	12	23.00	22.01	22.56	22.46
			1	24	23.00	22.60	22.05	22.08
			12	0	22.00	21.70	21.22	21.11
			12	6	22.00	21.74	21.38	21.18
			12	11	22.00	21.63	21.22	21.10
			25	0	22.00	21.70	21.33	21.15
		16QAM	1	0	23.00	21.85	21.39	21.57
			1	12	23.00	22.06	21.76	22.01
			1	24	23.00	21.57	21.30	21.48
			12	0	21.00	20.61	20.32	20.23
			12	6	21.00	20.78	20.31	20.26
			12	11	21.00	20.66	20.25	20.19
			25	0	21.00	20.72	20.21	20.17
Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		
			RB Size	RB Offset		24050/835	24075/837.5	24100/840
LTE Band 19	10MHz	QPSK	1	0	23.00	22.67	22.18	22.16
			1	24	23.00	22.57	22.30	22.26
			1	49	23.00	22.16	22.10	22.09
			25	0	22.00	21.54	21.17	21.21
			25	12	22.00	21.61	21.15	21.17
			25	24	22.00	21.57	21.12	21.09
			50	0	22.00	21.41	21.15	21.14
		16QAM	1	0	22.00	21.30	21.02	21.51
			1	24	22.00	21.43	21.14	21.63
			1	49	22.00	21.30	20.95	21.42
			25	0	21.00	20.25	20.23	20.24
			25	12	21.00	20.27	20.21	20.20
			25	24	21.00	20.34	20.15	20.20
			50	0	21.00	20.30	20.18	20.19
Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		
			RB	RB		24075/837.5		

			Size	Offset		
LTE Band 19	15MHz	QPSK	1	0	23.00	22.67
			1	37	23.00	22.97
			1	74	23.00	22.53
			36	0	22.00	21.68
			36	18	22.00	21.69
			36	37	22.00	21.60
			75	0	22.00	21.68
		16QAM	1	0	23.00	21.82
			1	37	23.00	22.07
			1	74	23.00	21.54
			36	0	21.00	20.81
			36	18	21.00	20.81
			36	37	21.00	20.74
			75	0	21.00	20.75

7.4. WLAN & Bluetooth Output Power

7.4.1. Output Power Results Of WLAN

Mode	Channel	Frequency (MHz)	Tune-up	Output Power (dBm)
802.11b	1	2412	15.00	14.07
	6	2437	15.00	14.81
	11	2462	15.00	14.26
802.11g	1	2412	13.00	11.97
	6	2437	13.00	11.90
	11	2462	13.00	12.26
802.11n HT20	1	2412	13.00	11.70
	6	2437	13.00	12.25
	11	2462	13.00	12.40
802.11n HT40	3	2422	12.00	10.70
	6	2437	12.00	10.98
	9	2452	12.00	11.10


NOTE: Power measurement results of WLAN 2.4G.

7.4.2. Output Power Results Of Bluetooth

BR+EDR	Output Power (dBm)				
	Channel	Tune-up	Data Rates		
			1M	2M	3M
	0CH	7.000	6.842	5.683	5.939
	39CH	7.000	6.827	6.128	6.318
	78CH	6.000	5.320	4.766	4.879

BLE	Channel	Tune-up	Output Power (dBm)
	0CH	7.000	6.430
	19CH	7.000	6.768
	39CH	7.000	5.306

8. Antenna Location



Distance of the Antenna to the EUT surface/edge						
Antennas	Front Side	Back Side	Left Side	Right Side	Top Side	Bottom Side
WWAN Main	≤ 25mm	≤ 25mm	≤ 25mm	≤ 25mm	>25mm	≤ 25mm
WLAN & Bluetooth	≤ 25mm	≤ 25mm	>25mm	≤ 25mm	≤ 25mm	>25mm
Positions for SAR tests						
Antennas	Front Side	Back Side	Left Side	Right Side	Top Side	Bottom Side
WWAN Main	Yes	Yes	Yes	Yes	NO	Yes
WLAN & Bluetooth	Yes	Yes	NO	Yes	Yes	NO

9. Stand-alone SAR test exclusion

Refer to FCC KDB 447498D01, the 1-g SAR and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f_{\text{(GHz)}}}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where:

- $f_{\text{(GHz)}}$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

Mode	P_{max} (dBm)	P_{max} (mW)	Distance (mm)	f (GHz)	Calculation Result	SAR Exclusion threshold	SAR test exclusion
Bluetooth	7.00	5.01	5	2.480	1.58	3.0	Yes

NOTE: Standalone SAR test exclusion for Bluetooth

When standalone SAR test exclusion applies to an antenna that transmits simultaneously with other antennas, the standalone SAR must be estimated according to following to determine simultaneous transmission SAR test exclusion:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f_{\text{(GHz)}}}/x] \text{ W/kg}$ for test separation distances $\leq 50\text{mm}$, where $x = 7.5$ for 1-g SAR and $x = 18.75$ for 10-g SAR.

When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

Mode	Position	P_{max} (dBm)	P_{max} (mW)	Distance (mm)	f (GHz)	x	Estimated SAR (W/Kg)
Bluetooth	Head	7.00	5.01	5	2.480	7.5	0.210
Bluetooth	Body	7.00	5.01	10	2.480	7.5	0.105
Bluetooth	Hotspot	7.00	5.01	10	2.480	7.5	0.105

NOTE: Estimated SAR calculation for Bluetooth

10. SAR Results

10.1. SAR measurement results

10.1.1. SAR measurement Result of GSM850

Test Position of Head	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
Left Cheek	189/836.4	GPRS(GMSK 4TS)	0.275	0.206	0.91	28.85	29.00	0.285
Left Tilt 15 Degree	189/836.4	GPRS(GMSK 4TS)	0.131	0.095	3.46	28.85	29.00	0.136
Right Cheek	189/836.4	GPRS(GMSK 4TS)	0.253	0.184	3.84	28.85	29.00	0.262
Right Tilt 15 Degree	189/836.4	GPRS(GMSK 4TS)	0.123	0.097	-2.16	28.85	29.00	0.127

NOTE: Head SAR test results of GSM850.

Test Position of Body-Worn with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
Front Side	189/836.4	GPRS(GMSK 4TS)	0.481	0.355	1.67	28.85	29.00	0.498
Back Side	189/836.4	GPRS(GMSK 4TS)	0.502	0.374	-0.65	28.85	29.00	0.520

NOTE: Body-Worn SAR test results of GSM850

Test Position of Hotspot with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
Front Side	189/836.4	GPRS(GMSK 4TS)	0.481	0.355	1.67	28.85	29.00	0.498
Back Side	189/836.4	GPRS(GMSK 4TS)	0.502	0.374	-0.65	28.85	29.00	0.520
Left Side	189/836.4	GPRS(GMSK 4TS)	0.466	0.341	-3.14	28.85	29.00	0.482
Right Side	189/836.4	GPRS(GMSK 4TS)	0.497	0.370	4.31	28.85	29.00	0.514
Bottom Side	189/836.4	GPRS(GMSK 4TS)	0.394	0.296	-4.42	28.85	29.00	0.408

NOTE: Hotspot SAR test results of GSM850

10.1.2. SAR measurement Result of GSM1900

Test Position of Head	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
Left Cheek	661/1880	GPRS(GMSK 4TS)	0.265	0.149	3.32	25.23	26.00	0.316
Left Tilt 15 Degree	661/1880	GPRS(GMSK 4TS)	0.134	0.075	4.36	25.23	26.00	0.160
Right Cheek	661/1880	GPRS(GMSK 4TS)	0.247	0.139	-2.42	25.23	26.00	0.295
Right Tilt 15 Degree	661/1880	GPRS(GMSK 4TS)	0.123	0.069	-0.90	25.23	26.00	0.147

NOTE: Head SAR test results of GSM1900

Test Position of Body-Worn with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
Front Side	661/1880	GPRS(GMSK 4TS)	0.341	0.180	0.38	25.23	26.00	0.407
Back Side	661/1880	GPRS(GMSK 4TS)	0.365	0.200	0.16	25.23	26.00	0.436

NOTE: Body-Worn SAR test results of GSM1900

Test Position of Hotspot with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
Front Side	661/1880	GPRS(GMSK 4TS)	0.341	0.180	0.38	25.23	26.00	0.407
Back Side	661/1880	GPRS(GMSK 4TS)	0.365	0.200	0.16	25.23	26.00	0.436
Left Side	661/1880	GPRS(GMSK 4TS)	0.300	0.161	-0.16	25.23	26.00	0.358
Right Side	661/1880	GPRS(GMSK 4TS)	0.281	0.158	2.93	25.23	26.00	0.336
Bottom Side	661/1880	GPRS(GMSK 4TS)	0.266	0.144	1.76	25.23	26.00	0.318

NOTE: Hotspot SAR test results of GSM1900

10.1.3. SAR measurement Result of WCDMA Band 2

Test Position of Head	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
Left Cheek	9400/1880	RMC12.2K	0.367	0.209	1.700	23.10	24.00	0.452
Left Tilt 15 Degree	9400/1880	RMC12.2K	0.187	0.109	0.63	23.10	24.00	0.230
Right Cheek	9400/1880	RMC12.2K	0.341	0.192	-4.28	23.10	24.00	0.420
Right Tilt 15 Degree	9400/1880	RMC12.2K	0.175	0.097	2.84	23.10	24.00	0.215

NOTE: Head SAR test results of WCDMA Band 2

Test Position of Body-Worn with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
Front Side	9400/1880	RMC12.2K	0.418	0.251	2.19	23.10	24.00	0.514
Back Side	9400/1880	RMC12.2K	0.537	0.329	-0.28	23.10	24.00	0.661

NOTE: Body-Worn SAR test results of WCDMA Band 2

Test Position of Hotspot with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
Front Side	9400/1880	RMC12.2K	0.418	0.251	2.19	23.10	24.00	0.514
Back Side	9400/1880	RMC12.2K	0.537	0.329	-0.28	23.10	24.00	0.661
Left Side	9400/1880	RMC12.2K	0.496	0.307	-3.97	23.10	24.00	0.610
Right Side	9400/1880	RMC12.2K	0.317	0.196	2.53	23.10	24.00	0.390
Bottom Side	9400/1880	RMC12.2K	0.421	0.246	0.14	23.10	24.00	0.518

NOTE: Hotspot SAR test results of WCDMA Band 2

10.1.4. SAR measurement Result of WCDMA Band 4

Test Position of Head	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
Left Cheek	1413/1732.6	RMC12.2K	0.520	0.315	0.26	23.23	23.50	0.553
Left Tilt 15 Degree	1413/1732.6	RMC12.2K	0.267	0.163	-4.44	23.23	23.50	0.284
Right Cheek	1413/1732.6	RMC12.2K	0.416	0.252	-2.10	23.23	23.50	0.443
Right Tilt 15 Degree	1413/1732.6	RMC12.2K	0.208	0.126	0.95	23.23	23.50	0.221

NOTE: Head SAR test results of WCDMA Band 4

Test Position of Body-Worn with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
Front Side	1413/1732.6	RMC12.2K	0.330	0.217	-3.22	23.23	23.50	0.351
Back Side	1413/1732.6	RMC12.2K	1.045	0.723	-0.05	23.23	23.50	1.112
Back Side Repeated	1413/1732.6	RMC12.2K	1.043	0.729	1.34	23.23	23.50	1.110
Back Side	1312/1712.4	RMC12.2K	0.962	0.619	-1.48	23.47	23.50	0.969
Back Side	1513/1752.6	RMC12.2K	0.996	0.672	-1.30	23.18	23.50	1.072

NOTE: Body-Worn SAR test results of WCDMA Band 4

Test Position of Hotspot with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
Front Side	1413/1732.6	RMC12.2K	0.330	0.217	-3.22	23.23	23.50	0.351
Back Side	1413/1732.6	RMC12.2K	1.045	0.723	-0.05	23.23	23.50	1.112
Back Side Repeated	1413/1732.6	RMC12.2K	1.043	0.729	1.34	23.23	23.50	1.110
Left Side	1413/1732.6	RMC12.2K	0.421	0.262	-4.48	23.23	23.50	0.448
Right Side	1413/1732.6	RMC12.2K	0.207	0.135	-2.63	23.23	23.50	0.220
Bottom Side	1413/1732.6	RMC12.2K	0.406	0.255	-0.48	23.23	23.50	0.432
Back Side	1312/1712.4	RMC12.2K	0.962	0.619	-1.48	23.47	23.50	0.969
Back Side	1513/1752.6	RMC12.2K	0.996	0.672	-1.30	23.18	23.50	1.072

NOTE: Hotspot SAR test results of WCDMA Band 4

10.1.5. SAR measurement Result of WCDMA Band 5

Test Position of Head	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
Left Cheek	4182/836.4	RMC12.2K	0.124	0.100	-0.54	22.97	23.00	0.125
Left Tilt 15 Degree	4182/836.4	RMC12.2K	0.065	0.057	-1.38	22.97	23.00	0.065
Right Cheek	4182/836.4	RMC12.2K	0.101	0.089	-2.62	22.97	23.00	0.102
Right Tilt 15 Degree	4182/836.4	RMC12.2K	0.049	0.043	-3.30	22.97	23.00	0.049

NOTE: Head SAR test results of WCDMA Band 5

Test Position of Body-Worn with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
Front Side	4182/836.4	RMC12.2K	0.157	0.128	-1.85	22.97	23.00	0.158
Back Side	4182/836.4	RMC12.2K	0.213	0.165	-0.07	22.97	23.00	0.214

NOTE: Body-Worn SAR test results of WCDMA Band 5

Test Position of Hotspot with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
Front Side	4182/836.4	RMC12.2K	0.157	0.128	-1.85	22.97	23.00	0.158
Back Side	4182/836.4	RMC12.2K	0.213	0.165	-0.07	22.97	23.00	0.214
Left Side	4182/836.4	RMC12.2K	0.166	0.121	0.99	22.97	23.00	0.167
Right Side	4182/836.4	RMC12.2K	0.189	0.146	-1.09	22.97	23.00	0.190
Bottom Side	4182/836.4	RMC12.2K	0.123	0.098	1.58	22.97	23.00	0.124

NOTE: Hotspot SAR test results of WCDMA Band 5

10.1.6. SAR measurement Result of LTE Band 2

Test Position of Head	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
1RB								
Left Cheek	18900/1880	15M QPSK(1,37)	0.291	0.167	1.00	23.02	24.00	0.365
Left Tilt 15 Degree	18900/1880	15M QPSK(1,37)	0.145	0.167	-4.47	23.02	24.00	0.182
Right Cheek	18900/1880	15M QPSK(1,37)	0.257	0.083	-4.99	23.02	24.00	0.322
Right Tilt 15 Degree	18900/1880	15M QPSK(1,37)	0.149	0.147	-4.92	23.02	24.00	0.187
50%RB								
Left Cheek	18900/1880	1.4M QPSK(3,1)	0.157	0.105	4.54	22.77	23.00	0.166
Left Tilt 15 Degree	18900/1880	1.4M QPSK(3,1)	0.078	0.049	-1.40	22.77	23.00	0.082
Right Cheek	18900/1880	1.4M QPSK(3,1)	0.129	0.075	-4.45	22.77	23.00	0.136
Right Tilt	18900/1880	1.4M QPSK(3,1)	0.067	0.030	4.59	22.77	23.00	0.071

15 Degree								
-----------	--	--	--	--	--	--	--	--

NOTE: Head SAR test results of LTE Band 2

Test Position of Body-Worn with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
1RB								
Front Side	18900/1880	15M QPSK(1,37)	0.328	0.202	2.34	23.02	24.00	0.411
Back Side	18900/1880	15M QPSK(1,37)	0.574	0.351	-1.11	23.02	24.00	0.719
50%RB								
Front Side	18900/1880	1.4M QPSK(3,1)	0.188	0.134	-0.88	22.77	23.00	0.198
Back Side	18900/1880	1.4M QPSK(3,1)	0.410	0.251	3.00	22.77	23.00	0.432

NOTE: Body-Worn SAR test results of LTE Band 2

Test Position of Hotspot with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conduc ted power (dBm)	Tune-u p power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
1RB								
Front Side	18900/1880	15M QPSK(1,37)	0.328	0.202	2.34	23.02	24.00	0.411
Back Side	18900/1880	15M QPSK(1,37)	0.574	0.351	-1.11	23.02	24.00	0.719
Left Side	18900/1880	15M QPSK(1,37)	0.162	0.097	-1.01	23.02	24.00	0.203
Right Side	18900/1880	15M QPSK(1,37)	0.227	0.135	-1.96	23.02	24.00	0.284
Bottom Side	18900/1880	15M QPSK(1,37)	0.473	0.284	1.57	23.02	24.00	0.593
50%RB								
Front Side	18900/1880	1.4M QPSK(3,1)	0.188	0.134	-0.88	22.77	23.00	0.198
Back Side	18900/1880	1.4M QPSK(3,1)	0.410	0.251	3.00	22.77	23.00	0.432
Left Side	18900/1880	1.4M QPSK(3,1)	0.111	0.079	2.90	22.77	23.00	0.117
Right Side	18900/1880	1.4M QPSK(3,1)	0.146	0.105	2.51	22.77	23.00	0.154
Bottom Side	18900/1880	1.4M QPSK(3,1)	0.287	0.173	0.51	22.77	23.00	0.303

NOTE: Hotspot SAR test results of LTE Band 2

10.1.7. SAR measurement Result of LTE Band 4

Test Position of Head	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
1RB								
Left Cheek	20175/1732.5	15M QPSK(1,37)	0.351	0.220	-1.09	22.96	24.00	0.446
Left Tilt 15 Degree	20175/1732.5	15M QPSK(1,37)	0.177	0.116	-4.57	22.96	24.00	0.225
Right Cheek	20175/1732.5	15M QPSK(1,37)	0.307	0.198	-2.36	22.96	24.00	0.390
Right Tilt 15 Degree	20175/1732.5	15M QPSK(1,37)	0.153	0.090	-1.86	22.96	24.00	0.194
50%RB								
Left Cheek	20175/1732.5	1.4M QPSK(3,2)	0.309	0.199	-3.41	22.71	23.00	0.330
Left Tilt 15 Degree	20175/1732.5	1.4M QPSK(3,2)	0.159	0.091	-1.01	22.71	23.00	0.170
Right Cheek	20175/1732.5	1.4M QPSK(3,2)	0.255	0.155	-2.49	22.71	23.00	0.273
Right Tilt 15 Degree	20175/1732.5	1.4M QPSK(3,2)	0.127	0.073	3.53	22.71	23.00	0.136

NOTE: Head SAR test results of LTE Band 4

Test Position of Body-Worn with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
1RB								
Front Side	20175/1732.5	15M QPSK(1,37)	0.439	0.288	2.33	22.96	24.00	0.558
Back Side	20175/1732.5	15M QPSK(1,37)	0.909	0.625	-1.04	22.96	24.00	1.155
Back Side	20025/1717.5	15M QPSK(1,37)	0.898	0.589	-1.59	23.05	24.00	1.118

Back Side	20325/1747. 5	15M QPSK(1,37)	0.922	0.651	-1.53	22.89	24.00	1.191
Back Side Repeated	20325/1747. 5	15M QPSK(1,37)	0.915	0.631	-0.79	22.89	24.00	1.181
50%RB								
Front Side	20175/1732. 5	1.4M QPSK(3,2)	0.361	0.229	-3.31	22.71	23.00	0.386
Back Side	20175/1732. 5	1.4M QPSK(3,2)	0.551	0.342	2.52	22.71	23.00	0.589
100%RB								
Back Side	20175/1732. 5	20M QPSK(100,0)	0.335	0.209	-3.28	21.67	22.00	0.361

NOTE: Body-Worn SAR test results of LTE Band 4

Test Position of Hotspot with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conduc ted power (dBm)	Tune-u p power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
1RB								
Front Side	20175/1732.5	15M QPSK(1,37)	0.439	0.288	2.33	22.96	24.00	0.558
Back Side	20175/1732.5	15M QPSK(1,37)	0.909	0.625	-1.04	22.96	24.00	1.155
Left Side	20175/1732.5	15M QPSK(1,37)	0.261	0.169	0.41	22.96	24.00	0.332
Right Side	20175/1732.5	15M QPSK(1,37)	0.339	0.210	4.32	22.96	24.00	0.431
Bottom Side	20175/1732.5	15M QPSK(1,37)	0.367	0.230	-1.26	22.96	24.00	0.466
Back Side	20025/1717.5	15M QPSK(1,37)	0.898	0.589	-1.59	23.05	24.00	1.118
Back Side	20325/1747.5	15M QPSK(1,37)	0.922	0.651	-1.53	22.89	24.00	1.191
Back Side Repeated	20325/1747.5	15M QPSK(1,37)	0.915	0.631	-0.79	22.89	24.00	1.181
50%RB								
Front Side	20175/1732.5	1.4M QPSK(3,2)	0.361	0.229	-3.31	22.71	23.00	0.386
Back Side	20175/1732.5	1.4M QPSK(3,2)	0.551	0.342	2.52	22.71	23.00	0.589
Left Side	20175/1732.	1.4M QPSK(3,2)	0.300	0.187	-4.03	22.71	23.00	0.321

	5							
Right Side	20175/1732. 5	1.4M QPSK(3,2)	0.247	0.152	3.44	22.71	23.00	0.264
Bottom Side	20175/1732. 5	1.4M QPSK(3,2)	0.449	0.284	-2.98	22.71	23.00	0.480
100%RB								
Back Side	20175/1732. 5	20M QPSK(100,0)	0.335	0.209	-3.28	21.67	22.00	0.361

NOTE: Hotspot SAR test results of LTE Band 4

10.1.8. SAR measurement Result of LTE Band 5

Test Position of Head	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
1RB								
Left Cheek	20525/836.5	5M QPSK(1,12)	0.106	0.086	-0.04	23.16	24.00	0.129
Left Tilt 15 Degree	20525/836.5	5M QPSK(1,12)	0.055	0.045	3.97	23.16	24.00	0.067
Right Cheek	20525/836.5	5M QPSK(1,12)	0.064	0.056	2.33	23.16	24.00	0.078
Right Tilt 15 Degree	20525/836.5	5M QPSK(1,12)	0.033	0.020	-2.24	23.16	24.00	0.040
50%RB								
Left Cheek	20525/836.5	1.4M QPSK(3,1)	0.097	0.075	-1.32	22.86	23.00	0.100
Left Tilt 15 Degree	20525/836.5	1.4M QPSK(3,1)	0.050	0.047	-0.21	22.86	23.00	0.052
Right Cheek	20525/836.5	1.4M QPSK(3,1)	0.061	0.045	0.74	22.86	23.00	0.063
Right Tilt 15 Degree	20525/836.5	1.4M QPSK(3,1)	0.031	0.025	0.67	22.86	23.00	0.032

NOTE: Head SAR test results of LTE Band 5

Test Position of Body-Worn with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
1RB								
Front Side	20525/836.5	5M QPSK(1,12)	0.166	0.127	3.51	23.16	24.00	0.201
Back Side	20525/836.5	5M QPSK(1,12)	0.186	0.145	-0.51	23.16	24.00	0.226
50%RB								
Front Side	20525/836.5	1.4M QPSK(3,1)	0.149	0.119	-3.51	22.86	23.00	0.154
Back Side	20525/836.5	1.4M QPSK(3,1)	0.167	0.132	1.51	22.86	23.00	0.172

NOTE: Body-Worn SAR test results of LTE Band 5

Test Position of Hotspot with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
1RB								
Front Side	20525/836.5	5M QPSK(1,12)	0.166	0.127	3.51	23.16	24.00	0.201
Back Side	20525/836.5	5M QPSK(1,12)	0.186	0.145	-0.51	23.16	24.00	0.226
Left Side	20525/836.5	5M QPSK(1,12)	0.157	0.125	-2.79	23.16	24.00	0.191
Right Side	20525/836.5	5M QPSK(1,12)	0.143	0.116	4.72	23.16	24.00	0.174
Bottom Side	20525/836.5	5M QPSK(1,12)	0.157	0.122	0.59	23.16	24.00	0.191
50%RB								
Front Side	20525/836.5	1.4M QPSK(3,1)	0.149	0.119	-3.51	22.86	23.00	0.154
Back Side	20525/836.5	1.4M QPSK(3,1)	0.167	0.132	1.51	22.86	23.00	0.172
Left Side	20525/836.5	1.4M QPSK(3,1)	0.132	0.105	4.40	22.86	23.00	0.136
Right Side	20525/836.5	1.4M QPSK(3,1)	0.149	0.116	4.60	22.86	23.00	0.154
Bottom Side	20525/836.5	1.4M QPSK(3,1)	0.155	0.120	-0.18	22.86	23.00	0.160

NOTE: Hotspot SAR test results of LTE Band 5

10.1.9. SAR measurement Result of LTE Band 7

Test Position of Head	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
1RB								
Left Cheek	21100/2535	15M QPSK(1,37)	0.305	0.147	-1.71	22.83	24.00	0.399
Left Tilt 15 Degree	21100/2535	15M QPSK(1,37)	0.155	0.077	4.78	22.83	24.00	0.203
Right Cheek	21100/2535	15M QPSK(1,37)	0.255	0.125	2.33	22.83	24.00	0.334
Right Tilt 15 Degree	21100/2535	15M QPSK(1,37)	0.127	0.061	-1.38	22.83	24.00	0.166
50%RB								
Left Cheek	21100/2535	15M QPSK(36,0)	0.264	0.127	0.56	21.69	23.00	0.357
Left Tilt 15 Degree	21100/2535	15M QPSK(36,0)	0.136	0.066	2.15	21.69	23.00	0.184
Right Cheek	21100/2535	15M QPSK(36,0)	0.240	0.111	3.27	21.69	23.00	0.324
Right Tilt 15 Degree	21100/2535	15M QPSK(36,0)	0.133	0.068	3.11	21.69	23.00	0.180

NOTE: Head SAR test results of LTE Band 7

Test Position of Body-Worn with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
1RB								
Front Side	21100/2535	15M QPSK(1,37)	0.567	0.269	-3.66	22.83	24.00	0.742
Back Side	21100/2535	15M QPSK(1,37)	0.906	0.534	0.79	22.83	24.00	1.186
Back Side	20825/2507.5	15M QPSK(1,37)	1.011	0.631	-0.48	23.27	24.00	1.196
Back Side	20825/2507.	15M QPSK(1,37)	1.007	0.553	1.97	23.27	24.00	1.191

Repeated	5							
Back Side	21375/2562. 5	15M QPSK(1,37)	0.903	0.590	-0.57	22.81	24.00	1.188
50%RB								
Front Side	21100/2535	15M QPSK(36,0)	0.388	0.187	-1.96	21.69	23.00	0.525
Back Side	21100/2535	15M QPSK(36,0)	0.566	0.263	-2.50	21.69	23.00	0.765
100%RB								
Back Side	21100/2535	10M QPSK(50,0)	0.596	0.434	0.08	22.08	23.00	0.737

NOTE: Body-Worn SAR test results of LTE Band 7

Test Position of Hotspot with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conduc ted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
1RB								
Front Side	21100/2535	15M QPSK(1,37)	0.567	0.269	-3.66	22.83	24.00	0.742
Back Side	21100/2535	15M QPSK(1,37)	0.906	0.534	0.79	22.83	24.00	1.186
Left Side	21100/2535	15M QPSK(1,37)	0.513	0.248	3.74	22.83	24.00	0.672
Right Side	21100/2535	15M QPSK(1,37)	0.489	0.339	2.60	22.83	24.00	0.640
Bottom Side	21100/2535	15M QPSK(1,37)	0.488	0.346	0.21	22.83	24.00	0.639
Back Side	20825/2507.5	15M QPSK(1,37)	1.011	0.631	-0.48	23.27	24.00	1.196
Back Side Repeated	20825/2507.5	15M QPSK(1,37)	1.007	0.553	1.97	23.27	24.00	1.191
Back Side	21375/2562.5	15M QPSK(1,37)	0.903	0.590	-0.57	22.81	24.00	1.188
50%RB								
Front Side	21100/2535	15M QPSK(36,0)	0.388	0.187	-1.96	21.69	23.00	0.525
Back Side	21100/2535	15M QPSK(36,0)	0.566	0.263	-2.50	21.69	23.00	0.765
Left Side	21100/2535	15M QPSK(36,0)	0.366	0.177	-1.71	21.69	23.00	0.495
Right Side	21100/2535	15M QPSK(36,0)	0.413	0.190	0.06	21.69	23.00	0.558
Bottom Side	21100/2535	15M QPSK(36,0)	0.310	0.143	-3.89	21.69	23.00	0.419
100%RB								
Back Side	21100/2535	10M QPSK(50,0)	0.596	0.434	0.08	22.08	23.00	0.737

NOTE: Hotspot SAR test results of LTE Band 7

10.1.10. SAR measurement Result of LTE Band 12

Test Position of Head	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
1RB								
Left Cheek	23095/707.5	5M QPSK(1,12)	0.027	0.025	0.08	22.85	24.00	0.035
Left Tilt 15 Degree	23095/707.5	5M QPSK(1,12)	0.015	0.011	-3.02	22.85	24.00	0.020
Right Cheek	23095/707.5	5M QPSK(1,12)	0.024	0.020	1.16	22.85	24.00	0.031
Right Tilt 15 Degree	23095/707.5	5M QPSK(1,12)	0.013	0.010	-2.16	22.85	24.00	0.017
50%RB								
Left Cheek	23095/707.5	1.4M QPSK(3,1)	0.017	0.016	-4.72	22.60	23.00	0.019
Left Tilt 15 Degree	23095/707.5	1.4M QPSK(3,1)	0.009	0.002	-3.23	22.60	23.00	0.010
Right Cheek	23095/707.5	1.4M QPSK(3,1)	0.011	0.010	0.82	22.60	23.00	0.012
Right Tilt 15 Degree	23095/707.5	1.4M QPSK(3,1)	0.006	0.003	-4.86	22.60	23.00	0.007

NOTE: Head SAR test results of LTE Band 12

Test Position of Body-Worn with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
1RB								
Front Side	23095/707.5	5M QPSK(1,12)	0.044	0.037	1.46	22.85	24.00	0.057
Back Side	23095/707.5	5M QPSK(1,12)	0.052	0.042	-3.02	22.85	24.00	0.068
50%RB								
Front Side	23095/707.5	1.4M QPSK(3,1)	0.034	0.026	0.95	22.60	23.00	0.037
Back Side	23095/707.5	1.4M QPSK(3,1)	0.040	0.033	0.21	22.60	23.00	0.044

NOTE: Body-Worn SAR test results of LTE Band 12

Test Position of Hotspot with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
1RB								
Front Side	23095/707.5	5M QPSK(1,12)	0.044	0.037	1.46	22.85	24.00	0.057
Back Side	23095/707.5	5M QPSK(1,12)	0.052	0.042	-3.02	22.85	24.00	0.068
Left Side	23095/707.5	5M QPSK(1,12)	0.049	0.036	-2.58	22.85	24.00	0.064
Right Side	23095/707.5	5M QPSK(1,12)	0.035	0.029	2.57	22.85	24.00	0.046
Bottom Side	23095/707.5	5M QPSK(1,12)	0.029	0.024	3.67	22.85	24.00	0.038
50%RB								
Front Side	23095/707.5	1.4M QPSK(3,1)	0.034	0.026	0.95	22.60	23.00	0.037
Back Side	23095/707.5	1.4M QPSK(3,1)	0.040	0.033	0.21	22.60	23.00	0.044
Left Side	23095/707.5	1.4M QPSK(3,1)	0.026	0.021	-0.68	22.60	23.00	0.029
Right Side	23095/707.5	1.4M QPSK(3,1)	0.021	0.011	2.90	22.60	23.00	0.023
Bottom Side	23095/707.5	1.4M QPSK(3,1)	0.015	0.010	2.07	22.60	23.00	0.016

NOTE: Hotspot SAR test results of LTE Band 12

10.1.11. SAR measurement Result of LTE Band 17

Test Position of Head	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
1RB								
Left Cheek	23790/710	10M QPSK(1,24)	0.077	0.039	-1.12	22.71	23.00	0.082
Left Tilt 15 Degree	23790/710	10M QPSK(1,24)	0.036	0.019	-0.49	22.71	23.00	0.038
Right	23790/710	10M	0.051	0.025	-4.01	22.71	23.00	0.055

Cheek		QPSK(1,24)						
Right Tilt 15 Degree	23790/710	10M QPSK(1,24)	0.027	0.018	1.66	22.71	23.00	0.029
50%RB								
Left Cheek	23790/710	10M QPSK(25,24)	0.041	0.023	-2.66	21.70	22.00	0.044
Left Tilt 15 Degree	23790/710	10M QPSK(25,24)	0.033	0.015	-0.86	21.70	22.00	0.035
Right Cheek	23790/710	10M QPSK(25,24)	0.027	0.018	3.06	21.70	22.00	0.029
Right Tilt 15 Degree	23790/710	10M QPSK(25,24)	0.025	0.011	-4.40	21.70	22.00	0.027

NOTE: Head SAR test results of LTE Band 17

Test Position of Body-Worn with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
1RB								
Front Side	23790/710	10M QPSK(1,24)	0.051	0.044	3.66	22.71	23.00	0.055
Back Side	23790/710	10M QPSK(1,24)	0.068	0.055	-1.02	22.71	23.00	0.073
50%RB								
Front Side	23790/710	10M QPSK(25,24)	0.040	0.034	-4.17	21.70	22.00	0.043
Back Side	23790/710	10M QPSK(25,24)	0.051	0.041	4.64	21.70	22.00	0.055

NOTE: Body-Worn SAR test results of LTE Band 17

Test Position of Hotspot with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
1RB								
Front Side	23790/710	10M QPSK(1,24)	0.051	0.044	3.66	22.71	23.00	0.055
Back	23790/710	10M QPSK(1,24)	0.068	0.055	-1.02	22.71	23.00	0.073

Side								
Left Side	23790/710	10M QPSK(1,24)	0.041	0.038	-4.53	22.71	23.00	0.044
Right Side	23790/710	10M QPSK(1,24)	0.049	0.033	-0.67	22.71	23.00	0.052
Bottom Side	23790/710	10M QPSK(1,24)	0.034	0.027	-3.57	22.71	23.00	0.036
50%RB								
Front Side	23790/710	10M QPSK(25,24)	0.040	0.034	-4.17	21.70	22.00	0.043
Back Side	23790/710	10M QPSK(25,24)	0.051	0.041	4.64	21.70	22.00	0.055
Left Side	23790/710	10M QPSK(25,24)	0.033	0.024	-4.75	21.70	22.00	0.035
Right Side	23790/710	10M QPSK(25,24)	0.029	0.023	1.09	21.70	22.00	0.031
Bottom Side	23790/710	10M QPSK(25,24)	0.015	0.010	-1.87	21.70	22.00	0.016

NOTE: Hotspot SAR test results of LTE Band 17

10.1.12. SAR measurement Result of LTE Band 19

Test Position of Head	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
1RB								
Left Cheek	24075/837.5	15M QPSK(1,37)	0.095	0.045	0.10	22.97	23.00	0.096
Left Tilt 15 Degree	24075/837.5	15M QPSK(1,37)	0.049	0.028	4.55	22.97	23.00	0.049
Right Cheek	24075/837.5	15M QPSK(1,37)	0.086	0.049	0.51	22.97	23.00	0.087
Right Tilt 15 Degree	24075/837.5	15M QPSK(1,37)	0.046	0.026	2.51	22.97	23.00	0.046
50%RB								
Left Cheek	24075/837.5	15M QPSK(36,18)	0.064	0.031	-4.29	21.69	22.00	0.069
Left Tilt 15	24075/837.5	15M QPSK(36,18)	0.034	0.019	3.12	21.69	22.00	0.037

Degree								
Right Cheek	24075/837.5	15M QPSK(36,18)	0.051	0.029	-4.27	21.69	22.00	0.055
Right Tilt 15 Degree	24075/837.5	15M QPSK(36,18)	0.023	0.015	0.92	21.69	22.00	0.025

NOTE: Head SAR test results of LTE Band 19

Test Position of Body-Worn with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
1RB								
Front Side	24075/837.5	15M QPSK(1,37)	0.151	0.119	-1.63	22.97	23.00	0.152
Back Side	24075/837.5	15M QPSK(1,37)	0.177	0.137	0.01	22.97	23.00	0.178
50%RB								
Front Side	24075/837.5	15M QPSK(36,18)	0.145	0.114	3.88	21.69	22.00	0.156
Back Side	24075/837.5	15M QPSK(36,18)	0.166	0.128	-0.87	21.69	22.00	0.178

NOTE: Body-Worn SAR test results of LTE Band 19

Test Position of Hotspot with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
1RB								
Front Side	24075/837.5	15M QPSK(1,37)	0.151	0.119	-1.63	22.97	23.00	0.152
Back Side	24075/837.5	15M QPSK(1,37)	0.177	0.137	0.01	22.97	23.00	0.178
Left Side	24075/837.5	15M QPSK(1,37)	0.143	0.114	-1.77	22.97	23.00	0.144
Right Side	24075/837.5	15M QPSK(1,37)	0.137	0.106	-0.97	22.97	23.00	0.138
Bottom Side	24075/837.5	15M QPSK(1,37)	0.154	0.111	-0.06	22.97	23.00	0.155
50%RB								
Front Side	24075/837.5	15M QPSK(36,18)	0.145	0.114	3.88	21.69	22.00	0.156

Back Side	24075/837.5	15M QPSK(36,18)	0.166	0.128	-0.87	21.69	22.00	0.178
Left Side	24075/837.5	15M QPSK(36,18)	0.120	0.094	-2.44	21.69	22.00	0.129
Right Side	24075/837.5	15M QPSK(36,18)	0.137	0.109	-1.59	21.69	22.00	0.147
Bottom Side	24075/837.5	15M QPSK(36,18)	0.129	0.095	2.07	21.69	22.00	0.139

NOTE: Hotspot SAR test results of LTE Band 19

10.1.13. SAR measurement Result of WLAN 2.4G

Test Position of Head	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
Left Cheek	6/2437	802.11 b	0.671	0.308	-2.48	14.81	15.00	0.701
Left Tilt 15 Degree	6/2437	802.11 b	0.355	0.163	3.79	14.81	15.00	0.371
Right Cheek	6/2437	802.11 b	0.483	0.228	-2.34	14.81	15.00	0.505
Right Tilt 15 Degree	6/2437	802.11 b	0.251	0.114	1.35	14.81	15.00	0.262

NOTE: Head SAR test results of WLAN 2.4G

Test Position of Body-Worn with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
Front Side	6/2437	802.11 b	0.123	0.109	1.39	14.81	15.00	0.129
Back Side	6/2437	802.11 b	0.143	0.139	-1.57	14.81	15.00	0.149

NOTE: Body-Worn SAR test results of WLAN 2.4G

Test Position of Hotspot with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
Front Side	6/2437	802.11 b	0.123	0.109	1.39	14.81	15.00	0.129
Back Side	6/2437	802.11 b	0.143	0.139	-1.57	14.81	15.00	0.149
Right Side	6/2437	802.11 b	0.119	0.091	-3.93	14.81	15.00	0.124
Top Side	6/2437	802.11 b	0.130	0.114	4.30	14.81	15.00	0.136

NOTE: Hotspot SAR test results of WLAN 2.4G

10.2. SAR Summation Scenario

Per KDB 447498 D01, simultaneous transmission SAR is compliant if,

- 1) Scalar SAR summation $< 1.6\text{W/kg}$.
- 2) $\text{SPLSR} = (\text{SAR}_1 + \text{SAR}_2)^{1.5} / (\text{min. separation distance, mm})$, and the peak separation distance is determined from the square root of $[(x_1 - x_2)^2 + (y_1 - y_2)^2 + (z_1 - z_2)^2]$, where (x_1, y_1, z_1) and (x_2, y_2, z_2) are the coordinates of the extrapolated peak SAR locations in the zoom scan. If $\text{SPLSR} \leq 0.04$, simultaneously transmission SAR measurement is not necessary.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		GSM 850	WLAN 2.4G			
Head	Left Cheek	0.285	0.701	0.986	N/A	N/A
	Left Tilt 15 Degree	0.136	0.371	0.506	N/A	N/A
	Right Cheek	0.262	0.505	0.766	N/A	N/A
	Right Tilt 15 Degree	0.127	0.262	0.390	N/A	N/A
Body-Worn	Front Side	0.498	0.129	0.626	N/A	N/A
	Back Side	0.520	0.149	0.669	N/A	N/A
Hotspot	Front Side	0.498	0.129	0.626	N/A	N/A
	Back Side	0.520	0.149	0.669	N/A	N/A
	Left Side	0.482	N/A	0.482	N/A	N/A
	Right Side	0.514	0.124	0.639	N/A	N/A
	Top Side	N/A	0.136	0.136	N/A	N/A
	Bottom Side	0.408	N/A	0.408	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of GSM850 and WLAN 2.4G.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		GSM 1900	WLAN 2.4G			
Head	Left Cheek	0.316	0.701	1.017	N/A	N/A
	Left Tilt 15 Degree	0.160	0.371	0.531	N/A	N/A
	Right Cheek	0.295	0.505	0.800	N/A	N/A
	Right Tilt 15 Degree	0.147	0.262	0.409	N/A	N/A
Body-Worn	Front Side	0.407	0.129	0.536	N/A	N/A
	Back Side	0.436	0.149	0.585	N/A	N/A
Hotspot	Front Side	0.407	0.129	0.536	N/A	N/A
	Back Side	0.436	0.149	0.585	N/A	N/A
	Left Side	0.358	N/A	0.358	N/A	N/A
	Right Side	0.336	0.124	0.460	N/A	N/A
	Top Side	N/A	0.136	0.136	N/A	N/A
	Bottom Side	0.318	N/A	0.318	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of GSM1900 and WLAN 2.4G.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		WCDMA Band 2	WLAN 2.4G			
Head	Left Cheek	0.452	0.701	1.153	N/A	N/A
	Left Tilt 15 Degree	0.230	0.371	0.601	N/A	N/A
	Right Cheek	0.420	0.505	0.924	N/A	N/A
	Right Tilt 15 Degree	0.215	0.262	0.478	N/A	N/A
Body-Worn	Front Side	0.514	0.129	0.643	N/A	N/A
	Back Side	0.661	0.149	0.810	N/A	N/A
Hotspot	Front Side	0.514	0.129	0.643	N/A	N/A
	Back Side	0.661	0.149	0.810	N/A	N/A
	Left Side	0.610	N/A	0.610	N/A	N/A
	Right Side	0.390	0.124	0.514	N/A	N/A
	Top Side	N/A	0.136	0.136	N/A	N/A
	Bottom Side	0.518	N/A	0.518	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of WCDMA Band 2 and WLAN 2.4G.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		WCDMA Band 4	WLAN 2.4G			
Head	Left Cheek	0.553	0.701	1.254	N/A	N/A
	Left Tilt 15 Degree	0.284	0.371	0.655	N/A	N/A
	Right Cheek	0.443	0.505	0.947	N/A	N/A
	Right Tilt 15 Degree	0.221	0.262	0.484	N/A	N/A
Body-Worn	Front Side	0.351	0.129	0.480	N/A	N/A
	Back Side	1.112	0.149	1.261	N/A	N/A
Hotspot	Front Side	0.351	0.129	0.480	N/A	N/A
	Back Side	1.112	0.149	1.261	N/A	N/A
	Left Side	0.448	N/A	0.448	N/A	N/A
	Right Side	0.220	0.124	0.345	N/A	N/A
	Top Side	N/A	0.136	0.136	N/A	N/A
	Bottom Side	0.432	N/A	0.432	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of WCDMA Band 4 and WLAN 2.4G.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		WCDMA Band 5	WLAN 2.4G			
Head	Left Cheek	0.125	0.701	0.826	N/A	N/A
	Left Tilt 15	0.065	0.371	0.436	N/A	N/A

	Degree					
	Right Cheek	0.102	0.505	0.606	N/A	N/A
	Right Tilt 15 Degree	0.049	0.262	0.312	N/A	N/A
Body-Worn	Front Side	0.158	0.129	0.287	N/A	N/A
	Back Side	0.214	0.149	0.364	N/A	N/A
Hotspot	Front Side	0.158	0.129	0.287	N/A	N/A
	Back Side	0.214	0.149	0.364	N/A	N/A
	Left Side	0.167	N/A	0.167	N/A	N/A
	Right Side	0.190	0.124	0.315	N/A	N/A
	Top Side	N/A	0.136	0.136	N/A	N/A
	Bottom Side	0.124	N/A	0.124	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of WCDMA Band 5 and WLAN 2.4G.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		LTE Band 2	WLAN 2.4G			
Head	Left Cheek	0.365	0.701	1.066	N/A	N/A
	Left Tilt 15 Degree	0.182	0.371	0.553	N/A	N/A
	Right Cheek	0.322	0.505	0.827	N/A	N/A
	Right Tilt 15 Degree	0.187	0.262	0.449	N/A	N/A
Body-Worn	Front Side	0.411	0.129	0.540	N/A	N/A
	Back Side	0.719	0.149	0.869	N/A	N/A
Hotspot	Front Side	0.203	N/A	0.203	N/A	N/A
	Back Side	0.284	0.124	0.409	N/A	N/A
	Left Side	N/A	0.136	0.136	N/A	N/A
	Right Side	0.593	N/A	0.593	N/A	N/A
	Top Side	0.365	0.701	1.066	N/A	N/A
	Bottom Side	0.182	0.371	0.553	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of LTE Band 2 and WLAN 2.4G.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		LTE Band 4	WLAN 2.4G			
Head	Left Cheek	0.446	0.701	1.147	N/A	N/A
	Left Tilt 15 Degree	0.225	0.371	0.596	N/A	N/A
	Right Cheek	0.390	0.505	0.895	N/A	N/A
	Right Tilt 15 Degree	0.194	0.262	0.457	N/A	N/A
Body-Worn	Front Side	0.558	0.129	0.686	N/A	N/A
	Back Side	1.191	0.149	1.340	N/A	N/A
Hotspot	Front Side	0.558	0.129	0.686	N/A	N/A
	Back Side	1.191	0.149	1.340	N/A	N/A

	Left Side	0.332	N/A	0.332	N/A	N/A
	Right Side	0.431	0.124	0.555	N/A	N/A
	Top Side	N/A	0.136	0.136	N/A	N/A
	Bottom Side	0.480	N/A	0.480	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of LTE Band 4 and WLAN 2.4G.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		LTE Band 5	WLAN 2.4G			
Head	Left Cheek	0.129	0.701	0.830	N/A	N/A
	Left Tilt 15 Degree	0.067	0.371	0.438	N/A	N/A
	Right Cheek	0.078	0.505	0.582	N/A	N/A
	Right Tilt 15 Degree	0.040	0.262	0.302	N/A	N/A
Body-Worn	Front Side	0.201	0.129	0.330	N/A	N/A
	Back Side	0.226	0.149	0.375	N/A	N/A
Hotspot	Front Side	0.201	0.129	0.330	N/A	N/A
	Back Side	0.226	0.149	0.375	N/A	N/A
	Left Side	0.191	N/A	0.191	N/A	N/A
	Right Side	0.174	0.124	0.298	N/A	N/A
	Top Side	N/A	0.136	0.136	N/A	N/A
	Bottom Side	0.191	N/A	0.191	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of LTE Band 5 and WLAN 2.4G.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		LTE Band 7	WLAN 2.4G			
Head	Left Cheek	0.399	0.701	1.100	N/A	N/A
	Left Tilt 15 Degree	0.203	0.371	0.574	N/A	N/A
	Right Cheek	0.334	0.505	0.838	N/A	N/A
	Right Tilt 15 Degree	0.166	0.262	0.428	N/A	N/A
Body-Worn	Front Side	0.742	0.129	0.871	N/A	N/A
	Back Side	1.196	0.149	1.345	N/A	N/A
Hotspot	Front Side	0.742	0.129	0.871	N/A	N/A
	Back Side	1.196	0.149	1.345	N/A	N/A
	Left Side	0.672	N/A	0.672	N/A	N/A
	Right Side	0.640	0.124	0.765	N/A	N/A
	Top Side	N/A	0.136	0.136	N/A	N/A
	Bottom Side	0.639	N/A	0.639	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of LTE Band 7 and WLAN 2.4G.

Test Position	Scaled SAR _{MAX}		Σ 1-g SAR	SPLSR	Remark
---------------	---------------------------	--	------------------	-------	--------

		LTE Band 12	WLAN 2.4G	(W/Kg)		
Head	Left Cheek	0.035	0.701	0.736	N/A	N/A
	Left Tilt 15 Degree	0.020	0.371	0.390	N/A	N/A
	Right Cheek	0.031	0.505	0.536	N/A	N/A
	Right Tilt 15 Degree	0.017	0.262	0.279	N/A	N/A
Body-Worn	Front Side	0.057	0.129	0.186	N/A	N/A
	Back Side	0.068	0.149	0.217	N/A	N/A
Hotspot	Front Side	0.057	0.129	0.186	N/A	N/A
	Back Side	0.068	0.149	0.217	N/A	N/A
	Left Side	0.064	N/A	0.064	N/A	N/A
	Right Side	0.046	0.124	0.170	N/A	N/A
	Top Side	N/A	0.136	0.136	N/A	N/A
	Bottom Side	0.038	N/A	0.038	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of LTE Band 12 and WLAN 2.4G.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		LTE Band 17	WLAN 2.4G			
Head	Left Cheek	0.082	0.701	0.783	N/A	N/A
	Left Tilt 15 Degree	0.038	0.371	0.409	N/A	N/A
	Right Cheek	0.055	0.505	0.559	N/A	N/A
	Right Tilt 15 Degree	0.029	0.262	0.291	N/A	N/A
Body-Worn	Front Side	0.055	0.129	0.183	N/A	N/A
	Back Side	0.073	0.149	0.222	N/A	N/A
Hotspot	Front Side	0.055	0.129	0.183	N/A	N/A
	Back Side	0.073	0.149	0.222	N/A	N/A
	Left Side	0.044	N/A	0.044	N/A	N/A
	Right Side	0.052	0.124	0.177	N/A	N/A
	Top Side	N/A	0.136	0.136	N/A	N/A
	Bottom Side	0.036	N/A	0.036	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of LTE Band 17 and WLAN 2.4G.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		LTE Band 19	WLAN 2.4G			
Head	Left Cheek	0.096	0.701	0.797	N/A	N/A
	Left Tilt 15 Degree	0.049	0.371	0.420	N/A	N/A
	Right Cheek	0.087	0.505	0.591	N/A	N/A

	Right Tilt 15 Degree	0.046	0.262	0.309	N/A	N/A
Body-Worn	Front Side	0.156	0.129	0.284	N/A	N/A
	Back Side	0.178	0.149	0.328	N/A	N/A
Hotspot	Front Side	0.156	0.129	0.284	N/A	N/A
	Back Side	0.178	0.149	0.328	N/A	N/A
	Left Side	0.144	N/A	0.144	N/A	N/A
	Right Side	0.147	0.124	0.271	N/A	N/A
	Top Side	N/A	0.136	0.136	N/A	N/A
	Bottom Side	0.155	N/A	0.155	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of LTE Band 19 and WLAN 2.4G.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		GSM 850	Bluetooth			
Head	Left Cheek	0.285	0.210	0.495	N/A	N/A
	Left Tilt 15 Degree	0.136	0.210	0.346	N/A	N/A
	Right Cheek	0.262	0.210	0.472	N/A	N/A
	Right Tilt 15 Degree	0.127	0.210	0.338	N/A	N/A
Body-Worn	Front Side	0.498	0.105	0.603	N/A	N/A
	Back Side	0.520	0.105	0.625	N/A	N/A
Hotspot	Front Side	0.498	0.105	0.603	N/A	N/A
	Back Side	0.520	0.105	0.625	N/A	N/A
	Left Side	0.482	N/A	0.482	N/A	N/A
	Right Side	0.514	0.105	0.620	N/A	N/A
	Top Side	N/A	0.105	0.105	N/A	N/A
	Bottom Side	0.408	N/A	0.408	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of GSM850 and Bluetooth.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		GSM 1900	Bluetooth			
Head	Left Cheek	0.316	0.210	0.527	N/A	N/A
	Left Tilt 15 Degree	0.160	0.210	0.370	N/A	N/A
	Right Cheek	0.295	0.210	0.505	N/A	N/A
	Right Tilt 15 Degree	0.147	0.210	0.357	N/A	N/A
Body-Worn	Front Side	0.407	0.105	0.512	N/A	N/A
	Back Side	0.436	0.105	0.541	N/A	N/A
Hotspot	Front Side	0.407	0.105	0.512	N/A	N/A
	Back Side	0.436	0.105	0.541	N/A	N/A
	Left Side	0.358	N/A	0.358	N/A	N/A
	Right Side	0.336	0.105	0.441	N/A	N/A

	Top Side	N/A	0.105	0.105	N/A	N/A
	Bottom Side	0.318	N/A	0.318	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of GSM1900 and Bluetooth.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		WCDMA Band 2	Bluetooth			
Head	Left Cheek	0.452	0.210	0.662	N/A	N/A
	Left Tilt 15 Degree	0.230	0.210	0.441	N/A	N/A
	Right Cheek	0.420	0.210	0.630	N/A	N/A
	Right Tilt 15 Degree	0.215	0.210	0.426	N/A	N/A
Body-Worn	Front Side	0.514	0.105	0.619	N/A	N/A
	Back Side	0.661	0.105	0.766	N/A	N/A
Hotspot	Front Side	0.514	0.105	0.619	N/A	N/A
	Back Side	0.661	0.105	0.766	N/A	N/A
	Left Side	0.610	N/A	0.610	N/A	N/A
	Right Side	0.390	0.105	0.495	N/A	N/A
	Top Side	N/A	0.105	0.105	N/A	N/A
	Bottom Side	0.518	N/A	0.518	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of WCDMA Band 2 and Bluetooth.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		WCDMA Band 4	Bluetooth			
Head	Left Cheek	0.553	0.210	0.764	N/A	N/A
	Left Tilt 15 Degree	0.284	0.210	0.495	N/A	N/A
	Right Cheek	0.443	0.210	0.653	N/A	N/A
	Right Tilt 15 Degree	0.221	0.210	0.432	N/A	N/A
Body-Worn	Front Side	0.351	0.105	0.456	N/A	N/A
	Back Side	1.112	0.105	1.217	N/A	N/A
Hotspot	Front Side	0.351	0.105	0.456	N/A	N/A
	Back Side	1.112	0.105	1.217	N/A	N/A
	Left Side	0.448	N/A	0.448	N/A	N/A
	Right Side	0.220	0.105	0.326	N/A	N/A
	Top Side	N/A	0.105	0.105	N/A	N/A
	Bottom Side	0.432	N/A	0.432	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of WCDMA Band 4 and Bluetooth.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		WCDMA Band 5	Bluetooth			
Head	Left Cheek	0.125	0.210	0.335	N/A	N/A
	Left Tilt 15 Degree	0.065	0.210	0.276	N/A	N/A
	Right Cheek	0.102	0.210	0.312	N/A	N/A
	Right Tilt 15 Degree	0.049	0.210	0.260	N/A	N/A
Body-Worn	Front Side	0.158	0.105	0.263	N/A	N/A
	Back Side	0.214	0.105	0.320	N/A	N/A
Hotspot	Front Side	0.158	0.105	0.263	N/A	N/A
	Back Side	0.214	0.105	0.320	N/A	N/A
	Left Side	0.167	N/A	0.167	N/A	N/A
	Right Side	0.190	0.105	0.296	N/A	N/A
	Top Side	N/A	0.105	0.105	N/A	N/A
	Bottom Side	0.124	N/A	0.124	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of WCDMA Band 5 and Bluetooth.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		LTE Band 2	Bluetooth			
Head	Left Cheek	0.365	0.210	0.575	N/A	N/A
	Left Tilt 15 Degree	0.182	0.210	0.392	N/A	N/A
	Right Cheek	0.322	0.210	0.533	N/A	N/A
	Right Tilt 15 Degree	0.187	0.210	0.397	N/A	N/A
Body-Worn	Front Side	0.411	0.105	0.516	N/A	N/A
	Back Side	0.719	0.105	0.825	N/A	N/A
Hotspot	Front Side	0.411	0.105	0.516	N/A	N/A
	Back Side	0.719	0.105	0.825	N/A	N/A
	Left Side	0.203	N/A	0.203	N/A	N/A
	Right Side	0.284	0.105	0.390	N/A	N/A
	Top Side	N/A	0.105	0.698	N/A	N/A
	Bottom Side	0.593	N/A	0.593	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of LTE Band 2 and Bluetooth.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		LTE Band 4	Bluetooth			
Head	Left Cheek	0.446	0.210	0.656	N/A	N/A
	Left Tilt 15 Degree	0.225	0.210	0.435	N/A	N/A

	Right Cheek	0.390	0.210	0.601	N/A	N/A
	Right Tilt 15 Degree	0.194	0.210	0.405	N/A	N/A
Body-Worn	Front Side	0.558	0.105	0.663	N/A	N/A
	Back Side	1.191	0.105	1.296	N/A	N/A
Hotspot	Front Side	0.558	0.105	0.663	N/A	N/A
	Back Side	1.191	0.105	1.296	N/A	N/A
	Left Side	0.332	N/A	0.332	N/A	N/A
	Right Side	0.431	0.105	0.536	N/A	N/A
	Top Side	N/A	0.105	0.105	N/A	N/A
	Bottom Side	0.480	N/A	0.480	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of LTE Band 4 and Bluetooth.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		LTE Band 5	Bluetooth			
Head	Left Cheek	0.129	0.210	0.339	N/A	N/A
	Left Tilt 15 Degree	0.067	0.210	0.277	N/A	N/A
	Right Cheek	0.078	0.210	0.288	N/A	N/A
	Right Tilt 15 Degree	0.040	0.210	0.251	N/A	N/A
Body-Worn	Front Side	0.201	0.105	0.307	N/A	N/A
	Back Side	0.226	0.105	0.331	N/A	N/A
Hotspot	Front Side	0.201	0.105	0.307	N/A	N/A
	Back Side	0.226	0.105	0.331	N/A	N/A
	Left Side	0.191	N/A	0.191	N/A	N/A
	Right Side	0.174	0.105	0.279	N/A	N/A
	Top Side	N/A	0.105	0.105	N/A	N/A
	Bottom Side	0.191	N/A	0.191	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of LTE Band 5 and Bluetooth.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		LTE Band 7	Bluetooth			
Head	Left Cheek	0.399	0.210	0.610	N/A	N/A
	Left Tilt 15 Degree	0.203	0.210	0.413	N/A	N/A
	Right Cheek	0.334	0.210	0.544	N/A	N/A
	Right Tilt 15 Degree	0.166	0.210	0.377	N/A	N/A
Body-Worn	Front Side	0.742	0.105	0.848	N/A	N/A
	Back Side	1.196	0.105	1.301	N/A	N/A
Hotspot	Front Side	0.742	0.105	0.848	N/A	N/A
	Back Side	1.196	0.105	1.301	N/A	N/A

	Left Side	0.672	N/A	0.672	N/A	N/A
	Right Side	0.640	0.105	0.745	N/A	N/A
	Top Side	N/A	0.105	0.105	N/A	N/A
	Bottom Side	0.639	N/A	0.639	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of LTE Band 7 and Bluetooth.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		LTE Band 12	Bluetooth			
Head	Left Cheek	0.035	0.210	0.246	N/A	N/A
	Left Tilt 15 Degree	0.020	0.210	0.230	N/A	N/A
	Right Cheek	0.031	0.210	0.242	N/A	N/A
	Right Tilt 15 Degree	0.017	0.210	0.227	N/A	N/A
Body-Worn	Front Side	0.057	0.105	0.163	N/A	N/A
	Back Side	0.068	0.105	0.173	N/A	N/A
Hotspot	Front Side	0.057	0.105	0.163	N/A	N/A
	Back Side	0.068	0.105	0.173	N/A	N/A
	Left Side	0.064	N/A	0.064	N/A	N/A
	Right Side	0.046	0.105	0.151	N/A	N/A
	Top Side	N/A	0.105	0.105	N/A	N/A
	Bottom Side	0.038	N/A	0.038	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of LTE Band 12 and Bluetooth.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		LTE Band 17	Bluetooth			
Head	Left Cheek	0.082	0.210	0.293	N/A	N/A
	Left Tilt 15 Degree	0.038	0.210	0.249	N/A	N/A
	Right Cheek	0.055	0.210	0.265	N/A	N/A
	Right Tilt 15 Degree	0.029	0.210	0.239	N/A	N/A
Body-Worn	Front Side	0.055	0.105	0.160	N/A	N/A
	Back Side	0.073	0.105	0.178	N/A	N/A
Hotspot	Front Side	0.055	0.105	0.160	N/A	N/A
	Back Side	0.073	0.105	0.178	N/A	N/A
	Left Side	0.044	N/A	0.044	N/A	N/A
	Right Side	0.052	0.105	0.158	N/A	N/A
	Top Side	N/A	0.105	0.105	N/A	N/A
	Bottom Side	0.036	N/A	0.036	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of LTE Band 17 and Bluetooth.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		LTE Band 19	Bluetooth			
Head	Left Cheek	0.096	0.210	0.306	N/A	N/A
	Left Tilt 15 Degree	0.049	0.210	0.260	N/A	N/A
	Right Cheek	0.087	0.210	0.297	N/A	N/A
	Right Tilt 15 Degree	0.046	0.210	0.257	N/A	N/A
Body-Worn	Front Side	0.156	0.105	0.261	N/A	N/A
	Back Side	0.178	0.105	0.284	N/A	N/A
Hotspot	Front Side	0.156	0.105	0.261	N/A	N/A
	Back Side	0.178	0.105	0.284	N/A	N/A
	Left Side	0.144	N/A	0.144	N/A	N/A
	Right Side	0.147	0.105	0.252	N/A	N/A
	Top Side	N/A	0.105	0.105	N/A	N/A
	Bottom Side	0.155	N/A	0.155	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of LTE Band 19 and Bluetooth.

11. Appendix A. Photo documentation

Refer to appendix Test Setup photo---SAR

12. Appendix B. System Check Plots

Table of contents
MEASUREMENT 1 System Performance Check - SID750 - Head
MEASUREMENT 2 System Performance Check - SID750 - Body
MEASUREMENT 3 System Performance Check - SID835 - Head
MEASUREMENT 4 System Performance Check - SID835 - Body
MEASUREMENT 5 System Performance Check - SID1800 - Head
MEASUREMENT 6 System Performance Check - SID1800 - Body
MEASUREMENT 7 System Performance Check - SID1900 - Head
MEASUREMENT 8 System Performance Check - SID1900 - Body
MEASUREMENT 9 System Performance Check - SID2450 - Head
MEASUREMENT 10 System Performance Check - SID2450 - Body
MEASUREMENT 11 System Performance Check - SID2600 - Head
MEASUREMENT 12 System Performance Check - SID2600 - Body


MEASUREMENT 1

A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Dipole</u>
<u>Band</u>	<u>CW750</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>CW (Crest factor: 1.0)</u>

B. SAR Measurement Results



Frequency (MHz)	750.000000
Relative permittivity (real part)	41.323162
Relative permittivity (imaginary part)	22.171263
Conductivity (S/m)	0.923162
Variation (%)	-3.640000



Maximum location: X=3.00, Y=3.00

SAR Peak: 1.30 W/kg

SAR 10g (W/Kg)	0.537238
SAR 1g (W/Kg)	0.849162



MEASUREMENT 2


A. Experimental conditions.

Area Scan	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
ZoomScan	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
Phantom	<u>Validation plane</u>
Device Position	<u>Dipole</u>
Band	<u>CW750</u>
Channels	<u>Middle</u>
Signal	<u>CW (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	750.000000
Relative permittivity (real part)	55.510582
Relative permittivity (imaginary part)	23.473421
Conductivity (S/m)	0.982152
Variation (%)	-0.710000

SURFACE SAR





VOLUME SAR



Maximum location: X=3.00, Y=3.00

SAR Peak: 1.30 W/kg

SAR 10g (W/Kg)	0.578236
SAR 1g (W/Kg)	0.866239



MEASUREMENT 3


A. Experimental conditions.

Area Scan	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
ZoomScan	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
Phantom	<u>Validation plane</u>
Device Position	<u>Dipole</u>
Band	<u>CW835</u>
Channels	<u>Middle</u>
Signal	<u>CW (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	835.000000
Relative permittivity (real part)	40.721241
Relative permittivity (imaginary part)	19.980512
Conductivity (S/m)	0.931642
Variation (%)	1.120000

SURFACE SAR





VOLUME SAR



Maximum location: X=3.00, Y=3.00

SAR Peak: 1.30 W/kg

SAR 10g (W/Kg)	0.599376
SAR 1g (W/Kg)	0.915438



MEASUREMENT 4


A. Experimental conditions.

Area Scan	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
ZoomScan	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
Phantom	<u>Validation plane</u>
Device Position	<u>Dipole</u>
Band	<u>CW835</u>
Channels	<u>Middle</u>
Signal	<u>CW (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	835.000000
Relative permittivity (real part)	54.452222
Relative permittivity (imaginary part)	21.663419
Conductivity (S/m)	1.001056
Variation (%)	-4.330000

SURFACE SAR





VOLUME SAR



Maximum location: X=3.00, Y=2.00

SAR Peak: 1.23 W/kg

SAR 10g (W/Kg)	0.612102
SAR 1g (W/Kg)	0.946209



MEASUREMENT 5


A. Experimental conditions.

Area Scan	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
ZoomScan	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
Phantom	<u>Validation plane</u>
Device Position	<u>Dipole</u>
Band	<u>CW1800</u>
Channels	<u>Middle</u>
Signal	<u>CW (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	1800.000000
Relative permittivity (real part)	38.561117
Relative permittivity (imaginary part)	14.032429
Conductivity (S/m)	1.402567
Variation (%)	-2.180000

SURFACE SAR





VOLUME SAR



Maximum location: X=3.00, Y=2.00

SAR Peak: 6.82 W/kg

SAR 10g (W/Kg)	2.017367
SAR 1g (W/Kg)	3.648451



MEASUREMENT 6


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Dipole</u>
<u>Band</u>	<u>CW1800</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>CW (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	1800.000000
Relative permittivity (real part)	53.242310
Relative permittivity (imaginary part)	15.601413
Conductivity (S/m)	1.563096
Variation (%)	1.240000

SURFACE SAR





VOLUME SAR



Maximum location: X=3.00, Y=2.00

SAR Peak: 6.82 W/kg

SAR 10g (W/Kg)	2.001079
SAR 1g (W/Kg)	3.716468



MEASUREMENT 7


A. Experimental conditions.

Area Scan	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
ZoomScan	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
Phantom	<u>Validation plane</u>
Device Position	<u>Dipole</u>
Band	<u>CW1900</u>
Channels	<u>Middle</u>
Signal	<u>CW (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	1900.000000
Relative permittivity (real part)	40.983087
Relative permittivity (imaginary part)	13.774000
Conductivity (S/m)	1.452036
Variation (%)	-3.360000

SURFACE SAR




VOLUME SAR




Maximum location: X=5.00, Y=2.00

SAR Peak: 6.70 W/kg


SAR 10g (W/Kg)	2.119456
SAR 1g (W/Kg)	3.660165



3D screen shot



Hot spot position



MEASUREMENT 8


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Dipole</u>
<u>Band</u>	<u>CW1900</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>CW (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	1900.000000
Relative permittivity (real part)	52.663435
Relative permittivity (imaginary part)	14.803103
Conductivity (S/m)	1.560066
Variation (%)	1.840000

SURFACE SAR





VOLUME SAR



Maximum location: X=5.00, Y=2.00

SAR Peak: 6.39 W/kg

SAR 10g (W/Kg)	2.139019
SAR 1g (W/Kg)	3.721402



MEASUREMENT 9


A. Experimental conditions.

Area Scan	<u>dx=12mm dy=12mm, h= 5.00 mm</u>
ZoomScan	<u>7x7x7,dx=5mm dy=5mm dz=5mm</u>
Phantom	<u>Validation plane</u>
Device Position	<u>Dipole</u>
Band	<u>CW2450</u>
Channels	<u>Middle</u>
Signal	<u>CW (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	2450.000000
Relative permittivity (real part)	38.961421
Relative permittivity (imaginary part)	13.472631
Conductivity (S/m)	1.832063
Variation (%)	-3.310000

SURFACE SAR





VOLUME SAR



Maximum location: X=0.00, Y=1.00

SAR Peak: 8.14 W/kg

SAR 10g (W/Kg)	2.412275
SAR 1g (W/Kg)	5.301415




MEASUREMENT 10

A. Experimental conditions.

<u>Area Scan</u>	<u>dx=12mm dy=12mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>7x7x7,dx=5mm dy=5mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Dipole</u>
<u>Band</u>	<u>CW2450</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>CW (Crest factor: 1.0)</u>

B. SAR Measurement Results



Frequency (MHz)	2450.000000
Relative permittivity (real part)	52.273497
Relative permittivity (imaginary part)	14.854266
Conductivity (S/m)	2.021316
Variation (%)	1.120000



Maximum location: X=0.00, Y=1.00

SAR Peak: 8.46 W/kg

SAR 10g (W/Kg)	2.330285
SAR 1g (W/Kg)	4.901270



MEASUREMENT 11


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=12mm dy=12mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>7x7x7,dx=5mm dy=5mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Dipole</u>
<u>Band</u>	<u>CW2600</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>CW (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	2600.000000
Relative permittivity (real part)	38.472685
Relative permittivity (imaginary part)	13.971997
Conductivity (S/m)	2.023171
Variation (%)	-2.940000

SURFACE SAR





VOLUME SAR



Maximum location: X=-1.00, Y=2.00

SAR Peak: 9.07 W/kg

SAR 10g (W/Kg)	2.314205
SAR 1g (W/Kg)	5.217867



MEASUREMENT 12


A. Experimental conditions.

Area Scan	<u>dx=12mm dy=12mm, h= 5.00 mm</u>
ZoomScan	<u>7x7x7,dx=5mm dy=5mm dz=5mm</u>
Phantom	<u>Validation plane</u>
Device Position	<u>Dipole</u>
Band	<u>CW2600</u>
Channels	<u>Middle</u>
Signal	<u>CW (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	2600.000000
Relative permittivity (real part)	52.682760
Relative permittivity (imaginary part)	15.334301
Conductivity (S/m)	2.210475
Variation (%)	-4.330000

SURFACE SAR





VOLUME SAR



Maximum location: X=0.00, Y=2.00

SAR Peak: 9.99 W/kg

SAR 10g (W/Kg)	2.228314
SAR 1g (W/Kg)	5.044167



13. Appendix C. Plots of High SAR Measurement

Table of contents
MEASUREMENT 1 GSM 850 Head
MEASUREMENT 2 GSM 850 Body
MEASUREMENT 3 GSM 1900 Head
MEASUREMENT 4 GSM 1900 Body
MEASUREMENT 5 WCDMA Band 2 Head
MEASUREMENT 6 WCDMA Band 2 Body
MEASUREMENT 7 WCDMA Band 4 Head
MEASUREMENT 8 WCDMA Band 4 Body
MEASUREMENT 9 WCDMA Band 5 Head
MEASUREMENT 10 WCDMA Band 5 Body
MEASUREMENT 11 WLAN 2.4G Head
MEASUREMENT 12 WLAN 2.4G Body
MEASUREMENT 13 LTE Band 2 Head
MEASUREMENT 14 LTE Band 2 Body
MEASUREMENT 15 LTE Band 4 Head
MEASUREMENT 16 LTE Band 4 Body
MEASUREMENT 17 LTE Band 5 Head
MEASUREMENT 18 LTE Band 5 Body
MEASUREMENT 19 LTE Band 7 Head
MEASUREMENT 20 LTE Band 7 Body
MEASUREMENT 21 LTE Band 12 Head
MEASUREMENT 22 LTE Band 12 Body
MEASUREMENT 23 LTE Band 17 Head
MEASUREMENT 24 LTE Band 17 Body
MEASUREMENT 25 LTE Band 19 Head
MEASUREMENT 26 LTE Band 19 Body

MEASUREMENT 1


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Left head</u>
<u>Device Position</u>	<u>Cheek</u>
<u>Band</u>	<u>GSM850</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>TDMA (Crest factor: 2.0)</u>


B. SAR Measurement Results

Frequency (MHz)	836.400000
Relative permittivity (real part)	40.630959
Relative permittivity (imaginary part)	20.001539
Conductivity (S/m)	0.929405
Variation (%)	0.910000

SURFACE SAR





VOLUME SAR



Maximum location: X=-48.00, Y=-24.00

SAR Peak: 0.36 W/kg

SAR 10g (W/Kg)	0.205974
SAR 1g (W/Kg)	0.275140



MEASUREMENT 2


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>GSM850</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>TDMA (Crest factor: 2.0)</u>


B. SAR Measurement Results

Frequency (MHz)	836.400000
Relative permittivity (real part)	54.459579
Relative permittivity (imaginary part)	21.642740
Conductivity (S/m)	1.005666
Variation (%)	-0.650000

SURFACE SAR





VOLUME SAR



Maximum location: X=-10.00, Y=-12.00

SAR Peak: 0.65 W/kg

SAR 10g (W/Kg)	0.374391
SAR 1g (W/Kg)	0.502410



MEASUREMENT 3


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Left head</u>
<u>Device Position</u>	<u>Cheek</u>
<u>Band</u>	<u>GSM1900</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>TDMA (Crest factor: 2.0)</u>


B. SAR Measurement Results

Frequency (MHz)	1880.000000
Relative permittivity (real part)	41.018200
Relative permittivity (imaginary part)	13.714300
Conductivity (S/m)	1.432382
Variation (%)	3.320000

SURFACE SAR





VOLUME SAR



Maximum location: X=-52.00, Y=-65.00

SAR Peak: 0.44 W/kg

SAR 10g (W/Kg)	0.148830
SAR 1g (W/Kg)	0.265337



MEASUREMENT 4


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>GSM1900</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>TDMA (Crest factor: 2.0)</u>


B. SAR Measurement Results

Frequency (MHz)	1880.000000
Relative permittivity (real part)	52.738899
Relative permittivity (imaginary part)	14.887700
Conductivity (S/m)	1.554938
Variation (%)	0.160000

SURFACE SAR





VOLUME SAR



Maximum location: X=3.00, Y=-12.00

SAR Peak: 0.60 W/kg

SAR 10g (W/Kg)	0.200407
SAR 1g (W/Kg)	0.365017



MEASUREMENT 5


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Left head</u>
<u>Device Position</u>	<u>Cheek</u>
<u>Band</u>	<u>Band2 WCDMA1900</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>WCDMA (Crest factor: 1.0)</u>


C. SAR Measurement Results

Frequency (MHz)	1880.000000
Relative permittivity (real part)	41.018200
Relative permittivity (imaginary part)	13.714300
Conductivity (S/m)	1.432382
Variation (%)	1.700000

SURFACE SAR





VOLUME SAR



Maximum location: X=-52.00, Y=-65.00

SAR Peak: 0.58 W/kg

SAR 10g (W/Kg)	0.209064
SAR 1g (W/Kg)	0.367473




MEASUREMENT 6

A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>Band2 WCDMA1900</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>WCDMA (Crest factor: 1.0)</u>

B. SAR Measurement Results



Frequency (MHz)	1880.000000
Relative permittivity (real part)	52.738899
Relative permittivity (imaginary part)	14.887700
Conductivity (S/m)	1.554938
Variation (%)	-0.280000



Maximum location: X=-8.00, Y=-43.00

SAR Peak: 0.78 W/kg

SAR 10g (W/Kg)	0.329195
SAR 1g (W/Kg)	0.537079



MEASUREMENT 7


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Left head</u>
<u>Device Position</u>	<u>Cheek</u>
<u>Band</u>	<u>Band4 WCDMA1700</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>WCDMA (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	1732.600000
Relative permittivity (real part)	39.017391
Relative permittivity (imaginary part)	13.985742
Conductivity (S/m)	1.345739
Variation (%)	0.260000

SURFACE SAR





VOLUME SAR



Maximum location: X=-49.00, Y=-50.00

SAR Peak: 0.82 W/kg

SAR 10g (W/Kg)	0.315190
SAR 1g (W/Kg)	0.520047



MEASUREMENT 8


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>Band4 WCDMA1700</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>WCDMA (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	1732.600000
Relative permittivity (real part)	53.636166
Relative permittivity (imaginary part)	15.641370
Conductivity (S/m)	1.505047
Variation (%)	-0.050000

SURFACE SAR





VOLUME SAR



Maximum location: X=-10.00, Y=-1.00

SAR Peak: 1.64 W/kg

SAR 10g (W/Kg)	0.722965
SAR 1g (W/Kg)	1.044901



MEASUREMENT 9


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Left head</u>
<u>Device Position</u>	<u>Cheek</u>
<u>Band</u>	<u>Band5 WCDMA850</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>WCDMA (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	836.400000
Relative permittivity (real part)	40.630959
Relative permittivity (imaginary part)	20.001539
Conductivity (S/m)	0.929405
Variation (%)	-0.540000

SURFACE SAR




VOLUME SAR



Maximum location: X=-47.00, Y=-28.00

SAR Peak: 0.14 W/kg

SAR 10g (W/Kg)	0.099534
SAR 1g (W/Kg)	0.124225



MEASUREMENT 10


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>Band5 WCDMA850</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>WCDMA (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	836.400000
Relative permittivity (real part)	54.459579
Relative permittivity (imaginary part)	21.642740
Conductivity (S/m)	1.005666
Variation (%)	-0.070000

SURFACE SAR





VOLUME SAR



Maximum location: X=-5.00, Y=13.00

SAR Peak: 0.26 W/kg

SAR 10g (W/Kg)	0.164807
SAR 1g (W/Kg)	0.212740



MEASUREMENT 11


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=12mm dy=12mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>7x7x7,dx=5mm dy=5mm dz=5mm</u>
<u>Phantom</u>	<u>Left head</u>
<u>Device Position</u>	<u>Cheek</u>
<u>Band</u>	<u>IEEE 802.11b ISM</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>IEEE802.11b (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	2437.000000
Relative permittivity (real part)	39.011002
Relative permittivity (imaginary part)	13.390300
Conductivity (S/m)	1.812898
Variation (%)	-2.480000

SURFACE SAR





VOLUME SAR



Maximum location: X=-25.00, Y=1.00

SAR Peak: 1.30 W/kg

SAR 10g (W/Kg)	0.308300
SAR 1g (W/Kg)	0.671373



MEASUREMENT 12


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=12mm dy=12mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>7x7x7,dx=5mm dy=5mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>IEEE 802.11b ISM</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>IEEE802.11b (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	2437.000000
Relative permittivity (real part)	52.331600
Relative permittivity (imaginary part)	14.805620
Conductivity (S/m)	2.004516
Variation (%)	-1.570000

SURFACE SAR





VOLUME SAR



Maximum location: X=-5.00, Y=13.00

SAR Peak: 0.40 W/kg

SAR 10g (W/Kg)	0.139377
SAR 1g (W/Kg)	0.143377



MEASUREMENT 13


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Left head</u>
<u>Device Position</u>	<u>Cheek</u>
<u>Band</u>	<u>LTE band 2</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>LTE (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	1880.000000
Relative permittivity (real part)	41.063801
Relative permittivity (imaginary part)	13.708100
Conductivity (S/m)	1.431354
Variation (%)	1.000000

SURFACE SAR





VOLUME SAR



Maximum location: X=-52.00, Y=-66.00

SAR Peak: 0.46 W/kg

SAR 10g (W/Kg)	0.167181
SAR 1g (W/Kg)	0.290829



MEASUREMENT 14


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>LTE band 2</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>LTE (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	1880.000000
Relative permittivity (real part)	52.745949
Relative permittivity (imaginary part)	14.896150
Conductivity (S/m)	1.555406
Variation (%)	-1.110000

SURFACE SAR





VOLUME SAR



Maximum location: X=-9.00, Y=-10.00

SAR Peak: 0.85 W/kg

SAR 10g (W/Kg)	0.351464
SAR 1g (W/Kg)	0.574444



MEASUREMENT 15


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Left head</u>
<u>Device Position</u>	<u>Cheek</u>
<u>Band</u>	<u>LTE band 4</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>LTE (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	1732.500000
Relative permittivity (real part)	39.025291
Relative permittivity (imaginary part)	13.970592
Conductivity (S/m)	1.344669
Variation (%)	-1.090000

SURFACE SAR





VOLUME SAR



Maximum location: X=-51.00, Y=-62.00

SAR Peak: 0.52 W/kg

SAR 10g (W/Kg)	0.220337
SAR 1g (W/Kg)	0.350539



MEASUREMENT 16


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>LTE band 4</u>
<u>Channels</u>	<u>High</u>
<u>Signal</u>	<u>LTE (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	1747.500000
Relative permittivity (real part)	53.526318
Relative permittivity (imaginary part)	15.611020
Conductivity (S/m)	1.512968
Variation (%)	-1.530000

SURFACE SAR





VOLUME SAR



Maximum location: X=-7.00, Y=-22.00

SAR Peak: 1.46 W/kg

SAR 10g (W/Kg)	0.651097
SAR 1g (W/Kg)	0.922363



MEASUREMENT 17


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Left head</u>
<u>Device Position</u>	<u>Cheek</u>
<u>Band</u>	<u>LTE band 5</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>LTE (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	836.500000
Relative permittivity (real part)	40.633549
Relative permittivity (imaginary part)	20.000200
Conductivity (S/m)	0.929454
Variation (%)	-0.040000

SURFACE SAR





VOLUME SAR



Maximum location: X=-47.00, Y=-22.00

SAR Peak: 0.12 W/kg

SAR 10g (W/Kg)	0.085655
SAR 1g (W/Kg)	0.106323



MEASUREMENT 18


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>LTE band 5</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>LTE (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	836.500000
Relative permittivity (real part)	54.463501
Relative permittivity (imaginary part)	21.636999
Conductivity (S/m)	1.005519
Variation (%)	-0.510000

SURFACE SAR





VOLUME SAR



Maximum location: X=-5.00, Y=10.00

SAR Peak: 0.22 W/kg

SAR 10g (W/Kg)	0.144645
SAR 1g (W/Kg)	0.185915



MEASUREMENT 19


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=12mm dy=12mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>7x7x7,dx=5mm dy=5mm dz=5mm</u>
<u>Phantom</u>	<u>Left head</u>
<u>Device Position</u>	<u>Cheek</u>
<u>Band</u>	<u>LTE band 7</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>LTE (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	2535.000000
Relative permittivity (real part)	38.805485
Relative permittivity (imaginary part)	13.841160
Conductivity (S/m)	1.949297
Variation (%)	-1.710000

SURFACE SAR





VOLUME SAR



Maximum location: X=-48.00, Y=-57.00

SAR Peak: 0.54 W/kg

SAR 10g (W/Kg)	0.146524
SAR 1g (W/Kg)	0.305468



MEASUREMENT 20


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=12mm dy=12mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>7x7x7,dx=5mm dy=5mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>LTE band 7</u>
<u>Channels</u>	<u>Low</u>
<u>Signal</u>	<u>LTE (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	2507.500000
Relative permittivity (real part)	53.132046
Relative permittivity (imaginary part)	15.140540
Conductivity (S/m)	2.111264
Variation (%)	-0.480000

SURFACE SAR





VOLUME SAR



Maximum location: X=-8.00, Y=-22.00

SAR Peak: 2.32 W/kg

SAR 10g (W/Kg)	0.630814
SAR 1g (W/Kg)	1.010619



MEASUREMENT 21


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Left head</u>
<u>Device Position</u>	<u>Cheek</u>
<u>Band</u>	<u>LTE band 12</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>LTE (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	707.500000
Relative permittivity (real part)	41.830959
Relative permittivity (imaginary part)	21.972778
Conductivity (S/m)	0.863652
Variation (%)	0.080000

SURFACE SAR





VOLUME SAR



Maximum location: X=-52.00, Y=-46.00

SAR Peak: 0.03 W/kg

SAR 10g (W/Kg)	0.024538
SAR 1g (W/Kg)	0.027478



MEASUREMENT 22


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>LTE band 12</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>LTE (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	707.500000
Relative permittivity (real part)	55.628460
Relative permittivity (imaginary part)	23.579800
Conductivity (S/m)	0.982492
Variation (%)	-3.020000

SURFACE SAR





VOLUME SAR



Maximum location: X=5.00, Y=3.00

SAR Peak: 0.07 W/kg

SAR 10g (W/Kg)	0.042211
SAR 1g (W/Kg)	0.052040



MEASUREMENT 23


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Left head</u>
<u>Device Position</u>	<u>Cheek</u>
<u>Band</u>	<u>LTE band 17</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>LTE (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	710.000000
Relative permittivity (real part)	41.809711
Relative permittivity (imaginary part)	22.001179
Conductivity (S/m)	0.867824
Variation (%)	-1.120000

SURFACE SAR





VOLUME SAR



Maximum location: X=10.00, Y=5.00

SAR Peak: 0.15 W/kg

SAR 10g (W/Kg)	0.038547
SAR 1g (W/Kg)	0.076981



MEASUREMENT 24


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>LTE band 17</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>LTE (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	710.000000
Relative permittivity (real part)	55.690762
Relative permittivity (imaginary part)	23.524500
Conductivity (S/m)	0.927911
Variation (%)	-1.020000

SURFACE SAR





VOLUME SAR



Maximum location: X=3.00, Y=2.00

SAR Peak: 0.08 W/kg

SAR 10g (W/Kg)	0.055370
SAR 1g (W/Kg)	0.067824



MEASUREMENT 25


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Left head</u>
<u>Device Position</u>	<u>Cheek</u>
<u>Band</u>	<u>LTE band 19</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>LTE (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	837.500000
Relative permittivity (real part)	40.637901
Relative permittivity (imaginary part)	19.981501
Conductivity (S/m)	0.929695
Variation (%)	0.100000

SURFACE SAR





VOLUME SAR



Maximum location: X=-10.00, Y=-7.00

SAR Peak: 0.19 W/kg

SAR 10g (W/Kg)	0.044770
SAR 1g (W/Kg)	0.094963



MEASUREMENT 26


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>LTE band 19</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>LTE (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	837.500000
Relative permittivity (real part)	54.452850
Relative permittivity (imaginary part)	21.643450
Conductivity (S/m)	1.007022
Variation (%)	0.010000

SURFACE SAR





VOLUME SAR



Maximum location: X=-5.00, Y=13.00

SAR Peak: 0.21 W/kg

SAR 10g (W/Kg)	0.137118
SAR 1g (W/Kg)	0.176808



14. Appendix D. Calibration Certificate

Table of contents
E Field Probe - SN 41/18 EPGO330
750 MHz Dipole - SN 03/15 DIP 0G750-355
835 MHz Dipole - SN 03/15 DIP 0G835-347
1800 MHz Dipole - SN 03/15 DIP 1G800-349
1900 MHz Dipole - SN 03/15 DIP 1G900-350
2450 MHz Dipole - SN 03/15 DIP 2G450-352
2600 MHz Dipole - SN 03/15 DIP 2G600-356



COMOSAR E-Field Probe Calibration Report

Ref : ACR.142.2.19.SATU.B

SHENZHEN NTEK TESTING TECHNOLOGY CO., LTD.
BUILDING E, FENDA SCIENCE PARK, SANWEI
COMMUNITY, XIXIANG STREET,
BAO'AN DISTRICT, SHENZHEN GUANGDONG, CHINA
MVG COMOSAR DOSIMETRIC E-FIELD PROBE
SERIAL NO.: SN 41/18 EPGO330

Calibrated at MVG US
2105 Barrett Park Dr. - Kennesaw, GA 30144



Calibration Date: 05/21/19

Summary:

This document presents the method and results from an accredited COMOSAR Dosimetric E-Field Probe calibration performed in MVG USA using the CALISAR / CALIBAIR test bench, for use with a COMOSAR system only. All calibration results are traceable to national metrology institutions.



COMOSAR E-FIELD PROBE CALIBRATION REPORT

Ref: ACR.142.2.19.SATU.B

	Name	Function	Date	Signature
Prepared by :	Jérôme LUC	Product Manager	5/22/2019	
Checked by :	Jérôme LUC	Product Manager	5/22/2019	
Approved by :	Kim RUTKOWSKI	Quality Manager	5/22/2019	

	Customer Name
Distribution :	CCIC SOUTHERN TESTING CO., LTD

Issue	Date	Modifications
A	5/22/2019	Initial release
B	5/27/2019	Change customer name and address



COMOSAR E-FIELD PROBE CALIBRATION REPORT

Ref: ACR.142.2.19.SATU.B

TABLE OF CONTENTS

1	Device Under Test	4
2	Product Description	4
2.1	General Information	4
3	Measurement Method	4
3.1	Linearity	4
3.2	Sensitivity	5
3.3	Lower Detection Limit	5
3.4	Isotropy	5
3.5	Boundary Effect	5
4	Measurement Uncertainty	5
5	Calibration Measurement Results	6
5.1	Sensitivity in air	6
5.2	Linearity	7
5.3	Sensitivity in liquid	7
5.4	Isotropy	8
6	List of Equipment	10



COMOSAR E-FIELD PROBE CALIBRATION REPORT

Ref: ACR.142.2.19.SATU.B

1 DEVICE UNDER TEST

Device Under Test	
Device Type	COMOSAR DOSIMETRIC E FIELD PROBE
Manufacturer	MVG
Model	SSE2
Serial Number	SN 41/18 EPGO330
Product Condition (new / used)	New
Frequency Range of Probe	0.15 GHz-6GHz
Resistance of Three Dipoles at Connector	Dipole 1: R1=0.186 MΩ Dipole 2: R2=0.191 MΩ Dipole 3: R3=0.201 MΩ

A yearly calibration interval is recommended.

2 PRODUCT DESCRIPTION

2.1 GENERAL INFORMATION

MVG's COMOSAR E field Probes are built in accordance to the IEEE 1528, OET 65 Bulletin C and CEI/IEC 62209 standards.



Figure 1 – MVG COMOSAR Dosimetric E field Dipole

Probe Length	330 mm
Length of Individual Dipoles	2 mm
Maximum external diameter	8 mm
Probe Tip External Diameter	2.5 mm
Distance between dipoles / probe extremity	1 mm

3 MEASUREMENT METHOD

The IEEE 1528, OET 65 Bulletin C, CENELEC EN50361 and CEI/IEC 62209 standards provide recommended practices for the probe calibrations, including the performance characteristics of interest and methods by which to assess their affect. All calibrations / measurements performed meet the fore mentioned standards.

3.1 LINEARITY

The evaluation of the linearity was done in free space using the waveguide, performing a power sweep to cover the SAR range 0.01W/kg to 100W/kg.



COMOSAR E-FIELD PROBE CALIBRATION REPORT

Ref: ACR.142.2.19.SATU.B

3.2 SENSITIVITY

The sensitivity factors of the three dipoles were determined using a two step calibration method (air and tissue simulating liquid) using waveguides as outlined in the standards.

3.3 LOWER DETECTION LIMIT

The lower detection limit was assessed using the same measurement set up as used for the linearity measurement. The required lower detection limit is 10 mW/kg.

3.4 ISOTROPY

The axial isotropy was evaluated by exposing the probe to a reference wave from a standard dipole with the dipole mounted under the flat phantom in the test configuration suggested for system validations and checks. The probe was rotated along its main axis from 0 - 360 degrees in 15 degree steps. The hemispherical isotropy is determined by inserting the probe in a thin plastic box filled with tissue-equivalent liquid, with the plastic box illuminated with the fields from a half wave dipole. The dipole is rotated about its axis (0°–180°) in 15° increments. At each step the probe is rotated about its axis (0°–360°).

3.5 BOUNDARY EFFECT

The boundary effect is defined as the deviation between the SAR measured data and the expected exponential decay in the liquid when the probe is oriented normal to the interface. To evaluate this effect, the liquid filled flat phantom is exposed to fields from either a reference dipole or waveguide. With the probe normal to the phantom surface, the peak spatial average SAR is measured and compared to the analytical value at the surface.

4 MEASUREMENT UNCERTAINTY

The guidelines outlined in the IEEE 1528, OET 65 Bulletin C, CENELEC EN50361 and CEI/IEC 62209 standards were followed to generate the measurement uncertainty associated with an E-field probe calibration using the waveguide technique. All uncertainties listed below represent an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2, traceable to the Internationally Accepted Guides to Measurement Uncertainty.

Uncertainty analysis of the probe calibration in waveguide					
ERROR SOURCES	Uncertainty value (%)	Probability Distribution	Divisor	ci	Standard Uncertainty (%)
Incident or forward power	3.00%	Rectangular	$\sqrt{3}$	1	1.732%
Reflected power	3.00%	Rectangular	$\sqrt{3}$	1	1.732%
Liquid conductivity	5.00%	Rectangular	$\sqrt{3}$	1	2.887%
Liquid permittivity	4.00%	Rectangular	$\sqrt{3}$	1	2.309%
Field homogeneity	3.00%	Rectangular	$\sqrt{3}$	1	1.732%
Field probe positioning	5.00%	Rectangular	$\sqrt{3}$	1	2.887%



COMOSAR E-FIELD PROBE CALIBRATION REPORT

Ref: ACR.142.2.19.SATU.B

Field probe linearity	3.00%	Rectangular	$\sqrt{3}$	1	1.732%
Combined standard uncertainty					5.831%
Expanded uncertainty 95 % confidence level k = 2					12.0%

5 CALIBRATION MEASUREMENT RESULTS

Calibration Parameters	
Liquid Temperature	21 °C
Lab Temperature	21 °C
Lab Humidity	45 %


5.1 SENSITIVITY IN AIR

Normx dipole 1 ($\mu\text{V}/(\text{V}/\text{m})^2$)	Normy dipole 2 ($\mu\text{V}/(\text{V}/\text{m})^2$)	Normz dipole 3 ($\mu\text{V}/(\text{V}/\text{m})^2$)
0.92	0.79	0.63

DCP dipole 1 (mV)	DCP dipole 2 (mV)	DCP dipole 3 (mV)
90	97	92

Calibration curves $e_i=f(V)$ ($i=1,2,3$) allow to obtain H-field value using the formula:

$$E = \sqrt{E_1^2 + E_2^2 + E_3^2}$$






COMOSAR E-FIELD PROBE CALIBRATION REPORT

Ref: ACR.142.2.19.SATU.B

5.2 LINEARITY

Linearity: $\pm 2.36\%$ ($\pm 0.10\text{dB}$)

5.3 SENSITIVITY IN LIQUID

Liquid	Frequency (MHz $\pm$ 100MHz)	Permittivity	Epsilon (S/m)	ConvF
HL750	750	40.76	0.93	1.54
BL750	750	56.70	0.98	1.59
HL850	835	40.86	0.92	1.60
BL850	835	56.35	0.99	1.64
HL900	900	42.84	0.95	1.61
BL900	900	53.25	1.05	1.65
HL1800	1800	39.56	1.40	1.74
BL1800	1800	52.84	1.45	1.81
HL1900	1900	39.67	1.38	2.03
BL1900	1900	52.84	1.59	2.08
HL2000	2000	38.71	1.42	1.86
BL2000	2000	52.03	1.52	1.92
HL2450	2450	38.72	1.80	2.05
BL2450	2450	54.91	1.97	2.12
HL2600	2600	39.98	1.89	2.06
BL2600	2600	54.42	2.18	2.11
HL5200	5200	36.68	4.45	1.85
BL5200	5200	49.02	5.46	1.92
HL5400	5400	36.08	4.69	1.75
BL5400	5400	49.55	5.53	1.83
HL5600	5600	35.34	4.95	1.88
BL5600	5600	47.60	5.77	1.95
HL5800	5800	34.81	5.08	1.89
BL5800	5800	47.81	6.12	1.94

LOWER DETECTION LIMIT: 9mW/kg

Page: 7/10

This document shall not be reproduced, except in full or in part, without the written approval of MVG.
The information contained herein is to be used only for the purpose for which it is submitted and is not to be released in whole or part without written approval of MVG.




COMOSAR E-FIELD PROBE CALIBRATION REPORT

Ref: ACR.142.2.19.SATU.B


5.4 ISOTROPY

HL900 MHz

- Axial isotropy: 0.05 dB
- Hemispherical isotropy: 0.07 dB

**HL1800 MHz**

- Axial isotropy: 0.06 dB
- Hemispherical isotropy: 0.07 dB






COMOSAR E-FIELD PROBE CALIBRATION REPORT

Ref: ACR.142.2.19.SATU.B

HL5600 MHz

- Axial isotropy: 0.06 dB
- Hemispherical isotropy: 0.09 dB





COMOSAR E-FIELD PROBE CALIBRATION REPORT

Ref: ACR.142.2.19.SATU.B

6 LIST OF EQUIPMENT

Equipment Summary Sheet				
Equipment Description	Manufacturer / Model	Identification No.	Current Calibration Date	Next Calibration Date
Flat Phantom	MVG	SN-20/09-SAM71	Validated. No cal required.	Validated. No cal required.
COMOSAR Test Bench	Version 3	NA	Validated. No cal required.	Validated. No cal required.
Network Analyzer	Rhode & Schwarz ZVA	SN100132	02/2019	02/2022
Reference Probe	MVG	EP 94 SN 37/08	10/2017	10/2019
Multimeter	Keithley 2000	1188656	01/2017	01/2020
Signal Generator	Agilent E4438C	MY49070581	01/2017	01/2020
Amplifier	Aethercomm	SN 046	Characterized prior to test. No cal required.	Characterized prior to test. No cal required.
Power Meter	HP E4418A	US38261498	01/2017	01/2020
Power Sensor	HP ECP-E26A	US37181460	01/2017	01/2020
Directional Coupler	Narda 4216-20	01386	Characterized prior to test. No cal required.	Characterized prior to test. No cal required.
Waveguide	Mega Industries	069Y7-158-13-712	Validated. No cal required.	Validated. No cal required.
Waveguide Transition	Mega Industries	069Y7-158-13-701	Validated. No cal required.	Validated. No cal required.
Waveguide Termination	Mega Industries	069Y7-158-13-701	Validated. No cal required.	Validated. No cal required.
Temperature / Humidity Sensor	Control Company	150798832	11/2017	11/2020



SAR Reference Dipole Calibration Report

Ref : ACR.109.1.18.SATU.A

**SHENZHEN NTEK TESTING TECHNOLOGY
CO., LTD.**

**BUILDING E, FENDA SCIENCE PARK, SANWEI
COMMUNITY, XIXIANG STREET,
BAO'AN DISTRICT, SHENZHEN GUANGDONG, CHINA
MVG COMOSAR REFERENCE DIPOLE**

FREQUENCY: 750 MHZ

SERIAL NO.: SN 03/15 DIP 0G750-355

Calibrated at MVG US

2105 Barrett Park Dr. - Kennesaw, GA 30144



Calibration Date: 04/19/2018

Summary:

This document presents the method and results from an accredited SAR reference dipole calibration performed in MVG USA using the COMOSAR test bench. All calibration results are traceable to national metrology institutions.



SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref: ACR.109.1.18.SATU.A

	Name	Function	Date	Signature
Prepared by :	Jérôme LUC	Product Manager	4/19/2018	<i>JS</i>
Checked by :	Jérôme LUC	Product Manager	4/19/2018	<i>JS</i>
Approved by :	Kim RUTKOWSKI	Quality Manager	4/19/2018	<i>Kim Rutkowski</i>

	Customer Name
Distribution :	SHENZHEN NTEK TESTING TECHNOLOGY CO., LTD.

Issue	Date	Modifications
A	4/19/2018	Initial release



SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref: ACR.109.1.18.SATU.A

TABLE OF CONTENTS

1	Introduction.....	4
2	Device Under Test	4
3	Product Description	4
3.1	General Information	4
4	Measurement Method	5
4.1	Return Loss Requirements	5
4.2	Mechanical Requirements	5
5	Measurement Uncertainty.....	5
5.1	Return Loss	5
5.2	Dimension Measurement	5
5.3	Validation Measurement	5
6	Calibration Measurement Results.....	6
6.1	Return Loss and Impedance In Head Liquid	6
6.2	Return Loss and Impedance In Body Liquid	6
6.3	Mechanical Dimensions	6
7	Validation measurement	7
7.1	Head Liquid Measurement	7
7.2	SAR Measurement Result With Head Liquid	8
7.3	Body Liquid Measurement	9
7.4	SAR Measurement Result With Body Liquid	10
8	List of Equipment	11



SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref: ACR.109.1.18.SATU.A

1 INTRODUCTION

This document contains a summary of the requirements set forth by the IEEE 1528, FCC KDBs and CEI/IEC 62209 standards for reference dipoles used for SAR measurement system validations and the measurements that were performed to verify that the product complies with the fore mentioned standards.

2 DEVICE UNDER TEST

Device Under Test	
Device Type	COMOSAR 750 MHz REFERENCE DIPOLE
Manufacturer	MVG
Model	SID750
Serial Number	SN 03/15 DIP 0G750-355
Product Condition (new / used)	Used

A yearly calibration interval is recommended.

3 PRODUCT DESCRIPTION

3.1 GENERAL INFORMATION

MVG's COMOSAR Validation Dipoles are built in accordance to the IEEE 1528, FCC KDBs and CEI/IEC 62209 standards. The product is designed for use with the COMOSAR test bench only.



Figure 1 – MVG COMOSAR Validation Dipole



SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref: ACR.109.1.18.SATU.A

4 MEASUREMENT METHOD

The IEEE 1528, FCC KDBs and CEI/IEC 62209 standards provide requirements for reference dipoles used for system validation measurements. The following measurements were performed to verify that the product complies with the fore mentioned standards.

4.1 RETURN LOSS REQUIREMENTS

The dipole used for SAR system validation measurements and checks must have a return loss of -20 dB or better. The return loss measurement shall be performed against a liquid filled flat phantom, with the phantom constructed as outlined in the fore mentioned standards.

4.2 MECHANICAL REQUIREMENTS

The IEEE Std. 1528 and CEI/IEC 62209 standards specify the mechanical components and dimensions of the validation dipoles, with the dimensions frequency and phantom shell thickness dependent. The COMOSAR test bench employs a 2 mm phantom shell thickness therefore the dipoles sold for use with the COMOSAR test bench comply with the requirements set forth for a 2 mm phantom shell thickness.

5 MEASUREMENT UNCERTAINTY

All uncertainties listed below represent an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$, traceable to the Internationally Accepted Guides to Measurement Uncertainty.

5.1 RETURN LOSS

The following uncertainties apply to the return loss measurement:

Frequency band	Expanded Uncertainty on Return Loss
400-6000MHz	0.1 dB

5.2 DIMENSION MEASUREMENT

The following uncertainties apply to the dimension measurements:

Length (mm)	Expanded Uncertainty on Length
3 - 300	0.05 mm

5.3 VALIDATION MEASUREMENT

The guidelines outlined in the IEEE 1528, FCC KDBs, CENELEC EN50361 and CEI/IEC 62209 standards were followed to generate the measurement uncertainty for validation measurements.

Scan Volume	Expanded Uncertainty
1 g	20.3 %



SAR REFERENCE DIPOLE CALIBRATION REPORT


Ref: ACR.109.1.18.SATU.A

10 g

20.1 %


6 CALIBRATION MEASUREMENT RESULTS

6.1 RETURN LOSS AND IMPEDANCE IN HEAD LIQUID



Frequency (MHz)	Return Loss (dB)	Requirement (dB)	Impedance
750	-35.83	-20	51.3 Ω - 1.2 j Ω

6.2 RETURN LOSS AND IMPEDANCE IN BODY LIQUID



Frequency (MHz)	Return Loss (dB)	Requirement (dB)	Impedance
750	-32.65	-20	50.8 Ω + 2.3 j Ω

6.3 MECHANICAL DIMENSIONS

Frequency MHz	L mm		h mm		d mm	
	required	measured	required	measured	required	measured
300	420.0 $\pm$ 1 %		250.0 $\pm$ 1 %		6.35 $\pm$ 1 %	

Page: 6/11

This document shall not be reproduced, except in full or in part, without the written approval of MVG.
The information contained herein is to be used only for the purpose for which it is submitted and is not to be released in whole or part without written approval of MVG.



SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref: ACR.109.1.18.SATU.A

450	290.0 ±1 %.		166.7 ±1 %.		6.35 ±1 %.	
750	176.0 ±1 %.	PASS	100.0 ±1 %.	PASS	6.35 ±1 %.	PASS
835	161.0 ±1 %.		89.8 ±1 %.		3.6 ±1 %.	
900	149.0 ±1 %.		83.3 ±1 %.		3.6 ±1 %.	
1450	89.1 ±1 %.		51.7 ±1 %.		3.6 ±1 %.	
1500	80.5 ±1 %.		50.0 ±1 %.		3.6 ±1 %.	
1640	79.0 ±1 %.		45.7 ±1 %.		3.6 ±1 %.	
1750	75.2 ±1 %.		42.9 ±1 %.		3.6 ±1 %.	
1800	72.0 ±1 %.		41.7 ±1 %.		3.6 ±1 %.	
1900	68.0 ±1 %.		39.5 ±1 %.		3.6 ±1 %.	
1950	66.3 ±1 %.		38.5 ±1 %.		3.6 ±1 %.	
2000	64.5 ±1 %.		37.5 ±1 %.		3.6 ±1 %.	
2100	61.0 ±1 %.		35.7 ±1 %.		3.6 ±1 %.	
2300	55.5 ±1 %.		32.6 ±1 %.		3.6 ±1 %.	
2450	51.5 ±1 %.		30.4 ±1 %.		3.6 ±1 %.	
2600	48.5 ±1 %.		28.8 ±1 %.		3.6 ±1 %.	
3000	41.5 ±1 %.		25.0 ±1 %.		3.6 ±1 %.	
3500	37.0 ±1 %.		26.4 ±1 %.		3.6 ±1 %.	
3700	34.7 ±1 %.		26.4 ±1 %.		3.6 ±1 %.	

7 VALIDATION MEASUREMENT

The IEEE Std. 1528, FCC KDBs and CEI/IEC 62209 standards state that the system validation measurements must be performed using a reference dipole meeting the fore mentioned return loss and mechanical dimension requirements. The validation measurement must be performed against a liquid filled flat phantom, with the phantom constructed as outlined in the fore mentioned standards. Per the standards, the dipole shall be positioned below the bottom of the phantom, with the dipole length centered and parallel to the longest dimension of the flat phantom, with the top surface of the dipole at the described distance from the bottom surface of the phantom.

7.1 HEAD LIQUID MEASUREMENT

Frequency MHz	Relative permittivity (ϵ_r')		Conductivity (σ) S/m	
	required	measured	required	measured
300	45.3 ±5 %		0.87 ±5 %	
450	43.5 ±5 %		0.87 ±5 %	
750	41.9 ±5 %	PASS	0.89 ±5 %	PASS
835	41.5 ±5 %		0.90 ±5 %	
900	41.5 ±5 %		0.97 ±5 %	
1450	40.5 ±5 %		1.20 ±5 %	
1500	40.4 ±5 %		1.23 ±5 %	
1640	40.2 ±5 %		1.31 ±5 %	
1750	40.1 ±5 %		1.37 ±5 %	

Page: 7/11

This document shall not be reproduced, except in full or in part, without the written approval of MVG.
The information contained herein is to be used only for the purpose for which it is submitted and is not to be released in whole or part without written approval of MVG.



SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref: ACR.109.1.18.SATU.A

1800	40.0 ±5 %		1.40 ±5 %	
1900	40.0 ±5 %		1.40 ±5 %	
1950	40.0 ±5 %		1.40 ±5 %	
2000	40.0 ±5 %		1.40 ±5 %	
2100	39.8 ±5 %		1.49 ±5 %	
2300	39.5 ±5 %		1.67 ±5 %	
2450	39.2 ±5 %		1.80 ±5 %	
2600	39.0 ±5 %		1.96 ±5 %	
3000	38.5 ±5 %		2.40 ±5 %	
3500	37.9 ±5 %		2.91 ±5 %	

7.2 SAR MEASUREMENT RESULT WITH HEAD LIQUID

The IEEE Std. 1528 and CEI/IEC 62209 standards state that the system validation measurements should produce the SAR values shown below (for phantom thickness of 2 mm), within the uncertainty for the system validation. All SAR values are normalized to 1 W forward power. In bracket, the measured SAR is given with the used input power.

Software	OPENSAR V4
Phantom	SN 20/09 SAM71
Probe	SN 18/11 EPG122
Liquid	Head Liquid Values: ϵ_{ps}^* : 40.0 σ : 0.93
Distance between dipole center and liquid	15.0 mm
Area scan resolution	$dx=8mm/dy=8mm$
Zoon Scan Resolution	$dx=8mm/dy=8mm/dz=5mm$
Frequency	750 MHz
Input power	20 dBm
Liquid Temperature	21 °C
Lab Temperature	21 °C
Lab Humidity	45 %

Frequency MHz	1 g SAR (W/kg/W)		10 g SAR (W/kg/W)	
	required	measured	required	measured
300	2.85		1.94	
450	4.58		3.06	
750	8.49	8.56 (0.86)	5.55	5.61 (0.56)
835	9.56		6.22	
900	10.9		6.99	
1450	29		16	
1500	30.5		16.8	
1640	34.2		18.4	
1750	36.4		19.3	
1800	38.4		20.1	

Page: 8/11



This document shall not be reproduced, except in full or in part, without the written approval of MVG.
The information contained herein is to be used only for the purpose for which it is submitted and is not to be released in whole or part without written approval of MVG.



SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref: ACR.109.1.18.SATU.A

1900	39.7		20.5	
1950	40.5		20.9	
2000	41.1		21.1	
2100	43.6		21.9	
2300	48.7		23.3	
2450	52.4		24	
2600	55.3		24.6	
3000	63.8		25.7	
3500	67.1		25	
3700	67.4		24.2	



7.3 BODY LIQUID MEASUREMENT

Frequency MHz	Relative permittivity (ϵ_r')		Conductivity (σ) S/m	
	required	measured	required	measured
150	61.9 $\pm$ 5 %		0.80 $\pm$ 5 %	
300	58.2 $\pm$ 5 %		0.92 $\pm$ 5 %	
450	56.7 $\pm$ 5 %		0.94 $\pm$ 5 %	
750	55.5 $\pm$ 5 %	PASS	0.96 $\pm$ 5 %	PASS
835	55.2 $\pm$ 5 %		0.97 $\pm$ 5 %	
900	55.0 $\pm$ 5 %		1.05 $\pm$ 5 %	
915	55.0 $\pm$ 5 %		1.06 $\pm$ 5 %	
1450	54.0 $\pm$ 5 %		1.30 $\pm$ 5 %	
1610	53.8 $\pm$ 5 %		1.40 $\pm$ 5 %	
1800	53.3 $\pm$ 5 %		1.52 $\pm$ 5 %	
1900	53.3 $\pm$ 5 %		1.52 $\pm$ 5 %	
2000	53.3 $\pm$ 5 %		1.52 $\pm$ 5 %	
2100	53.2 $\pm$ 5 %		1.62 $\pm$ 5 %	

Page: 9/11

This document shall not be reproduced, except in full or in part, without the written approval of MVG.
The information contained herein is to be used only for the purpose for which it is submitted and is not to be released in whole or part without written approval of MVG.



SAR REFERENCE DIPOLE CALIBRATION REPORT



Ref: ACR.109.1.18.SATU.A

2300	52.9 ±5 %		1.81 ±5 %	
2450	52.7 ±5 %		1.95 ±5 %	
2600	52.5 ±5 %		2.16 ±5 %	
3000	52.0 ±5 %		2.73 ±5 %	
3500	51.3 ±5 %		3.31 ±5 %	
3700	51.0 ±5 %		3.55 ±5 %	
5200	49.0 ±10 %		5.30 ±10 %	
5300	48.9 ±10 %		5.42 ±10 %	
5400	48.7 ±10 %		5.53 ±10 %	
5500	48.6 ±10 %		5.65 ±10 %	
5600	48.5 ±10 %		5.77 ±10 %	
5800	48.2 ±10 %		6.00 ±10 %	

7.4 SAR MEASUREMENT RESULT WITH BODY LIQUID

Software	OPENSAR V4
Phantom	SN 20/09 SAM71
Probe	SN 18/11 EPG122
Liquid	Body Liquid Values: ϵ_{ps}^* : 56.8 sigma : 1.00
Distance between dipole center and liquid	15.0 mm
Area scan resolution	dx=8mm/dy=8mm
Zoon Scan Resolution	dx=8mm/dy=8mm/dz=5mm
Frequency	750 MHz
Input power	20 dBm
Liquid Temperature	21 °C
Lab Temperature	21 °C
Lab Humidity	45 %

Frequency MHz	1 g SAR (W/kg/W)	10 g SAR (W/kg/W)
	measured	measured
750	8.85 (0.89)	5.91 (0.59)



Page: 10/11

This document shall not be reproduced, except in full or in part, without the written approval of MVG.
The information contained herein is to be used only for the purpose for which it is submitted and is not to be released in whole or part without written approval of MVG.



SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref: ACR.109.1.18.SATU.A

8 LIST OF EQUIPMENT

Equipment Summary Sheet				
Equipment Description	Manufacturer / Model	Identification No.	Current Calibration Date	Next Calibration Date
SAM Phantom	MVG	SN-20/09-SAM71	Validated. No cal required.	Validated. No cal required.
COMOSAR Test Bench	Version 3	NA	Validated. No cal required.	Validated. No cal required.
Network Analyzer	Rhode & Schwarz ZVA	SN100132	02/2016	02/2019
Calipers	Carrera	CALIPER-01	01/2017	01/2020
Reference Probe	MVG	EPG122 SN 18/11	10/2017	10/2018
Multimeter	Keithley 2000	1188656	01/2017	01/2020
Signal Generator	Agilent E4438C	MY49070581	01/2017	01/2020
Amplifier	Aethercomm	SN 046	Characterized prior to test. No cal required.	Characterized prior to test. No cal required.
Power Meter	HP E4418A	US38261498	01/2017	01/2020
Power Sensor	HP ECP-E26A	US37181460	01/2017	01/2020
Directional Coupler	Narda 4216-20	01386	Characterized prior to test. No cal required.	Characterized prior to test. No cal required.
Temperature and Humidity Sensor	Control Company	150798832	11/2017	11/2020



SAR Reference Dipole Calibration Report

Ref : ACR.109.2.18.SATU.A

SHENZHEN NTEK TESTING TECHNOLOGY CO., LTD.

BUILDING E, FENDA SCIENCE PARK, SANWEI
COMMUNITY, XIXIANG STREET,
BAO'AN DISTRICT, SHENZHEN GUANGDONG, CHINA
MVG COMOSAR REFERENCE DIPOLE

FREQUENCY: 835 MHZ

SERIAL NO.: SN 03/15 DIP 0G835-347

Calibrated at MVG US

2105 Barrett Park Dr. - Kennesaw, GA 30144



Calibration Date: 04/19/2018

Summary:

This document presents the method and results from an accredited SAR reference dipole calibration performed in MVG USA using the COMOSAR test bench. All calibration results are traceable to national metrology institutions.



SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref: ACR.109.2.18.SATU.A

	Name	Function	Date	Signature
Prepared by :	Jérôme LUC	Product Manager	4/19/2018	<i>JS</i>
Checked by :	Jérôme LUC	Product Manager	4/19/2018	<i>JS</i>
Approved by :	Kim RUTKOWSKI	Quality Manager	4/19/2018	<i>Kim Rutkowski</i>

	Customer Name
Distribution :	SHENZHEN NTEK TESTING TECHNOLOGY CO., LTD.

Issue	Date	Modifications
A	4/19/2018	Initial release



SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref: ACR.109.2.18.SATU.A

TABLE OF CONTENTS

1	Introduction.....	4
2	Device Under Test	4
3	Product Description	4
3.1	General Information	4
4	Measurement Method	5
4.1	Return Loss Requirements	5
4.2	Mechanical Requirements	5
5	Measurement Uncertainty.....	5
5.1	Return Loss	5
5.2	Dimension Measurement	5
5.3	Validation Measurement	5
6	Calibration Measurement Results.....	6
6.1	Return Loss and Impedance In Head Liquid	6
6.2	Return Loss and Impedance In Body Liquid	6
6.3	Mechanical Dimensions	6
7	Validation measurement	7
7.1	Head Liquid Measurement	7
7.2	SAR Measurement Result With Head Liquid	8
7.3	Body Liquid Measurement	9
7.4	SAR Measurement Result With Body Liquid	10
8	List of Equipment	11



SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref: ACR.109.2.18.SATU.A

1 INTRODUCTION

This document contains a summary of the requirements set forth by the IEEE 1528, FCC KDBs and CEI/IEC 62209 standards for reference dipoles used for SAR measurement system validations and the measurements that were performed to verify that the product complies with the fore mentioned standards.

2 DEVICE UNDER TEST

Device Under Test	
Device Type	COMOSAR 835 MHz REFERENCE DIPOLE
Manufacturer	MVG
Model	SID835
Serial Number	SN 03/15 DIP 0G835-347
Product Condition (new / used)	Used

A yearly calibration interval is recommended.

3 PRODUCT DESCRIPTION

3.1 GENERAL INFORMATION

MVG's COMOSAR Validation Dipoles are built in accordance to the IEEE 1528, FCC KDBs and CEI/IEC 62209 standards. The product is designed for use with the COMOSAR test bench only.



Figure 1 – MVG COMOSAR Validation Dipole



SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref: ACR.109.2.18.SATU.A

4 MEASUREMENT METHOD

The IEEE 1528, FCC KDBs and CEI/IEC 62209 standards provide requirements for reference dipoles used for system validation measurements. The following measurements were performed to verify that the product complies with the fore mentioned standards.

4.1 RETURN LOSS REQUIREMENTS

The dipole used for SAR system validation measurements and checks must have a return loss of -20 dB or better. The return loss measurement shall be performed against a liquid filled flat phantom, with the phantom constructed as outlined in the fore mentioned standards.

4.2 MECHANICAL REQUIREMENTS

The IEEE Std. 1528 and CEI/IEC 62209 standards specify the mechanical components and dimensions of the validation dipoles, with the dimensions frequency and phantom shell thickness dependent. The COMOSAR test bench employs a 2 mm phantom shell thickness therefore the dipoles sold for use with the COMOSAR test bench comply with the requirements set forth for a 2 mm phantom shell thickness.

5 MEASUREMENT UNCERTAINTY

All uncertainties listed below represent an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$, traceable to the Internationally Accepted Guides to Measurement Uncertainty.

5.1 RETURN LOSS

The following uncertainties apply to the return loss measurement:

Frequency band	Expanded Uncertainty on Return Loss
400-6000MHz	0.1 dB

5.2 DIMENSION MEASUREMENT

The following uncertainties apply to the dimension measurements:

Length (mm)	Expanded Uncertainty on Length
3 - 300	0.05 mm

5.3 VALIDATION MEASUREMENT

The guidelines outlined in the IEEE 1528, FCC KDBs, CENELEC EN50361 and CEI/IEC 62209 standards were followed to generate the measurement uncertainty for validation measurements.

Scan Volume	Expanded Uncertainty
1 g	20.3 %