

<u>+</u>	E							CUSTOMER:		
Ξ	C1	C1 C2 C3 C4								
	0.1	0.1	0.15	5	0.2					
	0.2	0.3	0.4		0.5	TITLE:		MODEL:		
	0.25	0.5	0.9		1.2	说明	说明书			
)	0.3	0.8	1.2		1.5					
5	0.5	1.3	1.8		3	UNIT'S	Ν	J/A	VER:	
0	0.7	1.5	2.5		4	MAT'L	N/A		SCVIE	1.1
0	0.9	1.8	3		5				SCALE	1:1
t	0°~30°/0.1° 30°~60°		/0.3°	60°~90	)°/0.5°	FINISH	Ν	<b>J/A</b>	SHEET	1/1
			2	4						5

			6		
		版本	履历	日期	
		V1.0	初版	20200506	
					٨
					A
nterfere	not more than <b>20</b> meters. And nce, such as <b>microwave ovens</b> ,				
	or about 50s, the blue indicator LED indicator of the secondary				
oor					
	y using the SSID and password				
	on with any other antenna or y other antenna or transmitter.				
th for a	n uncontrolled environment. This etween the radiator & your body.				В
,					
					С
	COMNEC	TM	└╽╽╽╺╧╾╴/╼╕┯╲╱╶┯╾╺╕┍┑╺╱╷╵		
	Easily Connecting	- 洑 ( ) m	圳市亿联无限科 inect Technolog	技有限公司 w Coll+d	
			PART NO.:	, y CO., Llu	
					Π
	DRAW	T			
	CHECK	李乔			
	APPD				
			6		