

Prüfbericht-Nr.: <i>Test Report No.:</i>	50182194 001	Auftrags-Nr.: <i>Order No.:</i>	114080743	Seite 1 von 48 <i>Page 1 of 48</i>
Kunden-Referenz-Nr.: <i>Client Reference No.:</i>	N/A	Auftragsdatum: <i>Order date:</i>	8-Aug-2018	
Auftraggeber: <i>Client:</i>	PAMEX INC. 4680 VINITA COURT, CHINO, CA, United States 91710			
Prüfgegenstand: <i>Test item:</i>	Wall Reader			
Bezeichnung / Typ-Nr.: <i>Identification / Type No.:</i>	Kapture KA-WR1N			
Auftrags-Inhalt: <i>Order content:</i>	FCC Part 15C (WiFi 2.4GHz)			
Prüfgrundlage: <i>Test specification:</i>	FCC 47CFR Part 15: Subpart C Section 15.247			
Wareneingangsdatum: <i>Date of receipt:</i>	27-Aug-2018			
Prüfmuster-Nr.: <i>Test sample No.:</i>	A000797975-001 Rad A000797975-002 Cond			
Prüfzeitraum: <i>Testing period:</i>	31-Aug-2018 - 12-Sep-2018			
Ort der Prüfung: <i>Place of testing:</i>	EMC/RF Laboratory Taipei			
Prüflaboratorium: <i>Testing laboratory:</i>	TUV Rheinland Taiwan Ltd.			
Prüfergebnis*: <i>Test result*:</i>	Pass			
geprüft von / tested by:		kontrolliert von / reviewed by:		
2018-09-20 Mars Y. J. Lin / Project Engineer		2018-09-20 Ryan W. T. Chen / Project Manager		
Datum <i>Date</i>	Name / Stellung <i>Name / Position</i>	Unterschrift <i>Signature</i>	Datum <i>Date</i>	Name / Stellung <i>Name / Position</i>
Sonstiges / Other:				
Zustand des Prüfgegenstandes bei Anlieferung: <i>Condition of the test item at delivery:</i>		Prüfmuster vollständig und unbeschädigt <i>Test item complete and undamaged</i>		
* Legende: 1 = sehr gut 2 = gut 3 = befriedigend 4 = ausreichend 5 = mangelhaft P(ass) = entspricht o.g. Prüfgrundlage(n) F(ail) = entspricht nicht o.g. Prüfgrundlage(n) N/A = nicht anwendbar N/T = nicht getestet Legend: 1 = very good 2 = good 3 = satisfactory 4 = sufficient 5 = poor P(ass) = passed a.m. test specification(s) F(ail) = failed a.m. test specification(s) N/A = not applicable N/T = not tested				
Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens. <i>This test report only relates to the a. m. test sample. Without permission of the test center this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any test mark.</i>				

TEST SUMMARY

5.1.1 ANTENNA REQUIREMENT

RESULT: Passed

5.1.2 PEAK OUTPUT POWER

RESULT: Passed

5.1.3 6dB BANDWIDTH

RESULT: Passed

5.1.4 POWER DENSITY

RESULT: Passed

5.1.5 CONDUCTED SPURIOUS EMISSIONS AND FREQUENCY BAND EDGE MEASURED IN 100kHz BANDWIDTH

RESULT: Passed

5.1.6 SPURIOUS EMISSION

RESULT: Passed

5.2.1 MAINS CONDUCTED EMISSIONS

RESULT: Passed

6.1.1 ELECTROMAGNETIC FIELDS

RESULT: Passed

Contents

1.	GENERAL REMARKS	5
1.1	COMPLEMENTARY MATERIALS.....	5
2.	TEST SITES	6
2.1	TEST LABORATORY	6
2.2	TEST FACILITIES	6
2.3	LIST OF TEST AND MEASUREMENT INSTRUMENTS.....	7
2.4	TRACEABILITY	8
2.5	CALIBRATION	8
2.6	MEASUREMENT UNCERTAINTY	8
3.	GENERAL PRODUCT INFORMATION.....	9
3.1	PRODUCT FUNCTION AND INTENDED USE	9
3.2	SYSTEM DETAILS AND RATINGS.....	9
3.3	INDEPENDENT OPERATION MODES.....	10
3.4	NOISE GENERATING AND NOISE SUPPRESSING PARTS	10
3.5	SUBMITTED DOCUMENTS.....	10
4.	TEST SET-UP AND OPERATION MODES.....	11
4.1	PRINCIPLE OF CONFIGURATION SELECTION	11
4.2	TEST OPERATION AND TEST SOFTWARE.....	11
4.3	ADDITIONAL ACCESSORIES AND AUXILIARY EQUIPMENT	12
4.4	COUNTERMEASURES TO ACHIEVE EMC COMPLIANCE.....	12
4.5	TEST SETUP DIAGRAM	12
5.	TEST RESULTS	14
5.1	TRANSMITTER REQUIREMENT & TEST SUITES.....	14
5.1.1	<i>Antenna Requirement</i>	<i>14</i>
5.1.2	<i>Peak Output Power</i>	<i>15</i>
5.1.3	<i>6dB Bandwidth</i>	<i>17</i>
5.1.4	<i>Power Density</i>	<i>25</i>
5.1.5	<i>Conducted spurious emissions and Frequency Band Edge measured in 100kHz Bandwidth.....</i>	<i>32</i>
5.1.6	<i>Spurious Emission</i>	<i>42</i>
5.2	MAINS EMISSIONS.....	43
5.2.1	<i>Mains Conducted Emissions.....</i>	<i>43</i>
6.	SAFETY HUMAN EXPOSURE	44

Prüfbericht - Nr.: 50182194 001

Test Report No.

Seite 4 von 48

Page 4 of 48

6.1	RADIO FREQUENCY EXPOSURE COMPLIANCE	44
6.1.1	Electromagnetic Fields.....	44
7.	PHOTOGRAPHS OF THE TEST SET-UP.....	45
8.	LIST OF TABLES	48
9.	LIST OF PHOTOGRAPHS.....	48

1. General Remarks

1.1 Complementary Materials

The following attachments are integral parts of this test report:

Appendix P: Photo Documentation

(File Name: 50182194 001APPENDIX P)

Appendix D: Test Result of Radiated Emissions

(File Name: 50182194 001APPENDIX D)

Test Specifications

The following standards were applied (in bold: product standards, otherwise: basic standards).

Table 1: Applied Standard and Test Levels

Radio
FCC CFR47 Part 15: Subpart C Section 15.247
ANSI C63.10:2013
KDB558074 D01 DTS Meas Guidance v04

2. Test Sites

2.1 Test Laboratory

TUV Rheinland Taiwan Ltd.
Taichung Branch Office

No.9, Lane 36, Minsheng Rd., Sec. 3, Daya District,
Taichung City 428
Taiwan (R.O.C.)

2.2 Test Facilities

TUV Rheinland Taiwan Ltd.
Taipei Office

11F. No.758, Sec. 4, Bade Rd., Songshan Dist.
Taipei City 105
Taiwan (R.O.C.)

FCC RegistrationNo.: 340738
IC Canada Registration No.: 9465A-1
TAF Accredited NCC Test Lab. No.:0759
TAF ISO17025 Certification effective periods: 2016-Jul-1st to 2019-Jun-30th



Testing Laboratory
0759

2.3 List of Test and Measurement Instruments

Table 2: List of Test and Measurement Equipment

Kind of Equipment	Manu-facturer	Type	S/N	Last Calibration	Next Calibration
Test Software	Farad	EZ_EMC	Ver. TUV3A1	N/A	N/A
EMI Test Receiver	R&S	ESR7	101062	2018/09/12	2019/09/12
Spectrum Analyzer	R&S	FSV 40	100921	2018/04/21	2019/04/21
Spectrum Analyzer	Agilent	N9010A	MY53470241	2018/04/25	2019/04/24
Preamplifier (30MHz -1GHz)	HP	8447F	2805A03335	2018/07/29	2019/07/29
Preamplifier (18 GHz -40 GHz)	COM-POWER	PAM-840	461257	2017/11/19	2018/11/19
Pre-Amplifier (1GHz~18GHz)	EM Electronics	EM01G18G	060558	2017/11/19	2018/11/19
Bilog Antenna	TESEQ	CBL6111D	29804	2018/06/23	2019/06/23
Horn Antenna	ETS-Lindgren	3117	138160	2018/05/03	2019/05/03
Horn Antenna (18GHz~40GHz)	COM-POWER	AH840	101031	2017/11/02	2018/11/02
EMI Test Receiver	R&S	ESCI7	100797	2017/12/28	2018/12/27
Temp. & Humid. Chamber	Giant Force	GCT-099-40-S	MAF0103-007	2018/07/13	2019/07/12
LISN (1 phase)	R&S	ENV216	101243	2018/06/02	2019/06/02
LISN	R&S	ENV216	101262	2018/06/16	2019/06/16
Test Software	Audix	e3	Ver. 9	N/A	N/A
Test Software	Agilent	300328 testsystem	V1.9.1	N/A	N/A
Power sensor	Agilent	U2021XA	MY53480013	2018/03/11	2019/03/10

2.4 Traceability

All measurement equipment calibrations are traceable to NML(Taiwan)/NIST(USA) or where calibration is performed outside Taiwan, to equivalent nationally recognized standards organizations.

2.5 Calibration

Equipment requiring calibration is calibrated periodically by the manufacturer or according to manufacturer's specifications. Additionally all equipment is verified for proper performance on a regular basis using in house standards or comparisons.

2.6 Measurement Uncertainty

The estimated combined standard uncertainty for radiated emissions and conducted emissions measurements are $\pm 3\text{dB}$.

Table 3: Emission Measurement Uncertainty

Parameter	Uncertainty
RF power, conducted	$\pm 1.5 \text{ dB}$
Adjacent channel power	$\pm 3 \text{ dB}$
Radiated emission of transmitter, valid up to 26 GHz	$\pm 6 \text{ dB}$
Radiated emission of receiver, valid up to 26 GHz	$\pm 6 \text{ dB}$
Temperature	$\pm 2 \text{ }^{\circ}\text{C}$
Humidity	$\pm 10 \text{ \%}$

3. General Product Information

3.1 Product Function and Intended Use

The EUT is a Wall Reader. It contains a WiFi compatible module enabling the user to communicate data through a Wireless interface.
For details refer to the User Guide, Data Sheet and Circuit Diagram.

3.2 System Details and Ratings

Table 4: Basic Information of EUT

Item	EUT information
Kind of Equipment	Wall Reader
Type Designation	Kapture KA-WR1N
Brand Name	Pamex
FCC ID	2AQ8A-KAWR1N

Table 5: Technical Specification of EUT

Technical Specification	Value
Operating Frequencies	2412~2462 MHz
Channel Spacing	5MHz
Channel number	11
Operation Voltage	DC 12V
Modulation	802.11b: DSSS 802.11g/n: OFDM with BPSK, QPSK, QAM 802.11n:OFDM with BPSK, QPSK, QAM
Antenna gain	3.3dBi

3.3 Independent Operation Modes

Basic operation modes are:

- A. Transmitting
 - 1. Low channel
 - 2. Middle channel
 - 3. High channel
- B. Receiving
- C. Standby
- D. Off

3.4 Noise Generating and Noise Suppressing Parts

Refer to the Circuit Diagram.

3.5 Submitted Documents

- | | |
|-------------------------|----------------------|
| - Block Diagram | - Circuit Diagram |
| - Photo Document | - Instruction Manual |
| - Technical Description | - Rating Label |

4. Test Set-up and Operation Modes

4.1 Principle of Configuration Selection

The equipment under test (EUT) was configured to measure its maximum power level. The test modes were adapted accordingly in reference to the instructions for use.

All Power Setting is Set 0.

4.2 Test Operation and Test Software

Setup for testing: Test samples are provided with a USB interface which makes it possible to control them through a test software installed on a notebook computer.

This software was running on the laptop computer connected to the EUT. It was used to enable the operation modes listed in section 3.3 as appropriate.

The samples were used as follows:

Conducted: A000797975-002

Radiation: A000797975-001

Full test was applied on all test modes, but only worst case was shown

IEEE 802.11b mode:

Channel Low (2412MHz), Channel Mid (2437MHz) and Channel High (2462MHz) with 1Mbps data rate were chosen for full testing.

IEEE 802.11g mode:

Channel Low (2412MHz), Channel Mid (2437MHz) and Channel High (2462MHz) with 6Mbps data rate were chosen for full testing.

IEEE 802.11n HT 20 mode:

Channel Low (2412MHz), Channel Mid (2437MHz) and Channel High (2462MHz) with 13Mbps data rate were chosen for full testing.

4.3 cial Accessories and Auxiliary Equipment

The product has been tested together with the following additional accessories:


Description	Manufacturer	Model No.	Serial No.
Notebook(EMC-06)	Lenovo	TP00048A	PB-0F8B2

4.4 Countermeasures to achieve EMC Compliance

The test sample which has been tested contained the noise suppression parts as described in the Constructional Data Form or the Technical Construction File. No additional measures were employed to achieve compliance.

4.5 Test Setup Diagram

Diagram of Measurement Configuration for Radiation Test



Note: Measurements above 1 GHz are done with a table height of 1.5m.

Diagram of Measurement Equipment Configuration for Mains Conduction Measurement (if applicable)





Diagram of Measurement Equipment Configuration for Conducted Transmitter Measurement



5. Test Results

5.1 Transmitter Requirement & Test Suites

5.1.1 Antenna Requirement

RESULT:**Passed**

Test standard : FCC Part 15.247(b)(4), Part 15.203

Limit : the use of antennas with directional gains that do not exceed 6 dBi

According to the manufacturer declaration, the EUT has an antenna with a directional gain of 3.3 dBi. The antenna is a printed PCB trace with no possibility of replacement with a non-approved antenna by the end-user. Therefore, the EUT is considered to comply with this provision.

Refer to EUT photo for details.

5.1.2 Peak Output Power

RESULT:
Passed

Test standard : FCC Part 15.247(b)(3)
 Basic standard : ANSI C63.10:2013, KDB558074
 Limit : 1 Watt
 Kind of test site : Shielded room

Test setup

Test Channel : Low/ Middle/ High
 Operation Mode : A
 Ambient temperature : 22-26 °C
 Relative humidity : 50-65 %
 Atmospheric pressure : 100-103 kPa

Table 6: Test result of Peak Output Power (802.11b)

Channel	Channel Frequency (MHz)	Output Power		Limit
		(dBm)	(W)	(W)
Low Channel	2412	13.65	0.02317	1
Middle Channel	2437	15.75	0.03758	1
High Channel	2462	14.46	0.02793	1

Table 7: Test result of AVG Output Power (802.11b)

Channel	Channel Frequency (MHz)	Output Power		
		(dBm)	(W)	(mw)
Low Channel	2412	11.55	0.01429	14.3
Middle Channel	2437	13.28	0.02128	21.3
High Channel	2462	12.58	0.01811	18.1

Table 8: Test result of Peak Output Power (802.11g)

Channel	Channel Frequency (MHz)	Output Power		Limit
		(dBm)	(W)	(W)
Low Channel	2412	18.47	0.07031	1
Middle Channel	2437	18.65	0.07328	1
High Channel	2462	18.63	0.07295	1

Table 9: Test result of AVG Output Power (802.11g)

Channel	Channel Frequency (MHz)	Output Power		
		(dBm)	(W)	(mw)
Low Channel	2412	16.36	0.04325	43.3
Middle Channel	2437	16.42	0.04385	43.9
High Channel	2462	16.37	0.04335	43.4

Table 10: Test result of Peak Output Power (802.11n HT20)

Channel	Channel Frequency (MHz)	Output Power		Limit
		(dBm)	(W)	(W)
Low Channel	2412	18.41	0.06934	1
Middle Channel	2437	18.65	0.07328	1
High Channel	2462	18.50	0.07079	1

Table 11: Test result of AVG Output Power (802.11n HT20)

Channel	Channel Frequency (MHz)	Output Power		
		(dBm)	(W)	(mw)
Low Channel	2412	16.25	0.04217	42.2
Middle Channel	2437	16.54	0.04508	45.1
High Channel	2462	16.38	0.04345	43.5

5.1.3 6dB Bandwidth

RESULT:**Passed**

Test standard	:	FCC Part 15.247(a)(2)
Basic standard	:	ANSI C63.10:2013, KDB558074
Kind of test site	:	Shielded room

Test setup

Test Channel	:	Low/ Middle/ High
Operation Mode	:	A

Ambient temperature	:	22-26°C
Relative humidity	:	50-65%
Atmospheric pressure	:	100-103 kPa

Table 12: Test result of 6dB Bandwidth (802.11b)

Channel	Channel Frequency (MHz)	6dB Bandwidth (MHz)	Limit (MHz)	Result
Low Channel	2412	9.004	0.5	Pass
Mid Channel	2437	9.087	0.5	Pass
High Channel	2462	9.067	0.5	Pass

Table 13: Test result of 6dB Bandwidth (802.11g)


Channel	Channel Frequency (MHz)	6dB Bandwidth (MHz)	Limit (MHz)	Result
Low Channel	2412	15.095	0.5	Pass
Mid Channel	2437	15.085	0.5	Pass
High Channel	2462	15.095	0.5	Pass

Table 14: Test result of 6dB Bandwidth (802.11n HT20)

Channel	Channel Frequency (MHz)	6dB Bandwidth (MHz)	Limit (MHz)	Result
Low Channel	2412	15.105	0.5	Pass
Mid Channel	2437	15.095	0.5	Pass
High Channel	2462	15.105	0.5	Pass


Test Plot of 6dB Bandwidth (802.11b)

Low Channel




Date: 7.SEP.2018 11:29:05

Middle Channel




Date: 7.SEP.2018 11:30:31

High Channel




Test Plot of 6dB Bandwidth (802.11g)


Low Channel



Middle Channel




High Channel




Test Plot of 6dB Bandwidth (802.11n HT20)

Low Channel




Date: 7.SEP.2018 11:53:09

Middle Channel



Date: 7.SEP.2018 11:51:09

High Channel



5.1.4 Power Density

RESULT:
Passed

Test standard : FCC Part 15.247(e)
 Basic standard : ANSI C63.10:2013, KDB558074
 Kind of test site : Shielded room

Test setup

Test Channel : Low/ Middle/ High
 Operation Mode : A
 Ambient temperature : 22-26°C
 Relative humidity : 50-65%
 Atmospheric pressure : 100-103 kPa

Table 15: Test result of Power Density (802.11b)

Channel	Channel Frequency (MHz)	Power Density	Limit
		(dBm)	(dBm)
Low Channel	2412	-14.16	8
Middle Channel	2437	-7.55	8
High Channel	2462	-13.57	8

Table 16: Test result of Power Density (802.11g)


Channel	Channel Frequency (MHz)	Power Density	Limit
		(dBm)	(dBm)
Low Channel	2412	-11.35	8
Middle Channel	2437	-10.76	8
High Channel	2462	-13.32	8

Table 17: Test result of Power Density (802.11n HT20)

Channel	Channel Frequency (MHz)	Power Density	Limit
		(dBm)	(dBm)
Low Channel	2412	-12.65	8
Middle Channel	2437	-10.61	8
High Channel	2462	-12.73	8


Test Plot of Power Density (802.11b)

Low Channel




Date: 7.SEP.2018 12:19:35

Middle Channel




Date: 7.SEP.2018 12:20:11

High Channel



Date: 7.SEP.2018 12:20:45


Test Plot of Power Density (802.11g)

Low Channel



Middle Channel




High Channel



Date: 7.SEP.2018 12:21:14


Test Plot of Power Density (802.11n HT20)

Low Channel



Middle Channel



High Channel


Date: 7.SEP.2018 12:24:19

**5.1.5 Conducted spurious emissions and Frequency Band Edge
measured in 100kHz Bandwidth****RESULT:****Passed**

Test standard	:	FCC part 15.247(d)
Basic standard	:	ANSI C63.10:2013, KDB558074
Limit	:	20dB (below that in the 100kHz bandwidth within the band that contains the highest level of the desired power)
Kind of test site	:	Shielded room

Test setup


Test Channel	:	Low/ Middle/ High for Conducted Spurious Emissions Low/ High for Frequency Band Edge
Operation mode	:	A
Ambient temperature	:	22-26°C
Relative humidity	:	50-65%
Atmospheric pressure	:	100-103 kPa

All emissions are more than 20dB below fundamental, details refer to following test plot, and compliance is achieved as well.

Due to the small size of the product and that there are no inductive components of significant size, 9kHz to 30MHz frequency range is not tested based on technical judgment.


Test Plot 100kHz Conducted Emissions (802.11b)

Low Channel




Date: 7.SEP.2018 10:48:43

Middle Channel




Date: 7.SEP.2018 10:47:53

High Channel




Test Plot 100kHz Conducted Emissions (802.11g)

Low Channel




Date: 7.SEP.2018 11:22:16

Middle Channel




Date: 7.SEP.2018 11:23:16

High Channel




Test Plot 100kHz Conducted Emissions (802.11n HT20)


Low Channel



Middle Channel




High Channel



Date: 7.SEP.2018 10:58:34


Test Plot 100kHz RBW of Band Edge (802.11b)

Low Channel



Date: 7.SEP.2018 11:06:49


High Channel



Date: 7.SEP.2018 11:02:48


Test Plot 100kHz RBW of Band Edge (802.11g)

Low Channel



Date: 7.SEP.2018 11:07:31


High Channel



Date: 7.SEP.2018 11:01:46


Test Plot 100kHz RBW of Band Edge (802.11n HT20)

Low Channel



Date: 7.SEP.2018 11:08:11

High Channel



Date: 7.SEP.2018 11:00:56

5.1.6 Spurious Emission

RESULT:**Passed**

Test standard	:	FCC part 15.247(d), FCC 15.205, FCC 15.209
Basic standard	:	ANSI C63.10: 2013
Limits	:	Radiated emissions which fall in the restricted bands, as defined in FCC 15.205(a) and RSS-Gen i5, 8.10 (Table 7), must comply with the radiated emission limits specified in FCC 15.209(a). Emission radiated outside the restricted and authorized frequency bands must either comply with the radiated emission limits specified for the restricted bands or in FCC15.247(d) .
Kind of test site	:	3m Semi-Anechoic Chamber

Test setup

Test Channel	:	Low/ Middle/ High
Operation mode	:	A, B

Remark: Testing was carried out within frequency range 30MHz to the tenth harmonic.

For details refer to Appendix D.

The Radiated Emissions testing was performed in the X, Y and Z axis orientation. The Z Axis orientation is the worst-case and recorded in this test report. Due to the small size of the product and that there are no inductive components of significant size, 9kHz to 30MHz frequency range is not tested based on technical judgment.

Prüfbericht - Nr.: 50182194 001
Test Report No.**Seite 43 von 48**
Page 43 of 48

5.2 Mains Emissions

5.2.1 Mains Conducted Emissions

RESULT:**Passed**

Test standard : FCC Part 15.207
FCC Part 15.107

Limits : Mains Conducted emissions as defined in
above test standards must comply with the
mains conducted emission limits specified

Kind of test site : Shielded Room

Test setup

Test Channel : Normal link
Operation mode : Normal link

Ambient temperature : 20-24 °C
Relative humidity : 50-65 %
Atmospheric pressure : 100-103 kPa

Remark: For details refer to Appendix D.

6. Safety Human exposure

6.1 Radio Frequency Exposure Compliance

6.1.1 Electromagnetic Fields

RESULT:**Passed**

Test standard : FCC KDB Publication 447498 D01 v06

Separation distance is more than 20 cm, thus mobile device exposure limits can be applied.

Maximum Exposure:

Power to Antenna (mW)	45.1 mW
Power to Antenna (dBm)	16.5 dBm
Antenna Gain	3.3 dBi
Power+Ant Gain	96.4 mW
Distance	20 cm
S=	0.019 mW/cm ²

Limit FCC:

1500-100,000 MHz 1.0 mW/cm²


---End---

7. Photographs of the Test Set-Up


Photograph 1: Set-up for Spurious Emissions (Front View)




Photograph 2: Set-up for Spurious Emissions (Back View 1)



Photograph 3: Set-up for Spurious Emissions (Back View 2)




Photograph 4: Set-up for Conducted testing



Photograph 5: Set-up for Main Emissions (Front View)



Photograph 6: Set-up for Main Emissions (Back View)



8. List of Tables

Table 1: Applied Standard and Test Levels	5
Table 2: List of Test and Measurement Equipment	7
Table 3: Emission Measurement Uncertainty.....	8
Table 4: Basic Information of EUT	9
Table 5: Technical Specification of EUT	9
Table 6: Test result of Peak Output Power (802.11b).....	15
Table 7: Test result of AVG Output Power (802.11b)	15
Table 8: Test result of Peak Output Power (802.11g).....	16
Table 9: Test result of AVG Output Power (802.11g)	16
Table 10: Test result of Peak Output Power (802.11n HT20)	16
Table 11: Test result of AVG Output Power (802.11n HT20).....	16
Table 12: Test result of 6dB Bandwidth (802.11b).....	18
Table 13: Test result of 6dB Bandwidth (802.11g).....	18
Table 14: Test result of 6dB Bandwidth (802.11n HT20).....	18
Table 15: Test result of Power Density (802.11b).....	25
Table 16: Test result of Power Density (802.11g).....	25
Table 17: Test result of Power Density (802.11n HT20)	25

9. List of Photographs

Photograph 1: Set-up for Spurious Emissions (Front View).....	45
Photograph 2: Set-up for Spurious Emissions (Back View 1)	45
Photograph 3: Set-up for Spurious Emissions (Back View 2)	46
Photograph 4: Set-up for Conducted testing	46
Photograph 5: Set-up for Main Emissions (Front View)	47
Photograph 6: Set-up for Main Emissions (Back View)	47