



FCC RF Test Report

APPLICANT : Motorola Mobility LLC
EQUIPMENT : Mobile Cellular Phone
BRAND NAME : Motorola
MODEL NAME : XT2413-2, XT2413V
FCC ID : IHDT56AN4
STANDARD : FCC Part 15 Subpart C §15.247
CLASSIFICATION : (DSS) Spread Spectrum Transmitter
TEST DATE(S) : Sep. 25, 2023 ~ Oct. 19, 2023

We, Sporton International Inc. (Shenzhen), would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International Inc. (Shenzhen), the test report shall not be reproduced except in full.

Jason Jia

Approved by: Jason Jia



Sporton International Inc. (ShenZhen)

1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan, Shenzhen, 518055

People's Republic of China



TABLE OF CONTENTS

REVISION HISTORY.....	3
SUMMARY OF TEST RESULT	4
1 GENERAL DESCRIPTION.....	5
1.1 Applicant.....	5
1.2 Manufacturer.....	5
1.3 Product Feature of Equipment Under Test.....	5
1.4 Product Specification of Equipment Under Test.....	6
1.5 Modification of EUT	6
1.6 Specification of Accessory.....	6
1.7 Testing Location	7
1.8 Test Software.....	7
1.9 Applicable Standards.....	7
2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST.....	8
2.1 Carrier Frequency Channel	8
2.2 Test Mode.....	9
2.3 Connection Diagram of Test System.....	10
2.4 Support Unit used in test configuration and system	11
2.5 EUT Operation Test Setup	11
2.6 Measurement Results Explanation Example.....	11
3 TEST RESULT	12
3.1 Number of Channel Measurement	12
3.2 Hopping Channel Separation Measurement	14
3.3 Dwell Time Measurement.....	20
3.4 20dB and 99% Bandwidth Measurement	22
3.5 Output Power Measurement.....	33
3.6 Conducted Band Edges Measurement.....	34
3.7 Conducted Spurious Emission Measurement	41
3.8 Radiated Band Edges and Spurious Emission Measurement	51
3.9 AC Conducted Emission Measurement.....	55
3.10 Antenna Requirements.....	57
4 LIST OF MEASURING EQUIPMENT.....	58
5 MEASUREMENT UNCERTAINTY	59
APPENDIX A. CONDUCTED TEST RESULTS	
APPENDIX B. AC CONDUCTED EMISSION TEST RESULT	
APPENDIX C. RADIATED SPURIOUS EMISSION	
APPENDIX D. DUTY CYCLE PLOTS	
APPENDIX E. SETUP PHOTOGRAPHS	



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR391515A	Rev. 01	Initial issue of report	Nov. 02, 2023
FR391515A	Rev. 02	Revise the typo of CSE description.	Nov. 08, 2023

SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.247(a)(1)	Number of Channels	$\geq 15\text{Chs}$	Pass	-
3.2	15.247(a)(1)	Hopping Channel Separation	$\geq 2/3$ of 20dB BW	Pass	-
3.3	15.247(a)(1)	Dwell Time of Each Channel	$\leq 0.4\text{sec}$ in 31.6sec period	Pass	-
3.4	15.247(a)(1)	20dB Bandwidth	-	Report only	-
3.4	-	99% Bandwidth	-	Report only	-
3.5	15.247(b)(1)	Peak Output Power	$\leq 125\text{ mW}$	Pass	-
3.6	15.247(d)	Conducted Band Edges	$\leq 20\text{dBc}$	Pass	-
3.7	15.247(d)	Conducted Spurious Emission	$\leq 20\text{dBc}$	Pass	-
3.8	15.247(d)	Radiated Band Edges and Radiated Spurious Emission	15.209(a) & 15.247(d)	Pass	Under limit 12.65 dB at 48.43 MHz
3.9	15.207	AC Conducted Emission	15.207(a)	Pass	Under limit 11.22 dB at 0.54 MHz
3.10	15.203 & 15.247(b)	Antenna Requirement	15.203 & 15.247(b)	Pass	-

Conformity Assessment Condition:

- The test results (PASS/FAIL) with all measurement uncertainty excluded are presented against the regulation limits or in accordance with the requirements stipulated by the applicant/manufacturer who shall bear all the risks of non-compliance that may potentially occur if measurement uncertainty is taken into account.
- The measurement uncertainty please refer to each test result in the section "Measurement Uncertainty"

Disclaimer:

The product specifications of the EUT presented in the test report that may affect the test assessments are declared by the manufacturer who shall take full responsibility for the authenticity.



1 General Description

1.1 Applicant

Motorola Mobility LLC

222 W,Merchandise Mart Plaza, Chicago IL 60654 USA

1.2 Manufacturer

Motorola Mobility LLC

222 W,Merchandise Mart Plaza, Chicago IL 60654 USA

1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	Mobile Cellular Phone
Brand Name	Motorola
Model Name	XT2413-2, XT2413V
FCC ID	IHDT56AN4
IMEI Code	Conducted: 352036360013864 Conduction: 352036360011892 Radiation: 352036360011736
IC	IHDT56AN4
HW Version	DVT2
SW Version	T3TF33.55
EUT Stage	Identical Prototype

Remark:

1. The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.
2. The model name XT2413-2, XT2413V are the same product except model name different for market segment.

1.4 Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx/Rx Frequency Range	2402 MHz ~ 2480 MHz
Number of Channels	79
Carrier Frequency of Each Channel	2402+n*1 MHz; n=0~78
Maximum Output Power to Antenna	Bluetooth BR(1Mbps) : 15.30 dBm (0.0339 W) Bluetooth EDR (2Mbps) : 12.20 dBm (0.0166 W) Bluetooth EDR (3Mbps) : 12.60 dBm (0.0182 W)
99% Occupied Bandwidth	Bluetooth BR(1Mbps) : 0.839 MHz Bluetooth EDR (2Mbps) : 1.167 MHz Bluetooth EDR (3Mbps) : 1.171 MHz
Antenna Type / Gain	IFA Antenna type with gain -5.6 dBi
Type of Modulation	Bluetooth BR (1Mbps) : GFSK Bluetooth EDR (2Mbps) : $\pi/4$ -DQPSK Bluetooth EDR (3Mbps) : 8-DPSK

1.5 Modification of EUT

No modifications are made to the EUT during all test items.

1.6 Specification of Accessory

Specification of Accessory				
AC Adapter 1	Brand Name	Motorola (AOHA)	Model Name	MC-101
AC Adapter 2	Brand Name	Motorola (Salcomp)	Model Name	MC-101
AC Adapter 3	Brand Name	Motorola (Chenyang)	Model Name	MC-101
Battery 1	Brand Name	Motorola (Sunwoda)	Model Name	QF50
Battery 2	Brand Name	Motorola (SCUD)	Model Name	QF50
USB Cable 1	Brand Name	Motorola (Saibao)	Model Name	S928D97979/S928D97981
USB Cable 2	Brand Name	Motorola (Naiyi)	Model Name	S928D97980/S928D97982

1.7 Testing Location

Sporton International Inc. (Shenzhen) is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.01.

Test Firm	Sporton International Inc. (Shenzhen)		
Test Site Location	1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan, Shenzhen, 518055 People's Republic of China TEL: +86-755-86379589 FAX: +86-755-86379595		
Test Site No.	Sporton Site No.	FCC Designation No.	FCC Test Firm Registration No.
	CO01-SZ TH01-SZ	CN1256	421272

Test Firm	Sporton International Inc. (Shenzhen)		
Test Site Location	101, 1st Floor, Block B, Building 1, No. 2, Tengfeng 4th Road, Fenghuang Community, Fuyong Street, Baoan District, Shenzhen City, Guangdong Province 518103 People's Republic of China TEL: +86-755-86066985		
Test Site No.	Sporton Site No.	FCC Designation No.	FCC Test Firm Registration No.
	03CH04-SZ	CN1256	421272

1.8 Test Software

Item	Site	Manufacturer	Name	Version
1.	03CH04-SZ	AUDIX	E3	6.2009-8-24
2.	CO01-SZ	AUDIX	E3	6.120613b

1.9 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- 47 CFR Part 15 Subpart C §15.247
- FCC KDB 558074 D01 15.247 Meas Guidance v05r02
- ANSI C63.10-2013

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.



2 Test Configuration of Equipment Under Test

2.1 Carrier Frequency Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)
2400-2483.5 MHz	0	2402	27	2429	54	2456
	1	2403	28	2430	55	2457
	2	2404	29	2431	56	2458
	3	2405	30	2432	57	2459
	4	2406	31	2433	58	2460
	5	2407	32	2434	59	2461
	6	2408	33	2435	60	2462
	7	2409	34	2436	61	2463
	8	2410	35	2437	62	2464
	9	2411	36	2438	63	2465
	10	2412	37	2439	64	2466
	11	2413	38	2440	65	2467
	12	2414	39	2441	66	2468
	13	2415	40	2442	67	2469
	14	2416	41	2443	68	2470
	15	2417	42	2444	69	2471
	16	2418	43	2445	70	2472
	17	2419	44	2446	71	2473
	18	2420	45	2447	72	2474
	19	2421	46	2448	73	2475
	20	2422	47	2449	74	2476
	21	2423	48	2450	75	2477
	22	2424	49	2451	76	2478
	23	2425	50	2452	77	2479
	24	2426	51	2453	78	2480
	25	2427	52	2454	-	-
	26	2428	53	2455	-	-

2.2 Test Mode


- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (Z plane) were recorded in this report, and the worst mode of radiated spurious emissions is Bluetooth 1Mbps mode, and recorded in this report.
- b. AC power line Conducted Emission was tested under maximum output power.

The following summary table is showing all test modes to demonstrate in compliance with the standard.


Summary table of Test Cases			
Test Item	Data Rate / Modulation		
	Bluetooth BR 1Mbps GFSK	Bluetooth EDR 2Mbps $\pi/4$ -DQPSK	Bluetooth EDR 3Mbps 8-DPSK
Conducted Test Cases	Mode 1: CH00_2402 MHz	Mode 4: CH00_2402 MHz	Mode 7: CH00_2402 MHz
	Mode 2: CH39_2441 MHz	Mode 5: CH39_2441 MHz	Mode 8: CH39_2441 MHz
	Mode 3: CH78_2480 MHz	Mode 6: CH78_2480 MHz	Mode 9: CH78_2480 MHz
Radiated Test Cases	Bluetooth BR 1Mbps GFSK		
	Mode 1: CH00_2402 MHz		
	Mode 2: CH39_2441 MHz		
	Mode 3: CH78_2480 MHz		
AC Conducted Emission	Mode 1 : GSM 850 Idle + Bluetooth Link + Adapter 1 + USB Cable + Battery 1 + Earphone		
Remark:			
1. For radiated test cases, the worst mode data rate 1Mbps was reported only, because this data rate has the highest RF output power at preliminary tests, and no other significantly frequencies found in conducted spurious emission.			
2. For Radiated Test Cases, The tests were performed with Adapter 1, Earphone and USB Cable 1.			

2.3 Connection Diagram of Test System

AC Conducted Emission:



Radiated Emission:



2.4 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	Base Station(LTE)	Anritsu	MT8820C	N/A	N/A	Unshielded,1.8m
2.	Bluetooth Earphone	Samsung	EO-MG900	PYAHS-107W	N/A	N/A
3.	WLAN AP	Dlink	DIR-820L	KA2IR820LA1	N/A	Unshielded,1.8m
4.	Earphone	N/A	N/A	N/A	N/A	N/A

2.5 EUT Operation Test Setup

For Bluetooth function, the engineering test program was provided and enabled to make EUT connect with Bluetooth base station to continuous transmit.

For AC power line conducted emissions, the EUT was set to connect with the WLAN AP under large package sizes transmission.

2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example :

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 13.60 dB and 10dB attenuator.

$$\begin{aligned}\text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)} \\ &= 13.60 + 10 = 23.60 \text{ (dB)}\end{aligned}$$

3 Test Result

3.1 Number of Channel Measurement

3.1.1 Limits of Number of Hopping Frequency

Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels.

3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.1.3 Test Procedure

1. The testing follows ANSI C63.10-2013 clause 7.8.3.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Enable the EUT hopping function.
5. Use the following spectrum analyzer settings: Span = the frequency band of operation;
RBW = 300kHz; VBW $\geq$ RBW; Sweep = auto; Detector function = peak; Trace = max hold.
6. The number of hopping frequency used is defined as the number of total channel.
7. Record the measurement data derived from spectrum analyzer.

3.1.4 Test Setup




3.1.5 Test Result of Number of Hopping Frequency


Please refer to Appendix A.



Number of Hopping Channel Plot on Channel 00 - 78



Date: 19.OCT.2023 17:25:21



Date: 19.OCT.2023 17:25:41

3.2 Hopping Channel Separation Measurement

3.2.1 Limit of Hopping Channel Separation

Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater.

3.2.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.2.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 7.8.2.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Enable the EUT hopping function.
5. Use the following spectrum analyzer settings:
Span = wide enough to capture the peaks of two adjacent channels;
RBW = 300kHz; VBW $\geq$ RBW; Sweep = auto; Detector function = peak; Trace = max hold.
6. Measure and record the results in the test report.

3.2.4 Test Setup




3.2.5 Test Result of Hopping Channel Separation

Please refer to Appendix A.




<1Mbps>

Channel Separation Plot on Channel 00 - 01




Channel Separation Plot on Channel 39 - 40






Channel Separation Plot on Channel 77 - 78



Date: 19.OCT.2023 17:36:23

<2Mbps>


Channel Separation Plot on Channel 00 - 01



Date: 19.OCT.2023 17:42:19




Channel Separation Plot on Channel 39 - 40



Date: 19.OCT.2023 17:47:07

Channel Separation Plot on Channel 77 - 78




Date: 19.OCT.2023 17:52:31




<3Mbps>

Channel Separation Plot on Channel 00 - 01



Date: 19.OCT.2023 17:56:29


Channel Separation Plot on Channel 39 - 40



Date: 19.OCT.2023 18:00:54



Channel Separation Plot on Channel 77 - 78



Date: 19.OCT.2023 18:04:55

3.3 Dwell Time Measurement

3.3.1 Limit of Dwell Time

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

3.3.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.3.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 7.8.4.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Enable the EUT hopping function.
5. Use the following spectrum analyzer settings: Span = zero span, centered on a hopping channel; RBW = 1 MHz; VBW $\geq$ RBW; Sweep = as necessary to capture the entire dwell time per hopping channel; Detector function = peak; Trace = max hold.
6. Measure and record the results in the test report.


3.3.4 Test Setup



3.3.5 Test Result of Dwell Time

Please refer to Appendix A.

Package Transfer Time Plot



Remark:

1. In normal mode, hopping rate is 1600 hops/s with 6 slots (5 Transmit and 1 Receive slot) in 79 hopping channels.
With channel hopping rate (1600 / 6 / 79) in Occupancy Time Limit (0.4 x 79) (s),
Hops Over Occupancy Time comes to (1600 / 6 / 79) x (0.4 x 79) = 106.67 hops.
2. In AFH mode, hopping rate is 800 hops/s with 6 slots in 20 hopping channels.
With channel hopping rate (800 / 6 / 20) in Occupancy Time Limit (0.4 x 20) (s),
Hops Over Occupancy Time comes to (800 / 6 / 20) x (0.4 x 20) = 53.33 hops.
3. Dwell Time(s) = Hops Over Occupancy Time (hops) x Package Transfer Time

3.4 20dB and 99% Bandwidth Measurement

3.4.1 Limit of 20dB and 99% Bandwidth

Reporting only


3.4.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.4.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 6.9.2 and 6.9.3.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Use the following spectrum analyzer settings for 20dB Bandwidth measurement.
Span = approximately 2 to 5 times the 20 dB bandwidth, centered on a hopping channel;
The RBW is set to 1% to 5% of the 99% OBW, the VBW is set to 3 times the RBW;
Sweep = auto; Detector function = peak;
Trace = max hold.
5. Use the following spectrum analyzer settings for 99 % Bandwidth measurement.
Span = approximately 1.5 to 5 times the 99% bandwidth, centered on a hopping channel;
The RBW is set to 1% to 5% of the 99% OBW, the VBW is set to 3 times the RBW;
Sweep = auto; Detector function = peak;
Trace = max hold.
6. Measure and record the results in the test report.

3.4.4 Test Setup




3.4.5 Test Result of 20dB Bandwidth

Please refer to Appendix A.




<1Mbps>

20 dB Bandwidth Plot on Channel 00



Date: 19.OCT.2023 17:30:49


20 dB Bandwidth Plot on Channel 39



Date: 19.OCT.2023 17:34:19




20 dB Bandwidth Plot on Channel 78



Date: 19.OCT.2023 17:37:03

<2Mbps>


20 dB Bandwidth Plot on Channel 00



Date: 19.OCT.2023 17:42:55




20 dB Bandwidth Plot on Channel 39



Date: 19.OCT.2023 17:48:19

20 dB Bandwidth Plot on Channel 78




Date: 19.OCT.2023 17:53:05




<3Mbps>

20 dB Bandwidth Plot on Channel 00



Date: 19.OCT.2023 17:57:10


20 dB Bandwidth Plot on Channel 39



Date: 19.OCT.2023 18:01:09



20 dB Bandwidth Plot on Channel 78






3.4.6 Test Result of 99% Occupied Bandwidth

Please refer to Appendix A.

<1Mbps>


99% Occupied Bandwidth Plot on Channel 00




Date: 19.OCT.2023 17:23:41



99% Occupied Bandwidth Plot on Channel 39




99% Occupied Bandwidth Plot on Channel 78






<2Mbps>

99% Occupied Bandwidth Plot on Channel 00



Date: 19.OCT.2023 17:40:18


99% Occupied Bandwidth Plot on Channel 39



Date: 19.OCT.2023 17:44:42




99% Occupied Bandwidth Plot on Channel 78




<3Mbps>

99% Occupied Bandwidth Plot on Channel 00






99% Occupied Bandwidth Plot on Channel 39



Date: 19.OCT.2023 17:59:11

99% Occupied Bandwidth Plot on Channel 78



Date: 19.OCT.2023 18:02:21

Note : The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

3.5 Output Power Measurement

3.5.1 Limit of Output Power

The maximum peak conducted output power of the intentional radiator shall not exceed the following:
For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band 0.125 watts. The power limit for 1Mbps, 2Mbps, 3Mbps and AFH modes are 0.125 watts.


3.5.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.5.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 7.8.5.
2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Measure the conducted output power with cable loss and record the results in the test report.
5. Measure and record the results in the test report.

3.5.4 Test Setup



3.5.5 Test Result of Peak Output Power

Please refer to Appendix A.

3.5.6 Test Result of Average Output Power (Reporting Only)

Please refer to Appendix A.

3.6 Conducted Band Edges Measurement

3.6.1 Limit of Band Edges

In any 100 kHz bandwidth outside the intentional radiation frequency band, the radio frequency power shall be at least 20 dB below the highest level of the radiated power. In addition, radiated emissions which fall in the restricted bands must also comply with the radiated emission limits.


3.6.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.6.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 7.8.6.
2. Set to the maximum power setting and enable the EUT transmit continuously.
3. Set RBW = 100kHz, VBW = 300kHz. Band edge emissions must be at least 20 dB down from the highest emission level within the authorized band as measured with a 100kHz RBW. The attenuation shall be 30 dB instead of 20 dB when RMS conducted output power procedure is used.
4. Enable hopping function of the EUT and then repeat step 2. and 3.
5. Measure and record the results in the test report.


3.6.4 Test Setup



3.6.5 Test Result of Conducted Band Edges


<1Mbps>

Low Band Edge Plot on Channel 00



Date: 19.OCT.2023 17:27:06

High Band Edge Plot on Channel 78




Date: 19.OCT.2023 17:36:50




<2Mbps>

Low Band Edge Plot on Channel 00



Date: 19.OCT.2023 17:42:44

High Band Edge Plot on Channel 78




Date: 19.OCT.2023 17:52:55

3.6.6 Test Result of Conducted Hopping Mode Band Edges


<1Mbps>

Hopping Mode Low Band Edge Plot



Date: 19.OCT.2023 17:32:34

Hopping Mode High Band Edge Plot




Date: 19.OCT.2023 17:38:27




<2Mbps>

Hopping Mode Low Band Edge Plot



Date: 19.OCT.2023 17:44:18

Hopping Mode High Band Edge Plot




Date: 19.OCT.2023 17:54:23




<3Mbps>

Hopping Mode Low Band Edge Plot



Date: 19.OCT.2023 17:58:37

Hopping Mode High Band Edge Plot



Date: 19.OCT.2023 18:07:25

3.7 Conducted Spurious Emission Measurement

3.7.1 Limit of Spurious Emission Measurement

In any 100 kHz bandwidth outside the intentional radiation frequency band, the radio frequency power shall be at least 20 dB below the highest level of the radiated power. In addition, radiated emissions which fall in the restricted bands must also comply with the radiated emission limits.

3.7.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.7.3 Test Procedure

1. The testing follows ANSI C63.10-2013 clause 7.8.8.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Set RBW = 100 kHz, VBW = 300kHz, scan up through 10th harmonic. All harmonics / spurs must be at least 20 dB down from the highest emission level within the authorized band as measured with a 100 kHz RBW.
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

3.7.4 Test Setup






3.7.5 Test Result of Conducted Spurious Emission


<1Mbps>

CSE Plot on Ch 00



Date: 19.OCT.2023 17:31:44


CSE Plot on Ch 00



Date: 19.OCT.2023 17:31:19




CSE Plot on Ch 39



Date: 19.OCT.2023 17:35:12


CSE Plot on Ch 39



Date: 19.OCT.2023 17:34:48




CSE Plot on Ch 78



Date: 19.OCT.2023 17:37:58

CSE Plot on Ch 78




Date: 19.OCT.2023 17:37:31




<2Mbps>

CSE Plot on Ch 00



Date: 19.OCT.2023 17:43:47


CSE Plot on Ch 00



Date: 19.OCT.2023 17:43:22




CSE Plot on Ch 39



Date: 19.OCT.2023 17:49:23


CSE Plot on Ch 39



Date: 19.OCT.2023 17:48:56




CSE Plot on Ch 78



Date: 19.OCT.2023 17:53:59

CSE Plot on Ch 78




Date: 19.OCT.2023 17:53:31




<3Mbps>

CSE Plot on Ch 00



Date: 19.OCT.2023 17:58:02


CSE Plot on Ch 00



Date: 19.OCT.2023 17:57:37




CSE Plot on Ch 39



Date: 19.OCT.2023 18:02:02


CSE Plot on Ch 39



Date: 19.OCT.2023 18:01:37




CSE Plot on Ch 78



Date: 19.OCT.2023 18:07:02

CSE Plot on Ch 78



Date: 19.OCT.2023 18:06:37

3.8 Radiated Band Edges and Spurious Emission Measurement

3.8.1 Limit of Radiated Band Edges and Spurious Emission

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. In addition, radiated emissions which fall in the restricted bands must also comply with the limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.8.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.8.3 Test Procedures


1. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
2. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
3. For each suspected emission, the EUT was arranged to its worst case and then tune the Antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level to comply with the guidelines.
4. Set to the maximum power setting and enable the EUT transmit continuously.
5. Use the following spectrum analyzer settings:
 - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Set RBW=100 kHz for $f < 1$ GHz, RBW=1MHz for $f > 1$ GHz ; VBW $\geq$ RBW; Sweep = auto; Detector function = peak; Trace = max hold for peak
 - (3) For average measurement: use duty cycle correction factor method per 15.35(c).
Duty cycle = On time/100 milliseconds
$$\text{On time} = N_1 * L_1 + N_2 * L_2 + \dots + N_{n-1} * L_{n-1} + N_n * L_n$$

Where N_1 is number of type 1 pulses, L_1 is length of type 1 pulses, etc.
Average Emission Level = Peak Emission Level + $20 * \log(\text{Duty cycle})$
6. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
7. For testing below 1GHz, if the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then peak values of EUT will be reported, otherwise, the emissions will be repeated one by one using the CISPR quasi-peak method and reported.
8. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than peak limit (that means the emission level in average mode also complies with the limit in average mode), then peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.


Note: The average levels were calculated from the peak level corrected with duty cycle correction factor (-24.79dB) derived from $20 \log(\text{dwell time}/100\text{ms})$. This correction is only for signals that hop with the fundamental signal, such as band-edge and harmonic. Other spurious signals that are independent of the hopping signal would not use this correction.

3.8.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz





3.8.5 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

There is a comparison data of both open-field test site and semi-Anechoic chamber, and the result came out very similar.

3.8.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix C.

3.8.7 Test Result of Radiated Spurious Emission (30MHz ~ 10th Harmonic or 40GHz, whichever is lower)

Please refer to Appendix C.

3.8.8 Duty cycle correction factor for average measurement

Please refer to Appendix D.

3.9 AC Conducted Emission Measurement

3.9.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.9.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.9.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.

3.9.4 Test Setup



3.9.5 Test Result of AC Conducted Emission

Please refer to Appendix B.



3.10 Antenna Requirements

3.10.1 Standard Applicable

If directional gain of transmitting antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the rule.

3.10.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

3.10.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.



4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
EMI Receiver	R&S	ESR7	101630	9kHz~7GHz;	Jul. 06, 2023	Sep. 25, 2023	Jul. 05, 2024	Conduction (CO01-SZ)
AC LISN	R&S	ENV216	100063	9kHz~30MHz	Aug. 21, 2023	Sep. 25, 2023	Aug. 20, 2024	Conduction (CO01-SZ)
AC LISN (for auxiliary equipment)	EMCO	3816/2SH	00103892	9kHz~30MHz	Oct. 17, 2022	Sep. 25, 2023	Oct. 16, 2023	Conduction (CO01-SZ)
Spectrum Analyzer	R&S	FSV40	101078	10Hz~40GHz	Apr. 06, 2023	Sep. 26, 2023~Oct. 19, 2023	Apr. 05, 2024	Conducted (TH01-SZ)
Pulse Power Sensor	Anritsu	MA2411B	1339473	30MHz~40GHz	Dec. 27, 2022	Sep. 26, 2023~Oct. 19, 2023	Dec. 26, 2023	Conducted (TH01-SZ)
Power Meter	Anritsu	ML2495A	1542004	50MHz Bandwidth	Dec. 27, 2022	Sep. 26, 2023~Oct. 19, 2023	Dec. 26, 2023	Conducted (TH01-SZ)
Thermo meter	Anymetre	JR593	#7	- 10°C ~ 50°C 10%RH~99%RH	Apr. 08, 2023	Sep. 26, 2023~Oct. 19, 2023	Apr. 07, 2024	Conducted (TH01-SZ)
EMI Test Receiver	R&S	ESR7	101404	9kHz~7GHz	Oct. 19, 2022	Oct. 09, 2023~Oct. 13, 2023	Oct. 18, 2023	Radiation (03CH04-SZ)
EXA Spectrum Analyzer	KEYSIGHT	N9010A	MY55150213	10Hz~44GHz	Jul. 07, 2023	Oct. 09, 2023~Oct. 13, 2023	Jul. 06, 2024	Radiation (03CH04-SZ)
Loop Antenna	R&S	HFH2-Z2	100354	9kHz~30MHz	Jun. 28, 2022	Oct. 09, 2023~Oct. 13, 2023	Jun. 27, 2024	Radiation (03CH04-SZ)
Bilog Antenna	TeseQ	CBL6111D	41909	30MHz~1GHz	May. 14, 2023	Oct. 09, 2023~Oct. 13, 2023	May. 13, 2024	Radiation (03CH04-SZ)
Double Ridge Horn Antenna	SCHWARZBECK	BBHA9120D	9120D-1474	1GHz~18GHz	Jul. 07, 2023	Oct. 09, 2023~Oct. 13, 2023	Jul. 06, 2024	Radiation (03CH04-SZ)
Horn Antenna	SCHWARZBECK	BBHA9170	9170#679	15GHz~40GHz	Jul. 08, 2023	Oct. 09, 2023~Oct. 13, 2023	Jul. 07, 2024	Radiation (03CH04-SZ)
Amplifier	Burgeon	BPA-530	102211	0.01Hz~3000MHz	Oct. 19, 2022	Oct. 09, 2023~Oct. 13, 2023	Oct. 18, 2023	Radiation (03CH04-SZ)
HF Amplifier	MITEQ	AMF-7D-0010 1800-30-10P-R	1943528	1GHz~18GHz	Oct. 19, 2022	Oct. 09, 2023~Oct. 13, 2023	Oct. 18, 2023	Radiation (03CH04-SZ)
HF Amplifier	MITEQ	TTA1840-35-HG	1871923	18GHz~40GHz	Jul. 07, 2023	Oct. 09, 2023~Oct. 13, 2023	Jul. 06, 2024	Radiation (03CH04-SZ)
Amplifier	Agilent Technologies	83017A	MY57280136	500MHz~26.5GHz	Aug. 21, 2023	Oct. 09, 2023~Oct. 13, 2023	Aug. 20, 2024	Radiation (03CH04-SZ)
AC Power Source	APC	AFV-S-600B	F119050019	N/A	Nov. 10, 2022	Oct. 09, 2023~Oct. 13, 2023	Nov. 10, 2023	Radiation (03CH04-SZ)
Turn Table	EM	EM1000	N/A	0~360 degree	NCR	Oct. 09, 2023~Oct. 13, 2023	NCR	Radiation (03CH04-SZ)

NCR: No Calibration Required

5 Measurement Uncertainty

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI 63.10-2013. All the measurement uncertainty value were shown with a coverage K=2 to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

Uncertainty of Conducted Measurement

Test Item	Uncertainty
Conducted Power	± 1.34 dB
Conducted Emissions	± 1.34 dB
Occupied Channel Bandwidth	± 0.012 %

Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_c(y)$)	2.7 dB
--	--------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_c(y)$)	5.1 dB
--	--------

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_c(y)$)	4.8 dB
--	--------

Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_c(y)$)	5.1 dB
--	--------

----- THE END -----



Appendix A. Conducted Test Results

Appendix A. Test Result of Conducted Test Items

Test Engineer:	Zhang Jiang	Temperature:	21~25	°C
Test Date:	2023/9/26~2023/10/19	Relative Humidity:	51~54	%

TEST RESULTS DATA***20dB and 99% Occupied Bandwidth and Hopping Channel Separation***

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	20db BW (MHz)	99% Bandwidth (MHz)	Hopping Channel Separation Measurement (MHz)	Hopping Channel Separation Measurement Limit (MHz)	Pass/Fail
DH	1Mbps	1	0	2402	0.900	0.815	0.999	0.6000	Pass
DH	1Mbps	1	39	2441	0.896	0.839	1.012	0.5971	Pass
DH	1Mbps	1	78	2480	0.900	0.837	1.003	0.6000	Pass
2DH	2Mbps	1	0	2402	1.296	1.163	1.003	0.8637	Pass
2DH	2Mbps	1	39	2441	1.287	1.165	0.999	0.8580	Pass
2DH	2Mbps	1	78	2480	1.287	1.167	1.003	0.8580	Pass
3DH	3Mbps	1	0	2402	1.300	1.171	1.003	0.8667	Pass
3DH	3Mbps	1	39	2441	1.300	1.169	1.007	0.8667	Pass
3DH	3Mbps	1	78	2480	1.300	1.171	1.007	0.8667	Pass

TEST RESULTS DATA***Dwell Time***

Mod.	Hopping Channel Number Rate	Hops Over Occupancy Time(hops)	Package Transfer Time (msec)	Dwell Time (sec)	Limits (sec)	Pass/Fail
Normal	79	106.67	2.89	0.31	0.4	Pass
AFH	20	53.33	2.89	0.15	0.4	Pass

TEST RESULTS DATA***Peak Power Table***

DH	CH.	NTX	Peak Power (dBm)	Power Limit (dBm)	Test Result
DH5	0	1	15.20	20.97	Pass
	39	1	15.30	20.97	Pass
	78	1	14.50	20.97	Pass
2DH5	0	1	12.20	20.97	Pass
	39	1	12.10	20.97	Pass
	78	1	11.60	20.97	Pass
3DH5	0	1	12.60	20.97	Pass
	39	1	12.40	20.97	Pass
	78	1	11.70	20.97	Pass

TEST RESULTS DATA**Average Power Table*****(Reporting Only)***


DH	CH.	NTX	Average Power (dBm)	Duty Factor (dB)
DH5	0	1	14.30	1.14
	39	1	14.10	1.14
	78	1	13.50	1.14
2DH5	0	1	9.30	1.15
	39	1	9.10	1.15
	78	1	8.60	1.15
3DH5	0	1	9.30	1.14
	39	1	9.10	1.14
	78	1	8.60	1.14

TEST RESULTS DATA***Number of Hopping Frequency***


Number of Hopping (Channel)	Adaptive Frequency Hopping (Channel)	Limits (Channel)	Pass/Fail
79	20	> 15	Pass



Appendix B. AC Conducted Emission Test Results



Test Engineer :	Lily Qiu	Temperature :	22~24°C
		Relative Humidity :	44~50%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Remark :	All emissions not reported here are more than 10 dB below the prescribed limit.		



Site : CO01-SZ
Condition: FCC 15C_QP LISN 20230420_N NEUTRAL

	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.54	30.58	-15.42	46.00	10.20	10.22	10.16	Average
2 *	0.54	44.78	-11.22	56.00	24.40	10.22	10.16	QP
3	0.60	29.19	-16.81	46.00	8.80	10.23	10.16	Average
4	0.60	44.29	-11.71	56.00	23.90	10.23	10.16	QP
5	0.76	25.11	-20.89	46.00	4.70	10.25	10.16	Average
6	0.76	38.21	-17.79	56.00	17.80	10.25	10.16	QP
7	1.09	27.83	-18.17	46.00	7.40	10.26	10.17	Average
8	1.09	41.53	-14.47	56.00	21.10	10.26	10.17	QP
9	2.40	23.42	-22.58	46.00	3.00	10.17	10.25	Average
10	2.40	37.62	-18.38	56.00	17.20	10.17	10.25	QP
11	3.82	22.96	-23.04	46.00	2.50	10.15	10.31	Average
12	3.82	37.26	-18.74	56.00	16.80	10.15	10.31	QP

Note:

- Level(dBμV) = Read Level(dBμV) + LISN Factor(dB) + Cable Loss(dB)
- Over Limit(dB) = Level(dBμV) – Limit Line(dBμV)



Appendix C. Radiated Spurious Emission Test Data

Test Engineer :	ZhangXu	Relative Humidity :	48~49%
		Temperature :	24-25℃



Radiated Spurious Emission Test Modes

Mode	Band (MHz)	Antenna	Modulation	Channel	Frequency	Data Rate	RU	Remark
Mode 1	2400-2483.5	2	Bluetooth BR_GFSK	00	2402	1DH5	-	-
Mode 2	2400-2483.5	2	Bluetooth BR_GFSK	39	2441	1DH5	-	-
Mode 3	2400-2483.5	2	Bluetooth BR_GFSK	78	2480	1DH5	-	-
Mode 4	2400-2483.5	2	Bluetooth BR_GFSK	78	2480	1DH5	-	LF

Summary of each worse mode

Mode	Modulation	Ch.	Freq. (MHz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Pol.	Peak Avg.	Result	Remark
1	Bluetooth BR_GFSK	00	2324.35	47.30	74.00	-26.70	H	PEAK	Pass	Band Edge
1	Bluetooth BR_GFSK	00	4804.00	46.31	74.00	-27.69	V	Peak	Pass	Harmonic
2	Bluetooth BR_GFSK	39	-	-	-	-	-	-	-	Band Edge
2	Bluetooth BR_GFSK	39	4882.00	45.00	74.00	-29.00	V	Peak	Pass	Harmonic
3	Bluetooth BR_GFSK	78	2483.66	51.90	74.00	-22.10	V	PEAK	Pass	Band Edge
3	Bluetooth BR_GFSK	78	7440.00	45.21	74.00	-28.79	V	Peak	Pass	Harmonic
4	Bluetooth BR_GFSK	78	48.43	27.35	40.00	-12.65	V	Peak	Pass	LF



Mode	1																																																																
	Band Edge																																																																
	2400-2483.5_Bluetooth BR_GFSK_CH00_2402MHz																																																																
ANT	2																																																																
Pol.	Horizontal																																																																
Peak	Level (dBuV/m) Date: 2023-10-09  <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>2324.35</td><td>47.30</td><td>74.00</td><td>-26.70</td><td>42.21</td><td>33.14</td><td>5.30</td><td>33.35</td><td>200</td><td>62</td><td>PEAK</td></tr><tr><td>2</td><td>2324.35</td><td>22.51</td><td>54.00</td><td>-31.49</td><td>17.42</td><td>33.14</td><td>5.30</td><td>33.35</td><td>200</td><td>62</td><td>AVERAGE</td></tr></table>												Limit	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg		1	2324.35	47.30	74.00	-26.70	42.21	33.14	5.30	33.35	200	62	PEAK	2	2324.35	22.51	54.00	-31.49	17.42	33.14	5.30	33.35	200	62	AVERAGE
		Limit	Read	Ant	Cable	Preamp	APos	TPos																																																									
	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark																																																								
		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																						
1	2324.35	47.30	74.00	-26.70	42.21	33.14	5.30	33.35	200	62	PEAK																																																						
2	2324.35	22.51	54.00	-31.49	17.42	33.14	5.30	33.35	200	62	AVERAGE																																																						
Level (dBuV/m) Date: 2023-10-09  <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>2402.00</td><td>90.35</td><td>-----</td><td>-----</td><td>84.87</td><td>33.35</td><td>5.37</td><td>33.24</td><td>200</td><td>62</td><td>PEAK</td></tr><tr><td>2</td><td>2402.00</td><td>65.56</td><td>-----</td><td>-----</td><td>60.08</td><td>33.35</td><td>5.37</td><td>33.24</td><td>200</td><td>62</td><td>AVERAGE</td></tr></table>												Limit	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg		1	2402.00	90.35	-----	-----	84.87	33.35	5.37	33.24	200	62	PEAK	2	2402.00	65.56	-----	-----	60.08	33.35	5.37	33.24	200	62	AVERAGE	
	Limit	Read	Ant	Cable	Preamp	APos	TPos																																																										
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark																																																									
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																							
1	2402.00	90.35	-----	-----	84.87	33.35	5.37	33.24	200	62	PEAK																																																						
2	2402.00	65.56	-----	-----	60.08	33.35	5.37	33.24	200	62	AVERAGE																																																						



Mode	1																																																														
	Band Edge																																																														
	2400-2483.5_Bluetooth BR_GFSK_CH00_2402MHz																																																														
ANT	2																																																														
Pol.	Vertical																																																														
Peak	Date: 2023-10-09 <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss Factor</th><th></th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2343.58</td><td>47.27</td><td>74.00</td><td>-26.73</td><td>42.08</td><td>33.19</td><td>5.32</td><td>33.32</td><td>100</td><td>180</td><td>PEAK</td></tr><tr><td>2</td><td>2343.58</td><td>22.48</td><td>54.00</td><td>-31.52</td><td>17.29</td><td>33.19</td><td>5.32</td><td>33.32</td><td>100</td><td>180</td><td>AVERAGE</td></tr></table>												Limit	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss Factor		Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2343.58	47.27	74.00	-26.73	42.08	33.19	5.32	33.32	100	180	PEAK	2	2343.58	22.48	54.00	-31.52	17.29	33.19	5.32	33.32	100	180	AVERAGE
		Limit	Read	Ant	Cable	Preamp	APos	TPos																																																							
	Freq	Level	Line	Margin	Level	Factor	Loss Factor		Remark																																																						
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																					
1	2343.58	47.27	74.00	-26.73	42.08	33.19	5.32	33.32	100	180	PEAK																																																				
2	2343.58	22.48	54.00	-31.52	17.29	33.19	5.32	33.32	100	180	AVERAGE																																																				
Date: 2023-10-09 <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss Factor</th><th></th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2402.00</td><td>99.16</td><td>-----</td><td>-----</td><td>93.68</td><td>33.35</td><td>5.37</td><td>33.24</td><td>100</td><td>180</td><td>PEAK</td></tr><tr><td>2</td><td>2402.00</td><td>74.37</td><td>-----</td><td>-----</td><td>68.89</td><td>33.35</td><td>5.37</td><td>33.24</td><td>100</td><td>180</td><td>AVERAGE</td></tr></table>												Limit	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss Factor		Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2402.00	99.16	-----	-----	93.68	33.35	5.37	33.24	100	180	PEAK	2	2402.00	74.37	-----	-----	68.89	33.35	5.37	33.24	100	180	AVERAGE	
	Limit	Read	Ant	Cable	Preamp	APos	TPos																																																								
Freq	Level	Line	Margin	Level	Factor	Loss Factor		Remark																																																							
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																						
1	2402.00	99.16	-----	-----	93.68	33.35	5.37	33.24	100	180	PEAK																																																				
2	2402.00	74.37	-----	-----	68.89	33.35	5.37	33.24	100	180	AVERAGE																																																				



Mode	1																																																																
	Harmonic																																																																
	2400-2483.5_Bluetooth BR_GFSK_CH00_2402MHz																																																																
ANT	2																																																																
Pol.	Horizontal																																																																
Peak Avg	Level (dBuV/m) Date: 2023-10-11 Frequency (MHz) <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>4804.00</td><td>45.75</td><td>74.00</td><td>-28.25</td><td>65.57</td><td>36.08</td><td>8.94</td><td>64.84</td><td>---</td><td>---</td><td>Peak</td></tr><tr><td>2</td><td>4804.00</td><td>20.96</td><td>54.00</td><td>-33.04</td><td>40.78</td><td>36.08</td><td>8.94</td><td>64.84</td><td>---</td><td>---</td><td>Average</td></tr></table>												Limit	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg		1	4804.00	45.75	74.00	-28.25	65.57	36.08	8.94	64.84	---	---	Peak	2	4804.00	20.96	54.00	-33.04	40.78	36.08	8.94	64.84	---	---	Average
		Limit	Read	Ant	Cable	Preamp	APos	TPos																																																									
	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark																																																								
		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																						
1	4804.00	45.75	74.00	-28.25	65.57	36.08	8.94	64.84	---	---	Peak																																																						
2	4804.00	20.96	54.00	-33.04	40.78	36.08	8.94	64.84	---	---	Average																																																						
Vertical																																																																	
Level (dBuV/m) Date: 2023-10-11 Frequency (MHz) <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>4804.00</td><td>46.31</td><td>74.00</td><td>-27.69</td><td>66.13</td><td>36.08</td><td>8.94</td><td>64.84</td><td>---</td><td>---</td><td>Peak</td></tr><tr><td>2</td><td>4804.00</td><td>21.52</td><td>54.00</td><td>-32.48</td><td>41.34</td><td>36.08</td><td>8.94</td><td>64.84</td><td>---</td><td>---</td><td>Average</td></tr></table>												Limit	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg		1	4804.00	46.31	74.00	-27.69	66.13	36.08	8.94	64.84	---	---	Peak	2	4804.00	21.52	54.00	-32.48	41.34	36.08	8.94	64.84	---	---	Average	
	Limit	Read	Ant	Cable	Preamp	APos	TPos																																																										
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark																																																									
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																							
1	4804.00	46.31	74.00	-27.69	66.13	36.08	8.94	64.84	---	---	Peak																																																						
2	4804.00	21.52	54.00	-32.48	41.34	36.08	8.94	64.84	---	---	Average																																																						



Mode	2																																																																																						
	Harmonic																																																																																						
	2400-2483.5_Bluetooth BR_GFSK_CH39_2441MHz																																																																																						
ANT	2																																																																																						
Pol.	Horizontal																																																																																						
Peak Avg	Level (dBuV/m) Date: 2023-10-11 PEAK_74 AVG_54 <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>4882.00</td><td>44.89</td><td>74.00</td><td>-29.11</td><td>64.93</td><td>36.13</td><td>8.70</td><td>64.87</td><td>---</td><td>---</td><td>Peak</td></tr><tr><td>2</td><td>4882.00</td><td>20.10</td><td>54.00</td><td>-33.90</td><td>40.14</td><td>36.13</td><td>8.70</td><td>64.87</td><td>---</td><td>---</td><td>Average</td></tr><tr><td>3</td><td>7323.00</td><td>43.54</td><td>74.00</td><td>-30.46</td><td>62.03</td><td>36.19</td><td>10.18</td><td>64.86</td><td>---</td><td>---</td><td>Peak</td></tr><tr><td>4</td><td>7323.00</td><td>18.75</td><td>54.00</td><td>-35.25</td><td>37.24</td><td>36.19</td><td>10.18</td><td>64.86</td><td>---</td><td>---</td><td>Average</td></tr></table>												Limit	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	4882.00	44.89	74.00	-29.11	64.93	36.13	8.70	64.87	---	---	Peak	2	4882.00	20.10	54.00	-33.90	40.14	36.13	8.70	64.87	---	---	Average	3	7323.00	43.54	74.00	-30.46	62.03	36.19	10.18	64.86	---	---	Peak	4	7323.00	18.75	54.00	-35.25	37.24	36.19	10.18	64.86	---	---	Average
		Limit	Read	Ant	Cable	Preamp	APos	TPos																																																																															
	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark																																																																														
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																													
	1	4882.00	44.89	74.00	-29.11	64.93	36.13	8.70	64.87	---	---	Peak																																																																											
2	4882.00	20.10	54.00	-33.90	40.14	36.13	8.70	64.87	---	---	Average																																																																												
3	7323.00	43.54	74.00	-30.46	62.03	36.19	10.18	64.86	---	---	Peak																																																																												
4	7323.00	18.75	54.00	-35.25	37.24	36.19	10.18	64.86	---	---	Average																																																																												
Vertical																																																																																							
Level (dBuV/m) Date: 2023-10-11 PEAK_74 AVG_54 <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>4882.00</td><td>45.00</td><td>74.00</td><td>-29.00</td><td>65.04</td><td>36.13</td><td>8.70</td><td>64.87</td><td>---</td><td>---</td><td>Peak</td></tr><tr><td>2</td><td>4882.00</td><td>20.21</td><td>54.00</td><td>-33.79</td><td>40.25</td><td>36.13</td><td>8.70</td><td>64.87</td><td>---</td><td>---</td><td>Average</td></tr><tr><td>3</td><td>7323.00</td><td>43.10</td><td>74.00</td><td>-30.90</td><td>61.59</td><td>36.19</td><td>10.18</td><td>64.86</td><td>---</td><td>---</td><td>Peak</td></tr><tr><td>4</td><td>7323.00</td><td>18.31</td><td>54.00</td><td>-35.69</td><td>36.80</td><td>36.19</td><td>10.18</td><td>64.86</td><td>---</td><td>---</td><td>Average</td></tr></table>												Limit	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	4882.00	45.00	74.00	-29.00	65.04	36.13	8.70	64.87	---	---	Peak	2	4882.00	20.21	54.00	-33.79	40.25	36.13	8.70	64.87	---	---	Average	3	7323.00	43.10	74.00	-30.90	61.59	36.19	10.18	64.86	---	---	Peak	4	7323.00	18.31	54.00	-35.69	36.80	36.19	10.18	64.86	---	---	Average	
	Limit	Read	Ant	Cable	Preamp	APos	TPos																																																																																
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark																																																																															
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																														
1	4882.00	45.00	74.00	-29.00	65.04	36.13	8.70	64.87	---	---	Peak																																																																												
2	4882.00	20.21	54.00	-33.79	40.25	36.13	8.70	64.87	---	---	Average																																																																												
3	7323.00	43.10	74.00	-30.90	61.59	36.19	10.18	64.86	---	---	Peak																																																																												
4	7323.00	18.31	54.00	-35.69	36.80	36.19	10.18	64.86	---	---	Average																																																																												



Mode	3																																																																																																											
	Band Edge																																																																																																											
	2400-2483.5_Bluetooth BR_GFSK_CH78_2480MHz																																																																																																											
ANT	2																																																																																																											
Pol.	Horizontal	Fundamental																																																																																																										
Peak	Level (dBuV/m) Date: 2023-10-09 Frequency (MHz) <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2483.66</td><td>49.34</td><td>74.00</td><td>-24.66</td><td>43.44</td><td>33.56</td><td>5.46</td><td>33.12</td><td>398</td><td>303</td><td>PEAK</td></tr><tr><td>2</td><td>2483.66</td><td>24.55</td><td>54.00</td><td>-29.45</td><td>18.65</td><td>33.56</td><td>5.46</td><td>33.12</td><td>398</td><td>303</td><td>AVERAGE</td></tr></table>		Limit	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2483.66	49.34	74.00	-24.66	43.44	33.56	5.46	33.12	398	303	PEAK	2	2483.66	24.55	54.00	-29.45	18.65	33.56	5.46	33.12	398	303	AVERAGE	Level (dBuV/m) Date: 2023-10-09 Frequency (MHz) <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2480.00</td><td>101.63</td><td>-----</td><td>-----</td><td>95.75</td><td>33.55</td><td>5.46</td><td>33.13</td><td>398</td><td>303</td><td>PEAK</td></tr><tr><td>2</td><td>2480.00</td><td>76.84</td><td>-----</td><td>-----</td><td>70.96</td><td>33.55</td><td>5.46</td><td>33.13</td><td>398</td><td>303</td><td>AVERAGE</td></tr></table>		Limit	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2480.00	101.63	-----	-----	95.75	33.55	5.46	33.13	398	303	PEAK	2	2480.00	76.84	-----	-----	70.96	33.55	5.46	33.13	398	303	AVERAGE
		Limit	Read	Ant	Cable	Preamp	APos	TPos																																																																																																				
	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark																																																																																																			
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																		
1	2483.66	49.34	74.00	-24.66	43.44	33.56	5.46	33.12	398	303	PEAK																																																																																																	
2	2483.66	24.55	54.00	-29.45	18.65	33.56	5.46	33.12	398	303	AVERAGE																																																																																																	
	Limit	Read	Ant	Cable	Preamp	APos	TPos																																																																																																					
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark																																																																																																				
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																		
1	2480.00	101.63	-----	-----	95.75	33.55	5.46	33.13	398	303	PEAK																																																																																																	
2	2480.00	76.84	-----	-----	70.96	33.55	5.46	33.13	398	303	AVERAGE																																																																																																	





Mode	3																																																																																																																				
	Band Edge																																																																																																																				
	2400-2483.5_Bluetooth BR_GFSK_CH78_2480MHz																																																																																																																				
ANT	2																																																																																																																				
Pol.	Vertical						Fundamental																																																																																																														
Peak	Level (dBuV/m) Date: 2023-10-09 Frequency (MHz) <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2483.66</td><td>51.90</td><td>74.00</td><td>-22.10</td><td>46.00</td><td>33.56</td><td>5.46</td><td>33.12</td><td>226</td><td>263</td><td>PEAK</td></tr><tr><td>2</td><td>2483.66</td><td>27.11</td><td>54.00</td><td>-26.89</td><td>21.21</td><td>33.56</td><td>5.46</td><td>33.12</td><td>226</td><td>263</td><td>AVERAGE</td></tr></table>							Limit	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2483.66	51.90	74.00	-22.10	46.00	33.56	5.46	33.12	226	263	PEAK	2	2483.66	27.11	54.00	-26.89	21.21	33.56	5.46	33.12	226	263	AVERAGE	Level (dBuV/m) Date: 2023-10-09 Frequency (MHz) <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2480.00</td><td>104.73</td><td>-----</td><td>-----</td><td>98.85</td><td>33.55</td><td>5.46</td><td>33.13</td><td>226</td><td>263</td><td>PEAK</td></tr><tr><td>2</td><td>2480.00</td><td>79.94</td><td>-----</td><td>-----</td><td>74.06</td><td>33.55</td><td>5.46</td><td>33.13</td><td>226</td><td>263</td><td>AVERAGE</td></tr></table>						Limit	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2480.00	104.73	-----	-----	98.85	33.55	5.46	33.13	226	263	PEAK	2	2480.00	79.94	-----	-----	74.06	33.55	5.46	33.13	226	263	AVERAGE
		Limit	Read	Ant	Cable	Preamp	APos	TPos																																																																																																													
	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark																																																																																																												
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																											
1	2483.66	51.90	74.00	-22.10	46.00	33.56	5.46	33.12	226	263	PEAK																																																																																																										
2	2483.66	27.11	54.00	-26.89	21.21	33.56	5.46	33.12	226	263	AVERAGE																																																																																																										
	Limit	Read	Ant	Cable	Preamp	APos	TPos																																																																																																														
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark																																																																																																													
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																											
1	2480.00	104.73	-----	-----	98.85	33.55	5.46	33.13	226	263	PEAK																																																																																																										
2	2480.00	79.94	-----	-----	74.06	33.55	5.46	33.13	226	263	AVERAGE																																																																																																										




Mode	3																																																																												
	Harmonic																																																																												
	2400-2483.5_Bluetooth BR_GFSK_CH78_2480MHz																																																																												
ANT	2																																																																												
Pol.	Horizontal																																																																												
Peak Avg	Level (dBuV/m) Date: 2023-10-13 PEAK_74 AVG_54 Frequency (MHz) <table><thead><tr><th></th><th>Freq</th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th colspan="2"></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>4960.00</td><td>43.38</td><td>74.00</td><td>-30.62</td><td>63.64</td><td>36.18</td><td>8.46</td><td>64.90</td><td>---</td><td>---</td></tr><tr><td>2</td><td>4960.00</td><td>18.59</td><td>54.00</td><td>-35.41</td><td>38.85</td><td>36.18</td><td>8.46</td><td>64.90</td><td>---</td><td>---</td></tr><tr><td>3</td><td>7440.00</td><td>44.99</td><td>74.00</td><td>-29.01</td><td>63.75</td><td>35.93</td><td>10.17</td><td>64.86</td><td>---</td><td>---</td></tr><tr><td>4</td><td>7440.00</td><td>20.20</td><td>54.00</td><td>-33.80</td><td>38.96</td><td>35.93</td><td>10.17</td><td>64.86</td><td>---</td><td>---</td></tr></tbody></table>												Freq	Limit	Read	Ant	Cable	Preamp	APos	TPos				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	4960.00	43.38	74.00	-30.62	63.64	36.18	8.46	64.90	---	---	2	4960.00	18.59	54.00	-35.41	38.85	36.18	8.46	64.90	---	---	3	7440.00	44.99	74.00	-29.01	63.75	35.93	10.17	64.86	---	---	4	7440.00	20.20	54.00	-33.80	38.96	35.93	10.17	64.86	---	---
		Freq	Limit	Read	Ant	Cable	Preamp	APos	TPos																																																																				
		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																		
	1	4960.00	43.38	74.00	-30.62	63.64	36.18	8.46	64.90	---	---																																																																		
	2	4960.00	18.59	54.00	-35.41	38.85	36.18	8.46	64.90	---	---																																																																		
3	7440.00	44.99	74.00	-29.01	63.75	35.93	10.17	64.86	---	---																																																																			
4	7440.00	20.20	54.00	-33.80	38.96	35.93	10.17	64.86	---	---																																																																			
Vertical																																																																													
Level (dBuV/m) Date: 2023-10-13 PEAK_74 AVG_54 Frequency (MHz) <table><thead><tr><th></th><th>Freq</th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th colspan="2"></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>4960.00</td><td>44.16</td><td>74.00</td><td>-29.84</td><td>64.42</td><td>36.18</td><td>8.46</td><td>64.90</td><td>---</td><td>---</td></tr><tr><td>2</td><td>4960.00</td><td>19.37</td><td>54.00</td><td>-34.63</td><td>39.63</td><td>36.18</td><td>8.46</td><td>64.90</td><td>---</td><td>---</td></tr><tr><td>3</td><td>7440.00</td><td>45.21</td><td>74.00</td><td>-28.79</td><td>63.97</td><td>35.93</td><td>10.17</td><td>64.86</td><td>---</td><td>---</td></tr><tr><td>4</td><td>7440.00</td><td>20.42</td><td>54.00</td><td>-33.58</td><td>39.18</td><td>35.93</td><td>10.17</td><td>64.86</td><td>---</td><td>---</td></tr></tbody></table>												Freq	Limit	Read	Ant	Cable	Preamp	APos	TPos				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	4960.00	44.16	74.00	-29.84	64.42	36.18	8.46	64.90	---	---	2	4960.00	19.37	54.00	-34.63	39.63	36.18	8.46	64.90	---	---	3	7440.00	45.21	74.00	-28.79	63.97	35.93	10.17	64.86	---	---	4	7440.00	20.42	54.00	-33.58	39.18	35.93	10.17	64.86	---	---	
	Freq	Limit	Read	Ant	Cable	Preamp	APos	TPos																																																																					
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																			
1	4960.00	44.16	74.00	-29.84	64.42	36.18	8.46	64.90	---	---																																																																			
2	4960.00	19.37	54.00	-34.63	39.63	36.18	8.46	64.90	---	---																																																																			
3	7440.00	45.21	74.00	-28.79	63.97	35.93	10.17	64.86	---	---																																																																			
4	7440.00	20.42	54.00	-33.58	39.18	35.93	10.17	64.86	---	---																																																																			




Mode	4																																																																																																																																																																																																																																																																							
	LF																																																																																																																																																																																																																																																																							
	2400-2483.5_Bluetooth BR_GFSK_CH78_2480MHz																																																																																																																																																																																																																																																																							
ANT	2																																																																																																																																																																																																																																																																							
Pol.	Horizontal							Vertical																																																																																																																																																																																																																																																																
QPI/ Peak	Level (dBuV/m) Date: 2023-10-13  Frequency (MHz) <table><thead><tr><th colspan="2"></th><th colspan="2">Limit</th><th colspan="2">Read</th><th colspan="2">Ant</th><th colspan="2">Cable Preamp</th><th colspan="2">APos</th><th colspan="2">TPos</th><th rowspan="3">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th></th><th></th><th></th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th colspan="3"></th></tr></thead><tbody><tr><td>1</td><td>51.34</td><td>20.40</td><td>40.00</td><td>-19.60</td><td>37.45</td><td>14.00</td><td>0.72</td><td>31.77</td><td>---</td><td>---</td><td>---</td><td>---</td><td>Peak</td></tr><tr><td>2</td><td>135.73</td><td>28.23</td><td>43.50</td><td>-15.27</td><td>40.85</td><td>17.70</td><td>1.19</td><td>31.51</td><td>---</td><td>---</td><td>---</td><td>---</td><td>Peak</td></tr><tr><td>3</td><td>255.04</td><td>26.28</td><td>46.00</td><td>-19.72</td><td>36.61</td><td>19.20</td><td>1.66</td><td>31.19</td><td>---</td><td>---</td><td>---</td><td>---</td><td>Peak</td></tr><tr><td>4</td><td>695.42</td><td>26.85</td><td>46.00</td><td>-19.15</td><td>28.50</td><td>26.50</td><td>2.75</td><td>30.90</td><td>---</td><td>---</td><td>---</td><td>---</td><td>Peak</td></tr><tr><td>5</td><td>811.82</td><td>30.10</td><td>46.00</td><td>-15.90</td><td>29.93</td><td>28.12</td><td>2.97</td><td>30.92</td><td>---</td><td>---</td><td>---</td><td>---</td><td>Peak</td></tr><tr><td>6</td><td>933.07</td><td>30.65</td><td>46.00</td><td>-15.35</td><td>28.42</td><td>29.92</td><td>3.21</td><td>30.90</td><td>---</td><td>---</td><td>---</td><td>---</td><td>Peak</td></tr></tbody></table>									Limit		Read		Ant		Cable Preamp		APos		TPos		Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor						MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg				1	51.34	20.40	40.00	-19.60	37.45	14.00	0.72	31.77	---	---	---	---	Peak	2	135.73	28.23	43.50	-15.27	40.85	17.70	1.19	31.51	---	---	---	---	Peak	3	255.04	26.28	46.00	-19.72	36.61	19.20	1.66	31.19	---	---	---	---	Peak	4	695.42	26.85	46.00	-19.15	28.50	26.50	2.75	30.90	---	---	---	---	Peak	5	811.82	30.10	46.00	-15.90	29.93	28.12	2.97	30.92	---	---	---	---	Peak	6	933.07	30.65	46.00	-15.35	28.42	29.92	3.21	30.90	---	---	---	---	Peak	Level (dBuV/m) Date: 2023-10-13  Frequency (MHz) <table><thead><tr><th colspan="2"></th><th colspan="2">Limit</th><th colspan="2">Read</th><th colspan="2">Ant</th><th colspan="2">Cable Preamp</th><th colspan="2">APos</th><th colspan="2">TPos</th><th rowspan="3">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th></th><th></th><th></th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th colspan="3"></th></tr></thead><tbody><tr><td>1</td><td>48.43</td><td>27.35</td><td>40.00</td><td>-12.65</td><td>42.78</td><td>15.50</td><td>0.69</td><td>31.62</td><td>---</td><td>---</td><td>---</td><td>---</td><td>Peak</td></tr><tr><td>2</td><td>134.76</td><td>26.36</td><td>43.50</td><td>-17.14</td><td>38.99</td><td>17.70</td><td>1.19</td><td>31.52</td><td>---</td><td>---</td><td>---</td><td>---</td><td>Peak</td></tr><tr><td>3</td><td>204.60</td><td>26.61</td><td>43.50</td><td>-16.89</td><td>41.35</td><td>15.10</td><td>1.45</td><td>31.29</td><td>---</td><td>---</td><td>---</td><td>---</td><td>Peak</td></tr><tr><td>4</td><td>629.46</td><td>27.71</td><td>46.00</td><td>-18.29</td><td>29.92</td><td>26.15</td><td>2.61</td><td>30.97</td><td>---</td><td>---</td><td>---</td><td>---</td><td>Peak</td></tr><tr><td>5</td><td>861.29</td><td>29.85</td><td>46.00</td><td>-16.15</td><td>28.49</td><td>29.30</td><td>3.08</td><td>31.02</td><td>---</td><td>---</td><td>---</td><td>---</td><td>Peak</td></tr><tr><td>6</td><td>950.53</td><td>30.57</td><td>46.00</td><td>-15.43</td><td>27.29</td><td>30.85</td><td>3.23</td><td>30.80</td><td>---</td><td>---</td><td>---</td><td>---</td><td>Peak</td></tr></tbody></table>									Limit		Read		Ant		Cable Preamp		APos		TPos		Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor						MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg				1	48.43	27.35	40.00	-12.65	42.78	15.50	0.69	31.62	---	---	---	---	Peak	2	134.76	26.36	43.50	-17.14	38.99	17.70	1.19	31.52	---	---	---	---	Peak	3	204.60	26.61	43.50	-16.89	41.35	15.10	1.45	31.29	---	---	---	---	Peak	4	629.46	27.71	46.00	-18.29	29.92	26.15	2.61	30.97	---	---	---	---	Peak	5	861.29	29.85	46.00	-16.15	28.49	29.30	3.08	31.02	---	---	---	---	Peak	6	950.53	30.57	46.00	-15.43	27.29	30.85	3.23	30.80	---	---	---	---	Peak
			Limit		Read		Ant		Cable Preamp		APos		TPos		Remark																																																																																																																																																																																																																																																									
	Freq	Level	Line	Margin	Level	Factor	Loss	Factor																																																																																																																																																																																																																																																																
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																																																																																																																																														
	1	51.34	20.40	40.00	-19.60	37.45	14.00	0.72	31.77	---	---	---	---	Peak																																																																																																																																																																																																																																																										
	2	135.73	28.23	43.50	-15.27	40.85	17.70	1.19	31.51	---	---	---	---	Peak																																																																																																																																																																																																																																																										
	3	255.04	26.28	46.00	-19.72	36.61	19.20	1.66	31.19	---	---	---	---	Peak																																																																																																																																																																																																																																																										
	4	695.42	26.85	46.00	-19.15	28.50	26.50	2.75	30.90	---	---	---	---	Peak																																																																																																																																																																																																																																																										
	5	811.82	30.10	46.00	-15.90	29.93	28.12	2.97	30.92	---	---	---	---	Peak																																																																																																																																																																																																																																																										
	6	933.07	30.65	46.00	-15.35	28.42	29.92	3.21	30.90	---	---	---	---	Peak																																																																																																																																																																																																																																																										
		Limit		Read		Ant		Cable Preamp		APos		TPos		Remark																																																																																																																																																																																																																																																										
Freq	Level	Line	Margin	Level	Factor	Loss	Factor																																																																																																																																																																																																																																																																	
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																																																																																																																																															
1	48.43	27.35	40.00	-12.65	42.78	15.50	0.69	31.62	---	---	---	---	Peak																																																																																																																																																																																																																																																											
2	134.76	26.36	43.50	-17.14	38.99	17.70	1.19	31.52	---	---	---	---	Peak																																																																																																																																																																																																																																																											
3	204.60	26.61	43.50	-16.89	41.35	15.10	1.45	31.29	---	---	---	---	Peak																																																																																																																																																																																																																																																											
4	629.46	27.71	46.00	-18.29	29.92	26.15	2.61	30.97	---	---	---	---	Peak																																																																																																																																																																																																																																																											
5	861.29	29.85	46.00	-16.15	28.49	29.30	3.08	31.02	---	---	---	---	Peak																																																																																																																																																																																																																																																											
6	950.53	30.57	46.00	-15.43	27.29	30.85	3.23	30.80	---	---	---	---	Peak																																																																																																																																																																																																																																																											

Appendix D. Duty Cycle Plots

DH5 on time (One Pulse) Plot



DH5 on time (Count Pulses) Plot on Channel 00



Note:

1. Worst case Duty cycle = on time/100 milliseconds = $2 * 2.88 / 100 = 5.76 \%$
2. Worst case Duty cycle correction factor = $20 * \log(\text{Duty cycle}) = -24.79 \text{ dB}$
3. DH5 has the highest duty cycle worst case and is reported.