

RF Exposure Evaluation Report

Product : New Energy Vehicle Integrated
Detection Tool
Trade mark : SmartSafe
Model/Type reference : iSmartEV P03
Serial Number : N/A
Report Number : EED32O81503007
FCC ID : 2AYANEVP03
Date of Issue : Nov. 16, 2022
: 47 CFR Part 1.1307
Test Standards : 47 CFR Part 2.1093
KDB447498D01 General RF Exposure Guidance v06
Test result : PASS

Prepared for:

HENZHEN SMARTSAFE TECH CO., LTD.

**3F, Building B, Qiao'an Technology Industrial Park, Guanlan, Longhua
New District, Shenzhen, China**

Prepared by:

Centre Testing International Group Co., Ltd.

Hongwei Industrial Zone, Bao'an 70 District,

Shenzhen, Guangdong, China

TEL: +86-755-3368 3668

FAX: +86-755-3368 3385

Compiled by:

mark.chen.

Reviewed by:

Tom chen

Mark Chen

Tom Chen

Approved by:

Aaron Ma

Date:

Nov. 16, 2022

Aaron Ma

Check No.: 2418220922



2 Version

Version No.	Date	Description
00	Nov. 16, 2022	Original

3 Contents

	Page
1 COVER PAGE	1
2 VERSION	2
3 CONTENTS	3
4 GENERAL INFORMATION	4
4.1 CLIENT INFORMATION	4
4.2 GENERAL DESCRIPTION OF EUT	4
4.3 PRODUCT SPECIFICATION SUBJECTIVE TO THIS STANDARD	4
4.4 TEST LOCATION	6
4.5 DEVIATION FROM STANDARDS	6
4.6 ABNORMALITIES FROM STANDARD CONDITIONS	6
4.7 OTHER INFORMATION REQUESTED BY THE CUSTOMER	6
5 RF EXPOSURE EVALUATION	7
5.1 RF EXPOSURE COMPLIANCE REQUIREMENT	7
5.2 MAXIMUM PERMISSIBLE EXPOSURE	8

4 General Information

4.1 Client Information

Applicant:	SHENZHEN SMARTSAFE TECH CO., LTD.
Address of Applicant:	3F,Building B, Qiao'an Technology Industrial Park, Guanlan, Longhua New District, Shenzhen, China
Manufacturer:	SHENZHEN SMARTSAFE TECH CO., LTD.
Address of Manufacturer:	3F,Building B, Qiao'an Technology Industrial Park, Guanlan, Longhua New District, Shenzhen, China
Factory:	SHENZHEN SMARTSAFE TECH CO., LTD.
Address of Factory:	3F,Building B, Qiao'an Technology Industrial Park, Guanlan, Longhua New District, Shenzhen, China

4.2 General Description of EUT

Product Name:	New Energy Vehicle Integrated Detection Tool
Mode No.:	iSmartEV P03
Trade mark:	SmartSafe
EUT Supports Radios application:	Bluetooth 5.0 dual mode: 2402-2480MHz 2.4GHz Wi-Fi: IEEE 802.11b/g/n(HT20): 2412MHz to 2462MHz IEEE 802.11n(HT40): 2422MHz to 2452MHz 5GHz Wi-Fi: U-NII-1: 5180-5240MHz; U-NII-3: 5745-5825MHz

4.3 Product Specification subjective to this standard

Frequency Range:	Bluetooth : 2402-2480MHz 2.4GHz Wi-Fi: IEEE 802.11b/g/n(HT20): 2412MHz to 2462MHz IEEE 802.11n(HT40): 2422MHz to 2452MHz 5GHz Wi-Fi: U-NII-1: 5150-5250MHz; U-NII-3: 5745-5825MHz
Modulation Type:	IEEE for 802.11b:DSSS(CCK,DQPSK,DBPSK) IEEE for 802.11g:OFDM(64QAM, 16QAM, QPSK, BPSK) IEEE for 802.11n(HT20/HT40): OFDM (64QAM, 16QAM,QPSK,BPSK) IEEE 802.11a: OFDM (BPSK, QPSK, 16QAM, 64QAM) IEEE 802.11ac(HT20/HT40/HT80): OFDM (BPSK, QPSK, 16QAM, 64QAM) BT/BLE: GFSK, 8DPSK, π /4DQPSK
Test Power Grade:	Default
Antenna Type (Bluetooth):	FPC Antenna
Antenna Gain (Bluetooth):	3.72dBi

Antenna Type (Wi-Fi):	FPC Antenna	
Antenna Gain (Wi-Fi):	Module 1: (2.4G): 3.72dBi; (5G): 2.96dBi; Module 2: (2.4G): 2.33dBi; (5G): 3.18dBi;	
Function (Wi-Fi):	☒ SISO ☐ 2x2 MIMO ☐ 3x3 MIMO ☐ 4x4MIMO	
Power Supply:	Adapter	model: CGSW65-120-5000II input: 100-240V~50/60Hz,1.5A output: 12.0V --- 5.0A 60.0W
Max Conducted Peak Output Power:	Module 1:BLE:7.26dBm, BT: -1.87dBm, 2.4G WIFI:16.55dBm, 5G WIFI:12.67dBm Module 2:2.4G WIFI:17.59dBm, 5G WIFI:7.56dBm.	
	The Max Conducted Peak Output Power data refer to the report EED32O81503001, EED32O81503002, EED32O81503003, EED32O81503004, EED32O81503005, EED32O8150306.	
Sample Received Date:	Sep. 23, 2022	
Sample tested Date:	Sep. 23, 2022 to Oct. 21, 2022	
Company Name and Address shown on Report, the sample(s) and sample Information was/ were provided by the applicant who should be responsible for the authenticity which CTI hasn't verified.		

4.4 Test Location

All tests were performed at:

Centre Testing International Group Co., Ltd

Building C, Hongwei Industrial Park Block 70, Bao'an District, Shenzhen, China

Telephone: +86 (0) 755 33683668 Fax: +86 (0) 755 33683385

No tests were sub-contracted.

FCC Designation No.: CN1164

4.5 Deviation from Standards

None.

4.6 Abnormalities from Standard Conditions

None.

4.7 Other Information Requested by the Customer

None.

5 RF Exposure Evaluation

5.1 RF Exposure Compliance Requirement

Given $E = \frac{\sqrt{30 \times P \times G}}{d}$ & $S = \frac{E^2}{377}$

Where E = Field strength in Volts / meter

P = Power in Watts

G = Numeric antenna gain

d = Distance in meters

S = Power density in milliwatts / square centimeter

Combining equations and re-arranging the terms to express the distance as a function of the remaining variables yields:

$$S = \frac{30 \times P \times G}{377 d^2}$$

Changing to units of mW and cm, using:

$$P \text{ (mW)} = P \text{ (W)} / 1000 \text{ and}$$

$$d \text{ (cm)} = d \text{ (m)} / 100$$

Yields

$$S = \frac{30 \times (P/1000) \times G}{377 \times (d/100)^2} = 0.0796 \times \frac{P \times G}{d^2} \quad \text{Equation 1}$$

Where d = Distance in cm

P = Power in mW

G = Numeric antenna gain

S = Power density in mW / cm²

5.2 Maximum Permissible Exposure

Substituting the MPE safe distance using $d = 20$ cm into Equation 1:

$$S = 0.000199 \times P \times G$$

Where P = Power in mW

G = Numeric antenna gain

S = Power density in mW / cm²

Module 1:

BLE:

Ch.	Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm ²)
39	2480	5.321	2.355	20	0.0025	1

BT Classic:

Ch.	Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm ²)
78	2480	0.65	2.355	20	0.0003	1

2.4G WIFI:

Ch.	Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm ²)
1	2412	45.186	2.355	20	0.0212	1

5G WIFI:

Ch.	Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm ²)
48	5240	18.493	1.977	20	0.0073	1

Module 2:

2.4G WIFI:

Ch.	Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm ²)
1	2412	57.412	1.71	20	0.0195	1

5G WIFI:

Ch.	Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm ²)
40	5200	5.702	2.080	20	0.0024	1

For BT Classic and WIFI

Module 1 and Module 2 can transmit simultaneously.

Simultaneous transmission mode	The sum of the ratios	Result
Module 1 BLE+ Module 2 2.4GWIFI	0.0025/1+0.0195/1	=0.022 < 1
Module 1 BLE+ Module 2 5GWIFI	0.0025/1+0.0024/1	=0.0049 < 1
Module 1 BT Classic+ Module 2 2.4GWIFI	0.0003/1+0.0195/1	=0.0198 < 1
Module 1 BT Classic+ Module 2 5GWIFI	0.0003/1+0.0024/1	=0.0027 < 1
Module 1 2.4GWIFI+ Module 2 2.4GWIFI	0.0212/1+0.0195/1	=0.0407 < 1
Module 1 2.4GWIFI+ Module 2 5GWIFI	0.0212/1+0.0024/1	=0.0236 < 1
Module 1 5GWIFI+ Module 2 2.4GWIFI	0.0073/1+0.0195/1	=0.0268 < 1
Module 1 5GWIFI+ Module 2 5GWIFI	0.0073/1+0.0024/1	=0.0097 < 1

The test report is effective only with both signature and specialized stamp, The result(s) shown in this report refer only to the sample(s) tested. Without written approval of CTI, this report can't be reproduced except in full.

*** End of Report ***