TEST REPORT

Reference No.....: WTN21X03018146W-2 FCC ID: 2AP2V-DESKLAMP11

Applicant: Shaoxing Prolux Lighting Co.,Ltd

Ludong Industrial Zone, BaiGuan Street, ShangYu District, Shaoxing City, Address:

Zhejiang Province, China

Product Name: **DESK LAMP**

Test Model.....: PL-0250QU

Standards: KDB 680106 D01 V03

Date of Receipt sample....: Mar.10, 2021

Date of Test: Mar.10, 2021 to Mar.19, 2021

Date of Issue: Mar.19, 2021

Test Result: **Pass**

Remarks:

The results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of compiler and approver.

Prepared By:

Waltek Testing Group (Shenzhen) Co., Ltd.

Address: 1/F., Room 101, Building 1, Hongwei Industrial Park, Liuxian 2nd Road, Block 70 Bao'an District, Shenzhen, Guangdong, China

Tel.: +86-755-33663308

Fax.: +86-755-33663309 Tested by:

Mike Shi / Project Engineer

Lion Cai / RF Manager

Reviewed By:

Silin Chen / Manager

Approved & Authorized By:

TABLE OF CONTENTS

1. GENERAL INFORMATION	
1.1 Product Description for Equipment Under Test (EUT)	
2. RF EXPOSURE TEST REPORT	
2.1 Standard Applicable	
2.2 Test Conditions	<i>6</i>
2.3 Test Procedure.	7
2.4 Test Result	
2.5 Test Photos	
APPENDIX PHOTOGRAPHS	10

Reference No.: WTN21X03018146W-2 Page 3 of 10

Report version

Version No.	Date of issue	Description
Rev.00	Mar.19, 2021	Original
/	/	/

1. GENERAL INFORMATION

1.1 Product Description for Equipment Under Test (EUT)

Client Information

Applicant: Shaoxing Prolux Lighting Co.,Ltd

Address of applicant: Ludong Industrial Zone, BaiGuan Street, ShangYu

District, Shaoxing City, Zhejiang Province, China

Manufacturer: Shaoxing Prolux Lighting Co.,Ltd

Address of manufacturer: Ludong Industrial Zone, BaiGuan Street, ShangYu

District, Shaoxing City, Zhejiang Province, China

General Description of EUT	
Product Name:	DESK LAMP
Trade Name:	1
Model No.:	PL-0250QU
Adding Model(s):	/
Note: The test data is gathered from a pro	duction sample, provided by the manufacturer.

Technical Characteristics of EUT	
Frequency Range:	110~205kHz
Modulation Type:	ASK
Antenna Type:	Coil Antenna
Input:	AC120V/60Hz
Wireless output:	5W Max
Power adapter:	/
USB output:	DC5V, 2.1A

Reference No.: WTN21X03018146W-2 Page 5 of 10

1.2 Test Equipment List and Details

Description	Manufacturer	Model	Serial No.	Cal Date	Due Date
MPE Measuring Instrument	Narda	ELT-400	M-0155/M-0170	2020-07-15	2021-07-14
Broadband Field Meter	Narda	NBM-520	D-1699	2020-06-21	2021-06-20

2. RF Exposure Test Report

2.1 Standard Applicable

According to § 1.1310 system operating under the provisions of this section shall be operating in a manner that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure.

TABLE 1-LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)


Frequency range (MHz)		Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)		
	(A) Limits for Occupational/Controlled Exposure					
0.3-3.0	614	1.63	*100	6		
3.0-30	1842/f	4.89/f	*900/f ²	6		
30-300	61.4	0.163	1.0	6		
300-1,500			f/300	6		
1,500-100,000			5	6		
	(B) Limits for General Population/Uncontrolled Exposure					
0.3-1.34	614	1.63	*100	30		
1.34-30	824/f	2.19/f	*180/f ²	30		
30-300	27.5	0.073	0.2	30		
300-1,500			f/1500	30		
1,500-100,000			1.0	30		

f = frequency in MHz * = Plane-wave equivalent power density

2.2 Test Conditions

Test Mode	Description	Remark	
TM1	Wireless Charging	AC120V/60Hz	
Measurement Distance:	15 cm		

2.3 Test Procedure



- a. The measurement probe was placed at test distance(15 cm for A,B,C,D,F and 20 cm for E) which is between the edge of the charger and the geometric center of probe.
- b. The highest emission level was recorded at the measurement points(A, B, C, D, E, F).
- c. The EUT was measured according to the distance of KDB 680106 D01 V03.

2.4 Test Result

The EUT dose comply with item 5.2 of KDB 680106 D01V03

- 1. Power transfer frequency is less that 1 MHz
 Yes, the device operate in the frequency range from 110kHz to 205kHz.
- 2. Output power from each primary coil is less than or equal to 15 watts Yes, the maximum output power of the primary coil is less than 15W.
- 3. The transfer system includes only single primary and secondary coils. This includes charging systems that may have multiple primary coils and clients that are able to detect and allow coupling only between individual pairs of coils Yes, the client device includes only single primary coils.
- 4. Client device is inserted in or placed directly in contact with the transmitter Yes, Client device is placed directly in contact with the transmitter.
- 5. Mobile exposure conditions only (portable exposure conditions are not covered by this exclusion).

Reference No.: WTN21X03018146W-2 Page 8 of 10

Yes, It is mobile exposure conditions only.

6. The aggregate H-field strengths at 15 cm surrounding the device and 20 cm above the top surface from all simultaneous transmitting coils are demonstrated to be less than 50% of the MPE limit.

Yes, The EUT field strength levels are less than 50% of the MPE limit, refer to test TM1 list, and the coils can't transmitted simultaneous.

Test Mode: TM1

	Electric Field Emis	sions	
Test Position	Measure Value (V/m)	Limit(V/m)	50% Limit (V/m)
Top	5.07	614	307
Bottom	4.39	614	307
Side 1	3.92	614	307
Side 2	6.59	614	307
Side 3	5.05	614	307
Side 4	5.16	614	307
	Magnetic Field Emis	ssions	
Test Position	Measure Value (A/m)	Limit(A/m)	50% Limit (A/m)
Тор	0.47	1.63	0.815
Bottom	0.64	1.63	0.815
Side 1	0.25	1.63	0.815
Side 2	0.41	1.63	0.815
Side 3	0.26	1.63	0.815
Side 4	0.34	1.63	0.815

Note: this EUT was tested in 3 orthogonal positions and the worst case position (D point) data was reported.

2.5 Test Photos



Reference No.: WTN21X03018146W-2 Page 10 of 10

APPENDIX PHOTOGRAPHS

Please refer to "ANNEX"

***** END OF REPORT *****