

# FCC TEST REPORT

Test report On Behalf of Shenzhen Xiangyou Technology Co.LTD For Magnetic Fast Wireless Car Charger Model No.: WXC-001

#### FCC ID: 2AYTX-WXC-001

Prepared for : Shenzhen Xiangyou Technology Co.LTD Room 3A18, Building A5, Hangcheng Innovation Pioneer Park, No.159 Hangcheng Avenue, Sanwei Community, Hangcheng Street, Baoan District, Shenzhen, China

Prepared By : Shenzhen Tongzhou Testing Co.,Ltd 1th Floor, Building 1, Haomai High-tech Park, Huating Road 387, Dalang Street, Longhua, Shenzhen, China

 Date of Test:
 Jan. 21, 2021 ~ Jan. 30, 2021

 Date of Report:
 Jan. 31, 2021

 Report Number:
 TZ210101955-E2

The test report apply only to the specific sample(s) tested under stated test conditions It is not permitted to copy extracts of these test result without the written permission of the test laboratory.



## **TEST RESULT CERTIFICATION**

Applicant's name	Shenzhen Xiangyou Technology Co.LTD
Address:	Room 3A18, Building A5, Hangcheng Innovation Pioneer Park, No.159 Hangcheng Avenue, Sanwei Community, Hangcheng Street, Baoan District, Shenzhen, China
Manufacture's Name	Shenzhen Xiangyou Technology Co.LTD
Address:	Room 3A18, Building A5, Hangcheng Innovation Pioneer Park, No.159 Hangcheng Avenue, Sanwei Community, Hangcheng Street, Baoan District, Shenzhen, China
Product description	
Trade Mark:	N/A
Product name:	Magnetic Fast Wireless Car Charger
Model and/or type reference :	WXC-001
Standards	FCC Rules and Regulations Part 2.1091, KDB680106 D01v03

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen Tongzhou Testing Co.,Ltd is acknowledged as copyright owner and source of the material. Shenzhen Tongzhou Testing Co.,Ltd takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Date of Test	
Date (s) of performance of tests	Jan. 21, 2021 ~ Jan. 30, 2021
Date of Issue	Jan. 31, 2021
Test Result	Pass

2

2

**Testing Engineer** 

Nanci

(Nancy Li)

Technical Manager

hen

(Hugo Chen)

Authorized Signatory :

Andy Zhan

(Andy Zhang)



### **1. GENERAL INFORMATION**

1.1 General Description of EUT

Equipment	Magnetic Fast Wireless Car Charger
Model Name	WXC-001
Serial No.	N/A
Model Difference	N/A
Trade Mark	N/A
FCC ID	2AYTX-WXC-001
Antenna Type	Coil Antenna
Antenna Gain	0dBi
Operation frequency	110-205KHz
Modulation Type	ASK
Power Rating	Input: 5V==3A, 9V==2A, 12V==2A Output: 5V==1.0A, 9V==1.12A, 9V==1.67A
Test Sample ID	TZ210101955-1#

Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.

The EUT antenna is Coil Antenna. No antenna other than that furnished by the responsible party shall be used with the device.



- 2. SUMMARY OF TEST RESULTS
- 2.1 Test procedures according to the technical standards: FCC KDB680106 D01 RF Exposure Wireless Charging Apps v03

FCC CFR 47						
Standard Section	Test Item	Judgment	Remark			
FCC CFR 47 part1, 1.1310 KDB680106 D01v03 (3)(3)	Electric Field Strength (E) (V/m)	PASS				
	Magnetic Field Strength (H) (A/m)	PASS				

#### 2.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement  $y \pm U$ , where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of  $k{=}2$ , providing a level of confidence of approximately  $95~\%_\circ$ 

No.	Item	Uncertainty
1	All emissions, radiated(<30M)(9KHz-30MHz)	±2.45dB
2	Temperature	±0.5°C
3	Humidity	±2%



#### 2.3 Test Instruments

Description	Brand	Model No.	Frequency Range	Calibrated Date	Calibrated Until
Broadband Field Meter	NARDA	NBM-550	-	Dec. 27, 2020	Dec. 27, 2021
Magnetic Field Meter	NARDA	ELT-400	1 – 400kHz	Dec. 27, 2020	Dec. 27, 2021
Magnetic Probe	NARDA	HF-3061	300kHz – 30MHz	Dec. 27, 2020	Dec. 27, 2021
Magnetic Probe	NARDA	HF-0191	27 – 1000MHz	Dec. 27, 2020	Dec. 27, 2021
Broadband Field Meter	NARDA	NBM-550	-	Dec. 27, 2020	Dec. 27, 2021
Electric Field Meter	COMBINOVA	EFM 200	5Hz – 400kHz	Dec. 27, 2020	Dec. 27, 2021
E-Field Probe	NARDA	EF-0391	100kHz – 3GHz	Dec. 27, 2020	Dec. 27, 2021
E-Field Probe	NARDA	EF-6091	100MHz – 60GHz	Dec. 27, 2020	Dec. 27, 2021

NOTE: 1. The calibration interval of the above test instruments is 12 months.

#### 2.4 Special Accessories

No.	Equipment	Manufacturer
1	Intelligent wireless charging full function test module	YBZ

## 2.5 Operation of EUT during testing

Test Mo	Fest Modes:							
Mode 1	AC/DC Adapter (12V/2A) + EUT + Wireless charger tester (Load 15W)	Record						
Mode 2	AC/DC Adapter (12V/2A) + EUT + Wireless charger tester (Load 10W)	Record						
Mode 3	AC/DC Adapter (12V/2A) + EUT + Wireless charger tester (Load 5W)	Record						
Mode 4	AC/DC Adapter (9V/2A) + EUT + Wireless charger tester (Load 10W)	Record						
Mode 5	AC/DC Adapter (9V/2A) + EUT + Wireless charger tester (Load 5W)	Record						
Mode 6	Mode 6 AC/DC Adapter (5V/3A) + EUT + Wireless charger tester (Load 5W) Record							
Note: All	test modes were pre-tested, but we only recorded the worst case in this report.							



#### 3. MAXIMUM PERMISSIBLE EXPOSURE

#### Limit of Maximum Permissible Exposure

Limits for Occupational / Controlled Exposure							
Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm²)	Averaging Time  E ², H ² or S (minutes)			
0.3-3.0	614	1.63	(100)*	6			
3.0-30	1842 / f	4.89 / f	(900 / f)*	6			
30-300	61.4	0.163	1.0	6			
300-1500			F/300	6			
1500-100,000			5	6			
Limits for General Population / Uncontrolled Exposure							
	Limits for General	Population / Uncont	rolled Exposure				
Frequency Range (MHz)	Limits for General Electric Field Strength (E) (V/m)	Population / Uncont Magnetic Field Strength (H) (A/m)	rolled Exposure Power Density (S) (mW/ cm²)	Averaging Time  E ², H ² or S (minutes)			
Frequency Range (MHz) 0.3-1.34	Limits for General Electric Field Strength (E) (V/m) 614	Population / Uncont Magnetic Field Strength (H) (A/m) 1.63	rolled Exposure Power Density (S) (mW/ cm <sup>2</sup> ) (100)*	Averaging Time  E  <sup>2</sup> , H  <sup>2</sup> or S (minutes) 30			
Frequency Range (MHz) 0.3-1.34 1.34-30	Limits for General Electric Field Strength (E) (V/m) 614 824/f	Population / Uncont Magnetic Field Strength (H) (A/m) 1.63 2.19/f	Power Density (S) (mW/ cm <sup>2</sup> ) (100)* (180 / f)*	Averaging Time  E  <sup>2</sup> , H  <sup>2</sup> or S (minutes) 30 30			
Frequency Range (MHz) 0.3-1.34 1.34-30 30-300	Limits for General Electric Field Strength (E) (V/m) 614 824/f 27.5	Population / Uncont Magnetic Field Strength (H) (A/m) 1.63 2.19/f 0.073	rolled Exposure Power Density (S) (mW/ cm <sup>2</sup> ) (100)* (180 / f)* 0.2	Averaging Time  E ², H ² or S (minutes) 30 30 30			
Frequency Range (MHz) 0.3-1.34 1.34-30 30-300 300-1500	Limits for General Electric Field Strength (E) (V/m) 614 824/f 27.5	Population / Uncont Magnetic Field Strength (H) (A/m) 1.63 2.19/f 0.073	rolled Exposure Power Density (S) (mW/ cm <sup>2</sup> ) (100)* (180 / f)* 0.2 F/1500	Averaging Time  E ², H ² or S (minutes) 30 30 30 30			

Note 1: f = frequency in MHz ; \*Plane-wave equivalent power density

Note 2: For the applicable limit, see FCC 1.1310, 680106 D01 RF Exposure Wireless Charging Apps v03 Note 3: Emissions between 100 kHz to 300 kHz should be assessed versus the limits at 300 kHz in Table

1 of Section 1.1310: 614 V/m and 1.63 A/m. A KDB inquiry is required to determine the applicable exposure limits below 100 kHz.



#### 4. TEST PROCEDURE

a. For devices designed for typical desktop applications, such a wireless charging pads, RF exposure evaluation should be conducted assuming a user separation distance of 15 cm. E and H field strength measurements or numerical modeling may be used to demonstrate compliance. Measurements should be made from all sides and the top of the primary/client pair, with the 15 cm measured from the center of the probe(s) to the edge of the device.

#### 4.1 TEST SETUP



#### 4.2 RESULT OF MAXIMUM PERMISSIBLE EXPOSURE

Temperature	22.8°C	Humidity	55%
Test Engineer	Tony Luo	Configurations	Mode 1

E-Field Strength at 15 cm from the edges surrounding the EUT and 15cm from the top surface of the EUT

				Measured E-Field Strength Values (V/m)					FCC	FCC
Test Mode	Power Load	Unit	Frequency Range (MHz)	Test Position A	Test Position B	Test Position C	Test Position D	Test Position E	E-Field Strength 50% Limits (V/m)	E-Field Strength Limits (V/m)
1	15W	v/m	0.186	98.1331	76.6441	80.0371	94.2123	91.611	307.0	614.0
2	10W	v/m	0.186	64.1654	66.7667	65.2964	70.0089	81.055	307.0	614.0
3	5W	v/m	0.186	71.3284	61.6772	63.9769	75.777	70.499	307.0	614.0
4	10W	v/m	0.186	81.9835	68.0268	64.1219	72.0317	80.2499	307.0	614.0
5	5W	v/m	0.186	65.0548	53.3443	56.4013	59.6343	63.7172	307.0	614.0
6	5W	v/m	0.186	58.2507	49.0857	56.1637	59.7137	55.9097	307.0	614.0

Note: V/m= A/m \*377

![](_page_7_Picture_0.jpeg)

H-Field Strength at 15 cm from the edges surrounding the EUT and 15cm from the top surface of the EUT

				Measured H-Field Strength Values (A/m)					FCC	FCC
Test Mod e	Power Load	Unit	Frequenc yRange (MHz)	Test Positio n A	Test Position B	Test Positio n C	Test Positio n D	Test Positio n E	H-Field Strength5 0% Limits (A/m)	H-Field Strength Limits (A/m)
1	15W	uT	0.186	0.3254	0.2541	0.2654	0.3124	0.3038		
I	15W	A/m	0.186	0.2603	0.2033	0.2123	0.2499	0.2430	0.815	1.63
0	10W	uT	0.186	0.2127	0.2214	0.2165	0.2321	0.2688		
2	10W	A/m	0.186	0.1702	0.1771	0.1732	0.1857	0.2150	0.815	1.63
2	5W	uT	0.186	0.2365	0.2045	0.2121	0.2512	0.2338		
3	5W	A/m	0.186	0.1892	0.1636	0.1697	0.2010	0.1870	0.815	1.63
Λ	10W	uT	0.186	0.2718	0.2256	0.2126	0.2388	0.2661		
4	10W	A/m	0.186	0.2175	0.1804	0.1701	0.1911	0.2129	0.815	1.63
5	5W	uT	0.186	0.2157	0.1769	0.1870	0.1977	0.2113		
5	5W	A/m	0.186	0.1726	0.1415	0.1496	0.1582	0.1690	0.815	1.63
6	5W	uT	0.186	0.1931	0.1628	0.1862	0.1980	0.1854		
0	5W	A/m	0.186	0.1545	0.1302	0.1490	0.1584	0.1483	0.815	1.63

H-Field Strength at 20cm from the top surface of the EUT

Test Mode	Power Load	Unit	Frequency Range (MHz)	Measured H-Field Strength Values (A/m) Test Position E	FCC H-Field Strength 50% Limits (A/m)	FCC H-Field Strength Limits (A/m)
1	15W	uT	0.186	0.2456		
	15W	A/m	0.186	0.1965	0.815	1.63
2	10W	uT	0.186	0.2131		
	10W	A/m	0.186	0.1705	0.815	1.63
3	5W	uT	0.186	0.2212		
	5W	A/m	0.186	0.1770	0.815	1.63
Λ	15W	uT	0.186	0.1999		
4	15W	A/m	0.186	0.1599	0.815	1.63
5	10W	uT	0.186	0.1691		
	10W	A/m	0.186	0.1353	0.815	1.63
6	5W	uT	0.186	0.1480		
	5W	A/m	0.186	0.1184	0.815	1.63

Note:A/m=uT/1.25

![](_page_8_Picture_0.jpeg)

4.3 Equipment Approval Considerations

The EUT does comply with KDB 680106 D01 as follow table.

Requirements of KDB 680106 D01	Yes / No	Description
Power transfer frequency is less than 1 MHz	Yes	The device operate in the frequency range 110KHz~205KHz
Output power from each primary coil is less than 15 watts	Yes	The maximum output power for each primary coil is 15W.
The transfer system includes only single primary and secondary coils. This includes charging systems that may have multiple primary coils and clients that are able to detect and allow coupling only between individual pairs of coils.	Yes	The transfer system includes one primary coils and are able to detect and allow coupling only between individual pairs of coils.
Client device is placed directly in contact with the transmitter.	Yes	Client device is placed directly in contact with the transmitter.
Mobile exposure conditions only (portable exposure conditions are not covered by this exclusion).	Yes	Mobile exposure conditions only
The aggregate H-field strengths at 15 cm surrounding the device and 20 cm above the top surface from all simultaneous transmitting coils are demonstrated to be less than 50% of the MPE limit.	Yes	The EUT H-field strengths at 15 cm surrounding the device and 20 cm above the top surface from all simultaneous transmitting coils are demonstrated to be less than 50% of the MPE limit.

#### 4.4 Conclusion

The detected emissions with a distance of 15cm surrounding the device and 20 cm above the top surface of the device are below the FCC E-Field Strength & H-Field Strength limits; and comply with the requirements of FCC KDB 680106 D01.

![](_page_9_Picture_0.jpeg)

Page 10 of 10

## PHOTOGRAPH OF TEST

![](_page_9_Picture_4.jpeg)

\*\*\*\*\*\*THE END\*\*\*\*\*