

TEST REPORT

Applicant: Queclink Wireless Solutions Co., Ltd.
Address: No.30, Lane 500, Xinlong Road, Minhang District,
Shanghai, China
Equipment Type: Telematics dual-lens LTE Dash Cam
Model Name: CV100LG
Brand Name: QUECLINK
FCC ID: YQD-CV100LG
Test Standard: 47 CFR Part 2.1091
KDB 447498 D01 v06
Test Date: Jun. 21, 2022 - Jun. 28, 2022
Date of Issue: Jul. 07, 2022

ISSUED BY:

Shenzhen BALUN Technology Co., Ltd.

Tested by: Julie Zhu

Checked by: Zong Liyao

Approved by: Wei Yanquan
(Chief Engineer)

Julie Zhu

Liyao.Zong

Wei Yanquan

Revision History

<u>Version</u>	<u>Issue Date</u>	<u>Revisions Content</u>
<u>Rev. 01</u>	<u>Jul. 07, 2022</u>	<u>Initial Issue</u>

TABLE OF CONTENTS

1	GENERAL INFORMATION.....	3
1.1	Identification of the Testing Laboratory	3
1.2	Identification of the Responsible Testing Location	3
2	PRODUCT INFORMATION	4
2.1	Applicant Information	4
2.2	Manufacturer Information.....	4
2.3	Factory Information.....	4
2.4	General Description for Equipment under Test (EUT).....	4
2.5	Ancillary Equipment.....	4
2.6	Technical Information	5
3	SUMMARY OF TEST RESULT	6
3.1	Test Standards	6
4	DEVICE CATEGORY AND LEVELS LIMITS	7
5	ASSESSMENT RESULT	9
5.1	Output Power	9
5.2	Tune-up power	10
5.3	RF Exposure Evaluation Result	10
5.4	Collocated Power Density Calculation	10
5.5	Conclusion.....	11

1 GENERAL INFORMATION

1.1 Identification of the Testing Laboratory

Company Name	Shenzhen BALUN Technology Co., Ltd.
Address	Block B, 1/F, Baisha Science and Technology Park, Shahe West Road, Nanshan District, ShenZhen, GuangDong Province, China
Phone Number	+86 755 6685 0100

1.2 Identification of the Responsible Testing Location

Test Location	Shenzhen BALUN Technology Co., Ltd.
Address	Block B, 1/F, Baisha Science and Technology Park, Shahe West Road, Nanshan District, ShenZhen, GuangDong Province, China
Accreditation Certificate	The laboratory is a testing organization accredited by FCC as a accredited testing laboratory. The designation number is CN1196.
Description	All measurement facilities used to collect the measurement data are located at Block B, 1/F, Baisha Science and Technology Park, Shahe West Road, Nanshan District, ShenZhen, GuangDong Province, China

2 PRODUCT INFORMATION

2.1 Applicant Information

Applicant	Queclink Wireless Solutions Co., Ltd.
Address	No.30, Lane 500, Xinlong Road, Minhang District, Shanghai, China

2.2 Manufacturer Information

Manufacturer	Queclink Wireless Solutions Co., Ltd.
Address	No.30, Lane 500, Xinlong Road, Minhang District, Shanghai, China

2.3 Factory Information

Factory	N/A
Address	N/A

2.4 General Description for Equipment under Test (EUT)

EUT Name	Telematics dual-lens LTE Dash Cam
Model Name Under Test	CV100LG
Series Model Name	N/A
Description of Model name differentiation	N/A
Hardware Version	N/A
Software Version	N/A
Dimensions (Approx.)	N/A
Weight (Approx.)	N/A

2.5 Ancillary Equipment

Note: Not applicable.

2.6 Technical Information

Network and Wireless connectivity	2G Network GSM/GPRS/EGPRS 1900 MHz; 3G Network WCDMA/HSDPA/HSUPA Band 2 4G Network FDD LTE Band 2/4/12/13 Bluetooth BLE 2.4G WIFI 802.11b, 802.11g, 802.11n(HT20) GPS, GLONASS
-----------------------------------	---

The requirement for the following technical information of the EUT was tested in this report:

Operating Mode	Bluetooth, GSM, WCDMA, LTE, WLAN		
Frequency Range	Bluetooth	2400 ~ 2483.5 MHz	
	WIFI	2412MHz ~ 2462MHz	
	GSM 1900	TX: 1850 ~ 1910 MHz	RX: 1930 ~ 1990 MHz
	WCDMA 2	TX: 1850 ~ 1910 MHz	RX: 1930 ~ 1990 MHz
	LTE Band 2	TX: 1850 ~ 1910 MHz	RX: 1930 ~ 1990 MHz
	LTE Band 4	TX: 1710 ~ 1755 MHz	RX: 2110 ~ 2155 MHz
	LTE Band 12	TX: 699 ~ 716 MHz	RX: 729 ~ 746 MHz
	LTE Band 13	TX: 777 ~ 787 MHz	RX: 746 ~ 756 MHz
Antenna Type	Bluetooth	PIFA Antenna	
	WIFI	PIFA Antenna	
	WWAN	PIFA Antenna	
Exposure Category	General Population/Uncontrolled Exposure		
EUT Stage	Mobile Device		

3 SUMMARY OF TEST RESULT

3.1 Test Standards

No.	Identity	Document Title
1	47 CFR Part 2.1091	Radiofrequency radiation exposure evaluation: mobile devices
2	KDB 447498 D01 v06	447498 D01 General RF Exposure Guidance D01 v06

4 DEVICE CATEGORY AND LEVELS LIMITS

Mobile Derives:

CFR Title 47 §2.1091(b)

(b) For purposes of this section, a mobile device is defined as a transmitting device designed to be used in other than fixed locations and to generally be used in such a way that a separation distance of at least 20 centimeters is normally maintained between the transmitter's radiating structure(s) and the body of the user or nearby persons.

FCC KDB 447498 D01 General RF Exposure Guidance v06 Limit

Devices operating in standalone mobile exposure conditions may contain a single transmitter or multiple transmitters that do not transmit simultaneously. A minimum test separation distance ≥ 20 cm is required between the antenna and radiating structures of the device and nearby persons to apply mobile device exposure limits. The distance must be fully supported by the operating and installation configurations of the transmitter and its antenna(s), according to the source-based time-averaged maximum power requirements of § 2.1091(d)(2). In cases where cable losses or other attenuations are applied to determine compliance, the most conservative operating configurations and exposure conditions must be evaluated. The minimum test separation distance required for a device to comply with mobile exposure conditions must be clearly identified in the installation and operating instructions, for all installation and exposure conditions, to enable users and installers to comply with RF exposure requirements. For mobile devices that have the potential to operate in portable device exposure conditions, similar to the configurations described in § 2.1091(d)(4), a KDB inquiry is required to determine the SAR test requirements for demonstrating compliance.

When the categorical exclusion provision of § 2.1091(c) applies, the minimum test separation distance may be estimated, when applicable, by simple calculations according to plane-wave equivalent conditions, to ensure the transmitter and its antenna(s) can operate in manners that meet or exceed the estimated distance. The source-based time-averaged maximum radiated power, according to the maximum antenna gain, must be applied to calculate the field strength and power density required to establish the minimum test separation distance. When the estimated test separation distance becomes overly conservative and does not support compliance, MPE measurement or computational modeling may be used to determine the required minimum separation distance.

According to FCC Part 1.1307, systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the commission's guidelines.

Limits for General Population/ Uncontrolled Exposure			
Frequency Range (MHz)	Electric Field Strength(E)(V/m)	Magnetic Field Strength (H)(A/m)	Power Density (S)(mW/cm ²)
0.3-1.34	614	1.63	(100)*
1.34-30	824/f	2.19/f	(180/f ²)*
30-300	27.5	0.073	0.2
300-1500			f/1500
1500-100,000			1.0

MPE calculation formula

$$S = \frac{PG}{4\pi R^2}$$

Where:

S = power density

P = output power (mW)

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = Separation distance between radiator and human body (cm)

5 ASSESSMENT RESULT

5.1 Output Power

GSM	
Mode	GSM 1900
ERP/EIRP (dBm)	32.96
Note: This report listed the worst case ERP/EIRP value, please refer to RF test report for more details.	

WCDMA	
Mode	Band 2
ERP/EIRP (dBm)	25.07
Note: This report listed the worst case ERP/EIRP value, please refer to RF test report for more details.	

LTE				
Mode	Band 2	Band 4	Band 12	Band 13
ERP/EIRP (dBm)	25.83	25.53	20.35	23.10
Note: This report listed the worst case ERP/EIRP value, please refer to RF test report for more details.				

Bluetooth			
Mode	GFSK (BLE 1Mbps)		
	Low Channel	Middle Channel	High Channel
Peak Power (dBm)	0.08	0.10	-0.24
Antenna Gain (dBi)	1.91		
EIRP/ERP	1.99	2.01	1.67
Note: This report listed the maximal case power value, please refer to RF test report for more details.			

2.4G WIFI			
Mode	802.11b	802.11g	802.11n20
Peak Power (dBm)	18.07	20.47	20.69
Antenna Gain (dBi)	1.91		
EIRP/ERP	19.98	22.38	22.60
Note: This report listed the maximal case power value, please refer to RF test report for more details.			

5.2 Tune-up power

Mode		Range
GSM 1900		30.00-33.00
WCDMA	Band 2	23.00-27.00
LTE	Band 2	23.00-26.50
	Band 4	23.00-26.00
	Band 12	18.00-21.00
	Band 13	21.00-24.00
Bluetooth		1.00-2.50
2.4G WIFI		17.00-23.00

5.3 RF Exposure Evaluation Result

Evolution mode		Maximum ERP/EIRP (dBm)	Antenna Gain (typical) (dBi):	Total Power (mw)	Distance (cm)	Power Density (mW/cm ²)	Limit of Power Density (mW/cm ²)	Power Density / Limit	Verdict
Bluetooth		2.50	1.91	1.778	20	0.0004	1	0.0004	Pass
2.4G WIFI		23.00	1.91	199.526	20	0.0397	1	0.0397	Pass
GSM 1900		33.00	2.63	1995.262	20	0.3969	1	0.3969	Pass
WCDMA	Band 2	27.00	2.63	501.1872	20	0.0997	1	0.0997	Pass
LTE	Band 2	26.50	2.63	446.6836	20	0.0889	1	0.0889	Pass
	Band 4	26.00	2.28	398.1072	20	0.0792	1	0.0792	Pass
	Band 12	21.00	-0.82	125.8925	20	0.0250	0.466	0.0536	Pass
	Band 13	24.00	1.36	251.1886	20	0.0500	0.518	0.0965	Pass

5.4 Collocated Power Density Calculation

Evolution mode	Frequency(MHz)	Power Density/Limit	$\Sigma(\text{Power Density / Limit})$ of WWAN + WLAN	Verdict
GSM 1900	1850MHz ~ 1910 MHz	0.3969	0.4366	Pass
2.4G WIFI	2412MHz ~ 2462MHz	0.0397		

Evolution mode	Frequency(MHz)	Power Density/Limit	$\Sigma(\text{Power Density / Limit})$ of WWAN + Bluetooth	Verdict
GSM 1900	1850MHz ~ 1910 MHz	0.3969	0.3973	Pass
Bluetooth	2400MHz ~ 2483.5MHz	0.0004		

Note:

1. $\Sigma(\text{Power Density} / \text{Limit})$: This is a summation of [(power density for each transmitter/ antenna included in the simultaneous transmission)/ (corresponding MPE limit)], for WLAN 2.4GHz+WWAN+ Bluetooth.
2. Both of the 2.4GHz/1900MHz can transmit simultaneously, the formula of calculated the MPE is $\text{CPD1} / \text{LPD1} + \text{CPD2} / \text{LPD2} + \dots \text{etc.} < 1$
CPD = Calculation power density
LPD = Limit of power density
3. The worst-case situation is 0.4366, which is less than "1". This confirmed that the device comply with FCC 1.1310 MPE limit.
4. The DUT work frequency range used is 2400 MHz ~ 2483.5 MHz and 1850MHz ~ 1910 MHz or 22412MHz ~ 2462MHz and 1850MHz ~ 1910 MHz the result close to the limit by the above formula, so we select worst case power to calculate the exclusion power threshold.
5. More power list please refer to RF test report.

5.5 Conclusion

This EUT is deemed to comply with the reference level limits, therefore the basic restrictions are compliant with human exposure limits.

Statement

1. The laboratory guarantees the scientificity, accuracy and impartiality of the test, and is responsible for all the information in the report, except the information provided by the customer. The customer is responsible for the impact of the information provided on the validity of the results.
2. The report without China inspection body and laboratory Mandatory Approval (CMA) mark has no effect of proving to the society.
3. For the report with CNAS mark or A2LA mark, the items marked with "☆" are not within the accredited scope.
4. This report is invalid if it is altered, without the signature of the testing and approval personnel, or without the "inspection and testing dedicated stamp" or test report stamp.
5. The test data and results are only valid for the tested samples provided by the customer.
6. This report shall not be partially reproduced without the written permission of the laboratory.
7. Any objection shall be raised to the laboratory within 30 days after receiving the report.

--END OF REPORT--