


ZW96S 说明书  
展开：210 x 297 mm  
材质：80G书写纸  
单色印刷



EVA LOGIK®

Outdoor Smart Plug

- ZW96S •



Meet your new smart Plug !



For outdoor use  
IP65 Rated

- (A) Manual / Program button**  
Single press: manually turn on/off your device.
- (B) Smart Outlet**  
This is your smart outlet that will be included in your smart home

Z-Wave Internet


The Internet of Things offers tremendous promise to consumers by enabling remote control and management of an ever-growing variety of connected devices—from home security systems to energy management, appliances and lighting, and remote home monitoring, just to name a few categories.

Analysts predict that billions of devices will be connected to the Internet of Things in the coming years. One key consideration is how all of these devices will be integrated and controlled, and common standards are key to enabling simple, straight forward installation and management of devices in the connected home.


The Z-Wave protocol is an interoperable, wireless, RF-based communications technology designed specifically for control, monitoring and status reading applications in residential and light commercial environments. Mature, proven and broadly deployed (with over 100 million products sold worldwide), Z-Wave is by far the world market leader in wireless control, bringing affordable, reliable and easy-to-use 'smart' products to many millions of people in every aspect of daily life.

Introduction

The EVA LOGIK WF96S is an enabled 15A outdoor smart plug designed for use for most residential lighting and motor applications. It's compatible with LED, halogen, incandescent, xenon, fluorescent and compact fluorescent bulbs. Works with Amozon Alexa, Google Assistant and IFTTT. Overload protection and no hub required. One smart outlet, you can use free App, or voice control by Alexa and Google Assistant to operate your devices in your home. Total load capacity for both outlets is 15A(1800W) Resistive. Plug the light you want to control into the Z-Wave Smart plug controlled outlet .  
**NOTE:** Plug directly into outlet, do not use with extension cords



**Note:**Your device may need to be within 100 feet of the controller to be included. If so, include the device to the network within 10 feet of the controller and relocate it to the desired position in your home. Be sure to refresh the network if the device is included in this manner.



- White LED indicator

Add to Z-Wave Network

Put the Z-wave interface controller into “Add” mode, triple press the Program button (A). It will be included to network.(Once your controller confirmed, refresh the Z-Wave network to optimize performance.)

Remove from Z-Wave Network

Put the Z-Wave interface controller into "Remove" mode, triple press the Program button (A). It will be excluded to network.

To return your switch to factory defaults

Manual reset:  
---Power off ZW96  
---Keep holding the PROG button  
---Power on, Press and keep holding the PROG button for no less than 10 seconds.  
Note: This should only be used in the event your network's primary controller is missing or otherwise inoperable.

Specifications

Model: ZW96S  
Power: 120V AC, 60Hz  
Signal (Frequency): 908.42 MHz  
Loading :15 Amp Max  
Operating Temperature Range: -4-122° F (-20-50° C)  
Approval: UL/FCC/Z-Wave Plus Certified

Parameter Settings

1: LED Indicator (LED flash 2 times set success)  
Manual setting out on, led on (default)  
Press button 5 times out on, led off  
Press button 10 times led no work  
--Parameter = 1, size = 1 byte, value = 00 (Plug On / LED On)  
--Parameter = 1, size = 1 byte, value = 01 (Plug On / LED Off)  
--Parameter = 1, size = 1 byte, value = 02 (LED Disabled)

2: Countdown (Plug Auto Shutoff) I Default = Off  
--Parameter = 2, size = 2 byte, value = xx xx  
Default value = 00 00, range 0-36000 sec)

3: Remembers and restores state after power failure

Association  
Support 2 group , each group max support 5 devices  
Group 1 lifeline  
Group 2 send basic set

\*The association group supports five nodes and lifeline function

FCC / IC

This device complies with part 15 of the FCC and Industry Canada license-exempt RSS standard(s). Operation is subject to the following two conditions:  
(1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

**FCC NOTE:** The manufacturer is not responsible for any radio or TV interference caused by unauthorized modifications to this equipment. Such modifications could void the user's authority to operate the equipment.

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help



CAUTION - PLEASE READ!



This device (ZW96S) is intended for installation in accordance with the National Electric Code and local regulations in the United States, or the Canadian Electrical Code and local regulations in Canada. If you are unsure or uncomfortable about performing this installation consult a qualified electrician.



WARNING - SHOCK HAZARD



**TURN OFF THE POWER** to the circuit for the switch and lighting fixture at the service panel (circuit breaker) prior to installation.

**ALL WIRING CONNECTIONS MUST BE MADE WITH THE POWER OFF** to avoid personal injury and/or damage to the switch.



OTHER WARNINGS



Risk of Fire  
Risk of Electrical Shock  
Risk of Burns

**NOTE:** This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

Important note: To comply with the FCC RF exposure compliance requirements, no change to the antenna or the device is permitted. Any change to the antenna or the device could result in the device exceeding the RF exposure requirements and void user's authority to operate the device.



MEDICAL EQUIPMENT



Please DO NOT use this switch to congrol Medical or Life Support equipment. Z-Wave devices should never be used to control the On/Off status of Medical and/or Life Support equipment.



CONTROLLING APPLIANCES



Please exercise EXTREME CAUTION when using Z-Wave devices to control appliances. Reason being is because the appliance you want to control may be in a separate room and if unintentional behavior occurs (such as adevice turning on or off - either intentionally via schedules, or unintentionally via network error) this event may lead to a hazardous condition. For these reasons, please note the following suggestions:

1) Do not include Z-Wave devices in Groups or Scenes if they control appliances.

2) Do not use Z-Wave devices to control electric heaters or any other appliances which may present a hazardous condition due to unattended, unintentional, or automatic power control



Z-wave Interoperability

This product can be included and operated in any Z-Wave network with other Z-Wave certified devices from other manufacturers and/or other applications. All non-battery operated nodes within the network will act as repeaters regardless of vendor to increase reliability of the network.

This Device supports Lifeline (association group 1) supporting 1 node for lifeline communication. Group 1 must be assigned the Node ID of the primary controller where unsolicited notifications will be sent. The Z-Wave controller should set this association automatically after inclusion. Lifeline association only supports the “Device Reset Locally” function. Refer to the instructions of your controller for any available details on how this can be set.

Command Class Information

GRNERIC DEVICE CLASS:  
10 - GENERIC\_TYPE\_SWITCH\_BINARY  
SPECIFIC DEVICE CLASS:  
01 - SPECIFIC\_TYPE\_POWER\_SWITCH\_BINARY

COMMANDCLASS:

71 - COMMAND\_CLASS\_ALARM  
85 - COMMAND\_CLASS\_ASSOCIATION  
59 - COMMAND\_CLASS\_ASSOCIATION\_GRP\_INFO  
70 - COMMAND\_CLASS\_CONFIGURATION  
5A - COMMAND\_CLASS\_DEVICE\_RESET\_LOCALLY  
7A - COMMAND\_CLASS\_FIRMWARE\_UPDATE\_MD  
72 - COMMAND\_CLASS\_MANUFACTURER\_SPECIFIC  
8E - COMMAND\_CLASS\_MULTI\_CHANNEL\_ASSOCIATION  
73 - COMMAND\_CLASS\_POWERLEVEL  
98 - COMMAND\_CLASS\_SECURITY  
9F - COMMAND\_CLASS\_SECURITY\_2  
6C - COMMAND\_CLASS\_SUPERVISION  
27 - COMMAND\_CLASS\_SWITCH\_ALL  
25 - COMMAND\_CLASS\_SWITCH\_BINARY  
55 - COMMAND\_CLASS\_TRANSPORT\_SERVICE  
86 - COMMAND\_CLASS\_VERSION  
5E - COMMAND\_CLASS\_ZWAVEPLUS\_INFO