



REPORT No.: SZ24040355S01

Annex F Test Position Consideration

Exposure Position	Wireless Interface	BT	2.4GHz WLAN WIFI 1	2.4GHz WLAN WIFI 2	2.4GHz WLAN MIMO	5GHz WLAN WIFI 1	5GHz WLAN WIFI2	5GHz WLAN MIMO	6GHz WLAN WIFI 1	6GHz WLAN WIFI 2	6GHz WLAN MIMO
Bottom Face	Calculated Frequency	2480MHz	2472MHz	2472MHz	2472MHz	5825MHz	5825MHz	5825MHz	7125MHz	7125MHz	7125MHz
	Maximum power (dBm)	12	22	22	24	22	22	25	14.5	15	14.5
	Maximum rated power(mW)	16.0	158.0	158.0	251.0	158.0	158.0	316.0	28.0	32.0	28.0
	Separation distance(mm)	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0
Edge 1	exclusion threshold	5.0	49.7	49.7	78.9	13.5	15.5	13.5	15.0	17.1	15.0
	Testing required?	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
	Separation distance(mm)	2.3	2.3	2.3	2.3	2.3	2.3	2.3	2.3	2.3	2.3
	exclusion threshold	5.0	49.2	49.7	78.9	13.5	15.5	13.5	15.0	17.1	15.0
Edge 2	Testing required?	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
	Separation distance(mm)	89.4	212.1	89.4	89.4	212.1	89.4	89.4	212.1	89.4	89.4
	exclusion threshold	490.0	1716.0	490.0	490.0	1683.0	457.0	457.0	1677.0	451.0	451.0
	Testing required?	No	No	No	No	No	No	No	No	No	No
Edge 3	Separation distance(mm)	200.0	200.0	200.0	200.0	200.0	200.0	200.0	200.0	200.0	200.0
	exclusion threshold	1595.0	1595.0	1595.0	1595.0	1562.0	1562.0	1562.0	1556.0	1556.0	1556.0
	Testing required?	No	No	No	No	No	No	No	No	No	No
	Separation distance(mm)	212.6	89.9	212.6	89.9	89.9	212.6	89.9	89.9	212.6	89.9
Edge 4	exclusion threshold	1721.0	494.0	1721.0	494.0	461.0	1688.0	461.0	455.0	1682.0	455.0
	Testing required?	No	No	No	No	No	No	No	No	No	No