



TEST REPORT

Application No.: BTEK240111002AE
Applicant: SHENZHEN ECARE ELECTRONICS CO., LTD
Address of Applicant: B201/B401/B501/B601, Hua Li Industrial Building, 404 Yu An Road, Bao An, Shenzhen, Guang Dong, China
Manufacturer: SHENZHEN ECARE ELECTRONICS CO., LTD
Address of Manufacturer: B201/B401/B501/B601, Hua Li Industrial Building, 404 Yu An Road, Bao An, Shenzhen, Guang Dong, China
Factory: SHENZHEN ECARE ELECTRONICS CO., LTD
Address of Factory: B201/B401/B501/B601, Hua Li Industrial Building, 404 Yu An Road, Bao An, Shenzhen, Guang Dong, China
Equipment Under Test (EUT):
EUT Name: Bluetooth Thermometer/Hygrometer
Model No.: TP350, TP350W, C50
Please refer to section 2 of this report which indicates which model was actually tested and which were electrically identical.
Trade Mark: N/A
Standard(s) : 47 CFR Part 15, Subpart C 15.247
Date of Receipt: 2024-01-11
Date of Test: 2024-01-11 to 2024-01-27
Date of Issue: 2024-01-31

Test Result:

Pass*

* In the configuration tested, the EUT complied with the standards specified above.

Damon Su
EMC Laboratory Manager





Revision Record				
Version	Chapter	Date	Modifier	Remark
01		2024-01-31		Original

Authorized for issue by			
		<div>Elma Yang</div> <div>Elma Yang/Project Engineer</div>	
		<div>Carl Yang</div> <div>Carl Yang/Reviewer</div>	



2 Test Summary

Radio Spectrum Technical Requirement				
Item	Standard	Method	Requirement	Result
Antenna Requirement	47 CFR Part 15, Subpart C 15.247	N/A	47 CFR Part 15, Subpart C 15.203 & 15.247(b)(4)	Pass

Radio Spectrum Matter Part				
Item	Standard	Method	Requirement	Result
Conducted Peak Output Power	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 11.9.1.3	47 CFR Part 15, Subpart C 15.247(b)(3)	Pass
Minimum 6dB Bandwidth		ANSI C63.10 (2013) Section 11.8.1	47 CFR Part 15, Subpart C 15.247a(2)	Pass
Power Spectrum Density		ANSI C63.10 (2013) Section 11.10.2	47 CFR Part 15, Subpart C 15.247(e)	Pass
Conducted Band Edges Measurement		ANSI C63.10 (2013) Section 11.13.3.2	47 CFR Part 15, Subpart C 15.247(d)	Pass
Conducted Spurious Emissions		ANSI C63.10 (2013) Section 11.11	47 CFR Part 15, Subpart C 15.247(d)	Pass
Radiated Emissions which fall in the restricted bands		ANSI C63.10 (2013) Section 6.10.5	47 CFR Part 15, Subpart C 15.205 & 15.209	Pass
Radiated Spurious Emissions (Below 1GHz)		ANSI C63.10 (2013) Section 6.4,6.5,6.6	47 CFR Part 15, Subpart C 15.205 & 15.209	Pass
Radiated Spurious Emissions (Above 1GHz)		ANSI C63.10 (2013) Section 6.4,6.5,6.6	47 CFR Part 15, Subpart C 15.205 & 15.209	Pass

Note:

Model No.: TP350, TP350W, C50

Only the model TP350 was tested. According to the declaration from the applicant, the electrical circuit design, layout, components used, internal wiring and functions of other models are identical for the above models, with only difference on model No.



3 Contents

	Page
1 Cover Page	1
2 Test Summary	3
3 Contents	4
4 General Information.....	6
4.1 Details of E.U.T.....	6
4.2 Description of Support Units	6
4.3 Measurement Uncertainty	6
4.4 Test Location.....	7
4.5 Deviation from Standards.....	7
4.6 Abnormalities from Standard Conditions	7
5 Equipment List	8
6 Radio Spectrum Technical Requirement	10
6.1 Antenna Requirement.....	10
6.1.1 Test Requirement:	10
6.1.2 Conclusion	10
7 Radio Spectrum Matter Test Results	11
7.1 Conducted Peak Output Power.....	11
7.1.1 E.U.T. Operation	11
7.1.2 Test Mode Description	11
7.1.3 Test Setup Diagram.....	11
7.1.4 Measurement Procedure and Data	11
7.2 Minimum 6dB Bandwidth.....	12
7.2.1 E.U.T. Operation	12
7.2.2 Test Mode Description	12
7.2.3 Test Setup Diagram	12
7.2.4 Measurement Procedure and Data	12
7.3 Power Spectrum Density.....	13
7.3.1 E.U.T. Operation	13
7.3.2 Test Mode Description	13
7.3.3 Test Setup Diagram	13
7.3.4 Measurement Procedure and Data	13
7.4 Conducted Band Edges Measurement	14
7.4.1 E.U.T. Operation	14
7.4.2 Test Mode Description	14
7.4.3 Test Setup Diagram	14
7.4.4 Measurement Procedure and Data	14
7.5 Conducted Spurious Emissions	15
7.5.1 E.U.T. Operation	15
7.5.2 Test Mode Description	15
7.5.3 Test Setup Diagram	15
7.5.4 Measurement Procedure and Data	15
7.6 Radiated Emissions which fall in the restricted bands	16
7.6.1 E.U.T. Operation	16
7.6.2 Test Mode Description	16
7.6.3 Test Setup Diagram	16
7.6.4 Measurement Procedure and Data	17
7.7 Radiated Spurious Emissions (Below 1GHz).....	19
7.7.1 E.U.T. Operation	19



7.7.2	Test Mode Description	19
7.7.3	Test Setup Diagram	19
7.7.4	Measurement Procedure and Data	20
7.8	Radiated Spurious Emissions (Above 1GHz)	23
7.8.1	E.U.T. Operation	23
7.8.2	Test Mode Description	23
7.8.3	Test Setup Diagram	24
7.8.4	Measurement Procedure and Data	25
8	Test Setup Photo	28
9	EUT Constructional Details (EUT Photos)	28
10	Appendix	29



4 General Information

4.1 Details of E.U.T.

Power supply:	DC 3V from 2 AAA Batteries
Frequency Range:	2402MHz to 2480MHz
Bluetooth Version:	V5.0
This test report is for BLE mode	
Modulation Type:	GFSK
Channel Spacing:	2MHz
Data Rate:	1Mbps
Number of Channels:	40
Sample Type:	Portable device
Antenna Type:	PCB Antenna
Antenna Gain:	5 dBi
Sample No.:	BTEK240111002AE-01
Remark: The information in this section is provided by the applicant or manufacturer, BANTEK is not liable to the accuracy, suitability, reliability or/and integrity of the information.	

4.2 Description of Support Units

Description	Manufacturer	Model No.	Serial No.
/	/	/	/

4.3 Measurement Uncertainty

Test Item	Measurement Uncertainty
Conducted Peak Output Power	$\pm 0.76\text{dB}$
Minimum 6dB Bandwidth	$\pm 3\%$
Power Spectrum Density	$\pm 0.35\text{dB}$
Conducted Band Edges Measurement	$\pm 0.8\text{dB}$
Conducted Spurious Emissions	$\pm 0.8\text{dB}$
Radiated Emissions which fall in the restricted bands	$\pm 5.1\text{dB}$ (1GHz-6GHz); $\pm 5.2\text{dB}$ (above 6GHz)
Radiated Spurious Emissions (Below 1GHz)	$\pm 5.1\text{dB}$
Radiated Spurious Emissions (Above 1GHz)	$\pm 5.1\text{dB}$ (1GHz-6GHz); $\pm 5.2\text{dB}$ (above 6GHz)



4.4 Test Location

All tests were performed at:

Shenzhen BANTEK Testing Co., Ltd.

A5&A6, Building B1&B2, No.45 Gangtou Road, Bogang Community, Shajing Street, Bao'an District, Shenzhen, Guangdong, China 518104

Tel: +86 0755-2334 4200 Fax: +86 0755-2334 4200

FCC Registration Number: 264293

Designation Number: CN1356

No tests were sub-contracted.

4.5 Deviation from Standards

None

4.6 Abnormalities from Standard Conditions

None



5 Equipment List

RF Conducted					
Equipment	Manufacturer	Model No	Serial No	Cal Date	Cal Due Date
Shielding Room	YIHENG ENELECTRONIC	5.5*3.1*3	YH-BT-220304-03	2022-03-03	2025-03-02
EXA Signal Analyzer	KEYSIGHT	N9020A	MY54230486	2023-06-12	2024-06-11
DC Power Supply	E3632A	E3642A	KR75304416	2023-06-12	2024-06-11
Attenuator	RswTech	SMA-JK-6dB	N/A	2023-06-12	2024-06-11
Attenuator	RswTech	SMA-JK-3dB	N/A	2023-06-12	2024-06-11
RF Control Unit	Techy	TR1029-1	N/A	2023-06-12	2024-06-11
RF Sensor Unit	Techy	TR1029-2	N/A	2023-06-12	2024-06-11
WIDEBAND RADIO COMMUNICATION TESTER	R&S	CMW 500	141258	2023-06-12	2024-06-11
MXG Vector Signal Generator	Agilent	N5182A	US46240522	2023-06-12	2024-06-11
Programmable Temperature&Humidity Chamber	GRT	GR-HWX1000	GR22051001	2023-06-12	2024-06-11
Measurement Software	TACHOY	RF TestSoft V2.0.0.0	N/A	N/A	N/A

RSE					
Equipment	Manufacturer	Model No	Serial No	Cal Date	Cal Due Date
3m Semi-Anechoic Chamber	YIHENG ENELECTRONIC	966	YH-BT-220304-01	2022-05-06	2025-05-05
EMI Test Receiver	Rohde&Schwarz	ESCI	100694	2023-06-12	2024-06-11
TRILOG Broadband Antenna	Schwarzbeck	VULB 9168	01324	2022-06-15	2025-06-14
Pre-Amplifier	Schwarzbeck	BBV 9745	#180	2023-06-12	2024-06-11
Measurement Software	Fara	EZ EMC Ver. FA-03A2	N/A	2023-06-12	2024-06-11
EXA Signal Analyzer	Keysight	N9020A	MY54440290	2023-06-12	2024-06-11
Horn Antenna	Schwarzbeck	BBHA 9120D	02695	2022-06-15	2025-06-14
Pre-Amplifier	Tonscend	TAP0118045	AP20K806109	2023-06-12	2024-06-11
Horn Antenna	SCHWARZBECK	BBHA9170	1157	2022-06-15	2025-06-14
Low Noise Pre-amplifier	SKET	LNPA-1840G-50	SK2022032902	2023-06-12	2024-06-11
Signal analyzer	ROHDE&SCHWARZ	FSQ40	100010	2023-06-12	2024-06-11
Loop Antenna	ETS	6502	00201177	2022-06-15	2025-06-14

General used equipment					
Equipment	Manufacturer	Model No	Serial No	Cal Date	Cal Due Date
Humidity/Temperature/B arometric Pressure Indicator	KUMAR	F132	N/A	2023-06-12	2024-06-11
Humidity/Temperature/B	KUMAR	F132	N/A	2023-06-12	2024-06-11





Shenzhen BANTEK Testing Co., Ltd.

Report No.: BTEK240111002AE001

Page: 9 of 43

arometric Pressure Indicator					
------------------------------	--	--	--	--	--



6 Radio Spectrum Technical Requirement

6.1 Antenna Requirement

6.1.1 Test Requirement:

47 CFR Part 15, Subpart C 15.203 & 15.247(b)(4)

6.1.2 Conclusion

Standard Requirement:

Testing shall be performed using the highest gain antenna of each combination of licence-exempt transmitter and antenna type, with the transmitter output power set at the maximum level. When a measurement at the antenna connector is used to determine RF output power, the effective gain of the device's antenna shall be stated, based on a measurement or on data from the antenna manufacturer.


15.247(b) (4) requirement:

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

EUT Antenna:

The antenna is integrated on the main PCB and no consideration of replacement. The best case gain of the antenna is 5dBi.

Please refer to internal photos.



7 Radio Spectrum Matter Test Results

7.1 Conducted Peak Output Power

Test Requirement 47 CFR Part 15, Subpart C 15.247(b)(3)

Test Method: ANSI C63.10 (2013) Section 11.9.1.3

Limit:

Frequency range(MHz)	Output power of the intentional radiator(watt)
902-928	1 for ≥ 50 hopping channels
	0.25 for $25 \leq$ hopping channels < 50
	1 for digital modulation
2400-2483.5	1 for ≥ 75 non-overlapping hopping channels
	0.125 for all other frequency hopping systems
	1 for digital modulation
5725-5850	1 for frequency hopping systems and digital modulation

7.1.1 E.U.T. Operation


Operating Environment:

Temperature: 24.1 °C Humidity: 51.2 % RH Atmospheric Pressure: 1010 mbar

7.1.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	00	TX mode_Keep the EUT in continuously transmitting mode with GFSK modulation.

7.1.3 Test Setup Diagram



7.1.4 Measurement Procedure and Data

cable loss=0.9dB

Please Refer to Appendix for Details



7.2 Minimum 6dB Bandwidth

Test Requirement 47 CFR Part 15, Subpart C 15.247a(2)
 Test Method: ANSI C63.10 (2013) Section 11.8.1
 Limit: ≥ 500 kHz


7.2.1 E.U.T. Operation

Operating Environment:
 Temperature: 24.1 °C Humidity: 51.2 % RH Atmospheric Pressure: 1010 mbar

7.2.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	00	TX mode_Keep the EUT in continuously transmitting mode with GFSK modulation.

7.2.3 Test Setup Diagram



7.2.4 Measurement Procedure and Data

cable loss=0.83dB

Please Refer to Appendix for Details



7.3 Power Spectrum Density

Test Requirement 47 CFR Part 15, Subpart C 15.247(e)

Test Method: ANSI C63.10 (2013) Section 11.10.2

Limit:

≤8dBm in any 3 kHz band during any time interval of continuous transmission

7.3.1 E.U.T. Operation


Operating Environment:

Temperature: 24.1 °C Humidity: 51.2 % RH Atmospheric Pressure: 1010 mbar

7.3.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	00	TX mode_Keep the EUT in continuously transmitting mode with GFSK modulation.

7.3.3 Test Setup Diagram



7.3.4 Measurement Procedure and Data

cable loss=0.83dB

Please Refer to Appendix for Details



7.4 Conducted Band Edges Measurement

Test Requirement 47 CFR Part 15, Subpart C 15.247(d)

Test Method: ANSI C63.10 (2013) Section 11.13.3.2

Limit:

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

7.4.1 E.U.T. Operation

Operating Environment:

Temperature: 20.3 °C


Humidity: 50.6 % RH

Atmospheric Pressure: 1010 mbar

7.4.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	00	TX mode_Keep the EUT in continuously transmitting mode with GFSK modulation.

7.4.3 Test Setup Diagram



7.4.4 Measurement Procedure and Data

cable loss=0.83dB

Please Refer to Appendix for Details



7.5 Conducted Spurious Emissions

Test Requirement 47 CFR Part 15, Subpart C 15.247(d)

Test Method: ANSI C63.10 (2013) Section 11.11

Limit:

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

7.5.1 E.U.T. Operation

Operating Environment:

Temperature: 24.1 °C


Humidity: 51.2 % RH

Atmospheric Pressure: 1010 mbar

7.5.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	00	TX mode_Keep the EUT in continuously transmitting mode with GFSK modulation.

7.5.3 Test Setup Diagram



7.5.4 Measurement Procedure and Data

cable loss=0.83dB

Please Refer to Appendix for Details



7.6 Radiated Emissions which fall in the restricted bands

Test Requirement 47 CFR Part 15, Subpart C 15.205 & 15.209

Test Method: ANSI C63.10 (2013) Section 6.10.5

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

7.6.1 E.U.T. Operation

Operating Environment:

Temperature: 20.3 °C


Humidity: 50.6 % RH

Atmospheric Pressure: 1010 mbar


7.6.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	00	TX mode_Keep the EUT in continuously transmitting mode with GFSK modulation.

7.6.3 Test Setup Diagram



30MHz-1GHz



Above 1GHz



7.6.4 Measurement Procedure and Data

- a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- d. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- g. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- h. Test the EUT in the lowest channel, the Highest channel.
- i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- j. Repeat above procedures until all frequencies measured was complete.

Remark 1: $\text{Level} = \text{Read Level} + \text{Cable Loss} + \text{Antenna Factor} - \text{Preamp Factor}$

Remark 2: For frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.



Note: Level = Reading level + Factor

All mode had been tested, only the worst 1M mode is in the report.

Test Mode: 01; Polarity: Horizontal; Modulation: GFSK; Channel: Low

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	2310.000	68.47	-30.59	37.88	74.00	-36.12	peak	P
2	2390.000	69.90	-30.49	39.41	74.00	-34.59	peak	P
3	2400.000	77.51	-30.48	47.03	74.00	-26.97	peak	P

Test Mode: 01; Polarity: Vertical; Modulation: GFSK; Channel: Low

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	2310.000	67.66	-30.59	37.07	74.00	-36.93	peak	P
2	2390.000	70.84	-30.49	40.35	74.00	-33.65	peak	P
3	2400.000	78.90	-30.48	48.42	74.00	-25.58	peak	P

Test Mode: 01; Polarity: Horizontal; Modulation: GFSK; Channel: High

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	2483.500	79.14	-30.39	48.75	74.00	-25.25	peak	P
2	2500.000	71.92	-30.37	41.55	74.00	-32.45	peak	P

Test Mode: 01; Polarity: Vertical; Modulation: GFSK; Channel: High

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	2483.500	79.04	-30.39	48.65	74.00	-25.35	peak	P
2	2500.000	71.44	-30.37	41.07	74.00	-32.93	peak	P



7.7 Radiated Spurious Emissions (Below 1GHz)

Test Requirement 47 CFR Part 15, Subpart C 15.205 & 15.209

Test Method: ANSI C63.10 (2013) Section 6.4,6.5,6.6

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

7.7.1 E.U.T. Operation

Operating Environment:

Temperature: 20.3 °C



Humidity: 50.6 % RH

Atmospheric Pressure: 1010 mbar

7.7.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	00	TX mode_Keep the EUT in continuously transmitting mode with GFSK modulation.

7.7.3 Test Setup Diagram



7.7.4 Measurement Procedure and Data

- a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- g. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- i. Repeat above procedures until all frequencies measured was complete.

Remark:


- 1) Through pre-scan found the worst case is the lowest channel. Only the worst case is recorded in the report.
- 2) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:
Final Test Level = Reading Level + Factor
- 3) Scan from 9kHz to 1 GHz, the disturbance below 30MHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.



For ANT 1

All mode had been tested, only the worst 1M mode is in the report.


Test Mode: 00; Polarity: Horizontal; Modulation: GFSK; Channel: High



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	43.5057	42.37	-17.72	24.65	40.00	-15.35	QP	200	0	P	
2	59.6493	42.24	-18.09	24.15	40.00	-15.85	QP	200	0	P	
3	133.1511	42.37	-17.94	24.43	43.50	-19.07	QP	200	0	P	
4	153.7385	42.57	-17.02	25.55	43.50	-17.95	QP	200	0	P	
5	295.1469	42.55	-17.93	24.62	46.00	-21.38	QP	200	0	P	
6 *	721.7259	44.05	-9.13	34.92	46.00	-11.08	QP	200	0	P	



Test Mode: 00; Polarity: Vertical; Modulation: GFSK; Channel: High



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	42.0066	41.77	-17.18	24.59	40.00	-15.41	QP	100	360	P	
2	56.3948	41.78	-17.98	23.80	40.00	-16.20	QP	100	360	P	
3	128.1130	42.99	-18.26	24.73	43.50	-18.77	QP	100	360	P	
4	155.9101	43.06	-17.15	25.91	43.50	-17.59	QP	100	360	P	
5	397.6334	43.27	-15.44	27.83	46.00	-18.17	QP	100	360	P	
6 *	694.4174	45.13	-9.89	35.24	46.00	-10.76	QP	100	360	P	

Note:

- 1) Pre-scan all modes and recorded the worst case results in this report (High Channel).
- 2) Emission level (dBuV/m) = 20 log Emission level (uV/m).
- 3) Level= Reading+ Factor, Margin= Level- Limit, Factor= Antenna Factor Cable Loss-Preamp Factor



7.8 Radiated Spurious Emissions (Above 1GHz)

Test Requirement 47 CFR Part 15, Subpart C 15.205 & 15.209

Test Method: ANSI C63.10 (2013) Section 6.4,6.5,6.6

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

7.8.1 E.U.T. Operation

Operating Environment:

Temperature: 20.3 °C

Humidity: 50.6 % RH


Atmospheric Pressure: 1010 mbar

7.8.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	00	TX mode_Keep the EUT in continuously transmitting mode with GFSK modulation.



7.8.3 Test Setup Diagram



7.8.4 Measurement Procedure and Data

- a. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- g. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- i. Repeat above procedures until all frequencies measured was complete.

Remark:

1) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Final Test Level = Level = Reading Level + Factor

2) Scan from 1GHz to 25GHz, the disturbance above 18GHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.

3) The field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.



TM00 / Polarization: Horizontal / Modulation: 1M/ CH: L

No.	Frequency (MHz)	Reading (dBuv)	Factor (dB/m)	Level (dBuv/m)	Limit (dBuv/m)	Margin(dB)	Detector	P/F
1	2915.412	69.46	-29.94	39.52	74.00	-34.48	peak	P
2	4277.557	68.49	-28.45	40.04	74.00	-33.96	peak	P
3	6084.767	64.57	-24.48	40.09	74.00	-33.91	peak	P
4	8646.226	70.26	-25.40	44.86	74.00	-29.14	peak	P
5	11046.493	68.27	-23.40	44.87	74.00	-29.13	peak	P
6	14218.292	70.02	-21.28	48.75	74.00	-25.25	peak	P

TM00 / Polarization: Horizontal / Modulation: 1M/ CH: L

No.	Frequency (MHz)	Reading (dBuv)	Factor (dB/m)	Level (dBuv/m)	Limit (dBuv/m)	Margin(dB)	Detector	P/F
1	2974.238	67.53	-28.94	38.59	74.00	-35.41	peak	P
2	4313.150	69.23	-28.04	41.19	74.00	-32.81	peak	P
3	6352.451	67.97	-25.74	42.23	74.00	-31.77	peak	P
4	8575.886	69.09	-24.77	44.31	74.00	-29.69	peak	P
5	11285.601	67.67	-22.35	45.31	74.00	-28.69	peak	P
6	14955.548	70.55	-21.04	49.51	74.00	-24.49	peak	P

TM00 / Polarization: Horizontal / Modulation: 1M/ CH: M

No.	Frequency (MHz)	Reading (dBuv)	Factor (dB/m)	Level (dBuv/m)	Limit (dBuv/m)	Margin(dB)	Detector	P/F
1	2915.037	69.69	-29.69	40.00	74.00	-34.00	peak	P
2	4277.033	68.32	-29.60	38.71	74.00	-35.29	peak	P
3	6086.028	65.03	-26.10	38.92	74.00	-35.08	peak	P
4	8646.793	69.45	-25.62	43.84	74.00	-30.16	peak	P
5	11046.707	67.45	-23.94	43.51	74.00	-30.49	peak	P
6	14218.488	71.09	-21.45	49.63	74.00	-24.37	peak	P

TM00 / Polarization: Horizontal / Modulation: 1M/ CH: M

No.	Frequency (MHz)	Reading (dBuv)	Factor (dB/m)	Level (dBuv/m)	Limit (dBuv/m)	Margin(dB)	Detector	P/F
1	2973.815	66.14	-29.01	37.12	74.00	-36.88	peak	P
2	4313.947	68.12	-29.04	39.08	74.00	-34.92	peak	P
3	6353.145	67.13	-25.81	41.32	74.00	-32.68	peak	P
4	8576.821	69.59	-25.51	44.08	74.00	-29.92	peak	P
5	11285.313	68.79	-24.14	44.65	74.00	-29.35	peak	P
6	14955.955	71.39	-20.11	51.27	74.00	-22.73	peak	P



TM00 / Polarization: Horizontal / Modulation: 1M/ CH: H

No.	Frequency (MHz)	Reading (dBuv)	Factor (dB/m)	Level (dBuv/m)	Limit (dBuv/m)	Margin(dB)	Detector	P/F
1	2915.229	69.27	-30.50	38.77	74.00	-35.23	peak	P
2	4276.341	68.20	-28.27	39.93	74.00	-34.07	peak	P
3	6085.392	65.00	-24.52	40.48	74.00	-33.52	peak	P
4	8646.550	70.50	-24.55	45.95	74.00	-28.05	peak	P
5	11048.316	68.80	-22.72	46.08	74.00	-27.92	peak	P
6	14217.528	70.20	-21.99	48.22	74.00	-25.78	peak	P

TM00 / Polarization: Horizontal / Modulation: 1M/ CH: H

No.	Frequency (MHz)	Reading (dBuv)	Factor (dB/m)	Level (dBuv/m)	Limit (dBuv/m)	Margin(dB)	Detector	P/F
1	2974.260	66.30	-28.95	37.34	74.00	-36.66	peak	P
2	4313.033	68.40	-28.96	39.44	74.00	-34.56	peak	P
3	6353.861	66.51	-25.90	40.60	74.00	-33.40	peak	P
4	8576.955	69.45	-25.18	44.27	74.00	-29.73	peak	P
5	11286.163	68.72	-24.01	44.71	74.00	-29.29	peak	P
6	14956.031	70.17	-20.87	49.30	74.00	-24.70	peak	P

Notes:

1).Measuring frequencies from 9 KHz~10th harmonic(ex.26GHz),at least have 20dB margin found between lowest internal used/generated frequency to 30 MHz.

2).Radiated emissions measured in frequency range from 9 KHz~10th harmonic (ex.26GHz)were made with an instrument using Peak detector mode.

3).18-25GHz at least have 20dB margin.No recording in the test report.

4) Level=Reading +Factor

Factor= Antenna Factor+ Cable Loss-Preamp Factor



8 Test Setup Photo

Refer to Appendix – Test Setup Photos.

9 EUT Constructional Details (EUT Photos)

Refer to Appendix EUT Photos






10 Appendix

Cable loss=0.83 dB

1. -6dB Bandwidth

Condition	Antenna	Rate	Frequency (MHz)	-6dB BW(kHz)	limit(kHz)	Result
NVNT	ANT1	1Mbps	2402	677.70	500	Pass
NVNT	ANT1	1Mbps	2440.00	679.47	500	Pass
NVNT	ANT1	1Mbps	2480	697.11	500	Pass






2. 99% Occupied Bandwidth


Condition	Antenna	Rate	Frequency (MHz)	99% BW(MHz)
NVNT	ANT1	1Mbps	2402	1.039
NVNT	ANT1	1Mbps	2440.00	1.038
NVNT	ANT1	1Mbps	2480	1.036

99%_Occupied_Bandwidth_NVNT_ANT1_1Mbps_2402





99%_Occupied_Bandwidth_NVNT_ANT1_1Mbps_2440






3. Duty Cycle


Condition	Antenna	Rate	Frequency (MHz)	Dutycycle(%)	Duty_factor
NVNT	ANT1	1Mbps	2402	64.52	1.90
NVNT	ANT1	1Mbps	2440.00	64.52	1.90
NVNT	ANT1	1Mbps	2480	61.29	2.13






4. Peak Output Power

Condition	Antenna	Rate	Frequency (MHz)	Max. Conducted Power(dBm)	Max. Conducted Power(mW)	Limit(mW)	Result
NVNT	ANT1	1Mbps	2402	-0.71	0.85	1000	Pass
NVNT	ANT1	1Mbps	2440.00	-1.61	0.69	1000	Pass
NVNT	ANT1	1Mbps	2480	-3.35	0.46	1000	Pass



Peak_Output_Power_NVNT_ANT1_1Mbps_2440





Peak_Output_Power_NVNT_ANT1_1Mbps_2480



5. Power Spectral Density

Condition	Antenna	Rate	Frequency (MHz)	Power Spectral Density(dBm)	Limit(dBm/3kHz)	Result
NVNT	ANT1	1Mbps	2402	-15.55	8	Pass
NVNT	ANT1	1Mbps	2440.00	-16.49	8	Pass
NVNT	ANT1	1Mbps	2480	-18.27	8	Pass






6. Bandedge

Condition	Antenna	Rate	TX_Frequency (MHz)	Max. Mark Frequency (MHz)	Spurious level(dBm)	limit(dBm)	Result
NVNT	ANT1	1Mbps	2402	2399.775	-59.179	-21.377	Pass
NVNT	ANT1	1Mbps	2480	2483.775	-69.205	-24.087	Pass

1_Reference_Level_NVNT_ANT1_1Mbps_2402




2_Bandedge_NVNT_ANT1_1Mbps_2402



1_Reference_Level_NVNT_ANT1_1Mbps_2480




2_Bandedge_NVNT_ANT1_1Mbps_2480




7. Spurious Emission

Condition	Antenna	Rate	TX_Frequency(MHz)	Spurious MAX.Value(dBm)	Limit	Result
NVNT	ANT1	1Mbps	2402	-57.424	-21.377	Pass
NVNT	ANT1	1Mbps	2440.00	-54.935	-22.252	Pass
NVNT	ANT1	1Mbps	2480	-59.159	-24.087	Pass

1_Reference_Level_NVNT_ANT1_1Mbps_2402




2_Spurious_Emission_NVNT_ANT1_1Mbps_2402




1_Reference_Level_NVNT_ANT1_1Mbps_2440




2_Spurious_Emission_NVNT_ANT1_1Mbps_2440



1_Reference_Level_NVNT_ANT1_1Mbps_2480



2_Spurious_Emission_NVNT_ANT1_1Mbps_2480



- End of the Report -

