

Applicant: Eastern Times Technology Co.,Ltd

Product: LIGHT-WEIGHT 3 MODES CONNECTION RGB GAMING

**MOUSE** 

Model No.: M816-PRO, DS-4028

Trademark: REDRGAON

Test Standards: FCC Part 15.249

Test result:

It is herewith confirmed and found to comply with the

requirements set up by ANSI C63.10 &FCC Part 15 Subpart C, Paragraph 15.249 regulations for the evaluation of

electromagnetic compatibility

Approved By

Terry long

Terry Tang

Manager


Dated: December 10, 2024

Results appearing herein relate only to the sample tested The technical reports is issued errors and omissions exempt and is subject to withdrawal at

# SHENZHEN TIMEWAY TESTING LABORATORIES

Zone C, 1st Floor, Block B, Jun Xiang Da Building, Zhongshan Park Road West, Tong Le Village, Nanshan District, Shenzhen, China

Tel (755) 83448688, Fax (755) 83442996, E-Mail:info@timeway-lab.com



Report No.: TW2411230-02E Page 2 of 34

Date: 2024-12-10



# **Special Statement:**

# FCC-Registration No.: 744189

The EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications commission. The acceptance letter from the FCC is maintained in our files. Registration No.: 744189.

# Industry Canada (IC) — Registration No.:5205A

The EMC Laboratory has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 5205A.

## **A2LA** (Certification Number:5013.01)

The EMC Laboratory has been accredited by the American Association for Laboratory Accreditation (A2LA). Certification Number:5013.01

CAB identifier: CN0033

Date: 2024-12-10



# **Test Report Conclusion**

#### Content 1.0 General Details 1.1 Test Lab Details.... Applicant Details..... 1.2 4 1.3 Description of EUT .... 4 1.4 Submitted Sample.... 4 Test Duration. 1.5 5 5 1.6 Test Uncertainty. 1.7 Test By..... 5 2.0 List of Measurement Equipment..... 6 7 3.0 Technical Details..... 3.1 Summary of Test Results.... 7 3.2 7 Test Standards.... 4.0 EUT Modification.... 7 Power Line Conducted Emission Test.... 5.0 8 Schematics of the Test..... 5.1 8 5.2 Test Method and Test Procedure. 8 Configuration of the EUT..... 5.3 8 5.4 EUT Operating Condition. 9 Conducted Emission Limit. 9 5.5 5.6 Test Result.... 6.0 Radiated Emission test.... 12 Test Method and Test Procedure. 6.1 12 6.2 Configuration of the EUT.... 13 6.3 EUT Operation Condition. 13 Radiated Emission Limit. 14 6.4 Test Result.... 6.5 15 7.0 Band Edge.... 23 7.1 Test Method and Test Procedure. 23 7.2 Radiated Test Setup. 23 7.3 Configuration of the EUT.... 23 7.4 EUT Operating Condition. 23 7.5 Band Edge Limit..... 23 7.6 Band Edge Test Result. 24 8.0 Antenna Requirement..... 28 20dB bandwidth measurement.... 9.0 29 FCC ID Label.... 10.0 38

The report refers only to the sample tested and does not apply to the bulk.

11.0

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

Photo of Test Setup and EUT View....

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES, reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.

Date: 2024-12-10



#### 1.0 General Details

#### 1.1 Test Lab Details

Name: SHENZHEN TIMEWAY TESTING LABORATORIES.

Address: Zone C, 1st Floor, Block B, Jun Xiang Da Building, Zhongshan Park Road West, Tong Le

Village, Nanshan District, Shenzhen, China

Telephone: (755) 83448688 Fax: (755) 83442996

Site on File with the Federal Communications Commission – United Sates

Registration Number: 744189 For 3m Anechoic Chamber

#### 1.2 Applicant Details

Applicant: Eastern Times Technology Co.,Ltd

Address: Building D, Nan An Industrial Area, Youganpu Village, Fenggang Town, Dongguan City,

Guangdong, China.

#### 1.3 Description of EUT

Product: LIGHT-WEIGHT 3 MODES CONNECTION RGB GAMING MOUSE

Manufacturer: Eastern Times Technology Co.,Ltd

Address: Building D, Nan An Industrial Area, Youganpu Village, Fenggang Town,

Dongguan City, Guangdong, China.

Trademark: REDRGAON

Additional Trademark: N/A

Model Number: M816-PRO Additional Model Name DS-4028

Hardware Version: 4028-B TX V1

Software Version: a3935981

Serial No.: RDM816-PRO24102501199
Rating: DC5V, 300mA or DC3.7V, 30mA
Battery: DC3.7V, 700mAh Li-ion battery

Modulation Type: GFSK

Operation Frequency: 2402-2480MHz (Bluetooth Low Energy)

Number of Channels: 40 Channel Separation: 2MHz

Antenna Designation PCB antenna with gain -2.89dBi Max (Get from the antenna specification)

#### 1.4 Submitted Sample: 2 Samples

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.

Report No.: TW2411230-02E Page 5 of 34

Date: 2024-12-10



#### 1.5 Test Duration

2024-11-23 to 2024-12-10

#### 1.6 Test Uncertainty

Conducted Emissions Uncertainty = 3.6dB

Radiated Emissions below 1GHz Uncertainty =4.7dB

Radiated Emissions above 1GHz Uncertainty =6.0dB

Conducted Power Uncertainty =6.0dB

Occupied Channel Bandwidth Uncertainty = 5%

Conducted Emissions Uncertainty = 3.6dB

Note: The measurement uncertainty is for coverage factor of k=2 and a level of confidence of 95%.

1.7 Test Engineer

The sample tested by

Print Name: Terry Tang

Page 6 of 34

Report No.: TW2411230-02E

Date: 2024-12-10



2.0 Test Equipment					
Instrument Type	Manufacturer	Model	Serial No.	Date of Cal.	Due Date
ESPI Test Receiver	R&S	ESPI 3	100379	2024-07-12	2025-07-11
LISN	R&S	EZH3-Z5	100294	2024-07-12	2025-07-11
LISN	R&S	EZH3-Z5	100253	2024-07-12	2025-07-11
Impuls-Begrenzer	R&S	ESH3-Z2	100281	2024-07-12	2025-07-11
Loop Antenna	EMCO	6507	00078608	2022-07-18	2025-07-17
Spectrum	R&S	FSIQ26	100292	2024-07-12	2025-07-11
Horn Antenna	A-INFO	LB-180400-KF	J211060660	2022-07-18	2025-07-17
Horn Antenna	R&S	BBHA 9120D	9120D-631	2022-07-18	2025-07-17
Power meter	Anritsu	ML2487A	6K00003613	2024-07-12	2025-07-11
Power sensor	Anritsu	MA2491A	32263	2024-07-12	2025-07-11
Bilog Antenna	Schwarebeck	VULB9163	9163/340	2022-07-18	2025-07-17
9*6*6 Anechoic			N/A	2022-07-26	2025-07-25
EMI Test Receiver	RS	ESVB	826156/011	2024-07-12	2025-07-11
EMI Test Receiver	RS	ESCS 30	834115/006	2024-07-12	2025-07-11
Spectrum	HP/Agilent	E4407B	MY50441392	2024-07-12	2025-07-11
Spectrum	RS	FSP	1164.4391.38	2024-07-12	2025-07-11
RF Cable	Zhengdi	ZT26-NJ-NJ-8M/FA		2024-07-12	2025-07-11
RF Cable	Zhengdi	7m		2024-07-12	2025-07-11
Pre-Amplifier	Schwarebeck	BBV9743	#218	2024-07-12	2025-07-11
Pre-Amplifier	HP/Agilent	8449B	3008A00160	2024-07-12	2025-07-11
LISN	SCHAFFNER	NNB42	00012	2024-07-12	2025-07-11
ESPI Test Receiver	R&S	ESPI 3	100379	2024-07-12	2025-07-11
LISN	R&S	EZH3-Z5	100294	2024-07-12	2025-07-11

## 2.2 Automation Test Software

#### For Conducted Emission Test

Name	Version		
EZ-EMC	Ver.EMC-CON 3A1.1		

#### For Radiated Emissions

Name	Version
EMI Test Software BL410-EV18.91	V18.905
EMI Test Software BL410-EV18.806 High Frequency	V18.06

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.

Page 7 of 34

Report No.: TW2411230-02E

Date: 2024-12-10



#### 3.0 Technical Details

## 3.1 Summary of test results

The EUT has been tested according to the following specifications:

Standard	Test Type	Result	Notes
FCC Part 15, Paragraph 15.203	Antenna Requirement	Pass	Complies
FCC Part 15, Paragraph 15.207	Conducted Emission Test	Pass	Complies
FCC Part 15 Subpart C Paragraph 15.249(a) & 15.249(b) Limit	Field Strength of Fundamental	Pass	Complies
FCC Part 15, Paragraph 15.209	Radiated Emission Test	Pass	Complies
FCC Part 15 Subpart C Paragraph 15.249(d) Limit	Band Edge Test	Pass	Complies

#### 3.2 Test Standards

FCC Part 15 Subpart C, Paragraph 15.249, ANSI C63.4:2014 and ANSI C63.10:2013

#### 4.0 EUT Modification


No modification by SHENZHEN TIMEWAY TESTING LABORATORIES

Date: 2024-12-10



#### 5. Power Line Conducted Emission Test

#### 5.1 Schematics of the test




**EUT:** Equipment Under Test

## 5.2 Test Method and test Procedure

The EUT was tested according to ANSI C63.10-2013. The Frequency spectrum from 0.15MHz to 30MHz was investigated. The LISN used was 50ohm/50uH as specified by section 5.1 of ANSI C63.10 –2013.

Test Voltage: 120V~, 60Hz Block diagram of Test setup



# 5.3 Configuration of the EUT

The EUT was configured according to ANSI C63.10-2013. All interface ports were connected to the appropriate peripherals. All peripherals and cables are listed below.

79 channels are provided to the EUT

#### A. EUT

Device	Manufacturer	Model	FCC ID
LIGHT-WEIGHT 3 MODES	Fastam Times		
CONNECTION RGB	Eastern Times	M816-PRO, DS-4028	TUVDS-4028B
GAMING MOUSE	Technology Co.,Ltd		

#### B. Internal Device

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.

Page 9 of 34

Report No.: TW2411230-02E

Date: 2024-12-10



Device	Manufacturer	Model	FCC ID/DOC
N/A			

# C. Peripherals

Device	Manufacturer	Model	Rating
Power Supply	KEYU	KA23-0502000DEU	Input: 100-240V~, 50/60Hz, 0.35A;
			Output: DC5V, 2A

# 5.4 EUT Operating Condition

Operating condition is according to ANSI C63.10-2013

- A Setup the EUT and simulators as shown on follow
- B Enable AF signal and confirm EUT active to normal condition

## 5.5 Power line conducted Emission Limit according to Paragraph 15.207

Frequency	Limits (dB µ V)			
(MHz)	Quasi-peak Level	Average Level		
$0.15 \sim 0.50$	66.0~56.0*	56.0~46.0*		
$0.50 \sim 5.00$	56.0	46.0		
5.00 ~ 30.00	60.0	50.0		

Notes:

- 1. \*Decreasing linearly with logarithm of frequency.
- 2. The tighter limit shall apply at the transition frequencies

#### 5.6 Test Results:

Pass

Date: 2024-12-10



## A: Conducted Emission on Live Terminal (150kHz to 30MHz)


## **EUT Operating Environment**

Temperature: 25°C Humidity: 65%RH Atmospheric Pressure: 101 kPa

**EUT set Condition: Charging and Communication by BT** 

**Results: Pass** 

Please refer to following diagram for individual



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F
1	0.1617	40.77	10.34	51.11	65.38	-14.27	QP	Р
2	0.1617	25.80	10.34	36.14	55.38	-19.24	AVG	Р
3	0.2046	35.82	10.32	46.14	63.42	-17.28	QP	Р
4	0.2046	24.00	10.32	34.32	53.42	-19.10	AVG	Р
5	0.4425	24.85	10.38	35.23	57.01	-21.78	QP	Р
6	0.4425	13.22	10.38	23.60	47.01	-23.41	AVG	Р
7	4.4547	18.89	12.15	31.04	56.00	-24.96	QP	Р
8	4.4547	9.37	12.15	21.52	46.00	-24.48	AVG	Р
9	17.0127	20.21	15.66	35.87	60.00	-24.13	QP	Р
10	17.0127	15.11	15.66	30.77	50.00	-19.23	AVG	Р

Date: 2024-12-10



# B: Conducted Emission on Neutral Terminal (150kHz to 30MHz)


## **EUT Operating Environment**

Temperature: 25°C Humidity: 65%RH Atmospheric Pressure: 101 kPa

EUT set Condition: Charging and Communication by BT

**Results: Pass** 

Please refer to following diagram for individual



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F
1	0.1890	33.07	10.32	43.39	64.08	-20.69	QP	Р
2	0.1890	15.65	10.32	25.97	54.08	-28.11	AVG	Р
3	0.3489	19.74	10.36	30.10	58.99	-28.89	QP	Р
4	0.3489	5.05	10.36	15.41	48.99	-33.58	AVG	Р
5	2.1078	17.56	11.36	28.92	56.00	-27.08	QP	Р
6	2.1078	9.93	11.36	21.29	46.00	-24.71	AVG	Р
7	4.4586	19.33	12.15	31.48	56.00	-24.52	QP	Р
8	4.4586	9.48	12.15	21.63	46.00	-24.37	AVG	Р
9	17.4495	17.82	15.77	33.59	60.00	-26.41	QP	Р
10	17.4495	12.71	15.77	28.48	50.00	-21.52	AVG	Р

Report No.: TW2411230-02E Page 12 of 34

Date: 2024-12-10




#### **6** Radiated Emission Test

- 6.1 Test Method and test Procedure:
- (1) The EUT was tested according to ANSI C63.10-2013. The radiated test was performed at Timeway EMC Laboratory. This site is on file with the FCC laboratory division, Registration No. 744189
- (2) The EUT, peripherals were put on the turntable which table size is 1m x 1.5 m, table high 0.8 m. All set up is according to ANSI C63.10-2013.
- (3) The frequency spectrum from 30 MHz to 25 GHz was investigated. All readings from 30 MHz to 1 GHz are quasi-peak values with a resolution bandwidth of 120 kHz. All readings are above 1 GHz, peak values with a resolution bandwidth of 1 MHz (Note: for Fundamental frequency radiated emission measurement, RBW=3MHz, VBW=10MHz). Measurements were made at 3 meters.
- (4) The antenna high is varied from 1 m to 4 m high to find the maximum emission for each frequency.
- (5) The antenna polarization: Vertical polarization and Horizontal polarization.

#### **Block diagram of Test setup**

For radiated emissions from 9kHz to 30MHz




Page 13 of 34

Report No.: TW2411230-02E


Date: 2024-12-10



For radiated emissions from 30MHz to1GHz



For radiated emissions above 1GHz



- 6.2 Configuration of The EUT

  Same as section 5.3 of this report
- 6.3 EUT Operating Condition

  Same as section 5.4 of this report.

Report No.: TW2411230-02E Page 14 of 34

Date: 2024-12-10



#### 6.4 Radiated Emission Limit

All emission from a digital device, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strength specified below:

#### A FCC Part 15 Subpart C Paragraph 15.249(a) Limit

Fundamental Frequency	Field Strength of Fundamental (3m)			Field S	trength of Harmo	nics (3m)
(MHz)	mV/m	dBuV/m		uV/m	dBu	V/m
2400-2483.5	50	94 (Average)	114 (Peak)	500	54 (Average)	74 (Peak)

Note: 1. RF Field Strength (dBuV) = 20 log RF Voltage (uV)

- 2.Distance refers to the distance in meters between the measuring instrument antenna and the closed point of any part of the device or system.
- 3. The emission limit in this paragraph is based on measurement instrumentation employing an average detector.

#### B. Frequencies in restricted band are complied to limit on Paragraph 15.209.

Frequency Range (MHz)	Distance (m)	Field strength (dB $\mu$ V/m)
0.009-0.490	3	20log(2400/F(kHz)) +40log (300/3)
0.490-1.70	3	20log(24000/F(kHz)) +40log (30/3)
1.705-30	3	69.5
30-88	3	40.0
88-216	3	43.5
216-960	3	46.0
Above 960	3	54.0

Note:

- 1. RF Voltage  $(dBuV) = 20 \log RF \text{ Voltage } (uV)$
- 2. In the Above Table, the tighter limit applies at the band edges.
- 3. Distance refers to the distance in meters between the measuring instrument antenna and the EUT
- 4. All scanning using PK detector. And the final emission level was get using QP detector for frequency range from 30-1000MHz.As to 1G-25G, the final emission level got using PK. For fundamental measurement, PK detector used.
- 5. For radiated emissions from 9kHz to 30MHz, the emission level is much less than the limit for more than 20dB. No necessary to take down the record.
- 6. Battery full charged during tests.

Report No.: TW2411230-02E Page 15 of 34

Date: 2024-12-10




#### 6.5 Test result

# A Fundamental & Harmonics Radiated Emission Data

Please refer to the following test plots for details: Low Channel-2402MHz

#### Horizontal




No.	Frequency	Results	Factor	Limit	Over Limit	Detector	Table	Height	ANT	Verdict
	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dB)		(o)	(cm)		
1	2402	91.71	-3.57	114.0	17.71	Peak	38.00	100	Horizontal	Pass

Report No.: TW2411230-02E Page 16 of 34

Date: 2024-12-10



#### Vertical



No.	Frequency	Results	Factor	Limit	Over Limit	Detector	Table	Height	ANT	Verdict
	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dB)		(o)	(cm)		
1	2402	83.17	-3.57	114.0	9.17	Peak	126.00	100	Vertical	Pass


Report No.: TW2411230-02E Page 17 of 34

Date: 2024-12-10



Please refer to the following test plots for details: Middle Channel-2440MHz

#### **Horizontal**




Ī	No.	Frequency	Results	Factor	Limit	Over Limit	Detector	Table	Height	ANT	Verdict
		(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dB)		(o)	(cm)		
	1	2440	91.57	-3.57	114.0	17.57	Peak	31.00	100	Horizontal	Pass

Report No.: TW2411230-02E Page 18 of 34

Date: 2024-12-10



#### Vertical



No.	Frequency	Results	Factor	Limit	Over Limit	Detector	Table	Height	ANT	Verdict
	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dB)		(o)	(cm)		
1	2440	81.41	-3.57	114.0	7.41	Peak	281.00	100	Vertical	Pass


Report No.: TW2411230-02E Page 19 of 34

Date: 2024-12-10



Please refer to the following test plots for details: High Channel-2480MHz

#### **Horizontal**



No.	Frequency	Results	Factor	Limit	Over Limit	Detector	Table	Height	ANT	Verdict
	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dB)		(o)	(cm)		
1	2480	91.65	-3.57	114.0	17.65	Peak	338.00	100	Horizontal	Pass


Page 20 of 34

Report No.: TW2411230-02E

Date: 2024-12-10



#### Vertical



No.	Frequency	Results	Factor	Limit	Over Limit	Detector	Table	Height	ANT	Verdict
	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dB)		(o)	(cm)		
1	2480	81.32	-3.57	114.0	7.32	Peak	175.00	100	Vertical	Pass

Frequency (MHz)

Note: (2) Emission Level = Reading Level + Antenna Factor + Cable Loss-Amplifier

- (3) Margin=Emission-Limits
- (4) According to section 15.35(b), the peak limit is 20dB higher than the average limit
- (5) For test purpose, keep EUT continuous transmitting
- (5) For emission above 18GHz and Below 30MHz, It is only the floor noise. No necessary to take down.
- (6) the measured PK value less than the AV limit.

Report No.: TW2411230-02E Page 21 of 34

Date: 2024-12-10




# B. General Radiated Emission Data Radiated Emission In Horizontal (30MHz----1000MHz)

EUT set Condition: Keep Tx transmitting

**Results:** Pass

Please refer to following diagram for individual



No.	Frequency	Results	Factor	Limit	Margin	Detector	Table	Height	Antenna	Verdict
	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dB)		(Degree)	(cm)		
1	41.395	28.00	-6.03	40.0	12.00	Peak	224.00	100	Horizontal	Pass
2	104.914	26.61	-6.23	43.5	16.89	Peak	106.00	100	Horizontal	Pass
3	179.585	36.04	-8.10	43.5	7.46	Peak	259.00	100	Horizontal	Pass
4	354.869	32.71	-2.19	46.0	13.29	Peak	338.00	100	Horizontal	Pass
5	701.072	36.77	2.55	46.0	9.23	Peak	318.00	100	Horizontal	Pass
6	914.904	38.13	5.41	46.0	7.87	Peak	119.00	100	Horizontal	Pass

Report No.: TW2411230-02E Page 22 of 34

Date: 2024-12-10




# Radiated Emission In Vertical (30MHz----1000MHz)

EUT set Condition: Keep Tx transmitting

**Results:** Pass

Please refer to following diagram for individual



No.	Frequency	Results	Factor	Limit	Margin	Detector	Table	Height	Antenna	Verdict
	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dB)		(Degree)	(cm)		
1	41.880	28.90	-5.47	40.0	11.10	Peak	225.00	100	Vertical	Pass
2	113.642	27.99	-6.49	43.5	15.51	Peak	221.00	100	Vertical	Pass
3	182.252	35.24	-7.51	43.5	8.26	Peak	259.00	100	Vertical	Pass
4	405.054	33.29	-1.48	46.0	12.71	Peak	259.00	100	Vertical	Pass
5	640.220	35.96	1.46	46.0	10.04	Peak	273.00	100	Vertical	Pass
6	961.210	39.02	5.23	54.0	14.98	Peak	360.00	100	Vertical	Pass

Date: 2024-12-10




#### 7. Band Edge

#### 7.1 Test Method and test Procedure:

- (1) The EUT was tested according to ANSI C63.10–2013. The radiated test was performed at Timeway EMC Laboratory. This site is on file with the FCC laboratory division, Registration No. 744189
- (2) Set Spectrum as RBW=1MHz, VBW=3MHz and Peak detector used for PK value. RBW=1MHz, VBW=10Hz and Peak detector used for AV value.
- (3) The antenna high is varied from 1 m to 4 m high to find the maximum emission for each frequency.
- (4) The antenna polarization: Vertical polarization and Horizontal polarization.

## 7. 2 Radiated Test Setup



For the actual test configuration, please refer to the related items – Photos of Testing

# 7.3 Configuration of the EUT

Same as section 5.3 of this report

# 7.4 EUT Operating Condition

Same as section 5.4 of this report.

## 7.5 Band Edge Limit

Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in Section 15.209, whichever is the lesser attenuation.

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.


Report No.: TW2411230-02E Page 24 of 34

Date: 2024-12-10



#### 7.6 Test Result

Product:	LIGHT-WEIGHT 3 MODES CONNECTION RGB GAMING MOUSE	Polarity	Horizontal
Mode	Keeping Transmitting	Test Voltage	DC3.7V
Temperature	24 deg. C,	Humidity	56% RH
Test Result:	Pass		




	No.	Frequency	Results	Factor	Limit	Over Limit	Detector	Table	Height	ANT	Verdict
		(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dB)		(o)	(cm)		
	1	2401.742	91.37	-3.57	74.0	17.37	Peak	25.00	100	Horizontal	N/A
:	2	2400.000	67.72	-3.57	74.0	-6.28	Peak	69.00	100	Horizontal	Pass
	2**	2400.000	51.85	-3.57	54.0	-2.15	AV	69.00	100	Horizontal	Pass
;	3	2390.000	38.22	-3.53	74.0	-35.78	Peak	137.50	100	Horizontal	Pass

Report No.: TW2411230-02E Page 25 of 34

Date: 2024-12-10



Product:	LIGHT-WEIGHT 3 MODES CONNECTION RGB GAMING MOUSE	Detector	Vertical		
Mode	Keeping Transmitting	Test Voltage	DC3.7V		
Temperature	24 deg. C,	Humidity	56% RH		
Test Result:	Pass				




No.	Frequency	Results	Factor	Limit	Over Limit	Detector	Table	Height	ANT	Verdict
	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dB)		(o)	(cm)		
1	2401.992	82.42	-3.57	74.0	8.42	Peak	311.00	100	Vertical	N/A
2	2400.000	59.58	-3.57	74.0	-14.42	Peak	317.00	100	Vertical	Pass
2**	2400.000	45.19	-3.57	54.0	-8.81	AV	317.00	100	Vertical	Pass
3	2390.000	40.55	-3.53	74.0	-33.45	Peak	320.00	100	Vertical	Pass

Report No.: TW2411230-02E Page 26 of 34

Date: 2024-12-10



Product:	LIGHT-WEIGHT 3 MODES CONNECTION RGB GAMING MOUSE	Polarity	Horizontal
Mode	Keeping Transmitting	Test Voltage	DC3.7V
Temperature	24 deg. C,	Humidity	56% RH
Test Result:	Pass		



No.	Frequency	Results	Factor	Limit	Over Limit	Detector	Table	Height	ANT	Verdict
	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dB)		(o)	(cm)		
1	2479.695	90.71	-3.57	74.0	16.71	Peak	300.00	100	Horizontal	N/A
2	2483.500	53.16	-3.57	74.0	-20.84	Peak	313.71	100	Horizontal	Pass
2**	2483.500	38.29	-3.57	54.0	-15.71	AV	313.71	100	Horizontal	Pass

Page 27 of 34

Report No.: TW2411230-02E

Date: 2024-12-10



Product:		MOUSE		B GAMING	Det	Detector		Vertical		
				Test '	Test Voltage	DC3.7V				
Т	Cemperature		24 deg. (	Ξ,	Humidity 56% RI		RH	H		
7	Гest Result:									
	rt 15C Class B 1GHz-18GHz -: E+2 - 90 - 80 -	2	M1							
level (dBuV/m)	60 - 50 - 40 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 -	ex a vick a deministrative and and an absolute	<i>f</i>	And the second s	aukult, phafaidhte de ag gadain de	ii buddayl lal idd is Ababi	i hombadah di hidud	hdd odd adding dding a	alpha daul dh'airine, is bh' ann	wally
	30- 20-	an London de maria de la proposició de la compansió de la compansió de la compansió de la compansió de la comp	<i></i>	2483.5	ency (MHz)	ii kundan alka li dhi i Abahi	d hopping habit hide	hald a backeter (delicense	digit david til skolo skilosov	2500
	30- 20- 10- 2470	Results	Factor	2483.5 Freque		Detector	Table	Height	ANT	
	30 - 20 - 10 - 2470		Factor (dB)	2483.5 Frequen	ency (MHz)					2500
	30- 20- 10- 2470	Results		2483.5 Frequent Limit (dBuV/m)	ency (MHz)  Over Limit		Table	Height		2500

Note: 1. The PK emission level less than the AV limit. No necessary to record the AV emission level.

Date: 2024-12-10



Page 28 of 34

## 8.0 Antenna Requirement

# **Applicable Standard**

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

This product has a PCB antenna with gain -2.89dBi maximum. It fulfills the requirement of this section.

Test Result: Pass


Page 29 of 34

Report No.: TW2411230-02E

Date: 2024-12-10



9.0 20dB Bandwidth Measurement					
Product:	LIGHT-WEIGHT 3 MODES CONNECTION RGB GAMING MOUSE	Test Mode:	Keep transmitting		
Mode	Keeping Transmitting	Test Voltage	DC3.7V		
Temperature	24 deg. C,	Humidity	56% RH		
Test Result:	Pass	Detector	PK		
20dB Bandwidth	2.160MHz				



Date: 27.NOV.2024 13:11:17


Page 30 of 34

Report No.: TW2411230-02E

Date: 2024-12-10



Product:	LIGHT-WEIGHT 3 MODES CONNECTION RGB GAMING MOUSE	Test Mode:	Keep transmitting
Mode	Keeping Transmitting	Test Voltage	DC3.7V
Temperature	24 deg. C,	Humidity	56% RH
Test Result:	Pass	Detector	PK
20dB Bandwidth	2.180MHz		



Date: 27.NOV.2024 13:25:30


Page 31 of 34

Report No.: TW2411230-02E

Date: 2024-12-10



Product:	LIGHT-WEIGHT 3 MODES CONNECTION RGB GAMING MOUSE	Test Mode:	Keep transmitting
Mode	Keeping Transmitting	Test Voltage	DC3.7V
Temperature	24 deg. C,	Humidity	56% RH
Test Result:	Pass	Detector	PK
20dB Bandwidth	2.160MHz		



Date: 27.NOV.2024 13:29:12

Report No.: TW2411230-02E Page 32 of 34

Date: 2024-12-10



#### 10.0 FCC ID Label

#### FCC ID: TUVDS-4028B

The label must not be a stick-on paper label. The label on these products must be permanently affixed to the product and readily visible at the time of purchase and must last the expected lifetime of the equipment not be readily detachable.

#### **Mark Location:**



Page 33 of 34 Report No.: TW2411230-02E

Date: 2024-12-10



#### 11.0 Photo of testing

#### 11.1 Conducted test View--



Date: 2024-12-10



#### Radiated emission test view





Photographs - EUT

Please refer test report TW2411230-01E

# -- End of the report--

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.